

Deployer: Application Software Deployer by Film IS

Deployer is a 32bit Windows application. It is used to copy files and directories from a source server to a destination server.



[Introduction](#)

[Deployer Features](#)

[How to use](#)

[Main Window](#)

[Source Window](#)

[Destination Window](#)

[Add Many Window](#)

[Log Window](#)

[Deployer Options](#)

1CONTENTS

2Contents

3Contents

#4\$5K6

{bmc deploy.bmp}

Deployer: Application Software Deployer Film IS

Deployer is a 32bit Windows appliation. It is used to copy files and directoriesfrom a source server to a destination server.

{bmc Mainm.bmp}

4INTRODUCTION

5Introduction

6Introduction

#7Deployer is a 32bit Windows appliation. It is used to copy files and directoriesfrom a source server to a destination server.

#8\$9K10**Deployer Features**

FEATURES:

- 0._ Multiple deployments. This is done in a batch mode, one deployment after another, in series.
- 0._ Test mode. Allows you to find any potential problems before an actual deployment.
- 0._ Pause and Un-Pause commands. Allow you to interrupt a deployment in progress to perform other tasks in the workstation. This may be necessary because a deployment in progress takes up many system resources.
- 0._ Simultaneous multiprocess. Allows software deployment to several locations at the same time. You can limit the number of simultaneous processes running.
- 0._ Partial deployments. You can deploy an application in as many steps as necessary.
- 0._ Deployer creates destination paths. If you deploy to a destination and it does not have the path the deployer will attempt to create the path (given that you have appropriate rights to the server).
- 0._ File log of messages and errors. Messages and errors are logged in a file and in the database.
- 0._ Log history. Deployer messages and error from previous deployments are stored in a separate log file. This allows optimum efficiency in database operations as history log can be quite large.
- 0._ Database storage of records and logs.
- 0._ Debug mode. Will display message boxes for just about all program operations.
- 0._ Show processes as windows. This allows you to see what the running processes are doing. It is recommended that this feature be disabled so the processes will use less memory for maximum efficiency.
- 0._ Time zone aware. Time zone information along with servers shut down and boot up times allow the Deployer to postpone a deployment to a destination if either the source or destination servers are down.
- 0._ Own INI file. Most program settings are stored in Deployer.ini
- 0._ Database backup and compaction. If Deployer becomes rather slow in database operations. It is recommended to perform a compact database operation.
- 0._ New record defaults. Defaults for Source and Destination records. This is useful when adding new records, so you type less. The defaults can be changed in Deployer.ini
- 0._ Standard controls and visual aids. Tool bar, status bar, menu bar, source and destinations grids, some commands are available with a right mouse click, current database field automatic highlight and color indicators.

LIMITATIONS:

- 0._ Works only with Micorsoft and Novell networks.
- 0._ It may not always disconnect all servers when deployment is done.
- 0._ The OCX control Session from Novell upon failiure to connect displays a dialog box. Causing the deployment to stop. This is a problem when doing unattended deployments. To minimize risk of encountering this problem use the test feature.
- 0._

8DEPLOYER_FEATURES

9Topics

10Topics: Features

#¹¹\$¹²K¹³How to use

To deploy an application follow these steps:

- 1) Add a source record.
 - 2) Add destination records.
 - 3) Test deployment. If there were any errors you will be prompted with a message.
 - 4) Start deployment. If there were any errors you will be prompted with a message.
- For first time users:

11IDH_DEPLOYER_USE

12Topics

13Topics: How to; Use; Deployer

#¹⁴\$¹⁵K¹⁶**Main Window**

[Text to be included at a later time]
{bmc Mainm.bmp}

14IDH_MAIN_WINDOW

15Topics

16Topics: Main

#¹⁷\$¹⁸K¹⁹**Source Window**

[Text to be included at a later time]
{bmc Sourcem.bmp}

17IDH_SOURCE_WINDOW

18Topics

19Topics: Source

#²⁰\$²¹K²²**Destination Window**

[Text to be included at a later time]
{bmc Destinationsm.bmp}

20IDH_DESTINATION_WINDOW

21Topics

22Topics: Destination

#²³\$²⁴K²⁵**Add Many Window**

[Text to be included at a later time]
{bmc AddManyWindowm.bmp}

23IDH_ADD_MANY_WINDOW

24Topics

25Topics: Add Many

#²⁶\$²⁷K²⁸**Log Window**

[Text to be included at a later time]
{bmc Logm.bmp}

26IDH_LOG_WINDOW

27Topics

28Topics: Log

#²⁹\$³⁰K³¹**Deployer Options**

[Text to be included at a later time]
{bmc Options1m.bmp}
{bmc Options2m.bmp}

#32\$K34

{bmc GotoFirst.bmp}

Goto first record

Goto first record

32IDH_CMD_GOTO_FIRST

33Goto First Record

34Goto First Record

#35\$K37

{bmc GotoPrevious.bmp} **Goto previous record**

Goto previous record

35IDH_CMD_GOTO_PREVIOUS

36Goto Previous Record

37Goto Prevuos Record

#³⁸~~\$~~³⁹⁴⁰K

{bmc GotoNext.bmp}

Goto next record

Goto next record

38IDH_CMD_GOTO_NEXT

39Goto Next Record

40Goto Next Record

#⁴¹\$⁴²K⁴³

{bmc GotoLast.bmp}

Goto last record

Goto last record

41IDH_CMD_GOTO_LAST

42Goto Last Record

43Goto Last Record

#⁴⁴\$⁴⁵K⁴⁶

{bmc Save.bmp} **Save record**

Saves the current record. Records are automatically saved when changing current record, exiting form or sometimes when changing a field. So it is not necessary to use save.

44IDH_CMD_SAVE

45Save

46Save

#⁴⁷\$⁴⁸K⁴⁹

{bmc Add.bmp} **Add record**

Adds a new record using defaults.

47IDH_CMD_ADD

48Add

49Add

#50\$51K52

{bmc AddMany.bmp}

Add many records at a time

This command shows the Add Many form. This form is used to add destinations from other source records. For example you can add destinations from another source and then modify some of the destination fields.

50IDH_CMD_ADD_MANY

51Add many

52Add many

#53\$5455

{bmc Clone.bmp} **Clone record**

Prompts you to clone the current record.

Copies the current record to a buffer, adds a new record and pastes the buffer into the new record. You can then make the necessary modifications to the record.

If you are cloning a source record all its destinations can be automatically cloned as well.

53IDH_CMD_CLONE

54Clone

55Clone

#⁵⁶\$⁵⁷K⁵⁸

{bmc Delete.bmp} **Delete record**

Prompts you to delete the current record.

If you are deleting a source record all its destinations are deleted automatically.

56IDH_CMD_DELETE

57Delete

58Delete

#⁵⁹\$⁶⁰K⁶¹

{bmc Open.bmp} **Open current record**

Opens the current record.

When a record is open you can change its fields.

59IDH_CMD_OPEN

60Open

61Open

#⁶²\$⁶³K⁶⁴

{bmc Find.bmp} **Find record**

Searches for a record.

It prompts you for input. You can enter the first few letters to search and it will attempt to find the first match.

62IDH_CMD_FIND

63Find

64Find

#65\$66K67

{bmc ViewLog.bmp}

View log form

Open the log form and displays the log for the current source or destination.

65IDH_CMD_VIEW_LOG

66View Log

67View Log

#⁶⁸\$⁶⁹K⁷⁰

{bmc Start.bmp} **Start deployment**

Runs the current deployment. NOTE: You can run multiple deployments by selecting more than one source records. To select a source record hold the 'Ctrl' key then click on the left gray area of the source grid, to select more keep the 'Ctrl' key down and select more records, then Start the deployment

68IDH_CMD_START

69Start

70Start

#⁷¹\$⁷²K⁷³

{bmc Test.bmp} **Test deployment**

Tests the current deployment. NOTE: You can test multiple deployments by selecting more than one source records. To select a source record hold the 'Ctrl' key then click on the left gray area of the source grid, to select more keep the 'Ctrl' key down and select more records, then Test the deployment

71IDH_CMD_TEST

72Test

73Test

#⁷⁴\$⁷⁵K⁷⁶

{bmc Pause.bmp} **Pause/Un-Pause**

Pauses/Un-Pauses the current deployment. This is usefull when you need to interrupt a deployment temporarily. Otherwise you can Stop the deployment and continue at a later time.

74IDH_CMD_PAUSE

75Pause/Un-Pause

76Pause/Un-Pause

#⁷⁷\$⁷⁸K⁷⁹

{bmc Options.bmp}

Change program options

Shows the options dialog box.

77IDH_CMD_OPTIONS

78Options

79Options

#80\$81K82

Backup database

Backup database makes a copy of the selected database (main/log)

It will show you a dialog box, then you can enter a file name with optional path and will make a compacted copy of the database in MS Access format.

80IDH_CMD_BACKUP

81Backup

82Backup

#83\$84K85

Compact database

Compacts main and log databases

In time the databases become large due to use. Compacting the databases ensures that they are in top shape.

83IDH_CMD_COMPACT

84Compact

85Compact

#⁸⁶\$⁸⁷K⁸⁸

Update version file

Creates new or updates application version file

When you run a deployment for the first time this file is created automatically for you. When you make changes to the application information the deployer's source form will prompt you if you want to update the version file. It is not necessary for you to run this command or to maintain a version file since the Deployer will take care of it.

86IDH_CMD_UPDATE_VERSION_FILE

87Update Version File

88Update version file

#89\$90K91

{bmc ViewLogFile.bmp}

View log file

Open Notepad and view process log file

This file contains detailed information on how a process performed a deployment.

89IDH_CMD_VIEW_LOG_FILE

90View log file

91View log file

#⁹²\$⁹³K⁹⁴

{bmc SaveLogFile.bmp} **Save log file**

Saves current log view into a file

92IDH_CMD_SAVE_LOG_FILE

93Save Log File

94Save Log File

#⁹⁵\$⁹⁶K⁹⁷

Options: OK Button

Saves current settings and closes the Options dialog box.

95IDH_CMD_OPTIONS_OK

96Options: OK Button

97Options: OK Button

#98\$99K100

Options: Cancel Button

Cancels current changes and closes the Options dialog box.

98IDH_CMD_OPTIONS_CANCEL

99Options: Cancel Button

100Options: Cancel Button

#¹⁰¹\$¹⁰²K¹⁰³

Options: Apply Button

Saves current settings.

101IDH_CMD_OPTIONS_APPLY

102Options: Apply Button

103Options: Apply Button

#¹⁰⁴\$¹⁰⁵K¹⁰⁶

Options: Reset Defaults Button

Resets options to program defaults.

104IDH_CMD_OPTIONS_RESET

105Options: Reset Defaults Button

106Options: Reset Defaults Button

#¹⁰⁷\$¹⁰⁸K¹⁰⁹

Options: Process Max Retry

In case of an error while attempting to run a process, this option determines how many times Deployer will attempt to run a process (Deployment Destination).

107IDH_OPT1_MAX_RETRY

108Options: Process Max Retry

109Options: Process Max Retry

#¹¹⁰\$¹¹¹K¹¹²

Options: Process Time Threshold

This option means that for example it is set to 1, the Deployer will only run a process if it's before 1 hour before the destination server shut down time. This prevents a deployment from being terminated abruptly by a server shutting down.

NOTE: This option should later be included in the destination field.

110IDH_OPT1_TIME_THRESHOLD

111Options: Process Time Threshold

112Options: Process Time Threshold

#¹¹³\$¹¹⁴K¹¹⁵

Options: Process Dispatch Refresh Rate

How many seconds the Deployer will wait before attempting to run another new process.

113IDH_OPT1_REFRESH_RATE

114Options: Process Dispatch Refresh Rate

115Options: Process Dispatch Refresh Rate

#¹¹⁶\$¹¹⁷K¹¹⁸

Options: Maximum Running Processes

How many processes can run simultaneously.

116IDH_OPT1_MAX_PROCESS

117Options: Maximum Running Processes

118Options: Maximum Running Processes

#¹¹⁹\$¹²⁰K¹²¹

Options: Kill Running Processes on Cancel

If this option is checked the Deployer will prompt you if you want to kill all running processes when you cancel a deployment.
If unchecked it will leave all running processes active until they finish.

119IDH_OPT1_KILL_PROCESS

120Options: Kill Running Processes on Cancel

121Options: Kill Running Processes on Cancel

