

Statements and expressions

Victor Eijkhout and Charlie Dey

spring 2017

Basics

Edit, compile, run

Exercise: make a file `zero.cc` with the following lines:

```
#include <iostream>
using namespace std;

int main() {
    return 0;
}
```

and compile it. Intel compiler:

```
icpc -o zeroprogram zero.cc
```

Alternative Gnu:

```
g++ -o zeroprogram zero.cc
```

Run this program: `./zeroprogram`

It doesn't do anything.

Add this line:

```
cout << "Hello world!" << endl;
```

(copying from the pdf file is dangerous! please type it yourself)

Compile and run again.

Statements

Program statements

- ▶ A program contains statements, each terminated by a semicolon.
- ▶ 'Curly braces' can enclose multiple statements.
- ▶ A statement can correspond to some action when the program is executed.
- ▶ Some statements are definitions, of data or of possible actions.
- ▶ Comments are 'Note to self', short:

```
cout << "Hello world" << endl; // say hi!
```

and arbitrary:

```
cout << /* we are now going  
        to say hello  
        */ "Hello!" << /* with newline */ endl;
```

Exercise 1

Take the 'hello world' program you wrote earlier, and duplicate the hello-line. Compile and run.

Does it make a difference whether you have the two hellos on the same line or on different lines?

Experiment with other changes to the layout of your source. Find at least one change that leads to a compiler error.

Fixed elements

You see that certain parts of your program are inviolable:

- ▶ There are *keywords* such as `return` or `cout`; you can not change their definition.
- ▶ Curly braces and parentheses need to be matched.
- ▶ There has to be a `main` keyword.
- ▶ The `iostream` and `namespace` are usually needed.

Exercise 2

Experiment with the `cout` statement. Replace the string by a number or a mathematical expression. Can you guess how to print more than one thing, for instance the string `One third is` and the result of $1/3$, with the same `cout` statement?

Variables

Typical variable lifetime

```
int i,j; // declaration
i = 5; // set a value
i = 6; // set a new value
j = i+1; // use the value of i
i = 7; // change the value of i
      // but this doesn't affect j
```

Variable declarations

Programs usually contain data, which is stored in a *variable*.

A variable has

- ▶ a *datatype*,
- ▶ a name, and
- ▶ a value.

These are defined in a *variable declaration* and/or *variable assignment*.

Variable names

- ▶ A variable name has to start with a letter,
- ▶ can contains letters and digits, but not most special characters (except for the underscore).
- ▶ For letters it matters whether you use upper or lowercase: the language is *case sensitive*.

Declaration

There are a couple of ways to make the connection between a name and a type. Here is a simple *variable declaration*, which establishes the name and the type:

```
int n;  
float x;  
int n1,n2;  
double re_part,im_part;
```

Declarations can go pretty much anywhere in your program, but need to come before use of the variable.

Assignments

Datatypes

Variables come in different types;

- ▶ We call a variable of type `int`, `float`, `double` a *numerical variable*.
- ▶ For characters: `char`. Strings are complicated.
- ▶ You can make your own types. Later.

Assignment

Once you have declared a variable, you need to establish a value. This is done in an *assignment* statement. After the above declarations, the following are legitimate assignments:

```
n = 3;  
x = 1.5;  
n1 = 7; n2 = n1 * 3;
```

You see that you can assign both a simple value or an *expression*; see section ?? for more detail.

Assignments

A variable can be given a value more than once. You the following sequence of statements is a legitimate part of a program:

```
int n;  
n = 3;  
n = 2*n + 5;  
n = 3*n + 7;
```

Special forms

Update:

```
x = x+2; y = y/3;  
// can be written as  
x += 2; y /= 3;
```

Integer add/subtract one:

```
i++; j--; /* same as: */ i=i+1; j=j-1;
```

Pre/post increment:

```
x = a[i++]; /* is */ x = a[i]; i++;  
y = b[++i]; /* is */ i++; y = b[i];
```

Exercise 3

Write a program that has several variables. Assign values either in an initialization or in an assignment. Print out the values.

Initialization

You can also give a variable a value in *variable initialization*. Confusingly, there are several ways of doing that. Here's two:

```
int n = 0;  
double x = 5.3, y = 6.7;  
double pi{3.14};
```

Exercise 4

Print out `true` and `false`. What do you get?

Input/Output

Floating point constants

- ▶ Default: `double`
- ▶ Float: `3.14f` or `3.14F`
- ▶ Long double: `1.41l` or `1.41L`.

This prevents numerical accidents:

```
double x = 3.;
```

converts float to double, maybe introducing random bits.

Truth values

So far you have seen integer and real variables. There are also *boolean values* which represent truth values. There are only two values: `true` and `false`.

```
bool found{false};
```

Terminal output

You have already seen cout:

```
float x = 5;  
cout << "Here is the root: " << sqrt(x) << endl;
```

Exercise 5

Write a program that

- ▶ Displays the message `Type a number,`
- ▶ accepts an integer number from you (use `cin`),
- ▶ and then prints out three times that number plus one.

Turn it in!

- ▶ If you have compiled your program, do:

```
test3np1 yourprogram
```

where 'yourprogram' stands for the name of your program.

- ▶ Is it reporting that your program is correct? If so, do:

```
test3np1 -s yourprogram
```

where the -s flag stands for 'submit'.

Expressions

Terminal input

There is also a *cin*, which serves to take user input and put it in a numerical variable.

```
int i;  
cin >> i;
```

However, this function is somewhat tricky.

<http://www.cplusplus.com/forum/articles/6046/>.

Better terminal input

It is better to use `getline`. This returns a string, rather than a value, so you need to convert it with the following bit of magic:

```
#include <iostream>
#include <sstream>
using namespace std;
/* ... */
std::string saymany;
int howmany;

cout << "How many times? ";
getline( cin,saymany );
stringstream saidmany(saymany);
saidmany >> howmany;
```

You can not use `cin` and `getline` in the same program.

Arithmetic expressions

- ▶ Expression looks pretty much like in math.
With integers: $2+3$
with reals: $3.2/7$
- ▶ Use parentheses to group $25.1*(37+42/3.)$
- ▶ Careful with types.
- ▶ There is no 'power' operator: library functions. Needs a line
`#include <cmath>`
- ▶ Modulus: `%`

Exercise 6

- ▶ What happens when you assign a positive floating point value to an integer variable?
- ▶ What happens when you assign a negative floating point value to an integer variable?
- ▶ What happens when you assign a float to a double? Try various number for the original float. Can you explain the result? (Hint: think about the conversion between binary and decimal.)

Exercise 7

Write two programs, one that reads a temperature in Centigrade and converts to Fahrenheit, and one that does the opposite conversion.

$$C = (F - 32) \cdot 5/9, \quad F = 9/5 C + 32$$

Can you use Unix pipes to make one accept the output of the other?