

Fortran classes and objects

Victor Eijkhout and Carrie Arnold and Charlie Dey

Fall 2017

Classes and objects

Fortran classes are based on type objects, a little like the analogy between C++ struct and class constructs.

New syntax for specifying methods.

Object is type with methods

You define a type as before, with its data members, but now the type has a contains.

```
Type,public :: Point
    real(8) :: x,y
contains
    procedure, public :: setzero
    procedure, public :: set
    procedure, public :: length
    procedure, public :: distance
End type Point
```

Methods have object as argument

You define functions that accept the type as first argument, but instead of declaring the argument as `type`, you define it as `class`.

The members of the class object have to be accessed through the `%` operator.

```
subroutine set(p,xu,yu)
  implicit none
  class(point) :: p
  real(8),intent(in) :: xu,yu
  p%x = xu; p%y = yu
end subroutine set
```

Objects definition, method invocation

Class objects are defined as type objects, just as if there were no class functions on them. The class functions are accessed as

```
object%function(arg1,arg2)
```

where the arguments do not include the class argument.

```
use PointClass  
implicit none  
type(Point) :: p1,p2  
  
call p1%set(1.d0,1.d0)  
call p2%set(4.d0,5.d0)
```

Use modules!

It is of course best to put the type definition and method definitions in a module, so that you can use it.

Mark methods as private so that they can only be used as part of the type:

```
Module PointClass
  private
contains
  subroutine setzero(p)
    implicit none
    class(point) :: p
    p%x = 0.d0 ; p%y = 0.d0
  end subroutine setzero
End Module PointClass
```

Point program

```
Module PointClass                                end subroutine set
  Type,public :: Point
    real(8) :: x,y                                End Module PointClass
  contains
    procedure, public :: set      Program PointTest
    procedure, public :: distance use PointClass
  End type Point                implicit none
                                type(Point) :: p1,p2

private
contains

                                call p1%set(1.d0,1.d0)
                                call p2%set(4.d0,5.d0)

    subroutine set(p,xu,yu)
      implicit none
      class(point) :: p
      real(8),intent(in) :: xu,yu  End Program PointTest
      p%x = xu; p%y = yu
    end subroutine set
```

Exercise 1

Take the point example program and add a distance function.