

2D Retinal Vessel Segmentation using Convolutional Neural Networks


Kevin Huynh (704283105) and Zicheng Liu (004460333)
Department of Computer Science
University of California, Los Angeles

Background

- In the medical domain, 2D retinal vessel imaging using fundus cameras is an integral tool in diagnosing various diseases.
- To extract more relevant medical information from these types of images, it is necessary to segment them, separating the retina blood vessels from the non-vessel tissue surrounding them.
- The highest-performing models of late are based upon the max-pooling convolutional neural network (CNN) [1].
- A max-pooling convolutional neural network is a CNN that alternates between convolutional filtering layers and max-pooling layers before finally outputting to a fully connected layer that predicts the most probable class of the pixel [3]. Because the filters extract local features from the images, CNNs do particularly well for retinal vessel image segmentation [1].


Methods

- We built a machine learning model, specifically a max-pooling convolutional neural network [3], to automatically segment 2D retinal blood vessel images.
- We trained and tested our model on the publicly available dataset DRIVE: Digital Retinal Images for Vessel Extraction [4]. This dataset consists of 20 training and testing retinal images along with manual blood vessel segmentations completed by a human expert.
- Before training the model, we divided our images into 120,000 patches and normalized the images by subtracting the mean intensity of the pixels.
- We trained 13 models of differing number of hidden units and dropout probabilities, and then ran cross-validation, choosing the version with the highest mean accuracy on the testing images as our model.



Results

- We segmented the images by classifying each pixel as a part of a retina blood vessel or not. We then used metrics including the receiver operating characteristic (ROC) curve, the precision-recall curve, maximum average accuracy score, and Cohen Kappa score to measure the performance of our model.



COMPARISONS TO OTHER STATE-OF-THE-ART MODELS [2]

Model	Max. Avg. Accuracy	Kappa Score
Our Proposed CNN	0.9430	0.6795
Maji et al.	0.9470	0.7031
Sheet et al.	0.9766	0.6287
Second Manual Annotator	0.9473	0.8213
Staal et al.	0.9422	-
Niemeijer et al.	0.9416	0.7145
Zana et al.	0.9377	0.6971
Jiang et al.	0.9212	0.6399
Martinez-Perez et al.	0.9181	0.6389
Chaudhuri et al.	0.8773	0.3357

Conclusion

- Our CNN does not beat the state-of-the-art; however, it is comparable and performs very well considering its simple architecture.
- Our model can be improved by appending more data to our training set by pre-processing the images more complexly, including rotating and scaling the images before obtaining the image patches.
- We can further tune the hyper-parameters by changing the filter sizes and strides of the convolutional and max-pooling in our model. With an un-optimal filter size, the most discriminative features may not be extractable. Thus, fine-tuning the filter size can improve our model's performance as it plays an important role in local feature extraction.
- Automatic image segmentation tools such as ours can be extremely useful as an assistant for healthcare professionals who must manually segment 2D retina blood vessel images every day.

References

- M. M. Fraz et al., "Blood vessel segmentation methodologies in retinal images - A survey," Computer Methods and Programs in Biomedicine, 2012, vol. 108, no. 1, pp. 407-433.
- D. Maji, A. Santara, P. Mitra, and D. Sheet, "Ensemble of Deep Convolutional Neural Networks for Learning to Detect Retinal Vessels in Fundus Images," arXiv:1603.04833, 2016.
- J. Masci, A. Giusti, D. Ciresan, G. Fricout, and J. Schmidhuber, "A fast learning algorithm for image segmentation with max-pooling convolutional networks," 2013, pp. 2713-2717.
- J.J. Staal, M.D. Abramoff, M. Niemeijer, M.A. Viergever, B. van Ginneken, "Ridge based vessel segmentation in color images of the retina", IEEE Transactions on Medical Imaging, 2004, vol. 23, pp. 501-509.