

# Project 3 – Ashikhmin BRDF

---

*CSE 168: Rendering Algorithms, Spring 2014*


## Description

Add support for multiple derived materials and implement the Lambert and Ashikhmin models. Both materials should implement the appropriate sampling routines to generate random output rays from a given input direction.

Also add support for recursive ray tracing of reflections. Use the BRDF sampling routines to generate reflection rays. You will need to shoot many camera rays per pixel and average the results.

## Sample Image

Project 3 should generate the following image (this used 100 rays per pixel, with up to 10 bounces):



## Project 3 Function

Project 3 should be able to be run with the following sample code (or something very similar):

```
void project3() {
    // Create scene
    Scene scn;
    scn.SetSkyColor(Color(0.8f, 0.9f, 1.0f));

    // Materials
    const int nummtls=4;
    AshikhminMaterial mtl[nummtls];

    // Diffuse
    mtl[0].SetSpecularLevel(0.0f);
    mtl[0].SetDiffuseLevel(1.0f);
    mtl[0].SetDiffuseColor(Color(0.7f,0.7f,0.7f));

    // Roughened copper
    mtl[1].SetDiffuseLevel(0.0f);
    mtl[1].SetSpecularLevel(1.0f);
    mtl[1].SetSpecularColor(Color(0.9f,0.6f,0.5f));
    mtl[1].SetRoughness(100.0f,100.0f);

    // Anisotropic gold
    mtl[2].SetDiffuseLevel(0.0f);
    mtl[2].SetSpecularLevel(1.0f);
    mtl[2].SetSpecularColor(Color(0.95f,0.7f,0.3f));
    mtl[2].SetRoughness(1.0f,1000.0f);

    // Red plastic
    mtl[3].SetDiffuseColor(Color(1.0f,0.1f,0.1f));
    mtl[3].SetDiffuseLevel(0.8f);
    mtl[3].SetSpecularLevel(0.2f);
    mtl[2].SetSpecularColor(Color(1.0f,1.0f,1.0f));
    mtl[3].SetRoughness(1000.0f,1000.0f);

    // Load dragon mesh
    MeshObject dragon;
    dragon.LoadPLY("dragon.ply");

    // Create box tree
    BoxTreeObject tree;
    tree.Construct(dragon);

    // Create dragon instances
    Matrix34 mtx;
    for(int i=0;i<nummtls;i++) {
        InstanceObject *inst=new InstanceObject(tree);
        mtx.d.Set(0.0f,0.0f,-0.1f*float(i));
        inst->SetMatrix(mtx);
        inst->SetMaterial(&mtl[i]);
        scn.AddObject(*inst);
    }

    // Create ground
    LambertMaterial lambert;
    lambert.SetDiffuseColor(Color(0.3f,0.3f,0.35f));
}
```

```

MeshObject ground;
ground.MakeBox(2.0f,0.11f,2.0f,&lambert);
scn.AddObject(ground);

// Create lights
DirectLight sunlgt;
sunlgt.SetBaseColor(Color(1.0f, 1.0f, 0.9f));
sunlgt.SetIntensity(1.0f);
sunlgt.SetDirection(Vector3(2.0f, -3.0f, -2.0f));
scn.AddLight(sunlgt);

// Create camera
Camera cam;
cam.LookAt(Vector3(-0.5f,0.25f,-0.2f),Vector3(0.0f,0.15f,-0.15f));
cam.SetFOV(40.0f);
cam.SetAspect(1.33f);
cam.SetResolution(800,600);
cam.SetSuperSample(10);

// Render image
cam.Render(scn);
cam.SaveBitmap("project3.bmp");
}

```

## Grading

This project is worth 12 points:

- Ashikhman BRDF Evaluation	4
- Ashikhman BRDF Sampling	2
- Lambert BRDF with sampling	2
- Reflections rays	4
- Total	12

## Notes

### *Ashikhmin BRDF*

Details on the Ashikhmin BRDF can be found at:


<http://www.cs.utah.edu/~michael/brdfs/jgtbrdf.pdf>

### *Supersampling*

The `cam.SetSuperSample(10)` is meant to set the camera to do 10x10 supersampling. If you haven't implemented antialiasing, then you can still just use have it generate 100 rays through the center of the pixel and average the colors (before converting to 24-bit integer).

## *Forward BRDF Evaluation*

To get things started, I suggest first implementing the forward evaluation of the BRDF and ignoring the sampling function and recursive ray reflections. If you render the image without any reflections and just computing the direct lighting on the BRDF, it will look like this:



This shows how the BRDF looks when lit from a single directional light only. The rest of the color in the final image comes from reflection rays hitting other surfaces in the environment.

## *Lambert BRDF*

The Lambert material provided in the sample code should be a good start. All that is needed is a `GenerateSample()` function that uses the cosine weighted hemisphere mapping. As it is much simpler than the Ashikhmin BRDF, it might be a good idea to try to get the project running with Lambert first.

## *Tangent Vectors*

You will need to support tangent vectors in the `Intersection` class. I suggest adding a `Vector3 TangentU, TangentV;` to the `Intersection` class. Computing correct tangents requires proper texture coordinates, and the sample models do not have any. Therefore, I suggest adding something like the following in `Triangle::Intersect()` after computing the normal:


```
hit.TangentU.Cross(rtVector3::YAXIS, hit.Normal);  
hit.TangentU.Normalize();  
hit.TangentV.Cross(hit.Normal, hit.TangentU);
```

### *Instanced Materials*

Notice the addition of the `InstanceObject::SetMaterial()` function. This is intended to allow instances to override the material of the object's they instance. To implement this, add a `Material*` to `InstanceObject` that defaults to null. In the `Intersect()` function, after an intersection is detected, it should set the `hit.Mtl` pointer to the instance material if it is non-null. If it is null, it should leave the `hit.Mtl` alone as it will be set to the individual triangle material.

### *Noise*

The rendering will have a lot of noise if you don't take many samples. While testing, you will probably want to use far fewer samples per pixel to keep the render speed fast. This is how the image would look with only 2x2 samples:



### **Extra Credit**

For 1 extra credit point total, you must do *all* of the following:

- Finite camera aperture (depth of field)
- Motion blur (initial and final matrix settable in `InstanceObject`)

And then render an image something like these:

