



St. Helens [SF] Static White

SURFACE




For use with  Light Source.


SPECIFICATIONS

Output Options	100lm/ft	300lm/ft	500lm/ft	750lm/ft	1000lm/ft
Fixture Wattage (White Lens)	1.7W	4.0W	8.5W	11.6W	—
Max Run Length (White Lens)	36ft	20ft	10ft	9ft	—
Fixture Wattage (Black Lens)	2.5W	8.5W	14.4W	—	—
Max Run Length (Black Lens)	29ft	12ft	7ft	—	—
Fixture Wattage (Other Lenses)	0.8W	2.5W	4.0W	6.4W	8.5W
Max Run Length (Other Lenses)	46ft	29ft	20ft	15ft	10ft
Light Color (CCT)	2700K	3000K	3500K	4000K	
Color Rendering	95+ CRI / 2-Step				
Lenses	White, Frosted, Clear, Black				
Mounting	Clip, Pivot Clip				
Finish	Anodized Silver, White, Black, Custom (Provide RAL #)				
Input Voltage	24VDC (Power Supply: 120VAC - 277VAC)				
Dimming	TRIAC, ELV, 0-10V, DMX, DALI, Bluetooth				
Dimensions	0.67" (17.1mm) × 0.33" (8.4mm)				
Production Interval	1.31" (33.3mm)				
Operating Temperature	-4°F (-20°C) to 113°F (45°C)				

FIXTURE DIMENSIONS



Side View



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____




St. Helens [SF] Static White

SURFACE




ACCESSORIES DIMENSIONS

Mounting Clip




Pivot Clip



ST. HELENS [SF] STATIC WHITE COMPONENTS

St. Helens [SF] - Profile



Static White LED Tape - High Density



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



St. Helens [SF] Static White

SURFACE



PART NUMBER EXAMPLE

ILL-SH01-SW - I - 27K - 100 - WH - MC - SV - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH	
ILL-SH01-SW							
iLuminate St. Helens [SF] Static White	I — Indoor	27K — 2700K	100 — 100lm/ft	WH — White Lens	MC — Mounting Clip	SV — Silver	
	O — Outdoor	30K — 3000K	300 — 300lm/ft	FR — Frosted Lens	PV — Pivot Clip	WH — White	
		35K — 3500K	500 — 500lm/ft	CL — Clear Lens		BK — Black	
		40K — 4000K	750 — 750lm/ft	BK — Black Lens		CU — Custom	
			1000 — 1000lm/ft				
LENGTH (IN)		START FEED DIRECTION		LENGTH	END FEED DIRECTION		LENGTH
Fixtures will be built as close to the requested length without going over based on 1.31" (33.3mm) production interval.				E — End	Blank — Endcap	E — End	Blank — Endcap
Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.				B — Back	2 — 2ft	B — Back	2 — 2ft
					5 — 5ft	C — Endcap	5 — 5ft
					10 — 10ft		10 — 10ft
					15 — 15ft		15 — 15ft
					20 — 20ft		20 — 20ft
				25 — 25ft		25 — 25ft	

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS -	-	- 24V -	-	-
iLuminate AC to DC Constant Voltage Power Supply	UNIV - Universal 5-in-1	24V - 24VDC	30W - 30W	JBOX - Dry/Damp Rated
	DMX - DMX512 Enabled		60W - 60W	IP66 - Wet Rated
	DALI - DALI-2 Enabled		100W - 100W	
	BLE - Bluetooth Enabled		200W - 100W x 2	
			300W - 100W x 3	

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____