DNS-Architektur – tsbe.int – Lösungsvorschlag

/etc/bind/named.conf.options

```
options {
    directory "/var/cache/bind";
    forwarders {8.8.8.8; 10.9.4.12;};
    allow-query {127.0.0.0/16; 192.168.0.0/16;};
    dnssec-validation no;
    dnssec-enable no;
    auth-nxdomain no;
};
```

/etc/bind/named.conf.local

```
zone "tsbe.int" in {
   type master;
   file "/etc/bind/db.tsbe.int";
};

zone "220.168.192.in-addr.arpa" in {
   type master;
   file "/etc/bind/db.192.168.220";
};
```

/etc/bind/db.tsbe.int

```
604800
                SOA
                        ns.tsbe.int. root.tsbe.int. (
@
                     2017090902
                                     ; Serial
                        604800
                                       ; Refresh
                         86400
                                       ; Retry
                        2419200
                                       ; Expire
                         604800 )
                                       ; Negative Cache TTL
                                     ns.tsbe.int.
@
          IN
                       NS
@
          IN
                       Α
                                     10.10.10.5
ns
          IN
                       A
                                     192.168.220.12
sap
          IN
                       Α
                                     192.168.220.15
                                     192.168.220.16
fibu
          ΙN
                       Α
          IN
                       Α
                                     192.168.220.12
www
```

TSBE Bern

/etc/bind/db.192.168.220

```
604800
        IN
                 SOA
@
                          ns.tsbe.int. root.tsbe.int. (
                      2013102402 ; Serial
                                       ; Refresh
; Retry
; Expire
; Negative Cache TTL
                          604800
                           86400
                         2419200
                          604800 )
@
          IN
                         NS
                                      ns.tsbe.int.
12
                                      ns.tsbe.int.
           ΙN
                         PTR
15
           IN
                         PTR
                                      sap.tsbe.int.
16
           ΙN
                         PTR
                                       fibu.tsbe.int.
```

/etc/network/interfaces

```
auto lo
iface lo inet loopback

auto eth0
iface eth0 inet static
   address 192.168.220.12
   network 192.168.220.0
   netmask 255.255.255.0
   broadcast 192.168.220.255
   gateway 192.168.220.1

#
   dns-nameservers 192.168.220.12
   dns-search tsbe.int
```

ifdown eth0 ifup eth0

/etc/init.d/bind9 restart tail /var/log/syslog

```
nslookup <u>ns.tsbe.int</u> -> DNS, -> WP PING DNS-IP nslookup 192.168.220.15 nslookup www.google.ch
```

DNS-Einstellungen vmWP2

