| SERIES | LUMENS | DRIVER | VOLTAGE | CCT | EMERGENCY | TRIM TYPE | REFLECTOR/FLANGED COLORS |
|---------|------------|--------------------------|--------------|--------------------|---|---------------------------------|--------------------------------------|
| HH5-LED | □ 900L | ☐ DIM10 | □ 120 | □ 22K | ☐ EMG-LED-10W | ☐ HH5-5501 | □ CL-WH |
| | □ 1200L | ☐ DIMTR ¹ | □ 277 | □ 27K | ☐ EMG-LED-20W | Flanged Downlight | □ CL-SCH |
| | □ 1500L | □ LUTH ² | ■ MVOLT | □ 30K | Typical lumen output of the luminaire is up to 1000L | ☐ HH5-5507 Flanged Wall Wash | □ SHZ-WH |
| | □ 2000L | □ LUT2W ¹ | □ 347 | □ 35K | with EMG-LED-10W option & 2000L with EMG-LED-20W option in emergency mode. | HH5-5577 | □ SHZ-SHZ |
| | □ 3000L* 4 | ☐ LUTFTB ⁵ | (DIM10 only) | □ 40K | Contact the factory for details. | Flanged Double Wall Wash | □ WT-WH |
| | | ☐ ELD0101 ² | | □ 50K ² | Remote mounted installation | | □ WH-WH |
| | | ☐ ELDODALI1 ² | | | | | ☐ MB-WH* |
| | | ☐ ELDODMX1 ² | | | | | □ CL-BK |
| | | □ BLE | OPTICS | CRI | | | ☐ MB-BK* |
| | | | □ VWD 70° | □ 90+ | | | |
| | | | □ WD 60° | □ 98+ ³ | | TRIMLESS | |
| | | | ☐ MWD 52° | | | ☐ HH5-TL-5501 | |
| | | | □ MD 36° | | | Trimless Downlight | * Black color trim is not ENERGYSTAR |
| | | | □ ND 30° | | | ☐ HH5-TL-5507 | certified |
| | | | ☐ SPD 24° | | | Trimless Wall Wash | |
| | | | ☐ NSPD 15° | | | | |
| | | | | | | | |
| | | | | | | | |