

Kevin Wang

---

# Structure of SC\_CPC\_workshop

---

**“Open-source” does not mean putting  
codes that only you can run on GitHub.**

**Kevin Wang\***

\*That's me!

---


[https://github.com/SydneyBioX/SC\\_CPC\\_workshop](https://github.com/SydneyBioX/SC_CPC_workshop)


- ▶ All teaching materials are identical to <https://github.com/SydneyBioX/SingleCellPlus>, except:
  - ▶ `Dockerfile` and other set-up scripts
  - ▶ `deployment` folder with all the passwords
  - ▶ `.gitignore` (to prevent public access to sensitive information)

---

# Google Cloud is a collection of services

- ▶ Our GC account currently hosts
  - ▶ data.zip (Storage Bucket)
  - ▶ Docker images (Container Registry)
  - ▶ Virtual machines (VM instances)





---

## Advantage of this structure

- ▶ Community: Multiple developers can commit to GitHub and trigger a GC build
- ▶ Task clarity: Developers only need to push\*, admin only need to deploy
- ▶ Rigorous: Everything that is available in a Docker image **must** be functional
- ▶ Accountable: Admin is solely responsible for deployment and budgeting
- ▶ Trackable: Every version is linked to a GitHub commit
- ▶ Reliable: Admin always have access to a working copy of Docker + website

\*Developers also need to build the website

**Specific files and  
functionalities**



---

## Building Docker image

- ▶ `Dockerfile` list out build commands:
  - ▶ docker pull from Bioconductor Docker image
  - ▶ Add and run build scripts into Docker (install.R and docker\_setup.sh)
  - ▶ Add `docker\_test.R`, `user\_setup.R` and `omg.R`

---

## `install.R`, `docker\_setup.sh` and `docker\_test.R`

- ▶ `install.R` controls how all R packages should be installed
- ▶ `docker\_setup.sh` does two things:
  - ▶ git pull from SydneyBioX/SC\_CPC\_workshop
  - ▶ download data.zip from [https://storage.googleapis.com/scp\\_data/data.zip](https://storage.googleapis.com/scp_data/data.zip)
- ▶ `docker\_test.R` renders the main RMarkdown files to check if they can be successfully compiled

---

## `user\_setup.R` and `omg.R`

- ▶ When the workshop begins, attendees should type ``source("/home/user_setup.R")`` into the R console.
- ▶ This copies all the files needed to run that workshop.
- ▶ Anything goes wrong during the workshop
  - ▶ Minor: ask attendees to fix it themselves
  - ▶ Major: type ``source("/home/omg.R")`` into the console (this is the last resort)

---

## Initiating the workshop

- ▶ ``deployment/password.Rmd`` uses
  - ▶ number of users
  - ▶ number of virtual machines needed

to generate passwords and store those as ``deployment/users.csv``. Print and distribute to attendees.

- ▶ ``deployment/GCE.R`` **must** be ran by a person authorised to ``scpworkshop`` GC account. Basic configurations (CPU, RAM or HD) are needed.