CSCA48 Exercise 1

Due: January 26 2018. 5:00pm

Let's play a game... the **banana game!** This one doesn't involve any coding at all, we're just working out manually. It should give you some practice with the general ideas of stacks and queues.

The BANANA game

The object of the game is to transform a word (source word) into another word (goal word) using only the container provided (the container must be left empty at the end of the game). This means that we can't add or delete any letters, but we can re-arrange them by putting them into a container and taking them out again. At each stage, we have three options:

- Add the next letter of source word onto the end of goal word (we'll call this move)
- Put the next letter from source word into the container (we'll call this put)
- Remove a letter from the container and add it to the end of goal word (we'll call this get)

For example, if we wanted to change the word CAT into the word ACT, we could do so with a simple container that only holds one letter (we'll call this container a Bucket):

- put(C)
- move(A)
- get() -> returns C
- move(T)

Try it out and make sure you understand how that works before you continue.

Using a Queue

With our simple container, we can't do too much. For example, there's no way we could change NICK into CNKI. (Try it... doesn't work). But could we do it if we had a Queue as our container? Let's see:

Operation	source word	goal word	Container
	NICK		
put(N)	ICK		N
put(I)	CK		NI
move(C)	K	С	NI
get()	K	CN	I
move(K)		CNK	I
get()		CNKI	

Try changing BANANA into AAABNN. Make sure you can do it before moving on.

Stacks

What if we want to change BANANA into AAANNB? Well now we have a problem. We've put the B into our container (a Queue), which means if we want to put anything else in (the Ns), we'll need to dequeue our B before we can get to the Ns. So we're stuck (convince yourself of this before moving on).

Maybe Stack ADT will help us:

In lecture, we defined a Queue and a Stack as: A container of objects accessed in FIFO (First-In First-Out) order and in LIFO (Last-In First-Out) order respectively. Can we solve our problem using a Stack as our container? Let's see:

Operation	source word	goal word	Container
	BANANA		
put(B)	ANANA		В
move(A)	NANA	A	В
put(N)	ANA	A	BN
move(A)	NA	AA	BN
put(N)	A	AA	BNN
move(A)		AAA	BNN
get()		AAAN	BN
get()		AAANN	В
get()		AAANNB	

Your Task

Your task this week is to play the Banana Game (who says CS students can't have any fun?). Try to create the following permutations of BANANA using the containers (bucket, stack and queue):

- 1. AAABBN
- 2. AAANNB
- 3. BNAAAN
- 4. NBNAAA
- 5. NNAAAB
- 6. NNBAAA
- 7. ANANAB
- 8. NABANA
- 9. NANANANABATMAN

What to Hand in

On Markus, you must submit a file called ex1.txt Note the file extension, it's not a Python file. Where, for each of the above cases, you indicate which (if any) of the three containers (Stack, Queue or Bucket) can be used to solve the banana game, and for each container that can be used, the series of operations that will turn BANANA into the given permutation (note that there may be more than one solution). For any example that can't be solved using any of the containers, simply write impossible.

Your file should be formatted as follows: each section will start with the word number on a line by itself. The next line will be just the word impossible if it can't be done with any container, or the list of containers with which it is possible. For every container with which the game can be solved, there will then be a line containing the container name, followed by a move list separated by spaces

A properly formatted, but in no way correct example submission file is below:

```
impossible

bucket stack queue
bucket put(A) move(B) get()
stack put(A) move(B) get()
queue put(A) move(B) get()

queue put(A) move(B) get()

queue
queue put(A) put(B) move(C) get() get()
```