Eduard Cerny Surrendra Dudani John Havlicek Dmitry Korchemny

The Power of Assertions in System Verilog



The Power of Assertions in SystemVerilog

Eduard Cerny • Surrendra Dudani John Havlicek • Dmitry Korchemny

The Power of Assertions in SystemVerilog



Dr. Eduard Cerny edcerny@synopsys.com

Dr. Surrendra Dudani dudani@synopsys.com John Havlicek john.havlicek@freescale.com

Dr. Dmitry Korchemny dmitry.korchemny@intel.com

ISBN 978-1-4419-6599-8 e-ISBN 978-1-4419-6600-1 DOI 10.1007/978-1-4419-6600-1 Springer New York Dordrecht Heidelberg London

Library of Congress Control Number: 2010934904

© Springer Science+Business Media, LLC 2010

All rights reserved. This work may not be translated or copied in whole or in part without the written permission of the publisher (Springer Science+Business Media, LLC, 233 Spring Street, New York, NY 10013, USA), except for brief excerpts in connection with reviews or scholarly analysis. Use in connection with any form of information storage and retrieval, electronic adaptation, computer software, or by similar or dissimilar methodology now known or hereafter developed is forbidden.

The use in this publication of trade names, trademarks, service marks, and similar terms, even if they are not identified as such, is not to be taken as an expression of opinion as to whether or not they are subject to proprietary rights.

Printed on acid-free paper

Springer is part of Springer Science+Business Media (www.springer.com)

Preface

This book is the result of the deep involvement of the authors in the development of EDA tools, SystemVerilog Assertion standardization, and many years of practical experience. One of the goals of this book is to expose the oral knowhow circulated among design and verification engineers which has never been written down in its full extent. The book thus contains many practical examples and exercises illustrating the various concepts and semantics of the assertion language. Much attention is given to discussing efficiency of assertion forms in simulation and formal verification. We did our best to validate all the examples, but there are hundreds of them and not all features could be validated since they have not yet been implemented in EDA tools. Therefore, we will be grateful to readers for pointing to us any needed corrections. The book is written in a way that we believe serves well both the users of SystemVerilog assertions in simulation and also those who practice formal verification (model checking). Compared to previous books covering SystemVerilog assertions we include in detail the most recent features that appeared in the IEEE 1800-2009 SystemVerilog Standard, in particular the new encapsulation construct "checker" and checker libraries, Linear Temporal Logic operators, semantics and usage in formal verification. However, for integral understanding we present the assertion language and its applications in full detail.

The book is divided into three parts.

Part I Opening is an extended introduction to assertions, their use in simulation, formal verification and other tools, and their meaning in relation to the rest of the SystemVerilog language.

Chapter 1 introduces the concept of assertions, their place in history of design verification, and discusses the use of assertions in hardware design and verification flow.

Chapter 2 introduces minimal necessary concepts from the SystemVerilog language other than assertions that are useful for understanding assertions and their usage. It also provides the basics of SystemVerilog simulation semantics.

Part II Assertions goes into details of the assertion language.

Chapter 3 describes the different assertion statements that can be used to ascertain correctness, provide constraints and collect coverage, both in clocked concurrent and unclocked immediate forms.

vi Preface

Chapters 4 and 5 provide the basic information on how to write simple properties and sequences that form the operational core of assertions.

Chapter 6 exposes system functions that help to write assertions without having to resort to additional procedural code, and introduces several system tasks for controlling assertion and action block execution.

Chapter 7 considers reusability of assertion bodies by showing how Boolean expressions, sequences, and properties can be defined and parameterized for later reuse.

Chapters 8 and 9 delve into the full intricacies of property and sequence operators. The former chapter also defines precisely the notions of vacuous and non-vacuous evaluations of assertions.

Chapter 10 provides an introduction to the treatment of assertions in formal verification by discussing the different ways formal verification can proceed and its role in the verification process.

Chapter 11 exposes details of the models and algorithms used in formal verification, in particular, *model checking*.

Chapter 12 describes sampling clocks, clock flow through assertions, and multiclocked assertions.

Chapter 13 provides information on the ways synchronous property evaluation can be terminated with success or failure using asynchronous and synchronous abort operators.

Chapter 14 shows how to use concurrent assertions inside always procedures, and how the leading clock is inferred. It also describes how evaluation attempts are started depending on the conditional and looping statements inside procedures.

Chapter 15 apologizes for local variables, but in fact shows how local variables provide much flexibility to assertions, especially in simulation.

Chapter 16 exposes the various forms of local variable declarations and rules of deployment, including special local variable arguments to properties and sequences.

Chapter 17 shows another facet of SystemVerilog assertions, that of recursive properties. They provide an alternate and succinct form for expressing complex properties.

Chapter 18 discusses coverage collection that is needed to measure the verification progress. Two forms are described, using assertion cover statements alone and in combination with test bench covergroups to form powerful data collection constructs.

Chapter 19 briefly introduces some techniques for debugging assertions, independently of services provided by specific EDA tools, and then discusses the efficiency of various assertion forms in simulation and formal verification.

Chapter 20 gives the theoretical base for full and precise understanding of the meaning of assertions. This chapter is particularly important to anyone who implements some form of an assertion verification engine.

Part III Checkers and Verification Libraries is primarily concerned with developing effective reusable verification objects.

Chapter 21 provides a detailed expose of a new encapsulation construct, the "checker". This construct is the basis for forming what we could call super

Preface vii

assertions, that is assertion entities that combine procedural code, free variables, variable assignments, coverage and assertion statements into one reusable parameterized checker unit.

Chapter 22 shows how checkers can be used effectively in formal verification. The chapter also provides deeper understanding of the behavior of checker variables.

Chapter 23 discusses how to create libraries of verification statements based on assertions, from simple let or property based forms, to the complex ones using checker encapsulation.

Chapter 24 concludes the book by looking forward in that it indicates the possible and potentially necessary future enhancement to the SystemVerilog assertion language, in particular in relation to more effective checker development.

We did our best to verify and compile each and every example and verify the text, however, not all SystemVerilog constructs are supported by commercial tools and the 2009 SystemVerilog LRM still leaves some points incomplete or ambiguous. We do not guarantee correctness and do not assume any liability and responsibility for issues resulting from applying the techniques described in the book.

Acknowledgments

The authors wish to express their gratefulness to many people who reviewed sections of the draft of the book, in particular, to Shalom Bresticker (Intel), Lena Korchemny (Inango), Jacob Katz (Intel), Scott Little (Freescale), Zeljko Zilic (McGill University), Christian Berthet (ST Microelectronics), Chris Spear (Synopsys), and Erik Seligman (Intel). Furthermore, the book was mostly written over the weekends, vacations, and evenings, hence we are thankful to our spouses and families for their patience and understanding.

Marlborough, MA, Marlborough, MA, Austin, TX, Haifa, Israel, January 2010 Eduard Cerny Surrendra Dudani John Havlicek Dmitry Korchemny

Contents

Part I Opening

1	Intro	duction		3
	1.1	The Co	ncept of Assertion	4
	1.2	Assertio	ons in Design Methodology	9
		1.2.1	Using Assertions for High Level Model	
		1.2.2	Using Assertions for RTL Model	13
		1.2.3	Using Assertions Beyond RTL	
	1.3	Assertio	ons in SystemVerilog	
	1.4		ng Assertions	
	1.5		on Reuse	
	1.6	SVA an	nd PSL	26
	Exerc	cises		27
2	Syste	mVerilo:	g Language and Simulation Semantics Overview	29
_	2.1		pes and Variable Declarations	
		2.1.1	Packed and Unpacked Arrays	
		2.1.2		
	2.2	New Ex	xpression Operators	
		2.2.1		
		2.2.2	Implication and Equivalence Operators	
	2.3	Extensi	ons to Event Controls	
	2.4	Clockir	ng Blocks	40
	2.5		ocedures	
	2.6	Interfac	ees	44
	2.7	Progran	ns	47
	2.8		nd \$Root	
	2.9		e	
	2.10	U	atement	
	2.11	Genera	te Constructs	55
	2.12		tion Semantics Overview	
		2.12.1	The Simulation Engine	
		2.12.2	Bringing Order to Events	

x Contents

		2.12.3	Carving Safe Regions	62
		2.12.4	A Time Slot and The Movement of Time	65
Pai	rt II	Assertion	ns	
3	Ass	ertion Sta	tements	71
	3.1	Asserti	on Kinds	71
	3.2		iate Assertions	
		3.2.1	Immediate Assertion Simulation	73
		3.2.2	Simulation Glitches	74
	3.3	Deferre	ed Assertions	75
		3.3.1	Deferred Assertion Simulation	75
		3.3.2	Deferred Assertion Actions	77
		3.3.3	Standalone Deferred Assertions	78
	3.4	Concur	rent Assertions	78
		3.4.1	Simulation Evaluation Attempt	
		3.4.2	Clock	
		3.4.3	Sampled Values for Concurrent Assertion	84
		3.4.4	Reset	85
		3.4.5	Boolean Expressions	
		3.4.6	Event Semantics for Concurrent Assertions	
	3.5	Assum	ptions	90
		3.5.1	Motivation	90
		3.5.2	Assumption Definition	91
		3.5.3	Checking Assumptions	92
	3.6	Restric	tions	94
	3.7	Covera	ge	94
		3.7.1	Motivation	95
		3.7.2	Coverage Definition	95
		3.7.3	Checking Coverage	97
	3.8	Checki	ng Assertions. Summary	97
	Exe	rcises		97
4	Bas	sic Proper	ties	101
	4.1		n Property	
	4.2		ne Property	
	4.3	Always	Property	105
		4.3.1	Implicit Always Operator	
	4.4	S_even	tually Property	
	4.5	Basic E	Boolean Property Connectives	109
	4.6		roperty	
	Exe	rcises		

Contents xi

5	Basic	Sequen	nces	115
	5.1	Boolea	an Sequence	116
	5.2	Sequer	ntial Property	117
	5.3	Sequer	nce Concatenation	
		5.3.1	Multiple Delays	
		5.3.2	Top-Level Sequential Properties	
		5.3.3	Sequence Fusion	
		5.3.4	Initial Delay	
	5.4		Implication	
		5.4.1	Nested Implication	
		5.4.2	Examples	
		5.4.3	Vacuous Execution	
	5.5	Conse	cutive Repetition	
		5.5.1	Zero Repetition	
	5.6		nce Disjunction	
	5.7	Conse	cutive Repetition Revisited	
		5.7.1	Repetition Range	
	5.8	Sequer	nces Admitting Empty Match	
		5.8.1	Antecedents Admitting Empty Match	134
	5.9		nce Concatenation and Delay Revisited	
	5.10		inded Sequences	
	Exerc	cises		139
6			stem Functions and Tasks	
	6.1		ctor Functions	
		6.1.1		
		6.1.2	One-Hot Encoding	
		6.1.3	Number of 1-Bits	
	<i>-</i> - -	6.1.4	Unknown Bits	
	6.2	-	ed Value Functions	
		6.2.1	General Sampled Value Functions	
		6.2.2	Global Clocking Sampled Value Functions	
	6.3		for Controlling Evaluation Attempts	
	6.4		for Controlling Action Blocks	
	Exerc	cises		162
7	Lat	Saguano	ee and Property Declarations; Inference	163
′			eclarations	
	7.1	7.1.1	Syntax of let	
		7.1.1	Uses of let	
	7.2		ace and Property Declarations	
	1.4	7.2.1	Syntax of Sequence–Endsequence	
		7.2.1		
	7.3		Syntax of Property–Endpropertye Expression and Clock Inference	
			e Expression and Clock Interence	
	LAUI	VIOUD		101

xii Contents

8	Adva	anced Properties	
	8.1	Sequential Property	183
	8.2	Boolean Property Operators	185
	8.3	Suffix Operators: Implication and Followed-By	189
	8.4	Unbounded Linear Temporal Operators	191
	8.5	Bounded Linear Temporal Operators	194
	8.6	Vacuous Evaluation	197
	Exerc	cises	201
9	Advanced Sequences		
	9.1	Sequence Operators	203
		9.1.1 Throughout	203
		9.1.2 Goto Repetition	
		9.1.3 Nonconsecutive Repetition	
		9.1.4 Intersection	
		9.1.5 Sequence Conjunction	
		9.1.6 Sequence Containment	
		9.1.7 First Match of a Sequence	
	9.2	Sequence Methods	
		9.2.1 Triggered: Detecting End Point of a Sequen	
		9.2.2 Matched	
	9.3	Sequence as Events	
		9.3.1 Sequence Event Control	
		9.3.2 Level-Sensitive Sequence Control	
		9.3.3 Event Semantics of Sequence Match	
	Exerc	cises	
10	Intro	oduction to Assertion-Based Formal Verification	229
	10.1	Counterexample and Witness	
	10.2	Complete and Incomplete Methods	
	10.3	Approximation	
		10.3.1 Overapproximation	
		10.3.2 Underapproximation	
		10.3.3 Pruning	
	10.4	Formal Verification Flows	
	10	10.4.1 Exhaustive Verification of Model Specification	
		10.4.2 Lightweight Verification	
		10.4.3 Early RTL Verification	
	10.5	Assume-Guarantee Paradigm	
	10.6	Formal Verification Efficiency	
	10.7	Hybrid Verification	
	Ever	•	

Contents xiii

11	Form	al Verifi	cation and Models	243
	11.1	Auxilia	ry Notions	243
		11.1.1	Relations	244
		11.1.2	Logic Notation and Quantifiers	244
		11.1.3	Languages	244
		11.1.4	Finite Automaton	245
	11.2	Formal	Verification Model	246
		11.2.1	Time	247
		11.2.2	Model Language	248
		11.2.3	Symbolic Representation	249
	11.3	Propert	ies	252
		11.3.1	Asserts	252
		11.3.2	Assumes	252
		11.3.3	Coverage	253
		11.3.4	Constraining a Model with Assumptions	254
	11.4	Safety a	and Liveness	254
		11.4.1	Safety Properties	255
		11.4.2	Liveness Properties	
	11.5	Weak a	nd Strong Operators	262
	11.6	Embede	ded Assertions	265
	11.7	Immedi	iate and Deferred Assertions	266
	Exerc	cises		267
12	Clock	KS		269
	12.1	Overvie	ew of Clocks	270
		12.1.1	Specifying Clocks	270
		12.1.2	Multiple Clocks	273
	12.2	Further	Details of Clocks	278
		12.2.1	Preponed Value Sampling	278
		12.2.2	Default Clocking	280
		12.2.3	Restrictions in Multiply-Clocked Sequences	281
		12.2.4	Scoping of Clocks	281
		12.2.5	Finer Points of Multiple Clocks	287
		12.2.6	Declarations Within a Clocking Block	292
	Exerc	cises		293
13	Reset	ts		295
	13.1	Overvie	ew of Resets	295
		13.1.1	Disable Clause	296
		13.1.2	Aborts	299
	13.2	Further	Details of Resets	
		13.2.1		
		13.2.2		
	Exerc	ises	T T	

xiv Contents

14	Proc	edural Concurrent Assertions	307
	14.1	Using Procedural Context	308
	14.2	Clock Inferencing	310
	14.3	Using Automatic Variables	313
	14.4	Assertions in a For-Loop	314
	14.5	Event Semantics of Procedural Concurrent Assertions	315
	14.6	Things to Watch Out	319
	14.7	Dealing with Unwanted Procedural Assertion Evaluations	321
15	An A	Apology for Local Variables	
	15.1	Fixed Latency Data Pipeline	
	15.2	Sequential Protocol	
	15.3	FIFO Protocol	
	15.4	Tag Protocol	
	15.5	FIFO Protocol Revisited	
	15.6	Tag Protocol Revisited	
		15.6.1 Tag Protocol Using a Single Static Bit	
		15.6.2 Tag Protocol Using Only Local Variables	
	Exerc	cises	340
16	Mech	hanics of Local Variables	
	16.1	Declaring Body Local Variables	
	16.2	Declaring Argument Local Variables	
	16.3	Assigning to Local Variables	
		16.3.1 Assignment Within Repetition	
		16.3.2 Sequence Match Items	
	16.4	Referencing Local Variables	
		16.4.1 Local Variable Flow	
		16.4.2 Becoming Unassigned	
		16.4.3 Multiplicity of Matching with Local Variables	
	16.5	Input and Output with Local Variables	
		16.5.1 Input with Local Variables	
		16.5.2 Output with Local Variables	
	Exerc	cises	369
17		ırsive Properties	
	17.1		
		Retry Protocol	
	17.3	Restrictions on Recursive Properties	
		17.3.1 Negation and Strong Operators	
		17.3.2 Disable Clause	
		17.3.3 Time Advance	
		17.3.4 Actual Arguments	
	Exerc	cises	389

Contents xv

18	Cove	rage	393
	18.1	Immediate and Deferred Coverage	
	18.2	Sequence and Property Coverage	
		18.2.1 Sequence Coverage	
		18.2.2 Property Coverage	
		18.2.3 Covergroup	
		18.2.4 Combining Covergroups and Assertions	
	18.3	Coverage on Weak and Strong Properties	
	18.4	Examples	
	Exerc	cises	
19	Debu	gging Assertions and Efficiency Considerations	409
	19.1	Debugging An Assertion Under Development	410
	19.2	Debugging Assertion Failures of a Test	414
	19.3	Efficiency Considerations	414
	Exerc	cises	418
20	Forn	nal Semantics	421
	20.1	Formal Semantics of Properties	421
		20.1.1 Basic Property Forms	422
		20.1.2 Derived Properties	
	20.2	Formal Semantics of Sequences	425
	20.3	Formal Semantics: Sequences and Properties	426
		20.3.1 Strong Sequential Property	427
		20.3.2 Extension of Alphabet	
		20.3.3 Weak Sequential Property	
		20.3.4 Property Negation	
		20.3.5 Suffix Implication	
		20.3.6 Suffix Conjunction: Followed-by	
	20.4	Formal Semantics of Clocks	
	20.5	Formal Semantics of Resets	434
	20.6	Formal Semantics of Local Variables	436
		20.6.1 Formalizing Local Variable Flow	436
		20.6.2 Local Variable Contexts	
		20.6.3 Sequence Semantics with Local Variables	437
		20.6.4 Property Semantics with Local Variables	
	20.7	Formal Semantics of Recursive Properties	
	Exerc	cises	443
Par	t III	Checkers and Assertion Libraries	
21	Chec	kers	447
	21.1	An Apology for Checkers	
	21.1	Checker Declaration.	
	21.2	21.2.1 Checker Formal Arguments	
		21.2.2 Checker Contents	
		21.2.3 Scoping Rules.	

xvi Contents

	21.3	Checker Instantiation	465
		21.3.1 Connecting Checker Argum	nents465
			467
			e472
			476
	21.4	Checker Variables	
	21.5	Covergroups in Checkers	485
	Exerc	ises	486
22	Chec	kers in Formal Verification	489
	22.1	Free Variables	
			s490
			ons491
		*	tements492
			Vith Checkers493
			495
			498
			ıs501
			n502
			Variables506
	22.2	Rigid Variables	
		•	imulation509
	Exerc	rises	
23	Chec	ker Libraries	513
	23.1	Weaknesses of Existing Checker Lib	
	23.2	Kinds of Checkers and Their Charac	
			515
		- ·	516
			516
			516
	23.3	Examples of Typical Checker Kinds	
			cker518
			tional Checker519
			emporal Checker522
			Checker
	23.4	Converting Module-Based Checkers	
	Exerc		529
24	Futu	re Enhancements	531
	24.1	Language Enhancements	
	24.2	Usability Enhancements	
Ref	erence	S	535
1nd	ex		

Acronyms

ABV	Assertion-Based Verification
ALU	Arithmetic Logic Unit
DUT	Device Under Test
FPGA	Field-Programmable Gate Arrays
FSM	Finite State Machine
FV	Formal Verification
HDL	Hardware Description Language
HDVL	Hardware Description and Verification Language
IP	Intellectual Property
LRM	Language Reference Manual
LSB	Least Significant Bit
LTL	Linear Temporal Logic
MSB	Most Significant Bit
NBA	Non-Blocking Assignment <=
OVL	Open Verification Library
OVM	Open Verification Methodology for SystemVerilog
PLI	Programming Language Interface
RTL	Register Transfer Level
SAR	Single Assignment Rule
SBV	Specification-Based Verification
SoC	System on Chip
SV	SystemVerilog
SVA	SystemVerilog Assertions
SVF	Sampled Value Function
SVTB	SystemVerilog Testbench
VMM	Verification Methodology Manual for SystemVerilog
VPI	Verification Programming Interface

Part I Opening

Chapter 1 Introduction

Πασῶν τῶν τεχνῶν ἀρχὴ χαλεπή.

The beginning of all arts is difficult.

In comparison with the total chip development effort, the portion of effort spent in design verification is growing at a faster rate and thus consuming a significantly larger portion of the development cost. Despite more automation of various processes and new techniques, the cost containment for verification continues to be a challenge. There are at least two important cost motivations behind the increased effort. One is the damaging effects of a late discovery of a bug in the design flow on project schedules, which ultimately results in product delays. The other is the enormous manufacturing cost of a chip re-spin due to revelation of a design flaw after the initial prototype of the chip.

Consequently, there is a strong belief that investing more in developing new design verification techniques and, correspondingly, increased effort to uncover design bugs early in the design flow are worthwhile. We now have new techniques, such as constrained random simulation, verification coverage closure, and assertion checking, employed by many major organizations with the aim of speeding up creation of testbenches and uncovering design errors.

SystemVerilog [7] is an extension of Verilog [4],¹ a well-known Hardware Description Language (HDL), to support new verification techniques that have already shown promising results in various organizations. Whereas Verilog was oriented primarily to design and test at the Register Transfer Level (RTL) and gate level, SystemVerilog added means for describing testbenches (SystemVerilog Testbench, SVTB), defining functional coverage, and specifying assertions (SystemVerilog Assertions, SVA).² By virtue of many new enhancements geared toward testing and checking, SystemVerilog surpassed Verilog as an HDL to become an HDVL – Hardware Description and Verification Language.

 $^{^{\}rm l}$ Until 2009 Verilog and SystemVerilog had separate standards. In 2009 both standards were merged into SystemVerilog standard.

² SystemVerilog also introduced many important object-oriented enhancements to Verilog, such as aggregate data types, classes, and interfaces [7].

The assertions technology was developed on the premise that writing specifications formally plays a critical role in detecting design errors. This is because tools can automatically detect errors based on the implemented design and its specification [43]. Keeping this goal in mind, SVA was designed as an integral part of SystemVerilog.

This book is dedicated to SystemVerilog Assertions. It teaches how to write assertions, how to design and use assertion libraries, and it discusses assertion applications and checking. To read and to understand this book, basic knowledge of Verilog is sufficient. A tour of important features from SystemVerilog is presented in Chap. 2. For an introduction to the basic Verilog layer of SystemVerilog, see [55].

In this chapter, we introduce SystemVerilog assertions informally, before their systematic treatment in Part II. For developing intuition on assertions, their meaning is explained by way of simple examples. The reader does not have to understand all the details at this stage, but only to grasp the concepts behind the examples. This chapter also includes an informal introduction of SVA language features that are handled in great detail in the rest of this book.

1.1 The Concept of Assertion

An assertion is a positive statement about a property of a design. It is positive in the sense that, should the statement be found as false, it indicates an error. Designers place assertions to express the intended behavior as specifications that can be interpreted and analyzed by tools. Since the property only states the behavior, it is often used to ensure that the design implementation of the behavior matches the assertion.

The use of assertions in contemporary hardware design methodologies has become widespread and matured over the past few years. In programming languages, assertions have had a longer history of use, primarily because the assertions tend to be simpler, embedded in the code to check Boolean properties. HDLs model behavior over explicit time domains, with properties synchronous to clocks as well as asynchronous with specific time delays. This aspect of HDL modeling pushed forward the development of language techniques for expressing complex temporal behavior in the form of assertions and algorithms to interpret temporal assertions. As a result, several commercial languages have emerged to support the growing needs of designers to perform design verification with the assistance of assertions, sometimes as the central groundwork in monitoring the progress of a design project.

By assertions, we mean statements that express properties to be true in a more general sense, without implying any specific intention or application. Although the most common application is for checking a design in order to detect bugs, other uses include making assumptions about the environment and tracking test scenarios for functional or behavioral coverage. Later in this chapter, we introduce various forms of applications that are provided by SVA.

```
module m(input logic c, clk);
1
    logic a = 1'b0;
2
    logic b = 1'b1;
3
    always @(posedge clk) begin
       a <= c;
5
      b <= !c;
6
    end
    // assertion
    al: assert property (@(posedge clk) a != b)
      else $error("a != b does not hold");
  endmodule : m
```

Fig. 1.1 A simple assertion

SystemVerilog provides assertion features that are declarative. That is, assertions do not describe how to check, but only what to check. Figure 1.1³ shows a simple example of an assertion in SVA.

Consider module m. Its functionality is implemented in lines 2–7 using an always procedure⁴ and nonblocking assignments.

Assertion at checks at each rising edge of clock clk that a != b. If the assertion does not hold, an error message a != b does not hold is issued. This assertion may be checked in simulation or by formal verification tools.

The experience of using assertions has shown important benefits described below.

Implementing Checks in Verilog is Difficult

One could ask how RTL correctness was checked in Verilog before the invention of SystemVerilog. Checks can be obtained by implementing Verilog code that is equivalent to writing assertions.

To appreciate why assertion implementation in RTL code is nontrivial and error prone, consider checking that grant should be asserted four clock cycles after req. For simplicity we ignore here the reset issue (see Exercise 1.2). A natural solution is to activate a counter when req is detected, and when the counter value becomes 4, check for grant, as shown in Fig. 1.2.

What happens if there are two req issued before the first grant is seen, as shown in Fig. 1.3? We would expect our checker to fail because the first request is not granted. But, instead, the checker will pass. When the second req comes, we reset the counter and start counting anew – when we wrote the checker we did not think about overlapping evaluations!

³ This example uses several SystemVerilog features not available in Verilog, e.g., logic data type (see Chap. 2 for more information).

⁴ The reader may be used to the term "always block", but according to the SystemVerilog 2009 standard, this construct is called "always procedure".

```
module reqgranted1(input logic req, grant, clk);
bit [2:0] ctr = '0;
always @(posedge clk) begin
  if (req) ctr <= 1;
  else if (ctr > 0 && ctr < 4) ctr <= ctr + 1;
  else if (ctr == 4) begin
    if (!grant) $display("Request not granted.");
    ctr <= '0;
  end
  end
end</pre>
```

Fig. 1.2 Checking nonoverlapping evaluations




Fig. 1.3 Two requests before grant

```
module reqgranted2(input logic req, grant, clk);
bit [3:0] sreg = '0;
always @(posedge clk) begin
    sreg <= {sreg, req};
    if (sreg[3] && !grant) $display("Request not granted.");
    end
endmodule : reqgranted2</pre>
```

Fig. 1.4 Checking overlapping evaluations

To take overlapping evaluations into account we can use a shift register instead of a counter, as shown in Fig. 1.4. When req is asserted it is fed into the shift register sreg. The Most Significant Bit (MSB) of sreg is set into 1 when there was a req four cycles ago, and therefore grant must be asserted in this case.

The same intent may be expressed with a single assertion:

```
assert property(@(posedge clk) req |-> nexttime[4] grant);
```

Readers who are not yet convinced by this example can carry out Exercise 1.3.

Assertions Formally Express Design Intent

SVA is a *Formal Specification Language*. It is used to describe design properties unambiguously and precisely. Usually properties are written as part of the high level design specifications in a text document. But writing specification in a natural language is ambiguous.

Consider the following typical property specification: *Each request should be granted in four clock cycles*. This specification is ambiguous:

- Do we count four clock cycles starting from the cycle when the request was issued, or from the next cycle?
- Do we require that the grant is issued during the first four cycles or exactly at the fourth cycle?
- May two requests be served by the same grant or should they be served by two separate grants?

The same specification written in SVA is unambiguous:

```
assert property (@(posedge clk) request |-> nexttime[4] grant);
```

This specification defines a clocked, or concurrent assertion, and it reads: when request is issued, it should be followed by grant in the fourth clock cycle measured from the clock cycle when request was issued.

Because of the formal nature of SVA, specifications can be interpreted by tools, and what is more important, understood by humans. When the specifications are formally defined, there is no place for misunderstanding.

Assertions Improve Bug Detection

Assertions promote systematic methodologies by tapping into several flexible ways of inserting design checks. Once a methodology is set up to accommodate the needs of a project and assertion libraries are established for the design style, the effort to craft assertions becomes on par with writing ordinary code. The use of assertions proliferates, within the design code and at the interfaces of design units, and thus the design scrutiny is raised to trap errors. The checks remain in place from test to test, without expending any additional effort. In a way, writing assertions turns into something as simple as inserting comments. As a matter of course, bugs get detected early and efficiently because of the widespread and comprehensive set of assertion probes.

Assertions Promote Faster Root Cause Analysis

Because assertions can represent temporal behavior, a failure of an assertion that stretches out over multiple clock cycles detects a bug and concisely isolates it to the assertion expression. Now, one only needs to examine and analyze the temporal expression of the assertion to determine the root cause of the failure. Several

modern debug tools support such an analysis to speed up the bug-fixing process. For example, by providing a precise window of time in which the failure occurred along with the cycle-by-cycle values of assertion signals, engineers can direct the analysis in the immediate design area of the failure. This is highly valuable and efficient.

A similar case with traditional techniques requires engineers to detect the failure by examining the output results, perhaps a mismatch of a value many cycles after the occurrence of the failure. A manual trace of values cycle by cycle through the design, without having specific clues about the behavior that actually caused the failure, is what the engineer must typically follow. As such, much of the difficult debugging is confined to the experts that retain intricate knowledge of the design.

Assertions Can Use Simulation and Formal Checking

The essential SVA features that exhibit temporality and clocking are strictly based on a mathematical framework, well understood and studied in academia. The availability of formalism made it possible to adopt proven algorithms for simulation and formal analysis. This lead the way to taking the same assertion and applying both methods, one in a simulation environment for a set of tests, and the other in formal verification to conduct thorough proof analysis. Barring the limitations imposed by the fundamental differences between the two methods, both methods are applied to the same assertions for benefits within their individual processes.

The great benefit from this symmetry of use is that engineers need to write assertions only once. In most cases, a failure in simulation can be reproduced in formal analysis, and vice versa. A good methodology provides sufficient adjustments to take care of the small practical differences and limitations between the two methods. Besides being efficient, using the same assertions expels the major impediment to ensuring that the same behavior is checked by simulation and formal methods. Formal methods would check the critical blocks, and simulation would concentrate on system integration and the remaining blocks within it.

Assertions Are Part of Design Documentation

Traditionally, design documentation at any level consists of two parts. One is a stand-alone specification in a natural language, outside the domain of SystemVerilog. The other is a set of comments spread throughout the code in SystemVerilog. Neither of these specifications has any executable impact on the behavior of the design. That is, the behavior shown by the interpretation of SystemVerilog code does not necessarily correlate with the documented comments or outside specifications. Another commonly experienced pitfall is the enduring burden to keep the documentation up to date as the SystemVerilog design code matures and evolves over the life of a project.

Assertions, on the contrary, are executable statements that check the behavior of the design, no matter at what stage the design is being interpreted. This enforces the stipulation that assertions must change in accordance with the changes in the design, so there is no additional undertaking. As the design progresses, the assertions get updated to comply with the changes, thereby maintaining the documentation aspect of the design as well. Any laxness in the process gets caught by an assertion failure, which must be corrected to move forward. Writing formal specifications in SVA is not always an easy task, but it usually pays off because it leads to better understanding of the design, better design quality, and better documentation.

1.2 Assertions in Design Methodology

Assertions are an important part of the design and verification flow. This section discusses the use of assertions at various stages of the flow.

Figure 1.5 depicts a block diagram of a typical design and verification flow. The stages in the flow less relevant to assertions are omitted from this block diagram.

Usually, at the project inception hardware designers or architects write a product specification in a natural language, for example, in English. Based on the product specification, a high-level architectural model [37] is created in languages such as SystemVerilog or SystemC [5]. This architectural model may not be anchored with an accurate model of the design clock cycle; rather, it models functionality at a high level. The objective is to develop an efficient architecture by performing tradeoff analysis for time and area estimates, physical and power domain partitioning, input/output port definitions, etc.

Once an architecture is determined from the high level analysis, the architectural model is taken as the basis for developing a clock cycle accurate RTL model. Ultimately, this model evolves into a stable base for driving synthesis and physical design. In many organizations, the RTL model is considered the golden reference for the design. This dictates that the model be maintained and updated with any changes to the design. The RTL model is then synthesized automatically or manually into a gate or a transistor level with a netlist that specifies the connectivity [49]. This synthesized netlist is processed further by place and route tools to physically place and connect the gates on a chip for manufacturing.

For each design stage, there is a related verification stage which checks the design correctness at the corresponding level of abstraction. Below we discuss the role of assertions at the relevant design and verification stages.

1.2.1 Using Assertions for High Level Model

The design specification is a document usually written in a natural language describing its architecture and functionality. This document normally includes the main design components, data formats and communication protocols. Below is a typical example of a specification:




Fig. 1.5 High-level design and validation flow

The system consists of a transmitter and a receiver connected by a point-to-point duplex channel. The transmitter sends to the receiver packets and gets an acknowledgment from the receiver upon the packet receipt. The packet contains a header and a body. The header consists of 8 bits, and the two most significant bits contain information about the transaction type: data~(10),~control~(01),~or~void~(00). The remaining 6 bits of the header contain the transaction tag in case of a data transaction, and are 0 in case of a control transaction. For void packets the tag field may contain any value. The packet body consists of three bytes; these bytes contain raw data for data transactions and commands for control transactions . . .

Upon receipt of a data or a control packet the receiver sends back to the transmitter an acknowledgment signal. The acknowledgment consists of 7-bits: the most significant bit is set to 1, and the remaining 6 bits contain the tag of the received packet. If a void packet is received, its contents are ignored and no acknowledgment is sent . . .

The transmitter is not allowed to send a new packet before an acknowledgment is received. If timeout is reached, the transmitter sends the same packet again. If after three retries it does not get an acknowledgment, it asserts the error signal and requires a manual reset.

Specifications written in natural languages are ambiguous, and cannot be processed by tools. If we rewrite the properties from this specification in SVA as shown in Fig. 1.6, tools are then able to verify model compliance to its specification. We do not give the complete specification here (for example, we do not specify how timeout is set, and how a packet is resent), but only a fragment to illustrate the concept.

We briefly describe the SVA code in Fig. 1.6, derived for the specification, to get an intuitive idea of how assertions can be extracted from a specification and used

```
typedef enum logic[1:0] {
1
       txa data = 2'b10, txa control = 2'b01,
2
       txa void = 2'b00, txa forbid = 2'b11 } txa t;
3
   typedef logic [5:0] tag_t;
   typedef logic [23:0] data t;
   typedef struct packed { txa t txa; tag t tag; data t data; }
       packet t;
   typedef struct packed { logic ack received; tag t tag; } ack t;
   checker spec (
8
9
    packet t tx packet, // Packet to be transmitted
     packet_t rx_packet, // Last received packet
10
     11
                      // Acknowledge
// Timeout active
// Error signal
     ack t ack,
     logic timeout,
13
     logic err,
14
                         // System clock
15
     event clk,
     logic rst);
                         // Reset
16
   default clocking @clk; endclocking
17
   default disable iff rst;
18
   // Legal transaction type
19
   let legal_txa(txa) = txa != txa_forbid;
20
   // Non-void packet sent
21
   let packet sent = sent && tx packet.txa != txa void;
22
   // Right acknowledgment received
23
   let right ack = ack.ack received && ack.tag == tx packet.tag;
24
   // Transmitted packet is always legal
25
   tx packet legal: assert property (legal txa(tx packet.txa))
26
       else $error("Transmitted packet is malformed");
27
   // Received packet is always legal
28
   rx packet legal: assert property (legal txa(rx packet.txa))
29
       else $error("Received packet is malformed");
30
   // No acknowledgment thrice
31
   sequence no_ack_thrice;
32
     (!right ack[+] ##1 timeout)[*3];
33
   endsequence
   // Despair - raise error flag
35
   no_ack: assert property (packet_sent ##1 no ack thrice |->
36
     always err) else $error("Err indication does not persist");
37
   endchecker : spec
```

Fig. 1.6 System specification

for ensuring model compliance. Lines 1–7 define new types (see Sect. 2.1). Line 1 defines an enumeration type giving names to specific integral values. Types tag_t and data_t define new names for logic arrays of corresponding bounds. Lines 6 and 7 assign names to the combined pieces of data.

Lines 8–38 define the specification as a checker. A checker is a special verification unit containing assertions and their related code. By default, assertions tx_packet_legal, rx_packet_legal, and no_ack use the clock declared in line 17. We discuss the default clocking statement in Sect. 12.2.2. Similarly, line 18 describes a default reset for all concurrent assertions in this checker. When rst is asserted, no concurrent assertion is checked. This is carried out to disable assertion checking during the reset sequence. Handling clocks and resets is a very important topic, but we postpone the discussion on the related SVA features until Chaps. 12 and 13.

Lines 20, 22, and 24 define aliases for different conditions used in the assertions. Sequence no_ack_thrice defined in lines 32–34 models the relationship between right_ack and timeout from the specification: "The transmitter is not allowed to send a new packet before an acknowledgment is received. If timeout is reached, the transmitter sends the same packet again. If after three retries it does not get an acknowledgment, it asserts the error signal and requires a manual reset." Thus, the whole sequence

```
(!right ack[+] ##1 timeout)[*3]
```

detects a situation when signal timeout is activated three times while awaiting acknowledgment.⁵ We discuss sequences in Chap. 5.

Assertion no_ack in line 36 states that if upon sending the packet (packet_sent) there is no acknowledgment (no_ack_thrice), then the error flag err should be asserted forever, that is, until the system reset occurs.

The above example shows that assertions can be inferred from a system level description for expressing them in SVA. These assertions can then be applied to a high level model in SystemVerilog and checked in simulation or they may be proven formally.

Using SVA for system level has some difficulties. The main issue is clocks. The system description is not always clock accurate, and is often formulated in terms of transactions and real time. The signal activities are not expressed in terms of transitions synchronized by design clocks. In contrast, SVA requires an exact clock specification for every assertion. For example, the SVA specification in Fig. 1.6 is less abstract than its verbal counterpart with respect to the specification of the clock, reset, and timeout signals.

However, SVA has an important advantage that the same assertions may be used directly or after some refinement as checkers in RTL verification, after the high level model is refined to an RTL model of the design. As long as the high level model

 $^{^5}$ This specification does not provide details about how the timeout condition is formed. Of course, a complete specification should provide them.

embodies an approximate notion of a clock, it may still be possible to describe assertions for the model. SVA provides several means for managing abstractions. For example, we can define clock and reset only once using default clocking and default disable iff statements. Specifying the exact clocks and resets requires changing these statements only. The assertion building blocks are encapsulated in let, sequence, and property statements. System refinement can thus be handled using appropriate abstraction means. In our example, if the timeout mechanism needs to be refined, it is enough to modify sequence no_ack_thrice. The mechanics of attaching or substituting one model with another in the refinement process is further supported by a configuration mechanism of SystemVerilog.⁶ This is an iterative step which continues to refine the architecture and to adjust the assertions according to the modified requirements.

The situation gets more complicated if the language of the model is not SystemVerilog. For example, high level models of Systems on Chip (SoCs) are often written in SystemC, as this language can be natively integrated with the C/C++ code of software components. Unfortunately, SystemC does not yet have its own formal specification subset for assertions or provide a standard integration with external formal specification languages [56]. Therefore, using SVA specifications with SystemC models is tool dependent. There are other languages, such as TLA [42] designed specially for high level system specification. These languages are more abstract than SVA, and therefore better suited for this purpose. Detailed discussion about high level model validation is out of the scope of this book.

There are attempts in the academia and in the industry [48, 60] to synthesize an RTL model directly from its formal specification, and some promising results have been demonstrated. Nevertheless, there is still a long way to go for this approach to become practical, and we do not discuss it in this book.

1.2.2 Using Assertions for RTL Model

The methodology of using assertions for RTL design verification is commonly known as Assertion-Based Verification (ABV), [15, 30, 38, 59]. The idea is to instrument RTL code with assertions to capture the design intent and to check the local correctness of the design. In the former case, assertions are written for checking the behavior at the interfaces. In the latter case, assertions are embedded in the design units, interspersed through the code as needed to check the local correctness.

Assertions on Interfaces

In this method, assertions are written to express the behavior as seen at an interface. Customarily, verification engineers write such assertions as they do not require

⁶ Configurations were introduced in Verilog 2001 [2].

intimate knowledge of the design details. This method of verification where the design units are viewed as black boxes, meaning without the knowledge of internal design details, is called *black-box verification*.

Verification engineers examine the high level specification of a design unit to infer rules and properties that must be satisfied by the design unit. Each rule may translate to one or more assertions. Once written and corrected, these assertions tend to remain unaffected by the changes in the internal design unit code. They are nonintrusive to the design units and can be retained physically outside the design units as well. SystemVerilog provides means of attaching checkers to the design units whenever needed using the bind statement, without actually modifying the source code of the design units.

Some examples of the functionality checked by the interface assertions are:

- Bus communication protocols
- Memory transactions
- Data transformations
- Transaction arbitration

Another pivotal use of these assertions is to detect errors when various design units are assembled into a larger unit. As integration issues emerge, they are effectively captured by these assertions. By maintaining the consistency of interfaces, individual design units are effectively freed from outside considerations, at least for verification purposes.

Embedding Assertions Within Design

Most often designers attend to their design units for local correctness. Within the scope of the design unit, they write assertions as they develop code to ensure signal relationships. When assertions are written over internal signals of a design unit for performing local checks, the verification process is termed as *white-box verification*.

A typical example is shown in Fig. 1.7.

Module shreg in Fig. 1.7 implements a shift register shift_reg in RTL code (lines 3–12). Two assertions check_shift and check_rst verify the implementation correctness of the code.

The first assertion <code>check_shift</code> checks that the new value of <code>shift_reg</code> is obtained by left rotation of its old value unless the new value was set explicitly when <code>set</code> was asserted. The system function <code>\$past</code> used in this assertion returns the value of its argument evaluated at the previous clock cycle (see Sect. 6.2.1.2). Note the operator <code>disable iff</code>, which disables the assertion check when the reset signal is active.

The second assertion <code>check_rst</code> checks that <code>shift_reg</code> is reset correctly. We use a deferred assertion which is not clocked, and not a concurrent one here because the register reset is asynchronous and we need to check it at each simulation step, and not only at the clock cycles. Section 1.3 and Chap. 3 explain the difference between deferred and concurrent assertions in more detail.

```
module shreg (input logic clk, rst, set, logic [7:0] val,
1
     output logic [7:0] shift reg);
2
     always @(posedge clk or posedge rst) begin
3
       if (rst) shift req <= 0;</pre>
       else begin
5
         if (set) shift reg <= val;</pre>
6
         else begin
           shift reg <= shift reg << 1;
           shift reg[0] <= shift reg[7];</pre>
10
       end
11
     end
     check shift: assert property (@(posedge clk)disable iff (rst)
13
14
       nexttime shift reg == $past({shift reg[6:0], shift reg[7]}));
15
     check rst: assert #0 (rst -> shift req == '0);
   endmodule : shreg
```

Fig. 1.7 Checks for a shift register

Below are some typical items to check in white-box verification:

- Compliance of interface
- Finite State Machine (FSM) transitions
- · Memory access correctness
- Stack and queue overflow and underflow
- Arithmetic overflow
- Signal stability

The complete list depends on a specific methodology; see [15, 30, 38, 59] for suggestions.

Although local assertions do not completely verify the design, their advantage is huge. They make design debugging more effective – a bug is detected and caught close to its origin. Thus, in Fig. 1.7 an incorrect implementation of the shift register will be immediately detected, and a failure of assertion <code>check_shift</code> or <code>check_rst</code> will point to the problematic code because these assertions are physically adjacent to it. Without these assertions, an implementation bug could manifest itself in another part of the design and probably several clock cycles later. One can imagine the difficulty of debugging that error.

Assertion Coverage

When administering a large verification project, one needs to know whether the intended functionality has been verified in its full scope, covering all functional scenarios of interest and all corner cases. Clearly, just making assertions a part of design flow does not adequately provide confidence in judging that the verification is complete or even comprehensive. Therefore, assertion coverage plays a critical part in decision making and tracking progress of the design verification project, keyed to the inquiry – "Are there enough assertions?"

The question is, what kind of coverage can be obtained from assertions to provide substantive indications? We note that, generally, there are two ways to approach this question. In the first approach, inquiries about the functionality are the central focus. In this regard, behavioral fragments expressed by various assertions must be matched against the specifications to determine the extent of the functionality included in the umbrella of the assertions. In the second approach, structural aspects of the design form the criteria. For example, the number of design elements (signals, registers, etc.) included in the assertion checks, the number of input and output signals included in assertions, and the number of assertions relative to the design code size. Both approaches are useful indicators that provide meaningful guidance in determining the required level of verification effort.

Coverage-Based Verification

A complementary approach to assertion-based verification is *coverage based verification*. Coverage-based verification starts by taking functional scenarios (*coverage points*) from the test plan and then collecting coverage of these scenarios on available tests. The goal is to refine tests so that all coverage points are hit. The main problem with this approach is its practical infeasibility: some scenarios are extremely difficult to cover, and some of them are even impossible. Usually, the first few tests hit many coverage points, and up to 60% coverage is quickly reached. The additional tests cover fewer and fewer new coverage points, while reaching 80% coverage or higher becomes increasingly challenging [15, 52] and unlikely in practice. Verification managers usually empirically set the desired coverage percentage, called the *coverage goal*. We discuss SVA tools for checking coverage in Sect. 3.7 and in Chap. 18.

1.2.3 Using Assertions Beyond RTL

Although assertions are most frequently used at the RT level, other areas of development later in the design phase can also benefit from their specification. Some analysis tools have already been developed, while others have been explored to take advantage of the expressibility of the assertion features. We discuss three important areas here.

Equivalence Verification

Equivalence [39] of two models usually means checking that the synthesized gatelevel netlist is equivalent to the golden RTL model (Fig. 1.5). Equivalence checking is also needed when local changes are made in the design to improve its performance or power consumption. Equivalence checking is usually done by formal verification because comparing model behaviors in simulation cannot provide good confidence in the correctness of design transformations. At first, it seems that there is no need for assertions in equivalence verification, but it turns out that the role of assertions is quite significant because two models are equivalent only under some assumptions on their inputs. For example, the input signal go of an RTL model may correspond to two input signals of the synthesized model: go and its negation ngo. To prove equivalence the following assumption about signal inversion should be supplied to the tool:

```
assume #0 (go ^ ngo);
```

In addition, assumptions about internal signals are used as hints for formal equivalence verification. To maintain correctness of the proof of equivalence, these assumptions must be proven as assertions in the corresponding blocks (see Sect. 10.5). Assumptions written for formal equivalence verifications are usually nontemporal; therefore, they are best represented with deferred assumptions having the syntax assume #0 as shown above.

Timing Verification

When an RTL model is synthesized into a gate-level model, a critical step is to verify its timing to ascertain correct functioning of the circuit [21]. Even though timing verification significantly differs from RTL verification, assertions are used there, although for different purposes. For example, RTL assertions are used to characterize signal paths, as in the following cases:

False Path Elimination Circuit performance is limited by the delay of the longest combinatorial path. Given the circuit configuration, if the actual signal transmission along this path is not possible then this path should be ignored for critical path and performance analysis [12, 22].

Clock Domain Crossing When data are transferred from a state element controlled by one clock to a state element controlled by another clock the data should be stable long enough to guarantee that it be sampled by the second clock [47].

Multicycle Path A multicycle path is a path between two state elements having a delay greater than one clock cycle. A multicycle path permits the sum of the delays of its combinatorial logic elements to be greater than one clock cycle. In this case, the second state element should be stable during the corresponding number of clock cycles [12].

We also mention the need for analog assertions [45] to specify the timing behavior of electrical components and interconnections. This type of assertion is specific to analog circuit analysis and performance verification, and it is currently not part of SVA. We do not discuss it further in this book.

Post-Silicon Validation

The advantages of RTL verification, on the one hand, are flexibility and high observability – all signal values at any time may be observed in simulation. On the other hand, it is very slow, and does not allow checking many important global scenarios. With post-silicon validation (and to great extent in emulation) the situation is the opposite: chip speed is very high, but signal observability is low [50].

Postsilicon debugging is challenging because a bug can remain unobserved for millions of cycles after its actual occurrence. ABV may help coping with this problem. For example, the most critical RTL assertions may be synthesized into the chip. Assertions fire immediately upon detecting an error, thus making bug detection and debugging much more efficient.

1.3 Assertions in SystemVerilog

There are three kinds of assertions in SystemVerilog:

- Immediate assertions
- Deferred immediate (or simply "deferred") assertions
- Concurrent assertions

The simplest assertions are *immediate assertions*. They act as procedural if statements and are legal in any place where procedural if statements may appear. Immediate assertions are nontemporal and are executed when the control flow reaches them. The main advantage of immediate assertions is that they have unrestricted applicability in various kinds of designs, synchronous and asynchronous, and in testbenches. Their ease of use makes them appealing, but the limited expressiveness lends their efficacy to detecting only simple bugs. In some cases, they are also prone to producing spurious failures due to simulation races. This is explained in Chap. 3.

Deferred assertions are an improvement over immediate assertions. They are similar to immediate assertions in that they are nontemporal and unrestricted in their use. Two important differences make them immensely useful over immediate assertions: they do not produce spurious failures, and they can be placed both inside and outside procedural code. Deferred assertions are explained in Chap. 3.

The most interesting and complex assertions are *concurrent assertions*. They are temporal and can describe design behaviors over time. For example, a concurrent assertion can state that a request should be granted in two clock cycles. Concurrent assertions are always clocked. Assertion a1 in Fig. 1.1 is a simple example of a concurrent assertion. This assertion is Boolean and checked immediately before the rising edge of c1k. Concurrent assertions may appear both inside and outside procedural code, but they cannot be placed in functions and tasks. The description of concurrent assertions occupies the major part of this book.

Figure 1.8 illustrates the use of all three kinds of assertions. Here, assertion at is an immediate assertion, a2 and a4 are deferred assertions, and a3 and a5 are concurrent assertions. Operator -> used in assertions a1, a2, and a4 is an implication

```
module m2(input logic c, d, clk);
1
2
     logic a, b;
     always comb begin
3
       a = c \& d; b = c | d;
       // Immediate assertion
5
       a1: assert (a -> b);
       // Deferred assertion
       a2: assert #0 (a -> b);
       // Concurrent assertion
9
       a3: assert property (@clk a != b);
10
11
     end
     // Deferred assertion
     a4: assert #0 (a -> b);
13
     // Concurrent assertion
14
     a5: assert property (@clk a != b);
15
   endmodule : m2
```

Fig. 1.8 Kinds of assertions

operator (see Sect. 2.2). always_comb used in line 3 is explained in Sect. 2.5. Notice that deferred assertions (e.g., a4) are legal outside procedural code, but immediate assertions would be illegal there. Immediate assertion a1 and deferred assertions a2 and a4 are checked whenever either a or b changes value, while concurrent assertions a3 and a5 are checked only at the clock event clk, which occurs when clk changes value.

Concurrent assertions use *sampled* values of their variables, that is, the values of the variables at the beginning of the simulation step, before any values change in the time-step. Therefore, in waveforms it looks as if concurrent assertions used past values of design signals from the preceding time-steps. This is described in detail in Sect. 3.4.3.

Assertion Statements

Assertion statements specify properties on the behavior of signals. There are three major assertion statements in SVA: assertions (the keyword assume), assumptions (the keyword assume), and cover statements (the keyword cover). Each type of statement directs what to do with the specified property. These statements may be immediate, deferred, or concurrent.

An assert statement makes sure that the design behaves as the properties in the statement prescribe. Its purpose is to check the correctness of the system. An assume statement states assumptions, specifying properties that should hold to enable the proper functioning of the system. Its purpose is to ensure that the checking is conducted under a system or environment that complies with the stated conditions. A cover statement checks that the behavior it specifies is actually exhibited while testing the system. Unlike assert statements, the interest lies in detecting only selective cases from all possible cases of valid behavior.

20 1 Introduction

In the following example, the same condition is used in all three types of assertions (al,ml,cl) to depict the difference in motivation.

```
bit ok;
// ...
al: assert property (@clk ok);
ml: assume property (@clk ok);
cl: cover property (@clk ok);
```

The difference between a1 and m1 is as follows: a1 states that ok must be 1'b1 for correct behavior. It is a property that the design is obliged to satisfy. m1 states that it can be taken for granted that ok is 1'b1. Assertions are checked while taking into account assumptions. Typically, but not necessarily, assumptions are written on primary inputs of the design, characterizing the behavior of the environment of the design.

The cover statement c1 states that there exists some valid system behavior where ok gets value 1'b1. This does not prevent the system from having other valid behaviors where this condition does not hold. Cover statements are usually written to ascertain that there exist tests exercising specific scenarios.

SVA assertion statements are further discussed in Chaps. 3 and 18.

1.4 Checking Assertions

This section introduces how assertions are checked in different verification environments:

- · Simulation.
- Emulation.
- Formal analysis.

Checking Assertions in Simulation

Simulation [55] is modeling the behavior on a sequence of input stimuli, called a (simulation) test. Simulation is the most popular method for checking assertions. All major SystemVerilog simulators, for example, VCS[®], Questa[®], and Incisive[®], support SVA and can check assertions, assumptions, and cover statements.

Of course, in simulation it is only possible to check whether an assertion is violated in a given test case. If it is violated, we find a problem. But the absence of violation does not mean that the design is correct – the same assertion may be violated in another test case, or it may even be violated later in simulation if the same test case is extended.

Although in theory no reasonable number of test cases is sufficient to exhaustively check correctness of real designs, in practice simulation with coverage measurements does provide significant confidence in system correctness if no assertion violations are detected.




Fig. 1.9 Transactions of assertion @ (posedge clk) req |-> ##[1:3] ack

Typical simulators can report not only assertion violations, but also individual transaction completions. By a transaction, we mean an individual case of assertion evaluation. Figure 1.9 illustrates transaction completions for the following assertion:

```
req ack: assert property (@(posedge clk) req |-> ##[1:3] ack);
```

This assertion states that each request req receives an acknowledgment ack in one to three clock cycles from the moment when req was asserted. Figure 1.9 shows two transactions, trans1 and trans2. Transaction trans1 starts at time 20 and completes at time 40, while transaction trans2 starts at time 90 but does not complete before the end of simulation. An incomplete transaction does not necessarily indicate a correctness problem because, had simulation lasted longer, the transaction might complete as expected. However, this situation requires further analysis. When crafting tests (directed and random) it is desirable to leave no transactions pending (incomplete). Time points where there are no pending transactions are called quiescent points. Although it is a good practice to ensure that the simulation always ends at quiescent points, in reality it is hard to attain such a state for all assertions at the same quiescent point. In general, it is necessary to analyze incomplete transactions for any unexpected behavior.

In Fig. 1.9 the transactions are delayed by one clock cycle with respect to the times at which req and ack rise. This may seem strange. For example, why does trans1 last from time 20 until 40, and not from 10 until 30? Concurrent assertions use sampled values of their variables, that is, the values that these variables have at the beginning of a simulation step (Sect. 1.3). At the beginning of the simulation step corresponding to time 10, the sampled value of req is still 0. Assertion req_ack will use the new value 1 of req only at time 20. This explains the shift in transaction marking in the figure.

Assertions may also be checked in *random simulation* [15, 31] environments. Random simulation can be achieved using testbenches that generate random stimuli using constraints or assumptions. While random simulation can hit a large amount of bugs rather quickly, it is difficult to achieve good coverage of corner cases. Another drawback of random simulation is its speed – resolving imposed constraints can be prohibitively slow.

22 1 Introduction

Simulation provides the most intuitive and user-friendly environment for assertion debugging. Even when assertions are not targeted for simulation, simulation may be used for assertion debugging. It seldom happens that complex assertions are written correctly the first time. Usually failures in new assertions are caused by bugs in the assertions themselves, not by design errors. Before checking assertions in other environments, such as emulation and formal verification, it is highly recommended to debug them in simulation. We discuss assertion debugging in Chap. 19.

Checking Assertions Using Hardware Acceleration

Checking assertions in simulation is intuitive and convenient, but unfortunately, simulation is slow compared to hardware speeds, and as a result, only very short testing sequences may be checked this way. For example, to check a CPU model, an operating system and several typical applications should be run on it, but it would take months or years to simulate a few seconds of the real work.

Solutions to bring the speed of simulation closer to that of the hardware being simulated include hardware acceleration, emulation [33], and rapid prototyping. In these methods, the design model is synthesized into a logic netlist, and this netlist is mapped onto a Field-Programmable Gate Array (FPGA) or an equivalent programmable device. Of course, checking a design in this way is still much slower than running the real device, but it is significantly faster than simulation. Because emulation tests are much longer than the simulation ones, they have a better likelihood of revealing bugs that could not be reached in simulation. To capture these bugs, assertions need also to be synthesized to become part of the emulation model. In theory all SVA constructs are synthesizable, enabling the solution to work in most cases. For other cases, however, this solution falls apart as some complex assertions synthesize into enormous size, consuming a large amount of available gates.

Checking Assertions Using Formal Verification

Formal Verification (FV) [16] is the most powerful method to check design correctness. It conducts exhaustive proof that the design complies with its specification. More precisely, formal verification tools prove assertion correctness under the hypothesis that all assumptions are satisfied. Unlike simulation and emulation, there is no need to provide input stimuli. If a tool can prove the assertion correctness, the assertion is correct for any set of input stimuli under the specified assumptions.

The main limitation of FV methods is the capacity of FV tools. They can handle only relatively small models, even though modern FV tools can efficiently

Actually many verification tools do require some input information, such as a clock pattern or a reset sequence.

1.5 Assertion Reuse 23

handle designs containing several thousands of state elements, latches and flipflops. Another important point to keep in mind is that the model for FV should be completely specified, requiring all its input assumptions to be explicitly stated. If some assumptions are missing, spurious assertion failures (so called *false negatives*) may be reported, as discussed in Sect. 10.3.

It follows that in simulation the main verification setup effort is modeling the environment and devising the testbench, while in FV a great deal of effort is spent on specifying assumptions.

Assertion Efficiency

It is often possible to express the same assertions in multiple ways. A specific style of assertion implementation may have a major effect on simulation or formal verification performance. Therefore, it is important to know how to write assertions efficiently. Unfortunately, in many cases formal verification and simulation impose different requirements on assertions for efficiency considerations, creating situations where efficiency tradeoff between the two methods becomes necessary. Possibilities exist to make a small sacrifice in assertion efficiency in formal verification that can provide a tremendous boost in simulation speed. Many factors are involved in making tradeoffs: complexity of assertions, number of assertions, and algorithms employed by a specific tool. When using a specific simulation or formal verification tool one should follow tool-specific recommendations about assertion efficiency.

1.5 Assertion Reuse

Although SVA is a powerful specification language, writing assertions is not an easy task. Even experienced people rarely write complex assertions correctly for the first time. Debugging assertions is more difficult than debugging RTL because the assertion language is declarative. Fortunately, many assertions are commonly encountered and may be reused by adapting them to different situations. For example, such assertions as "two signals are mutually exclusive", "a request is granted in *N* cycles", and "an FSM is never stuck" are routine. This presents an opportunity to define them once and then reuse by customizing as a library unit.

SVA provides many features for assertion reuse. Assertion components may be named and parameterized. Several related assertions, together with modeling code may be grouped as a unit for future reuse.

Expression Reuse

Expressions may be named and parameterized using a let statement, as shown in Fig. 1.10.

24 1 Introduction

```
logic a, b, c, d, cond, clk;
let onecold(sig) = $onehot(~sig);
// ...
always_comb begin
// ...
al: assert (onecold({a, b, c}) || d);
end
a2: assert #0 (onecold({a, b, c}) -> d);
a3: assert property (@(posedge clk) cond |=> onecold({a, b, c}));
```

Fig. 1.10 Expression reuse

```
logic ready, request, grant, clk;
// ...
sequence falling(x);
(x ##1 !x);
endsequence
al: assert property (@(posedge clk) falling(ready) |=> ready);
a2: assert property(@(posedge clk) request |=> falling(grant));
```

Fig. 1.11 Sequence reuse

In this example, a parameterized expression <code>sonehot(~sig)</code> is named <code>onecold</code> using a <code>let</code> statement. <code>sonehot</code> is a SVA system function returning <code>true8</code> when exactly one bit of its argument is set to 1. This <code>let</code> expression checks for <code>onecold</code> encoding which means exactly one bit of <code>sig</code> is 0. Notice that an instnace of the <code>let</code> expression is used in assertions <code>al, al, al</code> al is an immediate assertion ensuring that exactly one signal among <code>a, b,</code> and <code>c</code> is low when <code>d</code> is low. <code>al</code> is a deferred assertion ensuring that when exactly one signal among <code>a, b,</code> and <code>c</code> is low, <code>d</code> must be high. Another variation is the concurrent assertion <code>al</code> which specifies that after condition <code>cond</code> is true, exactly one signal among <code>a, b,</code> and <code>c</code> is 0.

We describe the let statement in Sect. 7.1.

Sequence Reuse

It is possible to assign names to sequences of signal values in time and to reference these sequences by name in assertions, as shown in Fig. 1.11.

falling is a sequence name, and x is its argument. (x ##1 !x) defines a sequence of values of signal x in time. Its meaning is that the value x = 1 is followed

 $^{^8}$ Strictly speaking, *true* is not defined in SystemVerilog, but we will use it where appropriate as an alias for 1'b1. Similarly, we will use *false* for 1'b0.

1.5 Assertion Reuse 25

by the value x = 0 in the next clock cycle. Sequence falling is reused in concurrent assertions at and a2.

Assertion a1 states that ready flag may drop at most for one clock cycle. More precisely, if ready gets deasserted after being asserted then at the next clock cycle ready should be asserted again. The operator |=> means "then at the next clock cycle", and it is called *non-overlapping suffix implication*. Assertion a2 states that request should be granted (grant = 1) in the next cycle, and one cycle later grant should be deasserted.

We describe sequences in Chaps. 5 and 9.

Property Reuse

Like expressions and sequences, properties may also be assigned a name to be used in concurrent assertions, as shown in Fig. 1.12.

In this example, <code>forever_n</code> is a property specifying that after n clock cycles (operator <code>nexttime[n]</code>) x should be true forever (operator <code>always</code>). This property is then reused in assertions at and at. Assertion at states that 100 clock cycles after reset phase was completed (<code>end_reset</code> asserted) the device should be operational forever (<code>operational</code> should always be high). Assertion at states that 5 cycles after entering a deadlock area (<code>enter_deadlock_area</code> asserted) signal stuck should be asserted forever.

We describe properties in Chaps. 4 and 8.

Assertion Libraries

Although the language features for naming an expression, a sequence or a property are beneficial for reuse in writing individual assertions, they are not sufficient for building a library of assertions. Commonly, an element from an assertion library

Fig. 1.12 Property reuse

⁹ For simplicity, here and in future examples we ignore the possibility of unknown and high-impedance values X and Z unless explicitly stated.

26 1 Introduction

```
checker mytrig (sequence trig, property prop, event clk);
al: assert property (@clk trig |-> prop);
cl: cover property (@clk trig);
endchecker: mytrig
module m (input logic done, ready, clock, output logic idle);
//...
always_comb begin
idle = done | | !ready;
end
mytrig check_consistency(done, idle, posedge clock);
endmodule: m
```

Fig. 1.13 A simple checker

encapsulates one or more related assertions, and some code to support the expressions used within the assertions, such as an FSM state or a variable value computed from a function.

A more suitable feature than what we have described so far is a checker. The checker construct is similar to a module in that it can contain assertions and modeling code, but its instantiation and parametrization accommodate the flexibility and usage that are specific to assertions.

The example shown in Fig. 1.13 illustrates the concept of checker.

mytrig is a **checker** which gets three arguments: trig, prop, and clk. trig should be a sequence, prop should be a property, and clk should be an event. mytrig consists of assertion at checking that whenever trig happens prop is true (operator | ->, called *overlapping suffix implication*), and a cover statement c1 monitoring whether trig happens.

The checker is instantiated in module m, line 10, with actual arguments done, idle, and posedge clock. Even though done and idle are signals, it is valid to pass them to the checker as actual arguments because Boolean expressions are special cases of sequences and properties.

We describe checkers and their use in Chaps. 21–23.

1.6 SVA and PSL

Beside SVA, PSL (Property Specification Language) [6] is another standard assertion specification language that is widely used in the industry. The goal of PSL is to provide a language subset for assertions that could work in conjunction with a variety of languages. To that end, the syntax is designed to be as neutral as possible, customized with a syntactic *flavor* for the individual language hosting the PSL features, such as SystemVerilog flavor and VHDL flavor. The semantics related to the integration of PSL with the host language is left open for the tools to define, to suit the environment of the tool.

1.6 SVA and PSL 27

Many of the PSL language features are semantically equivalent to those of SVA, but there are some differences of importance. One of the PSL features is the Optional Branching Extension (OBE) which defines operators for temporal properties in terms of branching time. The OBE features are meant only for formal verification and do not fit the simulation paradigm. SVA does not have the notion of branching time [28]; the time used in SVA is always linear (see Chap. 11), but all the linear time operators in SVA can be simulated. The OBE operators in PSL cannot be simulated.

PSL has an important mechanism of *vunits* (verification units) for encapsulating verification code. One vunit may inherit another in order to modify a portion of the verification environment. SVA has the checker construct and the bind statement. Vunits and checkers implement two different approaches to verification environment design: vunits are based on overriding and name matching, while checkers are based on argument mapping.

In contrast to PSL, SVA provides immediate and deferred assertions. The use and semantics of assertions in procedural code is undefined in PSL. Also, PSL lacks any notion of properties being invoked recursively. Since SVA is an integral part of SystemVerilog, its simulation semantics is well defined and SVA can be used much more widely within the context of SystemVerilog than is possible with PSL. Some examples of the benefits are:

- Sequences can be used outside the context of assertions.
- Integration with functional coverage features is powerful.
- Sampling of variables is precisely defined.
- Type compatibility and conversion is handled smoothly.

Exercises

- **1.1.** What is the main difference between the assertion specification language in SystemVerilog and the language subset used for RTL description?
- **1.2.** Modify the RTL code in Figs. 1.2 and 1.4 to take reset signal rst into account: when rst is asserted checking of active transactions should be stopped.
- **1.3.** Implement the following assertion

```
assert property(@(posedge clk) req[*2] |=> grant[*2]);
```

in RTL: two consecutive requests should be followed by two consecutive grants.

- **1.4.** What kinds of assertions exist in SVA? What is the difference between them?
- **1.5.** Compare formal specification languages with natural languages. What are the advantages of formal languages?
- **1.6.** What are the main advantages and disadvantages of checking assertions in (conventional) simulation?

28 1 Introduction

- **1.7.** Why is it useful to check assertions in emulation?
- **1.8.** What are main advantages and disadvantages of checking assertions using formal verification?
- **1.9.** Why assertion reuse is important? Which constructs exist in SystemVerilog for assertion reuse?
- **1.10.** What is the intended use of checkers in SystemVerilog?
- **1.11.** What are the main similarities and the main differences between SVA and PSL?
- 1.12. Simultaneous reads and writes
- (a) Express a statement forbidding simultaneous reads and writes as an immediate, deferred and concurrent assertion. Reuse the common part in all assertions.
- (b) Write a checker forbidding simultaneous reads and writes. Also check that both reads and writes actually happen.

1.13. Request is always granted

- (a) Write a concurrent assertion stating that each request should be granted at the next cycle.
- (b) Is it possible to express the same thing as an immediate assertion?
- (c) As a deferred assertion?
- **1.14.** Write the following assertion: When reset is deasserted it remains low forever.

Chapter 2 SystemVerilog Language and Simulation Semantics Overview

The limits of my language mean the limits of my world.

- Ludwig Wittgenstein

SystemVerilog language evolved from Verilog with three main goals:

- 1. To add features for describing test benches such that the stimulus generation portion of verification can go hand in hand with the design portion, replacing troublesome ad-hoc means for generating stimuli. Testbenches are often written using Verification Programming Interface(VPI) [7] to connect to external means such as verification languages, C/C++ programs [53], and scripts.
- 2. To add features for checking the expected behavior in simulation and formal methods. These features are related to assertions.
- 3. To simplify expressing hardware designs by providing language constructs such as struct, typedef, and new variants of always procedure.

Our objective in this chapter is to introduce some of the important SystemVerilog features that are often needed for writing assertions, or used in conjunction with assertions to support other tasks. We are not describing assertion features as they are covered in the rest of the book, but only assume that the reader has already gained sufficient overview of the assertion features from Chap. 1, at least in concept.

Some of the new features, especially those for writing testbenches, have a close semblance to constructs that you may have seen in programming languages. These include data types such as struct and typedef, auto-increment operators, classes and programs. They are similar in concept, but deviate sufficiently to suggest studying them without presumptions. Other features such as clocking blocks for describing clocks and interfaces for describing complex interconnections are brand new in purpose as well as in style.

Following the overview of the new features, we present an overview of the simulation semantics that establishes a framework to place the evaluation and semantics of assertions. It forms the basis for understanding assertion features described in this book.

Finally, this chapter is not meant to prepare you for writing testbenches or synthesizable designs. What we cover in this overview should motivate you to look for detailed syntax and semantics in other books on topics of test bench writing,

methodology and design [15, 31, 52]. The SystemVerilog Language Reference Manual [7] (referred in the rest of this book as LRM) is, of course, the most comprehensive, and is required as a reference.

In this chapter, we cover the following language features:

- Data type and variable declarations
- New expression operators
- Clocking block and event controls
- New procedures
- interface
- program
- \$unit and \$root
- package
- bind statement
- generate constructs

2.1 Data Types and Variable Declarations

First, we discuss integral data types which are said to represent logic values. The set of logic values in SystemVerilog have not changed from Verilog.

Integral Data Types

- 1 for true
- 0 for false
- X for unknown
- Z for high impedance

Some data types hold two values (0 and 1), while others hold all four values (0, 1, X and Z). Two-valued data types are:

- bit, unsigned, a single bit length
- byte, signed, 8-bit length
- shortint, signed, 16-bit length
- int, signed, 32-bit length
- longint, signed, 64-bit length

Four-valued data types are:

- logic, unsigned, a single bit length
- reg, unsigned, a single bit length
- integer, signed, 32-bit length
- time, unsigned, 64-bit length

Many other concepts about data types are adopted from common programming languages such as C++[24,53] and Java [32]. Some of the data types included in

this category are enum, struct, union, and string. Although similar in concept to their counterparts in programming languages, the detailed rules of interpretation have evolved to become incongruous to them. Many extensions are made to these concepts to suit the needs of hardware designers. A complete description of the rules and features can be found in the SystemVerilog LRM. We give a brief introduction to these types below.

enum Type

enum is a convenient way to name individual members of a group of integral constants. For example,

```
enum {on, off, disabled} SwitchStatus;
```

declares variable SwitchStatus to obtain one of three values: on, off and disabled. By default, constant values are of type int. The type of the constants can also be explicitly stated to be different than int. For example,

```
enum byte {on=10, off, disabled} SwitchStatus;
```

specifies the type of each constant to be byte and the starting value to be 10. The value of on is 10, off is 11 and disabled is 12.

struct Type

While an array is an aggregate of elements of the same type, struct is a set of named elements, where each element can be of a different type.

Example 2.1. A struct type declaration

```
bit clk;
struct {
  int id;
  enum {on, off, disabled}SwitchStatus;
  bit [7:0] op;
  bit [127:0] addr;
} trans;
al: assert property (@(posedge clk) trans.id < 200);
a2: assert property (@(posedge clk) trans.id < 200);</pre>
```

Each named element of trans can be accessed individually as shown above.

union Type

A slight variation from type struct is type union which is provided to map one or more members to the same storage, but allows access to the storage by naming either one of them and interpreting the type accordingly.

Example 2.2. A union type declaration

```
struct {
  int id;
  enum {on, off, disabled} SwitchStatus;
  bit [7:0] op;
  union {
   bit [127:0] fullAddr;
   bit [3:0] [31:0] aSlices;
  } addr;
} trans;
//...
al: assert property (@(posedge clk) trans.id < 200);
a2: assert property (@(posedge clk)
  trans.op < 16 |=> trans.addr.fullAddr[31:0] < 128);</pre>
a3: assert property (@(posedge clk)
  trans.op < 16 |=> trans.addr.aSlices[0] < 128);</pre>
```

Here, addr can be accessed either as fullAddr or in 8 32-bit slices from aslices. The important aspect of union is that it saves storage for data that is needed to be referenced in a variety of ways. There is no need to duplicate data or reassign to another data for the sake of getting a part of it.

typedef Type

In Example 2.2, trans is a user-defined type. Users can name a type by using typedef. Once defined as typedef, the name can be used in any place where a type can be used and interpreted as the original type defined by the typedef. For readers well acquainted with programming languages will find this concept rather convenient.

Example 2.3. A typedef declaration

```
typedef struct {
  int id;
  enum {on, off, disabled} SwitchStatus;
  bit [7:0] op;
  union {
    bit [127:0] fullAddr;
    bit [3:0] [31:0] aSlices;
  } addr;
} transT;
transT t1, t2;
```

struct trans from Example 2.2 is declared as a type name transT, which now allows convenient declaration of two variables t1 and t2 with the same type.

string Type

Another useful type added to SystemVerilog is string. It represents a dynamic array of characters, where each character is of type byte. As the representation is

dynamic, one can extend or shrink a variable of type string. Numerous other builtin operators and methods are provided such as equating two strings, concatenating multiple strings, and converting a string to other types.

Example 2.4. Use of string for messages

```
string urgentPkt = "Packet of high urgency";
string regularPkt = "Packet of regular urgency";
bit urgent, endPkt;
string arrivalMsg = " arrived before repeat cycle.";
string logMsg;
// ...
always @(endPkt)
  if (urgent) logMsg = {urgentPkt, arrivalMsg};
  else logMsg = {regularPkt, arrivalMsg};
```

Strings urgentPkt, regularPkt and arrivalMsg are initialized with literal strings. At every end of a packet indicated by signal endPkt, logMsg is constructed by concatenating individual substrings. Strings are often useful in constructing and displaying suitable assertion messages of success and failure. Strings can be passed to a checker, making it possible, for example, to customize messages from a library of assertions.

2.1.1 Packed and Unpacked Arrays

In SystemVerilog, arrays can be declared as *packed* or *unpacked*. Packed arrays represent contiguous bits, while unpacked arrays do not assume any specific layout of bits. Both forms are useful, and can be converted to either form using *bit-stream casting*.

Packed Array

A packed array is declared by specifying dimensions before the data identifier name, such as

```
bit [3:0] [7:0] u1;
```

where u1 is a two-dimensional array, with the higher level dimension as [3:0] and the lower level dimension as [7:0]. It can also be viewed as array u1 consisting of four subarrays, where each subarray is 8-bits long.

A one-dimensional packed array is also referred to as a vector.

Because data types with predefined length are already vectors, they cannot be used in packet array declarations while single bit length data types (bit, logic and reg) can. For example,

```
bit [31:0] status_bits;
```

¹ Checkers are described in Chap. 21

declares status_bits as a vector of 32 bits. Another way to represent the same data is by declaring it as a multidimensional packed array. Because packed arrays represent contiguous bits, an equivalent declaration is

```
bit [3:0][7:0] status_bits;
```

More than one dimension for packed arrays is provided simply to slice the data representation in a more intuitive form, so that the slices can be accessed with indices into arrays. In fact, a multidimensional packed array is equivalent to a vector of bits. This makes the conversion between two different dimensioned packed arrays straightforward as there is a common equivalent form of a vector representation, as long as the total number of bits are the same for both arrays.

For example,

```
logic [31:0] f1;
logic [3:0] [7:0] f2;
logic [1:0] [15:0] f3;
assign f1 = f2;
assign f3 = f1;
is the same as,
logic [3:0] [7:0] f2;
logic [1:0] [15:0] f3;
assign f3 = f2;
```

Unpacked Array

For unpacked arrays, the dimensions are specified after the data identifier name, such as

```
bit p1 [3:0] [7:0];
```

where p1 is a two-dimensional array, with the higher level dimension as [3:0] and the lower level dimension as [7:0]. Similar to the specification of packed arrays, p1 can be viewed as consisting of four sub-arrays of 8-bits length.

Bit-Stream Casting

Unpacked arrays do not intrinsically translate to a vector of contiguous bits, unless explicitly type casted using bit-stream casting. An example is shown below.

Example 2.5. Use of bit-stream casting

```
typedef bit unpackedArray [3:0][31:0];
typedef bit [127:0] packedVector;
unpackedArray aStatus;
packedVector vStatus;
always @(posedge clk)
   vStatus <= packedVector'(aStatus);</pre>
```

Bit-stream casting packedVector' (aStatus) is used in the assignment to vStatus, whereby array aStatus consisting a total of 128 elements of bits from the array are converted to a vector of 128 bits.

For a complete set of rules for bit-stream casting, the reader is advised to refer to the LRM.

2.1.2 Lifetime of Variables

Variables of any data type have lifetime associated with them. A variable can be static or automatic. A static variable can be accessed throughout the simulation, while access to an automatic variable is restricted during the time that its scope of declaration is active. In general, variables inherit the lifetime of their scopes.

Following are some of the important rules that govern whether the lifetime of a variable defaults to static or automatic. Variables are static by default when declared in

- Compilation unit scopes (scopes outside modules, programs, interfaces, and checkers)
- Module, interface, program, checker, package scopes (scopes outside tasks, functions and procedural blocks)
- Static tasks, functions or procedural blocks

Variables are by default automatic when declared in

- Automatic tasks, functions or procedural blocks
- For-loop initialization
- Classes

The following example illustrates the case of for-loop.

Example 2.6. Use of the for-loop construct

```
always @(posedge clk) begin
  shiftCtrl <= en && shiftCode[3];
  for (int i = 1; i < MAX_WIDTH, i++)
    shiftData[i-1] <= shiftData[i];
end</pre>
```

Index variable \mathtt{i} is automatic by default. The code in Example 2.6 is equivalent to

```
always @(posedge clk) begin
    shiftCtrl <= en && shiftCode[3];
    begin
        automatic int i;
        for (i = 1; i < MAX_WIDTH,i++)
            shiftData[i-1] <= shiftData[i];
    end
end</pre>
```

П

To override its default lifetime, a variable can be declared with an explicit lifetime of static or automatic in tasks, functions, classes, and procedural blocks.

Example 2.7. Overriding default static lifetime

```
module m1 (input logic [3:0] in1, output logic [31:0] out1);
    function [31:0] recur(input logic [3:0] in1);
2
      automatic logic [3:0] r1 = in1;
3
      if (r1 == 0) recur = 1;
4
      else recur = r1 * recur(r1 - 1);
5
    endfunction
6
    always @(in1)
7
      out1 = recur(in1);
8
  endmodule
```

Example 2.7 illustrates how a variable in a static function can be overridden to be automatic. Function recur is static by default, but variable r1 is overridden to be automatic by explicitly declaring it as automatic. An initial value equal to the value of in1 is assigned in line 3 to r1 which gets executed each time recur is entered.

Example 2.8. Overriding default automatic lifetime

In Example 2.8, function recur1 is declared as automatic, so by default ncount is automatic. But, variable ncount is overridden to be static by explicitly declaring as static. Unlike automatic variables, static variables are guaranteed to be initialized only once, and it occurs at the beginning of the simulation. Variable ncount is initialized in

П

```
static integer nCount = 0;
```

2.2 New Expression Operators

In this section, we describe some of the new expression operators available in SystemVerilog. These operators are meant not only for assertions, but also for any code using expressions. The following new operators are discussed:

- inside
- Implication and equivalence

2.2.1 inside Operator

SystemVerilog introduced a notation for sets of singular values and set membership operator inside on these sets. inside denotes the test for set membership.

Example 2.9. inside operator

```
module m1(input logic [3 : 0] in1, input logic clk);
logic c1;
assign c1 = in1 inside {2, 4, 6, 8};
always @(posedge clk)
if (c1==1'b1) $display ("Match for in1.");
else if (c1==1'b0) $display ("No match for in1.");
else $display ("This should never execute.");
endmodule
```

The inside operator compares values from the value set against an expression to determine whether there is a match. In Example 2.9, the value of expression in1 is compared against each value in the set {2,4,6,8} in line 3 to compute the assignment value for c1.

A singular set consists of a list of individual values and ranges of values. For a range of values, each value in the range is considered as if it were specified as an individual value. This is shown in the example below.

```
module m1(input logic [3 : 0] in1, input logic clk);
logic c2;
assign c2 = in1 inside {[1:8], [12:15]};
//...
endmodule
```

in1 is compared against values 1–8 and 12–15.

Moreover, an unpacked array is allowed as a set member, in which case, the comparison is made over the constituent singular values of each element of the array as shown in the example below.

```
module m1(input logic [3 : 0] in1, input logic clk);
logic c3;
byte ar[4] = '{4,6,8,10};
assign c3 = in1 inside {2,ar};
//...
endmodule
```

Here, in1 is compared against the value 2 and each element of array ar, namely, 4, 6, 8, and 10.

The values in the value set do not need to be integral. For nonintegral values, the equality operator == is used, while for integral values the *wildcard equality* operator ==? is used for comparison. Keep in mind that the wildcard equality operator considers values x and z for a bit as don't care values when they appear in the value set, resulting in a match for the bit regardless of the value of the corresponding bit in the expression.

Example 2.10. inside operator on a value set containing x or z

```
module m2(input logic [3:0] in2, input logic clk);
logic c4;
assign c4 = in2 inside {4'b00X1, 4'b1100, 4'b100Z};
always @(posedge clk)
   if (c4 == 1'b1) $display("Match for in2.");
   else if (c4 == 1'b0) $display("No match for in2.");
   else $display("This should never execute.");
endmodule
```

Example 2.10 shows a value set with values x and z. Due to x in 4'b00X1 and z in 4'b100Z, the value set in line 3 is equivalent to

```
{4'b0001, 4'b0011, 4'b00X1, 4'b00Z1, 4'b1100, 4'b1001, 4'b100X, 4'b100Z}
```

After comparing the expression with a value from the value set bit by bit, the resulting comparison is 1'bx if the result of the comparison for any bit is 1'bx.

Example 2.11. inside operator on an expression containing X or Z

```
module m3(input logic[3:0] in3, input logic clk);
logic c5;
assign c5 = in3 inside {4'b00X1, 4'b1100, 4'b100Z};
always @(posedge clk)
   if (c5 == 1'b1) $display("Match for in3.");
   else if (c5 == 1'b0) $display("No match for in3.");
   else if (c5 === 1'bX) $display("x/z miscompare for in3.");
   else $display("This should never execute.");
endmodule
```

In Example 2.11, c5 will be 1'bx whenever there is a x or z in in3 and there is no *wildcard* 4-value match with any value from the value set.

In summary, the result of inside is calculated after comparing the expression with each value in the value set as follows:

- When there is a match with a value, the result of the inside is 1'b1.
- When there is no match, but the result for a comparison is 1'bX, then the result
 of inside is 1'bX.
- Otherwise, the result of the inside operator is 1'b0.

2.2.2 Implication and Equivalence Operators

Two new logical operators have been added to SystemVerilog: implication written as ->, and equivalence written as ->.

Example 2.12. Assertion using logical implication operator

```
a1: assert property (@(posedge clk) rdy -> !rst);
    else $error ("Reset must be low.");
```

Using the implication operator, the assert statement ensures that signal rst must be low when signal rdy is high. When rdy is low, rst can be low or high.

For the equivalence operator, both signals must be high or low at the same time.

Example 2.13. Assertion using logical equivalence operator

```
always @(posedge clk)
a22: assert property (@(posedge clk) b1 <-> b2));
    else $error("Mismatch between b1 and b2.");
```

In the equivalence operator used in a2, whenever b1 is true, b2 must be true, and vice versa. Similarly, if b1 is false, b2 must be false, and vice versa.

In essence, these operators are shortcuts for other logical expressions. The implication (e1 -> e2) is logically equivalent to (!e1 $| | e2 \rangle$, and the equivalence (e1 <-> e2) is logically equivalent to (e1 -> e2) & (e2 -> e1).

2.3 Extensions to Event Controls

Before we discuss clocking blocks, let us review changes to the event control feature. The event control specification has been made easier with two new constructs to simplify writing clocking event expressions: an event operator edge, and a qualifier iff.

The event operator posedge detects a change when a value changes toward 1, while negedge detects a change when a value changes toward 0. The new event operator edge is a disjunctive operation of the two, detecting a change when the value changes either toward 1 or 0. For example, edge shortens the expression always @(posedge clk or negedge clk) to always @(edge clk).

An event control can be made conditional by adding the new operator iff to the event control. This is useful for many cases, such as to express gated clocks, where the event occurs only under certain active signals.

```
always @(edge clk iff clkEnable)
```

Here, the clock is guarded by signal clkEnable and is effective only when signal clkEnable is high.

Using iff, the event control is able to express this directly in the above statement. A special form of a blocking statement is the wait statement, which delays execution until the wait condition becomes true. An example follows.

Example 2.14. wait condition

The difference between an event control and a wait statement is that the condition of the wait statement is level-sensitive. There is no event expressed with @ in the condition (c1 == 4 && c2 == 5) of the wait statement. The condition is just an expression which is evaluated any time the value of any of the variables in the expression changes. When the condition becomes true, the statement is unblocked and the statement proceeds to the next procedural statement. Otherwise, it continues to delay the execution of the next statement.

2.4 Clocking Blocks

Clocking specification is rather crucial to synchronous designs as well as to concurrent assertions. This importance is reflected by the introduction of a new construct referred to as *clocking block*. The primary purpose of this construct is twofold.

One is to provide a flexible scheme for synchronizing and sampling of signals with respect to a design clock. Often the input signals are driven from a test bench to design units, while the test bench is modeled by a *program*. New values to signals for a test are set in the test bench with appropriate delays using a clocking block.

The other one is to enclose property and sequence definitions in a clocking block, using the common event control of the clocking block. This assists in grouping related properties and sequences as well as it provides the convenience of leaving out the explicit specification of a clock for each individual declaration of a property or sequence in the clocking block.

For use of clocking blocks in test benches, readers are advised to refer to the SystemVerilog LRM. A clocking block is declared with

- A name
- An event expression
- Variables sampled and driven by the clocking block
- A list of sequences and properties

2.4 Clocking Blocks 41

The example below illustrates a simple use of a clocking block.

Example 2.15. A clocking block declaration

```
module mCheck;
  bit a,b,c;
  // ...
  clocking mCB @(posedge clk);
    input a, b, c;
    sequence s1;
     b ##[1:24] c;
    endsequence
    sequence s2;
      a ##3 c;
    endsequence
    sequence s3;
      s1 within s2;
    endsequence
    property p1;
      s1 or s2;
    endproperty
  endclocking
  a1: assert property(mCB.p1) else $error("a1 violation");
  a2: assert property(mCB.s3) else $error("a2 violation");
endmodule
```

In Example 2.15, a clocking block named mCB is declared with the clocking event @(posedge clk). Variables a, b, and c are used as inputs in the clocking block and they get sampled with the event expression. Sequences s1, s2, and s3 are declared within the clocking block and they use the same event expression for the clock as the clocking block. Likewise, property p1 is declared in the clocking block and uses sequences s1 and s2. It should be noted that a clocking block creates a scope, and all items declared within it fall under that scope. Therefore, assertion a1 refers to property p1 as mCB.p1. There is one restriction of importance on the declarations of properties and sequences: no explicit clock is allowed in the declarations. Consequently, multiply clocked properties or sequences cannot be declared inside clocking blocks.

Default Clocking

An alternate way to accomplish the same convenience of a common clock, but without the restrictions of confining the sequences and properties to a single clock is by using the clocking block as the default for the module as shown next.

Example 2.16. Using a default clocking

```
module mCheck;
bit a,b,c;
default clocking mCB @(posedge clk); endclocking
sequence s1;
b ##[1:24] c;
```

The clocking block declared as default becomes the implied clock for those declarations which omit the clock. If needed, a different clock can be explicitly specified. Also, now that we have a declared clocking block, it can be used as an event expression itself. Expression @ (mCB) is an event triggered by @ (posedge clk).

2.5 New Procedures

In addition to always and initial, four new procedures are provided.

- always_combalways_latchalways_ff
- final

always_comb, always_latch, and always_ff follow the same syntax as always.

```
always comb Procedure
```

Like the always @(*) phrase, always_comb is used to express combinational logic and automatically infers the sensitivity list for the procedure.

Example 2.17. An always comb procedure

```
module m2 (logic c, d, clk);
logic a, b;
always_comb begin :blk
   a = c & d;
   b = c | d;
   a1: assert (a -> b);
end
endmodule
```

2.5 New Procedures 43

The always_comb procedure in Example 2.17 infers the sensitivity list (c,d) and triggers each time c or d changes. There are some differences of significance between always comb and always @(*) constructs as listed below.

- always_comb executes unconditionally at time 0, while always @(*) waits for
 a change in the value of an element from the sensitivity list.
- The sensitivity list of always_comb includes elements of functions used in the procedure, while always @(*) includes only the arguments of function calls.
- Variables on the left-hand side of an assignment, either directly in always_comb or in any invoked function within it, cannot be assigned from any other procedure, while always @(*) allows such assignments from multiple processes.
- Statements of always_comb cannot be nonblocking, while there is no such restriction in always @(*).

always latch Procedure

always_latch is identical in behavior to always_comb. It is intended to directly state that the logic included in the procedure represents one or more hardware latches. Taking advantage of this statement, tools often check to ensure that the logic indeed synthesizes to latches only.

Example 2.18. An always_latch procedure

Conventionally, out1 is inferred as a latch by most tools (latching when in 1 > in 2), although its inference as such is not important for simulation.

always_ff Procedure

always_ff, like always_latch, also serves a similar purpose to directly represent synthesizable hardware. The logic contained within always_ff synthesizes to sequential logic, such as flip-flops and registers.

Example 2.19. An always ff procedure

П

Some restriction must be followed in the procedure, as noted below.

- always ff must contain one and only one event control.
- always_ff must not contain any blocking statement other than the one event control.
- Variables on the left-hand side of an assignment, either directly in always_ff or
 in any invoked function within it, cannot be assigned from any other procedure.

final Procedure

final procedure is the opposite of the initial procedure. It executes at the end of the simulation. Often it is used as a clean-up routine and for displaying or storing information such as simulation final results, statistics, and coverage data. The users can declare more than one final procedure, in which case, they are executed sequentially, but in an arbitrary order.² Effectively, the final procedures constitute a single process in which the procedures execute sequentially.

Example 2.20. A final procedure

```
int fCount = 0;
always @(posedge clk) rdy_fail:
assert (rdy -> !rst) else fCount++;
final begin : f1
    $display("Number of assertions rdy_fail failed: %d",fCount);
    $display("Last value of = %h", PC);
end
```

Assertion rdy_fail increments fCount each time it fails. At the end of simulation, final procedure f1 prints the total number of assertion rdy_fail failures. A number of restrictions are placed on the statements contained in the final procedure. The restrictions emanate from the requirement that a final procedure must execute in zero time. In particular, the following restrictions should be noted.

- The statements are limited to the kind of statements allowed in functions.
- The final procedure executes only once.
- No events can be scheduled from the procedure as the simulation immediately terminates after completing all final procedures.

2.6 Interfaces

A number of enhancements have been made to improve the specification of connectivity between modules. Modules, as we know, often represent design units. As the designs are getting bigger, so are the number of connections between modules. One

² SystemVerilog LRM suggests that the order of execution for **final** procedures be deterministic for a tool.

2.6 Interfaces 45

of the enhancements is to provide automatic connection of module instance ports. The name and size of a module instance port are matched against the name and the size of variables contained in the module where the instance is specified. If both the name and the size match, then the connection is made. This shortcut is called *implicit* port connections and is syntactically denoted as (.*).

Example 2.21. Using implicit port connections

```
module sum(input logic [3:0] data, ctrl,
           input logic [7:0] addr,
           input byte d1, d2, d3,
           output byte v1, v2, v3);
  always comb begin
    case( ctrl )
    2 : v1 = data + d1;
    4 : v2 = data + d2;
    default: v3 = data + d3;
    endcase
endmodule
module dataAdd();
  logic [7:0] addr;
  logic [3:0] data;
  logic [3:0] ctrl;
  byte d1, d2, d3;
  byte v1, v2, v3;
  sum sumi (.*);
  // ...
endmodule
```

Variables data, ctrl, addr, d1, d2, and d3 declared in module dataAdd are connected to the input ports of instance sumi with the same name. Similarly, variables v1, v2, and v3 are connected to the output ports of sumi.

П

For simpler cases, the implicit port connections method works very conveniently. Yet, one can easily foresee how this method loses its benefit when the signal names or sizes change. Besides, there is no way to encapsulate a group of related signals together and consider them as a single port.

A container construct interface, similar to module, defines signals and other entities. But unlike module, it can be passed via ports as a group. The above example is now modified by using interface to illustrate one of the basic motivations behind this feature.

Example 2.22. Using an interface

```
interface busSigs;
  logic [7:0] addr;
  logic [3:0] data;
  logic [3:0] ctrl;
  byte v1,v2,v3;
  byte d1,d2,d3;
  a1: assert #0 (v1 > v2 + v3);
endinterface
```

```
module sum(busSigs sig);
  always_comb begin
    case( sig.ctrl )
    2: sig.v1 = sig.data + sig.d1;
    4: sig.v2 = sig.data + sig.d2;
    default: sig.v3 = sig.data + sig.d3;
    endcase
    end
endmodule
module dataAdd();
    busSigs busI();
    sum sumi (busI);
    //...
endmodule
```

Now, all signals are bundled into interface bussigs, and simply the interface is connected to module sum by instance busI. Individual signals such as ctrl and addr from the interface are accessed directly from the interface instance.

One clear advantage of this encapsulation is that the individual signals are no longer tied to the module ports. Rather, related signals are syntactically represented as a group as well as passed as a group. The contents of an interface can change, such as the data width or even the number of control signals, without affecting the module port definitions. Surely, the final usage of the interface would need to be modified further in the design, but the changes do not percolate beyond where they are needed.

The contents of an interface are not limited to signals. In fact, it may contain most entities allowed in modules such as,

- Data types and variables
- Clocking blocks, functions and tasks
- initial, always, and final procedures to define additional behavior
- Sequences, properties, and assertions

The assertions in an interface can ensure that the behavior included in the interface is checked and this monitoring is encapsulated well within it. Assertion s1 in interface busSigs is one example of this usage.

Another common use is to form a core of assertions to monitor the relationships within a group of related input signals of an interface. The interface is instantiated with selected design signals, forming connections to the input signals of the interface, thereby applying assertions to different sets of signals. In a similar way, sequences and properties defined in an interface can be accessed and reused to configure assertions in various portions of the design.

Example 2.23. Assertions in an interface

2.7 Programs 47

```
a1: assert property (@(posedge clk) ctrl[0] -> !rst);
a2: assert property (@(posedge clk) $onehot(ctrl));
a3: assert property
        (@(posedge clk) ctrl[0] |=> $stable(data));
endinterface
module dataAdd();
logic [1:0][7:0] addr;
logic [1:0][3:0] data;
logic [1:0][3:0] ctrl;
logic clock, reset;
busCheck bus1(addr[0], data[0], ctrl[0], clock, reset);
busCheck bus2(addr[1], data[1], ctrl[1], clock, reset);
//...
endmodule
```

Other important features of interface which we do not discuss here are:

- modport that controls the directions of signals and their visibility to the environment where the interface is instantiated
- Importing and exporting functions and tasks using modport
- Exporting clocking blocks for synchronous signals
- Parameterizing interfaces for customization of the interface contents as done for modules
- Virtual interfaces to select and configure interfaces and their connections at runtime

2.7 Programs

SystemVerilog provides features to clearly separate the testbench code from the design code. Design code is conventionally expressed in modules and the hierarchy is built up from modules and its instances. As a counterpart to modules, programs are used for describing testbenches with the primary purpose of generating and sending stimuli to the design signals and receiving responses to validate the design behavior. The code within program is referred to as *program block*.

A simple example of a program is shown below.

Example 2.24. A program declaration

```
ctrl = $random % 256;
lastD = lastD +2;
data = lastD;
addr = lastA++;
end
end
end
end
endrogram
```

Program test sets values for ctrl, data, and addr for each clock cycle. The fundamental differentiating aspect of a program block is its order of execution in relation to the execution of code in a module. In the cycle of evaluation, the statements in modules are executed first (Active region), followed by the evaluation of assertions (Observed region), and finally the statements of a program block are executed. This is illustrated in Fig. 2.2 and explained in detail in Sect. 2.12.3.

By embodying a systematic scheme of ordered evaluation, the tightly coupled course of stimulus generation and response acknowledgment is made to work efficiently, and the hazards of races between the inputs and outputs of the program block are averted. Moreover, explicit delays and synchronization that were needed before are minimized because the order of execution is deterministic and predetermined.

The program construct resembles the module construct in its declaration of ports and body. A program can contain:

- Ports such as modules
- Data types, nets, and variables
- Class declarations
- Function and task declarations
- Sequences, properties, and assertions
- Covergroups
- Initial and final procedures
- Continuous assignments
- Generate statements

A notable exception is the exclusion of always procedures from this list.

2.8 \$Unit and \$Root

Generally, there are two phases of processing in building a simulation model from a given set of source files: compilation and elaboration. Compilation reads one or more source files, performs syntactic and semantic analysis, and stores an intermediate model ready for elaboration. The source files can be compiled all at once or divided into multiple sets of files so that each set can be compiled separately into what is known as a *compilation unit*.

To build the final simulation model, all compilation units together must go through the elaboration phase which binds all components by evaluating parameter 2.8 \$Unit and \$Root 49

values, connecting instances, building hierarchies, and resolving references. For noninterpretive simulators, another step is needed to create object code from the elaborated model to create the final executable simulation model.

In SystemVerilog, each separately compiled unit can have declarations outside any scope to create a global scope for that compilation unit. This global scope is denoted as <code>sunit</code>. A declaration in <code>sunit</code> space is visible to all scopes within that compilation unit but not to scopes in other compilation units. An identifier in <code>sunit</code> scope can be referenced directly without a hierarchical path. This is illustrated in the following example.

Example 2.25. Declarations of a sunit and modules

```
wire [1:0] out; // $unit
wire [1:0] in; // $unit

module topM;
   //basic gate instantiations
   and g1(out[0], in[0], in[1]);
   xnor g2(out[1],in[0], in[1]);
   main m1 ();
endmodule

module main;
   initial begin
    #0 in = 0;
    #20
    $finish();
end
   always #5 in++;
endmodule
```

Signals in and out are referenced in modules topM and main without using a hierarchical path. These signals from \$unit are directly visible to all modules.

Because \$unit is a scope, objects in it can also be referenced with a hierarchical path using \$unit as the top level scope. This is particularly useful when the name of an object from \$unit scope is shadowed by another local object of the same name in another scope.

In Example 2.26, a local version of signal in is declared in module main, which shadows signal in from \$unit. Using syntax \$unit::in, signal in from \$unit is explicitly referenced in the assign statement. Other references of signal in in main refer to the locally declared version of the signal. In module topM, signals in and out refer to signals from \$unit.

Example 2.26. A declaration shadowed by another declaration

```
wire [1:0] out; // $unit
wire [1:0] in; // $unit
//basic gate instantiations
module topM;
   and      g1(out[0], in[0], in[1]);
   xnor      g2(out[1],in[0], in[1]);
```

П

```
main m1 ();
endmodule
module main;
  reg [1:0] in;
  assign $unit::in = in;
  initial begin
    #0 in = 0;
    #20 $finish();
  end
  always #5 in++;
endmodule
```

Thus, we have seen that each compilation unit has a special \$unit scope. When compilation units are elaborated, the root of the design is denoted as \$root. To explicitly specify a top-down hierarchical path starting from a top level module, the hierarchical path can be prefixed with \$root, such as \$root.topMod.regA. Ordinarily this is superfluous, but there are special situations where there is a need to distinguish between upward and downward hierarchical paths.

2.9 Package

The construct package is intended for reuse of common declarations across compilation units. One can use packages as libraries of useful declarations, such as functions, tasks, properties, sequences, and checkers.

Example 2.27. A package declaration and its usage

```
package p1;
  typedef struct {
    int i; int r;
  } IntPair;
endpackage
module top;
  p1::IntPair a;
  initial begin
    a.i= 10; #5 a.r = 5;
  end
endmodule
```

A declaration from a package can be used as shown in Example 2.27. package p1 declares a type IntPair, which is used in module top to declare variable a. When the same declaration is needed multiple times, one can use the import feature which makes the declaration visible throughout the scope.

Example 2.28. Importing a declaration from a package

```
package p1;
  typedef struct {
   int i; int r;
  } IntPair;
```

2.9 Package 51

```
endpackage
module top;
  import p1::Intpair;
  IntPair a, b;
  initial begin
    a.i= 10;
    b.i = 15;
    #5 a.r = 5;
    b.r = 20;
  end
endmodule
```

Once IntPair is imported into module top, it can be referenced without the syntax ::. When many declarations are needed from a package, the wildcard import can be used to make all declarations of the package visible throughout the scope.

Example 2.29. Use of a wildcard import

```
package p1;
  typedef struct {
    int i;
    int r;
  } IntPair;
  function IntPair intPairAdd(IntPair a, IntPair b);
    intPairAdd.r = a.r + b.r;
    intPairAdd.i = a.i + b.i;
  endfunction
endpackage
module top;
  import p1::*;
  IntPair a, b, c;
  initial begin
    a.i = 10;
    b.i = 15;
    c = intPairAdd (a, b);
    #5 a.r = 5;
    b.r = 20;
    c = intPairAdd (a, b);
  end
endmodule
```

p1::* makes all declarations within package p1 available to module top.

While the package import feature provides considerable convenience, the name visibility of a package identifier can create a conflict with an identifier in the scope where the package is imported. There are many rules to disambiguate such conflicts. Among these rules, there are two basic rules to remember.

- If an identifier is visible prior to the source point of the import then,
 - for the wildcard import, the identifier with the same name from the package is not made visible
 - for an explicit identifier import, it is illegal to import an identifier with the same name

- If an identifier is visible after the source point of the import,
 - for the wildcard import, the identifier with the same name from the package is made visible
 - for an explicit identifier import, it is illegal to import an identifier with the same name

Some of the commonly used declarations in a package are:

- Types and classes
- Nets and variables
- Functions and tasks
- Sequences, properties, let declarations, and checkers
- Covergroups

A unique aspect of package usage is that the declarations are truly shared. Accordingly, for example, a package creates only one instance of a declared variable or a net, regardless of how many times a package is imported, and the same variable is referenced in each import.

Example 2.30. Using shared net declarations from a package

```
package common;
  logic [1:0] out;
  logic [1:0] in;
endpackage
module topM;
  import common::*;
        g1(out[0], in[0], in[1]);
 xnor g2(out[1],in[0], in[1]);
  main m1 ();
endmodule
module main:
  import common::*;
  initial begin #0 in = 0;
    #20 $finish();
  end
  always #5 in++;
  always @(out) $display("out value:%b",out);
endmodule
```

Package common declares variables for shared use in the design. Same copy of variables in and out are accessed in both modules topM and main.

A package provides a natural means to store a library of useful sequence and property definitions. Wherever needed, it is simply imported and assertions are built from the library definitions to suit the application.

2.10 Bind Statement

Frequently, there is a need to bring subordinate code into the main design code. The following are some of the prevailing reasons for using such subordinate code:

- Assertions
- Procedural verification code

2.10 Bind Statement 53

- Coverage related code
- A patch to fix a bug

The bind construct provides an orderly way to bring such code by instantiating a module, a program, an interface or a checker into the target code from outside the target. An example is shown below.

```
bind dataAdd busCheck firstCheck(.*);
```

An instance of buscheck named firstCheck is included in module dataAdd. The port connections are made according to the *implicit* connection rules in module dataAdd.

The purpose of the bind statement is to add code in a place without actually modifying that code where it is added. Customarily, once the design is implemented, the design code is maintained with rigor and discipline to minimize code changes. During the verification phase, either verification engineers or designers themselves add code for monitoring the behavior of the design. The bind statement is ideal for that purpose, as the monitoring code can be added or removed without affecting the design code. This method is nonintrusive and efficient.

Less frequently, code is also added to temporarily fix a bug in the design code, or work around a deficiency. Once proven to work correctly, the patch is removed and the design code is fixed by actually modifying the code to retain the modified behavior permanently.

The bind statement can appear either in a module, an interface or in a compilation-unit scope. It binds a source instance to one or more target instances. When the source instance is bound, it behaves as if it were instantiated in the target instance. Based on this premise, semantic correctness check of the bound instance is performed.

The source instance can be a module, interface, program, or a checker instance, while the target instance can be a module or an interface instance. More than one source instance can be bound to the same target instance.

The following example illustrates binding a checker to a module instance.

Example 2.31. Binding a checker instance to a module instance

```
for (int i = 7; i > 0; i++)
        tmp[i] <= tmp[i - 1];
   out <= tmp[7];
end
  //...
endmodule
checker delayProps(logic sig, dSig, clk);
  property sigWindow(s, so);
    s |-> ##[1:16] so;
endproperty;
al: assert property (@(posedge clk)sigWindow(sig, dSig));
  //...
endchecker
```

The following bind statement

```
bind trans: ta delayProps p1(req, out, clk);
```

binds instance p1 to instance ta. This is equivalent to instantiating p1 in ta with the arguments req, out, clk of p1 connected to req, out, and clk of ta, respectively.

Assertion at checks property sigWindow between req and out, without actually modifying module trans.

The bind statement

```
bind trans: tb delayProps p1(req, out, clk);
```

performs the same binding for instance tb. Another variation of syntax is provided for convenience when the same binding is needed for all instances of a module. Rather than specifying instance by instance of the target module, one can just specify a module as the target, in which case the source instance is bound to all instances of that module or interface. In the above case, the two bind statements could be replaced by

```
bind trans delayProps p1(req, out, clk);
```

Now, all instances of trans are bound with instance p1, as if instance p1 were syntactically placed in module trans. There is no limitation on how many bind statements can be specified. For example below, two bind statements bind two separate instances to the same target instance.

Example 2.32. Binding a checker instance to all instances of a module

```
checker sigProps(logic req, clk);
  property sigRep(s);
    s |-> ##[1:8] !s;
  endproperty;
  al: assert property (@(posedge clk)sigRep(req));
    //...
endchecker: sigProps

module top;
  logic mclk, sig, snda, outa;
  logic sndb, outb;
  //...
  trans ta(mclk, sig, snda, outa);
```

2.11 Generate Constructs 55

```
trans tb(mclk, sig, sndb, outb);
bind trans delayProps p1(req, out, clk);
bind trans sigProps p2(req, clk);
endmodule: top
```

In this example, another checker sigProps is bound to trans in addition to delayProps to check a different relationship.

2.11 Generate Constructs

A technique to replicate design descriptions is needed to alleviate mechanical duplication of code by hand.

Example 2.33. Replicated instances

It is easy to see that the above code is not only time consuming to write, but it also suffers from the risk of inadvertently leading into typing and other mistakes. The generate looping constructs provide a clean way to write such repetitive code, as shown below.

П

П

Example 2.34. Using generate for-loop

Four instances named blk[0].inst, blk[1].inst, blk[2].inst, and blk[3].inst are generated. Here, **for** is a generate loop construct which defines a generate scheme for repeating the body of the loop.

Construct for consists of

- Looping index declared as genvar.
- Looping control consisting of index initialization, looping end condition, looping assignment.
- Generate block representing the body of the loop.

The index used in the looping control must be an elaboration time constant, generally consisting of constant literals or parameters. Conventionally, the generate loop iterations are configured based on the elaboration-time parameters.

The looping scheme is processed during the elaboration phase to unroll the generate block as many times as the loop condition holds true. Each iteration of the loop creates an instance of the generate block. After processing, the generate loop is completely replaced by the unrolled code, leaving no looping code for run time execution.

The looping index must be declared as genvar. This declaration must exist prior to using the index and its use is confined within the body of the loop. Also, it is treated like a localparam and can only be used in places where a localparam can be used. A reference to the genvar index outside the loop is illegal.

Another generate scheme uses a conditional if clause. In this scheme, one of the alternative blocks gets selected, based on the condition.

Example 2.35. Using generate if-else statement

In Example 2.35, for width equal to 1 the statement

```
always\_comb y = in1;
```

is used. Similarly, for width equal to 8, statement

```
always comb y = in2;
```

is used. Otherwise, statement

```
always_comb y = in3;
```

is used.

Again, the condition of if must consist of elaboration time constants. At the elaboration time, the condition is evaluated, resulting in the selection of one of the alternative blocks. After elaboration, only the body of the selected block remains.

For more than one alternative blocks, a generate case statement is often used as shown below. Example 2.36 suggests an alternative implementation for Example 2.35.

2.11 Generate Constructs 57

Example 2.36. Using generate case statement

The generate block in both conditional and looping case can be named or left unnamed. The use of naming the block is that the contents of the block can be identified and referenced with the block name. For the case of looping generate block, the name of the generate block instance is tagged with the index, like an array. In contrast, the contents of an unnamed generate block cannot be referenced from the outside.

П

In any case, a generate block creates a scope. The references, when legal, to the contents must be made as hierarchical references following the normal scoping rules

For complex situations, generate constructs can be nested. There is no restriction on the depth of nesting.

The generate block can contain most of the description items, including assertions, properties, and sequences. Disallowed items are stand-alone blocks containing procedural statements.

Syntactically, the generate looping (for-loop) and conditional (if-else and case) constructs are similar to the corresponding procedural statements. What distinguishes one from the other is that a generate construct can only appear outside any procedural code, while a procedural statement can only appear inside procedural code.

Optionally, the generate code can be enclosed within generate - endgenerate keywords for clear demarcation from the rest of the code. An example of using generate - endgenerate is shown below.

Example 2.37. Enclosing generate by generate-endgenerate keywords

The generate feature can be used in modules, programs, interfaces, and checkers. They cannot appear inside any procedural code.

2.12 Simulation Semantics Overview

This section provides an overview of SystemVerilog simulation semantics. SystemVerilog supplies many constructs to fulfill designer and testbench writer requirements for reducing the time to write tests and catching bugs early on in the design cycle. These constructs do not exist in isolation. While one can see the operations of individual constructs, understanding the interactions between the constructs is rather complex. In particular, the order in which the activities must take place is the crux of event semantics underlying the operational semantics of the language constructs.

We can see the necessity of ordering events from the following simple example.

Example 2.38. An example showing the order of execution of statements

```
module procReq(logic req, preGrant, grant, clk);
     logic allow;
2
    wire ctr, proceed;
3
     assign ctr = allow && preGrant;
4
     assign proceed = ctr && grant;
5
     always @(posedge clk) begin
6
        allow <= req;
8
     always @(posedge proceed) begin
9
        processTh();
10
     end
11
   endmodule :procReq
```

Assuming that input clk transitions from 0 to 1 and no other input changes at that time, the correct order of evaluation is:

- 1. assignment to allow in line 7
- 2. assignment to ctr in line 4
- 3. assignment to proceed in line 5
- 4. evaluation of processTh if proceed becomes true in line 10

As we will see in this section, this order of evaluation is obtained by creating events, scheduling events, and performing the computation directed by the scheduled events, all carried out in the order established by the semantic framework to obtain the intended result. The parallelism between the continuous statements and always statements in this example is broken down into ordered discrete events. Thus, in this case, the parallelism is unrolled into a sequential order as directed by the occurrence of events. In other cases, true parallelism may exist between statements, allowing indeterminate order of statement execution and values of variables.

In this section, we review the structure of event ordering, the event regions, the interactions between the execution of statements, and finally, the progression of time through this orderly management of events. Our interest is on the evaluation of assertion constructs as it unfolds over the event semantic structure by stepping through the regions, with often its own order within the regions. Nonetheless, assertion evaluation is tightly integrated with the rest of the language semantics, which dictates a broader discussion of the semantic framework to cover full semantics of assertions. We cover simulation semantics of other language features as needed for a frame of reference to complete the discussion on semantics of assertions. We predominantly make use of queues to explain scheduling and ordering.

Another important facet of SystemVerilog is Programming Language Interface (PLI) (or its newer version VPI) which provides an interface from the evaluation of language constructs to the external environment using other programming languages or scripts. The interface is used to inspect values, change values or get callbacks. There are certain points in the semantic structure where specific groups of VPI functions are allowed to take place. We, however, do not delve into the details of that allotment. The rest of the semantics are largely unaffected by its exclusion.

2.12.1 The Simulation Engine

There are two types of principal activities that help explain the event-driven simulation engine: *update event* and *evaluation event*. We call them *semantic events* to distinguish them from the **event** construct in SystemVerilog which is a data type used to name and trigger events.

An update event occurs whenever there is a change in the value of a variable. In Example 2.38, the nonblocking assignment

```
allow <= req;
```

causes an update event if the value of variable allow changes as a result of the assignment. The update event may trigger other activities and events dependent on the change in value.

There are many language constructs whose execution is tied to the occurrence of update events. The continuous assign statement in Example 2.38

```
assign ctr = allow && preGrant;
```

is may execute only when either the update event on allow or preGrant occurs. Similarly, the always statement in Example 2.38

```
always @(posedge clk) begin
  allow <= req;
end</pre>
```

is executed when the event (posedge clk) occurs.

However, the execution of a statement may not materialize immediately, but is scheduled as an evaluation event in a queue within a region for execution, based on the type of the statement and its surrounding context. By scheduling evaluation

events in various queues and by executing them later from the queues, the intended order between statements is accomplished. The execution of an evaluation event can result in further update events or evaluation events which are again scheduled. For instance, when the evaluation event for the always statement

```
always @(posedge clk) begin
  allow <= req;
end</pre>
```

is executed, an evaluation event for the nonblocking assignment

```
allow <= req;
```

emerges and gets scheduled. When this evaluation event for the nonblocking assignment is executed, an update event for variable allow is issued, assuming the value of allow changes as a result of the assignment. The creation and execution of these semantic events, together with their scheduling in queues is what keeps the simulation engine running. As long as there are scheduling events left to process, the engine keeps executing statements and progresses through time. The simulation ends only when there are no more semantic events left in the queues.

2.12.2 Bringing Order to Events

Now, we can see the important role of queues in the assembly of discordant events into a predictable simulation execution model.³ First, we focus on the execution of statements specified in the context of design code, rather than assertions or programs that represent test bench code. Semantic events issued from the design code are grouped in a *region* called the Active region. We elaborate upon the notion of a region, including the Active region and other regions, in the next section. For now, we limit our discussion to the activities within the queues of the Active region.

The queues represented in Fig. 2.1 belong to the Active region. There are three principal queues in this region: Active queue, Inactive queue and NBA queue.

As the name suggests, the Active queue contains semantic events pending for immediate execution. Events in this queue may be executed in any order, implying parallelism between events. The code must be written carefully as the indeterminate order of execution can cause unintended effects if the code contains interdependency of the variable value changes in the Active queue. After an event from the queue is executed, such as updating a variable value, it is removed from the queue. Initially at time 0, the initial processes are scheduled in the Active queue. If a statement is encountered with #0 as the delay control, an evaluation event for the statement is

³ Here, we deviate from the terminology used in the SystemVerilog LRM. In the LRM, a time slot is divided into regions and some regions are grouped to form a *region set*. We prefer to call regions within a region set as queues, and collapse a region set as simply a region. For example, we call the Active region set as the Active region, while its subregions Active region, Inactive region and NBA region are called Active queue, Inactive queue and NBA queue, respectively.




Fig. 2.1 The Active region

entered into the Inactive queue. When all events from the Active queue are executed with the queue being empty, the events from the Inactive queue are transferred to the Active queue, resulting in an empty Inactive queue. The execution of the events from the Active queue resumes once again.

Finally, if the execution encounters a nonblocking assignment, the expression on the right-hand side of the assignment is evaluated and an update event for the variable on the left-hand side with the computed value is appended to the NBA queue. The events from this queue start execution only when the Active and Inactive queues are empty. Unlike the Active queue, the events in the NBA queue are executed in the same order as they are entered in the queue. Therefore, the sequential order of nonblocking assignments in a procedure is replicated in the queue and those statements are executed in order.

Ordinarily, non-blocking assignments model register transfer statements triggered by the clock derived from its enclosing always procedure. As a result, the register stores the new value and propagates the value. If there is a combinational logic driven by the register, its value is further propagated by the new update event entered in the Active queue.

Algorithmically, the following steps are taken.

 Execute semantic events from the Active queue. New semantic events may be issued and entered in the appropriate queues. Execute until all events are consumed.

- 2. Transfer events from the Inactive queue to the Active queue and return to step 1. Skip this step if there are no events in the Inactive queue.
- 3. Execute events from the NBA queue. New update events issued from this execution are entered in the Active queue. Return to step 1.

The above algorithm is iterated until there are no more events left in any queue in the current time.

2.12.3 Carving Safe Regions

The event queues Active, Inactive and NBA are all confined to the Active region. The execution iterates over the queues in a region until all events scheduled in any of its queues are executed. Certain events, however, may be scheduled in the other regions.

The processing of events is sequentially ordered into distinct regions, where each region schedules, manages and executes events that are scheduled in the region. The processing proceeds from one region to the next and can iterate until no further processing is needed in any region for the given time-step.

We discuss the role of the following regions. Other regions are not important for the understanding of assertion semantics.

- 1. Preponed region
- 2. Active region
- 3. Observed region
- 4. Reactive region
- 5. Postponed region

The processing of regions also takes place in the order as shown above.

One region differs from another because of the kind of events that are handled by it. As we saw in the previous section, the Active region handles events from the design code. A procedural assertion is scheduled in the Observed region when the point of execution reaches that statement in the Active region. An update event on the port connection to a program schedules an update event in the Reactive region. Nevertheless, events scheduled in other regions cannot be executed from a region, which is currently being processed. This makes a region safe from execution interference of statements that belong to a semantically different region.

The Preponed region is a precursor to the time slot, where only the sampling of data values takes place. No value changes or events occur in this region. On the contrary, the postponed region is the tail end of the time slot meant for finishing simulation tasks that do not include value changes or events. Both of these regions are entered only once. Effectively, sampled values of signals do not change through the time slot.

There are two more important regions in the simulation engine to support SystemVerilog features: the Observed region and the Reactive region.

The Observed region is meant for the evaluation of sequences, properties, assertions, and checker code. Values that are not local to a property or a sequence remain constant during the Observed region. The evaluation mechanism and the queues that reside in this region are quite different than in Active region. Nevertheless, events do get scheduled into the Active and Reactive regions.

The Reactive region executes statements from programs. Programs are intended for writing testbenches, as external environments for designs, feeding stimulus, observing results from the stimulus and building tests to exercise the design. This region is a mirror image of the Active region, with similar events, queues and statement execution to the Active region. The corresponding queues are called Reactive queue, Re-Inactive queue, and Re-NBA queue. This region can also schedule events to the Active region, but does not execute events in the Active region.

The simulation engine processes one region at a time, and transitions from one region to the next only after exhausting events and evaluations in a region. The order of the movement between the regions is fixed as follows: Active region, Observed region, and Reactive region. The iterative motion between the regions continues until there are no more events or evaluation tasks left in any region. The regions and their order are depicted in Fig. 2.2.

The simulation engine iterates over the Active, Observed, and Reactive regions.

The example below illustrates how three regions are involved in executing statements.

Example 2.39. Simulation using the three regions

```
module procReq();
  wire req, preGrant, grant, clk;
  logic allow;
  wire ctr, proceed;
  assign ctr = allow && preGrant;
  assign proceed = ctr && grant;
  always @(posedge clk) begin: blk1
    allow <= req;</pre>
  end
  always @(posedge proceed) begin: blk2
    processTh();
  end
  al: assert property (@(posedge clk) (grant -> preGrant));
  test t1(req, preGrant, grant, clk);
endmodule : procReq
program test(output logic rW, pgW, gW, clkW);
  logic rR, pgR, gR, clkR;
  assign rW = rR;
  assign pgW = pgR;
  assign gW = gR;
  assign clkW = clkR;
  initial begin
```




Fig. 2.2 Three main regions

```
rR = 1;
#10;
pgR = 1;
#10;
clkR = 1; gR = 1;
end
endprogram
```

At time 0, the continuous assignments are evaluated once to propagate the initial values by scheduling update events in the Active region. The default values of rR, pgR, gR, and clkR are assigned to rW, pgW, gW, and clkW respectively. These values then propagate via ports to req, preGrant, grant, and clk. The clock clk, however, does not trigger, so there is no activity in the Observed region. In the Reactive region, rR gets assigned to 1 which causes an update event to assign rR to rW. Likewise, rW causes an update event for the port connection to req. There are no other events due to program statements. Signal req does not cause any event in module procReq.

At time 10, the state of the Active and Observed regions is unchanged. pgR gets assigned to 1 in the Reactive region, issuing an update event to assign to pgW and

its port connection preGrant. The new value of preGrant does not change the resulting value of allow && preGrant, so no new update events are scheduled in the Active region.

At time 20, clkR is assigned, followed by an assignment to clkW as an update event in the Reactive queue, and correspondingly its port connection to clk. This update event to clk results in scheduling an evaluation event for always procedure blk1 in the Active queue of the Active region. Similarly, assignment gR propagates to grant via an update event. As a result of the clock clk change, assertion al gets scheduled in the Observed region.

After the completion of the Reactive region, the simulation enters the Active region. Here, the execution of blk1 from the Active queue sets an update event to set the value of allow to 1 in the NBA queue. After iterating over the NBA queue, the Active queue is iterated again due to the continuous assignment to proceed to 1. Block blk2 gets executed, invoking task processTh. The Active region queues at this time are empty, so the control moves to the Observed region, where assertion al gets evaluated.

Simulation keeps running until there are no more semantic events to execute.

2.12.4 A Time Slot and The Movement of Time

In Example 2.39, we noted that the events get scheduled at different times, such as at time 10 and time 20. Each event is associated with a simulation time, which is the time maintained by the simulator to account for the delays in the design. Without the delays in the design, the simulation time will not advance and all events will occur at time 0.

The time delays in the system are specified with a scale and a precision. Nonetheless, time is discrete and there exists a global time precision which is the smallest unit of time in the system being simulated. *1step* denotes the smallest time precision.

```
Example 2.40.
module m1();
   timeunit lns;
   timeprecision 10ps;
   //...
endmodule
module m2();
   timeunit lns;
   timeprecision lps;
   //...
endmodule
```

In this example, the smallest unit of time(one step) is 1ps. The same time unit and precision can also be specified by the timescale compiler directive.

For the purpose of event semantics, a single step is referred to as a *time slot*. We have seen how the event queues and the regions establish the order of processing within a time slot. The time within a time slot remains constant, and thus, all events scheduled within a time slot refer to the same time. When all events are processed for a time slot, the simulation control moves to the nearest time slot containing scheduled events.

The step denotes the smallest time-step. A single step is referred to as a time slot.

Let us review how an event is scheduled for a time slot associated with a future time. The program portion from Example 2.39 is shown below.

When the execution reaches the statement,

```
#10;
```

an evaluation event is scheduled for a future time slot. Let us assume that the time for the time slot is t. The rest of the initial block gets scheduled at time t_1 equal to t plus 10 in the Reactive queue of the Reactive region. The statements scheduled for time t_1 are as follows.

```
pgR = 1;
#10;
clkR = 1;
gR = 1;
```

When the simulation control transitions to time t_1 , the scheduled event from the Reactive queue is executed. After executing statement,

```
pgR = 1;
```




Fig. 2.3 Scheduling for future time slots

another future evaluation event is scheduled in the Reactive queue of the Reactive region at time $t_2 = t_1 + 10$, with the following statements.

```
clkR = 1;
gR = 1;
```

In effect, Fig. 2.3 illustrates the initial state of scheduled events in the queues at the beginning of each time slot.

The events in the Reactive queue, as they execute, give rise to other events, scheduled in the Active queue of the Active region, thereby creating an order in accordance with the semantics of the statements.

The time advances only when the events of the current time slot are exhausted.

We briefly review the impact of assignments on scheduling events.

- A continuous assignment schedules an update event in the Active queue to update
 the value of its left-hand side, whenever there is a change in the right-hand side
 expression value.
- A blocking assignment without a delay executes immediately, and issues update events for statements dependent on the new value of the left-hand side. An assignment with 0 intra-assignment delay computes the right-hand side and schedules an evaluation event in the Inactive queue to make the assignment, issue other update events if necessary, and continue the sequential execution from that statement. For a greater delay, it schedules like for 0 delay in the Active queue for the future time.

A nonblocking assignment schedules an update event in the NBA queue to update
the left-hand side based on the current value of the right-hand side. For a delayed
statement, it schedules the event for a future time in the NBA queue based on the
delay.

These rules apply to the Active and Reactive regions in their corresponding queues. In the Observed region, only certain special statements are executed. Largely, the evaluation of the assertion is carried out without the need of the queues used in other regions. Chapters 3 and 14 discuss assertion simulation semantics in more detail.

Part II Assertions

Chapter 3 Assertion Statements

Language is a mixture of statement and evocation.

- Elizabeth Bowen

In this chapter, we describe SVA assertion statements:1

- Assert statements
- Assume statements
- · Restrict statements
- Cover statements

The term *assertion* is overloaded in SVA; in a narrower sense it means an assert statement, and in a broader sense it means any assertion statement listed above. In this chapter, we use the term assertion in its narrow meaning. We indicate the meaning explicitly when it is not clear from the context.

Assertions, assumptions, and cover statements may be of any assertion kind: immediate, deferred, and concurrent. Restrictions may only be concurrent.


For convenience, we briefly recapitulate main results of Sect. 1.4, how different kinds of assertion statements are checked in simulation and in formal verification. We then describe basic simulation semantics for different kinds of assertion statements. Their understanding is important to correctly choose the kind of assertions in each particular case. Knowing principles of assertion simulation is also important to correctly interpret simulation results on traces and waveform diagrams. The simulation semantics for concurrent assertions outside procedures is discussed in Sect. 3.4.6 and for procedural assertions in Sect. 14.5.

3.1 Assertion Kinds

Conventionally, the code representing the hardware design as the object of verification is called *Device Under Test* (DUT), while the testbench and other supplementary code is called *environment*, as shown in Fig. 3.1. For example, a CPU as a DUT

¹ In SVA, there is also **expect** statement used mostly in testbenches, but we do not describe it in this book.

Fig. 3.1 DUT and its environment



could have an environment consisting of a program generating the stimuli, a chipset model and a memory model.

Assertions specify the desired behavior of DUT for checking. Black-box assertions specify relationships between DUT inputs i_1, \ldots, i_m and DUT outputs o_1, \ldots, o_m , while white-box assertions specify relationships between internal signals.

As we mentioned in Sect. 1.3, in SystemVerilog there are three kinds of assertions:

- Immediate
- Deferred
- Concurrent

Assertions have the following syntax.

assertion ::= name : assert_keyword (assertion_body) action_block

The syntax for different types and kinds of assertions differs only by the keyword. assert_keyword is assert for immediate assertions, assert #0 for deferred assertions, and assert property for concurrent assertions. assertion_body is a non-temporal expression for immediate and deferred assertions, and a temporal expression for concurrent assertions. An action block contains code to be performed in case of assertion success (pass action) and failure (fail action). Both pass and fail actions of immediate and concurrent assertions (but not deferred) may be blocks with several statements each. If no fail action is specified with an assertion, an \$error system task is called with a default tool specific error message. Although assertion name is optional, it is highly recommended to always specify it. The significance of the name is that it gets reported by simulators, FV and debug tools. If an assertion name is omitted, verification tools assign a tool-specific name to the assertion.

Always specify assertion names.

3.2 Immediate Assertions

Immediate assertions are the simplest kind of assertions. These assertions are Boolean and unclocked, and they tightly follow the simulation flow. Immediate assertions may be placed only in procedural code.

3.2 Immediate Assertions 73

3.2.1 Immediate Assertion Simulation

Immediate assertions are akin to other procedural statements and behave like procedural if statements. The assertion condition is evaluated each time the control flow reaches the assertion. The evaluation is performed immediately with the values taken at that moment for the assertion condition variables. If the assertion condition is true, that is, it has a nonzero known value, the pass action is executed; otherwise, when the condition is false, that is, it has a zero value, or its value is x or z, the fail action is executed. Since the assertion condition is nontemporal, its execution computes and reports the assertion results at the same time. Also, the execution of the associated action block is scheduled in the Active queue of the region in which it executes.

The semantic region in which immediate assertions execute depends on where these assertions are placed in the source code. From the definition of an immediate assertion, it follows that normally in modules and in interfaces, the immediate assertions and their action blocks are executed in the Active region. In programs, they are executed in the Reactive region (Sect. 2.12.1). Immediate assertions are not allowed (Chap. 21) in checkers.

Figure 3.2 contains an example of immediate assertion a1, and the corresponding timing diagram for the values of its expression variables is shown in Fig. 3.3. Recall (Sect. 2.5) that the always_comb procedure executes unconditionally at time 0, and note that at time 0 both a and b have the value 1'b0. Therefore, the pass action is executed at time 0. The pass action increments counter al_success and prints a message a1: a and b have value 0. Because always_comb is sensitive to the arguments of assertion a1, each time the value of either a or b changes, a reevaluation of the assertion condition is prompted, followed by the execution of the appropriate action block. Thus, the pass action is executed at time 50, 150, and 190, while the fail action block is executed at 90.

In practice, the pass action of assertions is seldom used as assertions are expected to succeed. The success information may provide confidence in the beginning, but

```
always_comb begin
// ...
al: assert (a == b) begin
    al_success++;
    $info("al: a and b have value %b", a);
end
else begin
    al_failure++;
    $error("al failure: a = %b, b = %b", a, b);
end
end
```

Fig. 3.2 Immediate assertion




Fig. 3.3 Timing diagram for assertion a1

quickly becomes superfluous during the normal course of the development. The most common way is to specify only a fail action to issue an error message:

```
a1: assert (a == b)
else $error("a1 failure: a = %b, b = %b", a, b);
```

3.2.2 Simulation Glitches

The code in Fig. 3.2 is not as straightforward as it looks; the way variables a and b get their values greatly affects the behavior of assertion a1. Let us modify this code by explicitly specifying the assignments of a and b. The resulting code is shown in Fig. 3.4 where we deleted the assertion action blocks for convenience.

In this case, the continuous assignments and assertion all are executed in three separate processes: each continuous assignment is a separate process by itself and assertion all executes in the scope of always_comb. We had to place assertion all there, as immediate assertions are allowed only in procedural code. Consider the assertion behavior at time 50. SystemVerilog does not impose any predefined order of process execution for parallel processes such as the ones in this example, so let us assume the following order:

- Line 1 is executed. a is assigned the value 1, b is still keeping its old value 0.
- Line 3 is executed. Because a and b at this point have different values, assertion at fails, and an error message is issued.
- Line 2 is executed. b is assigned the value 1.
- Line 3 is executed again. Now the assertion passes, and no message is issued.

As a result, the user will think that the assertion failed at time 50, though essentially it passed, and its failure was just a simulation glitch. Had we assume a different simulation order (line 1, line 2, and line 3), no assertion failure would be reported.

This example clearly shows that, due to their vulnerability to 0-delay simulation glitches, using immediate assertions may be problematic. So, when should immediate assertions be used? From their simulation semantics it follows that they should be used in the following cases:

• Debugging simulation results by traversing the simulation flow and detecting situations such as glitches. However, as we pointed out earlier, immediate assertions

3.3 Deferred Assertions 75

```
assign a = ...;
assign b = ...;
always_comb a1: assert (a == b);
```

Fig. 3.4 Glitch in immediate assertion

may only discover glitches when they manifest in simulation, and not the real glitches in the circuit.

- When delay controls are specified that make the code impervious to glitches.
- In program testbenches which observe only the stable values of design variables because programs execute in the Reactive region.

In all other cases, we recommend to use deferred assertions.

Immediate assertions are sensitive to simulation glitches. Use them only when you need to follow exactly the simulation flow, in program-based testbenches, or when your code contains delay controls. In all other cases, when unclocked Boolean assertions are required, use deferred assertions.

3.3 Deferred Assertions

The official name of deferred assertions is "deferred immediate assertions" since they are a variant of immediate assertions. However, we will call them simply "deferred assertions", reserving the name "immediate assertions" for immediate assertions that are not deferred.

Deferred assertions are unclocked Boolean assertions, and they differ from immediate assertions in the following ways:

- Deferred assertions have a keyword assert #0.
- Deferred assertions are not sensitive to simulation glitches.
- Deferred assertions may be placed both inside and outside procedural code.
- Action blocks of deferred assertions execute in the Reactive region.
- An action block of a deferred assertion may only be a subroutine call.

3.3.1 Deferred Assertion Simulation

Deferred assertions evaluate like immediate assertions, but the results are tentative, contingent upon possible reexecution of the same assertion in the same region of the time slot. This can happen, for example in Fig. 3.4 when the enclosing process of an assertion is sensitive to variables with values that fluctuate before they stabilize in the Active region.

The reporting of deferred assertions is delayed (hence their name), and the deferred assertion actions are placed into a *deferred assertion report queue*.

When a process in which a deferred assertion exists retriggers in the same region, the results of the assertion, in contrast to immediate assertions, are not reported immediately. But, instead, they are scheduled in the Observed region in the deferred assertion report queue, pending further determination. If the process retriggers in the same course of the Active region, i.e, before the Observed region is reached, the previous result of the assertion is *flushed* from the deferred assertion report queue. Therefore, the simulation control in the Observed region sees at most one copy of the result of the assertion, which is then said to *mature*. The result or alternatively, the action block subroutine of the matured entry is then scheduled in the Re-active queue of the Reactive region and executed in that region.

Let us recall that a deferred assertion is evaluated as a result of a process execution control reaching the location of the assertion. This linkage of an assertion with the process is essential when determining whether to flush the assertion from the deferred assertion report queue. A retriggering of a process causes only those previous entries of the assertion results to be flushed that are linked with the process. To explain this, consider a function containing a deferred assertion. The function can be invoked from two different processes in the same time slot, resulting in a separate entry in the deferred assertion report queue for each process, but for the same assertion. Flushing an entry, if it occurs later, is determined according to the process which initiates the flushing.

Example 3.1. Let us revisit the example in Fig. 3.4 by replacing the immediate assertion with the deferred one, as shown in Fig. 3.5.

Consider what happens at time 50 for the same simulation order as described in Sect. 3.2.2.

Active region:

- Line 1 is executed. a is assigned the value 1, b is still keeping its old value 0.
- Line 3 is executed. Since a and b at this point have different values, the fail action entry of the assertion a2 is placed into the deferred assertion report queue.
- Line 2 is executed and b is assigned the value 1.
- Line 3 is executed again. The previous fail action entry of this assertion is removed from the deferred assertion report queue, and the success action entry is placed there instead. As the success action is void, effectively only the success result is placed into the entry.

```
assign a = ...;
assign b = ...;
always_comb a2: assert #0 (a == b);
```

Fig. 3.5 Deferred assertion

3.3 Deferred Assertions 77

Observed region: The deferred assertion report queue entry matures.

Reactive region: All actions from the deferred assertion report queue are executed. Since in our case the queue entry is without an action block, no actions are executed. A tool may, however, choose to report a success result for a2.

As we can see, in spite of a glitch in simulation, this glitch does not affect the behavior of deferred assertion a2.

The above example illustrates one case of flushing the results of deferred assertions. There are other circumstances where the act of flushing is also needed. In all, flushing should be perceived as unconditional when its enclosing process encounters one of the following situations.

- Process, which is previously suspended due to a wait statement or an event control, resumes after its wait statement or event control is enabled.
- Process is retriggered due to a value change of a variable in its sensitivity list.
- Process is explicitly disabled using the disable statement.

Since the deferred assertions are glitch-free, they are the preferable way to express unclocked Boolean assertions in RTL. However, when the code has event controls, the behavior of deferred assertions becomes nonintuitive, and it may result in missed failure reporting.

Do not use deferred assertions when the code has delay controls. Use immediate assertions instead.

3.3.2 Deferred Assertion Actions

The complex bookkeeping of deferred assertions explains the restriction imposed on their actions that they may consist only of a single subroutine call. A subroutine in SystemVerilog can be either a task or a function.

Example 3.2. The following deferred assertions are legal:

```
dal: assert #0 (a == b)
  else $error("p1 failure: a = %b, b = %b", a, b);
da2: assert #0 (a == b) $info("a and b have value %b", a);
da3: assert #0 (a == b) $info("a and b have value %b", a);
  else $error("da3 failure: a = %b, b = %b", a, b);
da4: assert #0 (a == b);
```

The following deferred assertions are *illegal*, as their fail actions contain either more than one statement, or are not a subroutine call:

```
da5: assert #0 (a == b) else begin
  ctr++; $error("p1 failure: a = %b, b = %b", a, b); end
```

```
da6: assert #0 (a == b) else ctr++;
da7: assert #0 (a == b) else begin
  $error("da7 failure: a = %b, b = %b", a, b); end
```

Delayed execution of deferred assertions puts forth a question about which values of the subroutine arguments are used during action execution. The answer is twofold:

- If a subroutine argument is passed by value, the argument value is used at the instant when the deferred assertion expression is evaluated.
- If a subroutine argument is passed by reference, the argument value from the Reactive region is used.

Since system tasks \$display, \$error, etc. pass their arguments by reference, it means that when these tasks are used with deferred assertions, the argument values from the Reactive region are printed. Although these values in the Reactive region may differ from the values used during the deferred assertion expression evaluation, in practice variables representing actual design signals remain the same, and the deferred assertion reporting works as expected.

3.3.3 Standalone Deferred Assertions

Unlike immediate assertions, deferred assertions may also be placed outside procedural code. In such cases, a deferred assertion is semantically treated as if the assertion were enclosed within an always comb procedure.

Example 3.3. The code from Fig. 3.5 may be equivalently rewritten as

```
assign a = ...;
assign b = ...;
a2: assert #0 (a == b);
```

Explicit always comb statement in Fig. 3.5 is redundant.

This feature of deferred assertions makes their usage more intuitive and convenient.

3.4 Concurrent Assertions

Concurrent assertions have the same format as the immediate ones – their action blocks are not limited to subroutine calls and may contain any statements, but their body has a more complex structure:

```
concurrent_assertion_body ::=
   [clocking_event] [ disable iff (reset) ] property
```

Here, the square brackets are not part of the syntax, they show that the corresponding constructs are optional.

3.4 Concurrent Assertions 79

Example 3.4. The following concurrent assertion

```
a1: assert property (@(posedge clk)
  disable iff (rst) a |-> nexttime[2] b);
```

is controlled by clocking event posedge clk and has a reset rst. The assertion property is a |-> nexttime[2] b.

Concurrent assertions can be placed:

- 1. in always procedures
- 2. in initial procedures
- 3. standalone (also called static) outside any procedure

For an assertion placed in either of the two procedures, it gets evaluated only when the control point reaches the assertion statement. Commonly, an assertion is placed in an initial procedure with the intention of evaluating the assertion only once. For example, assertion at checks that ready is low at the first tick of the clock:

```
initial a2: assert property (@(posedge clk) !ready);
```

In other cases, the assertion is monitored continuously: at each tick of its clock. For example, assertion a3 checks that ok is high at every tick of the clock:

```
a3: assert property (@(posedge clk) ok);
```

Or, an assertion monitored continuously can be placed in an always procedure as:

```
always @(posedge clk) begin
  d1 <= i1 | i2 ;
  a4: assert property (d1 |=> i3 | i4);
  dout <= f_ecap(d1);
end</pre>
```

Procedural assertions embedded in always procedures are discussed in detail in Chap. 14.

Assertions can be viewed as an observer machine that produces pass/fail output. This would be the case when assertions are included as part of the design in emulation or in formal verification. In simulation, however, a different view can be taken that is more suited for understanding the assertion behavior and debugging. In this view, an assertion is considered as a machine that issues an evaluation attempt or transaction at every tick of the leading clock of the assertion (while it is enabled) and ends by its success or failure. Each such transaction thus has a certain duration in time and can be controlled and analyzed separately from other such evaluation attempts. This chapter discusses this attempt-based view of assertion evaluation in simulation and examines efficiency issues connected with this view.

3.4.1 Simulation Evaluation Attempt

To explain the notion of a simulation attempt, let us consider the following simple assertion. We assume that default clocking has been defined, hence unless explicitly stated the clock is omitted from the examples.

a1: assert property(a ##1 b);

In simulation, the assertion will observe the values of signals a and b starting at every tick of the clock. Thus, at clock tick t the evaluation of a is performed, and if the result is true, it is followed by the evaluation of b at the next tick, t+1. If either a=0 at t or b=0 is true at t+1, the evaluation starting at t fails at time t or time t+1 respectively. However, if both a=1 at t and b=1 at t+1 are true, then the evaluation that started at t succeeds at t+1. An evaluation starting at clock tick t is independent of the evaluations starting at all other clock ticks. Consequently, the evaluation result of the attempt at t is independent of the results of attempts at all other clock ticks, and is thus called an *evaluation attempt* (starting at tick t).

Each such attempt has a start time corresponding to the simulation time of the leading clock tick, and an end time corresponding to the time of the clock tick at which the evaluation attempt either succeeds or fails. Furthermore, several attempts starting at different times may be under evaluation at the same time in a sort of pipeline fashion. For instance in our simple example, if a and b were true for several clock ticks, there would be two concurrent attempts. If the sequence definition spanned more than 2 cycles, more than 2 attempts could independently be evaluated at the same time.

An evaluation attempt has a start time and an end time. More than one attempt may be in flight at the same time.

If an assertion is always enabled, then there will be a series of evaluation attempts, starting at every tick of the leading clock. This is the case when the assertion is placed outside any procedure. However, if it is placed in an always procedure, then the start of an attempt is also controlled by the execution of the body of the always procedure reaching the position of the assertion. Furthermore, if an assertion is placed in an initial procedure, there will be only one evaluation attempt starting at the first tick of the leading clock.

We can thus see that a concurrent assertion outside a procedure will execute "always", inside an initial procedure it will execute once, and inside an always procedure it may execute more than "once". This is to some extent different from the more classical interpretation of assertions that are not part of a design language (e.g., in PSL). There, unless an explicit top-level always operator is specified in the assertion, the evaluation only starts at the first clock tick. For users who have been using PSL and plan to use SystemVerilog assertions, care must be taken not to include this top level always operator, because it could lead to some performance penalty in simulation, although the behavior remains correct as illustrated in Example 3.5.

3.4 Concurrent Assertions 81

Example 3.5. Operator always as a top-level property in an assertion.

```
module m;
bit clk, a, b;
default clocking ccc @(posedge clk); endclocking
a_always: assert property(always (a ##1 b));
//...
endmodule
```

Assertion a_always will start an evaluation attempt at every tick of it clock. The top-level operator is always, and thus in each such attempt it will redundantly fork off a new version of the always operator to perpetually check for every pair of consecutive values of a and b. Unless the simulator can detect this situation and do something about it, there may be an ever increasing number of evaluation attempts that never terminate, causing a heavier and heavier burden on the simulator.

Example 3.6. The following two assertions provide an interesting illustration of the meaning of an evaluation attempt.

```
module m;
bit clk, a, b;
al: assert property(@(posedge clk) a |=> b);
initial
   a2: assert property(@(posedge clk) always (a |=> b));
endmodule
```

Assertion at states that if a is true then it must be followed by b true at the next clock tick. Since the assertion is not in any procedure, it will evaluate attempts starting at every clock tick.

The body of assertion a2 also states that if a is true then it must be followed by b true at the next clock tick. However, since a2 is in an initial procedure, there will be only one attempt started at the first clock tick, but then due to the always property operator it will evaluate a |=> b continuously starting at every clock tick.

Is there a difference between the two assertions? If we are concerned about the first failure that may occur during a simulation, i.e., a being true at a clock tick followed by b false at the next clock tick, then there is no difference in reporting the failure. However, if we wish to detect any subsequent failures or we wish to know when the failing sequence of a and b started, then assertion all provides this information while all may not. This is because all runs only one attempt, and if a = b b fails somewhere it is a failure of always and thus a failure of only that attempt. In the case of all, the failing evaluation attempt of a = b will be reported with its start and end times. Thereafter, the assertion evaluation continues and may report other failing attempts.

3.4.2 Clock

Concurrent assertions must be controlled by a *clocking event*, or *clock* and all the assertion evaluation attempts are synchronized with this event. Subexpressions




Fig. 3.6 Signal glitches

of the property expressions may have their own clocking events. Multiclocked properties are relatively rare, and we postpone their description until Chap. 12. For now, we assume that the subexpressions of the assertion property expression do not modify the clock.

Since concurrent assertions are clocked, the main assertion clock must be present in the assertion. This clock either should be explicitly specified or inferred from the context: from an event control in the surrounding always or initial procedure, or from the default clocking. We discuss in detail clock inference rules in Sects. 12.2.2 and 14.2.

All signal values participating in the property expression are sampled at the assertion clock tick only, and their values between the clock ticks are completely ignored. For example, the assertion

```
al: assert property (@(posedge clk) a);
```

passes for the signal waveforms shown in Fig. 3.6. Although a is low between time 55 and 65, this is considered to be a glitch and is ignored, because the values of a are sampled on posedge clk, i.e., at times 10, 20, etc.

The role of a clock in concurrent assertions is to convert the continuous time into the discrete one. This is important since SVA temporal operators are defined for discrete time.

The clocking event follows standard SystemVerilog semantics, and it is based on the clock signal changes: posedge clk triggers when clk becomes 1, negedge clk triggers when clk becomes 0, clk triggers when clk changes value, and edge clk triggers when clk changes to 0 or to 1.2 For example, the assertion

```
a2: assert property (@clk a);
```

does *not* mean that a is checked each time when clk is high, but each time when clk changes.

Gated Clock

An assertion clock may be gated (see Sect. 2.3). For example, the following assertion has a gated clock which is active only when en is high:

```
a3: assert property (@(posedge clk iff en) a);
```

 $^{^2}$ clk and edge clk behave the same way when clk is of type bit, but they behave differently when the type is logic.

3.4 Concurrent Assertions 83

When en is low clock ticks are ignored. For example, this assertion passes in the case shown in Fig. 3.7 because clk is disabled while a is low until time 55.

Global Clocking

SystemVerilog provides the capability to specify one clocking event in the entire elaborated model as the *primary system clock*, called also *global clock*. This is done with a *global clocking* declaration, which is a special form of clocking block declaration.

Figure 3.8 illustrates the syntax of a global clocking declaration. Global clocking is specified in line 3 within the module m_global_clock. This declaration says that the event edge sys_clk is the primary system clocking event. Since the model has a global clocking declaration, the system function \$global_clock may be used to reference the primary system clocking event. Such a reference appears in line 7. In this model, \$global_clock behaves the same as a hierarchical reference m_global_clock. Global clocking name is optional, and GCLK could be omitted in our example.

A common purpose of declaring a global clock is to specify the primary clock for formal verification. The ticks of the primary clock are at the finest granularity of time in a formal model, and the global clock is assumed to tick forever. Global clocking in formal verification is discussed in Chap. 11. For consistency with simulation, it




Fig. 3.7 Gated clock

```
module m_global_clock;
bit sys_clk;
global clocking GCLK @(edge sys_clk); endclocking
// code to animate sys_clk in simulation
endmodule
module m_check(input logic a, b);
a_simple: assert property (@$global_clock a |=> b);
endmodule
```

Fig. 3.8 Global clocking declaration

is also recommended that in simulation all events be synchronized with the global clock. Nevertheless, the simulator is not required to check this property of the global clock.

In the presence of global clocking, a number of sampled value functions may be used that are synchronized to the global clock. These are discussed in Sect. 6.2.2. The global clocking declaration also defines a specific event to be referenced by \$global_clock and to govern the global clocking sampled value functions in simulation. Global clock use cases are provided in subsequent chapters.

3.4.3 Sampled Values for Concurrent Assertion

In simulation, all values of signals appearing in a concurrent assertion are sampled in the Preponed region as explained in Chap. 2. It means that concurrent assertions use the values of signals at the beginning of the simulation step in which the clocking event occurs. Assertion value sampling makes concurrent assertions insensitive to simulation glitches. The assertion body is evaluated using values collected in the Preponed region. The action blocks are executed in the Reactive region.

One should be aware of this peculiarity of concurrent assertions to correctly analyze their behavior in timing diagrams and simulation traces. Since the assertion action blocks are executed in the Reactive region, the signal values used in the action blocks may be inconsistent with the sampled values of the signals used in the assertion. To remedy this, the sampled value of the variables should be used explicitly by calling system function \$sample in the action blocks, as explained in Sect. 6.2.1.1.

Example 3.7. Below, we reuse the example from Sect. 3.2.1 by substituting immediate assertion by a concurrent one.

```
a2: assert property (@(posedge clk) a == b) begin
a2_success++;
$info("a2: a and b have value %b", a);
end
else begin
   a2_failure++;
$error("a2 failure: a = %b, b = %b", a, b);
end
```

The timing diagram with the addition of the clk waveform is reproduced in Fig. 3.9.

The pass action of assertion a2 executes at time 10, 30, 50, 70, 90, 170, and 190. Its fail action executes at time 110, 130, and 150. As an example, consider assertion status at time 90. Assertion a2 samples values of signals a and b in the Preponed region, that is *before* the value of a changes. Both a and b at time 50 have the sampled value 1, the assertion passes at that time, and its pass action is executed; counter a2_success is incremented by one, and the message a2: a and b have value 0 is printed. Yes, it is 0 that is printed, not 1 because the action

3.4 Concurrent Assertions 85




Fig. 3.9 Timing diagram for assertion a2

blocks of concurrent assertions are executed in the Reactive region, and the value of a there is already 0. The message is misleading, since the assertion uses the old value of a, while its action block uses the new one! To correct this, we should explicitly specify the sampled values of a and b in the action blocks: $\frac{\sin fo}{a^2}$: a and b have value b", $\frac{\sin fo}{a^2}$: in the pass action block, and $\frac{\sin fo}{a^2}$: a = b, b = b", $\frac{\sin fo}{a^2}$: $\frac{\sin fo}{a^2}$: b = b", $\frac{\sin fo}{a^2}$: \frac

There are several exceptions for the general rule of sampling signal values in concurrent assertions, the most important of them being the assertion main reset expression (the argument of disable iff statement). Other exceptions will be covered in subsequent chapters. Sampling of the main reset is explained in detail in Sect. 13.1.1.

The value of the main assertion reset is not sampled in concurrent assertions.

3.4.4 Reset

Usually, we are interested in checking an assertion only when the reset signal is inactive. disable iff operator is used to specify the reset expression of the assertion. If the main assertion clock is explicitly specified, disable iff should immediately follow it. If the assertion clock is omitted, disable iff should be the first operator in the assertion body. There may be at most one disable iff operator in the whole assertion.

If at any point prior to completion of an assertion evaluation attempt the reset is high or becomes high, then the evaluation attempt is discarded. Such attempts are called *disabled*. The reset is asynchronous, in the sense that it is monitored at every time-step, and not only at the ticks of the assertion clock. Therefore, it also makes it sensitive to simulation glitches.




Fig. 3.10 Assertion with reset

Example 3.8. Consider assertion a1

```
a1: assert property(@(posedge clk) disable iff (rst)
  req |-> nexttime[2] ack);
```

with the timing diagram shown in Fig. 3.10.

In this example, there are three assertion evaluation attempts beginning at times 20, 40, and 70 that satisfy the antecedent signal req.³ First two of them are disabled, and therefore the assertion does not fail even though there is no ack received. The last attempt is normal, and it succeeds because ack is received in two cycles after req is issued. Refer to Chap. 13 for detailed discussion about assertion resets.

As we mentioned, the disable iff expression acts asynchronously. Its evaluation goes on evaluating regardless of the occurrence of the clock tick of the associated assertion. And, should it evaluate to true, all evaluation attempts of that assertion that are "in flight" are declared disabled.

Example 3.9. An example of disable iff.

```
module reqgen(input logic busy, clk, rst, output logic req);
  wire idle;
  assign idle = !busy;
  always @(posedge clk or posedge rst) begin
    if (rst) req <= '0;
    else req <= !busy;
  end
  req_when_idle: assert property (
    @(posedge clk) disable iff (rst) idle |=> req)
    $display("req_when_idle completed");
endmodule: reqgen
```

³ One could be tempted to say that the attempts begin at times 15, 35, and 65, but recall that the attempts are synchronized with the rising edge of the clock.

3.4 Concurrent Assertions 87

In the usual way, assertion req_when_idle is scheduled in the Observed region as a result of the occurrence of its clock (posedge clock) in the Active region. None of the signals in the assertion expression, namely, idle and req, have any effect on the assertion outside the time slots in which the clock tick occurs. The disable iff expression (rst) is an exception to this general rule. req_when_idle is disabled in the time slot when signal rst becomes true. Its action block is scheduled in the same Reactive region.

Unlike other expressions in the body of a concurrent assertion, the disable iff expression is not sampled and can affect the result of the assertion from any scheduling region in which it becomes true.

3.4.5 Boolean Expressions

Boolean expressions are elementary building blocks for assertions. There are two places in an assertion statement where Boolean assertions are used:

- operands of property and sequence operators
- argument of disable iff as the top-level assertion reset or of default disable

As we saw in the previous sections, Boolean expressions as the operands of property and sequence operators are sampled, while as the arguments of disable iff or default disable are not sampled.

A Boolean expression is composed of SystemVerilog expressions, but with some restrictions on the operators, variables and their types.

Following data types are not allowed for the variables used in a Boolean expression:

- Noninteger type (shortreal, real and realtime)
- string
- event
- chandle⁴
- class
- Associative arrays
- Dynamic arrays

Other arrays are allowed, both packed and unpacked, including part-selects and bit-selects of array items. Arrays are commonly compared in the subexpressions of a Boolean expression, such as

```
logic [15:0] aA [4], aB[4];
a1: assert property (@(posedge clk)(aA == aB));
```

⁴ chandle is a data type used to represent storage for pointers passed to SystemVerilog from C code.

A variable in any subexpression of a Boolean expression, in general, must be declared as static. The static variable declared in a task, clocking block, module, program, or interface can be referenced. The restriction of not allowing an automatic variable is because its lifetime may not match that of an evaluation attempt of the assertion in which it is referenced. Limited use of automatic variables is allowed in procedural concurrent assertions as explained in Sect. 14.3.

All operators that accept the above-mentioned data types as operands are allowed with the exception of the following operators:

- assignment operators such as +=
- auto increment and decrement operators (++ --)

These operators are prohibited as they have side effects on the variables used in the assertions themselves.

3.4.6 Event Semantics for Concurrent Assertions

Next, let us consider a concurrent assertion which is not embedded in procedural code and decompose the assertion execution into various kinds of essential computational steps in the event semantic framework described in Chap. 2 (the **triggered** sequence method signals that the end of a sequence has been reached, and it is described in Sect. 9.2.1).

We can subdivide the activity as follows:

- Sample signals enable, req, end_ack, and busy which are needed for concurrent assertion evaluations.
- 2. Detect the occurrence of clock @ (posedge clk), since sequence ack and assertion all evaluations are activated by the clock.
- 3. Start a new attempt for sequence ack.
- 4. Determine whether there is a match for sequence ack.
- 5. Start a new attempt for assertion a1.
- 6. Resume evaluation of the previous attempts for this clock tick.
- 7. For an attempt of all resulting in a failure, schedule the action block execution in the Re-Active queue of the Reactive region.
- 8. For an attempt of all resulting in a success, report a success.
- 9. Execute action blocks.

These steps are taken in specific regions. Each region contributes to the execution of concurrent assertions as shown in Fig. 3.11.

Normally, the detection of an assertion clock occurs in the Active region. What sets a concurrent assertion apart from an immediate assertion is that the former is

3.4 Concurrent Assertions 89




Fig. 3.11 Assertion processing in regions

sensitive to its clock. Consequently, its evaluation resumes at the arrival of the clock and gets suspended at the end of the time slot in which the clock occurs.

Beside the clock, the new attempts of procedural concurrent assertions are bound to the procedural context in which they are specified. For instance,

```
function bit f1(bit arg);
//...
endfunction
always @(posedge e1) begin: B1
   a <= b + c;
   if (c1_enb)
   a2: assert property (f1 (a) ##2 f1(a));
   dout <= f1(a);
end</pre>
```

An evaluation attempt of assertion a2 can only be initiated if the simulation control reaches the statement. In this case, it means that,

- 1. Event (posedge e1) occurs
- 2. Signal ci_enb is true

Otherwise, a new attempt of a2 is not fired off. However, the previous attempts of a2 in progress are no longer coupled with (2); they are only sensitive to (1), hence their evaluation is resumed should (1) occur.

Additional queues are called upon in the Observed region to schedule new attempts and track other attempts that are in progress. Two queues, procedural assertion queue and matured assertion queue are added in the Observed region to dispatch the evaluation. The event semantics of procedural concurrent assertions is described in greater detail in Chap. 14.

3.5 Assumptions

We have mentioned the existence and general meaning of assumptions in previous chapters, here we provide a systematic study of assumptions.

3.5.1 Motivation

Figure 3.12 shows a module implementing a simple RAM.

When read is asserted, out is assigned the contents of the memory at address addr. When write is asserted, data is written at address addr. This module also

Fig. 3.12 Simple RAM

3.5 Assumptions 91

contains assertion stable_when_write checking that when write is asserted the module output out does not change. The system function \$stable returns true when the current value of the signal is identical to its value at the previous clock tick, and false, otherwise.

It looks like our design should satisfy this assertion, but if you try to formally verify the model, you will discover that the assertion fails. Why? The answer is surprising: when read and write are asserted together, the value of out may change. But how can it be? We know that read and write cannot be asserted together, otherwise the design would not function properly. But how should formal verification tools guess that this input condition is impossible?

As we can see from this example, to make the design work properly its inputs should be appropriately constrained. These constraints are called *assumptions*, and there is a special notation for assumptions in SVA. In our example, the following assumption is missing:

```
mutex: assume #0 ($onehot0({read, write}))
else $error("read/write contention");
```

This assumption reads that at all times signals read and write are mutually exclusive, that is, they cannot have value 1 simultaneously. To express this, we use the system function <code>\$onehoto</code> returning true when at most one bit of a vector is 1.

Assumptions are an important part of a design specification. Although we illustrated a design specification in Sect. 1.2.1, Fig. 1.6 only with assertions, a real design specification should have assumptions as well. Assumptions are also important for ABV, as they document the conditions that guarantee proper functioning of the module. It is difficult to underestimate the importance of assumptions in system integration: if each module clearly specifies its interface, most integration errors are discovered early as assumption violations.

3.5.2 Assumption Definition

The goal of assumptions is to *constrain a system behavior*. A system is composed of the DUT (model) and its environment (see Sect. 3.1, Fig. 3.1). The system behavior may be constrained either by constraining the DUT or by constraining its environment. If the DUT is deterministic, as normally happens when it is implemented in RTL,⁵ there is not much sense in constraining its behavior. Therefore, assumptions are used to constrain the behavior of the environment. Assertions and assumptions play dual roles – assertions specify the behavior of the DUT and assumptions specify the behavior of its environment.

⁵ In this section, we limit our discussion to deterministic models; study of nondeterministic models is postponed to Chap. 22.

92 3 Assertion Statements

```
function int quotient(int dividend, divisor);
  assume (divisor != 0) else $fatal("Division by zero");
  quotient = dividend / divisor;
endfunction
```

Fig. 3.13 Immediate assumption

Syntactically assumptions are similar to assertions, but they use the keyword assume instead of assert.

```
assumption ::= name: assume_keyword (assumption_body) action_block
```

Similar to assertions, assumptions may be immediate (keyword assume), deferred (keyword assume #0), and concurrent (keyword assume property).

Immediate Assumptions Figure 3.13 shows a typical example of an immediate assumption:

Note that in this case we do need an immediate assumption, the deferred version would not work. Indeed, even if there is a simulation glitch, we should make sure that divisor is non-zero.

Deferred Assumptions We have seen an example of a deferred assumption in Sect. 3.5.1, and we repeat it here for completeness:

```
mutex: assume #0 ($onehot0({read, write}))
else $error("read/write contention");
```

In this case, the deferred form is preferable as we want this assumption to be standalone.

Concurrent Assumptions The following is an example of a concurrent assumption constraining sig to remain stable for two clock ticks whenever trig is 1.

```
stable_input: assume property (@(posedge clk) disable iff (rst)
  trig |=> $stable(sig))
  else $error("sig is not stable");
```

3.5.3 Checking Assumptions

Checking assumptions has its own specifics: assumptions play different roles in simulation and in formal verification.

3.5.3.1 Assumptions in Simulation

Handling assumptions in simulation is not different from handling assertions. In simulation, it is checked that the constraints imposed by assumptions hold. In case when these constraints are violated, an error is flagged.

3.5 Assumptions 93

In simulation keywords assert and assume are synonymous; their choice emphasizes the verification intention. Assertions are used to check the DUT behavior, while assumptions are used to check the environment correctness, that is, the DUT input values are correct.

3.5.3.2 Assumptions in Formal Verification

Any specific DUT behavior may be described by a corresponding signal trace, a sequence of all DUT signal values in time. This is what we see in simulation if we request the dump of all DUT signals.⁶

In FV, assumptions are used to constrain the set of legal traces of a DUT, that is, the assumptions *are not checked* in FV. The role of assumptions and assertions in FV is absolutely different: *assertion satisfaction is checked provided that all assumptions hold*.

Thus, in the example from Sect. 3.5.1, assumption mutex is used to keep only those traces where read and write are not 1 at the same time. Assertion stable_when_write holds for those traces, while it fails without this mutex constraint.

3.5.3.3 Assumptions in Random Simulation

In the case where randomization is done only in the environment, for example, using constraint solving SystemVerilog Testbench (SVTB), there is no difference between random and deterministic simulation as far as checking assumptions is concerned. However, when the DUT input stimuli are generated directly, the assumptions in random simulation act as constraints. Therefore, the role of assumptions in random simulation is similar to their role in FV – to limit the legal traces of DUT. But if in FV we consider all legal traces simultaneously, in random simulation we generate only one legal trace.

A distribution operator dist in SystemVerilog can be used in assumptions for tuning them for random simulation. It is best to explain its usage on the following example.

The assumption

```
m1: assume property (@clk a dist {1 := 2, 3 := 1, 4 := 5});
```

means that a may only get values 1, 3, or 4. If this assumption is used as a constraint in a random testbench, the specified weights, or frequencies are taken into account. In our example, a assumes values 1, 3, and 4 with the respective weights of 2, 1, and 5.

If the distribution weight is omitted, 1 is assumed by default.

⁶ In simulation all traces are, of course, finite. In FV, we can also consider infinite traces. This is discussed in Chap. 11.

94 3 Assertion Statements

We are not going to further elaborate the distribution usage in assumptions as it falls beyond the scope of this book.

In formal verification dist acts as inside operator, and the weight specifications are ignored. It is also legal, though meaningless, to use distributions in assert and cover statements, and they are also treated as inside operators there.

3.6 Restrictions

Sometimes it is difficult to formally verify a block. It becomes necessary to verify special cases separately and then combine them together. We can take an Arithmetic Logic Unit (ALU) as an example. ALU can perform several commands, such as addition, subtraction, arithmetic shift, etc. It thus makes sense to split the verification process into several cases corresponding to the commands, i.e., we separately verify addition, subtraction, etc.

To specify the case of addition it is natural to use an assumption, such as

```
m1: assume property (@clk opcode == OP ADD);
```

where opcode is an operation code control variable in ALU, and OP_ADD means addition.

This will do the job in FV, but in simulation this assumption is likely to fail because the simulation test cases are not guaranteed to limit the ALU commands to addition only. The workaround is to wrap such assumptions in 'ifdef, which makes the code less readable and dependent on the custom setup.

In SystemVerilog, there is a cleaner solution, called *restriction*. Other than the keyword restrict, the restriction syntax is the same as the syntax of assertions and assumption. Unlike assertions and assumptions, restrictions have only concurrent form, and they cannot have actions:

```
restriction ::= name: restrict property ( property );
```

Restrictions are treated as assumptions in FV, but they are completely ignored in simulation. They are meant for limiting formal proofs to particular cases. Consequently, the above example should be rewritten as:

```
r1: restrict property (@clk opcode == OP_ADD);
```

Since restrictions are ignored in simulation, using actions with them is meaningless, this is why the restriction syntax does not allow actions.

3.7 Coverage

The last assertion statement cover has also been mentioned in previous chapters. In this section, we provide general information about cover statements, while the detailed discussion about coverage can be found in Chap. 18.

3.7 Coverage 95

```
read_asserted: cover property(@(posedge clk) disable iff (rst)
  read);
write_asserted: cover property(@(posedge clk) disable iff (rst)
  write);
rw_deasserted: cover property(@(posedge clk) disable iff (rst)
  !(read || write));
```

Fig. 3.14 Coverage statements for simple RAM

3.7.1 Motivation

Assertions and assumptions define how the DUT and its environment *must* behave. It is also highly desirable to document how they *can* behave. When testing the design, it is necessary to make sure that the tests cover important scenarios, and different corner cases. This is achieved by *functional coverage* – a methodology to specify the scenarios to be covered. For example, for the model shown in Fig. 3.12 it is useful to check the following scenarios:

- read is asserted.
- write is asserted.
- Both read and write are simultaneously deasserted.

The corresponding coverage statements are shown on Fig. 3.14

3.7.2 Coverage Definition

Cover statement is used to register when a specific scenario happens in the design. It has the following syntax:

```
cover_statement ::= name: cover_keyword (cover_body) pass_action
```

Unlike assertions and assumptions, coverage statements have only pass action which is executed when the coverage condition (scenario) is met. The corresponding statistical information is reported by a simulator and is registered in the coverage database. Like assertions and assumptions, coverage statements may be immediate, deferred, and concurrent.

Immediate Coverage The immediate coverage statement acts like an if statement: when the body expression is true, the pass action is performed. For example, the following statement prints a message each time when the counter reaches its maximal value:

```
c1: cover (ctr_max) $display("Counter reached its maximal
    value");
```

96 3 Assertion Statements

Deferred Coverage Deferred coverage is similar to immediate coverage, but it is glitch-free (see Sect. 3.3). In the following example, the message is issued each time the bus is active. bus drivers is a vector of wires driving the bus:

```
wire [15:0] bus_drivers;
c2: cover #0 (bus_drivers !== 16'bZ) $display("Bus is active");
```

3.7.2.1 Concurrent Coverage

There are two versions of concurrent coverage: property coverage and sequence coverage. Property coverage has the keyword cover property, and its body may contain an arbitrary property, as concurrent assertions and assumptions.

```
property_coverage_body ::=
    [clocking_event] [ disable iff (reset) ] property
```

If an evaluation attempt is successful, the pass action is executed only once per evaluation attempt.

The sequence coverage has the similar syntax, but it has the keyword cover sequence instead of cover property, and its body is limited to a sequence. ⁷

```
sequence_coverage_body ::=
   [clocking_event] [ disable iff (reset) ] sequence
```

Here, the pass action is executed at each sequence match.

The example in Fig. 3.15 illustrates the difference between the two forms.

The body of both statements is identical, the intention is to cover a scenario when write followed by several (maybe zero) busy cycles is followed by a read. But their behavior is different. For the trace shown in Table 3.1 c3 reports the hit only once per attempt – at time t+2, while c4 reports the hit twice – at times t+2 and t+3.

```
c3: cover property (@(posedge clk) write ##1 busy[*] ##1 read);
c4: cover sequence (@(posedge clk) write ##1 busy[*] ##1 read);
```

Fig. 3.15 Concurrent coverage

Table 3.1 Stimuli for c3 and c4

Clock cycle	write	busy	read
t	1	0	0
t + 1	0	1	0
t + 2	0	1	1
t + 3	0	0	1

⁷ See Chap. 5.

In practice, property coverage is much more useful than sequence coverage. The main use of sequence coverage is to react on each sequence match in the pass action block to trigger some testbench actions.

3.7.3 Checking Coverage

Usually coverage is checked in simulation, but there is an added value to check coverage in FV too.

3.7.3.1 Checking Coverage in Simulation

Checking coverage in simulation is somewhat similar to checking transaction completion for assertions – the simulator reports when a given sequence of signals happens. For example, for the cover statement

```
cover property(@(posedge clk) write ##1 read);
```

the simulator will report each time it detects write signal followed by read.

The simulators usually register successful completion of evaluation attempts in a coverage database to collect the coverage statistics across the available tests.

3.7.3.2 Checking Coverage in Formal Verification

In FV, the coverage condition (called also coverage point) is checked for its feasibility, that is, whether it can be reached when all the assumptions are met. FV tools either report that a coverage point cannot be reached, or provide a reachability witness, as discussed in Sect. 10.1.

3.8 Checking Assertions. Summary

Table 3.2 summarizes checking SVA assertions in simulation, 8 and in FV.

Exercises

- **3.1.** What do the assertions check?
- **3.2.** Write three versions of an assertion checking that all bits of some packed bit vector are set to 1: immediate, deferred, and concurrent. Explain the difference between them.

⁸ We ignore here the fact that assumptions may be used as constraints in random simulation. This feature of assumptions is seldom implemented in commercial simulation tools.

98 3 Assertion Statements

Table 3.2	Checking	assertions	in	simul	lation	and	in l	FV	

Assertion	Simulation	Formal verification
assert	Check whether an assertion is violated on a given simulation trace	Check whether an assertion can be violated while respecting all specified assumptions. If yes, report a counterexample
assume	Check whether an assumption is violated on a given simulation trace (same as for assertions)	Use as a constraint when checking assertions and coverage points. The assumption correctness is not checked
restrict	Ignore	Use as a constraint when checking assertions and coverage points
cover	Check whether a coverage condition is met on a given simulation trace	Check whether the coverage condition can be met while respecting all specified assumptions. If yes, report a coverage witness

- **3.3.** What is the goal of assumptions?
- **3.4.** Write three versions of an assumption stating that the signal parity checksum is 0: immediate, deferred, and concurrent. Explain the difference between them.
- **3.5.** What is the difference between assumptions and restrictions?
- **3.6.** Is it possible to specify actions with restrictions? Why?
- **3.7.** What is the goal of cover statements?
- **3.8.** What is the difference between assertions and cover statements?
- **3.9.** What is the difference between property and sequence coverage?
- **3.10.** Write the following statements:
- Two inputs of the block must be mutually exclusive.
- Two outputs of the block must be mutually exclusive.
- We will conduct our verification session only in case when two inputs of the block are mutually exclusive.
- We want to check that two inputs of the block may be mutually exclusive.
- We want to check that two outputs of the block are not necessarily mutually
 exclusive.

3.11. What is the difference between the following statements is simulation and in formal verification:

```
    p1: assert property(@(posedge clk)a)$display("a is high");
    p2: assume property(@(posedge clk)a)$display("a is high");
    p3: restrict property(@(posedge clk)a);
    p4: cover property(@(posedge clk)a)$display("a is high");
    p4: cover sequence(@(posedge clk)a)$display("a is high");
```

Chapter 4 Basic Properties

Where there is no property there is no injustice.

- John Locke

Properties play a central role in SVA because they form the bodies of concurrent assertions. A *property* is a temporal formula that can be either true or false on a given trace. As explained in Sect. 3.5.3, by trace we understand a series of all DUT signal values in time. Properties are interpreted over traces. In this chapter, we assume that each point on the trace corresponds to a tick of the clock on which the property is evaluated. This definition will not work for multiply clocked properties, but we currently limit our consideration to singly clocked properties only. The more general case is described in Chaps. 12, 13, and 20. Also, in formal verification (FV) we may assume that all the traces are infinite, which corresponds to the case when the property clock ticks infinitely many times. Of course, simulation traces are always finite. We informally describe the property semantics here, and defer the formal semantics of properties until Chap. 20.

This chapter is one of the central chapters of the book, and a good grasp of the material described here will be instrumental in understanding the rest of the book and in writing basic temporal assertions. Its contents are addressed both to users of simulation and to users of FV. FV issues are always commented so that the reader interested in only assertion simulation can skip them. However, we would like to stress that understanding FV issues may provide a deeper insight into the nature of temporal assertions, even for those who are not planning to use FV.

We describe only the elementary and most commonly used property operators here. The less frequently used and more complex operators are discussed in Chap. 8.

In this chapter, we use the following convention: letters a, b, c, and, e denote integral expressions or signals; p and q denote properties. All letters may be optionally indexed. We enumerate clock ticks with integer numbers starting with 0. In the diagrams, we mark the ticks where a Boolean expression holds with a black dot, and the ticks where a property holds with a black triangle.

¹ An exception is *disabled* status of a property when the **disable iff** operator is used. See Sect. 13.1.1.

102 4 Basic Properties

Table 4.1 Basic property operators

Operator	Associativity
not	_
nexttime	_
and	Left
or	Left
until	Right
until_with	Right
always	_
${ t s_eventually}$	_

The property operators described in this chapter are summarized in Table 4.1. They are grouped by their precedence, from highest to lowest.

Properties can be built from simpler properties in a recursive manner. First we define "primitive" properties, and then we show how to build new properties using property operators from existing ones. The primitive properties are constructed from sequences. However, the notion of a sequence is less intuitive before introducing the notion of a property. Therefore, in this chapter we consider a Boolean, which is the simplest form of sequence, as the primitive form, and postpone the introduction of sequences until Chap. 5. In Chap. 5, we clarify why primitive properties are in fact sequential properties and that Boolean properties are the simplest case of sequential properties.

Example 4.1. To illustrate what we mean by recursive definition of properties, consider property nexttime always e, the meaning of which is explained later. This property is built by applying property operator nexttime to the simpler property always e. The latter property, in its turn, is built by applying property operator always to the primitive property e.

4.1 Boolean Property

The simplest property is a *Boolean property* – an integral expression e, which is treated as Boolean. A Boolean expression is *true* if it has a known nonzero value and *false* otherwise. Now, extending the meaning, we define a Boolean property informally for a point on a trace as follows:

Boolean property e is true in clock tick i iff Boolean expression e is true in clock tick i.

Boolean Expressions and Properties What is confusing is how we can distinguish between Boolean expression and Boolean property if they both have exactly the same syntax? The answer is simple: if a Boolean is used in a context where a property is expected, then it is a Boolean property. For instance, on the one hand, e in the property expression nexttime always e from Example 4.1 is a Boolean property since a property operator always expects a property as its argument. On

the other hand, in the expression ~e, e is a Boolean expression, but not a Boolean property, since the bitwise negation operator ~ requires a Boolean² expression, and it cannot accept a property as its argument.

Our definition of Boolean property explains the meaning of the sentence "e is true in clock tick *i*". However, in the general definition of property given in the beginning of this chapter we defined the property truth relative to the entire trace, and not in a specific clock tick. So what does it mean that e is true on a whole trace, and not just in a specific clock tick of this trace? This question is general and it may be answered for any property, not just for a Boolean one. Consequently, we give a general answer to this question for arbitrary property p.

```
Property p is true on a trace iff it is true in clock tick 0 of this trace.
```

This implies that Boolean property e is *true* iff e is true in the clock tick 0, as shown in Fig. 4.1.

Example 4.2. If a DUT contains three signals a, b, and c, and in clock tick 0 = 1, b = 1, and c = 0 then the property a | b holds since a | b is true in clock tick 0.

Boolean expressions when used as Boolean properties cannot have side effects. For example, a++ == b cannot be used as Boolean property.

Although Boolean properties are very common as part of more complex properties, Boolean properties alone can be used for specifying the initial state of the system, as in the following example:

Example 4.3. Assume that initially the reset rst is active, and check that initially the value of ready is low.

Solution:

```
initial begin
  m1: assume property (@(posedge clk) rst);
  a1: assert property (@(posedge clk) !ready);
end
```

The behavior manifested by a Boolean property alone when placed in an initial procedure is useful because only one property evaluation attempt is executed. Placing such an assertion elsewhere would lead to unconditional evaluation of the Boolean at every assertion clock tick.



² Recall that according to our definition any integral expression is also a Boolean.

104 4 Basic Properties

4.2 Nexttime Property

Property nexttime p, as its name suggests, is *true* in clock tick i iff property p is true in clock tick i + 1. For a trace, according to the general definition (Sect. 4.1), property nexttime p is *true* iff property p is true in clock tick 1, as shown in Fig. 4.2.

If p is a Boolean expression e, nexttime e means that e is true in the clock tick 1.

Multiple nexttime Operators What happens if we apply the nexttime operator twice: nexttime nexttime p? According to the definition, it means that nexttime p holds in clock tick 1, which is equivalent to the statement that p holds in clock tick 2. Similarly, nexttime nexttime nexttime p means that p holds in clock tick 3, and so on. Since having a big chain of nexttime operators makes the property unreadable, SVA provides a shortcut nexttime [n], where n is an elaboration time constant. For example, nexttime [3] p is a shortcut for nexttime nexttime nexttime p. It is also legal to specify nexttime [0] p, which is roughly equivalent to just p in the case of singly clocked assertions. Its semantics in multiply clocked properties is described in Chap. 12.

nexttime is seldom used on its own. The following example illustrates such usage.


Example 4.4. Reset rst should be low in clock clk tick 9.

Solution:

```
initial a1: assert property(@(posedge clk) nexttime[9] !rst);
```

Discussion: This property does not say anything about the behavior of rst in clock ticks 0-8.

Finite and Infinite Traces The definition of property nexttime is not as trivial as it may seem. When we require a property to be true in the next clock tick we implicitly assume that the clock ticks at least one more time. This observation holds when clocks tick infinitely many times, and hence traces are infinite. Infinite traces allow us to ignore this important question in the definition of property operators, namely, what happens if the clock stops ticking in the middle of evaluation. Note that this question is important even for Boolean properties: How can we define the truth of a Boolean property on the empty trace? We do consider property behavior on finite traces in Chaps. 8 and 20, but in this chapter we ignore it because we wish to concentrate on the main behavior of property operators.



³ This is further discussed in Chap. 8.

4.3 Always Property 105

Efficiency Tip nexttime with a big factor is inefficient both in simulation and in FV. Try to keep the factor small, especially in complex assertions. In simulation, it is recommended not to exceed several hundreds for simple argument properties, and in FV not to exceed a couple of tens. The common rule is the smaller the better.

4.3 Always Property

Property always p is true in clock tick i iff p is true in all clock ticks $j \ge i$. It follows (See Sect. 4.1) that property always p is true iff property p is true in every clock tick, as shown in Fig. 4.3.

Property always p defines a series of "instances" of property p starting at clock ticks 0, 1, We say that an always property defines a series of evaluation attempts of the underlying property. For the always property to be true, all of the underlying attempts must evaluate to true.

Example 4.5. For a Boolean expression e, always e is true iff e is true in every clock tick.

Example 4.6. What is the meaning of nexttime always p?

Solution: According to the definition of nexttime property, always p should hold in clock tick 1. Therefore, property p should hold in every clock tick starting from clock tick 1.

Example 4.7. What is the meaning of always nexttime p?

Solution: According to the definition of always property, nexttime p should hold in every clock tick. Therefore, property p should hold in every clock tick starting from clock tick 1.

Discussion: Properties always nexttime p and nexttime always p (Example 4.6) are equivalent. \Box

Example 4.8. What is the meaning of always always p?

Solution: According to the definition of always property, always p should hold in every clock tick. Therefore, property p should hold in every clock tick.

Discussion: It follows that always always p is equivalent to always p, and that the outer always in this case is redundant.

Efficiency Tip Simulation performance of always always p may be much inferior to that of always p (see Sect. 3.4.1) if it is required to maintain information about all evaluation attempts that are in progress (for example, for debugging purposes).




Fig. 4.3 always property

106 4 Basic Properties

4.3.1 Implicit Always Operator

The always operator is useful for specifying system invariants. As we discussed in Sect. 3.4.6, all concurrent assertions placed outside procedural code are continuously monitored. This means that there is an implicit outermost always operator which defines a series of evaluation attempts. Consequently, the following assertions al and al are equivalent in the sense that either both pass or both fail.

```
al: assert property (@clk p);
is equivalent to
initial a2: assert property (@clk always p);
```

However, simulation reporting may be different, as explained in Sect. 3.4.1, because at has as many evaluation attempts as there are clock ticks, while at has only one attempt.

The explicit always operator is rarely used. The vast majority of assertions are either written outside procedural code or inside always procedures⁴ and thus have the implicit outermost always operator.

As in the case of the explicit double always operators, an always property in the body of a continuously monitored assertion may result in degradation of simulation performance.

Efficiency Tip Do not explicitly specify the outermost always in continuously monitored assertions.

Example 4.9. Check that signal sig may only have values 0, 1, 2, or 4.

Solution:

```
al: assert property (@(posedge clk) sig inside {0, 1, 2, 4}); assuming that al is a standalone assertion.
```

Discussion: Following the efficiency tip, this assertion should not be written as


```
a2: assert property (@(posedge clk)
  always sig inside {0, 1, 2, 4});
```

Although assertions a1 and a2 are equivalent, simulation performance of a2 may be worse.

4.4 S_eventually Property

Property s_eventually p is true in clock tick i iff p is true in some clock tick $j \ge i$. It follows that property s_eventually p is true iff property p is true in some clock tick, as shown in Fig. 4.4.

⁴ See Chap. 14 for discussion about procedural concurrent assertions.



The reader may wonder why the keyword s_eventually has a prefix s_. As explained in Chap. 8, s_eventually is a strong operator, and in SVA names of strong operators have a prefix s_.

Similar to always p, property s_eventually p defines a series of evaluations of p. But for s_eventually p to succeed only requires that at least one of those evaluations succeed.

Example 4.10. Reset rst should eventually be deactivated.

Solution:

```
\begin{tabular}{ll} \textbf{initial} & \textbf{al: assert property} & \textbf{(@(posedge clk) s\_eventually !rst);} \\ \end{tabular}
```

Checking s_eventually Property The s_eventually property differs significantly from all other properties described in this chapter.⁵ Consider, for instance, assertion al from Example 4.10. Suppose that we simulated the DUT for 10,000 clock ticks and rst remained high all the time. Does it mean that assertion al is wrong? No, it does not, since it might pass if we simulate few more clock cycles. The failure of this assertion can only be observed on an infinite trace in which rst is always high. Such assertions are called *liveness* assertions, and they are studied in Chap. 11. Generally speaking, liveness assertions cannot be falsified in simulation, but only in FV. However, we can say something about property s_eventually even observing its behavior in simulation: It looks suspicious if the condition of s_eventually does not happen during simulation. For instance, when executing any test from the testbench, it is reasonable to expect that in Example 4.10 a zero value of rst will be observed. In the case when the condition of s_eventually has never been observed, a simulation tool usually issues a warning message at the end of simulation.⁶

Example 4.11. What does s eventually always p mean?

Solution: According to the definition of s_eventually this property means that there exists some clock tick where always p is true. This is equivalent to the statement that p is true from some clock tick on.

Discussion: Strictly speaking, this property can neither fail nor pass in simulation. As mentioned earlier, a simulation tool may issue a warning message (or failure) at the end of simulation if in the last clock cycle a Boolean p is false.

⁵ Here, for convenience, we use the terms "property" and "assertion" interchangeably in the context of failure or success

⁶ As we explain in Chap. 8, since **s_eventually** is a strong operator, at the end of simulation when there are no more clock ticks and rst was high all the time, the simulator may declare failure of the property.

108 4 Basic Properties

Efficiency Tip Checking property s_eventually always p in simulation may be costly, especially if it is not in the scope of an initial procedure.

Example 4.12. Reset rst remains low starting from some moment.

Solution:

```
initial
```

```
a2: assert property (@(posedge clk) s_eventually always !rst);
```

Discussion: Note the difference between assertion a2 and assertion a1 from Example 4.10. Assertion a2 checks that rst at some moment becomes and *remains* low, whereas assertion a1 only checks that rst becomes low.

Exercise 4.5 discusses the meaning of a2 when it is a stand-alone assertion. As we mentioned above, the stand-alone version of this assertion may be inefficient in simulation.

```
Example 4.13. What does property always s_eventually p mean?
```

Solution: According to the definition of always this property means that property $s_{eventually}$ p holds in every clock tick i. This is equivalent to saying that for every clock tick i there is a clock tick $j \ge i$ where p is true. So,

```
always s eventually \Code{e}
```

holds if p is true infinitely many times, in other words, p is true infinitely often.

Discussion: This property can only be verified on infinite traces in formal verification because simulation traces are finite.

Efficiency Tip Checking property always s_eventually p may be costly in simulation.

Example 4.14. A pending request req should be eventually granted (gnt is asserted). This includes the case when the request is granted immediately.

More specifically, it is given that when the request becomes active it remains active until it is granted.

Solution: Consider an arbitrary clock tick *i*. The assertion should be satisfied in both of the following cases:

- 1. reg is never asserted in all clock ticks $\geq i$.
- 2. req is asserted for the first time $(\geq i)$ in some clock tick $j \geq i$, and gnt is asserted for the first time $(\geq j)$ in some clock tick $k \geq j$. In this case, req will also be pending until clock tick k.

Both cases imply that the attempt of the property $s_{eventually}$ req -> gnt starting in the clock tick i is satisfied, and assertion

```
a1: assert property(@(posedge clk) s eventually req -> gnt);
```

covers the desired behavior of the pending request. Note that all only checks the behavior of the grant in response to req. It does not check that a grant is not issued without a request. It also does not check that request, once issued, persists until granted.

Of course, this assumes that we verify the property on an infinite trace, hence in FV. In that case it is not difficult to see that the opposite is also true: Assertion al implies the required behavior. Indeed, if req goes high in some clock tick i, it will remain high until granted by definition. The attempt of the property starting

```
s eventually req -> gnt
```

in clock i guarantees that this req is granted.

Discussion: This property is a special case of property always s_eventually p described in Example 4.13. Assertion a1 is standalone, and therefore it has an implicit always operator. Its performance in simulation may be poor if req is asserted and no gnt is asserted for a long time (if ever). Simulation performance efficiency is discussed in detail in Sect. 19.3.

In this example, we assumed that the request remains pending until granted. Example 5.23 describes the case of an arbitrary, not necessarily pending request.

Fairness

Example 4.15. A device must be available infinitely many times. The device availability is indicated by high value of the ready signal.

Solution:

```
a1: assert property (@(posedge clk) s_eventually ready);
```

Discussion: This assertion is standalone, hence there is an implicit top-level always operator.

The property always s_eventually e is very important for verifying liveness properties in FV. It expresses the notion of *fairness*. Fairness indicates that some resource eventually becomes available, as in Example 4.15. The absence of fairness is called *starvation*, the situation when the requested resource is never available: Imagine a car waiting at an intersection forever on the red light when the traffic lights are broken. We get back to the notions of fairness and starvation in Chap. 11. In simulation, of course, this assertion cannot be verified (it cannot fail) because simulation will end in a finite number of clock ticks.

4.5 Basic Boolean Property Connectives

The following Boolean connectives between properties exist in SVA:

• not – negation not p is true iff p is false. 110 4 Basic Properties

- and conjunction
 - p and q is true iff both p and q are true.
- or disjunction
 - p or q is true iff either p or q (or both) are true.

The above definitions with obvious modifications apply also to the way property truth is determined in clock tick i. For example, p and q is true in clock tick i iff both p and q are true in clock tick i.

In the special case of Boolean properties, it is possible to rewrite Boolean property connectives in a different way. For example, e1 and e2 means that both e1 and e2 are true, which can be also expressed as e1 && e2.7 The domain of the operators && and and is different: && may be used with Boolean expressions only, while and requires sequence or property arguments. Since Boolean expressions in this case may also be considered as Boolean properties, both operators may be applied to them. Note also that && has greater precedence than and.

Similarly, e1 or e2 is equivalent to e2 | | e2, but not e is equivalent to !e only if the property clock eventually ticks (see Chap. 20).8

Example 4.16. The following expression is syntactically illegal: (a and b) $| \cdot |$ c. Although a and b is logically equivalent to a && b, it is not a Boolean expression. The operator $| \cdot |$, however expects both its operands to be Boolean expressions.

Example 4.17. What does not always p mean?

Solution: According to the definition of property not, this property is true iff always p is false, which means that p is false at least in one clock tick. This is exactly s_eventually not p. Similarly, not s_eventually p is always not p.

Discussion: For a Boolean expression e, not always e may be rewritten as s eventually !e and not s eventually e as always !e.

Example 4.18. Reset rst must be asserted during the first two cycles.

Solution:

```
initial al:
   assert property (@(posedge clk) rst and nexttime rst);
```

Discussion: Note that rst && nexttime rst is syntactically illegal: && expects both of its operands to be Boolean expressions, while nexttime rst is a property, but not a Boolean expression.

A more elegant way to write the same property is described in Sect. 5.5.

⁷ Even though && is a short circuit operator (that is, its second operand is not evaluated if the first operand is evaluated to false), and **and** is not, there is no difference between them in this case, since expressions used in assertions cannot have side effects. See Sect. 4.1.

⁸ The difference may not be observable in simulation depending on whether the simulator takes into account the strength of properties at the end of simulation. **not** e is a strong property, while !e is weak.

4.6 Until Property

Example 4.19. What is the meaning of (always p) and (always q)?

Solution: According to the definition of property and this property is true iff both p and q hold in each clock tick, that is, the original property is equivalent to always (p and q).

Discussion: (always p) or (always q) is not equivalent to always (p or q). Consider a case when p holds in all odd clock ticks, and q holds in all even ticks. Then always (p or q) is true, whereas (always p) or (always q) is false.

4.6 Until Property

Property p until q is true in clock tick i iff p is true in every clock tick $j \ge i$ until, but not including, the first clock tick $k \ge i$ where q is true. If there is no such k, p should be true in all clock ticks $j \ge i$.

It follows that property p until q is *true* iff the property p is true in every clock tick until (but not including) the first clock tick where q is true. See Fig. 4.5. If q never happens p should be true forever.

Note that p until q does not mean that p cannot be true starting from the clock tick when q becomes true. It only means that p does not have to be true after q becomes true for the first time. Also, the operator until is nonoverlapping: p does not have to be true when q becomes true for the first time (though, of course, p may be true at this moment).


There is also an *overlapping* version of until called until_with. The only difference between until and until_with is that for until_with to be true p *must* be true at the moment q becomes true for the first time, as stated in the following definition:

Property p until_with q is true iff the property p is true in every clock tick until (and including) the first clock tick where q is true. See Fig. 4.6. If q never happens p should be true forever. We leave the definition of the truth of property until with in clock tick i as an exercise to the reader.

p until with q is equivalent to p until (p and q). (Why? See Exercise 4.8.)

Example 4.20. Table 4.2 contains an initial trace fragment of signals a, b, c, d, and e.

- a until b is true since b is true in clock tick 0.
- a until c is true since a is true in clock tick 0, and c is true in clock tick 1.



112 4 Basic Properties

Table 4.2 Initial trace fragment for Example 4.20

Clock tick	a	b	С	d	е
0	1	1	0	0	0
1	1	1	1	0	0
2	0	1	0	1	0
3	0	0	1	1	1

- a until d is true since a is true in clock ticks 0 and 1, and d is true in clock tick 2.
- a until e is false since a is false in clock tick 2, and e is false in clock ticks 0, 1, and 2.
- b until with a is true since both a and b are true in clock tick 0.
- b until_with c is true since b is true in the clock ticks 0 and 1, and c is true in clock tick 1.
- b until_with e is false since b is false in clock tick 3, and e is false in clock ticks 0, 1, and 2.

Example 4.21. ready should be low until rst becomes inactive for the first time.

Solution:

```
initial a1: assert property(@(posedge clk) !ready until !rst);
```

Example 4.22. There cannot be a read before the first write:

Solution:

```
initial
```

```
a2: assert property (@(posedge clk) !read until_with write);
```

Exercises

- **4.1.** Write a restriction saying that initially all bus drivers are disconnected (have a high impedance value).
- **4.2.** Write the following assertion: rdy should be low while rst is active.
- **4.3.** What do the following properties mean?
- (a) always nexttime always p
- (b) nexttime always nexttime p
- **4.4.** Discuss the usage of the always operator in assertions.

4.6 Until Property 113

4.5. What is the meaning of the following assertion (note that it does not belong to an initial procedure)?

```
al: assert property (@(posedge clk) s eventually always !rst);
```

- **4.6.** What is the meaning of the following properties?
- (a) s eventually nexttime p
- (b) nexttime s eventually p
- (c) s eventually nexttime always p
- (d) always nexttime s_eventually p
- **4.7.** What do the following properties mean?
- (a) 1 until q
- (b) p until 1
- (c) 0 until q
- (d) 0 until_with q
- (e) p until 0
- (f) nexttime (p until q)
- (g) (nexttime p)until q
- (h) p until nexttime q
- (i) p until with nexttime q
- (j) p1 until (p2 until p3)
- (k) p1 until with (p2 until with p3)
- (l) always (p until q)
- (m) (always p)until q
- (n) p until always q
- (o) p1 until (p2 until always p3)
- **4.8.** Prove that p until with q is equivalent to p until (p and q).

Chapter 5 Basic Sequences

A sequence works in a way a collection never can.

- George Murray

In Chap. 4, we showed how to build complex properties from the elementary building blocks. We considered Boolean properties as the simplest building block. SVA provides sequences as more elaborate building blocks for properties. Since the simplest sequence is a Boolean expression, we could say that properties are built not from Boolean expressions, but from sequences.

Sequence is a rule defining a series of values in time. A sequence does not have a truth value, it has one initial point and zero or more *match*, or *tight satisfaction* points. Like properties, sequences are clocked. If the clock is not written explicitly, we assume that the sequence inherits this clock from the property to which it belongs. When a sequence is applied to a specific trace, it defines zero or more *finite* fragments on this trace starting at the sequence initial point and ending in its tight satisfaction points. We will call the length of a trace fragment defined by a sequence match simply the length of the sequence match. In the following sections, we define the sequence match separately for each kind of a sequence. Before we proceed to the accurate definitions, we informally illustrate the notion of a sequence on the following example.

Example 5.1. Sequence a ##[1:2] b defines the following scenario: a is followed by b in one or two clock ticks. Let the initial point of this sequence be clock tick 2. Then this sequence has a match if a is true in clock tick 2 and either b is true in clock tick 3 or b is true in clock tick 4. Thus, the following matching outcomes are possible:

- 1. a is false in clock tick 2 or b is false in clock ticks 3 and 4. In this case, the sequence has no match.
- 2. a is true in clock tick 2, b is true in clock tick 3, and b is false in clock tick 4. In this case, the sequence has a single match at clock tick 3.
- 3. a is true in clock tick 2, b is false in clock tick 3, and b is true in clock tick 4. In this case, the sequence has a single match at clock tick 4.
- 4. a is true in clock tick 2 and b is true in clock ticks 3 and 4. In this case, the sequence has two matches, or two tight satisfaction points: 3 and 4.

5 Basic Sequences

Sequence a ##[1:2] b defines 0, 1, or 2 trace fragments. In case 1 it defines zero fragments, in case 2 it defines one fragment, 2:3, in case 3 it also defines one fragment, 2:4, and in case 4 it defines two fragments, 2:3. and 2:4.

In this chapter, we use the following conventions: letters a, \ldots, e denote Boolean expressions, r and g denote sequences, and g and g denote properties. We numerate clock ticks with integer numbers starting with 0. In diagrams, we designate trace fragments defined by sequence matches with ovals.

The sequence and property operators described in this chapter are summarized in Table 5.1. They are grouped by their precedence, from highest to lowest. Additional sequence operators are covered in Chap. 9.

5.1 Boolean Sequence

Boolean expression e defines the simplest sequence – a *Boolean sequence*. This sequence has a match (or a tight satisfaction point) at its initial point if e is true. Otherwise, it does not have any satisfaction points at all. This is illustrated in Fig. 5.1.

Example 5.2. The initial fragment of the trace of signals a and b is shown in Table 5.2.

Table 5.1 Basic sequence and property operators

Operator	Associativity
[*]	_
[*]	_
[+]	_
##	Left
or	Left
->	Right
=>	Right

Fig. 5.1 Boolean sequence



Table 5.2 Initial trace fragment from Example 5.2

Clock tick	a	b
0	1	1
1	0	0
2	0	1
3	1	1

Boolean sequence a && b matches trace fragment 0:0 if its initial point is 0, and trace fragment 3:3 when its initial point is 3. For initial points 1 and 2 there are no sequence matches.

5.2 Sequential Property

Although a sequence itself cannot be true or false, it is possible to associate with a sequence a *sequential property* (or *sequence property*) in the following way:¹

Sequential property defined by sequence s is true in clock tick i iff there is no finite trace fragment i:j witnessing inability of sequence s with the initial point i to have a match. Sequence s should not admit an empty match (the notion of empty match is explained below in this section).

This definition is applicable only to sequential properties in the context of assertions or assumptions. In the context of cover statements, the definition of sequential property is different, as explained in Chap. 18. Except for Chap. 18 we will assume that in all examples sequential properties are written in the context of assertions or assumptions.

Although it is not easy to understand the full meaning and the rationale of the definition of a sequential property at this point, because we have not yet described the SVA constructs in which all nuances of this definition come into play, we need this definition now to build properties from sequences. We will explain some of its aspects here, while the other aspects will become clear to the reader only later.

Consider the most important special case of this definition: if a sequence has at least one match, then the corresponding sequential property is true. The entire definition is broader since it allows in some cases sequential properties to be true even if their sequences do not have any match. However, if there is some number L>0 such that all matches of sequence ${\tt s}$ have a length ${\tt \le } L$ then if ${\tt s}$ does not have any match then the sequential property ${\tt s}$ is false. Indeed, in this case the fact that sequence ${\tt s}$ does not have any match on a trace fragment of length L witnesses its inability to have any match. We will call such sequences bounded sequences. It is easy to see that all Boolean sequences are bounded, as all their matches are one clock cycle long.

Example 5.3. Sequence a ##[1:2] b informally described in Example 5.1 is bounded.

Solution: This sequence can only have matches of length 2 or 3, and its match upper bound L=3: if this sequence does not have a match on a trace fragment of three clock cycles, it does not have matches at all.

The definition of sequential properties for bounded sequences may be simplified:

 $^{^{1}}$ Actually, there is more than one way to associate a property with a sequence, as explained in Chaps. 8 and 20.

118 5 Basic Sequences

Sequential property corresponding to bounded sequence s is true iff sequence s has at least one nonempty match.

So, what is the nature of *unbounded* sequences? They should admit arbitrary long matches. Examples of unbounded sequences are provided in Sect. 5.10.

Another point to be clarified is the notion of *empty match*. The match is empty if the trace fragment it defines is empty. We will provide examples of empty match in Sects. 5.5.1 and 5.8. Note that a Boolean sequence cannot have an empty match. It either has a match of size 1 if its Boolean expression is true, or it does not have matches at all.

Pay attention to the clock tick where the truth value of a sequential property is defined.

The truth value of sequential property s corresponds to the *initial* point of sequence s, and *not* to the point of its tight satisfaction.

Example 5.4. Let a be true in clock tick 2, and false in all other clock ticks, and be true in clock tick 3, and false in all other clock ticks. Then sequential property a #[1:2] b is true in clock tick 2 (not 3!), and false in all other clock ticks.

Let us apply the definition of a sequential property to a Boolean sequence. Since Boolean sequences are bounded, Boolean sequential property e is true iff Boolean sequence e has a match, that is, when e is true. We come to the conclusion that Boolean sequential properties are exactly Boolean properties we described in Sect. 4.1. Therefore, sequential properties generalize Boolean properties, and it is possible to define all property operators from Chap. 4 apart from arbitrary sequential properties, as we mentioned in the introduction to that chapter.

5.3 Sequence Concatenation

From two sequences r and s, one can build a new sequence r ##1 s by concatenating these two sequences: there is a match of sequence r ##1 s if there is a match of sequence r and there is a match of sequence s starting from the clock tick immediately following the match of r, as shown in Fig. 5.2.

In other words, a finite trace matches r ##1 s iff it can be split into two adjacent fragments, the first one matching r, and the second one matching s. If both operands of sequence concatenation are bounded sequences, its result is also bounded.

Fig. 5.2 Sequence concatenation

Example 5.5. What is the meaning of a ##1 b, where a and b are Boolean expressions?

Solution: Let the initial point be clock tick i. Sequence a ##1 b has a match iff a is true in clock tick i and b is true in clock tick i+1. Sequence a ##1 b may have only one tight satisfaction point, in clock tick i+1. Therefore, this sequence means that b immediately follows a.

Discussion: Tight satisfaction of sequence a ##1 b does not depend on the value of b in clock tick i and on the value of a in clock tick i + 1. Although this looks obvious, this is a source of confusion for many people who *erroneously* believe that for this sequence match b must become true for the first time in clock tick i + 1. \square

Example 5.6. Write a sequence capturing the following scenario: request req, immediately followed by retry rtry, immediately followed by acknowledgment ack.

Solution: req ##1 rtry ##1 ack.

5.3.1 Multiple Delays

We will begin this section with a motivation example.


Example 5.7. Write the following sequence: request req followed by acknowledgment ack in two cycles.

Solution: This description is equivalent to "request, immediately followed by anything, immediately followed by acknowledgment". "Anything in a given clock tick" means a Boolean sequence that has a match in this clock regardless of the values of req and ack. To match, the corresponding Boolean expression should be true. Recall (Sect. 4.1) that true may be expressed with any nonzero known value, for example, value 1. So, the desired sequence may be written as req ##1 1 ##1 ack.

Example 5.7 illustrates a typical situation when two sequences are not adjoining, but there is a constant number of clock ticks between them (Fig. 5.3). There is a special syntax to capture this situation:

```
r ##n s
```

n must be a nonnegative elaboration time integral constant. We will call this interval between two sequences in clock cycles *delay* (not to be confused with the delay operator # in SystemVerilog).



120 5 Basic Sequences

Efficiency Tip Big delay values are inefficient both in simulation and in FV.

Example 5.8. Using this syntax, the sequence from Example 5.7 may be rewritten as req ##2 ack. \Box

5.3.2 Top-Level Sequential Properties

As stated in Sect. 5.2, there is a sequential property associated with each sequence nonadmitting an empty match. With the exception of Boolean sequential properties, top-level sequential properties are relatively rare in assertions and assumptions, and they are normally used to specify reset sequences.²

Example 5.9. Reset rst must be initially high and be low in clock tick 20.

Solution:

```
initial a1: assert property (@(posedge clk) rst ##20 !rst);
```

Discussion: We do not claim anything about the reset behavior in all clock ticks other than 0 and 20. \Box

You should be very careful when using sequential properties in continuously monitored assertions and assumptions since their meaning may be different from your intent, as illustrated by the following examples.

Example 5.10. What does the following assertion mean?

```
al: assert property (@(posedge clk) a ##1 b);
```

Solution: Since this assertion is continuously monitored (has an implicit outermost always operator), sequential property a ##1 b must be true in each clock tick. Hence, a must be true in each clock tick, and b must be true starting form clock tick 1.

Discussion: This assertion does *not* mean interleaving of a and b.


Example 5.11. We want to state that the value of sig toggles every cycle: 0101... or 1010.... The following assertion

```
a1: assert property (@(posedge clk) sig ##1 !sig);
```

does *not* check this condition. Similar to Example 5.10, it means that sig is true in each clock tick, and also that sig is false starting from clock tick 1. Therefore, this assertion is contradictory: it requires that starting from clock tick 1 sig be simultaneously true and false. Example 6.25 explains how to implement this assertion correctly.

² Top-level sequential properties are very common in cover statements, see Chap. 18.

Fig. 5.4 Sequence fusion



5.3.3 Sequence Fusion

Sequence fusion is an overlapping concatenation. The fusion of sequences r and s, denoted as r ##0 s, is matched iff for some match of sequence r there is a match of sequence s starting from the clock tick where the match of r happened (See Fig. 5.4). Note the difference between sequence concatenation r ##1 s and sequence fusion. For sequence concatenation, we start matching sequence s from the next clock tick after a match of r has happened, while for sequence fusion we start matching s from the same clock tick of the match of r.

Example 5.12. What is the meaning of fusion of two Boolean sequences a and b?

Solution: a ##0 b can have a match iff both a and b are true simultaneously. Therefore, a ##0 b is semantically equivalent to a && b. Note, however, that a ##0 b and a && b are not syntactically interchangeable. a ##0 b is a sequence, so it cannot be used as an operand in a Boolean expression. For example, a && b | | c (where c is a Boolean expression) is legal, whereas (a ##0 b) | | c is syntactically illegal.³

Example 5.13. What is the meaning of (a ##1 b) ##0 (c ##1 d), where a, b, c, and d are Boolean expressions?

Solution: Let the initial point of the sequence be clock tick i. Sequence a ##1 b has a match iff a is true in clock tick i and b is true in clock tick i+1. The match of sequence a ##1 b happens in clock tick i+1. Therefore, for the fusion to have a match, sequence c ##1 d should have a match starting from clock tick i+1. It means that c should be true in clock tick i+1, and d should be true in clock tick i+2. Bringing it all together, we have that sequence (a ##1 b) ##0 (c ##1 d) is equivalent to sequence a ##1 b && c ##1 d.

Example 5.14. Write a sequence describing two back-to-back transactions. The transactions are represented with sequences trans1 and trans2.

Solution: Consider two interpretations:

- trans2 starts in the clock tick when trans1 finishes.
- trans2 starts in the clock tick next to the endpoint of trans1.

The first scenario may be expressed as trans1 ##0 trans2, while the second scenario may be expressed as trans1 ##1 trans2.

We will provide more examples of sequence fusion in the following sections.

³ Also && is not the same as ##0 when match items are attached to the first sequence, see Chap. 16.

122 5 Basic Sequences

Fig. 5.5 ##3 s

5.3.4 Initial Delay

We will start this section with a motivation example:

Example 5.15. Skip n > 0 cycles before matching sequence s.

Solution: 1 ##n s. Recall that value 1 means true, matching anything at the initial clock tick of the resulting sequence.

The situation described in Example 5.15 is typical, and for convenience there is a special syntax to specify the number of clock ticks to be skipped before beginning a sequence match (Fig. 5.5), i.e., to specify *initial sequence delay*: ##n s. The delay in the number of clock ticks must be a nonnegative elaboration time constant. Our definition works for nonzero n. The case of n = 0 is considered in Sect. 5.9.

Efficiency Tip Large initial delays are inefficient in FV, and may also negatively affect simulation performance. See Sect. 19.3 for details.

Example 5.16. The value of a should be always true starting from clock tick 2.

Solution:

```
al: assert property (@(posedge clk) ##2 a);
```

Discussion: The same intent may be expressed using property operator nexttime:

```
a2: assert property (@(posedge clk) nexttime[2] a);
```

5.4 Suffix Implication

In Sect. 5.2, it was shown how properties may be built from sequences by promoting sequences to sequential properties. There are additional ways to build properties from sequences, the most important one being the *suffix implication*. A suffix implication is built from a sequence (s) and a property (p). s is called *antecedent*, and p is called *consequent*. Suffix implication is true when its consequent is true upon completion of its antecedent. Below we provide a more accurate definition.

There are two versions of suffix implication: *overlapping*, denoted as s |-> p, and *nonoverlapping*, denoted as s |=> p. In the overlapping implication the consequent is checked starting from the moment of *every* nonempty match of the antecedent. In the nonoverlapping implication the consequent is checked starting from the next clock tick after the antecedent match.

Nonoverlapping implication $s \mid -> p$ is *true in clock tick i* iff for *every* tight satisfaction point $j \geq i$ of s with initial point i, property p is true in clock tick j. For each match of the antecedent, the consequent is separately evaluated. According to the property truth definition from Sect. 4.1, property $s \mid -> p$ is true iff it is true in clock tick 0.

Nonoverlapping implication s |=> p is defined as

(s $\#\#1 @\$global_clock 1) | -> p$. The meaning of this defintion is explained in Chap. 12. For singly clocked assertions, this definition may be simplified:

```
s ##1 1 |-> p.
```

We want to stress that both overlapping $s \mid -> p$ and nonoverlapping $s \mid -> p$ implications and their consequent p are *properties*, whereas their antecedent is a *sequence*, and it is *not* promoted to sequential property.

Except for Boolean assertions, suffix implication is the most common way of building assertions. Antecedent s represents a *triggering condition*: when this condition holds, consequent p is checked. The suffix implication is very often used with stand-alone assertions (having an implicit outermost always operator) – the antecedent defines "interesting" attempts where we want to check the consequent.

Example 5.17. When rdy is asserted rst must be low.

Solution: We can use the overlapping implication. When rdy is true, Boolean sequence rdy has a match. At this point we need to check a Boolean property stating that rst is false:

```
al: assert property (@(posedge clk) rdy |-> !rst);
```

Discussion: When both antecedent and consequent are Boolean, the suffix implication is equivalent to the logical implication:

```
a2:assert property (@(posedge clk) rdy -> !rst);
```

Of course, it is illegal to use a suffix implication in a Boolean expression. Logical implications may be used in all kinds of assertions: immediate, deferred, and concurrent, while suffix implications are allowed in concurrent assertions only.

Example 5.18. done must be asserted in the next clock tick after sent has been asserted.

Solution: This assertion means that if in some clock tick sent has been asserted then at the next clock tick done should be asserted. There are several possibilities to divide this property into an antecedent and a consequent. We can say that the antecedent is sent, and the consequent is done starting from the next clock tick. The resulting assertion will be:

```
a1: assert property(@(posedge clk) sent |-> nexttime done);
```

The same intent may be expressed using sequential property in the consequent:

```
a2: assert property(@(posedge clk) sent |-> ##1 done);
```

We can move the delay into the antecedent to get the same effect:

```
a3: assert property(@(posedge clk) sent ##1 1 | -> done);
```

124 5 Basic Sequences

Note that assertion

```
a4_illegal: assert property(
  @(posedge clk) sent nexttime 1 |-> done);
```

is *illegal* since the antecedent of a suffix implication is a sequence, not a property, and using property operator nexttime is forbidden in sequences.

Of course, the best way to implement the same assertion is using non-overlapping implication as shown below.

```
a5: assert property(@(posedge clk) sent |=> done);
```

Assertion a5 is equivalent to assertion a3 by the definition of the nonoverlapping implication.

Example 5.19. In Example 5.18 we showed that it is possible to move a unit delay from antecedent to consequent and vice versa when the first operand in the consequent (or the last one in the antecedent) is 1. However, in the case of an arbitrary operand this is wrong. For example, property write ##1 done |=> read means that if done follows write then read must be asserted in the next clock tick after done. If there is no done after write the property passes. Property write |=> done ##1 read means a different thing: each write must be followed by a series of done and read. If there is no done after write the property fails. \Box

Example 5.20. If there is no acknowledgment ack within three clock ticks after request req was issued, request req must be resent unless an error indicator err is set.

Solution: From this formulation it is not clear when the request should be resent exactly: in three or in four clock ticks? We will consider both cases (assertions al and a2) differing by the type of the implication:

```
al: assert property (@(posedge clk)
  req ##1 !ack[*3] |-> req || err);
a2: assert property (@(posedge clk)
  req ##1 !ack[*3] |=> req || err);
```

The corresponding timing diagrams are shown in Figs. 5.6 and 5.7.




Fig. 5.6 Overlapping implication




Fig. 5.7 Nonoverlapping implication

5.4.1 Nested Implication

Suffix implications can be nested as illustrated in the following example.

Example 5.21. If start is asserted two clock ticks before send, then acknowledgment ack should arrive in three clock ticks after send was asserted.

Solution: This assertion means that if start is asserted and if two clock ticks later send is asserted, then in three clock ticks after send was asserted, ack must be asserted. This can be directly mapped into nested implications:

```
a1: assert property (@(posedge clk)
  start |-> ##2 send |-> ##3 ack);
```

Discussion: Nested suffix implication is unambiguous: the antecedent of the outermost implication is start, and not start |-> ##2 send because the latter expression is a property, and not a sequence, whereas the antecedent must be a sequence.

The same assertion may be reformulated in the following way: each time send is issued two cycles after start, ack should arrive three cycles after send, and rewritten as

```
a2: assert property (@(posedge clk) start ##2 send |-> ##3 ack);
```

Both forms are equivalent. Usually the form with a single implication is more intuitive than the one with nested implications, and it is easier to debug.

The rule of transforming nested implications works with appropriate modifications for any initial delays in the consequent. For example, $r \mid => p$ is equivalent to $r \# 1 s \mid => p$, and $r \mid -> s \mid -> p$ is equivalent to $r \# 0 s \mid -> p$.

5.4.2 Examples

In this section, we provide several important examples illustrating use of various sequence and property operators combined with suffix implication.

126 5 Basic Sequences

Example 5.22. Request req should be active until grant is asserted.

Solution: This assertion may be formulated as "Whenever the request is high, it should remain high until (not including) grant is asserted":

```
al: assert property(@(posedge clk) req |-> req until grant);
```

Discussion: If the request should remain asserted also in the first clock tick when the grant is asserted the assertion should be modified as:

```
a2: assert property(@(posedge clk) req |-> req until_with grant);
```

Efficiency Tip Boolean antecedents in suffix implication are efficient in FV, but they may be not very efficient in simulation when the consequent requires a long time for its completion. See Chap. 6 and Sect. 19.3 for a detailed discussion.

Example 5.23. Request req must be granted. This assertion means that each time request req is high, grant gnt should be high in some clock tick in the future.

Solution:

```
a1: assert property (@(posedge clk) req |=> s eventually gnt);
```

Discussion: This assertion does not distinguish between grants to different requests. For example, there may be the same grant for several requests, as shown in Fig. 5.8. This example reflects the fact that the normal semantics of assertions is global, and not pipelined: there is no easy way to distinguish between different attempts (transactions) of the same assertion. The pipelined semantics in our case means that each request should have its own grant. Chapter 15 explains how to implement pipelined semantics in assertions using local variables.

Example 5.24. After request req has been sent, acknowledgment ack should come before data (data ready).

Solution:

```
a1: assert property (@(posedge clk)
  req |-> !data_ready until_with ack);
```




Fig. 5.8 Two requests corresponding to the same grant

Discussion: In this implementation, the acknowledgment is allowed to be issued in the same clock tick as the request; see Exercise 5.5 for the case when the acknowledgment is expected to come strictly after the request. If the request is never granted – there is neither acknowledgment nor data – the assertion passes.

5.4.3 Vacuous Execution

The definition of the suffix implication states that the consequent is checked starting from the moment of *every* nonempty match of the antecedent. It follows that in the case when the antecedent does not have a match, the suffix implication holds. This case is called *vacuous execution* of the implication.

If an assertion is continuously monitored, it is natural that many of its attempts terminate vacuously. For instance, if in Example 5.22 each attempt is nonvacuous then the request is always active, which is not likely to happen in practice. But if all the assertion attempts pass vacuously, it indicates a serious problem in validation. What would you say about a civil engineer who constructed a bridge, and to the question "Will this bridge withstand if a heavy truck crosses it?" he will answer "Of course, it will. There was no truck crossing it until now, and the bridge hasn't collapsed yet"?

There exist different definitions of vacuity [11,29], the LRM provides a minimal set of rules that the tools are expected to check. We are not going to provide the entire list of vacuous scenarios in this book. The main source of the vacuous execution for assertions is the case we described: when the antecedent is false. Chapter 8 provides further details on vacuity.

Example 5.25. Property ok |->!err passes vacuously iff ok is false. But the equivalent property err |->!ok passes vacuously iff err is false. Therefore, the assertion vacuity depends on the exact style it is written.

5.5 Consecutive Repetition


We will begin this section with a motivation example.

Example 5.26. Write a sequence stating that a transmission phase lasting three consecutive cycles is followed by a receiving phase lasting two consecutive cycles. The transmission phase is represented by signal trn, and the receiving phase is represented by signal rcv

```
Solution: trn ##1 trn ##1 trn ##1 rcv ##1 rcv.
```

Discussion: This sequence defines a trace fragment of 5 clock cycles such that in the first three cycles trn is true, and in the last two cycles rev is true. For example, trn may also be true in the fourth or the fifth cycle of the fragment, and also in any clock cycle outside this trace fragment.

128 5 Basic Sequences



The sequence from Example 5.26 looks verbose, but the situation it describes is typical. In SVA, there is a special operator to denote a *consecutive repetition* of a sequence s n times, where n is a nonnegative elaboration time constant: s[*n] (see Fig. 5.9).

Example 5.27. Using the shortcut notation for the consecutive repetition, the sequence from Example 5.26 may be rewritten as trn[*3] ##1 rcv[*2].

Example 5.28. Assertion from Example 4.18 "Reset rst must be asserted during first two cycles" may be more elegantly expressed using sequences:

```
initial a1: assert property (@(posedge clk) rst[*2]);
```

Example 5.29. Signal sig remains high during 5 cycles.

Solution:

```
al: assert property (@(posedge clk) !sig ##1 sig |=> sig[*4]);
```

Discussion: This assertion states that once the signal goes high it remains high during 4 additional clock ticks. It does not forbid the signal to stay high for longer time. See Exercise 5.6 for an alternative interpretation.

5.5.1 Zero Repetition

It is possible to define a *zero repetition* of sequences: sequence s[*0] is a sequence admitting only an empty match. In other words, sequence s[*0] matches on any trace, but the trace fragment it defines is empty – it does not contain any clock tick. Because of this characteristic of zero repetition, it is also called *empty sequence*. Empty sequence is a strange creature, its behavior significantly differs from the behavior of "normal" sequences. It is rarely written explicitly, but its implicit use in delay and repetition ranges is rather common, therefore it is extremely important to understand its behavior. The meaning of empty sequence concatenation and fusion is not obvious, and it is clarified below.

The empty sequence cannot be promoted to a sequential property, as the definition of sequential property in Sect. 5.2 excludes sequences admitting an empty match. Thus, assertion assert property (@(posedge clk)s[*0]); is illegal.

5.5.1.1 Concatenation with Empty Sequence

In this section, we will clarify the meaning of sequence $r[\star 0]$ ##1 s. Let the initial point of the resulting sequence be clock tick i. According to the definition of sequence concatenation (Sect. 5.3), $r[\star 0]$ ##1 s has a match in clock tick $j \geq i$ iff the interval i:j may be split into two consecutive parts, the interval where sequence $r[\star 0]$ has a match and the interval where sequence s has a match. Since $r[\star 0]$ matches an empty trace fragment, the match of sequence $r[\star 0]$ ##1 s coincides with the match of sequence s. In other words, $r[\star 0]$ ##1 s is equivalent to s. Similarly, r ##1 s[$\star 0$] is equivalent to r.

Concatenation with an empty sequence clarifies the semantics of sequence concatenation operator ##1.

r ##1 s does *not* mean "skip one clock tick after match of r and then match s", but "start matching s after match of r".

5.5.1.2 Fusion with Empty Sequence

In this section, we will clarify the meaning of sequence r[*0] ##0 s. According to the definition of sequence fusion (Sect. 5.3.3), the match of sequence r[*0] ##0 s requires the clock tick of the match of r[*0] be the first clock tick of sequence s. Since r[*0] does not match any positive number of clock ticks, a match of sequence r[*0] ##0 s is impossible. Similarly, sequence r[*0] so cannot be matched, either. Therefore, a fusion with an empty sequence does not have a match.

This result reveals a very important fact:

Sequence fusion never admits an empty match.

5.5.1.3 Empty Sequence in Antecedent

What happens when the antecedent of a suffix implication is an empty sequence? In case of the overlapping implication $s[*0] \mid -> p$, its antecedent does not have nonempty matches, and according to the definition of the overlapping implication, $s[*0] \mid -> p$ trivially holds (is a tautology).

The situation with the nonoverlapping implication is completely different. According to its definition, $s[*0] \mid => p$ is equivalent to $s[*0] \#1 \ 1 \mid -> p$, which is, in its turn, equivalent to $1 \mid -> p$ (see Sect. 5.5.1.1). The latter is equivalent to p.

130 5 Basic Sequences

Although it is rarely used in its pure form, this pathological behavior of the empty sequence in antecedents is important to understand the semantics of more complex antecedents admitting empty matches, described in Sect. 5.8.1.

5.6 Sequence Disjunction

Sequence disjunction r or s is a sequence which has a match whenever either r or s (or both) have a match.

Boolean Disjunction For Boolean expressions a and b sequence a **or** b has a match iff a | | b is true. Therefore, in case of Boolean values, a sequence disjunction behaves as a logical disjunction.

Sequence Disjunction versus Property Disjunction Sequence disjunction and property disjunction have exactly the same syntax. The following rule shows how they are distinguished: if both r and s are sequences then r or s is a sequence disjunction, otherwise, it is a property disjunction. For example, the formula (a # 1 b) or # 1 c is a sequence disjunction, and (a # 1 b) or nexttime c is a property disjunction. In the context where both sequences and properties may appear, the exact decision is not important since in this case both definitions yield equivalent results. Why?

Example 5.30. There are two types of transactions: the read transaction when read request read is followed by data_ready in three cycles and the write transaction, when write request write is followed by done. Write a sequence representing a generic transaction.

Solution: The sequence representing the read transaction is read ##3 data_ready, the sequence representing the write transaction is write ##1 done. The generic transaction is their disjunction read ##3 data ready or write ##1 done.

Multiple Matches All sequences we considered until now could have at most one match. Sequence disjunction introduces sequences that can have multiple matches.

Example 5.31. Sequence a [\star 2] or b[\star 3] may have 0, 1, or 2 matches.

5.7 Consecutive Repetition Revisited

In Sect. 5.5, we introduced consecutive repetition with factors $n \ge 0$. The rules of building consecutive repetition may be summarized as follows:

• s[*0] is an empty sequence.

• s[*n], where n > 0 is defined recursively:

```
s[*n] \equiv s[*n-1] ##1 s.
```

In this section, we will define repetition ranges.

5.7.1 Repetition Range

Instead of a fixed number of repetitions one can specify a repetition range: finite s[*m:n] and infinite s[*n:\$]. m and n should be elaboration time constants, $m \le n$, and n stands for an "infinite number".

5.7.1.1 Finite Repetition Range

Consider an example of a finite repetition range first. What is the meaning of sequence $s[\star 2:4]$? Intuitively, it means that sequence s is repeated from 2 to 4 times. More formally, $s[\star 2:4]$ has a match iff either $s[\star 2]$ has a match, or $s[\star 3]$, or $s[\star 4]$ has a match. That is, $s[\star 2:4]$ is equivalent to $s[\star 2]$ or $s[\star 3]$ or $s[\star 4]$. This leads us to the following recursive definition:

```
s[*n:n] \equiv s[*n].

s[*m:n] \equiv s[*m:n-1] or s[*n], m < n.
```

Efficiency Tip Big repetition factors, and ranges with big finite upper bound are inefficient both in simulation and in formal verification.

5.7.1.2 Infinite Repetition Range

Consider now an example of an infinite repetition range: intuitively s[*1:\$] means that s happens one or more times. Following the definition of finite repetition range we would like to define s[*1:\$] as s or s[*2] or s[*3].... Unfortunately, such a definition does not work as it produces an infinite formula. Therefore, we need to define s[*1:\$] directly.

Let the initial point of sequence s[*1:\$] be clock tick i. Sequence s[*1:\$] has a tight satisfaction point (match) $j \geq i$ iff there is some number n > 0 such that j is the tight satisfaction point of sequence s[*n]. In other words, sequence s[*1:\$] is tightly satisfied on trace fragment i:j if it is possible to divide this trace fragment into one or more consecutive fragments so that each such fragment tightly satisfies s.

After we have defined infinite repetition range [*1:\$] we can define any infinite repetition range as follows:

```
s[*0:\$] \equiv s[*0] or s[*1:\$].

s[*n:\$] \equiv s[*0:n-1] or s[*1:\$], n > 1.
```

132 5 Basic Sequences

s[*n:\$] does *not* mean that sequence s is repeated infinitely many times, but that it is repeated n or more (finite) number of times.

There are shortcuts s[*] provided for s[*0:\$] (zero or more times), and s[+] for s[*1:\$] (one or more times) that we will widely use.

Example 5.32. Describe a transaction as a sequence. A transaction starts with Begin Of Transaction signal (bot) and ends with End Of Transaction signal (eot). Each transaction is at least two cycle long and transactions cannot overlap.

Solution: Since the transaction is at least two cycle long, bot and eot of the same transaction cannot be asserted in the same clock cycle. The fact that transactions cannot overlap means that between bot and the next eot there are no other occurrences of bot. We allow bot of the next transaction occur in the same clock cycle with eot of the previous transactions. Transactions should also be wellformed, therefore no two eot should occur without bot occurrence between them. Therefore, the sequence describing the transaction is

```
bot ##1 (!bot && !eot)[∗] ##1 eot. □
```

Example 5.33. Write the following assertion: rdy becomes asserted the first time when the reset sequence is over. The reset sequence is represented by the high value of rst.

Solution:

```
initial a1: assert property (@(posedge clk)
  rst && !rdy [*] ##1 !rst && rdy);
```

Discussion: The same assertion may be more intuitively rewritten using property operator until:

```
initial a2: assert property (@(posedge clk)
  rst && !rdy until !rst && rdy);
```

Example 5.34. We revisit Example 4.21: ready should be low until rst becomes inactive for the first time.

Solution: This time we are going to implement this assertion using sequences:

```
initial assert property(@(posedge clk) !ready[*] ##1 !rst);
```

Discussion: In this case, the property operator until may be implemented as a sequential property (see also Example 5.33). If a is a Boolean and s is a sequence, a until s is equivalent to sequential property a[*] ##1 s in the assertion or assumption context. However, in the common case r until s and the sequential property r[*] ##1 s are not equivalent. To understand this, compare (a ##1 b) [*] ##1 c and a ##1 b until c for values of a, b, and c shown in

Table 5.3 Initial trace fragment in Example 5.34

Clock tick	a	b	C
0	1	0	0
1	1	1	0
2	0	0	1

Table 5.3. Sequence (a ##1 b) [*] has a match in clock tick 1, therefore sequence (a ##1 b) [*] ##1 c has a match in clock tick 2, and the corresponding sequential property passes. Sequential property a ##1 b is false in clock tick 1 (recall that the truth value of a sequential property relates to the initial point of its sequence), while c is true the first time in clock tick 2. Therefore, property a ##1 b until c fails.

Example 5.35. When the first operand of until_with is an integral expression, and the second one is a sequence, a until_with s may be implemented with sequential property a[*] ##0 s.

Efficiency Tip Infinite repetition ranges may be inefficient in simulation. Their efficiency is explained in detail in Sect. 19.3. Infinite repetition ranges are efficient in FV if their lower bound is small.

Previous examples show that sequence and property operators are in some cases interchangeable in assertions. In such cases, it is a matter of style or of simulator efficiency, which solution to choose. The sequence operators are often more concise, but in many cases property operators are more readable. Sequence operators are more flexible as they can appear in both sequences and properties, whereas property operators may appear only within another property or assertion. On the other hand, property operators are more generic, as they can have both sequences and properties as their operands, while sequences may only have sequence (or Boolean) arguments. This fact makes property-based implementation more suitable for assertion libraries.

We will end this section with an example illustrating some semantics subtlety of the use of infinite repetition range in the antecedent.

Example 5.36. What does the following assertion mean?

```
a1: assert property (@(posedge clk) a[+] |-> p);
```

Solution: For each evaluation attempt a1 checks that when there is a continuous series of a, property p holds. For example, if there is a series aa at the beginning of some attempt, p should hold in the first two clock ticks of this attempt. But checking p in the second clock tick of this attempt is redundant: it will be checked in the first clock tick of the next attempt. Therefore, the original assertion is equivalent to

```
a2: assert property (@(posedge clk) a |-> p);
```

Discussion: There should be no difference between the efficiency of a1 and a2 in FV, but a2 is extremely inefficient in simulation. \Box

Efficiency Tip Never implement the property s |-> p as s [+] |-> p.

134 5 Basic Sequences

5.8 Sequences Admitting Empty Match

Sequences admitting an empty match introduce many subtle points that should be well understood. Unlike other sequences, *sequences that admit an empty match cannot be promoted to properties* according to the definition of sequential property (Sect. 5.2). One such sequence is an empty sequence described in Sect. 5.5.1. The empty sequence is rarely used explicitly, but it is often used implicitly as part of other sequences, for example, in repetition ranges of the form [*] or [*0:n]. In this section, we provide several examples illustrating a peculiar behavior of sequences admitting an empty match.

Example 5.37. The following assertion is illegal:

```
assert property (@(posedge clk) a[*]);
```

The reason is that in this assertion the sequence a[*] is promoted to a property while it admits an empty match.

Example 5.38. Sequence a ##1 b[*0:2] ##1 c matches traces ac, abc, and abbc. Note that in the trace ac there is no gap between a and c: b[*0] does not have any duration in time! \Box

Example 5.39. Sequence a[*] ##0 b[*] is equivalent to a[+] ##0 b[+], since the sequence fusion does not admit an empty match (Sect. 5.5.1).

Discussion: a[*] ##1 b[*] is not equivalent to a[+] ##1 b[+].

5.8.1 Antecedents Admitting Empty Match

Sequences admitting an empty match have many subtle points when they are used as antecedents. We will illustrate their behavior on sequence a [*]. Other sequences admitting an empty match exhibit a similar behavior. Consider overlapping implication a [*] |-> p first. According to the definition of zero-or-more repetition (Sect. 5.7.1.2), it is equivalent to a [*0] or a [*] |-> p. All nonempty matches of the antecedent are matches of a [*], and therefore a [*] |-> p is equivalent to a [*] |-> p. Therefore, it is possible to limit antecedents of overlapping implications with sequences that do not admit an empty match. The sequences admitting empty matches add nothing new in this case. 4

Now consider nonoverlapping implication a[*] = p. It can be rewritten as (a[*0] or a[+]) # 1 + p, which is equivalent to (a[*0] # 1) or (a[+] # 1) - p (see Exercise 5.2). The first disjunct of the antecedent is equivalent to 1, and the whole property can be reduced to p (see Sect. 5.5.1.1). Therefore, in the nonoverlapping implication the antecedents

⁴ Of course, with the exception of the empty sequence, which has only the empty match.

admitting an empty match are *completely redundant* when the assertion is continuously monitored. To summarize, antecedents admitting an empty match in suffix implications usually indicate a problem in the assertion.

Never use antecedents admitting an empty match in suffix implication.

Note also that in case of antecedents admitting an empty match, the transformation described in Example 5.18 is not valid. For example, s[*0] ##1 1 |-> p (i.e., 1 |=> p) is p, but s[*0] |-> nexttime p is a tautology.

5.9 Sequence Concatenation and Delay Revisited

In Sect. 5.3, we introduced sequence concatenation operators with factors $n \ge 0$. The rules of building sequence concatenation may be summarized as follows:

- r ##0 s is a sequence fusion.
- r ##1 s is a sequence concatenation.
- r ##n s, where n > 1 is defined recursively:

```
r ##n s \equiv r ##1 1[*n-1] ##1 s.
```

We also defined there initial delay operators with factors n > 0. Now we can provide a definition for any factor n > 0:

```
##n s \equiv 1[*n] ##1 s.
```

According to this definition ##0 s is equivalent to s (why? see Sect. 5.5.1.1), which is intuitive, as ##0 s means "wait 0 clock ticks before the sequence beginning".

Similar to consecutive repetition ranges (Sect. 5.7.1), it is possible to specify *delay ranges*, finite or infinite, between two sequences, as follows:

```
 \begin{array}{l} r \ \#\#[0:0] \ s \equiv r \ \#\#0 \ s. \\ r \ \#\#[m:n] \ s \equiv (r \ \#\#1 \ 1[\star m-1:n-1] \ \#\#1 \ s), where \ n \geq m > 0. \\ r \ \#\#[0:n] \ s \equiv (r \ \#\#0 \ s) \ or \ (r \ \#\#[1:n] \ s), where \ n > 0. \\ r \ \#\#[m:\$] \ s \equiv (r \ \#\#1 \ 1[\star m-1:\$] \ \#\#1 \ s), where \ m > 0. \\ r \ \#\#[0:\$] \ s \equiv (r \ \#\#0 \ s) \ or \ (r \ \#\#[1:\$] \ s), where \ n > 0. \\ \end{array}
```

Informally speaking r # [m:n] s means that there are m to n clock ticks between the tight satisfaction point of r and the initial point of s. r # [m:s] s means that there are m or more clock ticks between the tight satisfaction point of r and the initial point of s. As in the case with consecutive repetition there is a short-cut r # [*] s for r # [0:s] s ("zero or more clock ticks"), and r # [+] s for r # [1:s] s ("one or more clock ticks").

It is also possible to define *initial delay ranges*:

```
##[m:n] s \equiv 1 ##[m:n] s, where n \geq m \geq 0.
##[m:$] s \equiv 1 ##[m:$] s, where m \geq 0.
```

136 5 Basic Sequences

Informally speaking ##[m:n] s means skipping from m to n clock ticks before the initial point of n, and ##[m:n] s means skipping n or more clock ticks before the initial point of n. As usual, there is a shortcut ##[*] s for ##[0:n] s ("zero or more clock ticks"), and ##[*] s for ##[1:n] s ("one or more clock ticks").

Efficiency Tip Big delay factors, and ranges with big finite upper bound are inefficient both in simulation and in FV. Infinite delay ranges may also be inefficient in simulation. Their efficiency is explained in detail in Sect. 19.3. Infinite delay ranges are efficient in FV if their lower bound is small.

Example 5.40. Write a sequence describing the scenario when ready is asserted at the end of the transaction (signal etrans asserted) or in the next clock tick after it.

```
Solution: trans ##[0:1] ready
```

Example 5.41. Write the following sequence: grant gnt asserted from two to four clock ticks after request req was asserted.

```
Solution: req ##[2:4] qnt
```

Discussion: If the initial point is 0, this sequence means: req is true in clock tick 0, and gnt is true either in clock tick 2, 3, or 4. It does not say anything about req behavior after clock tick 0: req does not have to be deasserted there, though it can be. Neither does this sequence claim that gnt is false in clock ticks 0, 1, 5,

Example 5.42. Request req must be granted (grant gnt should be asserted) within 5 clock ticks.

Solution:

```
al: assert property (@(posedge clk) req |-> ##[1:5] qnt);
```

Discussion: In this example, it is also possible to have one gnt issued for several requests, as shown in Fig. 5.8.

Example 5.43. The device should become ready (ready asserted) from 10 to 12 cycles after power-on.

Solution:

```
initial a1: assert property (@(posedge clk) ##[10:12] ready);
```

Discussion: This assertion states that ready is asserted either in clock tick 10, 11 or 12. It does not state that ready must be continuously asserted in clock ticks 10, 11 and 12. It neither states that ready cannot be asserted before clock tick 10.

Example 5.44. Write a sequence describing a scenario when request req is granted (ant is received).

Solution: This means that gnt is asserted in one or more clock ticks after req: req #[+] gnt.

Example 5.45. Write a sequence describing a scenario when request req is granted (gnt) in two or more cycles.

```
Solution: req ##[2:$] gnt.
```

Discussion: This sequence does not specify that there be no grant in clock tick 1, it just requires at least one grant to happen in two or more clock ticks. \Box

Example 5.46. What is the meaning of the following assertion?

```
initial a1: assert property (@(posedge clk) ##[*] s |-> p);
```

Solution: According to the definition of the overlapping implication, at each tight satisfaction point of sequence ##[*] s property p should be true. This is equivalent to the requirement that p is true starting at all tight satisfaction points of sequence s with initial points 0, 1, Therefore, assertion a1 is equivalent to assertions a2 below:

```
a2: assert property (@(posedge clk) s |-> p);
```

Discussion: Assertions a1 and a2 are also equivalent to assertion a3.

```
a3: assert property (@(posedge clk) ##[*] s |-> p);
```

Although assertions a1, a2, and a3 are logically equivalent, their simulation performance is likely to be very different. Assertion a2 is the most efficient, assertion a1 is much less efficient, but using assertion a3 may lead to a tremendous performance degradation (see Sect. 19.3). FV performance for these three assertions is generally the same.

Efficiency Tip Never use infinite initial delay in antecedents.

5.10 Unbounded Sequences

In Example 5.42, we discussed the situation when a request had to be granted within 5 clock ticks. The suggested assertion was

```
al: assert property (@(posedge clk) req |-> ##[1:5] gnt);
```

We want now to modify the problem and require that the request req be granted some time in the future, without specifying any upper bound. It may seem that the only change required is to replace the range upper bound 5 with \$:

```
a2_wrong: assert property (@(posedge clk) req \mid-> ##[1:$] gnt); or, equivalently,
```

```
a3_wrong: assert property (@(posedge clk) req |=> ##[*] gnt);
```

However, both assertions a2_wrong and a3_wrong are *wrong*. To understand why, recall the definition of sequential property from Sect. 5.2 that we reproduce here for convenience.

138 5 Basic Sequences

Sequential property defined by sequence s is true in clock tick i iff there is no finite trace fragment i: j witnessing inability of sequence s with the initial point i to have a match. Sequence s should not admit an empty match.

When we introduced this definition, we were familiar only with bounded sequences – sequences whose all matches happen within a finite time interval. For bounded sequences, the definition of sequential property can be simplified: sequential property defined by a bounded sequence is true iff the sequence has at least one match (Sect. 5.2).⁵ Sequences built on top of infinite delay or repetition ranges using sequence operators described in this chapter are *unbounded*, i.e., they can have arbitrary long matches. For such sequences, the definition of sequential property cannot be simplified anymore.

In our example, sequence ##[*] gnt is unbounded. Any finite trace fragment does not witness the inability of this sequence to match. Indeed, the fact that gnt did not assume the high value during first 1,000 clock ticks starting from the sequence initial point, does not prevent gnt to assume the high value in the future. Therefore, sequential property ##[*] gnt is true, regardless of the actual values of gnt, and assertions a2_wrong and a3_wrong pass even if req is never granted. The correct solution was provided in Example 5.23:

```
a4: assert property (@(posedge clk) req |=> s_eventually gnt);
```

An alternative way to encode this assertion is discussed in Chap. 9.

Although sequential property of the form ##[*] s is meaningless, since it is a tautology, the sequence ##[*] s itself is not. We saw in Example 5.46 that operator ##[*] modified the meaning of the implication. Namely, assertion

```
initial a_always: assert property (@(posedge clk) ##[*] s |-> p); checks implication s |-> p in every clock cycle, whereas assertion initial a_always: assert property (@(posedge clk) s |-> p); checks this implication only once.
```

The definition of sequential property should be clear at this point for both bounded and unbounded sequences. However, its rationale has not been explained yet. Even worse, the behavior or assertions a2_wrong and a3_wrong is nonintuitive according to this definition. Nevertheless, this definition has many advantages that will be explained only in Chaps. 8 and 20. In this chapter, we will only provide one additional example, further clarifying the definition of sequential property.

We mentioned in Example 5.34 that a sequential property of the form a[*] ##1 b is equivalent to property a until b. This equivalence is intuitive, and it is conditioned by the definition of the sequential property. Indeed, property a[*] ##1 b fails iff there is a finite fragment of the trace witnessing that sequence a[*] ##1 b cannot have a match. This only happens if before the first occurrence of b there is a clock tick with a low value of a, i.e., exactly when property a until b fails. If b never happens and a always happens then any finite fragment

⁵ As follows from the definition, all sequence matches should be non-empty.

of the trace cannot witness the inability of sequence a [*] ##1 b to match, since potentially b could happen immediately after the end of this fragment. This is, again, consistent with the definition of until, which requires a to always happen if b never happens.

Exercises

- **5.1.** Write a sequence implementing the scenario "Asserted request is deasserted in the next clock tick".
- **5.2.** Show that if r, s, and t are sequences then
- (a) (r or s) ##n t is equivalent to (r ##n t) or (s ##n t)
- (b) r ##n (s or t) is equivalent to (r ##n s) or (r ##nt).

 Is (r ##n s) or t equivalent to (r or t) ##n (s or t)?
- **5.3.** Modify the transaction definition from Example 5.32 so that the beginning of the next transaction cannot happen in the same cycle as the end of the previous one.
- **5.4.** During transaction execution the ready flag must be low. The transaction is delimited by bot and eot signals. What happens if transactions can overlap?
- **5.5.** Modify the assertion from Example 5.24 to account only for the acknowledgment coming strictly after the request.
- **5.6.** Modify the assertion from Example 5.29 to require the signal to be active during exactly 5 cycles.

Chapter 6

Assertion System Functions and Tasks

It's a question of whether we're going to go forward into the future, or past to the back.

- Dan Quayle

This chapter describes system functions and tasks designed to be used in assertions. System tasks control the execution of assertions and their action blocks. Assertion system functions can be divided into two groups:

- Bit vector functions¹
- Sampled value functions

6.1 Bit Vector Functions

Table 6.1 contains a list of available *bit vector functions* along with their description. All bit vector functions have a bit vector as their single argument.

There is nothing special in bit vector functions that would prevent using them outside assertions. Unfortunately, the standard is not clear about their usage outside assertions, and the implementors may not support them outside assertion statements. Using these functions is legal in assertions of all kinds: immediate, deferred, and concurrent.

It is possible to write user functions that accomplish the same thing, however, writing them can be rather cumbersome and certainly less efficient in simulation. This is why the functions are included as part of the standard. The EDA tool providers can thus implement them in an as efficient way as possible within the tools.

6.1.1 Check for Mutual Exclusiveness

sonehoto checks that all bits of its single argument are mutually exclusive. More precisely, it returns 1'b1 if at most one bit of its argument is set to 1. Otherwise, it returns 1'b0. Bits carrying the values x or z are treated as 0.

¹ We mean by bit vector any packed integral expression here. The LRM is not clear whether an unpacked expression may appear as an argument of the described system functions.

Table 6.1 Bit vector functions

Name	Description
\$onehot0	Check that at most one bit in a vector is high
\$onehot	Check that exactly one bit in a vector is high
\$countones	Count number of bits in a vector with value high
\$isunknown	Check whether a vector has a bit with value x or z

Example 6.1. All bus drivers, that is, the bits set to 1'b1, of the vector bus_in must be mutually exclusive.

Solution:

```
a_mutex: assert #0 ($onehot0(bus_in));
```

Example 6.2. read and write requests cannot appear together.

Solution:

```
a norw: assert property (@(posedge clk) $onehot0({read, write}));
```

Discussion: In this example, we make the argument as a bit vector from two different signals using concatenation operator. \Box

6.1.2 One-Hot Encoding

System function \$onehot checks that exactly one bit of its argument is set to 1. If this condition is met, it returns 1'b1, otherwise, it returns 1'b0.

Example 6.3. Check that a control state of an FSM has a one-hot encoding when rst is low.

Solution:

Discussion: To check one-cold encoding use \$onehot (~state). □

6.1.3 Number of 1-Bits

System function \$countones returns a value equal to the number of bits of its arguments set to 1.

Example 6.4. The system stores the maximal number of simultaneously active transmitters in register trmax. The transmitter activity is encoded by vector

6.1 Bit Vector Functions 143

transmitters in which each bit represents activity of the corresponding transmitter. Check that total number of simultaneous active transmitters does not exceed the number stored in trmax.

Solution:

```
a_tract: assert property (@(posedge clk)
   $countones(transmitters) <= trmax);</pre>
```

\$onehot0(sig) is equivalent to \$countones(sig) <= 1, \$onehot(sig) is
equivalent to \$countones(sig) == 1. We recommend to use a specific system
function, and not \$countones whenever possible since it makes the user intent
clearer and may be handled more efficiently by tools.</pre>

6.1.4 Unknown Bits

System function \$isunknown returns 1'b1 if any bit of its argument has the value x or z.

Example 6.5. All bits of data should have known values (i.e., 0 or 1) when read is active.

Solution:

```
a_valid_data: assert property (@(posedge clk)
  read |-> !$isunknown(data));
```

All bit value system functions but \$isunknown treat unknown bit values (x or z) as 0. This may be a source of serious problems when checking assertions. For example, if we want to check that all bits of sig are mutually exclusive, i.e., at most one bit can have a nonzero value, then use the following assertion for this purpose

```
al: assert #0 ($onehot0(sig));
```

When only one bit of sig is set to 1, but some sig bits set to x, we will get a false positive: assertion at will pass while we might expect it to fail. To overcome this, one could fix the assertion using system function \$isunknown:

```
a2: assert #0 (!$isunknown(sig) && $onehot0(sig));
```

This is a good solution if you know that sig should not have any unknown bits, and make sure that this presumption is correct. However, if unknown values are legal in this context, you can get false negatives if exactly one bit of sig is set to x or z, and all other bits are 0. In this case, a better solution is

```
a3: assert #0 ($countones(~sig) >= $bits(sig) - 1);
```

Assertion a3 checks that there is at least n-1 bits of the complement of sig set to 1, where n is the size of sig. This is equivalent to checking that at most one bit of sig has a nonzero value (possibly x or z).

6.2 Sampled Value Functions

This section describes *Sampled Value Functions* (SVF) – system functions accessing present, past, and future sampled values of an integral expression. One can divide sampled value functions into two groups: general sampled value functions, and global clocking sampled value functions. Although sampled value functions have a temporal nature, they may be used wherever integral expressions are legal with some exceptions explained below and in later chapters.

6.2.1 General Sampled Value Functions

Table 6.2 contains the list of available general sampled value functions. Below we describe each function in more detail.

6.2.1.1 Present Sampled Values

System function \$sampled takes an integral expression as its argument, and returns the value of this expression as seen in the Preponed region. Using system function \$sampled in concurrent assertions and in checker bodies is redundant since the expressions used there are already sampled as explained in Sect. 3.4 and Chap. 21.²

Example 6.6. The following deferred cover statement prints a message when signal sig value changes:

```
c_changed: cover #0 (sig != $sampled(sig))
  $info("\%t: sig value changed", $time);
```

In this cover statement, the value of sig from the Observed region (which is normally the final value of sig in the current simulation step) is compared against sigle (sig), the value of sig at the beginning of this simulation tick. If these

Table 6.2	General	sample	ed val	lue f	functions
-----------	---------	--------	--------	-------	-----------

Name	Description
\$sampled	Return sampled value of expression
\$past	Return past value of expression
\$rose	Check whether expression value rose
\$fell	Check whether expression value fell
\$changed	Check whether expression value changed
\$stable	Check whether expression value remained stable

² There are several exceptions for this rules. For example, the value of assertion reset is normally not sampled. See Chaps. 13, 14, and 21.

values are different, a message is issued. This statement does not work in FV since in FV all signal values are conceptually sampled (see Chap. 11). There are more conventional ways to detect signal changes in a clock-based design, which work both in simulation and in FV as explained later in this chapter.

Example 6.7. As mentioned above, the use of \$sampled system function in concurrent assertions is redundant. Assertion

```
a1: assert property (@(posedge clk) $sampled(a));
is exactly the same thing as
a2: assert property (@(posedge clk) a);
```

The expression values except for clock and reset are sampled in concurrent assertions, i.e., taken from the Preponed region. Therefore, in this context a is the same thing as \$sampled (a).

The situation with resets is different. In assertion

```
a3: assert property (@(posedge clk) disable iff (rst) a);
```

the value of rst is *not* sampled. To make it sampled, it should be specified explicitly:

```
a4: assert property (@(posedge clk)
  disable iff ($sampled(rst)) a);
```

For further discussion about disable iff, see Chap. 13

The main use of system function \$sampled is in action block of concurrent assertions, as illustrated in the following example.

Example 6.8. Assertion

```
a1: assert property (@(posedge clk) a)
  else $error("Error: a = \%b.", a);
```

is violated at time 40 for the waveform shown in Fig. 6.1 (recall that in the assertion body the sampled value of a is used, and it is 0 at time 40). But the issued error message will be Error: a = 1. The reason is that the action block is executed in the Reactive region (Sect. 3.4) when the value of a is already 1. To make the reporting consistent, the function \$sampled has to be explicitly invoked in the action block:

```
a2: assert property (@(posedge clk) a)
else $error(''Error: a = \%b.'', $sampled(a));

clk

clk
```

Fig. 6.1 Assertion violation

а

Note that this rule is applicable to action blocks of concurrent assertions only. Specifying sampled values in action blocks of immediate or deferred assertions will produce inconsistent error messages because these assertions do not use sampled values. See also Sect. 3.4.3.

6.2.1.2 Past Sampled Values

Sampled value function \$past(e, n, en, @clk) has the following arguments:

- e an integral expression.
- $n \ge 1 a$ constant expression specifying the number of clock ticks (delay).
- en a gating expression for the clocking event.
- clk a clocking event.

All arguments but the first one are optional and have default values:

- If the clocking event is omitted, it is inferred from the context as described in Sect. 6.2.1.5. For example, if \$past is invoked in a singly clocked assertion then the clock of this assertion is assumed, both in the assertion body and in the assertion action blocks.
- The gating condition defaults to 1'b1 no clock gating.
- The number of clock ticks defaults to 1.

The last optional arguments may be skipped, like in \$past(a). If the intermediate ones are omitted, a comma should be placed for each omitted argument:

```
$past(a,,,@(posedge clk))
```

\$past returns the sampled value of e that was n strictly prior time-steps ago in which event @(clk iff en) occurred (see Sect. 2.3), i.e., the value is taken n ticks of clk ago, but counting only those clock ticks in which en was high.

Example 6.9. Table 6.3 contains sampled and past values of a for some time-steps for the waveforms shown in Fig. 6.2. For example, to find \$past(a,,,@(posedge clk)) at time 40 we must take the sampled value of a at time 30, which is 0. To find \$past(a,,,@(posedge clk)) at time 42 we must take the sampled value of a at the time of the last strictly preceding clock tick, which is 40, and this value is 1.

Values Before Initial Clock Tick The definition of \$past given above is incomplete: what happens if for a given time-step there are not enough previous clock ticks? In this case, \$past(e) returns an initial value of e. The initial value of a static variable is that as computed using the initial values stated in the declaration of the variables involved in e. If a static variable has no explicit initialization, the default value of the corresponding type is used, even if the variable is assigned a value in an initial procedure.

	1 1	
Time	\$sampled(a)	<pre>\$past(a,,,@(posedge clk))</pre>
30	0	0
40	1	0
42	0	1
50	0	1
60	1	0
70	1	1
80	0	1
90	0	0

Table 6.3 Sampled and past values of a




Fig. 6.2 Timing diagram for Examples 6.9, 6.14, 6.18, and 6.22

FV tools may ignore variable initialization everywhere, except in checker constructs. Also, many FV tools consider all variables to be of two-state value type, and therefore they assume that \$past(e) is 0 in clock tick 0 for any e.

Example 6.10. For the following declaration:

```
logic a = 1'b1, b = 1'b0;
logic c;
bit d;
wire w = a;
initial c = 1'b1;
```

the initial value of

- a is 1'b1.
- b is 1'b0.
- a | b is 1'b1.
- c is 1'bx, even though c is assigned a value in the initial procedure.

³ FV tools usually work with the synthesis model of DUT, and variable initialization is non-synthesizable. However, FV algorithms can deal with initial states and the tools can infer initial states by analyzing the variable initializations.

- dis 1'b0.
- w is 1'bx. w is a net, and wire w = a; is an implicit continuous assignments, and not initialization.

Beyond clock tick 0 the past values of these signals are their initial values. For example,

```
$past(a,,,@(posedge clk)) = 1'b1
and
$past(w,,,@(posedge clk)) = 1'bx
Beyond clock tick 1 (including)
$past(a, 2,,@(posedge clk)) = 1'b1
and
$past(w, 2,,@(posedge clk)) = 1'bx
```

etc. As mentioned in the note preceding this example, many FV tools will assume the past value of all these expressions to be 1'b0.

Example 6.11. Consider the following code fragment.

```
logic a;
a1: assert property(@(posedge clk) $past(a));
```

Assertion at fails in clock tick 0, since then past(a) returns x – the initial value of a.

This example shows that one should be careful when using past in assertions because it may lead to nonintuitive assertion behavior in the initial clock ticks. \Box

Example 6.12. Each grant gnt should be immediately preceded by a request req.

Solution:

```
al: assert property (@(posedge clk) gnt | -> $past(req));
```

Discussion: What happens if in the initial clock tick gnt is active? If req has not been explicitly initialized, \$past(req) is x or 0 depending on req type, and the assertion fails. In this case, this is a desired behavior.

Example 6.13. Gray Encoding: Check that signal sig has a Gray encoding, i.e., its two consecutive values differ in only one bit.

Solution: Here is the first take:

```
al_wrong: assert property (@(posedge clk)
    $onehot(sig ^ $past(sig)));
```

The result of the exclusive OR $^{\circ}$ operator between the current and the past values of sig contains ones in the bits that changed. We want to make sure that exactly one bit of the result is 1. But what happens in the initial clock tick? past(sig) will return x, the result of the exclusive OR will also be x, and assertion al_wrong

will fail in the initial clock tick! To handle the initial situation correctly, we need to delay the first check of the assertion:

```
a2: assert property (@(posedge clk)
  nexttime $onehot(sig ^ $past(sig)));
```

Now sig may have any value in the initial clock tick.

Discussion: One can argue that a real-life implementation should take into account the reset sequence during which no check is performed and therefore no initial delay is necessary:

```
a3_problematic: assert property (
  @(posedge clk) disable iff (rst) $onehot(sig ^ $past(sig)));
```

but this is also problematic. For example, if during reset and immediately after it sig was equal to 0, assertion a3_problematic will fail immediately after reset. Therefore, even in presence of a reset sequence, the initial delay may be necessary:

```
a4: assert property (@(posedge clk) disable iff (rst)
  nexttime $onehot(sig ^ $past(sig)));
```

A similar situation occurs when asserton and assertoff system tasks are used to disable the assertion execution during the reset sequence (Sect. 6.3)

Be careful with handling initial clock ticks when using \$past. In many cases, it requires introducing an initial delay.

Gated Clock The third argument of \$past specifies the gating condition. To compute a past value relative to a gated clock, the third argument should be explicitly specified. To compute \$past(a, n, en, @clk), it is necessary to take the sampled value of a at n clock cycles strictly prior to the current simulation tick, where only "enabled" clock ticks in which en is true are counted.

Example 6.14. Table 6.4 contains values of \$past(a, 1, en, @(posedge clk)) and of \$past(a, 2, en, @(posedge clk)) for the waveforms from the timing diagram shown in Fig. 6.2. As an example consider simulation time-steps

Time	<pre>\$past(a,1,en)</pre>	\$past(a,2,en)
30	0	0
40	0	0
50	1	0
60	1	0
62	1	0
70	1	0
80	1	1
90	0	1

Table 6.4 Past values of a relative to @ (posedge clk)

62 and 80. At time 62, the previous clock tick when en was high is at time 40, therefore past(a, 1, en, @(posedge clk)) is 1 - the sampled value of a at time 40. past(a, 2, en, @(posedge clk)) at time 62 is the same thing as past(a, 1, en, @(posedge clk)) at time 40, i.e., 0.

\$past(a, 1, en, @(posedge clk)) at time 80 is 1 – the sampled value of a at time 70. \$past(a, 2, en, @(posedge clk)) at time 80 is the same thing as \$past(a, 1, en, @(posedge clk)) at time 70. The last enabled clock tick prior to 70 is at time 40, therefore the result is 1.

Example 6.15. Verify the following implementation of a flip-flop:

```
always @(posedge clk)
   if (en) q <= d;</pre>
```

Solution:

```
a_ff: assert property (@(posedge clk)
  nexttime q == $past(d,, en));
```

Efficiency Tip past(..., n, ...) is not efficient for big delays n. It is recommended to minimize the number of calls of past, and to avoid calling it whenever it is not essential. The width of the expression e in past(e, ...) is not critical in simulation, but may significantly affect FV performance: every additional bit in e introduces performance penalty.

Example 6.16. Given the definition:

In fact, assertion at has three invocations of \$past, while at has only one. Assertion at has 32 * 3 = 96 application of \$past to individual bits, while at is applied to a single bit – the result of comparison. This is essential for FV and helps in simulation.

Sampled Value Functions Outside Concurrent Assertions \$past and other sampled value functions, except for the global clocking future value functions described in Sect. 6.2.2, are not limited to concurrent assertions. However, it should be understood that the clauses returned are based on the sampled values of the argument, as discussed in the following example.

Example 6.17. The following code

```
logic a, b;
always @(posedge clk)
   a <= $past(b);
has the same effect as
logic a, b, temp;
always @(posedge clk) begin
   temp <= $sampled(b); a <= temp;
end</pre>
```

provided that a is not assigned elsewhere.

To understand this, we need to apply the definition of past(b) – the sampled value of b on the prior clock rise. The value of b immediately after the prior clock rise is modeled by the variable temp, and a is equal to the sampled value of temp at that time-step, i.e., to the value of temp immediately before the clock rise.

6.2.1.3 Rose and Fell

Sampled value function rose(e, @clk) returns *true* iff the Least Significant Bit (LSB) of e has changed to 1, and false, otherwise. The sampled value function fell(e, @clk) returns true if the LSB of e has changed to 0, and false, otherwise. More precisely

```
$rose(e, @clk) \equiv $past(LSB(e),,,@clk)!== 1 && $sampled(LSB(e))=== 1. $fell(e, @clk) \equiv $past(LSB(e),,,@clk)!== 0 && $sampled(LSB(e))=== 0.
```

System functions \$rose and \$fell compare the past value with the current *sampled* value of the expression. The clocking event argument is optional and if omitted, its value is inferred from the context as explained in Sect. 6.2.1.5.

Example 6.18. For the timing diagram in Fig. 6.2, \$rose(a, @(posedge clk)) returns true for time-steps $30 < t \le 40$ and $50 < t \le 60$. For all other time-steps, it returns false.

```
$fell(a, @(posedge clk)) returns true for time-steps 40 < t \le 50 and 70 < t \le 80. For all other time-steps, it returns false.
```

Example 6.19. If an expression changes its value from 3'b100 to 3'b001, \$rose returns *true*, and fell returns *false*, since only the last significant bit counts. If an expression changes its value from x to 1, \$rose returns *true*, and if it changes its value from x to 0, \$fell returns *true*. If an expression becomes x, both \$rose and \$fell return *false*.

Example 6.20. Assume that sig is of type bit. The assertion from Example 5.29 "signal remains high during 5 cycles" may be rewritten as follows using function Srose:

```
a1: assert property (@(posedge clk) ##1 $rose(sig) |=> sig[*4]);
```

П

What happens if we omit the initial delay in assertion a1?

```
a2: assert property (@(posedge clk) $rose(sig) |=> sig[*4]);
```

Solution: The behavior of these assertions differs in case sig is high in clock tick 0. In clock tick 0, the antecedent of a2 is true because the past value of sig prior to the initial clock tick is 0. Therefore, assertion a2 requires sig remain true for four additional clock ticks. Assertion a1 does not have a nonvacuous attempt starting at clock tick 0, and it skips the comparison with the "prehistoric" value of sig.

Discussion: It is difficult to argue which solution is more natural, but consider the dual case when we want to check that the signal remains low during 5 cycles:

```
b1: assert property(@(posedge clk) ##1 $fell(sig) |=> !sig[*4]);
b2: assert property (@(posedge clk) $fell(sig) |=> !sig[*4]);
```

The behavior of assertions al and bl is similar, but the behavior of assertions al and bl is different! If in clock tick 0 the value of sig is low, \$fell(sig) will return false, so that assertions bl and bl are equivalent. One could argue that if sig were of type logic, the behavior of assertions al and bl would be consistent, as \$fell returns true in case of transition from x to 0. This is true in simulation, but usually not in FV, because most FV tools treat all variables as two-valued as mentioned above.

This example shows again that one should be very careful with the behavior of sampled value functions in the initial clock tick, and that it is better to avoid referencing sampled value functions by introducing an initial delay. Specifying a reset with assertions a2 and b2 makes their behavior unpredictable in the moment when the reset goes low, as explained in Example 6.13.

To conclude this example, we will mention that the assertion suggested in Example 5.29 is more efficient than the assertion a1.

Example 6.21. Assertion triggers in Examples 5.23, 5.42, and 5.24 are level-sensitive events: "When request is high...". In many cases, it is desirable to have edge-sensitive triggers: "When request becomes high...". For instance, Example 5.42 may be reformulated as: "When request becomes high it should be granted within 5 cycles." The corresponding assertion is (note the nexttime operator!):

```
a1: assert property (@(posedge clk)
  nexttime ($rose(req) |-> ##[1:5] gnt));
or
a2: assert property (@(posedge clk)
  ##1 $rose(req) |-> ##[1:5] gnt);
The same assertion is probably better to write as<sup>4</sup>:
a3: assert property (@(posedge clk))
```

!req ##1 req |-> ##[1:5] gnt);

⁴ Assertions all and all are equivalent, but assertions all and all are not completely equivalent: If in clock tick 0 req has value x, and in clock tick 1 – value 1, the consequent in clock tick 1 is checked in all, but not in all If the variable values are 2-valued, both assertions are equivalent. The situation when assertions behave differently in presence of unknown values is quite common, we will not always explicitly comment on it.

6.2.1.4 Changed and Stable

Sampled value function \$changed(e, @clk) returns *true* iff the past value of e is different from its current value, and *false*, otherwise. The sampled value function \$stable(e, @clk) returns *true* if the past value of e is identical to its current value, and *false*, otherwise. More precisely,

```
constant c
```

\$stable(e, @clk) is the same thing as !\$changed(e, @clk). \$changed and \$stable compare the past value with the current sampled value of the expression.

As in other clocked sampled value functions, the clock event argument is optional and if omitted, its value is inferred from the context (Sect. 6.2.1.5).

Example 6.22. For the timing diagram shown in Fig. 6.2, system function \$changed (a, @(posedge clk)) returns *true* for time-steps $30 < t \le 60$ and $70 < t \le 80$. For all other time-steps, it returns *false*. The value of \$stable is inverse.

Example 6.23. If e remains x, stable(e) is true. If e changes from 0 or 1 to either x or z, stable(e) is false.

Example 6.24. Signal sig should be always stable.

Solution: One can attempt to write this assertion as:

```
a1_wrong: assert property (@(posedge clk) $stable(sig));
```

but this implementation is *wrong*. The problem is, as usual, with clock tick 0. In clock tick 0 *stable* returns *true* only if the new value of sig coincides with its initial value. Therefore, assertion al_wrong checks that sig always preserves its initial value. As an illustration, consider the case when sig is of type logic, and when it is not explicitly initialized – the most common case in practice. In this case, assertion al_wrong succeeds iff sig is always x, apparently not what was intended to check. As always in such cases, the solution is to delay the assertion execution:

```
a2: assert property (@(posedge clk) nexttime $stable(sig));
```

Discussion: Assertion a2 is still problematic: it checks signal stability only on rising clk. In many cases in practice it is desirable to ensure absolute signal stability, for example, in verification of clock domain crossing (Sect. 1.2.3). We postpone this discussion until Sect. 6.2.2. In this section, we consider signal stability only relative to some specific clock.

Example 6.25. We are now ready to implement the assertion from Example 5.11 with the help of a sampled value function: "sig toggles every cycle: 0101...or 1010...".

Solution:

```
a_toggle: assert property (@(posedge clk) ##1 $changed(sig));
```

Example 6.26. Each time signal sig changes, it should remain stable for four additional cycles.

Solution:

```
al: assert property(@(posedge clk) ##1 $changed(sig) |=> $stable
    (sig)[*4]);
```

Discussion: It is possible to specify signal stability in clock phases instead of clock cycles.

```
a2: assert property(@clk
  ##1 $changed(sig) |=> $stable(sig)[*4]);
```

To stress that the assertion is controlled by any clock edge, assertion a2 may be rewritten as

```
a3: assert property(@(edge clk)
  ##1 $changed(sig) |=> $stable(sig)[*4]);
```

Both assertions have the same effect.

Example 6.27. Signal sig is stable between the start and the end events. The events are represented by the high value of signals start ev and end ev.

Solution:

```
a_stable: assert property (@(posedge clk)
   start ev |=> $stable(sig) until with end ev);
```

Discussion: The limitation that both start_ev and end_ev are signals may be relaxed. start_event may be an arbitrary sequence, and end_ev may be an arbitrary property. In such a case, the stability is checked only after sequence start_ev matches, and until the starting clock tick of a successful evaluation of property end_ev.

6.2.1.5 Clock Inference

All sampled value functions described in Sect. 6.2.1 but \$sampled have a clocking event as their argument. This argument may be omitted, in which case the clocking event is inferred from the context in a similar way to the inference of the clocking event in properties and sequences (Chaps. 12 and 14):

- 1. If the function is called from a concurrent assertion, the appropriate clocking event from the assertion is used.
- 2. If the function is called from an action block of an assertion statement, the leading clock of the assertion is used.
- 3. If the function is called from an always or initial procedure, the procedure clock is inferred. The rules of clock inference in procedures are described in Chap. 14.
- 4. Otherwise, the event from default clocking is used as described in Sect. 12.2.2.

6.2.2 Global Clocking Sampled Value Functions

Global clocking sampled value functions are sampled value functions controlled by the global clock. The global clock is the primary system clock, as explained in Sect. 3.4.2. There are two groups of global clocking sampled value functions: past and future.

Global clocking sampled value functions may be used only if global clocking has been defined.

6.2.2.1 Past Global Clocking Sampled Value Functions

Table 6.5 summarizes past global clocking functions. Past global clocking SVF are simple shortcuts for corresponding general sampled value functions described earlier.

```
\begin{array}{lll} & & & & & & & & & \\ & & & & & & \\ & & & & & \\ & & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & \\ & & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ & & \\ &
```

6.2.2.2 Future Global Clocking Sampled Value Functions

Table 6.6 summarizes future global clocking sampled value functions.

The future global clocking functions provide information about the future behavior of an expression. Unlike the past global clocking functions, there are no expressions using the general sampled value functions corresponding to future global clocking functions. Function \$future gclk(e) returns the sampled value

Table 6.5 Fast global clocking sampled value functions		
Name	Description	
\$past_gclk	Return expression value in previous tick of global clock	
<pre>\$rose_gclk</pre>	Check whether signal value rose from last tick of global clock	
\$fell_gclk	Check whether signal value fell from last tick of global clock	
<pre>\$changed_gclk</pre>	Check whether signal value changed from last tick of global clock	
\$stable_gclk	Check whether signal value remained stable relative to last tick	
	of global clock	

Table 6.5 Past global clocking sampled value functions

Name	Description
\$future_gclk	Return expression value in next tick of global clock
\$rising_gclk	Check whether signal value is rising
\$falling_gclk	Check whether signal value is falling
\$changing_gclk	Check whether signal value is changing
\$steady_gclk	Check whether signal value is not changing

Table 6.6 Future global clocking sampled value functions

of e in the next tick of the global clock.⁵ Other future global clocking SVF can be defined through function \$future gclk:

```
 \begin{array}{l} \mbox{\tt $rising\_gclk(e)$} \equiv \\ \mbox{\tt $sampled(LSB(e))!==1 \&\& $future\_gclk(LSB(e))===1} \\ \mbox{\tt $falling\_gclk(e)$} \equiv \\ \mbox{\tt $sampled(LSB(e))!==0 \&\& $future\_gclk(LSB(e))===0} \\ \mbox{\tt $$changing\_gclk(e)$} \equiv \\ \mbox{\tt $$sampled(e)!==$future\_gclk(e)$} \\ \mbox{\tt $$steady\_gclk(e)$} \equiv \\ \mbox{\tt $$sampled(e)===$future\_gclk(e)$} \\   \end{array}
```

There are several restrictions imposed on future value functions: they cannot be used in reset conditions, outside concurrent assertions, ⁶ and they cannot be nested.

Example 6.28. The following use of future functions is *illegal*:

```
always @(posedge_clk) a <= $future_gclk(b) && c;
al_illegal: assert #0 (a -> $future_gclk(b));
a2_illegal: assert property (@(posedge clk)
   disable iff (rst || $rising_gclk(interrupt)) req |=> gnt);
a3_illegal: assert property (@(posedge clk) req |-> $future_gclk (ack && $rising gclk(gnt));
```

In the first statement \$future_gclk(b) is used in an assignment, a1_illegal is not a concurrent assertion, in a2_illegal a future SFV is used in a reset condition, and in a3_illegal two future SVF are nested.

Efficiency Tip Global clock future value functions are usually more efficient in FV than past sampled value functions. In simulation, the picture is opposite.

Stability Assertions The following examples illustrate how a future sampled value function may be used to write assertions checking signal stability.

Example 6.29. sig value does not change.

Solution: We have already considered this assertion in Example 6.24, but the implementation there had two drawbacks: we had to delay the assertion by one clock tick

⁵ Formal interpretation of \$future gclk (e) is provided in Chap. 11.

⁶ Future global clocking sampled value functions are legal, however, in let-statements used in concurrent assertions, and in definitions of sequences and properties.

to handle the past value correctly in clock tick 0, and we could specify stability only relative to a clocking event. Controlling the assertion by the global clock and using a future value function overcome these drawbacks:

```
a stable: assert property (@$global clock $steady gclk(sig));
```

In this implementation, there is no need to have an initial delay since function \$steady_gclk(sig) checks that the sig value is identical to the one in the next clock tick, hence there is no reference to the values of sig prior to clock tick 0, as in the case with \$stable.

As \$global_clock indicates the primary system clock, all signal changes that we are willing to consider are synchronized with it as explained in Sect. 3.4.2 and Chap. 11, and if there is a signal change between the ticks of the global clock, it is considered to be a glitch and is ignored at the RTL level. Recall, however, that it is the user responsibility to define global clocking.

Example 6.30. Signal sig should be stable between two consecutive clock ticks. In other words, the signal value can change only when the clock is rising.

Solution:

```
al: assert property (@$global_clock disable iff(rst)
  $changing_gclk(sig) |-> $rising_gclk(clk));
```

Discussion: In this assertion, we consider the clock to be a regular signal, and not an event. The same assertion may be expressed using past sampled value function, but this is less natural and usually less efficient in FV:

```
a2: assert property (@$global_clock disable iff(rst)
##1 $changed(sig) |-> $rose(clk));
```

Equivalently, we could use past global clocking function ($\$changed_gclk(sig)$, etc.), but this is more verbose.

Clock as a Sampled Signal

Example 6.31. Enable en should be low when sig is going to change.

Solution: The easiest way to write this assertion is to use sig as a clock:

```
al: assert property(@sig !en);
```

Discussion: This solution works always in FV, but it does not always work in simulation. The reason is that in simulation it is required that the clock value changes at most once in any simulation tick, otherwise the simulation may not work correctly.

To overcome the limitation, the assertion can be rewritten in the following way:

```
a2: assert property(@$global clock $changing gclk(sig) -> !en);
```

This example shows that the global clock may be used as a "carrier" for other signals that cannot be used as a clock directly.

Clock Fairness

Example 6.32. Clock is always ticking.

Solution: It is required to check the clock fairness, i.e., that in any given moment there is some future moment when the clock ticks (see also Example 4.15):

```
a_fclk: assert property(@($global_clock)
    s eventually $rising gclk(clk));
```

Discussion: The assertion clock is \$global_clock relative to which the ticking of clk is checked. This assertion works only if \$global_clock ticks on both edges of clk or faster. If \$global_clock is the same as posedge clk, ticking of the clk cannot be detected: when posedge clk happens the sampled value of clk is always 0.

Efficiency Tip Assertion a_fclk is efficient in FV.⁷ In simulation, this assertion is not optimal, as it accumulates several overlapping attempts, as explained in Sect. 19.3.

However, checking this assertion in simulation is not useful. The simulation run is finite, and thus analyzing the run is not possible to conclude that the clock is always ticking. It is only possible to check that the clock ticks at least some predefined number of times during the simulation run (see Exercise 6.8). For practical needs, it may be even sufficient to examine the simulation trace.

One could wonder why general sampled value functions contain only the past version. Why is there no \$future(e, @clk) function in the language? The answer is simple: we do not know whether an arbitrary clock is fair. If clk stops ticking at some moment, the value \$future(e, @clk) is undefined. As for the global clock—the primary system clock—is concerned, it is required to be fair by definition, and \$future_gclk(e) always makes sense. This consideration is important in FV, where infinite traces are handled. See Sect. 11.2.3.1 for an additional explanation.

6.3 Tasks for Controlling Evaluation Attempts

It is often necessary to stop the evaluation and reporting of unwanted assertion failures during special initialization, power down, or reset operation phases of the design under verification. If there is some Boolean expression that characterizes such a phase, then the expression can be used in a disable iff clause in subsequent assertions to disable assertion failures during those phases. For other

⁷ This assertion is rather expensive to check in FV. We mean that among various versions of the same assertion, this assertion is one of the most efficient.

⁸ In simulation of concurrent assertions containing global clocking future sampled value functions the assertion behavior in the last tick of the global clock is usually ignored.

situations when a testbench initializes the design, the assertions can be disabled explicitly by using *assertion control tasks*:

- \$asserton
- \$assertoff
- \$assertkill

By default all assertions are enabled from time 0. To stop the start of any attempts from time t, it is sufficient to call sassertoff before the Observed region of the simulator at time t. This, however, does not stop any evaluation attempt that has been started earlier. To restart the evaluation, at some later time t, the task sasserton is called.

Therefore, to avoid executing all assertions during the initialization phase, \$assertoff should be called from the testbench at time 0, followed by \$asserton when exiting the initialization phase. This is illustrated in the following example.

```
Example 6.33.
module m;
bit clk;
default clocking ck @(posedge clk); endclocking
a: assert property( ... );
initial begin
    $assertoff();
    //... await reset activity completed ...
    @ck; //synchronize and start assertion from this tick
    $asserton();
end
    //... other code ..
endmodule
```

In this case, assertion a will start evaluation attempts starting from the moment statement @ck unblocks.

What if the call to \$asserton() were made in a program that exceutes in the Reactive region as in this code snippet?

Since the call is made from the Reactive region, the assertion is not yet enabled when the evaluation of a is to start in the Observed region, the first evaluation of a will only happen one clock tick later. Also, the \$assertoff does not execute until the Reactive region of time step 0, hence the assertion evaluation attempt at time 0 is enabled and will execute if there is a clock tick.

If the initialization phase is to be executed again later in the simulation, we should again stop the assertions, but in that case we should consider using \$assertkill. It stops the subsequent evaluation attempts, and also any evaluation attempts that have started earlier (that would still be continuing evaluation during the initialization phase). Calling this task thus avoids failures of evaluation attempts that do not matter anymore, even though they started during the "normal" design phase.

The above approach will work well if we need to stop all assertions, but what if some assertions should run during the special phase? The tasks accept a list of arguments that define the modules or scopes and the depth down to individual assertions to which the task call applies. The argument list is of the same form as for the well-known \$dumpvars task:

The *levels* argument is a nonnegative integer constant. When set to 0, it applies to all the items on the *list_of_modules_or_assertions* and all the instances below. When set to 1, it applies only to the items but not to the instances. When set to some n > 1, it applies to the items and to n-1 levels of instances below. Of course, if the item is a full hierarchical path to an assertion, the task applies only to that assertion since there are no levels below.

6.4 Tasks for Controlling Action Blocks

Assertions have optional *action blocks* (Chap. 3), that is, blocks of procedural code that are executed when the assertion attempt succeeds (pass action block) or fails (fail action block). In the case of covers, only the pass action block is available because cover failure is not interesting. The following example shows a concurrent assertion a and a concurrent cover c, each with action blocks.

Example 6.34.

```
a: assert property(p1)
  begin // pass action block
     process_pass();
     $info("assertion PASSED");
  end
  else begin // fail action block
     process_failure();
     $error("assertion FAILED");
  end
c: cover property(p2)
  begin // pass action block
     process_cover();
     $info("COVERED");
  end
```

By default, the action blocks execute on every success and failure of the assert and cover statements. This behavior may not be desirable, for example, when the property passes vacuously or when running massive regression tests where only failures should be reported.

SystemVerilog provides several tasks for controlling the execution of action blocks:

```
$assertpassoff
$assertpasson
$assertfailoff
$assertfailon
$assertvacuousoff
$assertnonvacuouson
```

The arguments to the system tasks are the same as for assertion control system tasks described in Sect. 6.3.

As it can be seen, the assertion action control tasks come in pairs, one for disabling and one for reenabling the action.

\$assertpassoff stops the execution of pass action blocks in the scope as specified by the arguments to the task call until \$assertpasson is called affecting the same scope.

\$assertfailoff stops the execution of fail action blocks in the scope as specified by the arguments to the task call until \$assertfailon is called affecting the same scope.

\$assertvacuousoff stops the execution of pass action blocks for vacuous evaluation attempts in the scope as specified by the arguments to the task call until \$assertpasson is called affecting the same scope.

All the "off" tasks do not affect evaluation attempts that are already in progress as well as action blocks that are currently executing.

The following are typical cases of using these tasks:

In regression tests, disable pass action blocks on assert and assume statements
unless their execution has some functional impact on the testbench behavior.
In covers, it could remain enabled if they provide information for some user-specific coverage analysis tools.

- Even when pass action blocks are enabled, we recommend to disable their execution on vacuous evaluation attempts because they may lead to an incorrect interpretation of the verification results.
- If default failure messages issued by the verification tool are sufficient, and fail and pass action block execution has no functional impact on the testbench, it may be preferable to disable the execution of fail action blocks. Verification tools often have means to control how many failures of assertions are reported by default reporting mechanisms. This is useful for catching the first few failures without cluttering the log with redundant repetitions of the same message.

Exercises

- **6.1.** Write an assertion checking that exactly n bits of a signal are high (low).
- **6.2.** Write an assertion checking one-cold encoding for four-state value variables.
- **6.3.** It was mentioned in Example 6.8 that invoking system function \$sampled in action blocks of immediate or deferred assertions for reporting purposes will result in inconsistent messages. Explain why.
- **6.4.** Modify the assertions in Example 6.13 to allow sig either remain unchanged or change in one bit in consecutive clock cycles. Write two versions of this assertion: one which does not impose any constraints on the initial value of sig, and the other requiring sig to be 0 upon the termination of the reset sequence.
- **6.5.** Rewrite assertion

```
b1: assert property(@(posedge clk) ##1 fell(sig) = !sig[*4]); from Example 6.20 without using sampled value functions.
```

- **6.6.** What will be the assertion behavior in Example 6.25 if the initial delay ##1 is dropped? Assume that sig is of type bit.
- **6.7.** What does the following assertion mean?

```
assert property(@($global_clock)
s eventually $changing gclk(clk));
```

What is the difference between this assertion and the assertion from Example 6.32

- **6.8.** Write an assertion stating that the clock ticks at least n times, where n is an elaboration time constant. See Example 6.32.
- **6.9.** There are two clocks: fast (fclk) and slow (sclk), and sclk is 8 times slower than fclk. Write the following assertion: signal sig may only change on the third rising edge of sclk after its last change.

Chapter 7 Let, Sequence and Property Declarations; Inference

The beginning of wisdom is to call things by their right names.

— Chinese proverb

In SystemVerilog, modules, programs, interfaces, checkers, functions, and tasks provide means for reuse, and for abstracting and hiding details. SystemVerilog assertions provide such means too. This is achieved using parameterized let, sequence, and property declarations. Their argument lists as well as instantiation semantics are quite different from the other reuse features. In addition, certain kinds of actual arguments can be inferred from the instantiation context. Similar to sequences and properties, let declarations allow to abstract expressions, making code more readable and reusable. They can be used anywhere, not only in assertions, but also one of their intended uses is for defining reusable parameterizable expressions for immediate and deferred assertions.

7.1 Let Declarations

let declarations are a way to define parameterizable templates for forming expressions. let can be declared in any declarative scope, wherever variables can be declared, and instantiated wherever expressions can be used. let declarations are similar to text macros, but they are better adapted for use in SystemVerilog expressions because they are part of the core language. They follow normal scoping rules. The formal arguments may be typed and can have default actual arguments. However, there are some practical restrictions to be placed both on the form of the expression definition and on the arguments, even though they are not stated explicitly in the SystemVerilog LRM. These will be discussed later in the section.

The following example shows some simple let usage and illustrates the effect of scoping rules applied to these declarations. They are contrasted with similar macro declarations.

Example 7.1. Effect of scoping rules.

```
module m;
logic clk, a, b, c, d;
let let exp = a && b;
```

```
always @(posedge clk) begin
  let let_exp = c || d;
  a <= let_exp;
  b <= a;
end
  assign c = let_exp;
  assign d = b;
endmodule</pre>
```

There are two let declarations of the same name let_exp, but each having a different expression associated with the name. The first one is defined in the module scope, and the second one in the always procedure scope. The variables used in the expression on the right-hand side of the let declaration must be visible at the point of declaration. Wherever a let is instantiated the nearest visible let declaration is used in that the expression on the right-hand side of the declaration is substituted in the place of the instance. Module m definition is thus equivalent to the following code:

```
module m;
logic clk, a, b, c, d;
always @(posedge clk) begin
    a <= c || d;
    b <= a;
end
assign c = a && b;
assign d = b;
endmodule</pre>
```

Suppose now that we replace the let declarations by macro definitions. The original module definition becomes

```
'define macro_exp a && b
module m;
logic clk, a, b, c, d;
always @(posedge clk) begin
'define macro_exp c || d
    a <= 'macro_exp;
    b <= a;
end
assign c = 'macro_exp;
assign d = b;
endmodule</pre>
```

After macro substitution, module $\mathfrak m$ is quite different from the one after let substitution

```
module m;
logic clk, a, b, c, d;
always @(posedge clk) begin
    a <= c || d;
    b <= a;
end
assign c = c || d;
assign d = b;
endmodule</pre>
```

7.1 Let Declarations 165

The difference is in the assign statement where in the case of let, it is the definition from the module scope that is used, whereas in the case of a macro, it is the latest definition in the lexical order. To imitate the scoping of let using macro definition, the symbol would have to be explicitly *undefined* when exiting the scope and again *defined* to the original expression, as shown next. Clearly, this is much more tedious and error prone.

```
'define macro_exp a && b
module m;
logic clk, a, b, c, d;
always @(posedge clk) begin
'define macro_exp c || d
    a <= 'macro_exp;
    b <= a;
'undef macro_exp
'define macro_exp a && b
    end
    assign c = 'macro_exp;
    assign d = b;
endmodule</pre>
```

Unlike macro definitions, let declarations follow normal scoping rules. The right-hand side expression from the definition is substituted in place of the instance.

П

The instantiation of let is quite different from, e.g., calling a function because the let body is substituted in the place of the instance. Unlike functions, let instantiations cannot be recursive.

let declarations can have formal arguments. Again, unlike in functions, the actual arguments are substituted for every occurrence of the corresponding formal argument when the instance is replaced by the let body. The actual argument variables must be visible in the instance scope. The formal argument types are restricted to the integral types allowed in assertions, and may be typed or untyped. If untyped, the actual argument expression is enclosed in parentheses before substitution in the place of the formal argument. The extra pair of parentheses is added to preserve the precedence of evaluation as indicated by the parent expression containing the let instance. If the formal argument is typed, then the self-determined type of the result of the evaluation of the actual argument must be cast compatible. Provided that the types are compatible, the actual expression is cast to the type of the formal argument before being substituted in place of the occurrences of the formal arguments in the let body.

¹ The compiler may issue a warning for the second macro definition, saying that the symbol has been redefined.

П

П

The following example shows the use of an untyped formal argument.

```
Example 7.2.
let orReduct(x) = |x;
module m;
logic [2:0] sel;
logic [7:0] [1:0] data;
logic a, b, v, w;
assign v = a && orReduct(sel);
assign w = orReduct(data);
//...
endmodule
```

After substitution, the code takes the following form:

```
module m;
  logic [2:0] sel;
  logic [7:0] [1:0] data;
  logic a, b, v, w;
  assign v = a && (|sel);
  assign w = (|data);
  //...
endmodule
```

In the above example, notice that because the formal is untyped, there is more latitude in using actual argument expression of different types in the let instance; no type conversion is performed and the validity of the substituted expression is completely determined by the expression within which it is substituted.

The formal arguments can also have a default actual argument. When no actual argument is provided in a let instance, the default one is used. The following example is similar to the preceding one except that the let is now defined inside the module and the formal argument x has a default actual expression sel. The first instance does not provide an actual argument, hence the default sel is taken. The result is the same as in the preceding example.

```
Example 7.3.
module m;
logic [2:0] sel;
logic [7:0] [1:0] data;
logic a, b, v, w;
let orReduct(x = sel) = |x;
assign v = a && orReduct();
assign w = b || orReduct(data);
//...
endmodule
```

When typed formal arguments are used, type checking is performed to ensure that the actual argument is type cast compatible with the formal argument. If that is so, then type casting takes place. This is illustrated in the next example.

7.1 Let Declarations 167

```
Example 7.4.
typedef bit [1:0] my_t;
let orReduct(my_t x) = |x;
module m;
logic [2:0] sel;
logic [7:0] [1:0] data;
logic a, b, v, w;
assign v = a && orReduct(sel);
assign w = orReduct(data);
//...
endmodule
```

The resulting code after substitution is as follows:

```
typedef bit [1:0] my_t;
module m;
logic [2:0] sel;
logic [7:0] [1:0] data;
logic a, b, v, w;
assign v = a && (|my_t'(sel));
assign w = (|my_t'(data));
//...
endmodule
```

Because of the type cast, only the low-order 2 bits of either argument are converted to bit and used in the reduction or operator.

Typed arguments enforce type compatibility and casting, but limit flexibility as compared to untyped arguments.

Let us recapitulate the way the variables in the default argument expression and the variables in the let body that are not formal arguments are resolved. The rules are similar to those for function and task declarations. Namely, the default arguments and the variables that are not formal arguments are resolved in the declarative context, while the actual arguments are resolved in the instantiation context.²

```
Example 7.5.
module m;
bit clk;
logic a, b;
let x = $past(a && b);
let y = $past(a && b, , ,@(posedge clk));
always_comb begin
   al: assert #0 (x);
   a2: assert #0 (y);
end
a3: assert property(@(posedge clk) a |-> x);
endmodule
```

² The SystemVerilog LRM provides many examples illustrating the use of let in various scoping contexts, with and without typed arguments and type casting, as well as the use of sampled value functions in let definitions.

In this example, let instances are used in three assertions, a1, a2, and a3. While the form of the instance is legal in a2 and a3, it is illegal in a1. Why?

The sampled value function requires a clocking event for updating the previous value of its argument. There is no clocking event available and it cannot be inferred when x is expanded in a1. This results in an illegal use of past. In a2, the clocking event is explicitly specified in the sampled value function in the definition of p. Therefore, after substitution of p into a2, a legal form of the deferred assertion a2 is obtained. Finally, in a3 there is no explicit clocking event in the sampled value function, after substituting the body of p into a3, the assertion contains the following body:

```
a3: assert property(@(posedge clk) a |-> ($past(a && b)));
```

The property in the assertion that resulted from the substitution is perfectly legal because the clocking event for the sampled value function is inferred from the assertion.

We now examine some problematic cases. They are not explicitly identified as illegal in the SystemVerilog LRM, but their use may lead to some unexpected results and should be considered as illegal. The first case involves explicit or implicit form of *variable Ivalue* assignment, that is, the variable or expression on the left-hand side of an assignment.

```
Example 7.6.
let inc1(int x) = x++;
let inc2(bit [7:0] y) = y+=2;
let combinetwo(integer v, w) = (v = v + w);
module m;
bit clk;
integer a, b;
al: assert property (@(clk) inc1(a));
a2: assert property (@(clk) inc2(a) == 1);
property p;
@(clk) combinetwo(a, b);
endproperty
a3: assert property (p);
endmodule
```

After substitution of let, we obtain the following code:

```
module m;
bit clk;
integer a, b;
a1: assert property (@(clk) (int'(a)++));
a2: assert property (@(clk) (((type bit [7:0])'a+=2) == 1));
property p;
   @(clk) ((a = a + b));
endproperty
a3: assert property (p);
endmodule
```

7.1 Let Declarations 169

Assertion all contains an illegal form -int'(a) is an expression, not a variable, hence the increment operator cannot be applied to it.

Assertion a2 results in an illegal form because type cast is applied to the whole implicit assignment, and it is not clear how the type cast is to be interpreted.

Assertion a3 is seemingly legal, but there is a side effect of replacing the current value of a by its sampled value summed with b. The SystemVerilog LRM does forbid assignment expressions in Boolean expressions in sequences and properties, but not let statements. Even if supported by a simulator, the outcome may be rather unexpected and difficult to understand. Which value is compared with 1 in assertion a2? The old one or the new one? It would appear that it should be the old sampled value, but is it? Is the sampled expression just \$sampled(a) or is it \$sampled(a + b) in assertion a3?

If the let definitions were written by the same person who writes the assertions, perhaps the expected outcome is clear to that person. However, if the let declarations are part of a package and the user knows little about its contents, then usage of such forms with side effects becomes problematic and should be illegal.

A similar recommendation applies to passing such expressions as actual arguments to otherwise simple innocuous let definitions. This is illustrated on the next example.

```
let inc(int x) = x;
module m;
  bit clk;
  integer a, b;
  a1: assert property (@(clk) inc(a++));
  a2: assert property (@(clk) inc(a+=1) == 1);
  property p;
    @(clk) inc((a = a + b));
  endproperty
  a3: assert property (p);
endmodule
  After substitution, the code is as follows
module m;
  bit clk;
  integer a, b;
  al: assert property (@(clk) int'(a++));
  a2: assert property (@(clk) (int'(a+=1) == 1));
  property p;
    @(clk) (int'(a = a + b));
  endproperty
  a3: assert property (p);
endmodule
```

Example 7.7.

The outcome of the let substitution is equally illegal or confusing as in the preceding example.

Do not use expressions with side effects such as increment/decrement and operator assignment expressions in let actual arguments and in let definitions.

Another issue that is not sufficiently discussed in the SystemVerilog LRM is the application of bit and part selects over let instances, part and bit selects over formal arguments in let defining expressions, and in passing bit or part select as actual arguments to let instances. The problem is that unless the user is aware of the let definition details, such use may create illegal expressions once the let body is substituted in place of the instance. We illustrate some of the problematic situations on the following example.

```
Example 7.8.
typedef bit[1:0] bt_t;
module m;
logic [7:0] a;
logic [7:0] [2:0] b;
logic c, d, e, f;
let lt1(bt_t x) = x;
let lt2(x) = x[1:0];
let lt3(x) = x;
assign c = lt2(a)[0];
assign d = lt1(a[4:0])[0];
assign e = lt2(a[4:0]);
assign f = lt3(a)[0];
```

After substitution of let arguments and bodies into the assignments, we get the following equivalent code:

```
typedef bit[1:0] bt_t;
module m;
logic [7:0] a;
logic [7:0] [2:0] b;
logic c, d, e, f;
assign c = (a[1:0]) [0];
assign d = (bt_t'(a[4:0])) [0];
assign e = ((a[4:0]) [1]);
assign f = (a) [0];
```

The assignments to c, d, and e result in illegal expression forms. This is because a bit or part select is taken from a parenthesized expression which is a part select itself. Assignment to f is equally illegal even though the argument is just a variable identifier in which case it would perhaps make sense to allow substitution without the enclosing parentheses.

Do not apply any select operators on let instances.

7.1 Let Declarations 171

7.1.1 Syntax of let

let declaration and its actual arguments have the following form:

```
let identifier [ (let_port_item{, let_port_item]}]) ] = expression;
```

let_port_item allows port types that are restricted to integral types and event. Also, untyped formal arguments may be used to indicate any type, but the type of the actual arguments is still restricted to any of the integral types and event. There is no use of port direction, hence port direction specification is not allowed.

Unlike in sequence and property declarations discussed later in this chapter, the port type using the keyword untyped is not allowed according to the SystemVerilog LRM. Untyped ports can thus be used at the beginning of the formal port list, but once a type is specified on a port, then all subsequent ports must have a type. This is illustrated in the following example:

Example 7.9. Typed arguments.

```
let my_let(x, bit y, z) = y ? x : z;
```

The formal argument x is untyped. It can be of any integral type. The arguments y and z are of type bit. This means that their actual arguments must be type compatible to type bit and is first cast to bit before substituting in the expression y? x: z in the let instance.

The formal arguments can also have default actual argument expressions assigned to the formal arguments.

The right-hand side of the definition and the actual arguments (default or otherwise) are general *expression* forms. As we discussed earlier, the expression must be void of implicit and explicit variable assignments.

A let *instance* can be used wherever an expression can be used. The instance consists of the let identifier followed in parentheses by a list of actual arguments. An actual argument can be specified in one of several ways, like in functions and tasks:

- Missing when an actual argument is not provided. The default expression for the corresponding formal argument is used.
- Positional binding the list of actual expressions is separated by commas. They are associated with the formal arguments in the order of appearance.
- Named binding .formal_identifier(actual_expression) the actual argument is explicitly associated with a named formal argument. The order in which they are written is immaterial. If actual_expression is missing, then again the default actual expression is used.

If a mix of positional and named binding is used, then the positional form must precede any named form.

7.1.2 Uses of let

let is useful for abstracting expressions and for configuring them as templates in a checker library. A strong case for this abstraction form is when such a template is picked up from a checker library, and instantiated in immediate and deferred assertions. The following example illustrates this point, but for detailed discussion of this topic, see Chap. 23.

```
Example 7.10.
```

Module check is a combinational checker that verifies in assertion at that the ports decoded and sel never has an x or z value in any bit position, and in assertion at that the port sel has at most one bit asserted 1. Assertion at is checking the expression regardless of whether rst is asserted or not because the default value of 0 is used as the actual argument for reset. Assertion at is disabled when rst is asserted 1.

Notice that we could have used functions <code>somehot</code> and <code>sisunknown</code> directly in the assertions, but then the reset argument would have to be always added in the expression of the assertion, which can be error prone. The <code>let</code> template in a library allows to hide this detail and makes the use of the functions more user friendly. Similarly, we could define a template for <code>spast</code> that provides different default values for its arguments than those provided by the function definition. The let declaration can be placed in a package and then imported wherever needed.

let definitions are also very important in checker definitions (Chap. 21), and that not only for the reason mentioned above, but also because they are used to serve the purpose of continuous assignments that are illegal in checker bodies.

let declarations are suitable for libraries of property-like templates in packages to be used in deferred and immediate assertions. They are necessary for replacing continuous assignments in checker definitions.

To conclude this section, we wish to mention that unlike wires, let definitions can be used to define expressions that are temporarily used and not meant to be synthesized. For instance,

```
always_comb w = a & b;
assert #0 (w == 1);
```

If w is used only in the assert statement, the synthesis tool may or may not synthesize this signal, even though it is not required in the physical implementation of the design. Using let w = a & b; instead avoids this problem. The conventional solution is to use 'ifdef ... 'endif to enclose nonsynthesizable code but it is less elegant.

It will be interesting to see what other uses will be devised for let, and what kind of support various software tools will provide for debugging code that contains let statements. Since let is part of the language unlike macros, it may be possible to trace its evaluations and even collect coverage.

7.2 Sequence and Property Declarations

Sequence and property declarations allow users to compose temporal formulas into units that can be instantiated in other such units as well as in assertions. This mechanism thus provides means for abstracting temporal behavior to building more complex temporal formulas. The declarations of a sequence and property are named, and available with optional arguments. The formal argument list definition in sequence declarations is similar to that in property declarations, except that the latter also allows properties as arguments. The declaration interface and substitution of an instance by the body of its definition are similar to let, but more complex due to the presence of clocks and disabling conditions. Furthermore, formal argument list and the association of the formal with actual arguments differs considerably from the port list defined for modules, programs, interfaces, functions, and tasks.

We illustrate briefly some of these constructs in the following example. More details are provided in the subsequent section.

```
Example 7.11.
sequence sf_after_a(
   event clk = $inferred_clk, logic a, sequence sf, int n = 1);
@(posedge clk) a ##n sf;
endsequence

property seq_impl_prop(logic rst = $inferred_disable,
   event clk = $inferred_clk, sequence sf, property pf);
   disable iff(rst) @clk sf |-> pf;
endproperty
```

The sequence sf_after_a has as its formal argument a clocking event named clk. It has a default actual argument which is, in this case, the system function \$inferred_clock. In the absence of an actual argument, it infers the clocking event from the instantiation context of the sequence. The sequence has three additional formal arguments. The first one is logic a. The type is explicitly specified to ensure that the actual argument be type compatible with logic. The second one is

sequence sf restricting the actual argument to be an expression or a sequence. An expression is allowed because it is also a simple (Boolean) sequence. The final argument is used as a constant in the delay operator and is thus restricted to an integral type. The body of sf_after_a states that n cycles after a the sequence sf should start evaluating at the next clock tick. When sf matches, the sequence sf after a matches as well.

Property seq_impl_prop has two formal arguments clk and sf that are of the same type as in the case of the preceding sequence declaration. It has two additional arguments, however. The first one of them, rst, is used as the disable iff expression of the property. It has a default actual argument that is used in the absence of an actual argument in the property instance. It can infer the disabling expression from a default disable iff expr declaration. The second one is an argument of type property and thus the actual argument can be an expression, a sequence or a property, but it cannot be a clocking event.

Suppose now that there are the following declarations in a module (or program or interface or checker):

```
Example 7.12.
logic reset, clock, v, w, x, y;
default disable iff !reset;
default clocking ck @(posedge clock);
endclocking
sequence s;
  v[*3];
endsequence
a_until: assert property(
  seq_impl_prop(, , sf_after_a(, w, s, 1), (x until y));
c_seq: cover property(disable iff (!reset)
  sf_after_a(, w, s, 1));
```

How are the assertion and coverage statements to be interpreted? First, some basic rules are applied in the order as shown below:

- 1. Substitute actual arguments for all occurrences of the formal arguments in the body specifications.
- 2. Substitute sequence or property instances by their body specifications.
- 3. Apply inference rules.
- 4. Apply clock flow rules to determine sampling clocks for all expressions that need a clocking event (see Chap. 12).

In general, the rules cannot be applied just once as stated, rather it has to be a recursive application of the rules starting from the top property expression in the assertion until all the substitutions are completed, resulting in a property specification containing no unclocked expressions and no instance of another property or sequence.

Let us apply these rules to the example. First consider assertion a_until. For substituting seq_impl_prop instance body into the assertion requires to determine its actual arguments. The first two actual arguments are missing in the instance specification; therefore, default values are used. In this case, they are inferred. For rst the argument \$inferred_disable is inferred from default disable iff and thus it is !reset. For clk, \$inferred_clock is inferred from default clocking and thus it is posedge clock.

The third argument is an instance of sequence sf_after_a which itself needs its actual arguments. The first argument is again inferred from **default clocking** as **posedge** clock. The second one is variable w and the third one is an instance of sequence s. The last argument is for pf, and it is simply x until y where x and y are variables declared in the module. The assertion with the actual arguments substituted has the following form:

```
a: assert property(seq_impl_prop(!reset, (posedge clock),
   sf_after_a((posedge clock), w, s, 1), (x until y));
```

We can now proceed with the substitution of the arguments into the body of seq_impl_prop. It becomes

```
disable iff (!reset) @(posedge clock)
  (sf_after_a((posedge clock), w, s, 1)) |-> (x until y)
```

The next step is to substitute the body of the sequence sf_after_a. Its sequence expression after substitution of the actual arguments becomes

```
@(posedge clock) w ##1 (v[*3])
```

where (v[*3]) is the body of sequence s. The final form of the body of assertion a_until before clock flow is applied is as follows:

```
disable iff(!reset) @(posedge clock) (@(posedge clock)
  (w ##1 (v[*3])) |-> (x until y)
```

The top-level clock is pushed into the antecedent sequence of the implication and then flows into the consequent property as explained in detail in Chap. 12. The result in this case is a single-clocked property, running on posedge clk.

```
disable iff(!reset) @(posedge clock)
  (w ##1 v[*3]) |-> (x until y)
```

What is the type of expressions x and y? Since x and y are variables (i.e., Boolean expressions), these expressions are in fact simple Boolean sequences. They are used in a property context as the operands of the until operator, hence they are *promoted* to properties.

Regarding the **cover property** statement c_seq, the sequence instance is identical to one used in the assertion; therefore, the final form of the sequence expression used in the property expression is as follows:

```
disable iff (!reset) (@(posedge clock) w ##1 (v[*3]))
```

In the preceding example, the inference was quite simple, both the clock and the disabling expression were obtained directly from the default declarations. What happens if an instance of a property or sequence is used directly inside the body of another property or sequence definition? How is the clock or disabling expression inferred in such cases? This will be discussed after we examine the syntax for defining sequences and properties.

7.2.1 Syntax of Sequence-Endsequence

The syntax of a sequence declaration is as follows, where items in [] brackets are optional:

```
sequence identifier(list_of_ports)
  {local_variable_declarations}
  sequence_expression;
endsequence [ : identifier ]
```

The *list_of_ports* consists of a possibly empty comma-separated list of individual port declarations. Each such port can have the following components:

```
[ local port_direction ] ] type
  identifier {dimension} [ = default_argument ]
```

where

- port direction is only allowed when the keyword local is used indicating that it is a local variable port (see Chap. 16). It can be input, output, or inout.
- *type* is a type specification. It is obligatory when the port is a local variable port, otherwise it is optional. In addition to any integral type, the type can also be an event, sequence, or the keyword untyped untyped indicates that the port(s) following the keyword do not have any formal type and is used to explicitly denote ports as untyped, especially when typed ports precede an untyped port.
- *identifier* {*dimension*} is a usual port name which can have an optional specification of dimensions provided that it is a local variable port or a typed integral port.
- *default argument* is an optional default actual argument. It has to be type compatible with the port type in the case the type is specified.

The declaration of a sequence is an extension of the interface of let. The main differences are the addition of types event and sequence, and the possibility to indicate local variable ports with their direction and type. There is also the addition of the keyword untyped to indicate ports that have no specified type. Let us concentrate on ports other than local variable ports, the latter are described in detail in Chap. 16. The type of a port may be specified, but it can also be left without a type like in let declarations. A port without a type specification can be specified only before any typed ports is stated on the port list which is the only way to do

that in let declaration, but also when the untyped keyword is used in place of a type specification. How is the type determined, used, and verified in that case? For example, consider the following sequence interface:

```
sequence s def(a, event b, int c, d, untyped s);
```

The port a is untyped and its type correctness depends on where it is used in the sequence. Port b must be a clocking event expression. Ports c and d are of type two-valued integer. The actual arguments bound to these ports must be type compatible with int. Finally, since s is preceded by untyped, the actual argument bound to this port can be anything compatible with its use in the sequence expression. Suppose that the sequence expression is as follows:

```
@b a && (c == d) \#1 s
```

In this case, a is restricted to be an integral expression, and c and d can be any integral type that can be cast to int. The actual argument bound to the last port, s, can be an expression or a sequence expression including a sequence instance. This is because it is used alone as one of the operands of the sequence operator ##1. If it were used as a in an expression, its type would have been restricted the same way as for a.

Consider now a different sequence expression:

```
@b (a + c == d) \#1 s
```

Let v be a variable of type bit, and the actual arguments of s_{def} be 2'bl1 + v, (posedge clk), 1, 0, v. When the actual arguments are substituted to the sequence expression, we obtain

```
@(posedge clk) ((2'b11 + v) + 1 == 0) \#1 v
```

Suppose that v is 1'b1 over two clock cycles. Will the sequence match or not? Before substituting the expression 2'b11 + v for the formal argument, it is enclosed in parentheses and cast to its self-determined type. Therefore, the result is an unsigned two-bit expression. When the value of v is 1'b1, it is 0 extended to 2'b01 before being added to 2'b11. The addition yields the result 2'b00. This result is then sign extended to int which yields 0 + 1 == 0 as the final Boolean expression. The sequence thus does not match at the first clock tick. If v were 1'b0 in the first clock cycle and 1'b1 in the second clock cycle, then the result of the addition is 2'b11, which after sign extension to int yields -1. Therefore, the result of the addition with 1 is 0. Consequently, the first expression evaluates to true, and the sequence will match at the second clock tick since v is 1'b1.

Actual arguments to sequences are enclosed in parentheses and cast to their self-determined type before being substituted for occurrences of formal arguments in the sequence body. The same applies to actual arguments to property instances discussed in the next section.

The actual argument for s could also be a sequence expression. For example, suppose that the actual argument is $x \#1 \ y \ or \ v \#2 \ w$. This is syntactically correct sequence expression. The variables x, y, v, w must exist in the instantiating context otherwise it is an error. Let the list of actual arguments be

```
2'b11 + v, (posedge clk), 1, 0, x ##1 y or v ##2 w
```

After substitution for the formal arguments, the resulting expression for sequence s def becomes

```
@(posedge clk) (2'b11 + v + 1 == 0) ##1 (x ##1 y or v ##2 w)
```

Notice the parentheses around the sequence expression that was substituted for the occurrence of the formal argument. It is only when the untyped argument is substituted into the sequence expression that its syntactic and semantic validity can be ascertained. In this case, all is well. If the same sequence expression were provided for the untyped formal argument a, it would result in an error, because after substitution, the actual argument sequence expression becomes an operand of an addition.

The question is, should untyped arguments be used at all? The advantage of untyped arguments is that they do not restrict the actual argument to any particular type. This can be very useful in the case of integral types where the dimensions need not be specified. The usual type checking is performed after the actual argument has been substituted wherever the formal argument appeared in the sequence definition. Therefore, the resulting error message may point to the body of the sequence and thus may not be easily comprehensible to the user. For instance, the interface of s_def could be written as

```
sequence s_def(bit [1:0] a, event b, int c, d, sequence s);
```

This still leaves much freedom as to the actual argument for s, because it can be any integral expression or a sequence expression. It would seem that if the sequence definition s_def above were to be reused, e.g., as part of a library package, then it is preferable to specify the expected types of the arguments except in the case where any integral type is allowed and type conversion to int is not desired (see Chap. 21 for further discussion about untyped vs. typed arguments).

The formal argument can also have default actual assignment specified in the header, as shown in the definition of <code>sequence_port_item</code>. The default argument specification is resolved in the scope of the sequence declaration. This is different from the usual actual arguments, which are resolved in the scope of the sequence instance. For example, let us consider the sequence header for <code>s_def</code> but add default actual argument specifications:

```
sequence s_def(
  a, event b = $inferred clock, int c, d, untyped s = x);
```

In this case, in the absence of actual arguments for the formals b and s, like in the instance specification $s_{def(2'b11+v)}$, 1, 0) or equivalently using named argument association $s_{def(a(2'b11+v))}$, .c(1), .d(0)), we can see that neither the formal b nor s has an actual argument. Therefore, the clocking expression of

the sequence instance will be inferred from the instantiation context (see Chap. 14), and the formal argument s will be replaced by x. This variable or sequence definition x must have been declared in the scope of the declaration of s def.

Next, we discuss **property** declaration, in particular in its differences from a sequence declaration.

7.2.2 Syntax of Property–Endproperty

The syntax of a property declaration is quite similar to that of a sequence declaration. The differences are as follows:

- 1. The encapsulation keywords are property-endproperty.
- 2. The formal and actual arguments can also be *property expressions*. The type of a formal argument may thus be **property**.
- 3. The body of a property declaration may contain *property operators* and refer to other *property instances*.
- 4. Local variable argument can only be local input (see Chap. 16).
- 5. The property may contain disable iff (condition) definition. The default actual argument to a formal of some integral type (or untyped) can be \$inferred disable (see Sect. 7.3).

The first one is obvious. The second and third differences are a natural extension from sequences to properties in that a property can receive a property expression as its argument and can operate on properties. Note also that under the property expression, sequence expressions and integral expressions are type compatible actual arguments. The fourth difference is because local variables do not flow out of properties (see Chap. 16). In properties, local variables have nowhere to flow out since no concatenation of properties exists. The fifth difference provides means to pass a default disable expression to a top-level property instance in an assertion. Some of these points are illustrated in the next example:

After clock inference, substitutions, and clock resolution are completed, this combination of properties and their instances results in the following assertion:

```
a_imply: assert property(
   disable iff (!reset)
   @(posedge clock) !d ##1 d |-> a |-> b until c);
```

The lack of specified actual argument for clk in the instance of pl causes to infer the actual from default clocking declarations. Since pl is the top-level property in the assertion, the disable iff specification is legal.

If, on the other hand, disable iff were included in p2 as shown in the next example, the resulting property expression in the assertion would become illegal. This is because disable iff would not apply to the top-level property.

```
Example 7.14.
module m;
bit clock, reset, a, b, c, d;
default clocking @(posedge clock); endclocking
//...
property p1(event clk = $inferred_clock, bit x, property p);
    @clk !x ##1 x |-> p;
endproperty
property p2;
disable iff (reset) a |-> (b until c);
endproperty
a_illegal: assert property(p1(.x(d), .p(p2)));
//...
endmodule
```

After substitutions are carried out, the result is the following illegal assertion because disable iff is not applied to the top-level property expression (see Sect. 3.4.4):

```
a_illegal: assert property( @(posedge clk) !d ##1 d |->
    disable iff (!reset) (a |-> (b until c)) );
```

Placing disable iff specifications into property definitions must be planned carefully, otherwise it can lead to unexpected compilation errors.

Like let definition, sequence and property definitions may be placed in packages for later reuse. In that case, particularly the use of disable iff into such reusable properties must be done with even greater care.

In the next sections, we examine the inference of disable iff expression and of clocking event.

7.3 Disable Expression and Clock Inference

The default disable iff statement provides a default disable condition for assertions where the disable condition is not explicitly specified. Similarly, default clocking provides a clocking expression that can be inferred when not explicitly specified. Both default statements can be specified only once in a module, interface, program, and checker, and their effect extends over the full scope of the object. It does not extend, however, to any instances of such objects. For a detailed discussion about clock and disable expression inference see Chaps. 12, 13, and 14.

Exercises

- **7.1.** Write down a parameterized let definition that can be included in a package for the following situation. Include means to make the let expression take some useful default value when the argument rst is 1'b1. Illustrate its use in some assertion and assignment statement.
- (a) Evaluate to 1'bl only when the vector argument sig has at most one 1 or one 0 and the rest is either x or z. Otherwise, return 1'b0. Should the argument sig be typed or untyped? Why?
- (b) Is it possible in a single let definition to restrict the above definition to return 1'b1 only if there is at most one 1 or one 0, and the rest are z (i.e., exclude x)?
- **7.2.** Write down a simple module that has the variables clk, reset, a, and b of type logic, and add a concurrent assertion that fails when a is 1, and at the next clock tick b is 0, 1, or x. Let the clock and reset be inferred from the module context.
- **7.3.** Provide a solution to Exercise 7.2 such that the property used in the assertion is first defined outside the module, e.g., in a package.
- **7.4.** What kind of actual arguments can be legally passed to the property that you defined in Exercise 7.3. Can you generalize the property to accept a wider range of arguments? How should the specification of the property change?

Chapter 8 Advanced Properties

No man acquires property without acquiring with it a little arithmetic also.

- Ralph Waldo Emerson

This chapter briefly recapitulates the basic properties discussed in Chap. 4 and discusses more complex property operators. First, we examine the property equivalents of Boolean operators, namely, not, or, and, implies, iff, if else, and case. Then we provide a description of temporal operators inspired by Linear Temporal Logic. The operators are described informally; the reader interested in formal semantics should consult Chap. 20. Recursive properties are described in Chap. 17, and the abort operators accept_on, reject_on, sync_accept_on, sync_reject_on are discussed in Chap. 13. In all examples, we assume that the properties and assertions are in the scope of a default clocking declaration, hence no explicit clocks are specified.

Most of the temporal operators come in two forms, weak and strong. The strong forms are identified by a prefix **s**_as in **s_nexttime** p. In simple terms, the strength determines the property evaluation result when there are not enough clock ticks to complete the evaluation of the operator, e.g., at the end of simulation or when the source stops emitting them. More precise explanation is given in Chap. 11.

Table 8.1 lists all the property operators available in the language. The order of appearance is in decreasing precedence, beginning with the highest on the top. Operators appearing in one block of the table have the same precedence. Blocks are separated by horizontal lines. For example, not, nexttime, and s_nexttime have the same precedence.

8.1 Sequential Property

In addition to the property operators listed in Table 8.1, sequences are promoted to properties when used in a property context. We call them sequential properties, or sequence properties (see also Chap. 5). This happens when a sequence is used as the only expression in an assertion or as an operand to a property operator that

Table 6.1 Froperty operators	
Operator	Associativity
not	_
nexttime, s_nexttime	_
and	Left
or	Left
iff	Right
until, s_until	Right
until_with, s_until_with	Right
implies	Right
->, =>	Right
#-#, #=#	Right
always, s_always	_
${\tt eventually}, {\tt s_eventually}$	_
if else, case	-
accept_on, sync_accept_on	_

 Table 8.1
 Property operators

requires the operand to be a property. Sequential properties can be *weak* or *strong*. A sequence becomes a strong property when it is the argument to a strong (...) qualifier, e.g., strong (a ##1 b). A strong sequential property holds if and only if the underlying sequence has a match. Without this strong qualifier, a sequence property is weak in the assertion or assumption context, and strong in the cover context. As we shall see, in situations where a sequence is strong by default, it can be made weak by using the qualifier weak (...). The distinction between strong and weak sequential properties is reflected in their truth value when there are not enough clock ticks to complete the evaluation of the sequence: If there are not enough clock ticks the weak sequence property succeeds, while the strong one fails.

Example 8.1. Consider the following assertions:

```
initial a1: assert property(a ##[+] b);
initial a2: assert property(strong(a ##[+] b));

a3: assert property(!a ##1 a | -> b[*] ##1 c);
a4: assert property(!a ##1 a | -> strong(b[*] ##1 c));

c1: cover property(a ##[+] b);
c2: cover property(weak(a ##[+] b));
```

reject on, sync reject on

Note: Recall that b[*] is a shortcut for b[*0:\$] and ##[1:\$] is a shortcut for ##[1:\$]. The sequence in assertion a1 is weak because it is used as the property of an assert statement, and there the default is weak. Therefore, when an attempt is triggered by a true and b does not become true, that evaluation attempt of the assertion succeeds. In this situation, however, a2 fails because the sequential property is explicitly qualified as strong.

Assertions a3 and a4 are a little more complex. Each contains two sequences: !a ##1 a and b[*] ##1 c. The former sequence is used as the antecedent (or precondition) of the suffix implication |->. If a thread of evaluation of that sequence does not complete due to lack of clock ticks or because !a is false or is not followed by a in the next clock tick, that thread fails, and in the context of the antecedent it contributes no match. In those cases the assertion attempt has a vacuous success (Sect. 8.6). The consequent sequence b[*] ##1 c is a weak property in a3 and a strong property in a4. The interpretation is similar to that of a1 and a2. That is, in the absence of a sufficient number of clock ticks or if b remains true forever while c is never true, the consequent of a3 succeeds, while that of a4 fails.

In the case of covers c1 and c2, the default strength of a sequence used as the coverage property is strong. This is done so that a coverage hit is not registered when the sequence does not complete evaluation, e.g., due to lack of clock ticks. To override the default behavior, the qualifier weak should be used, as in c2.

Let us now examine the various property operators from Table 8.1.

8.2 Boolean Property Operators

The following property operators express Boolean connectives between properties:

- not p negation
- p or q disjunction
- p and q conjunction
- p implies q implication
- p iff q equivalence
- if (b)p else q if conditional
- case (b) . . . case conditional

Here is their informal description; their formal semantics can be found in Chap. 20.

not p

The property not p is true iff the property p is false.

Example 8.2. What is not e where e is a Boolean expression? According to the definition, not e is true iff e is false as a property. If the clock ticks, then e is false as a property iff! e is true as a Boolean expression at the first clock tick. If the clock does not tick, then e is false as a property iff it is a strong sequential property at the first position of the trace. If the property clock is the global clock, then not e is equivalent to !e (see Chap. 20, Example 11.29).

¹ Though cover c2 is rather meaningless.

p or q

The property p or q is true iff either property p or property q is true (Chap. 4).

The syntax is the same as for sequence disjunction discussed in Chap. 5. When the sequence disjunction is used as a property it can be replaced by property disjunction with the same constraint on the strength of the sequence disjunction as on both p and q.

p and q

The property p and q is true iff both properties p and q are true (Chap. 4).

Note that the syntax of property and is similar to that of the sequence and operator s1 and s2 described in Chap. 9. However, they have similar meaning only when the sequence and is used as a property, and the strength of both p and q is the same as the strength of the sequence s1 and s2.

For further discussion, refer to Sects. 9.1.5 and 4.5.

```
p implies q
```

The property p implies q is true iff either property p is false or q is true (see Chap. 20).

When p and q are Boolean expressions e1 and e2, respectively, then e1 implies e2 is equivalent to e1 -> e2 provided the clock ticks. This equivalence holds, e.g., if the sampling clock is the global clock, which is guaranteed not to stop. For further discussion on the semantics of implies, see Chap. 20.

Previously (Chap. 5) we discussed suffix implication |->, which also involves a property, but only in the consequent. This has to be contrasted with property implication implies:

In $s \mid -> q$, where s must be a sequence and q some property, the evaluation of q starts at the time when any evaluation thread of s has a match. In p implies q, p and q are properties, hence there is no notion of an endpoint and a match. Both p and q start evaluating at the same time and the truth results are computed using the logical operator implies. For example, consider

```
a ##1 b |-> c ##1 d

VS.

a ##1 b implies c ##1 d
```

In the case of |->, the consequent c ##1 d will start evaluating when a ##1 b matches. In the case of implies, both a ##1 b and c ##1 d start evaluation at the same clock tick. Finally, if p is a sequence s, writing strong(s) implies q is equivalent to s |-> q only when s is a Boolean expression. The Boolean implication b1 -> b2 is a short-hand for !bit'(b1)|| b2. Therefore, unlike property

and suffix implications, such Boolean expressions have no notion of vacuity of evaluation. That is, the evaluation of b1 -> b2 as a sequence property is always nonvacuous (see Sect. 8.6).

An interesting example that uses implies is as follows.

Example 8.3. The signal sig should be high from m >= 0 clock ticks before event ev happens until n >= 0 clock ticks after it. That is, if ev happens at time 10, m = 2, and n = 3, then sig should be high at times 8, 9, ..., 13.

Solution:

```
a1: assert property (
   strong(##m ev) implies sig[*(m + n + 1)]);
```

We have used a strong sequence strong (##m ev) in the antecedent of implies so as to require that there are enough clock ticks for ev to become true.

To express the same using | -> the assertion becomes more complex:

```
a2: assert property (
    (!sig |-> !ev[*(m+1)]) and (ev |-> sig[*(n+1)]));
p iff q
```

The property p iff q is true iff either properties p and q are both true or they are both false (Chap. 20).

Like the case of implies, when p and q are Boolean expressions e1 and e2, respectively, then e1 iff e2 is equivalent to e1 <-> e2 provided the clock ticks, e.g., if the clock is the global clock.

When can iff be used? A very useful application is in verifying that two property definitions have the same meaning: The same property may be implemented in different ways because one implementation may be much more efficient in simulation and the other in formal verification. Often the two properties look and feel similar, yet they are not equivalent. If we check their equivalence in formal verification a counterexample explains the difference. Only the assertion comparing the properties and wire or module input declarations of the variables used in the assertion are required in this case; neither a model nor assumptions are needed.

Example 8.4. Check that the properties always nexttime e and nexttime always e are equivalent.

Solution:

```
wire e;
initial a: assert property (
   (always nexttime e) iff (nexttime always e));
```

The following example is perhaps less evident, yet the two properties are in fact equivalent:

```
Example 8.5.
property p1;
  not (a[*] ##1 b);
endproperty
property p2;
  strong(!b[+] ##0 !a);
endproperty
al: assert property(p1 iff p2);
```

The property if (b)p is true if Boolean b is false or p is true. The property if (b)p else q is true if Boolean b is true and p is true, or b is false and q is true.

Note that is possible to express the same using suffix implication, as

```
b |-> p and (b |-> p) and (! (bit'(b)) |-> q), respectively.
```

Clearly, the if-else form is easier to understand than its equivalent using suffix implication, as illustrated in the following example.

Example 8.6. In assertions a1 and a2, if b is true, a should be false or b should be false one clock tick later, else if b is false then a must be true, followed by b true one clock tick later. Clearly, assertion a1 is easier to understand. Assertion a3 uses an if property without the else clause. In that case, the equivalent formulation shown in assertion a4 is as easily understood, hence there is no preference between them.

Property case is a generalization of if-else for a multiple-valued condition b.

```
case (b)
b1: p1;
...
bN: pN;
default: p;
endcase
```

case (b) ...

П

The property case (b)... is true iff either pi evaluates to true for the first i such that the value of bi matches the value of b, or no bi matches the value of b and if the *optional* default item property p is specified then it evaluates to true. If the default case item is not specified and no bi matches the value of b, then the property case is vacuously true.

A case operator can be used, for example, to define a property in which a sequence delay varies based on some register value. Of course, for practical purposes a small range of delays is assumed:

```
Example 8.7. property p(bit [2:0] delay);
  case (delay)
    0: a;
    1: nexttime[1] a;
    2: nexttime[2] a;
    3: nexttime[3] a;
    4: nexttime[4] a;
    default: 1'b0; // delay too large endcase
endproperty : p
```

The same property could be written using a chain of if-else property operators, but the meaning of such nested operators is less obvious than when using the case operator. It is left to the reader as an exercise at the end of the chapter to rewrite the property in Example 8.7 using if-else.

Many of the following operators have been briefly described in Chap. 4, and their formal semantics can be found in Chap. 20. Here, we provide an intuitive recapitulation of the operators, further clarifying the distinction between the strong and the weak forms and between the bounded and unbounded forms. The bounded variants evaluate the operand property over finite, bounded numbers of clock ticks, while the unbounded ones evaluate over indefinite but finite numbers of clock ticks.

8.3 Suffix Operators: Implication and Followed-By

The following are suffix operators:

- Suffix implications | -> and | =>.
- Followed-by operators (also named suffix conjunctions) #-# and #=#.

```
Suffix implications | -> and | =>
```

The suffix implications have been discussed in Chap. 5. We summarize them here because we need them to describe the *followed-by* operators.

A *suffix implication* operator takes a sequence as the left-hand operand and a property as the right-hand operand: $s \mid -> p$ and $s \mid => p$. Whenever s matches, property p must hold. When s has no match then a suffix implication is vacuously true.

The difference between the two forms is that in the case of |-> the evaluation of property p starts at the clock tick that occurs at or after the tick when s matches. In the case of |-> the evaluation of p starts at the clock tick that occurs strictly after the clock tick when s matches. When the ending clock of s (meaning the clock of the latest evaluated expression of s) is the same as the leading clock of p, then in the case of s |-> p property p starts at the same clock tick when s matches, while in the case of s |-> p, property p starts at the clock tick following the match of s. This is why |-> is called an overlapping suffix implication, and |-> is a nonoverlapping one.

Followed-by

The followed-by operators #-# and #=# also have a sequence as the left-hand operand and a property as the right-hand operand: s #-# p and s #=# p. If s has no match, then followed-by evaluates to false. If s has one or more matches for a given evaluation attempt, then for the property to evaluate to true, at least one match of s must result in p evaluating to true (see Table 8.2). In this sense, the behavior is similar to sequence concatenation with ##0 and ##1 cycle delays. The difference is that sequence concatenation requires a sequence as the right-hand side operand, while followed-by accepts a property there. This is also the reason that followed-by is sometimes called a suffix conjunction or suffix concatenation. If property p is in fact a strong sequential property (e.g., if s1 #-# s2 appears in a cover), then s1 #-# strong(s2) is the same as strong(s1 ##0 s2). Similarly, s1 #=# strong(s2) is the same as strong(s1 ##1 s2). As to when p starts its evaluation relative to the match of s, the difference between #-# and #=# is the same as between the two forms of the suffix implication. The former is overlapping and the latter is nonoverlapping.

A followed-by operator is a dual operator of suffix implication. The following equivalences hold:

```
s #-# p \equiv not (s |-> not p), and s #=# p \equiv not (s |=> not p)
```

This means that even without the availability of the followed-by operators, the same behaviors could be obtained using the right-hand sides of the above equivalences. The intent is, however, more clearly conveyed by the shorter notation when a followed-by operator is used.

The question is where the use of followed-by is appropriate. Its principal usage is in cover property statements when the right-hand side argument cannot be restricted to a sequence. This often occurs in properties that are used in checker libraries, where the arguments of the checker are not restricted to be Boolean expressions or sequences only.

Table 8.2 Comparison of suffix implication and followed-by

Operator	Antecedent match	Antecedent no match
-> =>	each must yield consequent true	vacuous success
#-# #=#	at least one must yield consequent true	failure

Example 8.8. Consider the coverage property: When a "pattern" x is detected it is followed by a "pattern" y. We may have to restrict x to be a sequence, but y could be nonrestricted and be any property.

```
property p(sequence x, untyped y);
    x #-# y;
endproperty

Its usage could be

cov: cover property(p((req[*2]), (s_eventually ack)));
```

Example 8.9. Ascertain that a reset condition is true for some m initial clock ticks and then it remains false forever. Such a property is often used as an assumption on reset in formal verification.

Solution:

```
initial a: assume property(reset[*m] #=# always !reset);
```

We now examine the temporal operators inspired by Linear Temporal Logic.

8.4 Unbounded Linear Temporal Operators

Linear Temporal Logic (LTL) is a *modal* temporal logic with modalities referring to time, which in SVA means as measured by the occurrence of clock ticks. In LTL, it is possible to write formulae about the future of behaviors following a linear progression of time, such as that a property will eventually be true, that a property will be true until another property becomes true, and so on. The operators can be bounded with some specific ranges or unbounded. The following are linear temporal unbounded property operators available in SVA:

- Weak until and until_with, and their strong forms s until and s until with.
- Unbounded weak always.
- Unbounded strong s eventually.

until operators

- Weak p1 until p2
- Strong p1 s until p2

The operator comes in two forms, weak until and strong s_until. There is only the unbounded form of these operators. The formal semantics are covered in Chap. 20.

The weak until property holds true provided that either p2 is true at the first clock tick or p1 holds true at all clock ticks as long as p2 is false. If there is no clock

tick at which p2 is ever true, the property evaluates true. The strong form s_until is similar except when there is no clock tick at which p2 holds true – the strong form is false in that case.

Example 8.10. Suppose that condition c must hold true between the occurrences of conditions e1 and e2 but not necessarily including these clock ticks.

```
a1: assert property(e1 |=> c until e2);
a2: assert property(e1 |=> c s_until e2);
```

Discussion: Assertion at will succeed even if there are not enough clock ticks for detecting e2 true (provided that c holds till then), while a2 will declare failure in that situation due to the use of a strong until operator.

always and s eventually operators

The following are the unbounded forms of these operators:

- Unbounded weak always p
- Unbounded strong s_eventually p

Property always p is true if p holds true at every clock tick. The operator always is weak, hence when there are no more clock ticks, the property evaluates to true. It is equivalent to p until 1'b0. Recall that 1'b0 is Boolean false in System Verilog.

Property **s_eventually** p is true if there is a sufficient number of clock ticks to find one at which p is true.

What if we negate an always property as not always p? According to the definition this property is true iff always p is false, which means that p is false at least at one clock tick. This is exactly the property s_eventually not p. It is a strong eventually because there must be a clock tick where p is false (otherwise always p would be true).

It follows that s_eventually p is equivalent to not always not p. And also s_eventually p is equivalent to 1'b1 s_until p.

Notice how the negation changes the strength of the resulting property. Negating a weak always we obtain a strong s_eventually. This is because to falsify always we require that the operand property p be false somewhere in the future. It must happen, hence the eventuality is strong. always and s_eventually are dual properties.

In case of a Boolean property e, not always e may be rewritten as s eventually !e.

```
until with and s until with operators
```

The following are the unbounded forms of these operators:

- Unbounded weak p1 until_with p2
- Unbounded strong p1 s until with p2

The weak until_with property holds true provided that either p1 and p2 is true at the first clock tick or p1 holds true at all clock ticks until a clock tick when both p1 and p2 hold true. If there is no clock tick at which p1 and p2 is true, the weak property evaluates true. The strong form s_until_with is similar except when there is no clock tick at which p1 and p2 holds true – the strong form is false in that case.

As in the case of the dual operators always and s_eventually, until and s_until_with are dual operators, as are s_until and until_with. The following equivalences hold:

```
\begin{array}{lll} p & \textbf{s\_until} & q \equiv \textbf{not} & ((\textbf{not} & q) & \textbf{until\_with} & (\textbf{not} & p)) \\ p & \textbf{until} & q & \equiv \textbf{not} & ((\textbf{not} & q) & \textbf{s} & \textbf{until} & \textbf{with} & (\textbf{not} & p)) \end{array}
```

Example 8.11. Write an assertion that verifies the following situation: When Boolean trig is true, property p2 must hold at some clock tick strictly before a clock tick at which property p1 holds.

Solution:

```
a1: assert property (
   if (trig) (not p1) until with p2);
```

The specification is missing one important point, namely, must p2 ever occur? If not, then the above assertion is correct. If yes, then we should require p2 to be true at some clock tick by using the strong form

```
a2: assert property (
  if (trig) (not p1) s_until_with p2);
```

Example 8.12. When req becomes true it must hold until and including gnt. In addition, gnt must happen.

Solution:

```
al: assert property(
  !req ##1 req |-> req s until with gnt);
```

Discussion: If a new request can start immediately at the clock tick following gnt, the assertion would have to be modified as follows because there is no rising edge on req in that situation.

```
a2: assert property(
   (!req || qnt) ##1 req |-> req s until with qnt);
```

The sequence in the antecedent matches when either !req ##1 req happens (i.e., rising transition of req) or gnt ##1 req happens which is the case of a continuing request. Note that another assertion should verify that gnt does not occur without a req.

How should we modify the assertions if it is not required that gnt ever happens after asserting req? The answer is similar to the preceding example, Example 8.11, namely, replace the strong form s_until_with by the weak one until_with. Then, even if gnt never happens after being requested the property will evaluate true.

8.5 Bounded Linear Temporal Operators

Bounded operators are useful when the property to be verified must be satisfied within some specified range of clock ticks. There is the fixed delay property operator nexttime, which is similar to ##m in sequences. The operators always and eventually are provided with ranges in both strong and weak forms.

The behavior of the bounded operators is as follows.

nexttime and s nexttime operators

```
nexttime p
s_nexttime p
nexttime [m] p
s_nexttime [m] p
```

The semantics are split according to the value of the constant argument $\[mu]$ and according to the strength of the operator:

- 1. Weak form: nexttime p is true at tick t if p is true at tick t + 1 or if there is no tick t + 1 or if there are no clock ticks at all. nexttime [0] p has no delay, p has to be true at tick t or there is no tick t. In that sense it is equivalent to (1 |-> p). (nexttime [m] p) for some m > 0 is true if p is true at tick t + m or if there are not enough ticks.
- 2. Strong form: (s_nexttime [m] p), m > 0 is similar to the weak form except that it does require having a sufficient number of clock ticks, i.e., at least m. It is thus equivalent to (not nexttime [m] not p).

For singly clocked properties nexttime [0] p means "either the clock does not tick anymore, or p", and s_nexttime [0] p means "the clock ticks at least once, and p".

For example,

```
initial a: assert property(
    nexttime[0] s_eventually e);
```

means that either the clock does not tick at all, or e holds in some finite number of clock ticks. However,

```
initial a: assert property(
    s nexttime[0] always e);
```

means that the clock ticks at least once and e happens at each clock tick.

When m > 0 the weak form can also be defined recursively. This results in a repetitive application m times of nexttime on p:

```
nexttime nexttime ... nexttime nexttime p
```

As mentioned above, the strong form is defined by double negation: Therefore, for m == 1, nexttime not p says that p does not hold at the next clock tick and

it is a weak form. By negating it, a strong property is obtained saying that "it is not true that p does not hold at the next clock tick". That is, it must hold and there must be at least one clock tick.

Example 8.13. When initial reset rst is deasserted, property p must eventually hold after 2 clock ticks, and there must be enough clock ticks:

Solution:

```
initial a: assert property (
  rst ##1 !rst |-> s nexttime [2] s eventually p);
```

Efficiency Tip In general, it is recommended to use **s_nexttime** with strong operators, and **nexttime** with weak ones. For instance, **nexttime always** p and **s_nexttime s_eventually** p. It is important to note that p is a property. This situation is common and important for assertion libraries, where there are restrictions on the argument type.

Example 8.14. There cannot be two consecutive requests where req is a Boolean expression. One could be tempted to write the following assertion:

```
al: assert property (req and nexttime !req);
```

but this is **wrong**. Assertion all is contradictory: req and nexttime !req must be true at every clock tick, i.e., req must be true at each clock tick and !req must be true starting from the second clock tick. Already at the second clock tick it thus requires that both req and !req are true!

To write this assertion correctly, we can formulate it as "if there is a request, there should be no request at the next clock tick":

```
a2: assert property (req implies nexttime !req);
```

Or, since req is a Boolean expression (or a signal), the assertion can be written more simply as

```
a3: assert property (req |=> !req); or as
a4: assert property (not strong (req[*2]);
```

Example 8.15. If there is no acknowledgment ack after req, then in two clock ticks rtry should be asserted.

Solution: This can be reformulated as "if there is a request then either at the next tick there should be an acknowledgment, or in two cycles rtry should be asserted":

```
a1: assert property (
   req implies (nexttime ack) or nexttime [2] rtry);
```

The same assertion may be rewritten as:

```
a2: assert property (
  req implies (nexttime (ack or nexttime rtry));
```

If req, ack, and rtry are Boolean expressions then the assertion can be simplified as follows:

```
a: assert property (req |=> (ack or ##1 rtry));
```

Bounded eventually and always operators

```
eventually [m:n] p
s_eventually [m:n] p
s_eventually [m:$] p
always [m:n] p
s_always [m:n] p
always [m:$] p
```

The bounded forms of the operators eventually and always, both weak and strong, are derived operators that are defined using weak and strong forms of nexttime, respectively.

- 1. Let $m \geq 0$. (eventually [m:m] p) is the same as (nexttime [m] p). This is a simple equivalence between weak forms. Similarly, (s_eventually [m:m] p) is equivalent to (s nexttime [m] p).
- 2. Let m ≥ 0, n > m. (eventually [m:n] p) is defined recursively as (eventually [m:n-1] p or nexttime [n] p). This recursive definition can be expanded into a disjunction of n-m+1 nexttime properties. For example, eventually [2:4] p is equivalent to nexttime [2] p or nexttime [3] p or nexttime [4] p. To define the strong form s eventually [2:4] p, use s nexttime.
- 3. Let m ≥ 0. (always [m:m] p) is the same as writing (nexttime [m] p). Since the extent where always should hold is only one clock tick, always [m:m] is the same as eventually [m:m] p as well. The strong forms are defined using s nexttime.
- 4. Let n > m. (always [m:n] p) is the same as (always [m:n-1] p and nexttime [n] p). The expansion is a dual form of the expansion of (eventually [m:n] p), where the series of nexttime properties is formed using conjunctions. For example, always [2:4] p is equivalent to nexttime [2] p and nexttime [3] p and nexttime [4] p. The strong form is again defined using s nexttime.
- 5. Let m ≥ 0. (always [m:\$] p) is equivalent to (nexttime [m] always p). The lower bound m just shifts the check for property p to hold forever after m clock ticks. There is no strong form in this case due to the open-ended upper bound, which requires always p.
- 6. Let $m \ge 0$. (s_eventually [m:\$] p) is equivalent to (s_nexttime [m] s_eventually p).

As in the preceding case, the check for the property p to eventually hold is just shifted by m clock ticks. As a dual property to always [m:\$] p, there is no weak form.

Like the unbounded case, the form $s_{\texttt{eventually}}[m:n]$ p can also be defined using duality with always as not always [m:n] not p. The strong eventuality requires that p is true within m to n clock ticks and that there are enough clock ticks to cover this range. In the formulation using always, always [m:n] not p will succeed when p fails at each clock tick in the range (there need not be

8.6 Vacuous Evaluation 197

enough clock ticks to cover the range). Again, due to the top-level negation in not always [m:n] not p, that property will succeed provided p is true at some clock tick in the range. It is thus equivalent to the strong eventuality (s eventually [m:n] p).

Similarly, we can see that $(s_always[m:n] p)$ is equivalent to $(not\ eventually[m:n]\ not\ p)$. Again we see that the negation of a weak property becomes a strong property and vice versa.

One may ask the question why there is the weak eventually [m:n] p with a fixed range, while the open-ended range is only strong s_eventually [m:\$] p. It works out that if the latter were weak, the property would be in some sense meaningless because in an assertion it cannot ever fail. If there are not enough clock ticks before p is true, then the weak form succeeds. Only the strong form can declare failure in that case. This distinction between open and bounded ranges carries over by duality to the always operator. Namely,

```
not eventually [m:n] not p \equiv s_always [m:n] p not s_eventually [m:\$] not p \equiv always [m:\$] p.
```

In the final section of this chapter, we explain how vacuous successes of a property are determined depending on the type of the operator.

8.6 Vacuous Evaluation

When an assertion fails, it provides good information about the cause of the failure, often near its source in the design code. However, what happens if no assertion fails? Does that mean that the design is correct relative to the set of assertions used? In the chapter on coverage (Chap. 18), we can see that assertion success is not a guarantee; we still must make sure that the tests cover as much of the functionality of the design as possible. Yet, assertions by themselves can also help identifying verification holes (or badly written assertions), even when they do not fail.

Many typical assertions involve one of the following conditional operators:

- suffix implications |->, |=>
- Boolean implication ->
- if else operator, or
- implication implies

The antecedents (also called conditions) of these operators are also a good source of information about the quality of the tests (and assertions). Consider the simple Boolean property $x \rightarrow y$ where x and y are some Boolean expressions. The interpretation of this property is *if* x *is true then* y *must be true*. If x is false it does not impose any claim on y: the property is true regardless the truth of y. This success is called a *vacuous success*. That is, a success that carries no weight as far as the verification of the design is concerned. In practice, a more desirable test is the one in which variable x evaluates to true. Therefore, if an assertion has only vacuous

successes in a test, it means that either the test never stimulates the design in such a way as to make \times true, or that the design may never have a value assignment that makes the expression true. In the former case, we must make sure that other tests do trigger the assertion so that it does evaluate nonvacuously. In the latter case, we must examine \times and the design to see whether the problem is a bad formulation of the expression, or something wrong in the design that prevents the variables from achieving the expected values.

Most simulation and formal verification tools will report vacuous successes when the top-level property operator is one of the cases listed above. But what about other forms of properties? Can vacuity be determined in those cases as well? In general, detection of nonvacuity of an assertion a can be formulated using a derived assertion a', called a *witness assertion*, such that if both a and a' evaluate true then the success of a in nonvacuous. It is called a witness assertion because the sequence of signal values that satisfies a' (and a) is an example of the nonvacuous success of a. In the simple case of a -> b, the witness is the valuation a = 1 and b = 1. The difficulty lies in finding the witness assertion a'. Worse, for an assertion with complex property expressions, finding a witness assertion can be quite costly and requires using formal verification tools. The interested reader may wish to consult [11], [41], [18], for instance.

An alternative way to define nonvacuous execution of an assertion that is suitable for simulation is to define it recursively for each operator. This is how the SystemVerilog LRM defines nonvacuity.

The rules first define nonvacuous attempt evaluation for weak and strong sequences, and then for all property operators in terms of the evaluation of their operands. Finally, a nonvacuous success of an assertion evaluation attempt requires that the following two conditions be met:

- The assertion property attempt evaluates to true, and
- The evaluation attempt is nonvacuous.

The evaluation attempt of any sequence as a property, weak or strong (Sect. 8.1), is always nonvacuous since there is no explicit condition stated in a sequence. It is essentially a pattern match based on *regular expressions*, and the match is unconditional.

For property negation, not p, the evaluation attempt of p must be nonvacuous and not p must succeed. If p is a sequence p, then its evaluation attempt is always nonvacuous. Hence not p succeeds nonvacuously if p fails (no match in this evaluation attempt). It follows that success of a negated or a true form of a sequential property can never be vacuous.

For properties (p1 or p2) and (p1 and p2), they are both handled the same way: The evaluation attempt is nonvacuous if either the evaluation attempt of p1 or that of p2 is nonvacuous. For property and to succeed nonvacuously requires that both p1 and p2 evaluate to true and at least one of them be a nonvacuous success. Nonvacuous success of property or requires that at least one of p1 or p2 evaluate to true and at least one of the evaluations be nonvacuous. Let us examine the possible outcomes for property p; p1 or p2; endproperty. These are captured in Table 8.3.

8.6 Vacuous Evaluation 199

p1	nonvacuous	p2	nonvacuous	p	nonvacuous
false	no	false	no	false	no
false	no	false	yes	false	yes
false	no	true	no	true	no
any	any	true	yes	true	yes
false	yes	false	no	false	yes
false	yes	false	yes	false	yes
false	yes	true	no	true	yes
true	no	false	no	true	no
true	no	false	yes	true	yes
true	no	true	no	true	no
true	yes	any	any	true	yes

Table 8.3 Nonvacuous execution

Note the two lines that have **true** and **yes** in bold letters under p and *nonvacuous*. The result appears to be nonintuitive: one property fails as nonvacuous (e.g., (not s) we saw earlier) and the other property succeeds, but vacuously. It might seem that the result should be a vacuous success because the subproperty that succeeds does so vacuously. However, the LRM also says that evaluation of p is nonvacuous if either subevaluation of p1 or p2 is nonvacuous, independently of whether the subevaluation succeeds or fails. This means that p can succeed nonvacuously even though neither of the subevaluations of p1 or p2 succeeds nonvacuously.

There is another complication with the vacuity of property or: The problem happens when one argument property succeeds vacuously before the second one completes evaluation. In that case, the simulator cannot declare a vacuous success of the overall property immediately, but rather it must also evaluate the second property. Only when that second property attempt completes can the tool determines proper vacuity for the evaluation attempt of p. This will incur some performance penalty compared to an implementation that declares a success after the first property successfully completes, even if it is vacuous.

For property if (expr)p1 else p2, an evaluation attempt is nonvacuous when expr is true and p1 evaluates nonvacuously, or when expr is false and p2 evaluates nonvacuously. It follows that vacuity is determined by evaluation of the properties p1 and p2. If expr is true and p1 is a vacuous success, the overall property is a vacuous success; similarly, when expr is false, p2 determines the result. If the else clause is missing then the evaluation is nonvacuous if and only if expr is true and the evaluation of p1 is nonvacuous. When expr is false or when p1 is a vacuous success, the evaluation of the overall property is a vacuous success.

For properties of the form

- sequence_expr |-> p
- sequence_expr |=> p
- sequence expr #-# p
- sequence_expr #=# p

the evaluation is nonvacuous if sequence_expr has a match and the evaluation thread of p that results from the match evaluates nonvacuously. (Note that #-# and #-# are the dual operators of |-> and |=> introduced in Sect. 8.3.)

For the property p1 implies p2, the situation is surprisingly different from the suffix implications |-> and |=> in that vacuity does not depend on the consequent p2. For the overall property evaluation attempt to be nonvacuous, only evaluation of p1 must be nonvacuous. What happens if p1 evaluates to false nonvacuously? Then, perhaps surprisingly, the overall property succeeds nonvacuously. This is because an evaluation attempt of the property p1 implies p2 succeeds nonvacuously if and only if p1 implies p2 succeeds and the evaluation attempt is nonvacuous. The LRM is idiosyncratic in defining vacuity of p1 implies p2 to be independent of p2. This definition seems likely to change in the future. The reader is advised to check the details of available tool support and to watch for revisions to the standard.

The definitions of vacuity in the LRM for the other property operators can be analyzed in a similar way; we do not repeat them here in detail. We must stress again that given a complex property, to report vacuous successes of the evaluation attempts can incur considerable overhead in both simulation and formal verification. Instead of evaluating vacuity, it might be preferable to add cover property statements that are specific to the intent of the property. Of course, this also increases the load on the tool, but it is more under the control of the user.

The following example illustrates how the rules that are specific to individual operators are applied to determine vacuity of properties consisting of nested operators.

Example 8.16. Nested operators and vacuity.

```
a1: assert property(p1 or if (b) p2);
a2: assert property(s |-> (p1 or if (b) p2));
```

Assertion a2 uses the same property in its consequent as the body of a1.

An evaluation attempt of assertion all is a vacuous success under the conditions listed in Table 8.4.

An evaluation attempt of assertion a2 will have a vacuous success if either s has no match or s has at least one matching thread and for each of these threads the consequent evaluation falls into one of the cases in Table 8.4. That is, even though the antecedent matches, the consequent is a vacuous success and the assertion evaluation attempt is a vacuous success.

Table 0.4 Vacadas success of all								
p1	b	p2						
vacuous true	false	don't care						
vacuous true	true	vacuous false						
vacuous true	true	vacuous true						
vacuous false	false	don't care						
vacuous false	true	vacuous true						

Table 8.4 Vacuous success of a1

8.6 Vacuous Evaluation 201

Exercises

8.1. Rewrite Example 8.7 using a chain of if-else property operators. How could you verify that the two forms are equivalent?

8.2. Which properties are valid (i.e., always true)? Explain.

```
(a) ((s_eventually p1) and (s_eventually p2)) iff s_eventually (p1 and p2)
(b) ((s_eventually p1) or (s_eventually p2)) iff s_eventually (p1 or p2)
(c) ((always p1) implies (always p2)) iff always (p1 implies p2)
(d) 1'b1 until 1'b0
(e) 1'b1 s until 1'b0
```

perform the same checks of x.

- **8.3.** Write a property never p that states that its argument property p is never true.
- **8.4.** Write a property next_ev_p (logic b, property p) that evaluates to true if and only if its argument p holds at the next occurrence of the Boolean expression b. If there are not enough clock ticks for b to evaluate to true, then the property should fail.
- **8.5.** Write a property <code>next_ev_a_p(logic b, int m, n, property p)</code> that generalizes the property from Exercise 8.4 in such a way that p must hold in the range <code>[m:n]</code> of occurrences of <code>b</code> after the start of evaluation of <code>next_ev_a_p</code>. The occurrences of <code>b</code> need not be consecutive. For example, if the range is <code>[2:4]</code>, then p must hold from the 2nd to the 4th occurrence of <code>b</code> after the start of evaluation of <code>next_ev_a_p</code>. If there are not enough clock ticks to cover the range of occurrences of <code>b</code>, the property should evaluate false.
- **8.6.** Modify the property from Exercise 8.5 to form property next_ev_e_p(logic b, int m, n, property p) such that p is required to hold at least once during the range [m:n] of occurrences of b.
- **8.7.** Do a complete vacuity analysis for all valuations of the arguments for assertion

```
a: assert property(
   trig |-> next_ev_a_p(b1, 1, 4, (if (b2) resp)));
```

where next_ev_a_p is your encoding from Exercise 8.5, and trig, b1, b2, and resp are Boolean expressions.

Chapter 9 Advanced Sequences

Poe's saying that a long poem is a sequence of short ones is perfectly just.

John Drinkwater

In Chap. 5, we covered basic sequence operators, such as delays, consecutive repetition and disjunction. In this chapter, we learn about the remaining sequence operators. Although these remaining operators do not add any additional expressive power to the language, they are very convenient to use, and make assertions more readable and concise. We also consider sequence methods – constructs that generalize the sampled value function \$past for Boolean values to sequences, and discuss using sequences as events.

In examples throughout this chapter, we assume that a default clocking is defined, and thus omit the clock in assertions unless there it is need to emphasize a specific clock usage. We assume that e is a Boolean, r and s are sequences, and p is a property.

9.1 Sequence Operators

The available sequence operators grouped by their precedence from highest to lowest are listed in Table 9.1. For convenience, we also list here the operators covered in Chap. 5.

9.1.1 Throughout

Sometimes it is necessary to make sure that a Boolean condition holds throughout the whole sequence. For this purpose, it is possible to use the sequence operator throughout. The sequence e throughout s, where e is a Boolean expression and s is a sequence, has a match in clock tick t iff s has a match at t, and in each clock tick from the start of the evaluation of s until and including the match of s, the condition e is true (see Fig. 9.1).

Table 9.1 Sequence operators

Operator	Associativity
[*]	_
[*]	_
[+]	_
[->]	_
[=]	_
##	Left
throughout	Right
within	Left
intersect	Left
and	Left
or	Left



Fig. 9.1 e throughout s

Example 9.1. Write a sequence describing the following scenario: "Three consecutive enabled occurrences of read followed by four enabled occurrences of write". The occurrences of read and write are enabled if en is asserted.

Solution: The sequence may be implemented as

```
(read && en) [*3] ##1 (write && en) [*4]
```

Using the throughout operator, the same sequence may be rewritten in a more expressive way:

```
en throughout read[*3] ##1 write[*4]
```

Example 9.1 illustrates the fact¹ that throughout is a convenience operator which does not introduce any additional expressive power to the language. Yet, it greatly improves assertion readability and makes the intent clear.

Efficiency Tip The throughout operator is efficient both in simulation and in FV.


9.1.2 Goto Repetition

Motivation Example

Example 9.2. After request req is serviced by done asserted, signal ready should be asserted.

¹ It can be proven formally [19].

Fig. 9.2 Sequence e [->2]



Solution: We need to check ready in the clock tick following the clock tick when done became high *for the first time* after req is asserted:

```
al: assert property (req ##1 !done[*] ##1 done |=> ready);
```

The situation when something should happen for the first time described in Example 9.2 is very common. There is a special sequence operator, a *goto repetition*, stating that the condition e must happen for the first time: e[->1]. For an arbitrary integer constant $n \ge 0$, e[->n], where e is a Boolean, is a shortcut for (!e[*] ## e)[*n]. This sequence has a match when e happens for the n-th time, as shown in Fig. 9.2.

Unlike the consecutive repetition described in Sect. 5.5 which can be applied to arbitrary sequences, the goto repetition may be applied only to Boolean values.

Example 9.3. Using goto repetition, the assertion from Example 9.2 may be rewritten as

```
a2: assert property (req ##1 done[->1] |=> ready);
```

It is also possible to specify ranges in goto repetition: e[->m:n], $0 \le m \le n$, has a match when e happens for the m-th, m+1-st, ..., and the n-th time. The upper bound of the range may also be open-ended (\$). The formal definitions are as follows (we assume that $m \le n$):

```
\begin{array}{l} b[->m:n] \equiv (!b \ [*0:\$] \ \#11 \ b) \ [*m:n]. \\ b[->m:\$] \equiv (!b \ [*0:\$] \ \#11 \ b) \ [*m:\$]. \\ b[->m] \equiv (!b \ [*0:\$] \ \#11 \ b) \ [*m]. \end{array}
```

Example 9.4. After start is asserted, at each occurrence of request req, starting from the second and ending with the fifth one, enable en must be asserted.

Solution:

```
al: assert property (start ##1 req[->2:5] |-> en);
```

Example 9.5. After start is asserted, at each occurrence of request req, starting from the second one, enable en must be asserted.

```
al: assert property (start ##1 req[->2:$] |-> en);
```

Eventuality: It is possible to express eventuality using goto repetition. For example, the property **s_eventually** e is equivalent to **strong** (e[->1]). The operator **strong** is essential here, without it the property is meaningless in the assertion or assumption context as explained in Sect. 5.10.

Example 9.6. After start ev, signal next should be asserted at least twice.

Solution: This example is similar to Example 9.5 and one can be tempted to implement this assertion as

```
al redundant: assert property (start ev |=> strong(next[->2:$]));
```

However, assertion al_redundant is an overkill. To check that next appears at least twice, it is sufficient to check that it appears twice:

```
a2: assert property (start ev |=> strong(next[->2]));
```

Example 9.7. Event e must happen at least twice in the entire trace.

Solution: As explained in Example 9.6, the assertion may be written as

```
initial a1: assert property (strong(e[->2]));
```

Discussion: If we need to express that e should happen *exactly* twice, we should use followed-by (suffix conjunction):

```
initial a2: assert property (e[->2] #=# always !e);
```

If we need to express that e should happen *at most* twice, we should use suffix implication instead of suffix conjunction:

```
initial a3: assert property (e[->2] |=> always !e);
□
```

Next Occurrence

Example 9.8. When en is high, property p must be true in the nearest clock tick when signal e is true.

Solution:

```
al: assert property (en ##0 e[->1] \mid-> p);
```

Discussion: A possible satisfying trace is shown in Fig. 9.3.

The situation where at the next occurrence of e property p must hold is a common situation. We may define a reusable property named next occurrence as follows:²

```
property next_occurrence(e, property p);
  e[->1] |-> p;
endproperty
```




Fig. 9.3 Next occurrence

² In PSL [6], there is a property operator called *next_event* with a similar behavior.

We can now use this definition to rewrite assertion at as³

```
a2: assert property (en |-> next_occurrence(e, p));
```

Such language extensions using property definitions can be placed in packages for reuse. \Box

Example 9.9. Example 9.8 shows a weak form of the next_occurrence property. In the strong version of this property, e[->1] must happen, and property p should hold when e happens. This means that we must replace the suffix implication operator used in Example 9.8 with the followed-by (suffix conjunction) operator:

```
property strong_next_occurrence(e, property p);
  e[->1] #-# p;
endproperty
```

Efficiency Tip Using big factors and ranges in goto repetition is inefficient both in simulation and in formal verification. In simulation, goto repetition may be expensive if it causes long or never-ending attempts, and especially overlapping attempts, as explained in Sect. 19.3. For example, **assert property** (a ##1 b[->1] |=> c); is efficient if b happens every few clock ticks; it can be extremely inefficient if a often happens, and b never happens or if its occurrences are rare. The reason is that many property evaluation attempts may be simultaneously accumulated.

9.1.3 Nonconsecutive Repetition

Motivation Example

Example 9.10. Between the occurrences of the transmission start start_t and the transmission end end_t, exactly four packets must be sent. Each time a packet is sent, sent is asserted. The value of sent is not to be checked when start_t or end_t is asserted.

Solution: Using consecutive repetition this assertion may be written as:

```
al: assert property(start_t |=>
  (!end_t throughout (!sent[*] ##1 sent)[*4]
  ##1 !sent[*]) ##1 end t);
```


Using goto repetition, this assertion may be rewritten in a more compact way:

```
a2: assert property (start_t |=>
  (!end_t throughout sent[->4] ##1 !sent[*]) ##1 end_t);
```

The situation discussed in Example 9.10 where some Boolean must be true a predefined number of times between the match of one sequence and the beginning of another is rather common. There is a sequence operator [=...], called *nonconsecutive repetition*, that designates it. More precisely, sequence e[=n] has a match in some clock tick if before this clock tick e occurs exactly n times, as shown in Fig. 9.4.

³ See Sect. 5.4.1 for a discussion about nested implications.

Fig. 9.4 Sequence e [=2]



Like goto repetition, the nonconsecutive repetition may be applied only to Boolean (integral) values.

Example 9.11. Using nonconsecutive repetition, the assertion from Example 9.10 may be rewritten as

```
a3: assert property (
  start_t |=> (!end_t throughout sent[=4]) ##1 end_t);
```

It is possible to specify ranges in nonconsecutive repetition: e[=m:n], $0 \le m \le n$, has a match when e is true for the m-th, m+1-st,..., and the n-th time. The upper bound of the range may also be infinite (\$\$). The formal definitions are as follows (we assume that $m \le n$):

```
b[=m:n] \equiv b [->m:n] ##1 !b [*0:$].

b[=m:$] \equiv b [->m:$] ##1 !b [*0:$].

b[=m] \equiv b [->m] ##1 !b [*0:$].
```

Example 9.12. During one transaction delimited by start_t and end_t, packets ranging from 2 to 4 should be sent (sent asserted). sent is not to be checked when start_t or end_t is asserted.

Solution:

```
al assert property (
  start_t |=> (!end_t throughout sent[=2:4]) ##1 end_t);
```

Example 9.13. If during one transaction less than two packets are sent (sent asserted), the shortt bit should be asserted when end_t is asserted. sent is not to be checked when start_t or end_t is asserted.

Solution:


```
al: assert property (
   start_t ##1 (!end_t throughout sent[=0:1]) ##1 end_t
   |-> shortt);
```

Efficiency Tip Big factors and ranges in nonconsecutive repetition are inefficient both in simulation and in formal verification. In simulation, a nonconsecutive repetition may be expensive if it causes long or never-ending and overlapping attempts, as explained in Sect. 19.3.

9.1.4 Intersection

Intersection of two sequences r and s is a sequence r intersect s, which has a match when both sequences have a match simultaneously (see Fig. 9.5).

Fig. 9.5 Sequence intersection



Example 9.14. A command consists of two in-order read actions and one write action. After the command is issued (command is asserted), the completion of the write action (write_complete), and the completion of the second read action (read_complete) should happen simultaneously.

Solution: To express simultaneous completion, we use the intersect operator:

```
a1: assert property (
  command |-> write_complete[->1] intersect read_complete[->2]);
```

Example 9.15. Each transaction delimited by start_t and end_t should contain two read requests and three write requests.

Solution: In this case, we need to spot a clock tick t with the following characteristics:

- There should be exactly two read requests issued before t.
- There should be exactly three write requests issued before t.
- At clock tick *t*, the first occurrence of end_t should happen.

We can express this using the following assertion:

```
a1: assert property (start_t | ->
  read[=2] intersect write[=3] intersect end t[->1]);
```

Assertion at allows the last read or write request to happen simultaneously with the end of the transaction end_t and also with start_t. If we require that no read or write request happen simultaneously with end_t and start_t, and the transactions do not overlap, we need to rewrite the assertion as

```
a2: assert property (start_t |=>
!start_t throughout (read[=2] ##1 !read) intersect
(write[=3] ##1 !write) intersect end t[->1]);
```

Exercise 9.8 introduces yet another interpretation of this assertion: read and write request may happen at any time, but when they happen at the end of the transaction they are not counted as part of the current transaction. \Box

intersect operator does not really add more expressive power to the language, but it makes formulas exponentially more concise [19]. One can get a feeling why it is so by attempting to rewrite the assertion in Example 9.14 without intersect (see Exercise 9.7). Moreover, Example 9.15 is even more convincing. To rewrite assertions a1 and a2 without intersect, it is necessary to explicitly list all possible combinations of read and write:

```
read[=2] ##[0:1] write[=3] or read[=1] ##[0:1] write[=2] ##[0:1]
  read[=2] or ...
```

Efficiency Tip Operator intersect may be expensive in FV. The reason is that most FV engines in their internal representation eliminate the intersect operator and generate all possible combinations of events. The greater is the number of these combinations the more expensive it is for FV. However, it should be understood that intersect does not introduce inefficiency by itself (though some FV engines may process intersect less efficiently than the equivalent explicit representation), but it allows concise coding of complex sequences. Therefore, if intersect is really needed, there is no choice but to use it. However, if it is possible to write a more specific assertion instead, eliminating the need for intersect, this should always be the choice. For instance, if it is known in Example 9.15 that all write requests precede the read requests, read[=2] intersect write[=3] should be replaced by write[=3] ##1 read[=2].

In simulation, the overhead of **intersect** is acceptable except when sequence is compiled into an automaton in which case memory blow-up may occur during the automaton construction (see Sect. 19.3). This blow-up occurs in FV too.

Limiting Sequence Size Sometimes it is desirable to keep only those sequence matches that occur during some number of first clock ticks. This can be done using the idiom s **intersect** 1[*1:n], where s is a sequence, and n is an integer constant. Sequence 1[*1:n] has matches in clock ticks $1, \ldots, n$; therefore, only matches of s that happen during the first n clock ticks are retained, while all others are ignored.

This method may be used to truncate the antecedent sequences to boost simulation performance, as shown in Example 9.16. Note, however, that it is inefficient in FV.

Example 9.16. If acknowledgment ack is received after req, ready should be asserted simultaneously with the acknowledgment receipt.

Solution:

```
a1: assert property (req ##1 ack[->1] |-> ready);
```

Discussion: As we discussed in Sect. 9.1.2, this assertion may not be efficient in simulation when req persists until ack, and ack is sent long time after req is asserted or if ack is not sent at all. It is possible to modify assertion at to limit the time of waiting for ack to some predefined number of clock ticks, for example, 10:

```
a2: assert property (
   (req ##1 ack[->1]) intersect 1[*1:10] |-> ready);
```

If ack is asserted within 10 clock ticks from req issue, assertion a2 behaves like assertion a1; otherwise, the assertion evaluation attempt is ignored. If it is known that ack always arrives within 10 clock ticks, assertion a2 is more efficient in simulation than assertion a1 for most industrial simulators.

Note that 1[*1:10] could be replaced by 1[*2:10] since the antecedent takes at least two clock ticks.

Efficiency Tip Antecedent truncation is not efficient for formal verification. As mentioned in Sect. 10.6, the efficiency requirements for assertion checking in emulation are usually aligned with the requirements for FV rather than with simulation. Therefore, in emulation it is also better to avoid antecedent truncation, though it is less critical than in FV.

Throughout: The sequence operator throughout introduced in Sect. 9.1.1 is a special case of intersect: e throughout s is equivalent to e[*] intersect s. Since throughout does not introduce new event combinations, it is efficient both in simulation and in FV.

9.1.5 Sequence Conjunction

Conjunction of two sequences r and s is a sequence r and s. It has a match in clock tick t iff one of the sequences r and s has a match in that clock tick, and the other sequence has a match in some clock tick $t_1 < t$, as illustrated in Fig. 9.6

Sequence conjunction belongs to the intersect family, and r and s is a short-cut for r ##1 1[*] intersect s or r intersect s ##1 1[*].

If both a and b are Boolean, a and b has a match iff both a and b are true. Therefore, in this case a and b has the same meaning as a && b.4

Example 9.17. Two transactions t1 and t2 start at the same time when start_t is asserted. When both transactions complete, ready should be asserted. Transaction completion is signaled by end_t1 and end_t2, respectively.

```
Solution 9.1. a1: assert property (start_t ##1 (end_t1[->1] and
end_t2[->1]) |-> ready);
```

The antecedent matches when the longer of the two transactions completes.

Sequence Conjunction versus Property Conjunction As the sequence and property conjunctions have exactly the same syntax, how to distinguish between a conjunction of two sequential properties and a sequence conjunction promoted to a property? For example, in property en |-> r and s, where r and s are sequences, should r and s be interpreted as sequences with and as a sequence conjunction, or should they be interpreted as properties with and as a property conjunction? The answer is the same as in the case of disjunction (see Sect. 5.6): if the conjunction arguments are sequences, it is a sequence conjunction. Note, however, that

Fig. 9.6 Sequence conjunction



⁴ Except when a or b has a match item, see Chap. 16.

essentially the result may be interpreted either way, both definitions agree (this is also the case with disjunction), provided that the resulting sequence is promoted a property.

Efficiency Tip Sequence conjunction has a reasonable overhead in simulation, but in FV it may be expensive when it defines many different combinations of events (this is similar to the situation with intersect, see Sect. 9.1.4). However, top-level conjunction in a sequence promoted to property is not expensive.

Example 9.18. In property en |-> r and s, the sequence conjunction in the consequent is not expensive in FV, since r and s is promoted to a property, and and is its top level conjunction. This is because in that case sequence and can be converted to a property and with equivalent behavior.

In property en |-> (r and s) ##1 a, and is not a top level conjunction promoted to property, hence the conjunction may be expensive.

In property $(r \text{ and } s) \mid -> p$, the conjunction is in the antecedent of a suffix implication, the antecedent is never promoted to a property, hence the conjunction may be expensive.

9.1.6 Sequence Containment

The operator r within s checks that sequence r is contained within sequence s. More precisely, r within s has a match in clock tick t iff s begins in clock tick t_0 and has a match in clock tick t, and sequence r beginning in clock tick t_2 has a match in clock tick t_3 , such that $t_0 \le t_1 \le t_2 \le t$, as shown in Fig. 9.7.

The sequence containment operator belongs to the intersect family, and r within s is a shortcut for 1[*] ##1 r ##1 1[*] intersect s. Notice that r may have more than one match while s is evaluated.

Example 9.19. There should be at least one read request between two write requests.


Solution:

```
al: assert property (write |=> (read ##1 1) within write[->1]);
```

Discussion: Specifying read ##1 1 and not just read is important when the case of read appearing together with the second write should be excluded. □

Example 9.20. Two consecutive write requests cannot appear within a transaction delimited by start_t and end_t (including transaction delimiters).

Fig. 9.7 Sequence containment



Solution:

```
assert property (
   start_t |-> not strong(write[*2] within end_t[->1]));
```

Discussion: We need to specify the strong qualifier here to keep the property weak because the negation of a weak operator is strong (Chap. 8). Without it, this assertion would check among other things that each transaction eventually completes. This is usually not part of the assertion intent. In addition, checking the eventuality would impose heavy burden on FV tools.

Efficiency Tip within operator has similar overhead as intersect (Sect. 9.1.4).

Example 9.21. The sequence (a ##1 1) within b[->1] is relatively efficient in FV since it is equivalent to

```
!b[*] ##1 a ##0 !b[+] ##1 b
```

In contrast, sequence a[->2] within b[->2] is more expensive since it introduces many combinations of a and b: first a then b then a then b; first two a and then two b; a and b happening simultaneously, etc.

9.1.7 First Match of a Sequence

It is sometimes convenient to discard all sequence matches but the first one. This can be achieved using the operator first_match. Sequence first_match(s) has a match in clock tick t iff sequence s has a match in clock tick t, and it has no match in any clock tick t < t.

Example 9.22. If a and b have values 1 in clock ticks 0-4 then sequence a[*1:2] ##1 b[*2:3] has matches in clock ticks 2, 3, and 4. In contrast, sequence $first_{match}(a[*1:2]]$ ##1 b[*2:3]) has only one match in clock tick 2.

Example 9.23. When request req is issued and thereafter the first data chunk is received as identified by data bit asserted, acknowledgment ack should be sent.

Solution:

```
a1: assert property(first_match(req ##[+] data) |-> ack);
```

Discussion: Here, the first_match operator guarantees that the acknowledgment is only sent when data is asserted for the fist time. The same assertion rewritten using the goto repetition is more efficient:

```
a2: assert property(req ##1 data[->1] |-> ack);
```

Example 9.24. Let us modify the requirement of Example 9.23: Acknowledgment ack should be sent in response to a request, when two data chunks are received in consecutive clock ticks for the first time. The first solution can be easily adapted as follows:

```
a3: assert property(first_match(req ##[+] data[*2]) |-> ack);

The second solution can also be modified in the following way:

a4: assert property(req ##1 data[->1] ##1 data |-> ack);

Again, assertion a4 is likely to be more efficient than a3.
```

Trailing first_match in Sequential Properties: Trailing first_match in sequential properties, both weak and strong is redundant and can be omitted. For simplicity we explain this statement for strong sequential properties. Property strong (r ##1 s) is true iff there exists a match of sequence r ##1 s. This match exists if there exists a match of r followed by a match of s, but this is equivalent to the statement that there exists a match of r followed by the *first* match of s. Therefore,

```
strong(r ##1 s) is equivalent to strong(r ##1 first match(s)).
```

Similarly, it can be shown that a trailing first_match in the outermost and or or branch in a sequential property is redundant. For example, the sequential property r1 ##1 first match(s) or r2 is equivalent to r1 ##1 s or r2.

Example 9.25. The property a |-> b ##1 first_match (c[*] ##1 d) is equivalent to a |-> b ##1 c[*] ##1 d. The following properties are not equivalent (see Exercise 9.13):

```
(1) a |-> b ##1 first_match(c[*] ##1 d)##1 e and a |-> b ##1 c[*] ##1 d ##1 e.
(2) a ##1 first_match(b[*] ##1 c) |-> d and a ##1 b[*] ##1 c |-> d.
```

Efficiency Tip In general, other than as top level operator in a sequential property, first_match is expensive both in simulation and in FV, and should be avoided whenever possible.

9.2 Sequence Methods

There are two methods that may be applied to sequences: triggered⁵ and matched. The difference between sequence operators and sequence methods is that the

⁵ In SystemVerilog Standard 2005 [3], there was also the sequence method ended, but according to SystemVerilog Standard 2009 [7] ended is deprecated, and triggered should be used instead.

operators build a new sequence from its operands, whereas the sequence methods return a Boolean value. The syntax of sequence methods is also different: it has the form <code>sequence_instance.method_name</code>.

Even though the sequence method matched is targeted for multiclock sequences (see Chap. 12), we mention it here to explain its behavior in the simple case of a single clock.

Since sequence methods return a Boolean value, they may be used where Boolean expression are used. Nevertheless, several limitations apply. For example, sequence methods cannot be used in sampled value functions (Sect. 6.2).

9.2.1 Triggered: Detecting End Point of a Sequence

Given a sequence s, the method s.triggered returns true in clock tick t if there exists a clock tick $t_1 \leq t$ such that when s starts evaluating in clock tick t_1 , it has a match in clock tick t. s must be an instance of a named sequence. The last clocking event of s must be the same as the clocking event of the context where s.triggered is used. A reference to a formal argument may be used instead of the named sequence, but after actual argument substitution a legal reference to a sequence must result.

Example 9.26. The following code is legal:

```
logic a, b, c, d;
// ...
sequence s;
@(posedge clk) a ##[1:3] b;
endsequence : s
sequence t(x);
@(posedge clk) x[*5];
endsequence : t
property p(sequence r, untyped y);
a |-> r(y).triggered;
endproperty : p
al: assert property (@(posedge clk) c |-> s.triggered);
a2: assert property (@(posedge clk) c |-> t(d).triggered);
a3: assert property (@(posedge clk) p(t, d));
```

s and t (d) are instances of the named sequences. In r (y), r is a formal argument and so is y. $\hfill\Box$

Example 9.27. The following code is illegal:

```
logic a, b, c;
// ...
al_illegal: assert property (@(posedge clk)
    c |-> (a ##[1:3] b).triggered);
```

triggered method is applied to sequence expression a ##[1:3] b which is neither a named sequence instance nor a formal argument.

Example 9.28. Consider the following code:

```
logic a, b, c, d;
sequence s1;
  @(posedge clk) a ##1 b;
endsequence : s1
sequence s2;
  @(posedge clk1) a ##1 b;
endsequence : s2
sequence s3;
  @(posedge clk1) a ##1 @(posedge clk1) b ##1 @(posedge clk) c;
endsequence : s3
a1: assert property (@(posedge clk) d |-> s1.triggered);
a2_illegal: assert property (@(posedge clk) d |-> s2.triggered);
a3: assert property (@(posedge clk) d |-> s3.triggered);
```

Assertions all and all are legal. They are governed by clocking event @(posedge clk), and the last clocking event of sequences sl and sl to which triggered method is applied coincide with this clock. Assertion alliegal is illegal as the clock of the assertion differs form the last clocking event of sequence sl.

Example 9.29. Table 9.2 contains a trace of a and b, and the values of s.triggered, where s is defined as

```
sequence s;
@(posedge clk) a[*1:2] ##1 b[*1:2];
endsequence : s
```

Note that s.triggered returns the same value as r.triggered, where r is defined as

```
sequence r;
@(posedge clk) a ##1 b[*1:2];
endsequence : r
```

Why?

Example 9.30. Between request req and acknowledgment ack (inclusive), busy should be asserted. When both req, ack, and busy are Boolean, the desired assertion is

```
al: assert property (req |-> busy until with ack);
```

Tat	ole	9.	2	Sequence	end	po	ints
\overline{a}			-		^	-	

Clock tick	0	1	2	3	4	5	6	7	8	9	10	11	12
a	1	1	0	1	1	1	0	1	0	0	0	1	0
b	0	0	1	1	0	0	0	1	1	1	0	0	1
s.triggrered	0	0	1	1	0	0	0	0	1	1	0	0	1

How should we modify this assertion to allow req and ack be arbitrary sequences? For instance, these sequences could be defined as follows:

```
sequence req;
  start_req ##1 end_req;
endsequence : req
sequence ack;
  enable ##[1:10] end_ack;
endsequence
```

To make the assertion work, in this case we need to assure that busy is asserted starting from the *last* clock tick of req until the *last* clock tick of ack. There is no need to make any changes in all related to req handling, as the overlapping implication checks the consequent from the last clock tick of its antecedent. However, ack handling requires a modification because otherwise the assertion will check that busy is asserted only until the *first* clock tick of ack. The required modification is simple: we need to replace ack with ack.triggered:

```
a2: assert property (req |-> busy until_with ack.triggered);
```

Now suppose that we wish to take reset rst into account:

```
a3: assert property (disable iff (rst) req |-> busy until_with
    ack.triggered);
```

It should be noted that disable iff does not affect the behavior of the triggered method, and if sequence ack started before req was asserted and before rst was deactivated, it will not be aborted. However, in this case it would be natural to ignore ack. The easiest way to do this is to modify sequence ack to take rst into account as follows:

```
sequence ack;
!rst throughout enable ##[1:10] end_ack;
endsequence
```


One problem remains: the reset specified by the disable iff operator is asynchronous (see Chap. 13), while the behavior of the throughout operator is synchronous: it is checked only at clock ticks. Usually, this difference is not important. When it is, the sequence to which the method triggered is applied as well as the assertion should be controlled by the global clock if it exists.

To make the sequence to which the method triggered is applied sensitive to the assertion disabling condition reset, include !reset throughout as the top operator in the sequence. The sequence is disabled synchronously with the clock ticks of the sequence, however.

Past Temporal Operators In SVA, all property operators are directed to the future. For example, always p means that from the current clock tick on the property p

Table 9.3	Past temporal	operators

Operator	Description
sofar p	Holds in clock tick t iff p holds in all clock ticks $t_1 \le t$ (Fig. 9.8).
once p	Holds in clock tick t iff p holds in some clock tick $t_1 \le t$ (Fig. 9.9).
p since q	Holds in clock tick t iff q holds in some clock tick $t_1 \le t$, and p holds in all clock ticks t_2 , $t_1 < t_2 \le t$ (Fig. 9.10).
p backto q	A weak version of p since q: if q has not happened yet, p should hold in all clock ticks $t_1 \le t$.
previously p	Holds in clock tick t iff $t \neq 0$, and p holds in clock tick $t - 1$ (Fig. 9.11).
before p	Holds in clock tick t iff either $t = 0$ or p holds in clock tick $t - 1$. Thus, the only difference between <i>previously</i> p and <i>before</i> p is that <i>previously</i> p is false in clock tick 0, whereas <i>before</i> p is true.



holds, s_eventually p means that p happens in the current or in a future clock tick, p until q means that p holds from now on until q happens, nexttime p means, that p holds in the next clock tick, etc.

There exist also past temporal logic [27] in which the operators are directed or operate on past values of signals. We illustrate such past operators in Table 9.3.

It may be shown that past temporal operators do not add any additional expressive power to the language. Everything that may be expressed with future and past temporal operators may be expressed with future temporal operators only. Using past temporal operators just makes the formulas more succinct.

The past temporal operators are *not* part of SVA; nevertheless, it may be of interest to find an appropriate work-around. In the special case when the operands are Boolean, and not arbitrary property expressions, it is natural to use sequence method triggered as shown in Fig. 9.12. The figure shows property definitions

```
sequence seq previously(e);
 e ##1 1;
endsequence : seq_previously
property previously(e);
 seq previously(e).triggered;
endproperty : previously
sequence seq not first;
 ##1 1;
endsequence : seq not first
property first;
  !seq not first.triggered;
endproperty : first
sequence seq once(e);
 e ##[*] 1;
endsequence : seq once
property once(e);
 seq once(e).triggered;
endproperty : once
property sofar(e);
 !seq once(!e).triggered;
endproperty : sofar
sequence seq since(e1, e2);
 e2 ##1 e1[*];
endsequence : seq since
property since(e1, e2);
 seq since (e1, e2).triggered;
endproperty : since
```

Fig. 9.12 Past temporal properties

that implement several past temporal operators applied to Boolean values. ⁶ Besides the operators listed in Table 9.3, the figure contains the operator *first* that is not part of a past temporal logic, but is closely related to it. This operator does not have arguments; it returns *true* in clock tick 0, and *false* in all other clock ticks.

Figure 9.12 illustrates several points that we mentioned earlier:

- Sequence methods can be applied to sequence instances only; therefore, we had to create auxiliary sequences, such as seq previously, seq once, etc.
- Sequence methods return Boolean values. It is correct to use Boolean negation <code>!seq_once(!e).triggered</code> in the implementation of <code>sofar</code> instead of property negation <code>not seq_once(!e).triggered</code>. This also applies to the implementation of <code>first</code>.

 $^{^6}$ For some tools, it may be more efficient to implement seq_not_first using modeling code to set a flag after clock tick 0.

• It is legal to apply sequence methods to a sequence with arguments, such as seq previously (e) .triggered.

Figure 9.12 does not contain implementations of operators *before* and *backto*. Their implementation is left to the reader as exercise (Exercises 9.15 and 9.16)

9.2.1.1 Triggered Outside Assertions

Using triggered method is not limited to assertions, it is also legal in procedural code. For example, if a and b are wires, and s is a sequence, the following statement is legal:

```
assign a = s.triggered || b;
```

Even though this code looks innocent, it is dangerous in modules and interfaces to use a in a concurrent assertion. Consider the following assertion:

```
al: assert property (@(posedge clk) a);
```

Since the assertion uses a sampled value of a, in the simulation tick when the sequence had a match, the sampled value of s.triggered is 0, and a is equal to b. The value of s.triggered persists only until the end of the simulation tick, and at the beginning of the next simulation tick the new sampled value of s.triggered is again 0. Therefore, every evaluation attempt of assertion al is equivalent to evaluating

```
a2: assert property (@(posedge clk) b);
```

Clearly, assertion a2 does not reflect the initial intent.

Essentially, the intent of the assignment statement was to provide a name for the expression s.triggered || b to be reused in other contexts, for example, in concurrent assertions. This effect may be achieved using let which does not perform any assignment, but only associates a name with an expression:

```
let a = s.triggered || b;
```

Then assertion a1 is internally expanded into

```
al: assert property (@(posedge clk) s.triggered | | b);
```

which yields the desired result.

Using the triggered method in procedural code in modules or interfaces is often meaningless, as shown in the following example.

Example 9.31. In the code in Fig. 9.13, the value assigned to c in line 7 is always 0 because the value of ab.triggered is evaluated in the Observed region, while the nonblocking assignment is evaluated in the NBA region, before the ab.triggered has been evaluated. Since the sequence match event is not in the sensitivity list of the event control in line 6, there will be no reevaluation of the always procedure in the same clock tick.

```
module m(input logic clk, a, b, ...);
logic c;
sequence ab;
@ (posedge clk) a ##1 b;
endsequence
always @ (posedge clk) begin
c <= ab.triggered;
//...;
end
//...
endmodule : m
```

Fig. 9.13 triggered method in procedural code

triggered method may be safely used in procedural code in programs and checkers because the procedures are executed after the Observed region. The value of triggered has the correct value at that moment.

Do not use the triggered sequence method in procedural code in modules and interfaces outside concurrent assertions. triggered method may be safely used in procedural code in programs and checkers.

Using the triggered sequence method in let definition with subsequent let instantiation in concurrent assertions is safe.

9.2.2 Matched

The method matched returns the status of sequence termination but in the strictly subsequent clock tick. Therefore, in the case of single clock, s.matched is equivalent to sl.triggered, where sl is defined as follows:

```
sequence s1;
s ##1 1;
endsequence
```

Internally, matched stores the result of its source sequence match until the arrival of the *next* destination clock tick after the match. There are no limitations imposed on the last clocking event of sequence s.

There is not much sense in using matched in singly clocked assertions, but it is helpful in multiply clocked assertions where triggered might not be directly used. We explore this topic in depth in Chap. 12.

Unlike s.triggered, s.matched cannot be used outside sequences.

9.3 Sequence as Events

Sequences may be used as events, both edge sensitive and level sensitive.

9.3.1 Sequence Event Control

The syntax of the sequence event control is <code>@sequence_instance</code>; arbitrary sequence expressions cannot be specified with the event control. For example, <code>@(@(posedge clk)a ##1 b)</code> is illegal, as <code>@(posedge clk)a ##1 b</code> is a sequence expression, but not an instance.

Sequence event control is especially convenient in programs (see Sect. 2.7) to specify starting points of testbench execution. For example, we may wish to start some testbench activity when the initialization of the subsystem is complete (ready is asserted), and when the system has entered the normal power mode (pmode == normal when the last power mode switch pswitch occurred). The resulting code is shown in Fig. 9.14:

When program test starts executing, it immediately blocks until sequence operational matches. At that point, the program execution is resumed, task run test is called, followed by Test started message display.

Note the following:

• Since sequence operational is stand-alone, and not part of a property or of an assertion, it cannot infer its clocking event from an enclosing property or

```
task run test;
endtask : run test
typedef enum bit [1:0] {NONE, NORMAL, SLOW, FAST} Mode;
program test(input logic clk, ready, pswitch, Mode pmode, ...);
  // ...
  sequence operational;
    @(posedge clk) (pswitch && pmode == NORMAL ##1 !pswitch[*])
         ##0 ready;
 endsequence : operational
  initial begin
   @operational;
   run test;
    $display("Test started");
    // ...
  end
endprogram : test
```

Fig. 9.14 Using sequence event control in programs

assertion. Therefore, the sequence clocking event @(posedge clk) must be explicitly specified unless the sequence belongs to the scope of a clocking block, or default clocking is specified.

- Since the sequence event occurs if *any* attempt of the sequence has a match, it is not necessary to start sequence matching from the initial clock tick: This is why the sequence matching starts only from moments when pswitch && pmode == normal is true, and not from the first clock tick.
- The sequence may have many matches, but only the first one will have an effect in this specific case: when the sequence matches for the first time, the task run_test is executed, and control flow never returns to this point.

Sequence Event Controls in Modules and Interfaces: Sequence event control usage is not limited to programs only, it can also be used in modules and interfaces. Using sequence controls in modules may sometimes greatly simplify the design – it is similar to the situation with assertions, between their SVA specification and their manual implementation in procedural form. Unfortunately, industrial synthesis tools do not support this construct; therefore, the value of using it in modules and interfaces is only in nonsynthesizable (more abstract) models. However, using sequence event controls may be convenient in checkers.

9.3.2 Level-Sensitive Sequence Control

As explained in Sect. 2.3, the execution of procedural code may be delayed until some event happens, using wait statement. The wait statement can also be used with the sequence method triggered (but not matched!).

For example, the code in Fig. 9.14 can be rewritten using the wait statement as shown in Fig. 9.15.

When control flow reaches the wait statement, process execution is suspended until operational.triggered becomes true.

wait statement with sequence triggered is more verbose than sequence event control, but it may be more convenient when awaiting a Boolean expression containing a sequence triggered method to become true.

Example 9.32. Suspend the execution of the code until the command is complete (sequence command_compete has a match) or until an interrupt intr is asserted.

Solution:

```
wait(command complete.triggered || intr);
```

9.3.3 Event Semantics of Sequence Match

Like assertions, sequences are also evaluated in the Observed region in much the same way. Sequence match points play a significant role in assertions as well as

Fig. 9.15 Using level-sensitive sequence event control in programs

in other descriptions. Two situations are of particular importance. One is when a sequence match is used as a subexpression subsidiary to the assertion evaluation, whose result is used as a Boolean value true or false in the enclosing expression. The other situation is when it appears as an event control, likely used as a trigger for a process or a delayed statement.

Let us consider the first situation:

default clocking @(posedge clk);

endclocking

Example 9.33. A sequence match used as a subexpression

```
sequence req;
  start_req ##1 end_req;
endsequence: req
sequence end_ack;
  empty_slot[->1] ##1 no_conflict;
endsequence
sequence ack;
  enable ##[1:10] end_ack.triggered;
endsequence
a2: assert property (req |-> busy until_with ack.triggered);
```

In this example, sequences req, end_ack and ack, and assertion a2 are all triggered by the same clock. The match point of sequence ack is at work in the consequent property of the assertion. Hence, there is an obvious contingency of sequence ack to the property, creating an order for evaluating the sequence prior to the assertion evaluation in the same time slot in which the clock occurs. Furthermore, sequence ack is dependent upon the match point of end_ack. The final order of evaluation is: end ack, ack, a2.

Note that sequence req is simply substituted in a2 and becomes part of the assertion property antecedent. The match point of req is not explicitly needed.

We should clarify here that the order of sequence evaluation is statically determined at compile time. Also, any cyclic dependency between sequences is semantically illegal, ensuring that a proper order of evaluation can always be found. This order remains constant throughout the evaluation.

A sequence match is determined in the Observed region.

The value of method triggered on a sequence is set in the Observed region as soon as it is evaluated. Thereupon, the method can be safely used in the Observed region and in the Reactive region. At the end of the time slot, the value of triggered is reset to false, and remains false until a match point of the sequence is detected in some future Observed region. Clearly, its use in the Active region is not advised as discussed earlier.

But, sequence match points do contribute to an important application in the Active region. This brings us to the second situation: using a sequence match point as event control in procedures.

Example 9.34. A sequence match used as a process trigger or a delay statement

In this example, sequence <code>begin_mode</code> is used as event control in initial procedure <code>II</code>. The event control subjects its execution to obtaining a match point of sequence <code>begin_mode</code>. Accordingly, the initial process gets suspended as it must wait until the Observed region where the sequence is evaluated. If the match point is attained there, the simulation control makes its way back to the Active region again following the normal course via the Reactive region. Now in the Active region, the initial procedure resumes to execute the <code>\$display</code> statement.

Exercises

9.1. Two consecutive requests should be separated with four ack_wait, one acknowledge (ack), and two idle cycles (in this order).

9.2. What is the difference between the assertion from Example 9.6 and the assertions below?

- **9.3.** In this exercise, e is a Boolean expression, m and n are integer constants, p is a property. Implement the following PSL operators as SVA property definitions:
- (a) next_event e [n] p

This property holds in the current clock tick iff e does not hold at least n times, starting at the current clock tick, or p holds at the n-th occurrence of e.

(b) next_event! e [n] p

This property holds in the current clock tick iff e holds at least n times, starting at the current clock tick, and p holds at the n-th occurrence of e.

(c) next_event_a e [m:n] p

This property holds in the current clock tick iff p holds at the m-th through n-th occurrences, inclusive, of e, starting at the current clock tick. If there are less than n occurrences of e then p holds on all of them, starting from the m-th occurrence.

- (d) next_event_a! e [m:n] p
 - This property holds in the current clock tick iff e holds at least n times, starting at the current clock tick, and p holds at the m-th through n-th occurrences, inclusive, of e.
- (e) next_event_e e [m:n] p

This property holds in the current clock tick iff p holds at some occurrence of e among its m-th through n-th occurrences, inclusive, starting at the current clock tick, or there are less than n occurrences of e.

(f) next_event_e! e [m:n] p

This property holds in the current clock tick iff p holds at some occurrence of e among its m-th through n-th occurrences, inclusive, starting at the current clock tick, or there are less than n occurrences of e.

- **9.4.** Write the following assertions:
- (a) For each request, an acknowledgment should be sent from 2 to 5 times
- (b) For each request, an acknowledgment should be sent 2 or 5 times
- **9.5.** Implement the following assertion: In the transaction delimited by the start_t and end_t, there should be an even number of actions (act).
- **9.6.** What is the meaning of the following assertions?

```
a1: assert property (a[=1]);
a2: assert property (strong(a[=1]));
a3: assert property (a[=1] |-> b);
```

Discuss their efficiency in simulation and in FV.

- **9.7.** Implement the assertion from Example 9.14 without using operators from the intersect family.
- **9.8.** Implement the assertion from Example 9.15 to ignore read and write requests happening simultaneously with the end of the transaction end_t.
- **9.9.** During a memory transaction (delimited by start_t and end_t), the snoop request (snoop_req), and the credit update message (credit_update) must be sent in any order. The transaction must terminate in the clock tick when the later of these two events happen.
- **9.10.** Which of the following assertions is equivalent to the assertion from Example 9.19?

```
a1: assert property(write |=> read[=1] intersect write[->1]);
a2: assert property(write |=> read[=1] ##1 1 intersect write
    [->1]);
a3: assert property(write |=> read[=1:$] intersect write
    [->1]);
a4: assert property(write |=> read[=1:$] ##1 1 intersect
    write[->1]);
a5: assert property(write |=> ##[*] read ##1 1[*] intersect
    write[->1]);
a6: assert property(write |=> ##[*] read ##1 1[*] intersect
    write[->1]);
a7: assert property(write |=> ##[+] read ##1 1[*] intersect
    write[->1]);
a8: assert property(write |=> ##[+] read ##1 1[+] intersect
    write[->1]);
```

9.11. Implement the following assertion: If a transaction contains at least two read requests, there should be at least three clock tick delay between it and the following transaction. Assume that the transactions cannot overlap.

9.12. Write the following assertions:

- (a) After start is asserted, at least one of the following events should happen: Two consecutive read or two consecutive write. When the first such event happens (e.g., if two consecutive write happen first then in the clock tick of the second write), done must be asserted.
- (b) When after start is asserted, one of the following events happens for the first time: two consecutive read or two consecutive write, done must be asserted (e.g., if two consecutive write happen first then in the clock tick of the second write).
- (c) After start is asserted either read or write request should arrive, and in the clock tick when the first of them arrives, done must be asserted.
- (d) In the clock tick when one of the read or write requests arrives for the first time, done must be asserted.

- **9.13.** Show that the following properties are not equivalent (Example 9.25):
- (a) a |-> b ##1 first_match(c[*] ##1 d)##1 e and a |-> b ##1 c[*] ##1 d ##1 e
- (b) a ##1 first match(b[*] ##1 c) |-> d and a ##1 b[*] ##1 c |-> d
- **9.14.** Read transaction (delimited by start_read and end_read) may only be issued if a write transaction (delimited by srart_write and end_write) finished beforehand.
- **9.15.** Implement the past temporal operator *before* for a Boolean argument.
- **9.16.** Implement the past temporal operator *backto* for Boolean arguments.
- **9.17.** Modify the sequence event control example in Sect. 9.3.1 to take the reset rst into account in the sequence.

Chapter 10 Introduction to Assertion-Based Formal Verification

The man of science has learned to believe in justification, not by faith, but by verification.

- Thomas Huxley

In this and the following chapter, we probe deeper into the principles of formal assertion-based verification: its methods of application, formal semantics of assertions, and underlying models and algorithms. In this chapter our objective is to familiarize the reader with the terminology as well as the methodologies that have proven to be indispensable for many design groups.¹

There is a common opinion that only experts can do formal verification, but nobody claims that to simulate an RTL design one has to be an expert in simulation. Indeed, it is not that difficult to run a simulator, but in some forms it is not more difficult to run an FV tool either. Therefore, even people without special expertise can carry out FV to some extent.

To run lightweight FV on an RTL block, it is only necessary to formulate adequate assumptions constraining the inputs of the block. This is the trickiest and the most effort consuming step in the verification. After that, running a formal verification tool is not very different from running a simulation.

In contrast, an exhaustive formal verification of a design is a full-time job. It requires model reduction and pruning, often writing abstract models for parts of the design, checking specification completeness, iterative refinements, and algorithm tuning. Perhaps in the future, if FV tool capacity drastically grows or FV-friendly design methodologies are developed, exhaustive FV will become automated, but currently it is not. Therefore, exhaustive verification is performed only for the most critical blocks, where correctness is crucial and simulation is too unreliable. Examples include multipliers, dividers, other arithmetical units, arbiters, coherency managers, branch predictors, critical controllers, etc.

Verifying that assertions hold on a design is the primary purpose of FV, yet checking coverage is also useful for several reasons:

• To make sure that the FV model is not overconstrained, i.e., that the assumptions are not too strong and allow meaningful model behavior.

¹ This chapter and the next discuss special questions of formal verification and may be skipped. However, this chapter explains further the nature of assertions, and it should be useful even for readers who are interested only in simulation.

- To assist dynamic validation. If a coverage point is proven to be unreachable in FV, there is no point in trying to construct test cases for it. The benefit of checking coverage points in FV may be very significant.
- To evaluate new FV algorithms and tools. It is difficult to evaluate a new algorithm by trying to discover assertion violations in a real mature design. Hitting tough coverage points is more meaningful because the intended design behavior is known.

10.1 Counterexample and Witness

If an assertion fails in FV, the FV tool reports a *counterexample*, a sequence of input stimuli leading to the assertion failure. For convenience, the tool usually also shows the values of relevant internal signals. Suppose that a right shift operator >> were specified instead of the left shift operator << on line 8 of Fig. 1.7. The FV tool could produce the counterexample shown in Table 10.1. Indeed, we can see that at clock cycle 3 our assertion fails: shift_reg is 8'b000000000, while \$past({shift reg[6:0], shift reg[7]}) is 8'b000000010.

Note that some values in the counterexample are not important. For example, the value of val is important only at clock cycle 1, at other clock cycles it may assume any value without affecting the result. The FV tool may explicitly report a *don't care* (x) value in this case.

Cover statements may also be checked in FV: if a coverage point can be hit, the FV tools report a *witness*. A witness is a sequence of input stimuli leading to the coverage point hit, while satisfying all the specified assumptions. Otherwise, if the coverage point cannot be hit FV tools report that this coverage point is unreachable under the specified assumptions. It may also be impossible to hit the coverage point if the FV tool runs out of memory or allocated run time.

Consider the following cover statement for the shift register in Fig. 1.7:

```
cov_shift: cover property (@(posedge clk) disable iff (rst)
    shift_reg == 8'b10000000 && !set
##1 shift reg == 8'b000000001);
```

The cover statement states that we wish to cover two consecutive clock cycles such that in the first cycle shift_reg has the value 8'b100000000 and set is inactive, and in the second cycle shift_reg has the value 8'b000000001. A possible witness is shown in Table 10.2.

		1	_	
Clock cycle	set	rst	val	shift_reg
0	1'b0	1'b1	8'b00000000	8'b00000000
1	1'b1	1'b0	8'b00000001	8'b00000000
2	1'b0	1'b0	8'b00000000	8'b00000001
3	1'b0	1'b0	8'b00000000	8'b00000000

Table 10.1 Counterexample for check_shift

10.3 Approximation 231

Clock cycle	set	rst	val	shift_reg
0	1'b0	1'b1	8'b00000000	8'b00000000
1	1'b1	1'b0	8'b10000000	8'b00000000
2	1'b0	1'b0	8'b00000000	8'b10000000
3	1'b0	1'b0	8'b00000000	8'b00000001

Table 10.2 Witness for cov shift

As with assertion counterexamples, coverage point witnesses may contain don't care values. In our example, all values of val are actually don't cares except for the one in clock cycle 1.

10.2 Complete and Incomplete Methods

So far we discussed *complete* FV methods: these methods report for each assertion whether it passes or fails. Of course, this is the best thing to do, but because of capacity limitations, *incomplete* FV methods are often used. These methods have three possible outcomes: *passed*, *failed*, or *unknown*. Strictly speaking, even the methods we called complete can also report an unknown status for assertions when they time out or exceed memory limitations. The difference is that the complete methods are intended to find the exact solution, while the incomplete methods may give up even when computing resources are still available. Usually incomplete methods are much faster than complete ones.

Typical of incomplete FV methods are bounded FV methods: given a verification bound n they check that there is no assertion violation with a counterexample shorter than n cycles. These methods do not guarantee that an assertion is correct, but only that it cannot be violated "too soon". Bounded FV methods are widely used, and they can provide good confidence in design correctness. For example, if the design is pipelined, then the bound n equal to or a little bigger than the depth of the pipeline is usually sufficient.

10.3 Approximation

Sometimes approximation [14] is used in formal verification. While exact methods should always return accurate results, approximation-based methods can return an inaccurate result due to approximation error: either a false negative, in which case failure is reported for an assertion that should pass, or a false positive, in which case success is reported for an assertion that should fail. According to the error types introduced by the approximation, one distinguishes between overapproximation, which may introduce false negatives, and underapproximation, which may introduce false positives. Overapproximation is sound, meaning that a result of success is always accurate (i.e., free of approximation error). Underapproximation is safe, meaning that a result of failure is always accurate.

10.3.1 Overapproximation

Overapproximation occurs either automatically as part of the verification strategy of FV tools, in which case it is transparent to the users, or manually when a design model is abstracted. The abstract model is usually simpler than the original one and allows more behaviors. If the assertion is proved for this abstract model, it also holds on the original model. If the assertion fails on the abstract model, the counterexample may be *spurious*, i.e. impossible in the original model. Manual checking of whether counterexamples are spurious may be difficult, especially when there are many of them. Therefore, overapproximation may lead the user to ignore assertion failures, thus missing true bugs. The benefit of model reduction that enables a successful FV run is balanced by the cost of analysis and elimination of spurious counterexamples, as described further below.

Overapproximation may also happen inadvertently, for example, when one or more assumptions is missing. In this case the model allows for more behaviors than desired, hence we are likely to get false negatives. This is why a thorough system specification is important.

Another common case of overapproximation happens when we try to formally verify only a part of a bigger model by removing some subcomponents or blocks of statements. Figure 10.1 shows a toy module generating signal req: req is asserted only when the system state is idle. Assertion req_when_idle checks that if idle is asserted, then in the next clock cycle req is asserted unless rst happens.

Let us assume that we wish to verify a smaller model. We manually delete the assignment statement on line 3. What we obtained is an overapproximated model. Now the assertion will fail since idle may assume any value at any time.² This toy example illustrates a very important problem encountered in FV: on the one hand it

```
module reggen(input logic busy, clk, rst, output logic reg);
1
     wire idle;
2
     assign idle = !busy;
3
4
     always @(posedge clk or posedge rst) begin
5
       if (rst) req <= 1'b0;
6
       else if (busy) req <= 1'b0;</pre>
       else req <= 1'b1;</pre>
8
     req when idle: assert property (
10
       @(posedge clk) disable iff (rst) idle |=> req);
11
  endmodule : reggen
```

Fig. 10.1 Request generator

² One can argue that since idle is now unassigned it will keep the value X all the time. This is true in simulation, but FV tools usually consider undriven idle as a free variable, which may assume any value at any time.

10.3 Approximation 233

is desired to reduce the model to fit the capacity of FV tools, and on the other hand, it cannot be done by a naïve, mechanical deletion. The boundary around the missing model part must be carefully characterized by adding relevant assumptions. In our case, the following assumption needs to be added to define the behavior of idle:

```
idle when not busy: assume #0 (idle == !busy);
```

Of course, in this toy example we just replaced an assignment by an assumption, and the abstract version can hardly be more efficient than the original one. In realistic cases, however, model abstraction may bring significant performance improvement because the benefit of the model reduction outweighs the cost of the boundary assumptions.

10.3.2 Underapproximation

Underapproximation is very commonly used, although most people do not realize when they are using it. The most common example is simulation: we check the model behavior only on a given simulation trace, while other possible traces remain unchecked. Simulation is safe: if the assertion fails in simulation, the model is definitely wrong (presuming, of course, that the assertion is written correctly and no assumption is violated). There may be false positives, however: if the assertion passes in simulation, it does not mean that the design is correct. Therefore, simulation is not sound.

Another common example of underapproximation is bounded verification: if the assertion fails within the verification bound, a bug is discovered and can be analyzed using the generated counterexample. If the bug cannot be stimulated within the bound, no assertion violation is reported and we cannot conclude anything about the validity of the assertion.

There is nothing wrong with underapproximation. It is convenient because all failures are correct and no spurious counterexamples are reported. One should, however, keep in mind that the underapproximation is not sound: if no bugs are reported the model is not necessarily correct. Of course, everybody understands this when running simulation, but it is possible to get confused with FV. Therefore, FV tools usually issue an appropriate message in case underapproximation is used, such as "the assertion has not been violated up to bound 50 clock cycles", rather than "the assertion passed".

Underapproximation happens inadvertently when we overconstrain the model by writing stronger assumptions than intended. If we add the following assumption to the original model in Fig. 10.1

```
always busy: assume #0 (busy);
```

assertion req_when_idle will hold trivially, or *vacuously*, because idle is never asserted in this case. This situation is dangerous because we may believe that everything is checked, but essentially nothing is verified. Many FV tools report assertion

vacuity to help spot such cases. Unfortunately, overconstraining is usually less obvious, and it cannot always be discovered by automatic tools. Therefore, it is important to validate the assumptions, as discussed in Sect. 10.5. As mentioned earlier, trying to hit coverage points also helps to discover overconstraining.

Empty Model

An extreme case of model overconstraining occurs when there are contradictory assumptions added to the original model, such as adding

```
always_busy: assume #0 (busy);
and
  always_idle: assume #0 (idle);
to Fig. 10.1.
```

It is possible to think that in this case all the assertions will fail in FV, but the opposite is true – all of them will pass, vacuously. This is because the hypothesis of the FV proof is that all the assumptions are satisfied, but this hypothesis does not hold due to the contradiction in the assumptions. We have in fact created an *empty model* – the entire constrained model contains no state due to the contradiction.

An empty model may occur not only when two assumptions are mutually contradictory. There may be a larger set of contradictory assumptions in which no two of them are mutually contradictory. For example,

```
m1: assume property (@(posedge clk) a |=> c);
m2: assume property (@(posedge clk) b |=> !c);
m3: assume property (@(posedge clk) a && b);
```

Assumption m1 states that if a is true then c will be true in the next clock cycle. Assumption m2 states the same thing about b and !c, while assumption m3 states that a and b are always true. Therefore, overall the set of assumptions implies that c and !c should be true simultaneously! Clearly, this is an impossible situation.

An empty model may also occur when assumptions contradict the behavior of the design, as shown in Fig. 10.2. Here, the statement in line 2 causes a to toggle every clock cycle, while assumption a_stable requires that a remain stable all the time. Therefore, it is recommended that every assumption has *some* design input or a free variable in its support. Otherwise, the assumption is likely to collide with the behavior of the design.

```
logic a;
always @(posedge clk) a <=!a;
a_stable: assume property (@(posedge clk) nexttime $stable(a));
```

Fig. 10.2 Empty model example

10.3 Approximation 235

Many FV tools have the capability to report an empty model, but usually their ability is limited to several basic cases, as exhaustive empty model discovery is very costly.

10.3.3 **Pruning**

Since FV tool capacity is limited, it is important to reduce the model size. We have mentioned that this operation should be done carefully. A blind removal of a part of the model will likely result in numerous false negatives. *Pruning* (see, e.g., [51]) provides a more controlled model size reduction for FV purposes.

The main pruning directives are *set* and *free*. *set* assigns a constant value (for example, 0 or 1) to a given signal, while *free* disconnects a signal from its fan-in. There is no standard SystemVerilog support for pruning directives,³ hence FV tools usually provide some custom directives for model pruning. With these directives, the user can prune a model without actually changing the design. For instance, to verify data propagation through a pipeline, it may be sufficient to watch the propagation of a single bit, while all other bits may be set to zero. Furthermore, if there is some complex logic defining the behavior of a signal, and an assertion should hold for every value of this signal, there is no need to keep this complex logic. It is possible to free the signal. For example, to verify a pipeline stage that performs addition, the verification does not depend on the functionality of the preceding stages. Therefore, the logic driving the data incoming to this stage can be safely pruned.

All FV tools automatically prune most of the irrelevant parts of the model. Manual pruning is needed only for those signals that affect the checked assertion or the assumptions in some indirect way that the automatic pruning algorithms cannot determine. The verification engineer must thus have detailed knowledge of the design.

Note that the pruning directives relate to different types of approximation:

- Setting an input signal is underapproximation we eliminate some model behaviors, which can lead to false positives but not to false negatives. Setting input signals is thus safe but not sound.
- *Freeing any signal* in the model is an overapproximation it can only introduce more behaviors than allowed by the original model. Therefore, it can only introduce false negatives, but not false positives. Freeing is sound but not safe.
- Setting an internal signal may forbid some behaviors of the original model, but
 may also introduce new behaviors (for example, when in the original model a
 signal is toggling, and now it is set to a constant value). This kind of pruning
 may introduce both false positives and false negatives, and it is neither safe nor
 sound.

There exist additional pruning directives, such as black-boxing parts of the model, but these are beyond the scope of this book.

³ The SystemVerilog **force** statement is the best candidate, but it is usually ignored by FV tools.


10.4 Formal Verification Flows

We now have the necessary background to discuss formal verification flows in RTL design and verification. There are many possible scenarios; we focus on three of them:

- Exhaustive verification of model specification.
- Lightweight verification.
- Early RTL verification.

10.4.1 Exhaustive Verification of Model Specification

Figure 10.3 represents a block diagram of the typical FV flow for exhaustively verifying model compliance to its specification.



Legend: CEX — Counterexample.

Fig. 10.3 Exhaustive formal verification flow

The flow starts with writing the specification for the design. The specification is checked first for sanity and debugging in simulation. If there is no simulation environment available, it is possible to check parts of the specification on manually created traces. Upon completion of sanity checks and debug, a formal verification tool is applied. There may be three outcomes of checking a specific assertion:

Success: The assertion is true for any input sequences for which all the assumptions hold. In this case, it is tempting to say that the model is correct, but the assertion may pass because of overconstraining assumptions or because the assertion itself is too weak (e.g., vacuous).

Failure: A counterexample is generated consisting of an explicit or implicit input sequence for which all assumptions hold, but on which the assertion fails. There may be several reasons for assertion failure. For example, the assertion may be wrong. If the assertion is correct, the model may be underconstrained, e.g., the applied abstraction may be too coarse. If it is not clear whether the counterexample is real or spurious, the assertion failure should be reproduced in simulation. This may be challenging since it requires propagating the counterexample from the inputs of the FV model to the inputs of the simulation model. Usually, this task is done manually or with the support of debugging tools. A fully automatic solution for the problem of counterexample propagation is as hard as formal verification of the simulation model. If the assertion appears to be correct, the problem may lie in the design. Further probing using simulation should then lead to the identification of the source of the problem.

Unknown: The verification result is inconclusive. This can happen because of timeout, memory overflow, or because of an incomplete verification algorithm. To obtain conclusive results, it becomes necessary to refine the verification model: to use a more aggressive or a smarter abstraction, reduce the model size, or add auxiliary assertions. These auxiliary assertions are called *lemmas*: they may be easier to prove, and when proved, they can be used as assumptions to prove the original assertion. Another possibility is to tune the FV tool options – to choose a specific FV algorithm, adjust its parameters, etc.

Note that it is also important to verify the completeness of the specification, that is, whether the assertions fully represent the desired behavior and assumptions. We leave this rather sophisticated problem out of the scope of this book. The interested reader may consult for example [25].

10.4.2 Lightweight Verification

Figure 10.4 represents a block diagram of the lightweight FV flow for verifying local assertions inserted in the RTL code. Unlike in the exhaustive verification flow where the goal is to prove formally the correctness of the model, here the objective is to obtain a greater confidence in the overall model correctness and to detect bugs in the design. The lightweight verification flow is much less effort-consuming than the exhaustive verification flow.




Fig. 10.4 Lightweight formal verification flow

To save on verification effort, it is not required to build a special verification model. The main purpose of this flow is bug hunting, hence only assertion failures are investigated. Failure investigation in this case is much simpler than in exhaustive verification; spurious counterexamples are due only to missing assumptions. There is no need for model refinement or tool tuning.

Lightweight verification is usually faster than the exhaustive flow because only small parts of the RTL design affect the behavior of the local assertions.

10.4.3 Early RTL Verification

Another application of FV is early RTL verification [58]. The flow is essentially the same as in lightweight verification, but it runs in the early stages of the design using fast verification algorithms, such as bounded FV with small verification bounds. The goal of this flow is to clean up obvious bugs quickly, before the simulation environment is ready. It is well known that building a simulation environment is a complex task, and using FV in the early stages of the design allows starting verification earlier, thus reducing the time to market.




Fig. 10.5 Assume-guarantee paradigm

10.5 Assume-Guarantee Paradigm

As we have seen, the correctness and completeness of FV of a design block depends very much on the specification of assumptions. To check assumptions for the block, it is necessary to prove them as assertions on the parts of the design that drive the block, as shown in Fig. 10.5.

In this example, we verify *Block2* using assumption m stating that the two inputs i1 and i2 are complements of each other. This assumption should be proven as an assertion al on the outputs ol and ol when verifying *Block1*.

Unfortunately, it is not always possible formally to verify assumptions as assertions of another block:

- the other block may be more complex,
- the drivers of the signals participating in the assumption may belong to different blocks which then must be taken together, thus increasing the complexity of the model,
- the signals in the assumptions may be generated by an Intellectual Property (IP) block, etc.

In all these cases, the assumptions should at least be checked in simulation. Furthermore, the assumptions should also be provided for simulation checking with larger models into which the design is integrated.

10.6 Formal Verification Efficiency

For any FV flow, and especially for exhaustive verification, the quality of assertions is critical. If in simulation inefficient assertions increase the simulation time, in FV assertion efficiency may be a question of life and death: an FV session with an inefficient assertion may not produce a conclusive result. Of course, assertion efficiency in FV, as in simulation, is a matter of specific algorithms and tools, but there are common principles that should be understood in order to write efficient assertions.

Unfortunately, the requirements for assertion efficiency imposed by simulation and FV are often different, sometimes even contradictory. The good news is that in many cases a reasonable compromise can be found. When no compromise exists, one should go after intended assertion usage – simulation or FV. If an assertion is

targeted for both modes, then efficiency in FV should be preferred. In rare critical cases the same assertion can have different implementations for simulation and for FV. These cases should be avoided whenever possible because it may be difficult to ensure assertion equivalence.

The assertion efficiency requirements in emulation are usually more aligned with FV than with simulation since both emulation and FV require assertion synthesis, while assertion simulation algorithms may be implemented in a different way that does not require synthesis. Note, however, that assertions synthesized for FV can be nondeterministic, while for emulation they must be deterministic.

10.7 Hybrid Verification

There exist also hybrid methods combining simulation and FV for checking assertions. These methods provide better coverage than simulation but are less exhaustive than FV. The methods can usually handle much bigger designs than pure FV. Actually, hybrid verification is a special case of underapproximation. There are many variations of hybrid verification methods, but usually their main idea is to interleave conventional or random simulation and FV [13, 36].

The concept of hybrid verification is illustrated in Fig. 10.6. The design is simulated until simulation time t_1 , and starting from the system state in time t_1 bounded FV is performed. Then the system is simulated until another time moment t_2 , and bounded FV is performed again starting from the new state of the system, and so on. Figure 10.6 shows a case when no bugs have been found during the proper simulation, but two bugs are detected by bounded FV in neighborhoods of states of the simulation trace.

Hybrid verification requires that state information from the design and assertions can be mapped between the simulation and formal model. In turn this may require that the design and the assertions be synthesizable.




Fig. 10.6 Hybrid verification

Exercises

- **10.1.** What are counterexamples and witnesses? What is the purpose of reporting counterexamples and witnesses in formal verification?
- **10.2.** Assume that in Fig. 1.7 line 9 is omitted. Provide a counterexample exhibiting violation of check shift.
- **10.3.** Based on the shift register shown in Fig. 1.7, provide a witness for the following cover statement:

```
cover property (@(posedge clk) disable iff (rst)
shift_reg == 8'b10000000 && ##1 8'b000000010);
```

- **10.4.** What are complete and incomplete methods in formal verification?
- **10.5.** What is the meaning of abstraction as used in formal verification?
- **10.6.** What kinds of approximation do you know? When are they used? What kind of approximation can result in false positives? In false negatives? What kind of approximation is simulation?
- **10.7.** What kind of approximation is produced because of a missing assumption? A redundant assumption?
- **10.8.** What result will be produced by FV in the case of contradictory assumptions? In the case when an assumption contradicts the model?
- **10.9.** What is an empty model?
- **10.10.** What is pruning? Why is it used in FV?
- **10.11.** One of the additional pruning methods is *black-boxing*, in which a submodel is considered to be a black box. What kind of approximation is introduced by black-boxing?
- **10.12.** What is the easiest way to debug specification correctness?
- **10.13.** Why are spurious counterexamples produced by FV tools? How can one check whether a counterexample is spurious?
- **10.14.** What should be done if the FV result is inconclusive for an assertion?
- **10.15.** How can assumption correctness be checked?
- **10.16.** What is hybrid verification and when should it be used?

Chapter 11 Formal Verification and Models

Hope is a great falsifier. Let good judgment keep her in check.

- Baltasar Gracian

In this chapter, we explain how assertions are interpreted in formal verification. The DUT is represented as a set of states and a set of transitions between these states. In FV, all DUT transitions are synchronized by the *global clock*, which is the fastest clock in the system. All other clocks are synchronized with it. The scope of this book does not admit detailed explanation of formal verification algorithms. Instead, we provide hints about the way formal verification is conducted.

The material in this chapter is useful primarily to people who deal with formal verification. If you are interested in assertion simulation only you may skip the chapter, but it is recommended to read the chapter if you want to obtain a deeper understanding of SystemVerilog assertions.

Throughout this chapter, we make the following assumptions unless otherwise stated:

- We use the following conventions: the letters a, b, and e designate Boolean expressions; the letters r and s designate sequences; and the letters p and q designate properties.
- We freely switch between the abstract research notation and SystemVerilog notation depending on the context. For example, when explaining theoretical background we denote the disjunction of Boolean variables as $a \lor b$. Illustrating the same formula in SystemVerilog, we write it as $a \mid \mid b$. Analogously, in the research notation we use \neg for negation (Boolean NOT), \wedge for conjunction (Boolean AND), \rightarrow for implication, and \oplus for XOR.
- All variables and expressions are 2-state, even if their type is explicitly specified as logic. The values x and z are interpreted as 0.
- All properties are clocked by the global clock.

11.1 Auxiliary Notions

In this section, we briefly describe several logical and mathematical notions that will be used later in this chapter. The reader familiar with them may skip this section.

11.1.1 Relations

The *Cartesian product* of two sets, A and B, is the set $A \times B$ consisting of all ordered pairs (a, b) such that $a \in A$ and $b \in B$.

Example 11.1. If
$$A = \{x, y\}$$
, and $B = \{0, 1, 2\}$, then $A \times B = \{(x, 0), (x, 1), (x, 2), (y, 0), (y, 1), (y, 2)\}$.

A Cartesian product of an arbitrary number of sets $A_1 \times A_2 \times ... \times A_n$ is defined as the set of all tuples $(a_1, ..., a_n)$, where $a_1 \in A_1, ..., a_n \in A_n$.

A binary relation R between two sets A and B is any set of ordered pairs (a, b) such that $a \in A$ and $b \in B$. In other words, R is a binary relation iff $R \subseteq A \times B$.

Example 11.2. The order \leq of integer numbers \mathbb{Z} is a binary relation: $\leq\subseteq\mathbb{Z}\times\mathbb{Z}$. For example, $(3,5)\in\leq$, but $(6,4)\notin\leq$. Of course, we are accustomed to writing $3\leq 5$ instead of $(3,5)\in\leq$ and $6\nleq 4$ instead of $(6,4)\notin\leq$.

It is possible to define relations of an arbitrary arity: an n-ary relation R between the sets A_1, \ldots, A_n is any set of tuples (a_1, \ldots, a_n) such that $a_1 \in A_1, \ldots, a_n \in A_n$. In other words, R is an n-ary relation between A_1, \ldots, A_n iff $R \subseteq A_1 \times \cdots \times A_n$.

11.1.2 Logic Notation and Quantifiers

Boolean Logic: In logical formulas, we are using the following notation for Boolean operators: \neg for negation (Boolean NOT), \wedge for conjunction (Boolean AND), \vee for disjunction (Boolean OR), \rightarrow for implication, and \oplus for XOR.

Quantifiers: In mathematical logic, there are two quantifiers: a *universal quantifier* \forall and an *existential quantifier* \exists . If P(x) is a formula dependent on some variable x then $\forall x \ P(x)$ is true iff P(x) is true for all values of x. $\exists x \ P(x)$ is true iff P(x) is true for some value of x. Of course, the result of the quantification depends on the variable domain.

Example 11.3. Suppose that the domain of x is the set of integers. The formula $\forall x \exists y \ x = 2y$ is true if the domain of y is the set of real or rational numbers, but it is false if the domain of y is the set of integers or natural numbers.

11.1.3 Languages

We call a finite set $\Sigma = \{\sigma_1, \dots, \sigma_k\}$ an *alphabet*, and its elements $\sigma_1, \dots, \sigma_k$ *letters*. Any sequence of letters is called a *word*, or a *trace*, and we use these terms interchangeably. If the word does not contain any letters, it is called the *empty word* and is denoted ε . We distinguish between *finite* and *infinite* words (traces).

Any set *L* of words is called a *language*. If all the words of the language are finite, the language is called *finitary*, if all the words of the language are infinite, the language is called *infinitary*.

Example 11.4. The words of written English form a finitary language according to our definition. Its alphabet consists of 26 Latin letters "a" through "z", and for every sequence of Latin letters we can say whether it is an English word or not. For example, building is an English word, whereas building is not.

11.1.4 Finite Automaton

A finite automaton \mathscr{A} is a tuple $\langle \Sigma, S, S_0, \rho, F \rangle$, where Σ is an alphabet, $S = \{s_1, \ldots, s_n\}$ is a finite set of *states*, $S_0 \subseteq S$ is the set of initial states, $\rho \subseteq S \times \Sigma \times S$ is the *transition relation*, and $F \subseteq S$ is the set of the *accepting states*.

It is convenient to represent a finite automaton as a directed graph in which vertices are automaton states and edges are labeled with the alphabet letters to represent the transition relation. If $s_i, s_j \in S$ and $\sigma \in \Sigma$, then there is a labeled edge $s_i \stackrel{\sigma}{\to} s_j$ in the graph iff $(s_i, \sigma, s_j) \in \rho$. We mark the initial states with a double incoming arrow and the final states with a double circle.

Example 11.5. The alphabet of the automaton depicted in Fig. 11.1 consists of two letters: 0 and 1. The automaton has three states: s_1 , s_2 , and s_3 . There is one initial state, s_1 , and one final state, s_3 . The transition relation ρ consists of the following triples: $(s_1, 0, s_1)$, $(s_1, 1, s_1)$, $(s_1, 1, s_2)$, $(s_2, 0, s_3)$, and $(s_2, 1, s_3)$.

This automaton is nondeterministic in the following sense: from state s_1 on letter 1, the automaton can transition either to s_1 or to s_2 .

A finite automaton \mathscr{A} accepts a word w on Σ iff there is a path from one of its initial states to one of its final states such that the successive transitions are labeled by the consecutive letters from w. The set of the words accepted by the automaton \mathscr{A} forms the language $L(\mathscr{A})$, called the *language of the automaton* \mathscr{A} .

Example 11.6. The automaton \mathscr{A} defined in Example 11.5 accepts all words over the alphabet $\{0, 1\}$ that have length of at least two and 1 as the penultimate letter. \square




Fig. 11.1 Finite automaton

¹ For our purpose, there is no need to distinguish between small and capital letters. We also ignore the fact that there exist words with spaces, hyphens, etc.

11.2 Formal Verification Model

The DUT in FV is represented as a *formal verification model*, also known as a *Kripke structure*.

The formal verification model M is a tuple $\langle Q, I, V, R \rangle$, where Q is a set of states, $^2I \subseteq Q$ is the set of initial states, V is a finite set of Boolean variables, and $R \subseteq Q \times Q$ is the transition relation. We also assume that the relation R is *total*, i.e., for any $q \in Q$ there exists $q' \in Q$ such that $(q, q') \in R$. In other words, the transition relation is total if from any state there is at least one transition (possibly to the same state).

Each state is characterized by the set of variables that are true in it. If two different states have exactly the same set of variables true in them, then these states may be merged into one. R contains all state pairs such that it is possible to transition from the first state of the pair to the second one.

Example 11.7. Consider the module m defined by

This module can be represented as an FV model. It seems at first that V should consist of the four variables i, a, c, and o. But it is easy to see that the value of a is uniquely determined by the value of i. Therefore, the variable a is redundant. This situation can be generalized:

Only state variables and primary inputs should be included in the variable set V of an FV model. The signals that are Boolean functions of other signals should not be included in the variable set.


For the FV model of m, we thus have $V = \{i, c, o\}$ and Q consists of the eight states $\emptyset, \{i\}, \{c\}, \{o\}, \dots, \{i, c, o\}$. The transitions of this model are depicted in Fig. 11.2.

Note that the input signals i and c may have any initial values, and that the initial value of o is unknown. In simulation, this unknown value is designated as x, while in the FV model the unknown value just means that both initial values 0 and 1 for o are possible. All the eight combinations of these variables may occur at system initialization. It follows that all the states of this model are also initial states, i.e., I = Q.

We now explain the transitions on several examples. Note that the output o can change only when c changes from 0 to 1. Therefore, if no input changes then neither

² The definition does not require having a finite number of states, but we assume that their number is finite since this is true for any RTL model.

Fig. 11.2 Formal verification model corresponding to module m



does the output change. Consequently, from any state there is a transition to the same state in Fig. 11.2, a self-loop. The input i may change independently of c and o. Therefore, transitions for all values of i are possible. This explains why there are vertical bidirectional edges in Fig. 11.2. When c changes from 0 to 1, the next value of o must be equal to the negation of the current value of i. This yields the transitions $\emptyset \to \{o, c\}$, $\emptyset \to \{i, o, c\}$, $\{i\} \to \{c\}$, and $\{i\} \to \{i, c\}$. We leave the explanation of the other transitions as an exercise to the reader.

11.2.1 Time

To complete the picture, we need to introduce the notion of time. We assume that RTL models are *synchronous*, i.e., that there is a *global clock*, called also the *primary system clock* that synchronizes all the system transitions. Any signal change may happen only at a tick of the global clock. This assumption is applicable even if the system has several clock domains. For example, if there are two clock domains controlled by clocks <code>clkl</code> and <code>clk2</code>, then the global clock should be defined as an event <code>clk1</code> or <code>clk2</code>. In SystemVerilog, the global clock is introduced with <code>global clocking</code>, and it can be referenced as <code>\$global_clock</code> (Sect. 3.4.2). The mapping of the global clock to events using <code>global clocking</code> is important in simulation, but in FV this mapping is not necessary. In this chapter, we refer to the global clock even if <code>global clocking</code> has not been defined in the design.

One might wonder why ticks of the global clock are not identified with simulation ticks. Sometimes this is a good idea, but if all interesting signals are synchronized by a relatively slow clock, then this mapping is too inefficient. Another reason may be that we need to map the system clock to some clock in simulation to ignore transitions that happen between ticks of the global clock.

The time in FV of RTL is discrete, and it is defined in terms of the ticks of the global clock. Time 0 corresponds to the initial tick of the global clock, time 1 corresponds to the next one, etc. It is also assumed that the global clock never stops ticking. Therefore, the time in FV is infinite.

Fig. 11.3 Formal verification model explicitly clocked by \$global_clock



All transitions in formal verification models are synchronized by \$global_clock.

Example 11.8. The model in Example 11.7 is controlled by an arbitrary clock posedge c. If posedge c is the global clock, as in the code snippet below, then the FV model can be simplified: $V = \{i, o\}, Q = \{\emptyset, \{i\}, \{o\}, \{i, o\}\}, I = Q$. The transitions of this model are depicted in Fig. 11.3:

This model is much simpler than that in Example 11.7. While the simulation model remains exactly the same, c is no longer a variable of the FV model. To understand the transition diagram, consider the state $\{i\}$ as an example. In this state, i=1 and o=0. In the next tick of the system clock o must be 0, while i may assume any value. Thus, we have two transitions: $\{i\} \rightarrow \emptyset$, and $\{i\} \rightarrow \{i\}$.

11.2.2 Model Language

We can interpret each state of an FV model as a letter in the alphabet $\Sigma = 2^V$. The notation 2^V is used to designate the set of all subsets of the set V. For instance, the alphabet of the FV model from Example 11.8 is $\Sigma = \{\emptyset, \{i\}, \{o\}, \{i, o\}\}.^3$

According to its transition relation, the FV model accepts some sequences, or *paths*, of its states, while it prohibits others. For instance, the model from Example 11.8 accepts the sequence of states $\{i\}, \{i\}, \ldots$ because it has the transition $\{i\} \rightarrow \{i\}$ ", whereas the model forbids the sequence $\emptyset, \emptyset, \ldots$ because it does not have the transition $\emptyset \rightarrow \emptyset$. Therefore, an FV model defines an infinitary language (see Sect. 11.1.3) over Σ consisting of all the paths it accepts. The path q_0, q_1, \ldots is

³ We distinguish between the alphabet Σ and the set of states Q since in the general Q does not need to contain all combinations of variables, whereas Σ does.

accepted by the FV model if it starts in an initial state: $q_0 \in I$, and each pair of consecutive states q_i and q_{i+1} is connected by the transition relation: $(q_i, q_{i+1}) \in R$. These paths are exactly the words of the model language L(M). According to the terminology introduced in Sect. 11.1.3, the words are also called traces, and they are traces as also understood by hardware engineers. Indeed, a trace may be considered as a dump of all variable values at each tick of the global clock. The main difference between these traces and conventional simulation traces is that the simulation traces are finite, whereas the FV model defines infinite traces.

11.2.3 Symbolic Representation

In the above examples, we built explicit representations of FV models: each state and each state transition appeared separately. This approach is feasible only when the number of variables is very small. Even a modest design containing 300 state elements (latches and flip-flops) may have more states than there are atoms in the universe! To address this problem, a symbolic state representation is used.

It is possible to represent each state as a Boolean function that has the value 1 in this state and 0 in all other states. Such a function identifying a single state from 2^V can be written as a conjunction of literals, one for each variable: if a variable is false in the state then the corresponding literal is the negation of the variable; otherwise the corresponding literal is the variable itself. A conjunction of this form is called a *minterm* over V. It is easy to see that the minterms over V are in one-to-one correspondence with the elements of 2^V .

Example 11.9. The states \emptyset , $\{i\}$, $\{o\}$, and $\{i,o\}$ from Example 11.8 may be represented by the minterms $\neg i \land \neg o, i \land \neg o, \neg i \land o$, and $i \land o$, respectively.

Boolean functions may also be used to represent sets of states. Given a set $S \subseteq 2^V$, each element of S can be represented symbolically by its corresponding minterm, and the Boolean function representing S itself is then just the disjunction of these minterms. This function returns the value 1 on the elements of S and the value 0 on elements not in S. For this reason, the function is called the *characteristic function* of the set S, and it is denoted as χ_S .

Example 11.10. The set of states $S = \{\{o\}, \{i, o\}\}$ from Example 11.8 has the characteristic function $\chi_S = (\neg i \land o) \lor (i \land o) = o$. The empty set has the characteristic function $\chi_\emptyset = 0$, while the set of all states has the characteristic function $\chi_Q = 1$.

The same principle may be applied to symbolically represent transition relations with their characteristic functions. Recall that the transition relation R is a binary relation, that is, a set of pairs (sect. 11.1.1): $R \subseteq Q \times Q$. To build the characteristic function of a pair, it is necessary to distinguish between the variables describing the first state of the pair and those describing the second state. This is achieved by

duplicating the set of variables for the second set and distinguishing the variables with a prime. We call the original variables *current state variables* and the primed variables *next state variables*. We also expand this notation to variable expressions: if e is an expression built from the current state variables, then e' is the expression obtained from e by replacing each current state variable by the corresponding next state variable.

If a pair $p \in R$, then p = (c(p), n(p)). c(p) is the current state of p, and n(p) is the next state of p. Let $\chi_{c(p)}$ and $\chi_{n(p)}$ be the characteristic functions of c(p) and n(p), respectively. Using our convention of primes for next state variables, the characteristic function of p is $\chi_{c(p)} \wedge \chi'_{n(p)}$ and the characteristic function of the transition relation R as a whole is

$$\bigvee_{p\in R}\chi_{c(p)}\wedge\chi'_{n(p)}.$$

Example 11.11. The symbolic representation of the transition relation R from Example 11.7, Fig. 11.3 is

To understand how this symbolic representation is obtained, consider the state $\{i\}$ as an example. From Fig. 11.3, there are two transitions from $\{i\}: \{i\} \to \{i\}$, and $\{i\} \to \emptyset$. To symbolically represent the transition $\{i\} \to \{i\}$, we encode $\{i\}$ from the source of the transition with the current state variables and $\{i\}$ from the target of the transition with the next state variables, and then form a conjunction. This yields $i \land \neg o \land i' \land \neg o'$. Similarly, the symbolic encoding of the transition $\{i\} \to \emptyset$ is $i \land \neg o \land \neg i' \land \neg o'$. The set of these two transitions is represented as a disjunction $(i \land \neg o \land i' \land \neg o') \lor (i \land \neg o \land \neg i' \land \neg o')$. Although the further transformations

simplifying the characteristic function of the transition relation are routine, it is instructive to understand an interpretation of these transformations. For example, $i \land \neg o \land i' \land \neg o' \lor i \land \neg o \land \neg i' \land \neg o' = i \land \neg o \land \neg o'$ means that all the transitions from state $\{i\}$ lead to states where o is false. This agrees with the behavior of module m: if the current value of i is high then the next value of o is low.

The series of simplifications yields a compact formula for the entire transition relation: $i \oplus o'$. This result expresses the essence of the whole model: the next value of o is the negation of the current value of i.

11.2.3.1 Sampled Value Functions

The next state v' of a variable $v \in V$ may be interpreted as the value of v in the next tick of the global clock, and therefore in SystemVerilog v' corresponds to $future_gclk(v)$. Using global clocking future sampled value functions (Sect. 6.2.2.2), it is possible to explicitly express a transition relation in SystemVerilog.

Example 11.12. The transition relation $i \oplus o'$ of the module m from Example 11.8 may be represented in SystemVerilog as i != $future_gclk(o)$, and the module m is equivalent to the following assumption m1

```
m1: assume property (@$global clock i != $future gclk(o));
```

This equivalence should be understood in the following sense: the set of infinite traces (relative to the global clock) consistent with the module m is identical to the set of the traces satisfying the assumption m1.

The global clocking future sampled value functions do not require any additional modeling. They are already built into the FV model. On the contrary, the past sampled value functions do require additional modeling. For example, the function <code>spast(a,,,@(posedge clk))</code>, is represented as follows:

```
type(a) pa;
always @(posedge clk) pa <= a;</pre>
```

As we have seen, each past value of a one-bit expression effectively adds a new variable to the FV model, and thus *doubles* the total number of the model states!

Efficiency Tip In FV, future value functions are more efficient than their past value counterparts.⁴

⁴ Some FV tools represent the transition relations not between current and next variables, but between past and current variables. However, this approach is inconsistent with the SystemVerilog semantics requiring the past value of a bit variable be 0 at the initial moment.

11.3 Properties

In Sect. 11.2, we saw that an FV model M defines an infinitary language L(M), the set of infinite traces it accepts. Each property p also defines an infinitary language L(p), the set of infinite traces that satisfy it.

Example 11.13. If $V = \{a, b, c\}$, the property $p = always \ a$ defines a language $L(p) = \{a^{\omega}\}$, that is, a set of all infinite traces $aa \dots$ The notation a^{ω} means repetition of a infinitely many times.

The alphabet of this language is $\Sigma = 2^V$, the set of all subsets of the set $\{a,b,c\}$. $aa\ldots$ is therefore not a single trace, but a family of traces, as a is a symbolic representation of the set of the letters $\{\{a\},\{a,b\},\{a,c\},\{a,b,c\}\}\}$. As a disjunction of minterms, $a=(a\wedge\neg b\wedge\neg c)\vee(a\wedge b\wedge\neg c)\vee(a\wedge\neg b\wedge c)\vee(a\wedge b\wedge c)$. The property p requires a to be true at each position of the trace, whereas the variables b and c may have arbitrary values.

We say that M satisfies the property p, or that M is a model for p, or that p is valid on M, and write $M \models p$, iff all traces that M accepts also satisfy p.

Example 11.14. Let p be defined as the property always $i \mid => 10$. The FV model M corresponding to the module m from Example 11.8 satisfies p, i.e., $M \models p$, since every trace accepted by M satisfies p.

There are two important special cases of properties: **true** and **false** (corresponding to SystemVerilog 1'b1 and 1'b0, respectively). The property **true** is satisfied on any trace. Therefore, its language consists of all possible traces defined by a given set of variables. The property **false** is not satisfied on any trace. Therefore, its language is empty.

In Chap. 3, we introduced SystemVerilog assertion statements: assertions, assumptions, and cover. From the formal point of view, all these statements are properties used in different contexts. Below we discuss their formal meaning.

11.3.1 Asserts

When we check the validity of a property, it plays the role of an *assert*, as explained in Chap. 3. From the definition of $M \models p$, it follows that the property is valid iff the language defined by this property contains the language defined by the model, i.e., iff $L(M) \subseteq L(p)$. For any model $M \models \mathbf{true}$, and $M \not\models \mathbf{false}$.

11.3.2 Assumes

As a property defines its own infinitary language, it is possible to check validity of an assertion relative to this property instead of checking its validity on a model. We say

11.3 Properties 253

that the property p is valid assuming the property q, and write $q \models p$, iff all traces satisfying q also satisfy p. When the validity of a property is assumed, it plays the role of an *assumption*, as explained in Chap. 3. Note that for any assertion p, false $\models p$ since $\emptyset \subseteq L(p)$.

 $q \models p$ is equivalent to $L(q) \subseteq L(p)$. As we have seen in Example 11.8, an assumption may replace a model in the sense that it defines the same language (i.e., set of traces) as the model. More formally, the FV model $M = \langle V, Q, I, R \rangle$ is equivalent to the following assumption:

```
initial assume property (I and always R);
```

If all states of the model are initial, i.e., I = Q, then this assumption is just an invariant represented by the transition relation:

```
assume property (R);
```

An assumption may be composed with a model, which is written as $M \mid q$. This composition defines the set of traces that are common for both M and q. In other words, $L(M \mid\mid q) = L(M) \cap L(q)$. The assertion p is valid on the composition $M \mid\mid q$, written as $M \mid\mid q \models p$, iff $L(M \mid\mid q) \subseteq L(p)$.

Example 11.15. The assertion always nexttime o is valid on the composition of the module m from Example 11.8 and the assumption always !i;

If assumption q and model M are contradictory, that is, there is no common trace satisfying them, then $L(M) \cap L(q) = \emptyset$. In this case, $M \mid\mid q \models p$ for any assertion p. In this situation, the composite model $M \mid\mid q$ is *empty* (Sect. 10.3.2). An empty composite model also results when several assumptions are contradictory. It is a common mistake to think that formal verification fails when a model is empty, in fact the opposite is true:

If a model is empty then formal verification declares success for any assertion.

Example 11.16. Adding the assumption always $i \mid => 0$ to Example 11.8, both assertions always $0 \mid => !0$ and always $i \mid = 0$ hold (as do any other assertions) because the model is empty.

11.3.3 Coverage

If a property p is used as an assertion, we verify its validity on a model M, that is, every trace accepted by M satisfies p. If we replace the requirement of validity by the requirement of satisfiability, we obtain the notion of coverage (Sect. 3.7).

We say that a property p is *satisfiable*, or that p is *covered*, on M if *there exists* a trace accepted by M that satisfies p. In other words, p is satisfiable, or covered, on M" iff $L(M) \cap L(p) \neq \emptyset$. The notions of satisfiability and of validity are dual: p is satisfiable on M iff $M \not\models \neg p$.

Example 11.17. Property $s_{\text{eventually}} \circ \text{ is satisfiable on model } M$ from Example 11.8 because the trace $\neg i, \dots$ satisfies p (in this trace the value of i at time 0 is 0, and thus the value of o at time 1 is 1). The same property is not valid on M because it is not satisfied on any trace of the form i^{ω} , which are legal traces of M. \square

11.3.4 Constraining a Model with Assumptions

If assertion p holds on model M then it also holds on M composed with assumption q. This is because the composition $M \mid\mid q$ may not accept more traces than model M alone does.

The situation with coverage is the opposite: if property p is covered on a composition $M \mid\mid q$, then it is also covered on model M alone, since M accepts all traces that $M \mid\mid q$ does.

Informally speaking, adding assumptions increases the chances of a property to become valid, but decreases its chances of being covered. This does not necessarily mean that adding assumptions makes FV easier for assertions and more difficult for coverage goals. For example, adding assumptions may make the formulas used in FV more complicated, and thus make the work of FV tools much harder. See Sect. 10.3 for a discussion on approximation and abstraction.

11.4 Safety and Liveness

Compare the following two assertions a1 and a2:

```
a1: assert property (always a);
a2: assert property (s_eventually a);
```

Can these assertions fail in simulation? Assertion a1 certainly can if in some global clock tick the value of a is 0. We can even say that if this assertion is violated on some infinite trace then there is a finite prefix of this trace where this assertion is violated, namely, the trace fragment until (including) the first occurrence of a = 0. But what about assertion a2? We can simulate this assertion during millions of ticks and never see a assuming the value 1. Does it mean that assertion a2 is violated in simulation? Obviously not: had we simulated a2 a few more ticks we might discover that a holds. Assertion a2 cannot fail in simulation except at the end as discussed in Chap. 8.

We can formulate our findings in terms of the counterexamples: every counterexample of all has a finite prefix such that all its extensions are counterexamples. On the contrary, in the case of all every finite trace has an extension that is not a counterexample. Informally speaking, all the counterexamples of the assertion all are finite, whereas all the counterexamples of the assertion all are finite, whereas all the counterexamples of the assertion all the counterexample of the assertion all have the form $w = \neg a^{\omega}$.

This leads us to the following property classification. Property *p* is *safety* if each counterexample has a finite prefix, and all its extensions are counterexamples. Such a prefix is a *bad prefix*. The property *p* is *(pure) liveness* if every finite trace has an extension that is not a counterexample. Speaking informally, we can say that safety properties check that something bad never happens, whereas liveness properties check that something good eventually happens. Safety properties may fail in simulation, whereas pure liveness properties cannot. Only FV can fully check liveness properties as FV can deal with infinite traces.⁵ The vast majority of all properties used in practice are safety.

Are there properties that are neither safety nor liveness? Yes, such properties exist. As an example, consider the property a **s_until** b. The trace $w_1 = (\neg a \land \neg b)b \dots$ has a bad prefix $(\neg a \land \neg b)$; all the extensions are counterexamples, while the trace $w_2 = (a \land \neg b)^\omega$ provides an infinite counterexample, such that each finite prefix has an extension that is not a counterexample. Indeed, on w_1 there is no a before the first occurrence of b, and on w_2 b never happens. Such properties are called *hybrid* or *general liveness* properties.

For our purpose, the distinction between the pure and general liveness properties is not that important, and we will reserve the term *liveness* for both pure and general liveness properties. We explicitly use the terms "pure" or "general" when we need to distinguish between these two types of liveness.

The notions of safety and liveness are fundamental in FV. The users of FV tools should be able to determine for any property whether it is safety or liveness, and try to use safety properties as much as possible. This is necessary for FV to be efficient, as checking safety is generally more efficient than checking liveness. To help the user write efficient properties, some FV tools report the type of each property, safety, or liveness.

11.4.1 Safety Properties

Algorithms for formal verification of assertions are called *model checking*. A systematic description of model checking is beyond the scope of this book, and we discuss here only a simple special case to give an idea of how an FV tool works for safety properties. Some basic understanding will give insight into assertion efficiency.

The basic idea of model checking of safety properties is simple. All states of the FV model are partitioned into good and bad. Entering a bad state signifies a failure of the property. Model checking of a safety property can thus be formulated as a reachability problem: is there a path from one of the initial states of the FV model

⁵ Some liveness properties may pass in simulation, like property **s_eventually** a if a is observed to hold at one point in time. However, there are liveness properties that can neither fail nor pass in simulation, like the property **s_eventually always** a.

to one of its bad states? If such a path exists, the property fails, if not, it holds. This path, if it exists, represents a bad prefix of the property, or, informally speaking, its finite counterexample.

Property always a provides the simplest example. All states of the FV model containing a are good, while those not satisfying a are bad. The good states are those in the set $\{v \in V | a \in v\}$, while the bad states are those in the set $\{v \in V | a \notin v\}$.

An arbitrary safety property may be reduced to a property of this form. The common algorithm is to build a finite nondeterministic automaton \mathscr{A} (Sect. 11.1.4) corresponding to the complement of the safety property. The language of this automaton consists of bad prefixes of the safety properties, or, in other words, this automaton recognizes bad prefixes of the safety property. The accepting states of \mathscr{A} are called the *bad states*. It can be shown[57] that it is always possible to construct \mathscr{A} with a single bad state. The automaton \mathscr{A} may be synthesized into RTL[9] such that each automaton state becomes a new RTL variable. This results in an augmented FV model \mathscr{M}' containing both variables of the original model \mathscr{M} and the variables corresponding to the states of \mathscr{A} . If the bad state is represented by variable \mathscr{B} then the original safety property is equivalent to the property always \mathscr{B} of the augmented model.


The exact description of building the automaton of the complement of a safety property is beyond the scope of this book. Instead, we illustrate the idea on the following examples.


Example 11.18. Build an automaton for the complement of the property always a \mid => b.

Solution: The automaton for the complement is shown in Fig. 11.4.

Discussion: The automaton in this example is nondeterministic. It remains in the initial state s_1 until it follows one of the evaluation attempts of $a \mid => b$. The attempt may start whenever. It will be nonvacuous only if a holds when it starts. Then, the automaton moves to state s_2 . If in the next tick of the global clock b does not hold, the automaton moves to state s_3 , which is the bad state of the automaton. \Box

Example 11.19. Synthesize the automaton from Fig. 11.4 (Example 11.18) into RTL.





⁶ It is not required that the language $L(\mathscr{A})$ of this automaton coincide with *all* bad prefixes of the safety property, it is sufficient if $L(\mathscr{A})$ contains *some* of its bad prefixes [40].

Solution:

```
logic s1 = 1'b1, s2 = 1'b0, s3 = 1'b0;
always @$global_clock begin
    s1 <= s1;
    s2 <= s1 && a;
    s3 <= s2 && !b;
end</pre>
```

Discussion: This code implies that s1 always equals to 1'b1 and therefore its computation is redundant. The optimized code is:

```
logic s2 = 1'b0, s3 = 1'b0;
always @$global_clock begin
    s2 <= a;
    s3 <= s2 && !b;
end

s3 == 1 is a bad state: if s3 becomes 1'b1, the assertion fails.</pre>
```

The fact that a safety property may be synthesized into RTL reflects the well-known practice of implementing assertions in RTL as an instrumented code. This practice was common before the assertion specification languages became widely accepted (Chap. 1).

Example 11.20. Build an automaton for the complement of the property always a |=> ##3 b.

```
Solution: Its automaton is depicted in Fig. 11.5.
```

As we can see from the comparison of Examples 11.18 and 11.20, the more complex the property is and the bigger its bounded time windows are, the more states its automaton has. Interestingly, infinite time windows do not introduce many additional states, as illustrated in the following example.

Example 11.21. Build an automaton of the complement of the property always a[+] ##1 b |=> c.

Solution: See Fig. 11.6.

Discussion: This automaton contains only 4 states. Compare it with the automaton for the complement of the property a [3] ##1 b \mid => c (Exercise 11.2).

Fig. 11.5 Automaton for complement of property **always** a |=> ##3 b





Fig. 11.6 Automaton for complement of property always a [+] ##1 b |=> c



Efficiency Tip The general trend is as follows: The more complex the automaton for a property, the less efficient it is in FV.

How can a safety property be recognized? In the case the property does not contain negations, the property is safety if it uses the following operators only:

- · weak sequence
- suffix implications
- nexttime
- always
- until, until with
- Boolean connectives and and or.

If the above operators are in the scope of a negation (or of an odd number of negations) the resulting property is usually not safety. However, such operators as strong sequences, s_eventually, s_until, and s_until_with become safety properties when negated.

Example 11.22. Property nexttime (a until_with b) is a safety property because it consists of the operators nexttime and until_with that are not in the scope of any negation.

Property not strong (a[*] ##1 b) is safety property since the strong sequence is negated.

Property strong (a[*] ##1 b) implies weak (c ##[+] d) is a safety property because it contains a strong sequence under negation in the antecedent, and a weak sequence without negation in the consequent. Recall that A implies B is equivalent to not A or B.

Property not (not weak (a [*] ##1 b) or not weak (c ##[+] d)) is a safety property because both weak sequences are in the scope of two negations. \Box

Note that most FV tools recognize safety and liveness properties syntactically. For example, even though a until b is by definition the same thing as (a s_until b) or always a, it is likely that most FV tools report the former property as safety, while the latter as liveness (see [26, 40]).

11.4.2 Liveness Properties

Model checking of liveness properties is significantly more complex than model checking of safety properties. Liveness properties cannot be verified using direct

reachability analysis. This is because for safety properties any path to a bad state is finite, and all counterexamples found this way are necessarily finite, while liveness properties have infinite counterexamples. Checking liveness properties is much less efficient that checking safety properties because the tool must search (explicitly or implicitly) for infinite cycles in the model that do not satisfy the property.

Efficiency Tip Avoid writing liveness properties unless they are absolutely necessary.

Example 11.23. To check that some condition c holds between two events ev1 and ev2 implemented as Boolean expressions, we can write the following property: always ev1 |-> c s_until_with ev2. Before we proceed further, we should ask ourselves whether it is indeed the property that we need to check. Perhaps, it checks more than we really need. It checks two things:

- 1. c holds between ev1 and ev2, and
- 2. Each time that ev1 holds, ev2 also eventually holds.

The question is whether we really want to check the second condition which is liveness? Usually, the answer is "no". If not, we should rewrite the property as always ev1 |-> c until_with ev2. This property is safety, and it only checks for the first condition.⁷

Example 11.24. To check that each request is granted, we can write the following property: always req \mid => s_eventually gnt. This property is liveness, and in this case liveness is what we actually want. Although this property is expensive, we are prepared to pay for it.

11.4.2.1 Why Write Liveness Properties?

Why should we write liveness properties if they are expensive? There may be several reasons for doing so. One common reason is to check that there is no starvation in the system. For example, if a CPU needs access some resource, this resource should be eventually available.

Another common reason to use liveness properties is specification abstraction. For example, we might need to ensure that each request is eventually granted. The following liveness property is suitable for this purpose:

```
always req |-> s eventually gnt
```

Of course, in a real system there is always an upper bound on the request service time, but if the system implementation changes or if the upper bound is large, then a liveness property can be more appropriate.

⁷ By a chance the operator **s_until_with** has a clumsier syntax in SVA than the operator **until with**: this was done to make the safety property **until with** a natural choice.

For example, suppose we know that the request service time is bounded by 600 clock ticks, and also that the system implementation may be modified in which case the upper bound may grow to 700. To make it a safety property, we could have written the property as

```
always req |-> ##[1:701] qnt
```

However, we are not really interested in the exact time bound, and the efficiency of this bounded safety property in FV is very poor. We thus have a tradeoff between the safety property, with an automaton comprising more than 700 states and with about twice as many edges, and the liveness property, with only a couple of states. Checking the liveness property is likely to be more efficient.

11.4.2.2 Counterexamples for Liveness Properties

There is an important question about liveness property checking: How can infinite counterexamples be found and reported in the first place? Obviously, tools and humans can deal with finite representations only. Fortunately, it can be shown [23] that if a property has an infinite counterexample, then it also has a lasso-shaped counterexample, that is, a counterexample of the form $w_1w_2^{\omega}$. Here, w_1 and w_2 are finite words, w_1 is a prefix, and w_2 is an infinitely repeated part. For instance, $(a \wedge b)ba(ab)^{\omega}$ has the form $w_1w_2^{\omega}$ for $w_1 = (a \wedge b)ba$ and $w_2 = ab$.

11.4.2.3 Assumptions and Liveness

So far we have considered property classification into safety and liveness from the point of view of assertions. It turns out that even the simplest assumptions introduce liveness into the system.

Example 11.25. Given assertion al and assumption ml not in the scope of an initial procedure, they are equivalent to the assertion al

```
m1: assume property (a);
a1: assert property (b);
initial a2: assert property ((always a) implies (always b));
as explained in Example 20.1.
```

For conciseness, we switch now to the notation of the research literature, where operator always is designated as G, and operator s_eventually as F. Using this notation, the property corresponding to the assertion a2 may be written as $Ga \rightarrow Gb$. This property is equivalent to $(\neg Ga) \lor Gb$, which is, in its turn, equivalent to $(F \neg a) \lor Gb$. The latter form explicitly contains an eventuality, and shows that a2 is a general liveness assertion. Hence, the combination of m1 and a1 introduces liveness condition into the system.

Example 11.25 shows that all assumptions of the form always q, that is, the vast majority of all assumptions, introduce liveness. To understand why, consider some assertion p and an assumption of the form Ga stating that a is an invariant of the system. Assume, for simplicity, that p is a safety property. Suppose that at some time i assertion p fails on trace w. In other words, the trace prefix $w^{0,i}$ is a counterexample of p: $w^{0,i} \not\models p$. We are ignoring the assumption Ga for a moment. Assume now that the assumption Ga holds on the trace prefix $w^{0,i}$, that is, a holds at each position of w from 0 to i (inclusive). Does it mean that $w^{0,i}$ is a real counterexample of p? Strictly speaking, no: if a = **false** at some point in time i is, then assumption i does not hold, and therefore assertion i holds (vacuously).

In practice, invariant assumptions are always used, which means that the model checking of safety properties is not relevant at all – if we take assumptions into account, all our properties become liveness! In spite of this, the FV tools usually ignore the liveness component introduced by assumptions when checking safety properties and only check that until the time of an assertion failure no assumptions have been violated. Some tools even check that the assumptions are not violated a few more global clock ticks after the assertion violation. Strictly speaking, this is incorrect, but it is a reasonable compromise. Also, this method is safe: if the assertion passes then the subsequent behavior of an assumption is not important.

11.4.2.4 Automata of Clocked Properties


In Sect. 11.4.1, we showed that safety properties may be represented as finite automata. How will the property automaton change if we take the property's clock into account?

Consider property $@c \ a \ | => b$. We assume that occurrence of clocking event @c has been resolved to testing of a Boolean expression c with respect to the global clock (see Sect. 20.4). The automaton for the property complement is shown in Fig. 11.7 (the corresponding unclocked version is shown in Fig. 11.4).

The automaton in Fig. 11.7 differs from the automaton in Fig. 11.4 in several points:

• There is a self-loop in the state s_2 labeled with $\neg c$, which reflects the automaton waiting for the clock c to transition to the state s_3 .

Fig. 11.7 Automaton for complement of property @c always a |=> b



⁸ We are not talking about corner cases such as when the same property is used both as an assumption and as an assertion.

• There is an additional guard c on the edges $s_1 \to s_2$ and $s_2 \to s_3$ allowing the state transitions only at a clock tick.

The automaton reaches its accepting state s_3 iff the property fails. For the property to fail, the clock must tick enough times to allow the transition from the initial state to the accepting state.

It is quite natural that the automaton of the complement of the clocked property is more complex than that of the unclocked property, and therefore FV of clocked properties is more expensive than FV of the unclocked ones. The main penalty of the verification of the clocked properties is due to the fact that their clock is considered to be an arbitrary signal. In practice, however, the waveform of the clock is often well known, and can be expressed through the system clock in a regular manner. For example, the clock may tick each second tick of the global clock. In such a case, FV of clocked properties can be made much more efficient. Therefore, many FV tools ask for a clock pattern. Some of them may also derive this information from the global clocking statement and RTL. However, some FV tools may ignore the global clocking statement.

11.5 Weak and Strong Operators

Temporal operators behave differently relative to their clock: some of them require their clock to tick enough times to witness success, whereas others just require no evidence of failure while the clock is ticking. The operators belonging to the first group are called *strong*, and the operators from the second group are called *weak*.

The weak operators considered so far are weak, |->, |=>, nexttime, always, until, and until_with. The operators strong, s_nexttime, s_eventually, s_until, and s_until_with are strong. The suffix conjunction operators #-# and #=# are also strong. All strong operators denoted by keywords have a special mnemonics: their names begin with the prefix s_, except for the operator strong. The weak operators, when they are not in the scope of a negation, yield only safety properties.

Example 11.26. Consider the following properties:

```
    @clk s_nexttime a
    @$global_clock s_nexttime a
    @clk a s_until b
    @$global_clock a s_until b
    @clk (a s until b) or always b.
```

Property (1) is a liveness property, as it checks that clk ticks at least twice. Property (2) is a safety property even though it has a strong operator. As the global clock is fair according to its definition, the operators nexttime and s_nexttime mean the same thing when they are controlled by the global clock.

Property (3) is a liveness property as it checks that b eventually happens and that clk ticks enough times to witness the occurrence of b. Property (4) is also liveness, even though it is controlled by the global clock, as it checks that b eventually happens. Property (5) is a safety property since it is equivalent to a until b. However, it is likely that most FV tools will not recognize it as safety, as it contains a s_until operator, and it looks syntactically like a general liveness property.

Most property operators have both weak and strong versions, such as until and s_until. However, the unbounded operator always has only a weak form, and the unbounded operator s_eventually has only a strong form. When we say that eventually a happens, our intent is that a happens in some clock tick, and therefore the clock cannot stop ticking before a has been detected. When we say that a always happens, our intent is that a happens at each clock tick. If there are no clock ticks, the value of a is not checked. Therefore, in this case there is no requirement that the clock ticks.

Suffix Implication

Why is suffix implication a weak operator? Suffix implication requires its consequent to be true for each match of its antecedent. There is no requirement that the antecedent match, and therefore there is no requirement that the clock ticks enough times to witness a match of the antecedent.

Negation

Negation reverses the strength of an operator.

Example 11.27. Property @clk not weak(a) is equivalent to @clk strong(!a). Indeed, according to the clock rewriting rules, explained in Sect. 20.4, @clk not weak(a) is equivalent to not weak(@clk a). The latter property holds iff property weak(@clk a) fails. This property fails iff either clk does not tick at least once or a is false at the first clock tick a. This is in its turn equivalent to @clk strong(!a). \(\mathbb{\mathb

Example 11.28. Property not (a until b) is strong. It checks that the clock ticks enough times to witness that a until b does not hold. Property not (a s_until b) is weak. If the clock stops ticking early, property a s_until b will fail, and its negation will pass.

Since property implication p implies q is equivalent to (not p) or q, the strength of the antecedent is reversed and the strength of the consequent is preserved. Therefore, for the implication to be weak, property p should be strong and property q should be weak.

Example 11.29. Consider the following assertions:

```
a1: assert property (@clk !a);
a2: assert property (@clk not a);
initial a3: assert property (@clk !a);
initial a4: assert property (@clk not a);
```

Assertions at and at are equivalent. Property @clk not a is equivalent to property @clk strong(!a) (Example 11.27). In the context of assertion at, properties @clk strong(!a) and @clk weak(!a) are equivalent as we check them only at the ticks of clk.

Assertions a3 and a4 are not equivalent: a3 is satisfied if clk never ticks, whereas assertion a4 fails in this case.

The implicit always in continuously monitored assertions causes the clock to be treated weakly at the top level.

Operator Composition

We know that strong operators require their clock to tick enough times, while there is no such restriction in weak operators. To interpret the semantics of a property containing both weak and strong operators, one should refer to the formal semantics of these operators and to their clock rewriting rules.

Example 11.30. Which requirements are imposed on the clock in property @clk always s_eventually p? Property @clk always s_eventually p holds if in each tick of clk property @clk s_eventually p holds. This means that if there is an ith tick of clk, then there must exist a jth tick of clk, $j \geq i$, at which property p holds. To summarize, property @clk always s_eventually p is satisfied if one of the following conditions holds:

- Clock clk does not tick at all.
- Clock clk ticks finitely many times and p holds when the clock ticks for the last time
- Clock clk ticks infinitely many times, and p holds in infinitely many ticks of the clock.

Sometimes mixing weak and strong operators in the same property is unavoidable, as in the case of always s_eventually p, or s_eventually always p. However, when there is no special reason to mix weak and strong operators, it is more efficient and more intuitive to use operators of the same strength in the property. For example, instead of p until s_nexttime q, use either p until nexttime q or p s_until s_nexttime q, depending on whether or not it is important to prove that q eventually happens.

11.6 Embedded Assertions 265

Do not mix weak and strong operators in the same property unless it is unavoidable.

11.6 Embedded Assertions

Thus far we have considered the formal semantics of stand-alone assertions (i.e., concurrent assertions placed outside procedural code) and properties. In this section, we discuss how embedding concurrent assertions in procedural code modifies their formal semantics. The simulation semantics of embedded assertions is described in Chap. 14. In FV, the support of embedded assertions is restricted, but it covers most cases of importance.

As explained in Chap. 4, if an assertion is in the scope of an initial procedure, it is monitored only once, and if it is in the scope of an always procedure, it is monitored continuously. In other words, if an assertion or an assumption is embedded in an always procedure, an outermost always property operator is implicitly added to this assertion.⁹

If an assertion or an assumption is placed in the scope of one or several procedural conditional statements, such as if or case, an implicit suffix implication is added to this assertion with the overall condition in the antecedent.⁹

Example 11.31. Consider the following code fragment:

```
always @(posedge clk) begin : b1
  if (en) begin : b2
    // ...
    if (cond) begin : b3
        // ...
    end : b3
    else begin : b4
        // ...
        al: assert property (p);
    end : b4
        // ...
    end : b2
    // ...
end : b1
```

Assertion a1 is equivalent to the following stand-alone assertion:

```
assert property (@(posedge clk) en && !cond |-> p);
```

This equivalent assertion has an additional suffix implication operator |-> with the antecedent en && !cond. The condition en && !cond is the entry condition of the block b4 to which the assertion a4 belongs. This is quite natural since we expect the assertion attempt to be triggered only when the block b4 is activated. \square

⁹ See Chap. 18 for the semantics of embedded coverage statements.

As we know, assertions may also be placed in the scope of a looping statement. To be tractable for FV, the looping statement must be statically unrollable, and the assertion is replicated according to the iterations.

Example 11.32. Consider the following code fragment:

```
property p(int i, j);
    a[i] |-> ##[1:2] b[j];
endproperty : p

always @(posedge clk) begin : b1
    // ...
    for (int i = 0; i < 5; i++) begin : b2
        // ...
        for (int j = 0; j < i; j++) begin : b3
        // ...
        al: assert property (p(i, j));
        end : b3:
    end : b2
end : b1</pre>
```

The assertion a1 is equivalent to the following 10 stand-alone assertions:

```
assert property (@(posedge clk) p(1, 0));
assert property (@(posedge clk) p(2, 0));
...
assert property (@(posedge clk) p(4, 3));
```

Note that the loops b2 and b3 are statically unrollable in spite of the fact that the upper bound of the loop b3 is not a constant.

11.7 Immediate and Deferred Assertions

So far in this chapter we have dealt only with concurrent assertions. Immediate and deferred assertions are also meaningful for FV when they are instantiated in synthesizable code and when the data they reference are synthesizable. For FV, there is no difference between immediate and deferred assertions. Therefore, we limit our discussion to deferred assertions.

For FV, all deferred assertions are transformed into (possibly embedded) concurrent assertions using the following scheme: assertion assert #0 (e); is transformed into assertion assert property (@clk e); for some clock clk. Assumptions and cover statements are transformed similarly. It remains to define how the clock is inferred for deferred assertions.

If the deferred assertion is not in the scope of an always procedure such that the clock is inferrable from it for concurrent assertions, the global clock is inferred. The global clock is inferred even if there is no global clocking definition in the design: recall that global clocking is only required to map the global clock into an event for simulation, and in FV models the global clock is inherently defined.

П

Example 11.33. Consider the following code fragment:

```
al: assert #0 (e1);
always_comb begin
  // ...
  if (en) begin
    // ...
    a2: assert #0 (e2);
    end else // ...
end
For FV, this code is rewritten using concurrent assertions as follows:
al: assert property (@$global_clock e1);
```

always_comb begin
 // ...
 if (en) begin
 // ...
 a2: assert property (@\$global_clock e2);
 end else // ...
end

If the deferred assertion is in the scope of an always procedure with an inferrable clock then this deferred assertion is treated in FV as a concurrent assertion.

Example 11.34. Consider the following code fragment:

```
always @(posedge clk) begin
  // ...
  if (en) begin
   // ...
   al: assert #0 ($onehot0({a, b});
  end
end
```

In FV, the deferred assertion at is interpreted as a concurrent assertion:

```
always @(posedge clk) begin
   // ...
   if (en) begin
    // ...
    al: assert property ($onehot0({a, b});
   end
end
```

Exercises

- **11.1.** Write a module implementing a counter modulo 4 and build the corresponding FV model. Write a symbolic representation of its transition relation.
- 11.2. Build an automaton for the complement of the property always a [3] ##1 b \mid => c. Compare it with the automaton for the complement of the property always a [+] ##1 b \mid => c

11.3. What do the following properties mean?

```
    @clk s_eventually always p.
    @clk s_nexttime nexttime p.
    @clk nexttime s_nexttime p.
    @clk p until s_nexttime q.
    @clk p s_until nexttime q.
```

11.4. Rewrite the following properties without using negation:

```
(a) @clk not weak(a ##1 b)(b) @clk not strong(s[->2]).
```

- 11.5. What is the meaning of the property @clk p s_until_with always q?
- 11.6. What is the meaning of the embedded assertion a1?

Chapter 12 Clocks

The only reason for time is so that everything doesn't happen at once.

- Albert Einstein

Concurrent assertions are fundamentally temporal in nature. The evaluation of a concurrent assertion, and of its constituent subsequences and subproperties, evolves over time in a discrete way. *Clocks*, or, more precisely, *clocking events*, are the constructs that define the discretization of time. Clocking events form a rich subset of general SystemVerilog events. These include familiar edge events, such as posedge clk, declared events, as well as more general and complex event expressions.

In SVA, clocking events are declarations with scopes, not operators. As such, they do not have strengths. Rather, they determine the measurement of time and the times of evaluation of operators and expressions within their scopes. Within the scope of a clocking event, one unit, or *cycle*, of discrete time is measured from one occurrence of the clocking event to the next. Occurrences of a clocking event are also called *ticks of the clock*, or simply *clock ticks*. The intervals between successive clock ticks can be regular or irregular in length, but in all cases they constitute one unit of discrete time. This reckoning gives meaning to operators such as ##1, |=>, and nexttime, whose semantics involves the notion of the "next point in time". The *leading clocking event* of a concurrent assertion, together with the context in which the assertion is written, determine when evaluation attempts of the assertion begin.

This chapter discusses the mechanics of declaring clocks and the rules that determine their scoping, including default clocking. Many concurrent assertions of practical interest are *singly clocked*, meaning that all parts of the assertion are governed by a single clocking event. Other concurrent assertions have portions that fall under the scopes of two or more clocking events and are called *multiply clocked*. SystemVerilog 2009 relaxes the rules on where the clocking event may change, allowing, e.g., clock changes after ##0 and |-> that were previously illegal.

¹ The SystemVerilog LRM avoids the phrase "multiply clocked", using instead the grammatically suspicious adjectives "multiclock" and "multiclocked".

270 12 Clocks

12.1 Overview of Clocks

This section gives an intuitive overview of clocks based on examples.

Clocks, or, more precisely, clocking events, define the discretization of time within concurrent assertions. They are declarations with scopes, not operators. A clocking event for a concurrent assertion must not occur more than once per time-step. If a clocking event occurs more than once in a time-step, then the LRM defines no behavior for the assertion and a tool may issue an error. It is the assertion writer's responsibility to ensure that the clocks for assertions are "glitch-free" in this sense. Within the scope of a clocking event, one unit, or cycle, of discrete time is measured from one occurrence of the clocking event (i.e., clock tick) to the next. Since the clocking event must be glitch-free, one unit of discrete time is at least one time-step. Clocks also influence the sampling of values within a concurrent assertion. The sampled value of a variable or net is the value from the Preponed region of a time-step. If a reference to a variable or net appears within the scope of a clocking event, then the time-steps relevant for sampling are those in which the clocking event occurs.²

12.1.1 Specifying Clocks

This section describes various ways to specify clocks for concurrent assertions, illustrated by singly clocked examples.

The concurrent assertion in Fig. 12.1 specifies an explicit clocking event control,³ @(posedge clk), in line 3. The scope of the clocking event is the entire property expression a |=> b, so al is an example of a *singly clocked* assertion. This implies that the references to a and b in line 4 are evaluated using sampled values in timesteps in which posedge clk occurs. The one cycle delay specified by |=> from its antecedent to its consequent is from one occurrence of posedge clk to the next. Finally, the *leading clocking event* of al is also posedge clk. Since al is a static concurrent assertion (i.e., one that is not in a procedural context), a new evaluation attempt of al begins at each occurrence of posedge clk.

```
module simple_clock(input logic clk, a, b);
al: assert property(
    @(posedge clk)
    a |=> b
);
endmodule
```

Fig. 12.1 Module with explicitly clocked concurrent assertion

² See Sect. 12.2.1 for exceptions.

³ We use the phrase "clocking event control" to emphasize the inclusion of the @ symbol in the syntax.

12.1 Overview of Clocks 271

Figure 12.2 shows a possible waveform for the signals in this example. The event posedge clk occurs at times 20, 30, 50, 75, and 95. The intervals from time 20 to 30, from time 30 to 50, etc. each constitute one cycle of discretized time, although their lengths vary in units of simulation time. This illustrates the fact that the clock ticks do not have to be regular as measured against simulation time. From among these clock ticks, the sampled value of a is 1'b1 only at times 20 and 75. Therefore, the evaluation attempts of al that begin at times 30, 50, and 95 succeed vacuously. The attempt that begins at time 20 checks the sampled value of b at time 30 and finds it to be 1'b1, so this attempt succeeds. The attempt that begins at time 75 checks the sampled value of b at time 95 and finds it to be 1'b0, so this attempt fails. The fact that the sampled value of b is 1'b1 at the clock tick at time 50 is irrelevant for the evaluation of al.

Clocking events form a rich subset of general SystemVerilog events and are specified using a limited event control syntax:

```
clocking_event ::=
    @ identifier
    | @ ( event_expression )
```

The event expression in the form @ (event_expression) can be a familiar edge event, such as posedge clk, the name of a declared event, or a more general, and possibly complex, event expression. The identifier in the form "@ identifier" can be the name of a declared event or the name of a clocking block, the latter specifying the clocking event of the referenced clocking block.

Figure 12.3 illustrates some of the different forms of the clocking event control syntax in a module with various explicit concurrent assertion clocking declarations.




Fig. 12.2 Waveform for module simple_clock

```
module various_clocks(input logic clk1, clk2, a, b, c);
event e;
always @(negedge clk1) ->e;
clocking PCLK2 @(posedge clk2); endclocking
a2: assert property(@(negedge clk1) a |=> b);
a3: assert property(@e a[*2] |=> c);
a4: assert property(@PCLK2 a |=> b);
endmodule
```

Fig. 12.3 Module with various explicit concurrent assertion clocking declarations

Assertion a2 is clocked by an explicit edge event expression and is similar to a1 in the previous example. Assertion a3 is clocked by named event e. The always procedure in line 3 triggers e at every occurrence of negedge clk1, so a3 behaves equivalently to the following variant:

```
a3 v2: assert property(@(negedge clk1) a[*2] |=> c);
```

The clocking event for a4 is PCLK2, the name of the clocking block in line 4, and so a4 is clocked by the event posedge clk2 of that clocking block.

Often, many assertions within a module, interface, program, or checker share the same clock. In this situation, it is convenient to specify a *default* clocking block (see also Sect. 2.3). The module various_clocks from Fig. 12.3 is recoded in an equivalent way in Fig. 12.4. Line 2 declares NCLK1 to be the default clocking for the module, with event negedge clk1. As a result, explicit clocking events can be omitted on assertions a2 and a3: the default is understood to apply to them. The default can be overridden by an explicit clocking event, as in a4.

Default clocking applies to concurrent assertions, not to sequence and property declarations. This convention allows a sequence or property to be declared without clocks and to inherit the clock from the context in which it is instantiated. Figure 12.5 shows another equivalent encoding of module various_clocks illustrating this style. This encoding also dispenses with the declaration of clocking block PCLK2, putting the event expression posedge clk2 directly in a4.

Clocks may also be declared within named sequence or property declarations. A clock in the declaration of a named sequence or property declaration applies to all instances of the named sequence or property, overriding any clock from the context in which it is instantiated. Figure 12.6 illustrates this style with another equivalent encoding of module various_clocks. The named property p1 can no longer be instantiated in a2 because the clocking event posedge clk2 in the declaration of p1 would override the default clocking in the instance.

```
module various_clocks(input logic clk1, clk2, a, b, c);
default clocking NCLK1 @(negedge clk1); endclocking
clocking PCLK2 @(posedge clk2); endclocking
a2: assert property(a |=> b);
a3: assert property(a[*2] |=> c);
a4: assert property(@PCLK2 a |=> b);
endmodule
```

Fig. 12.4 Module with default clocking

```
module various_clocks(input logic clk1, clk2, a, b, c);
default clocking NCLK1 @ (negedge clk1); endclocking
property p1; a |=> b; endproperty
a2: assert property(p1);
a3: assert property(a[*2] |=> c);
a4: assert property(@(posedge clk2) p1);
endmodule
```

Fig. 12.5 Module with default clocking and unclocked property declaration

12.1 Overview of Clocks 273

```
module various_clocks(input logic clk1, clk2, a, b, c);
default clocking NCLK1 @(negedge clk1); endclocking
property p1; @(posedge clk2) a |=> b; endproperty
a2: assert property(a |=> b);
a3: assert property(a[*2] |=> c);
a4: assert property(p1);
endmodule
```

Fig. 12.6 Module with default clocking and clocked property declaration

```
module various clocks(input logic clk1, clk2, a, b, c);
1
      default clocking NCLK1 @(negedge clk1); endclocking
2
      property p1(event ev = $inferred clock);
3
         @ev a |=> b;
4
5
      endproperty
      a2: assert property(p1);
6
7
      a3: assert property(a[*2] |=> c);
      a4: assert property(p1(.ev(posedge clk2)));
8
   endmodule
```

Fig. 12.7 Module with default clocking and clocked property declaration with event argument

Another approach for specifying clocks in declarations of named sequences and properties is to pass the clocking events as arguments. This can be done with untyped arguments or with arguments of type event. SystemVerilog 2009 adds the system function \$inferred_clock, which can be used as a default actual argument. If no actual argument is passed to the formal in an instance, then \$inferred_clock as default actual specifies that the clock from the instantiation context applies. Figure 12.7 illustrates this usage with a final equivalent coding of module various_clocks. a2 instantiates p1 without an actual, so \$inferred_clock specifies that the default clocking applies. a4 instantiates p1 and passes the event expression posedge clk2 to the event argument ev.

12.1.2 Multiple Clocks

All examples of concurrent assertions in the preceding section were singly clocked. Figure 12.8 gives an example of a multiply clocked assertion. The leading clocking event for a5 is **posedge** clk1, and the reference to a is within the scope of this clock. The reference to b is within the scope of **posedge** clk2.

The multiply clocked behavior of a5 merits further explanation. Since the leading clock is **posedge** clk1 and since a5 is a static concurrent assertion, a new evaluation attempt of a5 begins at each tick of **posedge** clk1. Let t_0 be such a time. If the sampled value of a at t_0 is 1'b0, then the attempt succeeds vacuously. Otherwise, the antecedent of |=> is matched at t_0 , and evaluation of the consequent is obligated. Since the consequent is governed by a different clock, |=> does *not* specify advancement to the next tick of **posedge** clk1 after t_0 . Rather, |=> serves as a *synchronizer*

```
module multiply_clocked(input logic clk1, clk2, a, b, c);
a5: assert property(
    @(posedge clk1) a |=> @(posedge clk2) b
    );
endmodule
```

Fig. 12.8 Module with multiply clocked assertion




Fig. 12.9 Waveform for assertion a5 in module multiply_clocked

between the two clocks. It specifies that evaluation of the consequent begin at the nearest tick of posedge clk2 that is strictly after t_0 . In that time-step, the sampled value of b is checked, and if it is 1'b1, then the overall attempt succeeds. Otherwise, the overall attempt fails.

Figure 12.9 shows a possible waveform for a5. An attempt of a5 begins at every tick of posedge clk1. The sampled value of a is 1'b1 at times 20, 40, 60, and 80, so in each of these time-steps the antecedent of |=> matches. The attempt beginning at time 20 looks for the nearest tick of posedge clk2 that is strictly later than time 20. This clock tick is at at time 35, where the sampled value of b is found to be 1'b0, and so the attempt fails. Because the operator |=> has been used, it does not matter that posedge clk2 occurs at time 20 since this occurrence is not strictly later. The attempts beginning at times 40 and 60 both find the nearest strictly future tick of posedge clk2 at time 65, where the sampled value of b is 1'b1, and so these attempts succeed. The attempt beginning at time 80 finds the nearest strictly future tick of posedge clk2 at time 95, where the sampled value of b is again 1'b1, and so it succeeds. As before, the fact that posedge clk2 occurs at time 80 is irrelevant because the operator |=> has been used.

SystemVerilog 2009 allows | -> also to be used as a synchronizer between different clocks. Suppose that the following assertion is added to the module in Fig. 12.8:

```
a6: assert property(
   @(posedge clk1) a |-> @(posedge clk2) b
);
```

If a match of the antecedent of |-> ends at time t_0 , then the consequent will be checked at the nearest time greater than *or equal to* t_0 in which posedge clk2 occurs. Comparing with the waveform in Fig. 12.9, the attempt of a6 beginning at time 20 succeeds because posedge clk2 occurs at time 20 and the sampled value

12.1 Overview of Clocks 275

of b at that time is 1'b1. The attempts of a6 beginning at times 40 and 60 behave the same as the corresponding attempts of a5. Finally, the attempt of a6 beginning at time 80 fails because there is a tick of **posedge** clk2 at this time and the sampled value of b is 1'b0.

The operators ##1 and ##0 can be used as synchronizers between different clocks in sequences. Use of the latter as a synchronizer is new in SystemVerilog 2009. The timing associated with ##1 as a synchronizer is the same as that of |=>. Here is an example:

```
sequence s1;
  @(posedge clk1) a[*2] ##1 @(posedge clk2) b;
endsequence
```

Referring again to Fig. 12.9, s1 matches over the intervals from times 20 to 65, 40 to 65, and 60 to 95. The following variant replaces ##1 with ##0:

```
sequence s2;
  @(posedge clk1) a[*2] ##0 @(posedge clk2) b;
endsequence
```

The timing associated with ##0 as a synchronizer is the same as that of |->. Therefore, the intervals in Fig. 12.9 over which s2 matches are from times 20 to 65 and 40 to 65. There is no match of s2 beginning at time 60 because the subsequence a [*2] matches ending at time 80 and there is an tick of posedge c1k2 at this time with the sampled value of b equal to 1'b0.

##1 and ##0 are the only sequence operators that can be used as synchronizers between different clocks. For all other sequence operators, the operands must be singly clocked sequences clocked by the same clocking event. Here is an example of an illegal sequence declaration:

```
sequence s3_illegal;
  @(posedge clk) a[*2] within @(negedge clk) b[->1];
endsequence
```

This sequence is illegal because the operands of within are clocked by different clocking events.

In addition to |=> and |->, the property operators #=# and #-# can be used as synchronizers between different clocks. The timing of #=# (resp., #-#) as a synchronizer is the same as that of |=> (resp., |->). if-else and case can also serve as synchronizers, with timing the same as that of |->. Here is an example:

```
a7: assert property(
   @(ev1)
   if (a)
        @(ev2) b[*2]
   else
        @(ev3) c
);
```

In a7, the scope of ev1 is the condition a of the if-else. Assuming that a is of type bit, the following variant behaves equivalently to a7 and explains how the timing of if-else as a synchronizer is the same as that of |->:

```
1    a7_v2: assert property(
2    @(ev1)
3    ( a |-> @(ev2) b[*2])
4    and
5    (!a |-> @(ev3) c)
6    );
```

This encoding also illustrates some of the *clock flow* rules of clock scoping. The scope of ev1 distributes to the two operands of and and flows into the parenthesized subproperties in lines 3 and 5. As a result, a in line 3 and !a in line 5 are both under the scope of ev1.

The LTL operators nexttime, always, s_eventually, until, and their variants can also be used as synchronizers. When this is done, the time advance specified by the LTL operator is determined by the *incoming* clock, not by the leading clock or clocks of the operands. See Sect. 12.2.5.1 for more details.

The logical property operators and, or, iff, and implies can be used to join differently clocked properties. Figure 12.10 gives an example. The scope of ev1 includes the antecedent a [*2] of |=> and the operand !a of and in line 4. and joins one operand clocked by ev1 and one clocked by ev2. The antecedent of |=> matches if the sampled value of a is 1'b1 at two successive ticks of ev1. Suppose that such a match ends at t_0 . Line 4 of the consequent says that at the nearest tick of ev1 strictly after t_0 , the sampled value of a must be 1'b0. Line 6 of the consequent says that at the nearest tick of ev2 strictly after t_0 , the sampled value of b must be 1'b1.

A multiply clocked concurrent assertion is required to have a unique leading clock. If the concurrent assertion is static (i.e., not within a procedural context), then it has implicit "always" semantics and the leading clock determines when new evaluation attempts of the assertion begin. If the concurrent assertion is procedural, then the leading clock determines when evaluation begins of an attempt that has matured from the procedural assertion queue (see Chap. 14). The following example is illegal:

```
a8_illegal: assert property(
   @(ev1) a or @(ev2) b
);
```

The assertion is illegal because it has two leading clocks, ev1 and ev2.

The remainder of this section discusses a few abstract, but practically motivated, examples of multiply clocked properties.

Fig. 12.10 Logical operator joining differently clocked properties

12.1 Overview of Clocks 277

Example 12.1. Write an assertion to check that the time from any occurrence of EV1 to the nearest strictly subsequent occurrence of EV2 is at least MINTIME simulation time-steps.

Solution: This encoding uses local variables (see Chap. 15) to capture timestamps for comparisons. Because of the use of timestamps, it is not so well suited for formal verification.

```
property p_mintime(event ev1, ev2, integer mintime);
integer basetime;
@(ev1) (1'b1, basetime = $time)
|=> @(ev2) $time >= basetime + mintime;
endproperty
a_EV1_EV2_MINTIME: assert property(
p_mintime(.ev1(EV1), .ev2(EV2), .mintime(MINTIME))
);
```

The expectation is that MINTIME is a constant, perhaps a parameter, that has been coordinated with the simulation timescale. Line 2 declares the local variable basetime. Line 3 specifies that when ev1 occurs, the value of \$time is stored in basetime. According to line 4, at the nearest strictly subsequent occurrence of ev2, the value of \$time must be at least the sum of basetime and mintime.

Example 12.2. Write an assertion to check that after an occurrence of event ev_start, event ev_wait cannot occur any earlier than the time-step of the first occurrence of event ev_enable.

Solution: This solution assumes that in any time-step these events will occur before the Observed region.

```
sequence s ev(event ev);
1
       @(ev) 1'b1
2
       ##0 @(ev enable or ev wait) 1'b1;
3
    endsequence
4
    a order: assert property (
5
       @(ev start) 1'b1
6
       |=> @(ev enable or ev wait) (
7
           s_ev(ev_wait).triggered
8
          ->
9
           s ev(ev enable).triggered
10
       )
11
    );
12
```

The basic idea of this solution is as follows. If ev_start occurs, then advance to the nearest strictly subsequent occurrence of either ev_enable or ev_wait. In that time-step, if ev_wait has occurred, then ev_enable must also have occurred.

In line 6, the antecedent of |=> matches at an occurrence of ev_start. The consequent is clocked by the compound event expression "ev_enable or ev_wait", so it advances to the nearest strictly subsequent occurrence of either ev_enable or ev_wait. Lines 8 through 10 use the Boolean implication -> to encode the check that if ev_wait has occurred in the current time-step, then ev_enable must also have occurred in the current time-step. The job of s_ev is to detect whether its event

formal argument ev occurs. The detection is accomplished by applying sequence method triggered to instances of s_ev in lines 8 and 10.

In line 2, s_ev begins a match at an occurrence of its event formal argument ev. Line 3 is counterintuitive. It addresses the following restriction on the use of triggered: the ending clock of a sequence instance to which triggered is applied must be identical to the clock governing the context in which the application of triggered appears. In lines 8 and 10, triggered is applied in a context clocked by ev_enable or ev_wait, so line 3 ensures that s_ev ends on this clock. Line 3 does not actually cause any time advance for matches of the instances of s_ev in lines 8 and 10. The reason is that the actual event arguments in these instances are ev_wait and ev_enable. If one of these events occurs in a time-step, then a fortiori the compound event "ev_enable or ev_wait" occurs in that time-step.

12.2 Further Details of Clocks

This section delves into further details of specifying clocks, their scoping, and the use of multiple clocks.

12.2.1 Preponed Value Sampling

In general, references to variables and nets that appear in a concurrent assertion use *sampled values*, i.e., the values from the Preponed region of the time-step. The following are exceptions for this rule:

- Assertion local variables.
- Disable condition of disable iff.
- Clocking event expressions.
- Actual arguments passed to ref or const ref arguments⁴ of subroutines attached to sequences.
- Assertion action blocks.

References to local variables always use current values. References in the other contexts above always use current values unless they appear within the system function \$sampled. Since subroutines attached to sequences and action blocks execute in the Reactive region, this means that references in the last two contexts use Reactive region values.

If Preponed value sampling applies to a reference to a variable or net and the reference appears within the scope of a clocking event, then the time-steps in which

⁴ ref and const ref both specify that the actual argument is passed by reference. External changes to the actual argument are visible to the subroutine. A ref argument can also be modified by the subroutine, while a const ref argument cannot.

the reference is evaluated are those in which the clocking event occurs. References in the abort condition of an asynchronous abort (accept_on or reject_on) use sampled values, but the abort condition is not governed by a clock.⁵

As a simple example, consider the following:

```
a_strange_clk: assert property(
    @(posedge clk)
    clk

else $display("FAIL: clk=%b", clk);
```

For simplicity, assume that <code>clk</code> is of type <code>bit</code> and that it changes value at most once in any time-step. The reference to <code>clk</code> within the clocking event in line 2 uses the current value, while the reference in line 3 uses the sampled value. In a time-step in which <code>posedge clk</code> occurs, the sampled value will always be <code>l'bo</code>. Therefore, in each such time-step, <code>a_strange_clk</code> will fail and the action block in line 4 will execute. The reference to <code>clk</code> after the control string in the display statement uses the current, Reactive region value. Since there was a tick of <code>posedge clk</code> in the current time-step, prior to the Observed region, the value of <code>clk</code> in the Reactive region is <code>l'bl</code>. Therefore, there is a mismatch between the value in line 3 that causes the assertion failure and the value written by the display statement. Changing the display to

```
$display("FAIL: clk=%b", $sampled(clk));
```

fixes the mismatch. The assertion remains counterintuitive, though, because of the relationship between lines 2 and 3. Care must always be taken when interpreting assertions that reference the same variable in contexts where sampling is and is not used.

There are two other kinds of references within concurrent assertions that do not use sampling:

- const cast expressions or automatic variables in a concurrent assertion within procedural code.
- Free checker variables.

References within a const cast expression or to an automatic variable in a concurrent assertion within procedural code resolve to the values that existed when the assertion was placed in the procedural assertion queue. See Chap. 14 for more details. References to free checker variables use current values, which may reflect the result of randomization in the current time-step. See 22.1 for more details.

Preponed value sampling in a concurrent assertion is not allowed to conflict with other sampling defined within a clocking block. In particular, if a clocking block input variable is referenced in a concurrent assertion, then the variable must be sampled with #1step⁶ in the clocking block and the clock governing the reference in the assertion (if there is one) must be the same as that of the clocking block.

⁵ Technically, one could say that disable conditions and asynchronous abort conditions are not within the scope of any clock.

⁶ #1step specifies Preponed value sampling.

```
module various clocks (input logic clk1, clk2, a, b, c);
1
       default clocking NCLK1 @(negedge clk1); endclocking
2
       clocking PCLK2 @(posedge clk2); endclocking
3
           assert property(a |=> b);
4
           assert property(a[*2] |=> c);
5
       a3:
       module nested 1;
6
          default clocking PCLK2;
          a4: assert property(a |=> b);
8
       endmodule
9
       module nested 2;
10
              assert property(a |=> @PCLK2 c);
          a9:
11
       endmodule
12
    endmodule
13
```

Fig. 12.11 Module and nested modules with default clocking declarations

12.2.2 Default Clocking

A clocking block may be declared as the default within a given module, interface, program, or checker. There are two syntactic forms for specifying default clocking. One prepends the keyword default to the clocking block declaration, as in the following example:

```
default clocking PCLK @(posedge clk); endclocking
```

The other uses a separate top-level declaration to specify the default clocking, as in the following example:

```
clocking PCLK @(posedge clk); endclocking
...
default clocking PCLK;
```

The scope of a default clocking declaration is the entire module, interface, program, or checker in which it appears, including nested modules, interfaces, or checkers. A nested module, interface, or checker may, however, have its own default clocking declaration, which overrides a default from outside. The scope of a default clocking declaration does not descend into instances of modules, interfaces, or checkers.

The clocking event of a default clocking block will be called the *default clocking event*, or simply the *default clock*. Throughout the scope of a default clocking declaration, the default clock applies to all cycle delay operations whose clocking is not otherwise specified. In particular, the default clock serves as the leading clock of all concurrent assertions whose leading clock is not explicitly specified or otherwise inferred (see Chap. 14 for rules of inference of clocks for procedural concurrent assertions).

If the default clock is the leading clock for a concurrent assertion, then the rules of clock flow (see Sect. 12.2.4.1) determine what subsequent parts of the concurrent assertion are also clocked by the default clock. If the concurrent assertion has no explicit or otherwise inferred clocking event, then it is singly clocked by the default clock.

Figure 12.11 shows a variant of module various_clocks that illustrates these ideas. a2 and a3 are singly clocked by the default clock NCLK1. Module nested_1 has its own default clock, so a4 is singly clocked by PCLK2. Module nested_2 inherits the default clock NCLK1 from its parent. a9 is multiply clocked. Its leading clock is the default clock NCLK1, but its consequent is clocked by PCLK2.

A default clock does not apply to declarations of sequences or properties. Clock scoping rules apply to instances of such declarations in the context of instantiation.

12.2.3 Restrictions in Multiply-Clocked Sequences

The only synchronizers allowed in sequences are ##0 and ##1. Therefore, the general form of a multiply clocked sequence s is

$$s = r_0 ##n_1 r_1 ##n_2 \cdots ##n_k r_k$$

where $k \geq 1$, each r_i , $0 \leq i \leq k$, is a singly clocked sequence, and each n_i , $1 \leq i \leq k$, is either 0 or 1. We may assume that in this form r_i and r_{i+1} are differently clocked for each $0 \leq i < k$, since otherwise they could be combined into a larger singly clocked subsequence. Then the sequences r_i are the maximal singly clocked subsequences of s.

SVA requires that the maximal singly clocked subsequences of a multiply clocked sequence not admit empty match. This guarantees that each r_i has unambiguous starting and ending clock ticks for any match, thereby ensuring that there is a well-defined leading clock and that the clock changes for each synchronizer are well defined.

For example, the following multiply clocked sequence is illegal:

```
@(ev1) a[*] ##1 @(ev2) b
```

The maximal singly clocked subsequences are @(ev1)a[*] and @(ev2)b, and the former admits empty match. In this situation, we cannot be sure whether the leading clock is ev1 or ev2, and this ambiguity is disallowed. Changing the sequence to

```
@(ev1) a[+] ##1 @(ev2) b
```

makes it legal. The first maximal singly clocked subsequence is now @(ev1)a[+], which does not admit empty match. Now we can be sure that the leading clock of the sequence is ev1 and that ##1 synchronizes between a tick of ev1 and a tick of ev2.

12.2.4 Scoping of Clocks

In SVA, clocking events controls are declarations with scopes, not operators. As such, clocks have no strengths. The scoping rules for clocks have been designed

to allow the scopes of clocks to extend intuitively through the structure of the assertions, sequences, and properties and to reduce the need for parenthesization and repetition of clocking event controls.

There are actually two sets of rules that work together to determine how each part of a concurrent assertion is clocked. The first set of rules, called *clock flow* rules, defines how scopes of clocks descend from the outside in, beginning with the default clock or inferred clock, if it exists. A basic idea in clock flow is that the scope of a clocking event cannot flow across another clocking event control. In other words, the inner clock blocks and takes precedence over a clock flowing in from above or outside. The second set of rules defines the *set of semantic leading clocks* for a sequence or property expression. These rules work from the inside out and capture the notions that inner clocks take precedence over outer clocks and that some expressions require an incoming clock.

In the presence of instances of named sequences and properties, both sets of rules are understood to apply to the assertions, sequence expressions, and property expressions that result from expanding the instances.⁷

12.2.4.1 Clock Flow

The clock flow rules define how scopes of clocks descend from the outside in. They are intended to be intuitive and to reduce the need for parenthesization and repetition of clocking event controls. Reliance on the rules can always be reduced by adding explicit clocking event controls, although doing so in sequence or property declarations may reduce their reusability. Here are the clock flow rules:

- CF1: A default clock flows to every concurrent assertion in its scope.
- CF2: An inferred clock for a procedural context (see Chap. 14) overrides a default clock and flows to every concurrent assertion in its scope.
- CF3: Clock c flows out of @ (c).
- CF4: A clock c that flows to a clocking event control @(d) does not flow across the clocking event control. Instead, the scope of c is halted by @(d), and the scope of d begins after @(d).
- CF5: A clock that flows to an instance of a named sequence or property flows into the body of the corresponding declaration, except in the case of an instance of a named sequence to which a sequence method is applied. If the instance is of a sequence, then the clock also flows across the instance, regardless of whether a sequence method is applied. A clock in the body of a declaration does not flow out of an instance.
- CF6: A clock that flows to a parenthesized subexpression (either a subsequence or a subproperty) flows into the subexpression. If the subexpression is a sequence,

⁷ See the Rewriting Algorithms in Annex F.4 of the SystemVerilog 2009 LRM.

⁸ Rule CF2 can be thought of as a special case of CF4 if the inferred clock is understood to specify a clocking event control at the beginning of each of the concurrent assertions in its scope.

П

then the clock also flows across the parenthesized subexpression. A clock inside the subexpression does not flow out of the enclosing parentheses. This rule applies to parentheses enclosing a sequence to which one or more sequence match items are attached. Analogous rules apply to operators with explicit parentheses: strong(), weak(), first match().

- CF7: A clock that flows to a maximal Boolean expression b governs b and flows across b. Analogous rules apply to Boolean repetitions b = -n, b = n, etc.
- CF8: A clock that flows to one of the operators ##n, [*n], |->, |=>, #-#, and #=# flows across the operator. If the operator is not a synchronizer, then the clock also governs time advances associated with the operator. Analogous rules apply to ranged variants of these operators.
- CF9: A clock that flows to the left operand of one of the infix operators or, and, intersect, within, throughout, iff, implies, and until flows to the operator and distributes to (i.e., flows into) both operands. The clock also governs time advance for until. Analogous rules apply to the various variants of these operators.
- CF10: A clock that flows to one of the prefix operators not, nexttime, always, and eventually flows to the operand of the operator. The clock also governs time advance in nexttime, always, and eventually. Analogous rules apply to the various variants of these operators.
- CF11: A clock that flows to an if-else governs the test condition of the if-else. The clock also flows into each of the underlying properties of the if-else. Analogous rules apply to case.
- CF12: A clock that flows to a disable iff, accept_on, or reject_on flows into the underlying property. The clock does *not* govern the reset condition.
- CF13: A clock that flows to a sync_accept_on or sync_reject_on governs the abort condition and flows into the underlying property.

The following examples illustrate the clock flow rules.

Example 12.3. Analyze the clock flow in the following property:

```
@(ev1) a |=> b ##1 @(ev2) c
```

Solution: By CF3, ev1 flows to a. By CF7, ev1 governs a and flows to |=>. By CF8, ev1 flows across |=> to b. By CF7, ev1 governs b and flows to #1. By CF8, ev1 flows across #1 to @(ev2). By CF4, the scope of ev1 does not flow across @(ev2). Therefore, #1 is a synchronizer between ev1 and ev2. By CF3, ev2 flows to c. By CF7, ev2 governs c. In summary, the property is equivalent to the following, in which each of the Booleans is explicitly clocked:

```
@(ev1) a |=> @(ev1) b ##1 @(ev2) c
```

Example 12.4. Analyze the clock flow in the following property:

```
@(ev1) a ##1 (b ##1 @(ev2) c) |=> d
```

Solution: By CF3, CF7, and CF8, ev1 flows to and governs a and flows across ##1 to the parenthesized subsequence (b ##1 @ (ev2) c). By CF6, ev1 flows into and across the parenthesized subsequence. Therefore, ev1 flows to and across |=> (CF8), and so it flows to and governs d (CF7). Within the parenthesized subsequence, ev1 flows to, governs, and flows across b (CF7), flows across ##1 (CF8), and ends at @ (ev2) (CF4). Therefore, the ##1 within the parenthesized subsequence synchronizes between ev1 and ev2. By CF3, ev2 flows to and governs c, but ev2 does not flow out of the enclosing parentheses by CF6. As a result, |=> is a synchronizer between ev2 and ev1. In summary, the property is equivalent to the following, in which each of the Booleans is explicitly clocked:

```
@(ev1) a ##1 @(ev1) b ##1 @(ev2) c |=> @(ev1) d
```

Example 12.5. Analyze the clock flow in the following module:

```
module m1 (logic a, b, c, d, event ev1, ev2);
default clocking EV1 @(ev1); endclocking
sequence s4; b ##1 @(ev2) c; endsequence
a10: assert property(a ##1 s4 |=> d);
endmodule
```

Solution: By CF1, ev1 flows to a10, hence flows to and governs a (CF7) and flows across ##1 to the instance of s4 (CF8). By CF5, ev1 flows into the body of s4 for this instance and also across the instance (CF5). Within the body of s4, ev1 flows to and governs b (CF7), flows across ##1 (CF8), and stops at @(ev2) (CF4). ev2 governs c (CF3, CF7), but ev2 does not flow out of the instance of s4 (CF5). ev1 flows across |=> (CF8), and so it flows to and governs d (CF7). In summary, a10 behaves the same as the property in the preceding example.

After application of the clock flow rules, each Boolean expression that stands as a subsequence within a concurrent assertion must be governed by a clock. Otherwise, the assertion is not legal. The following example illustrates an illegal assertion:

By CF3 and CF7, ev1 governs a, but by CF6 ev1 does not flow out of the enclosing parentheses. There is no default clock, so no clock governs b.

12.2.4.2 Semantic Leading Clocks

The rules of semantic leading clocks define how the leading clock or clocks of a sequence or property are determined from the inside out. One of the basic ideas of clock flow is that an outer clock is replaced by, rather than flowing through, an inner

clock. This means that @(c)@(d) p behaves semantically the same as @(d) p. Syntactically, the leading clock of @(c)@(d) p appears to be c, but semantically it is d.

Another principle of concurrent assertions is that every subsequence, in particular every Boolean that stands as a subsequence, must be clocked. When examining semantic leading clocks from the inside out, though, there may be no clock at hand. For example, in the presence of default clocking, the following concurrent assertion is legal:

```
c1: cover property (a ##1 b);
```

When examining the underlying sequence a ##1 b, there is no clock at hand in the expression. Therefore, the definition of semantic leading clocks uses a device to indicate that a clock needs to be provided from outside, namely the *inherited* semantic leading clock.

The rules of semantic leading clocks propagate these ideas through the various sequence and property forms. They appear below and define the set LC of semantic leading clocks for a sequence or property. In the rules, b denotes a Boolean; n denotes a natural number; r, r_1 , r_2 denote sequences; item denotes a sequence match item; p, p_1 , p_2 denote properties; x denotes either a sequence or a property; and c denotes a clocking event.

- LC1: If inherited $\in LC(x)$, then $LC(@(c) x) = \{c\} \cup (LC(x) \{inherited\})$. Otherwise, LC(@(c) x) = LC(x).
- LC2: LC((x)) = LC(x).
- LC3: $LC(b) = LC(b[->n]) = LC(b[=n]) = \{inherited\}$. Analogous rules apply to variants of these operators.
- LC4: $LC(b \text{ throughout } r) = \{inherited\} \cup LC(r)$.
- LC5: $LC(r_1 \text{ and } r_2) = LC(r_1) \cup LC(r_2)$. The same rule applies if and is replaced by any of or, intersect, and within.
- LC6: $LC(r_1 \# n r_2) = LC(r_1)$. Analogous rules apply to variants of # n.
- LC7: $LC(r[\star n]) = LC(r)$. Analogous rules apply to variants of $[\star n]$.
- LC8: LC((r, item)) = LC(r).
- LC9: $LC(\texttt{first_match}(r)) = LC(r)$. The same rule applies if $\texttt{first_match}()$ is replaced by strong() or weak().
- LC10: LC(not p) = LC(p).
- LC11: $LC(p_1 \text{ and } p_2) = LC(p_1) \cup LC(p_2)$. The same rule applies if and is replaced by any of or, iff, and implies.
- LC12: $LC(r \mid -> p) = LC(r)$. The same rule applies if $\mid ->$ is replaced by any of $\mid ->$, #-#, and #=#.
- LC13: $LC(\text{nexttime } p) = \{\text{inherited}\}$. The same rule applies if nexttime is replaced by always or s_eventually or by variants of any of these operators.
- LC14: $LC(p_1 \text{ until } p_2) = \{inherited\}$. Analogous rules apply to the variants of until.
- LC15: If p is an if-else or case property, then $LC(p) = \{inherited\}$.

 LC16: LC(accept_on(b) p) = LC(p). The same rule applies if accept_on is replaced by reject_on or disable iff.

• LC17: $LC(sync_accept_on(b) p) = \{inherited\}$. The same rule applies when $sync_accept_on$ is replaced by $sync_reject_on$.

Rule LC1 captures the fact that an outer clock applied to x is semantically significant if, and only if, something within x requires an incoming clock, as evidenced by the presence of *inherited* in LC(x). Rule LC3 says that Booleans require incoming clocks.

Rules LC1 through LC9 account for semantic leading clocks in sequences. They do not enforce the various restrictions on the clocking of sequences, such as those from Sect. 12.2.3. Rather, they allow for partial clocking of sequences that still requires an incoming clock, as in

```
(a[*2]  and @(ev1)  b[->1]) ##1 c
```

LC of this sequence is {inherited, ev1}, where inherited records the fact that a [*2] requires an incoming clock. Since and is not a synchronizer for sequences, the incoming clock must be identical to ev1 for the concurrent assertion in which this sequence appears to be legal.

Rules LC1, LC2, and LC9 through LC17 account for semantic leading clocks in properties. LC13 and LC14 capture the fact that the incoming clock governs time advancement in the temporal operators of the nexttime, always, s_eventually, and until families. LC15 indicates that the condition of an if-else or case is governed by the incoming clock, while LC16 indicates that the reset condition of an asynchronous abort is independent of the incoming clock.

Rule LC17 reflects the definition in the SystemVerilog 2009 LRM for synchronous aborts, namely, that the incoming clock governs the abort condition and serves as leading semantic clock. However, the LRM leaves ambiguous whether and how synchronous abort operators may be used as synchronizers. Therefore, it is advised to use synchronous aborts only when there is at most one explicit (i.e., non-*inherited*) semantic leading clock of the underlying property and this clock is identical to the incoming clock.

The top-level property of a concurrent assertion is always required to have a single semantic leading clock after the resolution of clock scoping. If p is such a top-level property, then this means that LC(p) must have one of the following forms:

- $\{c\}$. In this case, c is the unique, explicit semantic leading clock of p, and no incoming clock is required or has any effect.
- {*inherited*}. In this case, *p* has no explicit semantic leading clock and requires an incoming clock, either from default clocking or from a procedural context.

⁹ In fact, various rewrite rules in Annex F.5 of the LRM lead to the conclusion that, while the abort condition of a synchronous abort is governed by the incoming clock, the set of semantic leading clocks is determined from the underlying property, in contradiction to LC17.

• {inherited, c}. In this case, c is an explicit semantic leading clock of p, but p also requires an incoming clock, which must be identical to c.¹⁰

Example 12.6. Compute the set of semantic leading clocks in the following assertion and determine any requirements on the context in which the assertion appears:

```
al2: assert property(
    a or @(ev1) b and nexttime @(ev2) c
);

Solution:
LC(b \text{ and nexttime } @(ev2) \text{ c})
= LC(b) \cup LC(\text{nexttime } @(ev2) \text{ c}) \qquad \text{(LC11)}
= \{inherited\} \qquad \text{(LC3, LC13)}
Therefore by LC1,
```

LC(@(ev1) b and nexttime $@(ev2) c) = {ev1}$

By LC3, $LC(a) = \{inherited\}$, and so by LC11, the set of semantic leading clocks for the entire assertion is $\{ev1, inherited\}$. This means that the assertion must be in a context that guarantees an incoming clock, either by default clocking or by inference from a procedural context, and the incoming clock must be identical to ev1.

12.2.5 Finer Points of Multiple Clocks

This section covers a few finer points regarding the use of multiple clocks in sequences and properties.

12.2.5.1 Clocking LTL Operators

When LTL operators nexttime, always, s_eventually, until, and their variants are used as synchronizers, it is important to remember that the time advance specified by the LTL operator is determined by the incoming clock, not by the leading clock or clocks of the operands. Consider the following:

```
module m3 (logic a, b, clk1, clk2);
  a13: assert property(
    @(posedge clk1) a |-> nexttime @(posedge clk2) b
  );
  a14: assert property(
    @(posedge clk1) a |-> ##1 @(posedge clk2) b
  );
endmodule
```

¹⁰ The LRM does not define precisely the criterion "identical", but through examples it indicates that syntactically identical events are "identical", while syntactically distinct, but semantically equivalent, events are not "identical".




Fig. 12.12 Waveform for assertions all and all of module m3

Assertions all and all look similar, but they behave differently. In both, the antecedent of |-> matches whenever the sampled value of a is 1'bl at an occurrence of posedge clkl. Suppose that this occurs at time t_0 . In all, posedge clkl flows to nexttime, and so the nexttime causes advance to the next occurrence of posedge clkl strictly after t_0 before looking for a concurrent or subsequent occurrence of posedge clkl at which to evaluate b. In all, ##1 is a synchronizer between the occurrence of posedge clkl at t_0 and the earliest strictly subsequent occurrence of posedge clk2, where it evaluates b.

This difference is illustrated in the waveform of Fig. 12.12. The solid arrows represent evaluations of a13, while the dashed arrows represent evaluations of a14. The evaluation attempt of a13 beginning at time 20 matches the antecedent of |-> at time 20 and then advances to time 40 because of the nexttime clocked by posedge c1k1. At time 40, the attempt begins looking for the next concurrent or future occurrence of posedge c1k2, which is at time 65. At time 65, the sampled value of b is checked and found to be 1'b1, so the overall evaluation passes. The evaluation of a14 beginning at time 20 behaves differently. After matching the antecedent of |-> at time 20, the synchronizer ##1 causes this evaluation to begin looking for the next strictly future occurrence of posedge c1k2, which is at time 35. At time 35, the evaluation checks b and fails. The evaluation of a13 beginning at time 60 advances to time 80 due to the nexttime. Since posedge c1k2 also occurs at time 80, b is checked at this time, and the evaluation fails. Again, the evaluation of a14 beginning at time 60 behaves differently. This evaluation finds the next strictly future occurrence of posedge c1k2 at time 65, checks b there, and passes.

The structure of al3 ensures that evaluation of nexttime always begins in a time-step in which posedge clkl occurs and therefore is already aligned to the governing (i.e., incoming) clock for nexttime. It is possible to use nexttime as a synchronizer in a way that need not start in a time-step aligned to its governing clock. In such a case, nexttime specifies both of the following temporal actions:¹¹

¹¹ It may seem strange that **nexttime** specifies both alignment and advancement to the next tick. This behavior is aligned with PSL and is needed in order for the behavior of **nexttime** as a synchronizer to converge to the singly clocked behavior of **nexttime** under certain clock convergence scenarios. See Sect. 12.2.5.3 and Exercise 12.5.

- First proceed to the nearest current or future tick of the governing clock (i.e., first *align* with the governing clock).
- From that point, advance to the next tick of the governing clock.

Here is an example illustrating such use of nexttime:

```
module m3_v2 (logic a, b, clk1, clk2);
  a13_v2: assert property(
    @(posedge clk1) a |-> @(posedge clk2) nexttime b
  );
endmodule
```

Figure 12.13 shows a waveform with solid arrows representing the temporal actions of nexttime in the evaluation of al3_v2. Note that all signals are the same as in Fig. 12.12 except for clk2, which no longer has a posedge at time 65. For the evaluation attempt beginning at time 20, alignment with posedge clk2 does not advance time. Advancing to the next tick carries the attempt to time 35, where it fails. For the evaluation attempt beginning at time 60, alignment with posedge clk2 carries the attempt to time 80. For the attempt beginning at time 80, alignment with posedge clk2 does not advance time. For both of these attempts, advancement to the next tick carries the attempt to time 95, where the result is pass. Because posedge clk1 and posedge clk2 both occur at times 20 and 80, these evaluation attempts behave the same as al4.

The operator nexttime[0] specifies only alignment with its governing (i.e., incoming) clock. For any property p, nexttime[0] p is equivalent to 1'b1 |-> p. This operator can be used, e.g., if p may have a leading clock different from the incoming clock and it is desired to ensure that alignment with the incoming clock occurs first. Examples of such usage are given in Sect. 17.1.

Similar considerations apply when other LTL operators are used as synchronizers: time advance specified by the LTL operator is always with respect to the clock governing (i.e., incoming to) the LTL operator, and evaluation of the LTL operator first specifies alignment to that clock in case its evaluation is not guaranteed to begin at such a point. See Exercise 12.4.




Fig. 12.13 Waveform for assertion all v2 of module m3 v2

12.2.5.2 Unclocked Synchronizers and Logical Operators

The synchronizers if-else, case, and the LTL operators must always be within the scope of a clock because the incoming clock determines when the condition of the if-else or case is evaluted and when the time advance of an LTL operator occurs.

The other synchronizers are ##1 and ##0 for sequences and |=>, |->, #=#, #-# for properties. These operators can synchronize between clocks specified by their operands and are not themselves actually required to be within the scope of a clock. In a similar way, the logical operators and, or, iff, and implies can join differently clocked operands and do not themselves require a clock.

The situation of an unclocked synchronizer or logical operator occurs when the synchronizer or operator is the top-level operator of a concurrent assertion in a context where there is no incoming clock. Of course, the concurrent assertion must still have a single semantic leading clock.

The following example illustrates an unclocked synchronizer and an unclocked logical operator in static concurrent assertions within a module with no default clocking:

```
module m4 (logic a, b, c, event ev1, ev2);
    a15: assert property((@(ev1) a) |=> (@(ev2) b));
    a16: assert property((@(ev1) b) or (@(ev1) c));
endmodule
```

Both a15 and a16 have ev1 as semantic leading clock. In a15, the synchronizer |=> is not within the scope of any clock, and in a16 the logical operator or is not within the scope of any clock.

The following example is illegal because an operator that is not a synchronizer remains unclocked:

```
module m5 (logic a, b, event ev1, ev2);
  a17_illegal: assert property(
        (@(ev1) a) |-> ##2 (@(ev2) b)
   );
endmodule
```

The operator ##2 is not a synchronizer and requires a clock to determine how time is advanced, but in this module it is not within the scope of a clock.

12.2.5.3 Continuity Under Clock Convergence

The semantics of multiple clocks has been designed so that it has a quality of *continuity* with respect to convergence of clocks. In other words, as the different clocks coordinated by synchronizers or logical operators become semantically equivalent, the behavior of the multiply clocked sequence or property converges to the behavior of the singly clocked sequence or property obtained by aligning all the clocks to a single clock. As an example of this idea, consider the following:

```
module m6 (logic a, b, event ev1, ev2);
a15: assert property((@(ev1) a) |=> (@(ev2) b));
```

```
a18: assert property(@(ev1) a |=> b);
endmodule
module m7;
  logic A,B;
  event EV;
   ...
  m6 m6_inst(.a(A), .b(B), .ev1(EV), .ev2(EV));
endmodule
```

The instance of m6 within m7 connects the same event EV to both of the ports ev1 and ev2. Therefore, ev1 and ev2 are equivalent in this instance, and so a15 and a18 behave identically.

12.2.5.4 Sequence Methods

SystemVerilog 2009 provides two methods for detecting the endpoint of match of an instance of a named sequence: triggered and matched. triggered is discussed in detail in Sect. 9.2. Both of these methods may be used in multiply clocked sequences and properties, but their behaviors are very different.

Whenever triggered is used in a Boolean expression of a sequence, the clock governing that Boolean expression must be the same as the ending clock of the sequence instance to which triggered is applied. This restriction was illustrated in Example 12.2 from Sect. 12.1.2.

matched can, and should, be used when the ending clock of the instance to which it is applied is *different* than the clock governing the Boolean expression in which matched appears. matched serves as a synchronizer between these two clocks. Upon completion of a match of the underlying instance, this fact is stored until the earliest strictly subsequent time-step in which there is a tick of the clock governing the context in which matched appears. In that time-step, the value of the application of matched to the instance is true.

As an example, suppose that we need to check that if dvalid is true at an occurrence of posedge dclk, then the sequence req ##1 ack must have already completed a match clocked at posedge rclk, but the match must not have completed before the nearest strictly prior occurrence of posedge dclk, if such an occurrence exists. It does not matter when the match starts. This can be encoded using matched as shown in Fig. 12.14. Line 7 illustrates the syntax for applying method matched to an instance of a sequence.

Figure 12.15 shows a waveform for a_matched. There are two matches of the instance s_req_ack (posedge rclk). The first is from times 20 to 40 and causes line 7 to be true at time 55. The second is from times 60 to 80 and causes line 7 to be true at time 105. As a result, the evaluation of a_matched that starts at time 55 succeeds. However, the evaluation of a_matched that starts at time 80 fails. The match of s_req_ack (posedge rclk) completing at time 40 is too early because of the prior posedge dclk at time 55, while the match completing at time 80 is too late because it is not strictly before time 80. The other evaluations of a_matched succeed vacuously.

```
sequence s_req_ack(event ev);
@ (ev) req ##1 ack;
endsequence
a_matched: assert property(
@ (posedge dclk)
dvalid |->
s_req_ack(posedge rclk).matched
);
```

Fig. 12.14 Assertion using matched




Fig. 12.15 Waveform for assertion a matched

12.2.6 Declarations Within a Clocking Block

Sequences and properties may be declared within a clocking block. No explicit clocking event control can be written in such a declaration. Instead, all instances of the named sequence or property are understood to be singly clocked by the clocking event of the clocking block. If a declaration of a sequence or property within a clocking block itself instantiates a sequence or property, then that instance must be singly clocked by a clock that is identical to the clock of the clocking block.

Concurrent assertions cannot be written within a clocking block. Therefore, to instantiate a named sequence or property that is declared within a clocking block, the clocking block must be named and the named sequence or property must be referenced hierarchically.

Here is an example:

```
module decl_in_clocking_block (logic a, b, c, clk);
  clocking PCLK; @(posedge clk);
    property p3; a |=> p4; endproperty
  endclocking
  property p4; b until c; endproperty
  a19: assert property(PCLK.p3);
endmodule
```

Since p4 is declared without clocks, the instance of p4 within the declaration of p3 is legal. The clock of p3 is posedge c1k, which flows into and clocks this instance of p4.

Exercises

- **12.1.** Write an assertion to check that after an occurrence of event ev_start, there is no occurrence of event ev_wait until strictly after an occurrence of event ev enable (cf. Example 12.2).
- **12.2.** Without using the nexttime operator, rewrite assertion al4 from Sect. 12.2.5.1 so that its behavior is identical to that of al3.
- **12.3.** Using the waveform in Fig. 12.12, analyze the behavior of the following assertion:

```
a1: assert property(
    @(posedge clk1) a |=> @(posedge clk2) nexttime b
);
```

12.4. Using the waveform in Fig. 12.12, analyze the behavior of the assertions in the following module for the evaluation attempts beginning at times 20 and 60:

```
module m (logic a, b, clk1, clk2);
   al: assert property(
     @(posedge clk1) a |->
      (@(posedge clk2) a) until (@(posedge clk2) b)
   );
   a2: assert property(
     @(posedge clk1) a |-> @(posedge clk2) a[*] ##1 b
   );
endmodule
```

12.5. Consider the assertion

```
a1: assert property(
    @(posedge clk1) a |-> @(posedge clk2) nexttime b
);
```

Create waveforms in which clk2 converges to clk1 from the right to explain why the synchronizing behavior of **nexttime** must both align and advance to the next tick in order for the multiply clocked semantics to converge to the singly clocked semantics. What happens if clk2 converges to clk1 from the left?

12.6. Analyze the clock flow in each of the following expressions.

```
    @(ev1) a |=> @(ev2) b until c.
    @(ev1) a |=> (@(ev2) b) until c.
    not(@(ev1) a) #-# (@(ev2) b) implies (@(ev3) c).
    @(ev1) (a ##1 @(ev2) b) |=> if (c) @(ev3) d else e.
    @(ev1) sync_accept_on(a) b until @(ev2) c and nexttime @(ev3) d.
```

12.7. Compute the set of semantic leading clocks for each of the following properties.

```
    (@(ev1) a ##1 b[*]) |=> c.
    if (a) @(ev1) p else q.
    @(ev1) if (a) p else q.
    @(ev1) a implies (@(ev2) b) or c.
    (@(ev1) a) implies (@(ev2) b) or c.
    accept_on(a) (@(ev1) b) and strong(c throughout @(ev2) d).
```

12.8. Using rules of clocking, determine for each of the following whether it is legal, illegal, or its legality depends on the existence or nature of an incoming clock. For those in the last category, identify the conditions on an incoming clock to make the expression legal. Assume that a, b, c, etc. are Boolean expressions with no embedded clocking event controls.

```
    @(ev1) a ##1 b[*] |=> c.
    (@(ev1) a ##1 b[*]) |=> c.
    @(ev1) a within @(ev2) b[->1].
    (@(ev1) a) within b[->1].
    assert property(if (a) @(ev1) b else c);.
    assert property(@(ev1) if (a) b else c);.
    assert property(@(ev1) a implies (@(ev2) b) or c);.
```

Chapter 13 Resets

The Metropolis should have been aborted long before it became New York, London or Tokyo.

- John Kenneth Galbraith

As the evaluation of a concurrent assertion evolves over time, certain conditions may occur upon which it is desired to stop the present evaluation attempt in a preemptive or abortive way. The prototypical example is the occurrence of design reset: most concurrent assertions should not continue evaluation across reset of the design. As a result, such preemptive or abortive conditions have come broadly to be termed *reset conditions*. It is cumbersome, at best, to instrument every step of a concurrent assertion with sensitivity to a reset condition. Therefore, SVA provides *reset* constructs with which reset conditions can be declared and their scopes specified.

This chapter covers declaration, scoping, and semantics of reset constructs. SystemVerilog 2009 introduces four new resets, the *abort* property operators, which come in both synchronous and asynchronous, as well as both passing and failing, flavors. These are in addition to the existing asynchronous <code>disable iff</code> construct at the top level of a concurrent assertion.

13.1 Overview of Resets

This section gives an intuitive overview of resets based on examples.

A *reset condition* is a condition upon which it is desired to stop evaluation of a concurrent assertion or subproperty in a preemptive or abortive way. The prototypical example is the occurrence of design reset: most concurrent assertions should not continue evaluation across reset of the design under test. Encoding a concurrent assertion to be sensitive throughout its evaluation to occurrence of a reset condition is cumbersome, so SVA provides various *reset* constructs with which to declare reset conditions and specify their scopes.

A reset is *asynchronous* if the associated reset condition is checked at every time-step during the evaluation of the underlying property. SVA provides three asynchronous resets: disable iff, accept_on, and reject_on. A reset is *synchronous* if the associated reset condition is governed by a clock and checked only

296 13 Resets

in time-steps in which the clocking event occurs. SVA provides two synchronous resets: sync_accept_on and sync_reject_on. Apart from disable iff, all of the resets are new in SystemVerilog 2009 and are referred to collectively as *abort* operators.

13.1.1 Disable Clause

A *disable clause* is specified with the compound keyword disable iff. It defines a top-level asynchronous reset condition that applies throughout the evaluation of a concurrent assertion. The reset condition is called the *disable condition* of the disable clause. With the exception of overriding an incoming default disable condition (see below), all nesting of disable clauses is illegal.

The meaning of a disable clause is that the current (*not* the sampled) value of the disable condition is checked continuously throughout the evaluation of the underlying property of the concurrent assertion. If, at any point prior to completion of that evaluation, the disable condition is or becomes true, then evaluation of the property stops and neither passes nor fails. Instead, the overall result of the evaluation is *disabled*. If the disable condition neither is nor becomes true during the evaluation, then the evaluation either passes or fails according to the result of the evaluation of the underlying property.

Figure 13.1 gives a simple example. A disable clause may be specified either before or after an explicit clocking event control in a concurrent assertion, but it must precede all other terms of the underlying property. In this example, the disable condition is reset. The underlying property appears in line 3 and is singly clocked by posedge clk.

Figure 13.2 shows a possible waveform for a_disable. The attempt that begins at time 20 is disabled by the transition to 1'bl of reset at time 35. In the absence of the disable clause, this attempt would have failed at time 40, but, because it is preempted, no failure occurs and the failing action block in line 4 does not execute. The attempt that begins at time 40 is also disabled. Exactly when it is disabled depends on the behavior of reset at time 40. According to the waveform, the sampled value of reset at time 40 is 1'bl, but a disable condition is evaluated using current values, not sampled values. If the value of reset remains 1'bl until the beginning of the

```
a_disable: assert property(
    disable iff (reset)
    @(posedge clk) a |=> b
4 ) else $display("FAIL");
```

Fig. 13.1 Simple concurrent assertion with a disable clause

13.1 Overview of Resets 297




Fig. 13.2 Waveform for a disable

assertion evaluation attempt at time 40, then that attempt is preempted at time 40.¹ Otherwise, the attempt is disabled by the brief, glitchy transition to 1'b1 of reset at time 55.² Again, because of the preemption, this attempt neither passes nor fails, even though, in the absence of the disable clause, the evaluation of the underlying property would have passed at time 60. The attempts that begin at times 60, 80, and 100 are not disabled. The first fails at time 80, the second passes at time 100, and the third passes vacuously at time 100.

To avoid preemption on glitches in the disable condition, such as the pulse at time 55 in Fig. 13.2, \$sampled can be used to force evaluation using only sampled values. Suppose that line 2 of Fig. 13.1 is changed to

disable iff (\$sampled(reset))

The disable condition is still monitored continuously, but the use of \$sampled means that, in any time-step, only the sampled value of reset is relevant, and this value is persistent throughout the time-step. As a result, the glitch in reset at time 55 is no longer visible to the disable condition. And the behavior at time 40 is more predictable: the sampled value of reset at time 40 is 1'b1, which persists as the sampled value throughout the time-step and preempts the attempt beginning at time 40.

A disable clause may be specified within the declaration of a named property. The disable clause must follow any local variable declarations (see Chap. 16). It may be specified either before or after an explicit clocking event control in the body of the property declaration, but it must precede all other terms of the underlying property. If a named property specifies a disable clause, then instances of the property must

¹ The LRM is not entirely clear on this point, but its language suggests strongly that a disable condition must be true during the evaluation of the underlying property to preempt that evaluation. In particular, preemption does not occur by virtue of the disable condition having been true in a time-step at some point strictly prior to the beginning of an evaluation attempt. Given some degree of ambiguity in the LRM, tools may differ in their implementation of preemption in the time-step that an assertion evaluation begins.

² It is presumed that this impulse is a glitch, although, technically, the graphical representation does not imply this without further information, e.g., concerning the timescale. A waveform tool can identify glitches unambiguously.

298 13 Resets

ensure that, after elaboration,³ the disable clause is at the top level of each concurrent assertion in which it appears, preceded only by local variable declarations and leading clocking event controls. The following variant of the code in Fig. 13.1 behaves equivalently:

```
property p_disable;
disable iff (reset) a |=> b;
endproperty
a_disable: assert property(
    @(posedge clk) p_disable
b) else $display("FAIL");
```

A disable clause may *not* be specified within the declaration of a named sequence.

13.1.1.1 Default Disable Condition

Like a clocking event, a disable condition may be shared by many concurrent assertions. In this situation, it is convenient to be able to specify a *default disable condition*. A default disable condition applies throughout the generate block, module, interface, or program in which it appears, including nested scopes except those with their own default disable condition. The default applies to all concurrent assertions within the scope that do not have disable conditions otherwise specified. It does not apply to declarations of named sequences or properties. The following example illustrates the syntax:

```
module m_default_disable(logic reset, a, b, clk);

default disable iff reset;
a_disable: assert property(
    @(posedge clk) a |=> b
) else $display("FAIL");
a_override: assert property(
    disable iff (1'b0)
    @(posedge clk) reset |=> !reset
);
endmodule
```

The default disable condition, reset, applies to a_disable. Since a_override has an explicit disable condition, the disable condition 1'b0 applies to it and overrides the default.

Nesting of disable conditions is only allowed when the inner disable condition overrides an incoming default disable condition. The overriding by the disable clause in line 7 above is a legal example. Figure 13.3 shows an illegal example. Line 8 results in a nesting of disable conditions, the outer one from the concurrent assertion a_disable in line 7 and the inner one from the instantiated

³ See the Rewriting Algorithms specified in Annex F.4 of the SystemVerilog LRM.

13.1 Overview of Resets 299

```
module m illegal disable nesting(logic reset, a, b, clk);
1
      default clocking PCLK @(posedge clk); endclocking
2
      property p_disable;
3
          disable iff (reset) a |=> b;
5
      endproperty
       a disable: assert property (
6
7
          disable iff (reset)
8
          p disable
          else $display("FAIL");
       )
9
   endmodule
```

Fig. 13.3 Illegal nesting of disable conditions

property p_disable in line 4. The outer disable condition is not a default. Therefore, the nesting is illegal, despite the fact that the two disable conditions are identical.

13.1.2 Aborts

The term *abort* refers to resets specified by the following property operators: accept_on, reject_on, sync_accept_on, and sync_reject_on. The first two of these are *asynchronous* aborts, while the last two are *synchronous* aborts. Each of these property operators has two operands. The first is the *abort condition*, which is enclosed in parentheses, and the second is the underlying property governed by the abort operator. Here is an example of the syntax:

```
a_simple_abort: assert property (
   @(posedge clk)
   start
4   |=>
   accept_on(retry) check_trans_complete
6 );
```

Line 5 specifies an asychronous accept_on with retry as abort condition. The underlying property is the instance check trans complete.

Aborts behave similarly to a disable clause in the way that they preempt evaluation of the underlying property, but there are a number of important differences:

- The scope of an abort condition is limited to its underlying property operand, not the entire concurrent assertion. A thread or subthread of evaluation does not become sensitive to the abort condition until it reaches the associated abort operator.
- Abort conditions are always checked using sampled values. Therefore, unlike a disable condition, an abort condition is not sensitive to glitches.

300 13 Resets

• If the sampled value of an abort condition is 1'b1 in any time-step in which an evaluation is sensitive to it, then the evaluation is aborted. This rule applies even in the same time-step that the underlying property evaluation would complete.

- An abort is a property, so the result of an evaluation is either pass or fail. An
 aborted evaluation results in pass for the "accept" operators and fail for the
 "reject" operators. This result applies only to the abort property itself. If the
 abort property is a subproperty, then this result must be combined with the results
 of other subevaluations in the usual ways to determine the overall result of the
 concurrent assertion evaluation.
- Abort operators may be nested arbitrarily.
- There are no default abort conditions.

13.1.2.1 Asynchronous Aborts

Figure 13.4 shows a simple concurrent assertion with an asynchronous abort. It is similar to the assertion a_disable of Fig. 13.1, but its abort condition is retry. The underlying property is a |=> b, and the entire concurrent assertion is clocked by posedge clk. At each occurrence of this clocking event, evaluation of the abort property begins. This starts monitoring of the abort condition, using sampled values of retry, and also starts evaluation of the underlying property. Because the abort is asynchronous, the sampled value of retry is checked in every time-step, including the first, that the evaluation of the underlying property is ongoing and has neither been aborted nor already completed on its own. If the sampled value of retry is 1'b1 in any of these checks, then the evaluation is aborted and passes in that time-step. If the evaluation is not aborted, then it completes when the underlying property evaluation completes (i.e., at the next occurrence of posedge clk) and the result of the evaluation is the same as that of the underlying property.

Figure 13.5 shows an example waveform for a_accept. It is similar to Fig. 13.2 and will illustrate differences between an asynchronous abort and a disable clause. The evaluation attempt of a_accept that begins at time 20 is aborted in the first time-step after time 35 and passes at that time. The evaluation does not abort at time 35 because sampled value of retry is 1'b0 in that time-step. The sampled value of retry at time 40 is 1'b1, so the attempt beginning at time 40 immediately aborts and passes in that time-step. The glitch on retry at time 60 does not affect

Fig. 13.4 Simple concurrent assertion with an asynchronous abort

13.1 Overview of Resets 301




Fig. 13.5 Waveform for a accept

```
a_accept_reject: assert property(
   @(posedge clk)

accept_on (retry)

a |=> reject_on(bad) b[*2]

b else $display("FAIL");
```

Fig. 13.6 Concurrent assertion with nested asynchronous aborts

any sampled value, so the evaluation beginning at time 60 is not aborted. This evaluation fails at time 80. The evaluation beginning at time 80 is also not aborted and passes at time 100.

Abort operators may be nested. The scope of the outer abort condition includes any nested abort property. The scope of the nested abort condition is limited to the underlying property of that abort operator. While evaluating the inner abort property, the outer abort condition takes precedence over the inner abort condition in case both conditions occur in the same time-step.

Figure 13.6 shows a concurrent assertion with nested asynchronous aborts. The outer abort is an accept_on with abort condition retry whose scope is the entire property of the concurrent assertion. The inner abort is a reject_on with abort condition bad whose scope is the consequent of |=>. The entire assertion is singly clocked by posedge clk. The inner abort does not begin evaluation until after matching the antecedent a and advancing to the next occurrence of posedge clk, as specified by |=>. Only at that point does the evaluation become sensitive to the inner abort condition.

Figure 13.7 shows a waveform for a_accept_reject. The evaluation attempt that begins at time 20 begins executing the outer abort, becomes sensitive to the abort condition retry, and matches the antecedent of |=> at time 20. The evaluation then advances to time 40 and begins executing the inner abort. At that time, it becomes sensitive also to the abort condition bad and tests that the sampled value of b is 1'b1. The evaluation then continues toward time 60 and encounters both retry and bad in the time-step after time 55. In this situation, the outer abort condition takes precedence. Therefore, the evaluation of the outer abort property aborts and

302 13 Resets




Fig. 13.7 Waveform for a accept reject

```
a_sync_accept: assert property(
   @(posedge clk)
   sync_accept_on (retry)
   a |=> b
   ) else $display("FAIL");
```

Fig. 13.8 Concurrent assertion with synchronous aborts

passes in that time-step, and hence the overall evaluation of the concurrent assertion also passes. The evaluation that begins at time 60 starts similarly. The fact that the sampled value of bad is 1'b1 at time 60 is irrelevant because this evaluation is not yet sensitive to the inner abort condition. After matching the antecedent of |=>, the evaluation advances to time 80. The glitch on retry at time 65 is not observable by the abort operator. The evaluation does not abort in the time-step after time 75 because, again, it is not yet sensitive to bad. At time 80, though, the evaluation becomes sensitive to bad. Since the sampled value of bad is 1'b1 at time 80, the evaluation of the inner abort property aborts and fails in that time-step. This causes the consequent of |=> to fail. Therefore, the overall evaluation of the concurrent assertions fails at time 80 and the failing action block executes.

13.1.2.2 Synchronous Aborts

The synchronous abort operators <code>sync_accept_on</code> and <code>sync_reject_on</code> behave the same as their asynchronous counterparts with the exception that their abort conditions are only checked in time-steps in which there is an occurrence of the clocking event.

Figure 13.8 shows a concurrent assertion with a synchronous abort. The assertion behaves like a_accept in Fig. 13.4 except that the abort condition retry is only checked in time-steps in which posedge clk occurs. In the waveform in Fig. 13.5,

13.1 Overview of Resets 303

that begins in time 20 is aborted, but not in the time-step after time 35 as in the case of the asynchronous abort. Instead, the synchronous abort occurs at time 40, where there is an occurrence of <code>posedge clk</code> and the sampled value of <code>retry</code> is 1'bl. This illustrates the fact that if the sampled value of an abort condition is 1'bl in the same time-step that the underlying property evaluation would complete, the abort condition takes precedence and the evaluation is aborted. Since the abort is of the "accept" form, the evaluation of the synchronous abort property passes at time 40, hence there is an overall pass for the concurrent assertion.

Figure 13.9 shows the result of rewriting a_accept_reject from Fig. 13.6 using synchronous aborts. Figure 13.10 shows the same waveform as Fig. 13.7, but with arrows adjusted for the evaluations of a_sync_accept_reject. The pulse on retry beginning at time 55 is not relevant to the synchronous abort because it does not affect the sampled value at a tick of the clock. Therefore, the evaluation beginning at time 20 is aborted at time 60. The clock ticks at this time, and the sampled value of bad is 1'b1. Therefore, the inner abort condition causes failure of the consequent of |=>, hence failure of the overall concurrent assertion, and the failing action block executes. The evaluation that begins at time 60 behaves the same as that of a_accept_reject because both evaluations become sensitive to bad at time 80, which is a tick of the clock at which the sampled value of bad is 1'b1.

```
a_sync_accept_reject: assert property(
  @(posedge clk)
sync_accept_on (retry)
a |=> sync_reject_on(bad) b[*2]
) else $display("FAIL");
```

Fig. 13.9 Concurrent assertion with nested synchronous aborts




Fig. 13.10 Waveform for a sync accept reject

304 13 Resets

13.2 Further Details of Resets

This section covers a few further details of specifying resets.

13.2.1 Generalities of Reset Conditions

The examples of reset conditions so far in this chapter have been simple references to variables or nets. Reset conditions can be general expressions, with the following provisos:

- 1. Reset conditions may not reference assertion local variables.
- A disable condition may reference a sequence instance to which the sequence method triggered is applied. An abort condition may not make such a reference.
- 3. If a reset condition references a sampled value function other than \$sampled, then the clock of the sampled value function must be explicitly specified.
- 4. Reset conditions may not contain instances of sequences to which the sequence method matched is applied.

The rationale for the first rule is that the meaning of such a reference may be unclear at the beginning of evaluation or as subevaluation threads create copies of local variables and assign independent values to them. The second rule reflects the fact that the sampled value of triggered is not useful – it is always 1'b0. The third and fourth rules echo the fact that the asynchronous reset conditions are not governed by a clock.⁴

As an example of a more general reset condition, suppose that design reset is synchronous and occurs only if the sampled value of reset is 1'b1 in a time-step in which posedge clk occurs. If we need to check that dout is equal to last cycle's value of dIn, but only if no reset occurred in either cycle, this can be accomplished by the code in Fig. 13.11 (see also Exercise 13.3).

```
a19: assert property(
@(posedge clk)
sync_accept_on(reset || $past(reset, posedge clk))
dOut == $past(dIn)
);
```

Fig. 13.11 Abort with a compound abort condition

⁴ These rules exist in the SystemVerilog 2009 LRM, although they could be relaxed for synchronous aborts.

```
a_abort_subproperties: assert property(
  @(posedge clk)
  a |=>
  (accept_on (retry) b[*2])
  and
  (reject_on (bad) c |=> !c)
  );
```

Fig. 13.12 Assertion with multiple abort subproperties




Fig. 13.13 Waveform for a_abort_subproperties

13.2.2 Aborts as Subproperties

Since an abort is a property, it participates in the determination of the result of evaluation of an enveloping property in the same way as other subproperties, regardless of whether the disposition of the abort is due to occurrence of the abort condition.

In the assertion of Fig. 13.12, the consequent of \mid => in line 3 is the conjunction of two abort subproperties.

Consider the waveform of Fig. 13.13. The attempt of a_abort_subproperties beginning at time 20 starts subevaluations of lines 4 and 6 at time 40. The occurrence of retry in the time-step after time 45 causes the evaluation of line 4 to pass. The evaluation of line 6 continues, and the occurrence of bad in the time-step after time 55 causes the evaluation of line 6 to fail. The overall assertion therefore fails. The attempt of a_abort_subproperties beginning at time 60 passes.

Exercises

13.1. Explain why assertions at and at below have the same passing and failing evaluation behavior:

```
a1: assert property(@(posedge clk) sync_accept_on(a)
   b[*2] |=> c
);
```

306 13 Resets

```
a2: assert property(@(posedge clk)
   !a throughout b[*2] |=> a || c
);
```

Rewrite the following coverage assertion without using sync reject on:

```
c1: cover property(@(posedge clk) sync_reject_on(a)
   b[*2] ##1 c
);
```

13.2. In the module below, determine for each occurrence of a nested disable condition whether or not the nesting is legal. Also, for each concurrent assertion that is not involved with an illegal nested disable clause, identify the disable condition that governs it, if any.

```
module #(parameter BAD) m (
      logic a, b, c, clk, reset, retry, bad
2
    );
3
4
       default clocking PCLK @(posedge clk); endclocking
       default disable iff reset;
5
       property p; disable iff (retry) b |=> c; endproperty
6
            assert property(a |=> b);
            assert property(disable iff (retry) a |=> b);
            assert property(p);
9
10
       a3:
            assert property(a |=> p);
       generate if (BAD)
11
          begin: GEN BAD
             default disable iff bad;
13
             a0: assert property(a |=> b);
             al: assert property(disable iff (retry) a |=> b);
15
             a2: assert property(p);
16
             a3: assert property(a |=> p);
17
          end
       endgenerate
19
       module m nested;
20
          default disable iff reset && bad;
21
          a0: assert property(a |=> b);
22
               assert property(disable iff (retry) a |=> b);
23
24
          default disable iff retry;
25
          a2: assert property(p);
              assert property(a |=> p);
26
       endmodule
27
    endmodule
```

- **13.3.** Give an alternative encoding of the assertion in Fig. 13.11 that uses a simpler abort condition.
- **13.4.** Explain the meaning of the following properties:

```
1. accept_on(a) reject_on(b) p.
2. reject_on(a) accept_on(b) p.
```

Chapter 14 Procedural Concurrent Assertions

My use of language is part and parcel of my message.

- Theo Van Gogh

A traditional way of writing assertions is to place them and consider them as procedural statements. Various programming languages already provide some syntactic forms to express assertions, either as first class language features or as language extensions [1, 44, 46, 54] by using pragmas or comments. Depending on the objectives of a language, assertions can vary from being simple Boolean checks that ensure the sanctity of variable values to being event or time based for expressing checks over temporality of values. We have already seen the immediate and deferred assertions in Sects. 3.2 and 3.3 of SystemVerilog that are used as procedural statements.

A concurrent assertion used in a procedure is called.

Clearly, concurrent assertions are more complex than immediate or deferred assertions. The influence of clocks and synchronous delays in the assertion evaluation is appreciable. Such evaluations may require more than a single simulation timestep, sometimes open ended with no predetermined time span. Yet, a concurrent assertion attempt behaves in a similar way to a task, that, once started, carries on its execution of statements with no predetermined time span. Another procedural statement that is similar in its behavior is <code>fork..join</code>, which starts executing parallel processes with their individual threads of evaluation and possibly terminating without a coordinated end point between the threads.

In this chapter, we describe how concurrent assertions can be placed in procedural code and how one can make use of the code context in which they are placed. There are many nuances that one needs to be known for proper usage of embedding assertions in procedural code. We discuss a commonly used form for replicating assertions by placing them in a for-loop. We describe in detail the simulation semantics, that is, how procedural assertions are handled in simulation. Finally, we describe the use of the disable statement to terminate the ongoing evaluation of procedural assertions.

14.1 Using Procedural Context

Due to the temporal behavior of concurrent assertions, they are restricted to be placed either in an always procedure or an initial procedure. Contrary to functions and other constructs which must not incur any time delays, these procedures allow evaluations to continue past a single time unit. The always procedure may be of any kind, including always_comb which has an implicit event expression for controlling the execution of the procedure. Concurrent assertions cannot be placed in a function, task, or a class.

```
Concurrent assertions may only be placed in an {\tt always} or {\tt initial} procedure.
```

Let us start with a simple example of placing a concurrent assertion in an always procedure.

Example 14.1. A concurrent assertion in an always procedure

```
module elUnit(input logic clk, ...);
logic i1, i2, i3, i4, d1, dout;
always @(posedge clk) begin
   d1 <= i1 | i2;
   a1: assert property (d1 |=> i3 | i4);
   dout <= f_ecap(d1);
end
//...
endmodule</pre>
```

A new evaluation attempt of assertion al is started each time a clock tick posedge clk occurs. all evaluates to make sure that if dl is true at the beginning, then i3 | i4 must be true one clock cycle later. Each started attempt provides results from its own evaluation, without interfering in the evaluation of other attempts.

Placing an assertion in procedural code greatly improves the understanding of its purpose. The preceding code forms the context and the reasons for its placement. This naturally leads to greater readability and maintainability of the code and the assertion. When it fails, debugging the assertion also improves because the context of the assertion becomes readily available. In the above example, it is clear that assertion al is placed to ensure the correctness of temporal values variables i3 and i4, given a new value of d1. If the temporal values of variables i1 or i4 violate the assertion, an error message is generated to indicate to the user its precise point of failure in the source code. This is immensely useful to the user as the debugging of the failure is made by inspecting the values of the variables d1, i3 and i4 along with its appropriate contextual values of its surrounding quantities i1 and i2.

The context of the assertion is used in the semantics of its execution in two ways. First, the assertion is treated as a statement by the event simulation semantics to start

П

an evaluation at its procedural point of execution. Second, the leading clock of the assertion is derived from the enclosing procedure for subsequent clock cycles. This is illustrated by slightly modifying Example 14.1.

A procedural concurrent assertion derives its clock from the context.

Example 14.2. A concurrent assertion under an enabling condition

```
module elUnit(input logic clk, ...);
logic i1, i2, i3, i4, d1, dout, c1_enb;
always @(posedge clk) begin
   d1 <= i1 | i2;
   if (c1_enb)
      a2: assert property (d1 |=> i3 | i4);
   dout <= f_ecap(d1);
end
//...
endmodule</pre>
```

Assertion a2 gets invoked only if the value of c1_enb is true. The invocation of a2 uses two quantities from its context: its clock and the enabling condition. Note that the clock of a2 is not explicitly specified in the assertion.

In an initial procedure, the execution is initiated at the beginning of simulation, and is carried on until the end of the procedure, without ever returning to the initial point again. During this flow of execution, assertion attempts are spawned as many times the execution reaches an assertion.

An example of embedding a concurrent assertion in an initial procedure is shown in Example 14.3.

Example 14.3. A concurrent assertion in an initial procedure

```
module b1Unit(input bit clk, rst, ....);
bit running;
initial begin: B1
  if (!rst) begin
    a3: assert property (@(posedge clk) running until rst);
    //...
  end
end
//...
endmodule
```

Procedural block B1 is executed at time 0. Suppose that rst is initially low. At that point, assertion a3 is initiated. It waits until the clock tick posedge c1k occurs, and then starts an evaluation attempt. No more new assertion attempts are started, but the initial attempt will continue its evaluation until completed in accordance with the normal assertion semantics.

14.2 Clock Inferencing

When an assertion leading clock is not explicitly specified, this clock is inferred from the assertion context. For concurrent assertions outside procedural code, the clock inference rules have been discussed in Chap. 12. For procedural assertions, the clock is inferred from its preceding event control statement in the procedure, governed by the following rules on the expressions in the event control:

- 1. There is only one event control in the procedure.
- 2. There is no blocking statement in the procedure (e.g., #n, wait).
- 3. The event expression contains an edge operator (posedge, negedge or edge), and optionally a conditional clause iff. Also, such event expression is not a proper subexpression of a larger event expression of this form.
- 4. Any variable in the edge expression is not used anywhere else in the procedure.
- 5. Only one event expression from the event control qualifies using (3) and (4).

If the event expression satisfies the above rules, then the entire event expression is considered as the inferred clock.

Clock inferencing closely follows common design synthesis guidelines.

Example 14.1 illustrates a simple form of edge event expression that is inferred by an assertion as its clock.

Example 14.4. Clock inferencing with iff in the event control

```
always @(posedge clk iff en)
begin
    d1 <= i1 | i2 ;
    a4: assert property (d1 |=> i3 | i4);
    dout <= f_ecap(d1);
end</pre>
```

The entire expression posedge clk iff en is inferred as the clock, not just the subexpression posedge clk.

The following examples illustrate some cases when the rules disqualify event expressions to be inferred as the leading clock of the assertions. In such cases, clocks may be explicitly specified for the assertions. Another alternative is to declare a default clock for the module, which provides the clock for assertions that would otherwise remain unclocked.

Example 14.5. No clock inferencing – an event expression without an edge operator

```
logic clk;
// ...
always @(clk) begin
   d1 <= i1 | i2 ;
   a5: assert property (d1 |=> i3 | i4);
   dout <= f_ecap(d1);
end</pre>
```

The event expression clk does not contain any of the edge operators. Therefore, clk is not the leading clock for assertion a5.

Example 14.6. No clock inferencing – a variable in the event expression used in the procedure

```
always @(posedge (e1 | e2) iff !reset) begin
   d1 <= i1 | i2 ;
   e1N = ~e1;
   a6: assert property (d1 |=> i3 | i4);
   dout <= f_ecap(d1);
end</pre>
```

Because variable e1 is used in the assignment, expression posedge (e1 | e2) is disqualified to become the leading clock for assertion a6. This restriction, however, does not apply to the operand expression of operator iff. Variable reset may be used in the always procedure.

Variables of the iff operand expression may be used freely in the procedural block.

When the event control consists of a list of event expressions, denoted either by a comma or by operator or, then there must be only one event expression from the list that satisfies the primary restrictions explained above. Otherwise, the event control is not considered as the leading clock for the assertions that follow.

Example 14.7. No clock inferencing – two event expressions qualifying as a leading clock

```
always @(posedge e1 or posedge e2) begin
  d1 <= i1 | i2 ;
  a7: assert property (d1 |=> i3 | i4);
  dout <= f_ecap(d1);
end</pre>
```

Only one valid event expression may be specified in the event control for the inferred clock.

In the following example, asynchronous reset is specified as an event expression. In this case, the clock is inferred for assertion a7 since only posedge e1 is valid as the clock for a7. Expression posedge reset is not valid due to the use of signal reset inside the procedure.

Example 14.8. A common use of asynchronous reset event.

```
always @(posedge e1 or posedge reset) begin
  if (reset)
    d1 <= 0;</pre>
```

```
else begin
    d1 <= i1 | i2 ;
    a8: assert property (d1 |=> i3 | i4);
    dout <= f_ecap(d1);
end
end</pre>
```

In addition to the form of the event expression, the following restrictions on the body of the procedure also prevent clock inferencing.

- No other event control appears in the procedure
- No blocking statement appears in the procedure

In the example below, the additional event control statement @(posedge e2) prevents any clock inferencing for assertion a9.

Example 14.9. No clock inferencing – additional event control

```
always @(posedge e1) begin
  d1 <= i1 | i2 ;
  @(posedge e2) egL <= sL & sL1;
  a9: assert property (d1 |=> i3 | i4);
  dout <= f_ecap(d1);
end</pre>
```

Only one timing control may appear in the procedure for clock inferencing.

In the example below, the inclusion of a delay statement #6 bars clock inferencing for assertion alo.

Example 14.10. No clock inferencing – presence of a delay statement

```
always @(posedge e1) begin
    d1 <= i1 | i2 ;
    #6;
    a10: assert property (d1 |=> i3 | i4);
    dout <= f_ecap(d1);
end</pre>
```

Whether a concurrent assertion is placed in an always procedure or an initial procedure, the assertion is invoked, like any other statement, only if the simulation execution reaches the assertion statement. From that moment onward, the temporal assertion evaluation is driven by its leading clock as if the assertion were placed outside its enclosing procedure. If the leading clock is the same as the contextually inferred clock, then the evaluation for that clock tick happens in the same timestep as its invocation. Otherwise, the evaluation waits further until the leading clock occurs. We discuss the precise semantics of scheduling procedural concurrent assertions later in this chapter.

14.3 Using Automatic Variables

An important consideration in constructing a procedural concurrent assertion is the presence of variables declared in the procedure that are part of the simulation execution reaching the assertion statement. Static variables are treated differently than the automatic variables. Even though the values of static variables are in progress during the simulation execution, those variables in the assertion expression use the sampled values, following the same paradigm as all other concurrent assertions. Using sampled values for its variables is essential to obtaining a deterministic result. This is due to the fact that continuing temporal evaluation from one clock tick to the next takes place in its own thread of execution, which is apart from the execution its procedural block.

The value of an automatic variable is sampled at the time when the assertion attempt is started.

The semantics for an automatic variable is, however, varied slightly, as necessitated by the variable lifetime being tied to the existence of the procedure in which they are declared. The lifetime of an assertion attempt, as we know, depends on the temporality of its expression. Therefore, the value of an automatic variable is captured at the time when the assertion attempt is started, and that value is used for the variable throughout that evaluation attempt.

Example 14.11. Use of automatic variables in procedural assertions

```
logic av, r12, r_i, c1_long,;
always @(*) begin
   av = f1(r_i);
   if (c1_long) begin
      automatic logic av1;
      av1 = f2(av++);
      al1: assert property (av |=> s_eventually (r12 || av1));
   end
end
```

Each time all in invoked, the value of variable avl is recorded at that point and used in the expressions (rl2 || avl) for every clock tick until the end of that attempt. Note that all uses sampled values of av and rl2 because they are static variables. This may cause a problem since avl is computed based on nonsampled value of av.

One good option exists for users to decide whether to use the sampled value or the *latched* value of a static variable in assertion expressions. By using const' cast, e.g., const' (v), the value of variable v is latched at the starting of the assertion attempt and used throughout that attempt despite variable v being a static variable. In this way, static variables can be treated as automatic variables in assertion evaluation.

Example 14.12. Use of const' cast for static variables

```
logic av, r_i, c1_long, r12;
always (*) begin
    av = f1(r_i);
    if (c1_long) begin
        automatic logic av1;
        av1 = f2(av++);
        a12: assert property (const'(av) |=> r12 || av1);
    end
end
```

By using const' cast for static variable av, the behavior of assertion all is more consistent with respect to the values of av and av1.

The same rules apply for automatic variables in the action blocks. Namely, automatic variables in action blocks use their latched value at the beginning of the corresponding assertion attempt. Recall that at the time of execution of action blocks values of static variables are taken from the Reactive region, and do not use the sampled values from the Preponed region.

14.4 Assertions in a For-Loop

So far we have seen how clocks and values are applied to procedural assertions. In this section, we show a form in which an assertion is replicated and activated under nested conditions. This form is wellsuited and natural to express a variety of scenarios and is based on dynamic values of the surrounding conditions.

Example 14.13. Replication of assertions using for-loop

```
logic treg;
logic [3:0] dreg;
logic [7:0] tr;
//...
always @(posedge clk) begin
   if (treg) begin
     for (int i = 0; i < 4; i++) begin
        dreg[i] <= tr[i + 1];
        al3: assert property (dreg[i] ##[1:8] tr[i + 1]);
   end
end</pre>
```

Four assertion attempts of al3 are initiated when the for-loop gets executed, each with a different value of index i, from 0 to 3. Following their invocation, the inferred clock (posedge clk) drives each assertion attempt to progress and finish independent of each other. Here, variable i being an automatic variable maintains its value

that it assumed at the time of starting the assertion. Thus, this assertion can be considered as four assertions:

```
always @(posedge clk) begin
  if (treg) begin
    for (int i = 0; i < 4; i++) begin
        dreg[i] <= tr[i + 1];
    end
    a13_1: assert property (dreg[0] ##[1:8] tr[1]);
    a13_2: assert property (dreg[1] ##[1:8] tr[2]);
    a13_3: assert property (dreg[2] ##[1:8] tr[3]);
    a13_4: assert property (dreg[3] ##[1:8] tr[4]);
  end
end</pre>
```

The four assertions a13_1, a13_2, a13_3, and a13_4 are started whenever the condition treg is true for a clock tick of posedge clk. In fact, FV tools split the single assertion into four equivalent assertions as shown here. This technique is well suited for formal verification as it generally does not distinguish between assertion attempts in its determination of assertion failures.

In the following example, the for-loop iterations are controlled by signal count, resulting in a varying number of assertion invocations from clock tick to clock tick. Again, the automatic variable i is not sampled.¹

Example 14.14. A variable for-loop index replicating of assertions

```
always @(posedge clk) begin
  if (treg) begin
    for (int i = 0; i < count; i++) begin
       dreg[i] <= tr[i + 1];
       al4: assert property (dreg[i] ##[1:8] tr[i + 1]);
    end
  end
end</pre>
```

14.5 Event Semantics of Procedural Concurrent Assertions

Before delving into the details of semantics, let us first review event simulation semantics that are important for the execution of procedural concurrent assertions. As we saw in Sect. 2.12, the event semantics of assertion simulation is mostly carried out in three regions: Active region, Observed region, and Reactive region. Although scheduling evaluation, performing evaluation, and detecting events take place in all three regions, each region has a unique role in these activities for assertions. The majority of actual evaluation of assertion expressions takes place in the Observed region, the scheduling is largely performed in the Active region, and the Reactive

¹ FV tools may not be able to handle assertions in procedural loops, which cannot be statically unrolled.

region is used for processing the action blocks. The role of the regions and their order is depicted in Fig. 2.2.

To befit procedural concurrent assertion evaluation within the event simulation semantics, two new semantic objects are introduced: *procedural assertion* queue and *matured assertion* queue.

Procedural assertion queues are used for scheduling assertions in the Observed region. They are mainly temporary holding places until it is determined in the Observed region that those assertions should mature for evaluation. Thereupon, the assertions are transferred to the matured assertion queue to await the arrival of the leading clocks. Each procedure, such as always or initial, that contains procedural concurrent assertions has a procedural assertion queue. But, there is only one matured assertion queue for all procedures, while in the procedural assertion queue, an assertion attempt can get purged as we will illustrate in the examples later.

Note that these semantic objects have no significance in the language or its usage, other than to explain the semantics of the procedural concurrent assertions.

Here are the roles of the two queues for processing an assertion:

- 1. In the Active region, when the statement evaluation reaches a concurrent procedural assertion, the assertion attempt is entered in the procedural assertion queue of the process.
- 2. During the execution in the Active region, an assertion attempt waiting in the procedural assertion queue may get purged.
- 3. In the Observed region, the assertion from the procedural assertion queue is transferred to the matured assertion queue.
- 4. If the leading clock of the assertion did trigger in the Active region, then an assertion attempt begins and the assertion is removed from the matured assertion queue to follow its normal course of evaluation. Otherwise, the assertion awaits in the matured assertion queue until its leading clock triggers in some future time-step.

Each procedure containing a concurrent assertion uses its own procedural assertion queue to enter and purge the assertion attempts.

Figure 14.1 illustrates the role of the two queues.

We will see later how an assertion gets removed from the procedural assertion queue. First, let us follow an example to see how events cause assertion evaluation.

Example 14.15. Events on always triggering assertion evaluation

```
always @(*) begin: B1
    r11 <= v11;
    if (c1_long) begin
        r12 <= v12 & v13;
        a15: assert property (@ (posedge clk) r11 ##2 r12);
    end
end</pre>
```




Fig. 14.1 The Role of queues for procedural assertions

When always procedure block B1 gets triggered because of its implicit events to which B1 is sensitive, the nonblocking assignment to r11 gets scheduled. Next, if c1_long is false, no further action takes place. Otherwise, r12 is scheduled like r11 previously. Assertion a15 is now placed in the procedural assertion queue associated with B1. No other events occur in the Active region, hence the simulation control moves to the Observed region. In the Observed region, a15 is still in the procedural assertion queue, so it moves a15 to the matured assertion queue. If the leading clock (posedge c1k) occurs in the Active region, then an evaluation attempt of a15 is initiated in the current time-step in the Observed region. Otherwise, a15 stays in the matured queue pending a clock (posedge c1k) tick in a future time-step. Once an evaluation attempt matures, it continues its evaluation at every clock tick until it completes, independently of any other attempt that may be initiated.

Now, let us see how an extraneous assertion attempt is blocked from evaluation. Example 14.15 is slightly modified to activate multiple event triggers in a single time-step for block B1.

П

Example 14.16. Multiple event triggers on always consolidating assertion evaluation

```
always @(*) begin: B1
    r11 <= v11 | v12;
    if (c1_long) begin
        r12 <= v12 & v13;
        a16: assert property (@ (posedge clk) r11 ##2 r12);
    end
end</pre>
```

In Example 14.16, if signals v11 and v12 change their values in the same time-step, then block B1 gets evaluated twice, causing two invocations of assertion a16. This causes all assertions currently in the procedural assertion queue for the block to be purged as block B1 is re-entered in the same time-step. Consequently, the first entry of a16 is replaced by the second entry in the queue. Finally, this latest entry of a16 is transferred to the matured assertion queue in the Observed region, and subsequently gets evaluated upon the arrival of a clock (posedge clk) tick. By using the two queues, the effect of zero-width glitches within a single time-step is eliminated by purging all but the latest invocation of the assertions.

Multiple invocations of procedural concurrent assertions are prevented when zero-width glitches cause reexecution.

Furthermore, the semantics also takes care of the situation where multiple invocations are made to an assertion within a for-loop.

Example 14.17. Event semantics for assertions in a for-loop

```
always @(*) begin
   if (c1_long) begin
      for (int i=0; i<4; i++) begin
        dreg[i] <= tr[i+1];
      a17: assert property (@ (posedge clk) dreg[i] ##2 r12);
      end
   end
  end
end</pre>
```

In this example, four instances of assertion al 7 are entered in the procedural assertion queue. As explained earlier, each assertion instance is considered distinct for the purpose of evaluation, and is distinguished from others by the value of the index variable associated with its invocation.

In addition to entering an assertion instance in the procedural assertion queue, corresponding values of const' and automatic variables of the assertion expression are stored for their use when an evaluation attempt eventually takes place from the matured queue. These values also identify the scheduled attempts when multiple evaluations in the same time-step occur. For example, the value of i will be 0, 1, 2, and 3 for the respective assertion instances. As in Example 14.16, multiple evaluation of the for-loop within the same time-step will purge all but the last four assertion instances in the procedural assertion queue.

14.6 Things to Watch Out

There are many subtle situations that arise due to unscrupulous placement of procedural concurrent assertions. One such case is when an assertion is placed after a timing delay statement. In the following example, we can see how an assertion gets evaluated transiently.

Example 14.18. An assertion placed after a delay statement

Consider the time-step in which block B1 starts evaluating. Assertion a18 enters in the procedural assertion queue. The evaluation of the blocking delay statement causes to block further evaluation in the Active region, and to enter the Observed region. Assertion a18 is transferred to the matured assertion queue, pending the arrival of its clock. Due to the blocking effect of the delay statement, multiple invocations of B1 in the same time-step cannot occur since process is suspended.

The behavior of a19 is quite different. After the delay of five units of time, the block restarts its evaluation in the Active region. a19 thus enters the procedural assertion queue. If in the same time-step, there is another invocation of the always procedure due to a change in the value of either v11, v12 or v13, assertion a19 would be purged from the queue. B1 starts to evaluate once again from its first statement until the delay statement, without rescheduling a19 in that time-step.

An event control statement and a wait statement can have a slightly different effect. Although the LRM is not clear in that respect, it would appear that if the wait or event control statement unblocks immediately still in the Active region, then as far as the assertions are concerned, it is as if the blocking statement did not occur.

Example 14.19. An assertion placed after a wait statement

If wait_clk is true when the wait statement is entered and immediately exit, and if the always_comb procedure is triggered again in the same time-step, then the first invocations of both a20 and a21 get purged.

Another peculiar situation transpires when the event control of the always procedure is different than the clock of the assertion, as in the example below.

П

Example 14.20. An assertion with a different clock than its always procedure

```
always @(posedge clk) begin
    i3 <= lb1 && lb8;
    i4 <= lb2 && lb11;
end
always @(posedge el) begin
    d1 <= i1 + i2 ;
    a22: assert property (@(posedge clk) d1 |=> (i3 + i4));
    dout <= f_ecap(d1);
end</pre>
```

The number of evaluations of a22 is entirely dependent on the rate of occurrences of event posedge e1 and the assertion clock (posedge c1k). There is only one instance of a22 scheduled per occurrence of event posedge e1, regardless of the frequency of the assertion clock. This seems reasonable. But, it is substantially different when posedge e1 occurs much more frequently than the assertion clock. In that case, a22 is placed into the matured assertion queue more than once and all those instances get evaluated for the same occurrence of the assertion clock.

When a clock is inferred and is also explicitly specified for a procedural concurrent assertion, the number of evaluation attempts depends on the relative frequencies of the two clocks.

We have seen how the procedural assertion evaluation framework filters out superfluous assertion evaluations due to the transient value changes in signals in the Active region. This glitch protection is lost if the signal changes in the Reactive region rather than the Active region. One such case is shown below.

Example 14.21. An assertion trigger due to a change in Reactive region

```
program prg();
     integer i;
2
3
     initial
        for (i=0; i< 8; i++) begin</pre>
4
         mod.v11= 1; #5;
5
          mod.v11 = 0;
6
       end
7
   endprogram
8
9
   module mod(input sig2,clk);
10
     bit v11,r11,r12;
11
     wire v12;
12
     assign v12 = sig2;
13
     always @(posedge v11 or posedge v12) begin: B1
14
       r11 = v11 | v12;
15
       a23: assert property (@(posedge clk) v11 ##1 v12);
16
       r12 = v11 \& v12;
17
     end
18
   endmodule
19
```

П

In Example 14.21, when the event (posedge v12) occurs due to the assign statement in line 13, block B1 is evaluated. As expected, assertion a23 is entered in the procedural assertion queue, with a transfer to the matured assertion queue in the Observed region, assuming there were no more changes. Now, in the Reactive region, when variable v11 is assigned, it causes the initiation of the Active region once again, retriggering block B1, followed by another entry of assertion a23 in the procedural assertion queue. Finally, that assertion evaluation is also transferred to the matured queue when the Observed region is entered for the second time. At that point, there are now two instances of a23 in the mature assertion queue that await their clock tick.

14.7 Dealing with Unwanted Procedural Assertion Evaluations

As we learnt from Example 14.21, there are some situations where redundant evaluations of assertions occur. The user is provided with an explicit means to stop such cases. The procedural assertion queue can be purged entirely or for a specific assertion with the disable statement. But, the evaluation attempts already advanced to the matured queue or the ongoing attempts that were started in previous time-steps are not affected.

In Example 14.21, we can add a disable statement for the assertion such as shown below to prevent the extra evaluation of a23.

Example 14.22. A disable statement purging an assertion evaluation

```
program prq();
  integer i;
  initial
    for (i=0; i< 8; i++) begin
      mod.v11 = 1;
      #5;
      mod.v11 = 0;
    end
endprogram
module mod(input bit sig2,clk);
  bit v11, r11, r12;
  wire v12;
  assign v12 = siq2;
  always @(posedge v11 or posedge v12) begin: B1
     r11 = v11 | v12;
     a24: assert property (@(posedge clk) v11 ##1 v12);
     r12 = v11 \& v12;
     if (v11==0) disable a24;
  end
endmodule
```

The entry of assertion a24 is removed by the disable statement under the condition that block B1 was retriggered by variable v12.

Evaluation attempts from the matured queue or ongoing from previous timesteps are not affected by the disable statement.

In some cases, purging of all assertions for a block may be appropriate.

Example 14.23. A disable statement purging all assertion evaluations in a block

```
always @(*) begin: B2
  if (c1_long) begin
    for (int i=0; i<4; i++) begin
       dreg[i] = tr[i+1];
       treg = flogic (dreg[i]);
       a25: assert property (@ (posedge clk) dreg[i] ##2 r12);
    end
  end
end
always @(*)
  if (c1 long && treg) disable B2;</pre>
```

In Example 14.23, expression (c1_long && treg) is known to be outside the bounds of checks in assertion a25. As such, all instances of assertion a25 are eliminated for evaluation in that time-step. For all other cases, assertions are evaluated normally.

To conclude this chapter, we mention that in formal verification, the procedural assertions are extracted from the procedures as shown in Example 14.13, including the enabling conditions, and evaluated as regular concurrent assertions. For details on formal verification, see Chap. 11.

Chapter 15 An Apology for Local Variables

Local color has a fatal tendency to remain local; but it is also true that the universal often borders on the void.

- DuBose Heyward and Hervey Allen

Local variables are a powerful feature of SystemVerilog Assertions that enable an assertion to capture the value of an expression at a specified point in its evaluation and store that value for later reference, perhaps after further modification. This feature makes the encoding of many assertions much easier and helps to eliminate the need for auxiliary state machines to support assertions. Local variables are also a feature that distinguishes SVA from PSL.¹

A local variable must be declared within the declaration of a named sequence or property, and the scope of a local variable does not extend outside the sequence or property in which it is declared. Local variables are, therefore, not a first-class construct of SVA. Each evaluation attempt of a named sequence or property has its own copies of the local variables declared within it. In this sense, local variables are "local" to these individual evaluation attempts.

This chapter gives an intuitive introduction to local variables based on examples. For each example, an alternative encoding is shown that does not use local variables. By comparing the encodings, the reader should gain an appreciation for the semantics and, in most cases, the benefits of local variables. Throughout this chapter, we assume that all assertions are clocked at posedge clk and that there is a default clocking specification.

15.1 Fixed Latency Data Pipeline

To get started, suppose that there is a fixed latency data pipeline whose data checking requirement is specified by the following English:

- 1. start is a signal of type logic. dataIn and dataOut are signals of type dataType.
- 2. LATENCY is a positive integer parameter.

¹ There has been discussion of adding local variables to PSL, but this had not yet been done in [6].

- 3. Whenever start is high, dataIn is valid.
- 4. The value of dataIn when start is high must equal the value of dataOut LATENCY cycles later.

The specification can be encoded without using local variables as shown in Fig. 15.1.

By using <code>\$past(dataIn, LATENCY)</code>, one should expect performance in simulation and formal verification to be similar to that of encoding a cascade of LATENCY delay variables of type <code>dataType</code>. If LATENCY equals three, then the cascade of delay variables is

```
dataType dataIn_D1, dataIn_D2, dataIn_D3;
always @(posedge clk) begin
  dataIn_D1 <= $sampled(dataIn);
  dataIn_D2 <= dataIn_D1;
  dataIn_D3 <= dataIn_D2;
end</pre>
```

and the reference to \$past(dataIn,LATENCY) is like a reference to dataIn_D3 (see also the discussion of \$past in Sect. 11.2.3.1).

Using a local variable, the pipeline data check can be encoded as shown in Fig. 15.2. The local variable data of type dataType is declared on line 2 within the declaration of property p_pipeline_data_check. Local variable declarations follow the same format as other variable declarations in SystemVerilog. Line 3 is an example of attaching a local variable assignment to a Boolean expression. The Boolean start is separated from the local variable assignment data = dataIn by a comma, and the two are enclosed in parentheses. (start, data = dataIn) is a sequence (not a Boolean) with the following meaning:

- The value of start is tested when evaluation of the sequence begins.
- If the value of start is high, then the value of dataIn is assigned to the local variable data and the sequence matches at that point.

```
a_pipeline_data_check: assert property(
    start
    |->
    ##LATENCY dataOut == $past(dataIn, LATENCY)
    );
```

Fig. 15.1 Encoding of pipeline data check without local variables

```
property p_pipeline_data_check;
dataType data;
(start, data = dataIn)
| ->
##LATENCY dataOut == data;
endproperty
a_pipeline_data_check: assert property(p_pipeline_data_check);
```

Fig. 15.2 Encoding of pipeline data check with a local variable

 Otherwise, the sequence fails to match and no assignment to the local variable data occurs.

If start is high when evaluation of p_pipeline_data_check begins, then the value of dataIn is assigned to data and the antecedent of the implication |-> in line 4 matches. Therefore, the consequent specified in line 5 must match. Line 5 says that LATENCY cycles should be advanced and then the value of dataOut must equal the value stored in the local variable data. In summary, when start is high, the value of dataIn is captured in the local variable data, and this value is compared LATENCY cycles later to the value of dataOut.

From a data storage perspective, the simulation performance of the encoding with the local variable should never be worse than that of the encoding using \$past. This is because at most LATENCY threads of evaluation of p_data_pipeline_LATENCY can be active simultaneously, each with its own copy of the local variable data. The storage needed for the local variable encoding varies in direct proportion to the frequency of occurrences of start, while the storage needed for the encoding using \$past is fixed by the parameter LATENCY.²

15.2 Sequential Protocol

Now let us switch from a fixed latency pipeline to a protocol that is *sequential* in the sense that its transactions do not overlap. In this protocol, there is not a constant latency from dataIn to dataOut. Instead, a Boolean signal complete determines when dataOut is valid. Here is the English description:

- 1. start and complete are signals of type logic. dataIn and dataOut are signals of type dataType.
- 2. Whenever start is high, dataIn is valid. Whenever complete is high, dataOut is valid.
- 3. If start is high, then the value of dataIn at that time must equal the value of dataOut at the next strictly subsequent cycle in which complete is high.
- 4. If start is high, then start must be low in the next cycle and remain low until after the next strictly subsequent cycle in which complete is high.
- 5. complete may not be high unless start was high in a preceding cycle and complete was not high in any of the intervening cycles.

The last two English rules specify that the protocol is sequential. Let us say that a Boolean *occurs* if it is high. Then these rules say that a second start cannot occur until after the complete for the first start occurs, and an occurrence of complete corresponds to the nearest preceding occurrence of start. A transaction

² In formal verification, a nondeterministic representation of the encoding with the local variable is even more efficient, comparable to a nondeterministic representation of an encoding using a rigid checker variable (see Example 22.28).

```
a no start: assert property (
1
       start |=> !start throughout complete[->1]
2
3
    );
    a no complete: assert property (
4
       complete |=> !complete throughout start[->1]
5
6
    initial
7
       a initial no complete: assert property (
8
          !complete throughout start[->1]
9
10
```

Fig. 15.3 Encoding of control part of sequential protocol

spans the set of cycles from an occurrence of start to its corresponding occurrence of complete, and two transactions do not overlap.

Note that this specification decomposes into a control part, which ensures the sequential pairing of occurrences of start and complete, and a data part, which checks the data correspondence between dataIn and dataOut for each such pair. The control part of the specification does not involve data or local variables and can be encoded as shown in Fig. 15.3.

Assertion a_no_start checks rule 4. Rule 5 is checked by a_no_complete and a_initial_no_complete. The first two assertions are symmetric in start and complete, while the last is not. Since the last assertion is within an initial procedure, only one evaluation attempt of a_initial_no_complete is begun at the first occurrence of the clocking event. That evaluation checks that there is no occurrence of complete until after the first occurrence of start.

Now let us move to the data part of the specification and begin without using local variables. Since the latency from an occurrence of start to the next subsequent occurrence of complete is not fixed, \$past will not work. The value of dataIn at an occurrence of start needs to be stored somewhere, though, since otherwise it is lost and the comparison with dataOut cannot be made. Since the protocol is sequential, one auxiliary storage variable can be used to hold the value of dataIn from the nearest preceding occurrence of start. Figure 15.4 shows such an encoding.³

Using local variables, we can follow the same data capture idiom from the pipeline data check. The encoding is shown in Fig. 15.5. Note the similarity between lines 6 and 7 from Fig. 15.4 and lines 3 and 4 from Fig. 15.5. The encoding with local variables avoids the auxiliary modeling code to define how last_dataIn is updated, and it makes clear the timing of the data capture because the local variable assignment data = dataIn is attached to the Boolean start.

³ The use of \$sampled specifies that sampled values of start and dataIn are used in the **always** procedure, maintaining consistency with the implicit use of sampled values in a seq data check.

15.3 FIFO Protocol 327

```
dataType last dataIn;
1
2
   always @(posedge clk)
       if ($sampled(start))
3
          last dataIn <= $sampled(dataIn);</pre>
4
   a seq data check: assert property (
5
       start ##1 complete[->1]
6
       |-> dataOut == last dataIn
7
8
   );
```

Fig. 15.4 Encoding of sequential protocol data check without local variables

```
property p_seq_data_check;
dataType data;
(start, data = dataIn) ##1 complete[->1]
|-> dataOut == data;
endproperty
a_seq_data_check: assert property(p_seq_data_check);
```

Fig. 15.5 Encoding of sequential protocol data check with a local variable

15.3 FIFO Protocol

Next, let us generalize the sequential protocol to a FIFO (i.e., in-order) protocol by allowing multiple occurrences of start prior to the next occurrence of complete and multiple occurrences of complete before the next occurrence of start. The occurrences of start and complete pair up by order, so that for each $n \geq 1$, the nth occurrence of start pairs with the nth occurrence of complete. Here are the English rules:

- start and complete are signals of type logic. dataIn and dataOut are signals
 of type dataType.
- 2. Whenever start is high, dataIn is valid. Whenever complete is high, dataOut is valid.
- 3. MAX OUTSTANDING is a positive integer parameter.
- 4. start may be high if and only if complete is not high and the number of preceding occurrences of start minus the number of preceding occurrences of complete is less than MAX OUTSTANDING.
- 5. complete may be high if and only if start is not high and the number of preceding occurrences of start minus the number of preceding occurrences of complete is positive.
- 6. For all $n \ge 1$, at the *n*th occurrence of complete, the value of dataOut must equal the value of dataIn at the *n*th occurrence of start.

As with the sequential protocol, this specification decomposes into a control part, governing the signals start and complete, and a data part. The control part of the specification must keep track of the difference between the number of preceding occurrences of start and the number of preceding occurrences of complete.

Let us call this difference the *number of outstanding transactions*. One way to keep track of this number is to encode an auxiliary variable to store it. Figure 15.6 shows how this can be done.

Line 1 references the \$clog2 system function, which returns the ceiling of the base-2 logarithm of its argument. This declaration ensures that outstanding has enough bits to store the number MAX_OUTSTANDING (see Exercise 15.3). (Question: Why is it important that outstanding be able to store MAX_OUTSTANDING?) The always procedure updates outstanding, incrementing it whenever start occurs and decrementing it whenever complete occurs. Of course, if start or complete does not obey the control part of the specification, then outstanding may overflow or underflow.

Using outstanding, the control part of the FIFO protocol specification can be encoded as shown in Fig. 15.7. Without using local variables, the various values of dataIn for the outstanding transactions need to be stored in some data structure. A bounded queue of maximum size MAX_OUTSTANDING is a good choice because of the in-order pairing of corresponding occurrences of start and complete. Figure 15.8 shows the declaration and management of such a queue, as well as the simple data check assertion that references it.

```
bit [0:$clog2(MAX_OUTSTANDING)] outstanding;
initial
outstanding <= '0;
always @(posedge clk)
outstanding <= outstanding + $sampled(start - complete);</pre>
```

Fig. 15.6 Encoding of the number of outstanding transactions

```
a_start_valid: assert property (
    start | -> !complete && outstanding < MAX_OUTSTANDING
);
a_complete_valid: assert property (
    complete | -> !start && outstanding > 0
6 );
```

Fig. 15.7 Encoding of control part of FIFO protocol

```
dataType dataQ[$:MAX OUTSTANDING-1] = {};
1
   always @(posedge clk)
2
3
       if ($sampled(start))
          dataQ.push back($sampled(dataIn));
4
       else if ($sampled(complete))
5
          dataQ.pop front;
6
   a fifo data check: assert property (
7
      complete |-> dataOut == dataQ[0]
8
```

Fig. 15.8 Encoding of FIFO protocol data check without using local variables

15.3 FIFO Protocol 329

Note the use of the built-in queue methods <code>push_back</code> in line 4 and <code>pop_front</code> in line 6. Because of this update policy, the data needed for comparison with <code>dataOut</code> at the next occurrence of <code>complete</code> is always in <code>dataQ[0]</code>, which is referenced in the assertion in line 8. The execution of <code>pop_front</code> in line 6 does not lose the data needed for the comparison in line 8 because the reference to <code>dataQ[0]</code> within the assertion is to the sampled value, which is not affected by the execution of the queue method in the same time-step.

Using local variables, the same data capture idiom we have seen for the pipeline and sequential protocol examples continues to work. The challenge is to determine when the corresponding complete occurs. To accomplish this, we capture not only dataIn when start occurs, but also the value of outstanding. The value of outstanding determines how many occurrences of complete must be skipped before arriving at the occurrence of complete at which the data comparison should be performed. As occurrences of complete are observed, they are accounted for so that the assertion detects when the corresponding complete occurs. An encoding following this approach is shown in Fig. 15.9.4

Property p_fifo_data_check has two local variables, data declared in line 2 and numAhead declared in line 3. The type of numAhead is the same as that of outstanding. In general, any number of local variables may be declared within the declaration of a named sequence or property. In line 4, two local variable assignments are attached to the Boolean start. The first stores the value of dataIn in the local variable data, just as we have seen before. The second stores the value of outstanding in the local variable numAhead. If multiple local variable assignments need to be performed on successful test of a Boolean, then the assignments are simply separated by commas and are performed in the order in which they are written. When line 4 completes, numAhead holds the number of occurrences of complete that need to be skipped before arriving at the occurrence of complete at which the data check will be performed. Lines 5 and 6 cause the evaluation to advance to the cycle of the data check and are discussed in detail below. Finally, line 8 performs the simple data comparison.

```
property p_fifo_data_check;
1
      dataType data;
2
3
      bit [0:$clog2(MAX OUTSTANDING)] numAhead;
       (start, data = dataIn, numAhead = outstanding)
4
       ##1 (numAhead > 0 ##0 complete[->1], numAhead--)[*]
5
       ##1 (numAhead == 0 ##0 complete[->1])
6
7
      dataOut == data;
8
9
   endproperty
                        assert property (p fifo data check);
   a fifo data check:
```

Fig. 15.9 Encoding of FIFO protocol data check using local variables

⁴ Since the overall check involves the code from both Figs. 15.6 and 15.9, it is natural to put all of this code into a checker. See Exercise 21.6.

Line 5 does the job of advancing the evaluation through the occurrences of complete that need to be skipped. This line deserves careful study. It begins with ##1, which simply advances to the cycle after the occurrence of start. The rest of the line is a repetition of zero or more occurrences of the sequence

```
(numAhead > 0 ##0 complete[->1], numAhead--)
```

Let us call this sequence the *skipping sequence*. The top level structure of the skipping sequence attaches the local variable assignment numAhead-- to the subsequence

```
numAhead > 0 ##0 complete[->1]
```

In general, local variable assignments may be attached to any sequence that does not admit an empty match. The assignment numAhead - uses the decrement operator -- and behaves the same as numAhead = numAhead - 1. The subsequence to which it is attached begins with the Boolean condition numAhead > 0, which is true if and only if there remain occurrences of complete that need to be skipped. This Boolean is fused via ##0 to the sequence complete[->1], which advances to the next occurrence of complete. Each match of the skipping sequence in the repetition therefore behaves as follows:

- Confirm that numAhead > 0, hence that there remains at least one occurrence of complete that needs to be skipped.
- Advance to the next occurrence of complete by matching complete [->1].
- Decrement numAhead.

Because numAhead is decremented for each match in the repetition, the skipping sequence is matched at most a number of times equal to the value that was stored in numAhead in line 4. In fact, as explained below, line 6 forces the skipping sequence to be matched exactly this number of times. It is possible that this number is zero, meaning that no occurrences of complete need to be skipped. In this case, no matches of the skipping sequence are possible, and the zero repetition case is used to match line 5.

Line 6 does two jobs. The first is to prevent the repetition of line 5 from stopping early. This is done by enforcing the Boolean condition numAhead == 0. If the evaluation tries to proceed from line 5 to line 6 when numAhead > 0, then the Boolean numAhead == 0 will be false and the evaluation must revert to line 5 to attempt another repetition of the skipping sequence. The second job of line 6 is to advance to the next occurrence of complete by matching complete [->1]. This occurrence is the one that corresponds to the occurrence of start in line 4 and at which the data check should be performed.

As an intuitive summary, the matching of lines 5 and 6 accomplishes the following:

- While numAhead is positive, advance to the next occurrence of complete and decrement numAhead.
- When numAhead becomes zero, advance to the next occurrence of complete and stop.

15.4 Tag Protocol 331

Managing a local variable counter such as numAhead within a repetition as shown in this example may seem daunting at first. After fully understanding a few such patterns, the reader will acquire the skill and confidence to put them into practice.

Exercise 15.6 explores the storage requirements of the encodings of the FIFO protocol data check with and without local variables.

15.4 Tag Protocol

In this section, we switch from an in-order protocol to an out-of-order protocol in which two occurrences of complete do not have to be in the same order as the corresponding occurrences start. Additional data are needed to determine which occurrence of complete corresponds to a given occurrence of start. This protocol uses a tag to do the matching. The signal tagIn is valid with an occurrence of start and determines the tag of the transaction. The tag is active for that transaction while the transaction is outstanding. The signal tagOut is valid with an occurrence of complete, and matching of the values of tagIn and tagOut is used to define the correspondence. While a tag is active for a transaction, it must not be reused by another transaction. Here are the English rules:

- 1. start and complete are signals of type logic. dataIn and dataOut are signals of type dataType. tagIn and tagOut are signals of type tagType.
- 2. Whenever start is high, dataIn and tagIn are valid. Whenever complete is high, dataOut and tagOut are valid.
- 3. In each cycle, each tag value is either active or inactive, according to the following rules:
 - Every tag value begins inactive.
 - If there is no occurrence of start or complete in a cycle, then no tag value changes state in the next cycle.
 - A tag value becomes active the cycle after an occurrence of start at which tagIn held that value.
 - A tag value becomes inactive the cycle after an occurrence of complete at which tagout held that value.
- 4. start may be high if and only if complete is not high and the value of tagIn is inactive in that cycle.
- 5. complete may be high if and only if start is not high and the value of tagout is active in that cycle.
- 6. An occurrence of start corresponds to an occurrence of complete if and only if the following conditions are all satisfied:
 - The occurrence of start is strictly before the occurrence of complete.
 - The value of tagIn at the occurrence of start equals the value of tagOut at the occurrence of complete.
 - There is no earlier occurrence of complete satisfying both of the two preceding conditions.

```
bit active[tagType];
1
    always @(posedge clk)
2
       if ($sampled(start)) begin
3
          a no tag reuse: assert #0 (
4
              !active.exists($sampled(tagIn))
5
6
          active[$sampled(tagIn)] <= 1'b1;</pre>
7
       end
8
       else if ($sampled(complete)) begin
9
          a_comp_tag_ok:
                           assert #0 (
10
              active.exists($sampled(tagOut))
11
12
          active.delete($sampled(tagOut));
13
14
```

Fig. 15.10 Encoding of tag protocol control check

7. If an occurrence of start corresponds to an occurrence of complete, then the value of dataIn at that occurrence of start equals the value of dataOut at that occurrence of complete.

The control part of the tag protocol specification is more complicated than in our previous examples. As for the FIFO protocol, auxiliary variables can help in encoding the control part of the specification. In the tag protocol, we need to keep track of which tags are active. An associative array of bits can be used to do this as shown in Fig. 15.10. This encoding uses deferred assertions to perform the control checks specified in rules 4 and 5. Note that the value associated to a tag in the associative array active is not important, only whether or not the tag exists in the array.

Without using local variables, a similar associative array can be used to store the data values for the active tags. This array keeps track of which tags are active and their associated data, so the active array is no longer needed in this approach. Another deferred assertion can perform the data check specified in rule 7. Such an encoding is shown in Fig. 15.11.

The data check can be encoded using local variables in a style similar to that of the FIFO data check with local variables, as shown in Fig. 15.12. At start, the property captures the values of both tagIn and dataIn in the local variables tag and data. The property then advances to the nearest occurrence of complete at which tagOut equals the value stored in tag, and at that point compares dataOut to the value stored in data. This encoding still relies on the deferred assertions in Fig. 15.10 to perform the control checks.

Associative arrays are convenient for encoding the checks of the tag protocol, but because of their dynamic and unbounded nature, they will typically not be supported in formal verification tools. To provide an encoding for formal verification, the auxiliary variables should be declared in a way that is explicitly bounded. If the number of tag values is not too large, then the active associative array can be recoded as a

15.4 Tag Protocol 333

```
dataType data[tagType];
1
    always @(posedge clk)
2
       if ($sampled(start)) begin
3
          a no tag reuse:
                            assert #0 (
4
              !data.exists($sampled(tagIn))
5
6
          data[$sampled(tagIn)] <= $sampled(dataIn);</pre>
7
       end
8
9
       else if ($sampled(complete)) begin
                            assert #0 (data.exists($sampled(tagOut)));
          a_comp_tag_ok:
10
          a data check: assert #0(
11
              $sampled(dataOut) == data[$sampled(tagOut)]
12
13
          data.delete($sampled(tagOut));
14
15
       end
```

Fig. 15.11 Encoding of tag protocol control and data check

```
property p_tag_data_check;
tagType tag;
dataType data;
(start, tag = tagIn, data = dataIn)
##1 (complete && tagOut == tag)[->1]
|-> dataOut == data;
endproperty
a_tag_data_check: assert property (p_tag_data_check);
```

Fig. 15.12 Encoding of tag protocol data check using local variables

```
bit active[0:MAX TAG];
1
2
    initial
       active <= '0;
3
    always @(posedge clk)
4
       if ($sampled(start))
5
          active[$sampled(taqIn)] <= 1'b1;</pre>
6
       else if ($sampled(complete))
7
          active[$sampled(tagOut)] <= 1'b0;</pre>
8
    a no tag reuse: assert property (start |-> !active[tagIn]);
    a comp tag ok:
                     assert property (complete |-> active[tagIn]);
10
```

Fig. 15.13 Encoding of tag protocol control check without associative arrays

bounded array. For simplicity, suppose that the tag values range from 0 to MAX_TAG. Then the array of active bits can be encoded as shown in Fig. 15.13, which also encodes the control checks using concurrent assertions that are supported by formal verification tools. The code of this figure, together with that of the data check using local variables shown in Fig. 15.12, gives a complete encoding of the tag protocol checks suitable for formal verification tools. This code could be collected naturally into a checker (cf. Exercise 21.7).

If the number of tag values times the number of bits needed to store a data value is also not too large, then a similar bounded array of elements of type dataType can be used to store the data of the active transactions, replacing the associative array of Fig. 15.11.

In practice, it may be that the number of tag values or the product of the number of tag values times the number of bits needed to store a data value will be too large for static allocation and formal verification. If the number of active transactions can be bounded by a number significantly smaller than the number of tags, then smaller arrays that store the tag and data values for each active transaction can be encoded. Such arrays are essentially RTL implementations of bounded associative arrays.

Suppose that the positive integer parameter MAX_ACTIVE is an upper bound for the number of active transactions. Figure 15.14 shows an encoding of the tag protocol control checks using two arrays of size MAX_ACTIVE. The first array, valid, is

```
bit valid[0:MAX ACTIVE-1];
1
2
    tagType activeTag[0:MAX ACTIVE-1];
    initial
3
       valid <= '0;
4
    typedef bit[0:$clog2(MAX ACTIVE)] indexType;
5
    function indexType freeIndex;
6
       for (indexType i=0; i < MAX ACTIVE; i++)</pre>
7
           if (!valid[i])
8
              return i;
9
       return MAX ACTIVE; // no free index
10
    endfunction
11
    function indexType tagIndex (tagType tag);
12
       for (indexType i=0; i < MAX ACTIVE; i++)</pre>
13
14
           if (valid[i])
              if (activeTag[i] == tag)
15
                  return i;
16
       return MAX ACTIVE; // tag not found
17
18
    endfunction
    always @(posedge clk)
19
20
        if ($sampled(start)) begin
           valid[freeIndex] <= 1'b1;</pre>
21
           activeTag[freeIndex] <= $sampled(tagIn);</pre>
22
       end
23
       else if ($sampled(complete))
24
           if (tagIndex($sampled(tagOut)) < MAX ACTIVE)</pre>
25
26
              valid[tagIndex($sampled(tagOut))] <= 1'b0;</pre>
    a_no_tag_reuse: assert property (
2.7
       start
28
        |-> tagIndex(tagIn) == MAX ACTIVE // tagIn not found
29
30
    a comp tag ok:
                     assert property (
31
       complete
32
        |-> tagIndex(tagOut) < MAX ACTIVE // tagOut found
33
    );
34
```

Fig. 15.14 Encoding of tag protocol control check with bound on number of active transactions

of bits and keeps track of which indexes are currently in use storing tags of active transactions. The second array, activeTag, stores the tags of the active transactions. Line 5 defines indexType, which can store values from 0 through MAX_ACTIVE (cf. Exercise 15.3). The auxiliary function freeIndex returns the smallest index that is not currently storing a tag, if there is one. Otherwise, it returns MAX_ACTIVE. The auxiliary function tagIndex returns the smallest index that is currently storing a tag and whose entry in the activeTag array is equal to the function's argument tag. If the tag protocol control checks are satisfied, then there will be at most one such index. If there is no such index, then the function returns MAX_ACTIVE.

A similar array can be encoded to store the data values for the active transactions and used to encode the tag protocol data check in a way that is suitable for formal verification. See Exercise 15.9. The complexity of the data management in such arrays is striking in comparison with the simplicity of the data check using local variables.

15.5 FIFO Protocol Revisited

This section shows an alternative encoding of the FIFO protocol control and data checks that uses only local variables.

The encoding with local variables from Sect. 15.3 makes use of only one nonlocal variable, namely, outstanding as defined in Fig. 15.6. Thus, the present encoding needs to keep track of the number of outstanding transactions internally by using local variables. This encoding is shown in Fig. 15.15.

The style of this encoding is somewhat more complicated than those shown in Sect. 15.3, although each of its parts corresponds to a part of the encoding using local variables that appears in that section. This encoding uses a typedef on line 1 to provide the type counterType that simplifies the declarations on lines 2 and 10. The top-level property p_fifo_all_checks is responsible for accounting for the number of outstanding transactions, performing the control checks, and calling property p_fifo_data_check to perform the data check. The accounting of the number of transactions is done in the repetition in lines 11–15, and this approach, which will be explained in more detail below, assumes that there is only one evaluation attempt of p_fifo_all_checks running. For this reason, the assertion a_fifo_all_checks beginning on line 25 appears in an initial procedure. See Exercise 15.7.

The data checking property p_fifo_data_check is very similar to the property of the same name from Sect. 15.3, so we focus on the differences. In line 2, numAhead is declared as a formal argument. The keywords local input in this declaration specify that the formal argument numAhead is in fact a local variable that will receive an initial value from its actual argument. p_fifo_all_checks computes the value of outstanding in line 13 and passes it in to numAhead through the instantiation in line 19. In all other respects, numAhead behaves the same here

⁵ Local variable formal arguments are new in the SystemVerilog 2009 standard.

```
typedef bit [0:$clog2(MAX OUTSTANDING)] counterType;
1
    property p_fifo_data_check(local input counterType numAhead);
2
3
       dataType data = dataIn;
       ##1 (numAhead > 0 ##0 complete[->1], numAhead--)[*]
4
       ##1 (numAhead == 0 ##0 complete[->1])
5
       |->
6
       dataOut == data;
7
    endproperty
8
9
    property p fifo all checks;
       counterType outstanding, nextOutstanding = '0;
10
11
           (start | complete)[->1],
12
          outstanding = nextOutstanding,
          nextOutstanding += start - complete
14
       ) [+]
15
       |->
16
       if (start) (
17
           (!complete && outstanding < MAX OUTSTANDING)
18
          and p fifo data check (.numAhead (outstanding))
19
       ) else ( // complete
20
           !start && outstanding > 0
2.1
       );
    endproperty
23
    initial
24
       a fifo all checks: assert property (
25
26
          p fifo all checks
27
```

Fig. 15.15 Encoding of all FIFO protocol checks using only local variables

as it did in Sect. 15.3. In line 3, the local variable data is declared, and the declaration includes a declaration assignment to the value of dataIn. The meaning of this assignment is that whenever evaluation of p_fifo_data_check begins, the copy of data for that evaluation begins with the value of dataIn at that time. Line 17 guarantees that p_fifo_data_check is called only when start occurs, so dataIn is valid whenever the declaration assignment of line 3 is performed. The rest of p_fifo_data_check is identical to the encoding from Sect. 15.3 and behaves the same.

The structure of p_fifo_all_checks is an implication whose antecedent is an unbounded repetition (lines 11–15) and whose consequent enforces the control checks (lines 18 and 21) and the data check (line 19). There are two local variables, outstanding and nextoutstanding, both declared in line 10. The reason for having two local variables will be explained below. Note that nextoutstanding is declared with a declaration assignment to the value '0. This assignment corresponds to the nonblocking assignment on line 3 of Fig. 15.6.

⁶ Local variable declaration assignments are new in the System Verilog 2009 standard.

The repetition in lines 11–15 uses a pattern similar to the decrementing counter from line 5 of Fig. 15.9. In this case, successive iterations of the repetition match each time a start or complete occurs. The assignments in lines 13 and 14 are executed for each iteration and are performed in the order that they appear. The assignment to nextoutstanding is analogous to line 5 of Fig. 15.6 and accomplishes the basic accounting of the number of outstanding transactions.

The reason for using the two local variables is that when outstanding is declared as a static variable as in Sect. 15.3, references to it from within sequences and properties resolve to the sampled value for that cycle. On the contrary, when outstanding is declared as a local variable, then any assignment to it is immediately visible to subsequent parts of the sequence or property. Thus, the present encoding uses nextoutstanding to compute the new number of outstanding transactions, and outstanding is assigned the old value of nextoutstanding just before nextoutstanding is updated. The result is that the local variable outstanding has the same timing as the static variable from Sect. 15.3. Of course, the local variable outstanding can be eliminated from p_fifo_all_checks (see Exercise 15.8). An alternative encoding using recursive properties also avoids the use of two local variables (see Fig. 17.11).

15.6 Tag Protocol Revisited

This section shows two alternative encodings of the tag protocol control and data checks using local variables. One uses a single-bit auxiliary static variable, and the other requires no auxiliary static variable. These encodings also do not rely on the existence of the small bound, MAX ACTIVE, on the number of active transactions.

15.6.1 Tag Protocol Using a Single Static Bit

An encoding of the tag protocol control and data checks using local variables and a single-bit auxiliary static variable is shown in Fig. 15.16. It is unlikely that this encoding is supported in current formal verification tools because assignment to the static variable is done within a task that is called from within a property. Nevertheless, there is nothing in the encoding that is essentially beyond the capabilities of formal verification tools. Its simplicity and elegance stand in contrast to the more cumbersome data management of the encodings that rely on MAX_ACTIVE (e.g., as shown in Fig. 15.14 and explored in Exercise 15.9).

Property p_start_and_data_checks captures the values of tagIn and dataIn in the local variables tag and data whenever start occurs (line 12). Lines 15–17 check that, beginning in the next cycle, there is not another occurrence of start with the same tag until after the nearest occurrence of complete with the same tag. These lines enforce the rule that an active tag cannot be reused, as specified in rule 4

```
bit complete justified;
1
    initial
2
3
       complete_justified = 1'b0;
    always @(posedge clk)
4
       complete justified = 1'b0;
5
    task t justify complete;
6
       complete justified = 1'b1;
7
    endtask
8
    property p_start_and_data_checks;
9
       tagType tag;
10
       dataType data;
11
        (start, tag = tagIn, data = dataIn)
12
        =>
13
        (
14
           !(start && tagIn == tag)
15
          throughout
16
           (complete && tagOut == tag) [->1]
17
18
       ##0 (1'b1, t justify complete)
19
       ##0 dataOut == data;
20
    endproperty
2.1
    a start and data checks:
                                 assert property (
22
       p start and data checks
23
24
    a complete check: assert property (
25
26
       complete |=> complete justified
27
```

Fig. 15.16 Encoding of all tag protocol checks using local variables and a single-bit static variable

of the tag protocol. When the corresponding complete occurs, line 20 compares dataOut with the local variable data. This comparison performs the data check specified in rule 7 of the tag protocol.

It remains to explain how this encoding performs the check specified in rule 5: complete may occur only if tagout is an active tag. To gain some insight into why checking rule 5 is more difficult than checking the rule 4, it is helpful to note that there is an incomplete symmetry between start and complete in the tag protocol. The symmetry can be described by the following statements:

- Once start occurs for a given tag, another start may not occur for that tag until after complete occurs for that tag.
- Once complete occurs for a given tag, another complete may not occur for that tag until after start occurs for that tag.

These statements can be encoded in a straightforward way using local variables: the first is represented in lines 12 through 18 of Fig. 15.16; for the second, see Exercise 15.10. The asymmetry is that initially there can be a start on any tag, but there cannot be a complete on a tag until after an occurrence of start on that tag. Accounting for the tags for which no start has occurred is the challenging part, and doing so explicitly is essentially encoding a data structure to represent all the tags in a particular state, similar to the data structures discussed in Sect. 15.4.

The novelty of the present encoding is that it entirely avoids explicit representation of such a data structure. Instead, it makes use of the fact that there is one evaluation thread of property <code>p_start_and_data_checks</code> tracking each active tag. When a <code>complete</code> occurs, we need to determine whether or not there is such a thread tracking the tag value in <code>tagOut</code>. SystemVerilog provides no way to query such information from a set of threads of evaluation. Instead, <code>p_start_and_data_checks</code> is encoded so that the relevant thread, if it exists, announces itself. The medium of communication is the static bit <code>complete_justified</code>.

The communication mechanism works as follows. In every time-step in which posedge clk occurs, the communication bit is cleared by writing the value 1'b0 into complete_justified in line 5. This assignment occurs in the Active region, which is before any assertion evaluation in the Observed region and before any subsequent evaluations in the Reactive region.

If complete occurs and there is a thread of evaluation with tag == tagOut, then that thread will finish match of lines 15–17 and execution will proceed to line 19, where t_justify_complete is called. Line 19 illustrates attachment of a subroutine call to a sequence. The sequence in this case is just the Boolean 1'b1. Like local variable assignments, subroutine calls may appear in such a commaseparated list, and they are scheduled to execute in the Reactive region in the order that they appear. When it executes, the task t_justify_complete simply writes the value 1'b1 into complete_justified, overwriting the value 1'b0 previously written in line 5. Furthermore, the value 1'b1 will remain in complete_justified until after the Preponed region of the next time-step in which posedge clk occurs. Therefore, a thread announces itself as justifying a complete by causing the value of complete_justified to be 1'b1 in the Preponed region of the time-step of the next occurrence of posedge clk. In the Active region of that time-step the value 1'b0 will again be written into complete_justified, clearing the communication bit.

The assertion a_complete_check simply looks for an announcement by requiring that complete_justified be high the cycle after each occurrence of complete. Because the reference to complete_justified in line 26 uses the sampled value, it is able to see the announcement even though the communication bit is also cleared in the same cycle. This accomplishes the validation of complete as specified in rule 5 of the tag protocol.

15.6.2 Tag Protocol Using Only Local Variables

In the previous solution, the mechanism for announcing the existence of a justifying thread relies somewhat delicately on the SystemVerilog scheduling semantics in the way the static bit complete_justified is updated. Another approach is to code an auxiliary sequence that will match exactly when a justifying thread exists and finishes matching lines 15–17 of Fig. 15.16. The existence of a justifying thread is

```
sequence s start and complete;
1
       tagType tag;
2
3
       (start, tag = tagIn)
4
           !(start && tagIn == tag)
5
           throughout
6
           (complete && tagOut == tag)[->1]
7
       );
8
9
    endsequence
    property p_start_and_data_checks;
10
       dataType data;
11
       (start, data = dataIn)
12
       |->
13
       s_start_and_complete
14
       ##0 dataOut == data;
15
    endproperty
16
    a start and data checks: assert property (
17
       p start and data checks
18
    );
19
    a complete check: assert property (
20
       complete |-> s_start_and_complete.triggered
21
```

Fig. 15.17 Encoding of all tag protocol checks using only local variables

then detected by reference to the endpoint of match of this sequence using the sequence method triggered (see Sect. 9.2.1). No auxiliary static bit is needed. Such an encoding is shown in Fig. 15.17.

The auxiliary sequence is s_start_and_complete. It simply mimics the temporal patterns of lines 12–18 of Fig. 15.16. In order to maximize the sharing of sequential code between the auxiliary sequence and the correctness property p_start_and_data_checks, the latter has been reorganized to instantiate the former in line 14 as part of the consequent of the operator |->. The result is equivalent to the version of the property in the previous encoding. Sequence method triggered is applied to the instance of the auxiliary sequence in line 21. This method converts the sequence instance into a Boolean that is true in any cycle in which the sequence finishes a match and is false otherwise, accomplishing the communication of the announcement.

Because there are two instances of the auxiliary sequence, this solution incurs a nominal doubling of the local variable storage for tags as compared to the previous encoding. A tool could mitigate or eliminate this storage overhead by recognizing that the antecedent start of |-> in line 12 is not restrictive on the possible matches of s start and complete in the consequent.

Exercises

15.1. Show that if the three assertions of Fig. 15.3 hold, then the following assertion also holds:

```
a mutex: assert property (!(start && complete));
```

- **15.2.** Suppose that the sequential protocol is relaxed to allow an occurrence of complete to be concurrent with the corresponding occurrence of start. If this happens, then start may occur again in the subsequent cycle.
- Modify the precise English description of the protocol to account for this relaxation.
- 2. Modify the encodings given in Figs. 15.3, 15.4, and 15.5 to align them with this relaxation.
- 15.3. Show that for any positive value of MAX_OUTSTANDING that does not overflow \$clog2, the declaration of outstanding in Fig. 15.6 has enough bits to store the number MAX_OUTSTANDING. Show that if MAX_OUTSTANDING is not a power of two, then this declaration has more than enough bits to store the number MAX_OUTSTANDING. Find a declaration that always allocates the minimum number of bits required to store the number MAX_OUTSTANDING.
- **15.4.** Will the behavior of p_fifo_data_check in Fig. 15.9 change if the ##1 in line 5 is changed to ##0? If so, does the new behavior correctly advance to the cycle at which the data comparison of line 8 needs to be performed? What happens if the ##1 in line 6 is changed to ##0?
- 15.5. The encoding of p_fifo_data_check in Fig. 15.9 uses the decrementing local variable counter numAhead. Give an alternative encoding that uses an incrementing local variable counter. [Hint: Use three local variables, one to capture dataIn, another to capture outstanding, and the other to serve as the incrementing counter.]
- 15.6. Assume that storage for the queue declared in line 1 of Fig. 15.8 is allocated at compile time. (This is likely an accurate assumption for a formal verification tool, although it might not be accurate for a simulation tool.) Compare the storage requirements for the encodings of a_fifo_data_check with local variables (Fig. 15.9) and without local variables (Fig. 15.8). Consider the storage requirements for the local variables if outstanding remains small compared to MAX_OUTSTANDING and if outstanding becomes close to MAX_OUTSTANDING.
- **15.7.** What will happen if the assertion a_fifo_all_checks of Fig. 15.15 is written as a module item instead of within an initial procedure?
- **15.8.** Show how to recode p_fifo_all_checks from Fig. 15.15 to eliminate the local variable outstanding.
- **15.9.** Suppose that the product of the number of tag values times the number of bits needed to store a data value in the tag protocol is too large to allocate storage for the data associated with every tag. Enhance the encoding shown in Fig. 15.14 to store also the data for each active transaction. Show how to encode the tag protocol data check without using local variables.
- **15.10.** Write a property using only local variables that checks that once complete occurs for a given tag, another complete may not occur for that tag until after start occurs for that tag.

Chapter 16 Mechanics of Local Variables

I think I can safely say that nobody understands quantum mechanics

- Richard Feynman

The previous chapter introduced local variables by illustrating their use in intuitive and realistic examples of increasing richness. This chapter covers the mechanics of declaring, assigning, and referencing local variables in a more complete way. Input and output with local variables, and behavior of local variables with LTL operators, multiple clocks, and resets are discussed.

Local variables are divided into two kinds. A *body local variable* is one that is declared in the body of a named sequence or property, whereas an *argument local variable* is one that is declared as a formal argument of a named sequence or property. The second kind is new in SystemVerilog 2009 and is especially helpful for writing recursive properties (see Chap. 17) in which local variable values need to be passed into recursive property instances. In most respects, local variables of both kinds behave the same, and the term *local variable* is used to refer to one of either kind. Another usability feature added in SystemVerilog 2009 enables initialization of a local variable to be specified in the local variable's declaration.

Certain sequence and property operators (e.g., or, and, always) cause the evaluation of an assertion to fork into subevaluation threads. Depending on the operator and its context, the forked subevaluation threads may or may not later join. Local variables have been designed to work well in this multithreaded setting. When evaluation forks, each of the subevaluation threads receives its own copy of all the local variables together with all the values currently stored in them. As the subevaluations continue, each thread independently manages its copies of the local variables.

Forked subevaluation threads of property operators never join back, so the local variables in the forked threads remain independent. For a sequence operator, the nature of the operator (or vs. and, e.g.) determines how the subevaluations join when the sequence matches. A system of rules defines which local variables may be referenced after match of that sequence. These rules ensure that a local variable that might have inconsistent values in a thread of evaluation ensuing from the match may not be referenced after the match until an unambiguous value is stored into it. The rules can be checked at compile time and do not depend on the particular values stored in the local variables in the evaluation threads.

There are mechanisms for passing values of local variables into instances of named sequences or properties and out of instances of named sequences. Argument local variables enable improved type checking and self-documentation of code intent for these mechanisms.

We continue to assume that, unless otherwise specified, all assertions are clocked at posedge clk and there is a default clocking specification.

16.1 Declaring Body Local Variables

Body local variables are declared immediately after the header of the named sequence or property in which they appear. Here is an example:

```
sequence s1;
  logic l_a, l_b[4];
  dataType l_data;
  @(posedge clk)
  ...
endsequence
```

This example declares 1_a to be a local variable of type logic, 1_b to be a local variable that is an unpacked array of four elements of type logic, and l_data to be a local variable of the user-defined type dataType. Body local variable declarations precede the main sequence or property of the declaration. In particular, they precede any clocking event or disable iff specified in the declaration.

The form of a body local variable declaration is a special case of the form of a SystemVerilog variable declaration. The data type of a local variable declaration must be explicit and must be one of the types allowed in assertion Boolean expressions (see Sect. 16.6.1 of the SystemVerilog 2009 LRM). The following example shows some illegal local variable declarations.

Unlike other SystemVerilog variables, local variables have no default initial values. A body local variable may optionally be declared with a *declaration assignment*. Declaration assignments are also called *initialization assignments* because in each evaluation they provide the initial values to the associated local variables. This feature is new is SystemVerilog 2009. Consider the following example:

```
sequence s2(logic start, b[4]);
  logic l_a = 1'b0, l_b[4] = b;
  dataType l_data;
  @(posedge clk)
  start ##1 ...
endsequence
```

The local variables 1_a and 1_b have declaration assignments. The expression on the right-hand side of a declaration assignment can be any expression that may be assigned to the local variable. It need not be constant. For a given evaluation of s2, the declaration assignments are performed in the first time-step in which there is an occurrence of the leading clocking event, posedge c1k. At that point, 1_a is assigned the value 1'b0 and 1_b is assigned the value of the unpacked array formal argument b. The local variable 1_data, however, has no value at that point and is said to be unassigned. If evaluation of s2 begins in a time-step in which posedge c1k has occurred, then the declaration assignments are performed at that point.

Evaluation of the right-hand side of a declaration assignment follows the rules for evaluation of the right-hand side of an ordinary local variable assignment, as discussed in Sect. 16.3. The delay, as necessary, of the performance of a declaration assignment until occurrence of the leading clocking event of the sequence or property implies that these assignments are semantically equivalent to ordinary local variable assignments performed at the appropriate points. For example, \$2\$ above is semantically equivalent to the following variant:

```
sequence s2_v2(logic start, b[4]);
  logic l_a, l_b[4];
  dataType l_data;
  @(posedge clk)
  (start, l_a = 1'b0, l_b[4] = b) ##1 ...
endsequence
```

The local variable declaration assignments have been moved and attached to the first Boolean expression, start, of the sequence.

Declaration assignments are performed in the order that they appear, so there can be dependency of the right-hand side of a later assignment on a local variable whose declaration assignment is performed previously. It is illegal, though, for the right-hand side of the later assignment to depend on a local variable for which there is no declaration assignment. Here is an example of legal declaration assignments illustrating such a dependency:

```
property p1(byte data);
  byte l_byte = data, l_byteMasked = l_byte & mask;
   ...
endproperty
```

When the declaration assignments are performed, 1_byte is first assigned the value of data, and then 1_byteMasked is assigned the bitwise-and of the value just assigned to 1_byte and the value of mask. The following example shows illegal declaration assignments:

```
property p1_illegal;
   byte l_byte, l_byteMasked = l_byte ^ mask;
   ...
endproperty
```

¹ In a singly clocked setting, where all timing is aligned to the same clocking event, evaluation of a sequence or property always begins in a time-step in which the clocking event has occurred.

```
property p_mult_leading_clks;

byte l_v = e;

(@(posedge clk1) al until bl == l_v)

and
(@(posedge clk2) a2 until b2 == l_v);
endproperty
```

Fig. 16.1 Property with local variable declaration assignment and multiple leading clocks

The declaration assignments are illegal because the right-hand side of the assignment to 1_byteMasked references 1_byte, for which there is no declaration assignment.

The timing of declaration assignments involves some subtlety in the presence of multiple clocks. The key principle is that a declaration assignment is always performed after aligning with a leading clocking event. This ensures that the value stored by the declaration assignment comes from a known sampling point. If a property has multiple leading clocking events,² then separate local variables are created for each leading clocking event and the corresponding declaration assignments are performed upon reaching alignment with each of those various clocking events.

Figure 16.1 shows declaration of a property with a local variable declaration assignment and multiple leading clocks. Suppose evaluation of p_mult_leading_clks begins at time t_0 . At that time, two copies of 1_v are created. One copy is used in the evaluation of the subproperty on line 3 and the other copy is used in the evaluation of the subproperty on line 5. The assignment 1_v = e for the first copy is performed in the first time-step concurrent or subsequent to t_0 in which posedge clk1 occurs. Similarly, the assignment 1_v = e for the second is performed in the first time-step concurrent or subsequent to t_0 in which posedge clk2 occurs. The behavior of p_mult_leading_clks is therefore equivalent to the following variant, in which the declaration assignment has been eliminated:

```
property p_mult_leading_clks;
byte l_v;
(@(posedge clk1) (1'b1, l_v = e) #-# a1 until b1 == l_v)
and
(@(posedge clk2) (1'b1, l_v = e) #-# a2 until b2 == l_v);
endproperty
```

 $^{^2}$ According to SystemVerilog 2009, only properties can have multiple leading clocking events. Sequences always have a unique leading clocking event.

16.2 Declaring Argument Local Variables

The preceding section presented the following example:

```
sequence s2(logic start, b[4]);
  logic l_a = 1'b0, l_b[4] = b;
  dataType l_data;
  @(posedge clk)
  start ##1 ... // assume no further reference to b
endsequence
```

The body local variable 1_b has a declaration assignment whose entire right-hand side is a reference to the like-typed formal argument b. The declaration assignments are performed when the evaluation reaches alignment with posedge clk, and at that point the value in the formal argument b is assigned to 1_b. Assume that the body of s2 makes no further reference to b. Then the sole use of this formal argument is to provide the local variable 1_b its initial value, which is determined from the actual argument expression associated with b in the relevant instance of s2.

In such a case, it is convenient to be able to declare the formal argument itself as a local variable. SystemVerilog 2009 provides this capability in *argument local variables*. Under the assumption that the only reference to b in s2 is in the declaration assignment to 1_b, the following variant is semantically equivalent to s2:

```
sequence s2_v3(logic start, local input logic l_b[4]);
  logic l_a = 1'b0;
  dataType l_data;
  @(posedge clk)
  start ##1 ...
endsequence
```

The keyword local specifies that 1_b is an argument local variable, while the direction input specifies that 1_b will receive its initial value from the associated actual argument expression, after casting to the type of 1_b. The keyword local prevents preceding data type information from applying to the associated formal argument, so the data type logic must be repeated for 1_b.

The semantic equivalence of s2 and s2_v3 is exact. In general, an argument local variable of direction input behaves exactly like a body local variable of the same type, together with a dummy formal argument of the same type, where the body local variable has a declaration assignment whose entire right-hand side is a reference to the dummy formal argument. As a result, an input argument local variable gets its initial value at the same time-step in which body local variable declaration assignments are performed.

Argument local variables are considered to precede body local variables. If a sequence or property has both input argument local variables and body local variables with declaration assignments, then the initialization assignments of the input

 $^{^3}$ In the SystemVerilog 2009 LRM, the longer phrase "local variable formal argument" is used rather than "argument local variable".

```
property p1_v2(local input byte 1_byte);
  byte 1_byteMasked = 1_byte & mask;
  ...
endproperty
```

Fig. 16.2 Body local variable declaration assignment referencing argument local variable

```
sequence s_arg_dirs(
       local input byte 1 s i,
2
       local inout byte 1 s io,
3
       local output byte 1 s o
4
    );
5
       ... // l s o must be assigned in the body
6
    endsequence
7
8
    property p_arg_dirs;
9
       byte 1 p io, 1 p o;
10
       (start, l_p_io = e_io)
       |-> s arg dirs(e i, l p io, l p o)
12
       |-> results ok(l p io, l p o);
13
    endproperty
14
```

Fig. 16.3 Sequence with argument local variables of all directions

argument local variables are performed first. It is legal for the right-hand side of a body local variable declaration assignment to reference an input argument local variable. Figure 16.2 shows a variant of property p1 from the preceding section illustrating this capability.

Argument local variables can also be declared of direction output or inout, but only in a sequence declaration. An argument local variable of a property must be of direction input. An output argument local variable outputs its value to the actual argument whenever the sequence matches. The actual argument must itself be a local variable. An inout argument local variable behaves as a combination of an input and an output argument local variable – it receives its initial value from the actual argument and also outputs its value back to the actual argument whenever the sequence matches. The actual argument must again be a local variable.

Figure 16.3 gives an example of a sequence <code>s_arg_dirs</code> with argument local variables of all three directions and a property <code>p_arg_dirs</code> that instantiates it. The instance of <code>s_arg_dirs</code> on line 12 passes the expression <code>e_i</code> to <code>l_s_i</code> and passes the local variables <code>l_p_io</code> and <code>l_p_o</code> to <code>l_s_io</code> and <code>l_s_o</code>, respectively. In the evaluation of <code>s_arg_dirs</code>, <code>l_s_i</code> gets its initial value from <code>e_i</code>, while <code>l_s_io</code> gets its initial value from <code>l_p_io</code>, which is assigned the value of <code>e_io</code> in line 11. <code>l_s_o</code> gets no initial value. Whenever <code>s_arg_dirs</code> matches, the values of <code>l_s_io</code> and <code>l_s_o</code> are output to <code>l_p_io</code> and <code>l_p_o</code>, respectively, and these values are used in the check of <code>results_ok</code> in line 13. Further details on <code>output</code> and <code>inout</code> argument local variables will be discussed in Sect. 16.5.

The following rules apply in declaration of argument local variables: If a direction is specified for an argument, then the keyword local must also be specified, and if the keyword local is specified, then the data type must be explicitly specified, including any packed dimensions. Unpacked dimensions may also be specified. Since the arguments of s_arg_dirs have distinct directions, they must each specify the keyword local and therefore must also repeat the data type byte.

It is allowed to specify the keyword local without a direction, and in this case the direction input is understood. Thus, the following variant is semantically equivalent to s_arg_dirs:

```
sequence s_arg_dirs_v2(
   local byte l_s_i,
   local inout byte l_s_io,
   local output byte l_s_o
);
   ...
endsequence
```

Consecutive declarations of argument local variables can share the same specifications of the keyword local, the direction, and the data type (including any packed dimensions), but only if the following conditions are satisfied:

- The first of the declarations specifies local, specifies the direction either explicitly or implicitly, explicitly specifies the data type (including any packed dimensions), and does not specify any unpacked dimensions.
- Subsequent declarations specify only the formal argument identifier. No packed or unpacked dimensions may be specified together with the subsequent identifiers.

Here is an example of legal declarations illustrating this capability and the restrictions:

```
sequence s3(
  local input byte l_a, l_b,
  local input byte l_c[8],
  local input byte l_d,
  local inout byte l_e,
  local input bit l_f,
  local input bit [0:3] l_g, l_h
);
  ...
endsequence
```

1_a and 1_b are both of direction input and data type byte. 1_c is of direction input and is an unpacked array of eight bytes. Because of the unpacked dimension, the declaration of 1_c cannot share the keyword local and direction with either the preceding or the subsequent declaration. Because the direction of 1_e does not match the preceding direction, the declaration of 1_e must specify the keyword local and the direction and data type. 1_g and 1_h are both packed vectors of

4 bits. Even though 1_g has the same direction and base data type as 1_f, it has different packed dimension and so must have its own specification of the keyword local, direction, and data type.⁴

An input argument local variable may be declared with an optional default actual argument, which can be any expression that may be assigned to the argument local variable. An output or inout argument local variable may not be given a default actual argument because the actual argument must specify the local variable that will receive the output value. The syntax for a default actual argument is the same as that for ordinary formal arguments of sequences or properties (see Chap. 7). The default actual argument serves as the actual argument in any instance of the sequence or property that does not otherwise specify the actual argument. As usual, names in the default actual argument expression resolve in the context of the sequence or property declaration, not in the context of its instantiation. Here is a modification of property p1 that specifies a default actual argument:

```
property p1_v3(local input byte 1_byte = data);
   byte 1_byteMasked = 1_byte & mask;
   ...
endproperty
```

The default actual argument for 1 byte is data.

16.3 Assigning to Local Variables

The fundamental capability provided by local variables is to enable an assertion to capture the value of an expression at a specified point in its evaluation and store that value for later reference, perhaps after further modification. This section discusses rules for assigning to local variables. The declaration and initialization assignments introduced in Sects. 16.1 and 16.2 are particular cases of assignments to local variables. They must follow the rules presented here.

A local variable assignment may be attached to a subsequence of a named sequence or property. The local variable assignment is written after the subsequence, separated by a comma, and the pair is enclosed in parentheses. The subsequence must not admit an empty match. Whenever the subsequence matches in the course of evaluation of the named sequence or property, the local variable assignment is performed. The result of attaching a local variable assignment to a subsequence is always a sequence, even if the subsequence were itself a Boolean. Here is a simple example:

```
property p_ttype_vs_data;
   transType l_ttype;
   (start, l_ttype = ttype)
   ##1 (dataValid within complete[->1])
   |-> ttypeAllowsData(l_ttype);
endproperty
```

⁴ The rules of sharing components of declarations are more stringent than necessary. Future versions of SystemVerilog may relax them.

The local variable assignment <code>l_ttype = ttype</code> has been attached to the Boolean subsequence <code>start</code>. Whenever <code>start</code> is tested and evaluates to true, the Boolean subsequence matches and the local variable assignment is performed, capturing the value of <code>ttype</code> for later reference in the call to the function <code>ttypeAllowsData</code>. This property checks that if <code>dataValid</code> occurs after <code>start</code> and not later than <code>complete</code>, then the transaction type specified in <code>ttype</code> at the time of <code>start</code> is one that allows data as encoded in <code>ttypeAllowsData</code>.

Multiple local variable assignments may be attached to a single subsequence. The local variable assignments are performed in order whenever the subsequence matches.

```
sequence s_compare_two_data_and_parity;
  dataType l_data;
  parityType l_parity;
  start
  ##1 (dataValid[->1], l_data = data, l_parity = parity)
  ##1 dataValid[->1]
  ##0 data == l_data && parity == l_parity;
endsequence
```

This sequence compares the values of data and parity from the first two occurrences of dataValid after start. Two assignments have been attached to the first goto subsequence dataValid[->1]: 1_data = data and 1_parity = parity. The local variables capture the values of data and parity from the first occurrence of dataValid and hold them for comparison with the corresponding values at the second occurrence of dataValid. If the corresponding values are equal, then the overall sequence matches.

In general, the evaluation of the right-hand side of a local variable assignment follows the rules for evaluation of expressions within a concurrent assertion. After resolving the terms of the expression through elaboration (including argument passing, module instantiation, bind instantiation, etc.), sampled values are used for those terms that are not local variables, while current values are used for terms that are local variables. These rules apply to declaration assignments for body local variables and initialization assignments for argument local variables.

Each evaluation attempt of a named sequence or property gets its own, private copy of all the declared local variables for use within that evaluation. Local variables are thus "local" to an individual thread of evaluation, and variables for one thread of evaluation cannot be referenced in another thread of evaluation. The examples presented so far in this chapter have required only one copy of each local variable per evaluation attempt. In general, evaluation of a sequence or property may involve branching into subevaluations. Part of the power of local variables is that their semantics includes automatic allocation of additional copies when needed to store multiple values arising from such subevaluations. Consider the example in Fig. 16.4. This property checks that for every occurrence of dataValid that happens after start and not later than complete, the values of data and parity that are present with dataValid satisfy the condition encoded in the function parityOK. The local variable assignments are attached to the Boolean subsequence dataValid, and the resulting sequence is the first operand of the within operator. The within sequence

```
property p data and parity;
1
       dataType l_data;
2
       parityType 1 parity;
3
       start ##1
4
5
           (dataValid, 1 data = data, 1 parity = parity)
6
          within complete[->1]
8
       |-> parityOK(l data, l parity);
    endproperty
10
```

Fig. 16.4 Data and parity check




Fig. 16.5 Waveform for data and parity check

is itself part of the antecedent of |->. The semantics of |-> requires that every match of its antecedent result in a check of its consequent. Because dataValid may occur at multiple points within the interval of matching of complete[->1], there may be multiple matches of the antecedent, and each such match will have its own copy of the local variables to store the values of data and parity from the particular point that dataValid occurred for that match.

Figure 16.5 shows a possible waveform for this property. Only the values of data and 1_data are shown, since the timing of the local variable capture for 1_parity is the same. start occurs at time 20 and complete occurs at time 90. Between them there are three occurrences of dataValid, at times 30, 50, and 70. Therefore, the evaluation of p_data_and_parity that starts at time 20 will obtain three copies of 1_data, one for each of the three occurrences of dataValid. These copies are shown as 1_data_{30}, 1_data_{50}, and 1_data_{70} in the waveform, along with the values of data that they capture.

16.3.1 Assignment Within Repetition

If the operand of a sequence repetition is a subsequence with a local variable assignment attached, then the local variable assignment executes on each iterative match of the subsequence. Such assignments can be used to count the number of iterations or to compute aggregate values based on increments that are observable at the successive matches of the subsequence.

Figure 16.6 shows an example of counting the number of iterations.⁵ When start occurs, the property stores the transaction type in the local variable 1 ttype (line 4). The property checks that the number of occurrences of dataValid that happen after start and not later than complete is allowable for the transaction type according to the function numBeatsOK. The number of occurrences of dataValid is counted in the local variable numBeats. numBeats is initialized to zero in its declaration on line 3. The various occurrences of dataValid are matched by the goto dataValid[->1] within the repetition on line 6, and numBeats is incremented for each of these matches. The increment expression numBeats++ illustrates the fact that local variable assignments may be specified by increment and decrement expressions. They may also be specified by general operator assignments (+=, &=, etc.). The subsequence of lines 6 and 7 is intersected with the goto complete [->1] of line 9 to ensure that only the relevant occurrences of dataValid are counted. The zero repetition option for [*] in line 7 allows the last dataValid to be concurrent with complete. The zero repetition option for [*] in line 6 allows for the possibility that there is no occurrence of dataValid.

16.3.2 Sequence Match Items

A local variable assignment attached to a sequence is an example of a *sequence match item*, i.e., an item to be performed upon match of the sequence. The other

```
property p ttype vs beats;
1
       transType l_ttype;
2
       int numBeats = 0;
3
        (start, l_ttype = ttype) ##1
4
5
           (dataValid[->1], numBeats++)[*]
6
              ##1 !dataValid[*]
7
           intersect
8
           complete[->1]
9
10
        |-> numBeatsOK(l ttype, numBeats);
11
    endproperty
12
```

Fig. 16.6 Counting using a local variable assignment within a repetition

⁵ For formal verification, the **int** type of numBeats should be replaced with the type of smallest bitwidth needed for the counter.

kind of sequence match item is a subroutine call. A subroutine called as a sequence match item can be a task, a task method, a void function, a void function method, or a system task.

Sequence match items may be attached to any sequence that does not admit empty match. The first match item is separated from the sequence by a comma, and further match items may be written as a comma-separated list. The sequence and list of match items are enclosed in parentheses. Whenever the sequence matches, the match items are processed in the order of the list. Local variable assignments are performed immediately in the Observed region. Subroutine calls are scheduled for execution in the Reactive region in the order that they appear. The assertion evaluation does not wait on or get information back from a subroutine.

Arguments passed to a subroutine call must be passed either by value as inputs or by reference (ref or const ref). Local variables may be passed only by value and must flow to the point of the subroutine call (see Sect. 16.4.1). Actual arguments passed by value are evaluated in the Observed region like other expressions in assertions: current values are used for local variables, whereas sampled values are used otherwise. Actual arguments passed by reference are evaluated using Reactive region values when the subroutine executes.

A common use of subroutine calls as sequence match items is to export information from the assertion evaluation thread, especially values of local variables. The export can be for debugging, to communicate with other parts of a testbench, or to populate a coverage model. The capability to place the subroutine call as a sequence match item is essential to get visibility to the local variables, which cannot be referenced from an action block. Figure 16.7 shows a variant of p_data_and_parity illustrating this usage. In each time-step that datavalid is matched in line 7, the local variable assignments are performed in line 8 and then the \$display system task is scheduled to execute in the Reactive region. The arguments to the display are inputs. Their values are computed in the Observed region, using the values assigned to the local variables in line 8 and the sampled valued of \$time.

```
property p data and parity v2;
1
       dataType l_data;
2
       parityType l parity;
3
       start ##1
4
6
              dataValid,
              l_data = data, l_parity = parity,
8
              $display("time=%0d data=%h parity=%h",
9
                 $time, l data, l parity)
10
11
          within complete[->1]
12
13
        |-> parityOK(l data, l parity);
14
    endproperty
15
```

Fig. 16.7 Property with subroutine call attached to a sequence

```
covergroup cg SEC type
1
       with function sample(startType startCode, endType endCode);
2
       SC: coverpoint startCode;
3
       EC: coverpoint endCode;
4
5
       SEC: cross SC, EC;
    endgroup
6
    cg_SEC_type cg_SEC = new();
7
    sequence s SEC;
8
       startType l startCode;
9
       (start, 1 startCode = startCode)
10
       ##1
11
       (
12
          complete[->1],
13
          cg_SEC.sample(l_startCode, endCode)
14
       );
15
    endsequence
16
    c_SEC: cover property(s_SEC);
```

Fig. 16.8 Collecting coverage using a local variable and a subroutine call

As another example, suppose that startCode is a signal of type startType that is valid with start, while endCode is a signal of type endType that is valid with complete. Suppose that we want to collect coverage on the pairs of startCode and endCode values that occur for transactions of the sequential protocol (see Sect. 15.2). This can be done using a covergroup and calling its sample method as a sequence match item. Figure 16.8 shows an encoding. The signature of the covergroup sample method is declared in line 2, and the covergroup is instantiated in line 7. The sequence s_SEC has a local variable to capture the value of startCode. Once complete is reached in line 13, the covergroup sample method is called in line 14. The signal endCode is valid at this time, while the startCode has been stored in 1_startCode. See Sect. 18.2.3 for further discussion of covergroups and Sect. 18.2.4 for more examples of this kind.

16.4 Referencing Local Variables

A local variable that is assigned a value may be referenced within the same named sequence or property. Local variables can be referenced in expressions such as:

- Boolean expressions.
- Bit-select and part-select expressions.
- Array indices.
- Arguments of task and function calls.
- Arguments of sequence and property instances.
- Expressions assigned to local variables.

Local variables cannot be referenced in the following kinds of expressions:

- Expressions that are required to be compile-time constants, such as n in each of the following operators: ##n, [*n], [-n]. Local variables also may not be referenced in the constant expressions of ranged forms of these operators.
- Clocking event expressions.⁶
- The reset expression of a disable iff.
- The abort condition of a reset operator (accept_on, sync_accept_on, and the reject forms of these operators).
- An argument expression to a sampled value function (\$rose, \$fell, \$past, etc.).

A local variable that is unassigned may not be referenced.

Each evaluation attempt of a sequence or property has its own, private copies of the local variables declared in that sequence or property. Further copies of the local variables may be created as the evaluation evolves, branching into subevaluation threads. In general, a local variable assigned in a thread of evaluation may be referenced later in that thread or in a descendent of that thread. However, SystemVerilog provides no mechanism for externally referencing or cross-referencing a local variable. One evaluation attempt cannot reference the copies of a local variable from another evaluation attempt. Similarly, a subevaluation thread cannot reference updates to a sibling's copy of a local variable. If the siblings are subsequence evaluations that later join (e.g., subevaluations of operands of sequence and or intersect), then structural rules described below determine whether or not the thread of evaluation that proceeds from the join can reference the updates from one of the siblings. Hierarchical references to local variables are illegal.

As a simple example to illustrate these ideas, suppose ttype is valid with start and that if there is an occurrence of start with ttype == INV or ttype == PRG, then at the next two occurrences of start, ttype must not have the same value that it has at the current occurrence of start. This check can be coded as

```
property p_ttype_check;
transType l_ttype;
(start && (ttype == INV || ttype == PRG), l_ttype = ttype)
| => start[->1:2]
| -> ttype != l_ttype;
endproperty
```

Consider the waveform shown in Fig. 16.9. The evaluation attempt of property p_{type_check} that begins at time 20 observes an occurrence of start together with ttype == INV, and so it stores INV in its copy of the local variable l_{type} . This copy of the local variable is represented by the row labeled l_{type} in the waveform. Another evaluation attempt of p_{type_check} begins at time 40, observes an occurrence of start together with ttype == PRG, and stores PRG in

⁶ Clause 16 of the SystemVerilog 2009 LRM does not explicitly forbid references to local variables in clocking event expressions, but such references are excluded from the clock rewrite rules in Annex F.5.1, so no formal semantics is defined for assertions with such references.




Fig. 16.9 Waveform for transaction type check

its copy of the local variable, which is labeled 1_ttype_{40} in the waveform. The evaluation that begins at time 20 sees only 1_ttype_{20} , not 1_ttype_{40} . At time 40, this thread observes the first subsequent occurrence of start, and the check ttype $!=1_ttype$ in line 5 compares PRG != INV and succeeds. At time 80, though, this thread fails since line 5 compares INV != INV, and so the overall evaluation beginning at time 20 fails. The evaluation that begins at time 40 succeeds since its two checks of line 5 compare INV != PRG at time 80 and READ != PRG at time 90.

16.4.1 Local Variable Flow

To understand more thoroughly where a local variable may be referenced and what value will be yielded, we need to explore in more detail how the scope of the local variable extends into various subsequences and subproperties and how the value stored in the local variable is carried along and changed in the corresponding subevaluations. A local variable is said to *flow into* a subsequence or subproperty if it is assigned (i.e., has a value) when evaluation of the subsequence or subproperty begins. A local variable is said to *flow out of* a subsequence if it is guaranteed to be assigned (i.e., to have a value) upon reaching the end of a match of the subsequence.

In general, if a local variable flows into a subsequence or subproperty, then the local variable may be referenced within that subsequence or subproperty provided the local variable remains assigned at the point of reference. (See Sect. 16.4.2 for a discussion of how a local variable may become unassigned.) A reference to a local variable yields the latest value assigned to it in the evaluation or subevaluation that reaches the point of the reference. The latest assignment may have occurred in the current time-step. A local variable reference is always to the current value stored in the variable, not the sampled value.

```
property p ttype vs beats;
1
       transType 1 ttype;
2
       int numBeats = 0;
3
       (start, 1 ttype = ttype) ##1
4
5
           (dataValid[->1], numBeats++)[*]
6
              ##1 !dataValid[*]
7
           intersect
8
           complete[->1]
g
10
       |-> numBeatsOK(l ttype, numBeats);
11
    endproperty
12
```

Fig. 16.10 Illustrating local variable flow, reference, and reassignment

As an example of local variable flow, reference, and reassignment, let us revisit the property p ttype vs beats, which is copied here in Fig. 16.10. The property has two local variables: 1 ttype has no declaration assignment, while numBeats has a declaration assignment initializing its value to 0. Therefore, 1 ttype is unassigned and does not flow into the body of the property in line 4, while numBeats does flow into line 4. If start evaluates to true in line 4, though, then 1 ttype is assigned the value of ttype. Therefore, both 1 ttype and numBeats flow into line 5. The subsequence of lines 5–10 makes no reference to and no re-assignment of 1 ttype. Therefore, 1 ttype flows with value unchanged into line 11, where it is referenced as an argument to the call to function numBeatsOK. In contrast, the subsequence on line 6 makes reference to and re-assigns numBeats for each consecutive match of dataValid[->1] in the repetition. The reference to numBeats is implicit in the increment operator ++. As a result, numBeats flows out of the subsequence of lines 6 and 7. Because numBeats is reassigned in only one of the operands of the intersect operator appearing on line 8, numBeats also flows out of the entire subsequence of lines 5-10. Therefore, numBeats flows with its last reassigned value into line 11, where it is also referenced as an argument to the call to function numBeatsOK.

The rules of local variable flow have been designed to be intuitively reasonable and also computable at compile time, rather than varying dynamically with the course of evaluation. The rules do not depend on the specific value stored in a local variable at a particular point, only on whether the local variable is guaranteed to be assigned some value at that point. Because the rules depend only on the structure of the sequences and properties and where the assignments to the local variables occur, they can be checked at compile time.

Below are the rules of local variable flow for declaration, instance, sequence, and property forms. In these rules, v, w stand for local variables; r, s stand for sequences; p, q stand for properties; e stands for an expression; and b stands for a Boolean expression.

• DF: A local variable declared in a named sequence or property flows into the body sequence or property expression of that declaration iff it is assigned in an initialization assignment.

- IF1: A local variable that flows into an instance of a named sequence or property does not flow into the body sequence or property expression in the declaration of that instance. The value of the local variable may be passed into the instance through an argument (see Sect. 16.5.1).
- IF2: A local variable that flows out of the body sequence expression of the declaration of a named sequence⁷ does not flow out of an instance of the named sequence. If the local variable is an untyped formal argument or an argument local variable of direction output or inout, then its value may be passed out of the instance (see Sect. 16.5.2).
- SF1: v flows out of b iff v flows into b. Analogous rules apply when b is replaced by Boolean repetitions $b \left[->n \right]$, $b \left[=n \right]$, etc.
- SF2: v flows out of (r, v = e). If w flows into (r, v = e), then w flows into r. w flows out of (r, v = e) iff w flows out of r. If e references w, then w must flow out of r.
- SF3: If v flows into r ##n s, then v flows into r. If v flows out of r, then v flows across ##n into s. v flows out of r ##n s iff v flows out of s. Analogous rules apply to the variants of the binary concatenation operator. The flow rules for unary concatenation are obtained from those for binary concatenation by replacing r with 1 t b1.
- SF4: If v flows into r or s, then v flows into both r and s. v flows out of r or s iff v flows out of both r and s.
- SF5: If v flows into r and s, then v flows into both r and s. v flows out of r and s iff either v flows out of r and there is no assignment to v in s or v flows out of s and there is no assignment to v in r. Analogous rules apply to intersect and within.
- SF6: If v flows into b throughout r, then v flows into both b and r. v flows out of b throughout r iff v flows out of r.
- SF7: If v flows into first_match(r), then v flows into r. v flows out of first_match(r) iff v flows out of r.
- SF8: v flows out of r [*0] iff v flows into r [*0]. The value of v does not change as a result of empty match of r [*0].
- SF9: If v flows into r [*n], where n is positive, then v flows into the first iteration of r. v flows out of r [*n] iff v flows out of r, in which case v flows into and out of each iteration of r. If v does not flow out of r, then v does not flow into any iteration of r after the first. Analogous rules apply to ranged forms of the repetition operator. If the lower range is zero, then the flow rule is obtained by decomposing r [*0:n] as r [*0] or r [*1:n] (n positive or \$).
- PF1: If v flows into strong (r), then v flows into r. An analogous rule applies
 to weak.
- PF2: If v flows into not p, then v flows into p.

⁷ More precisely, that flows out of the sequence expression that results from the body sequence expression of the declaration by substituting actual arguments from an instance for formal arguments, as described in the rewriting algorithms of Annex F.4 of the SystemVerilog 2009 LRM.

- PF3: If v flows into p or q, then v flows into both p and q. Analogous rules apply to and, implies, and iff.
- PF4: If v flows into $r \mid -> p$, then v flows into r. If v flows out of r, then v flows across $\mid ->$ and into p. Analogous rules apply to $\mid ->$, #-#, and #-#.
- PF5: If v flows into if (b) p else q, then v flows into b, p, and q. An analogous rule applies to case.
- PF6: If v flows into nexttime p, then v flows into p. Analogous rules apply to s nexttime and to the indexed forms of these operators.
- PF7: If v flows into always p, then v flows into p. Analogous rules apply to s always and to the ranged forms of these operators.
- PF8: If v flows into p until q, then v flows into both p and q. Analogous rules apply to s_until, until_with, and s_until_with.
- PF9: If v flows into s_eventually p, then v flows into p. Analogous rules apply to the ranged form of this and the weak eventually operator.
- PF10: If v flows into disable iff (b) p, then v flows into p. Analogous rules apply to accept on, reject on, sync accept on, and sync reject on.

As an example of analyzing local variable flow using these rules, consider the property in Fig. 16.11. By Rule DF, 1_v does not flow into line 3. By Rule SF2, 1_v flows out of line 4, and so by Rule SF5, 1_v flows out of line 7. Rule PF4 then says that 1_v flows into line 9, and so by Rule PF8, 1_v flows into both line 10 and line 12. This implies that the reference to 1_v in line 10 is legal. By Rule PF3, 1_v flows into both line 13 and line 15. This implies that the reference to 1_v in line 13 is legal. Finally, by Rule PF6, 1_v flows into the expression c != 1_v , so the reference to 1_v in line 15 is also legal.

```
property p_flow_analysis;
1
        byte l_v;
2
        (
3
            (a[->1], l v = e)
            within
5
6
            b[->1]
        )
7
        #=#
8
9
            (c == 1 v)
10
            until
11
12
            (
                (d == l_v)
13
               and
               nexttime(c != l_v)
            )
        );
17
    endproperty
```

Fig. 16.11 Property illustrating local variable flow

16.4.2 Becoming Unassigned

Once assigned, local variables only become unassigned upon match of subsequences formed from certain sequence operators. Code in which local variables become unassigned is of poor style and should be avoided.

Figure 16.12 shows an example in which the local variable 1_v becomes unassigned upon match of an and subsequence. The semantics of the and sequence operator requires the subevaluations of the operands to join together once both have matched. This requires all local variables that are assigned to have consistent, unambiguous values in the continuing thread of evaluation. There are assignments to 1_v in both operands of the and (lines 4 and 6), so 1_v may not have a single value upon match of the and. According to Rule SF5, 1_v does not flow out of the and subsequence, and as a result 1_v becomes unassigned in line 7. The reference to 1 v in line 8 is therefore illegal.

SF5 applies similarly to sequence operators intersect and within. Therefore, when coding local variable assignments in operands of sequence and, intersect, or within, do not make assignments to a single local variable in more than one operand. The ambiguous example from Fig. 16.12 can be recoded using two local variables as shown in Fig. 16.13. Note, in particular, that the comparison to c in line 8 has been disambiguated in Fig. 16.13 as the disjunction c = 1 va |c| c = 1 vb.

Figure 16.14 shows a different problem occurring with assignments in operands of a sequence or. In this example, 1_v is not assigned before the or, and it is assigned in only one operand of the or (line 4). The semantics of sequence or specifies that if either operand subsequence matches, then there is a match of the or, and evaluation continues for each such match. After line 7, it is not known which operand of the or matched, and so it is not known whether 1_v has been assigned. According to Rule SF4, 1_v does not flow out of the or, and 1_v becomes unassigned in line 7. The reference to 1_v in line 8 is therefore illegal.

The situation in Fig. 16.14 can be remedied by ensuring that 1_v will be assigned a value no matter which operand of the or matches. This can be done by assigning a value to 1_v prior to the or or by assigning a value to 1_v in the second operand (line 6). Figure 16.15 uses a declaration assignment to provide a value to 1_v prior to the or.

Fig. 16.12 Local variable becomes unassigned due to ambiguity of value after and

Fig. 16.13 Assigning to distinct local variables in the operands of and

```
1
   sequence s or ambiguous;
      bit l_v;
2
         // DF: 1 v does not flow in
3
          (a[->1], l v = e)
4
         or
5
         b[->1] // SF1: l_v does not flow out
6
         // SF4: l_v does not flow out, becomes unassigned
7
      ##1 c == l v; // illegal reference to l v
8
   endsequence
```

Fig. 16.14 Local variable becomes unassigned due to ambiguity of value after or

Fig. 16.15 Local variable assigned before or

The flow rules must be applied recursively to sequences and properties with nested structure. Figure 16.16 shows an example in which the second operand of an or subsequence is itself an and subsequence. According to SF5, 1_v does not flow out of the and (line 10). Even though 1_v is assigned before the or (line 2) and is assigned within each operand of the or, SF4 then implies 1_v does not flow out of the or and becomes unassigned in line 11. The reference to 1_v on line 12 is therefore illegal.

```
sequence s nested ambiguity;
1
       bit 1_v = 1'b0;
2
3
           (a[->1], l v = e)
4
5
          or
           (
6
              (b1[->1], l_v = f1)
7
              and
8
g
              (b2[->1], l v = f2)
             // SF5: 1 v does not flow out
10
              // SF4: 1 v does not flow out, becomes unassigned
11
       ##1 c == l v; // illegal reference to l v
12
    endsequence
13
```

Fig. 16.16 Nested structure results in local variable becoming unassigned

16.4.3 Multiplicity of Matching with Local Variables

Without local variables, multiple matches of a sequence over the same interval of a trace can usually be treated as the same.⁸ For example, consider the following assertion:

```
a_mult_match: assert property(
        (a[*1:2] or b[*1:2]) |-> c
);
```

For each evaluation attempt, the antecedent sequence can either not match or match over one or two cycles. If a and b are not mutually exclusive, then each match could be of multiplicity either one or two. Checking of the consequent is obligated for each match of the antecedent, but the consequent evaluation is the same for multiple matches over the same interval. Therefore, a tool can simply keep track of which intervals are matched by the antecedent and not distinguish multiple matches over the same interval.

With local variables, the values stored in them can differentiate matches over the same interval of a trace. If there are subsequent references to the local variables, then tools must keep track of the different values in the local variables for multiple matches over the same interval. The following code illustrates this situation:

```
property p_mult_match_loc_var;
   byte l_v;
   ((a[*1:2], l_v = e) or (b[*1:2], l_v = f)) |-> g != l_v;
endproperty
a_mult_match_loc_var: assert property(p_mult_match);
```

Property p_mult_match_loc_var has the same possibilities for matching of its antecedent as assertion a_mult_match. However, because different expressions are assigned to the local variable 1_v in the two operands of or, this local variable

⁸ When collecting coverage for a **cover sequence** assertion statement, all matches must be counted with the appropriate multiplicities.

can distinguish multiple matches over the same interval. Since 1_v is referenced in the consequent, tools must keep track of all of the various multiple matches of the antecedent and the associated values of 1_v. The checking performed by a mult match loc var is equivalent to the following assertion:

16.5 Input and Output with Local Variables

This section describes the mechanisms provided by SystemVerilog for passing values of local variables into instances of named sequences and properties and out of instances of named sequences. Special rules apply when passing values into an instance of a named sequence to which a sequence method (triggered or matched) is applied. There is no notion of passing values of local variables out of instances of named properties.

16.5.1 Input with Local Variables

In general, any local variable that is assigned a value at the point of instantiation of a named sequence or property may have its value passed into that instance simply by referencing the local variable as an entire actual argument expression of the instance or as a proper subexpression of an actual argument expression of the instance. The local variable itself cannot be referenced from within the instance, so the instance does not track changes to the local variable or to copies of it that might occur in the instantiating context. Rather, the value of the local variable passed into the instance remains constant throughout the evaluation of the instance.

The following simple example illustrates input of a local variable to an instance of a named property:

```
property p no repeat ttype(
2
       transType varying ttype, captured ttype
3
    );
4
       start[->1:2]
       |-> varying_ttype != captured_ttype;
5
    endproperty
7
   property p_ttype_check;
       transType 1 ttype;
8
       (start && (ttype == INV | | ttype == PRG), l_ttype = ttype)
10
       |=> p_no_repeat_tt(
          .varying ttype(ttype), .captured ttype(l ttype)
11
12
       );
    endproperty
13
```

This example is an equivalent recoding of the property p_ttype_check from Sect. 16.4. It uses an auxiliary property, p_no_repeat_ttype. In the instance of p_no_repeat_ttype in lines 10–12, the signal ttype is passed to the formal argument varying_ttype, while the local variable 1_ttype is passed to the formal argument captured_ttype. During an evaluation of this instance of p_no_repeat_ttype, the formal argument captured_ttype behaves as a constant equal to the value of the local variable 1_ttype at the time the evaluation begins. Referring back to the waveform in Fig. 16.9, the evaluation of p_ttype_check beginning at time 20 causes an evaluation of p_no_repeat_ttype to begin at time 30. This evaluation continues until time 80, and throughout it the formal argument captured_ttype has the value INV. By contrast, argument varying_ttype tracks changing values of the actual argument ttype because ttype is a signal rather than a local variable. Therefore, the evaluation of p_no_repeat_ttype that begins at time 30 fails at time 80, where it observes the second occurrence of start together with varying_ttype and captured_ttype both equal to INV.

Note that the preceding example is also equivalent to the following:

```
property p no repeat ttype(
1
2
       transType varying_ttype, captured_ttype
    );
3
       start[->1:2]
4
       |-> varying_ttype != captured_ttype;
5
    endproperty
6
    property p ttype check;
7
8
       transType l_ttype;
       (start && (ttype == INV | | ttype == PRG), l_ttype = ttype)
10
       (
11
           (1'b1, l ttype = ttype)
                                       // no effect on instance below
12
          and
13
          p no repeat ttype (
14
              .varying ttype(ttype), .captured ttype(1 ttype)
15
16
       );
17
    endproperty
```

In this variant, 1_ttype is modified in line 12. Flow rules PF4 and SF5 say that the value of 1_ttype that flows into line 14 is determined by the assignment to 1_ttype in line 9. The assignment in line 12 does not affect the instance of p_no_repeat_ttype in lines 14–16. This emphasizes the fact that changes to a local variable in the instantiating context that do not flow into an instance do not affect the evaluation of the instance (cf. Exercise 16.7).

It can be useful for the value of a local variable passed into an instance to be further modified within the evaluation of the instance. The example of Fig. 16.17 passes a local variable to an argument local variable of direction <code>input</code>. It modularizes the encoding of the FIFO protocol data check from Fig. 15.9 so that an instance of sequence <code>s_skip</code> accomplishes the skipping of occurrences of <code>complete</code> to get to the occurrence that is relevant for the current evaluation attempt

```
sequence s skip (
1
       local input bit [0:$clog2(MAX_OUTSTANDING)] numToSkip
2
    );
3
       (numToSkip > 0 ##0 complete[->1], numToSkip--)[*]
4
       ##1 (numToSkip == 0 ##0 complete[->1]);
5
    endsequence
6
7
   property p_fifo_data_check;
       dataType data;
8
       bit [0:$clog2(MAX OUTSTANDING)] numAhead;
9
       (start, data = dataIn, numAhead = outstanding)
10
       ##1 s skip(.numToSkip(numAhead))
11
       |->
       dataOut == data;
13
14
    endproperty
    a_fifo_data_check: assert property (p_fifo_data_check);
```

Fig. 16.17 FIFO protocol data check using a subsequence

of p_fifo_data_check. The local variable numAhead is assigned in line 10, and its value is then passed to the argument local variable numToSkip in line 11.

SystemVerilog also allows untyped formal arguments to be Ivalues in assignments and thereby function as local variables. The sequence s_skip from Fig. 16.17 can be recoded as shown below:

```
sequence s_skip(numToSkip);
  (numToSkip > 0 ##0 complete[->1], numToSkip--)[*]
  ##1 (numToSkip == 0 ##0 complete[->1]);
endsequence
```

The usual rules of passing actual arguments to untyped formal arguments apply in this case: the bitwidth of numToSkip for a given instance is determined by the corresponding actual argument, and there is no type checking to ensure compatibility between the formal and actual argument.

Exception for Sequence Methods

There is an exception to all of the preceding discussion of this section: it does not apply to a local variable passed to an instance of a named sequence to which a sequence method (triggered or) is applied. SystemVerilog does not allow the value of a local variable passed into such an instance to be observed by the instance. This means that the declaration of the sequence must not reference the corresponding formal argument unless the formal argument has been assigned as a local variable

⁹ In addition, a local variable passed to a sequence instance to which a sequence method is applied must be the entire actual argument passed to the corresponding formal argument and must not be passed to an argument local variable of direction **input** or **inout**.

within the sequence body. This restriction is important for the preservation of forward progress of time and causality because, in general, it is not known how the time of assignment to a local variable in the instantiating context relates to the start time of a match of the sequence to which a sequence method is applied. For example, the following contrived code is not legal:

```
sequence s_3_in_a_row(bit signal, goal);
(signal == goal)[*3];
endsequence
property p_illegal_causality;
bit l_v;
(start, l_v = a)
|-> s_3_in_a_row(.signal(b), .goal(l_v)).triggered;
endproperty
```

In line 7, this code attempts to pass the value of local variable 1_v into an instance of sequence s_3_in_a_row to which sequence method triggered is applied. The intended meaning of the code is that if start occurs, then b must equal a now and b must now have held this value for at least three cycles, including the current one. This encoding is forbidden by SystemVerilog because it requires evaluation of s_3_in_a_row to be aware of the future value of a when looking for a match to satisfy the instance to which triggered is applied (cf. Exercise 16.8).

16.5.2 Output with Local Variables

Values of local variables can be output only from instances of named sequences. There is no notion of passing values of local variables out of instances of named properties because:

- The evaluation of a property or subproperty is terminal in the sense that there is no ensuing thread of assertion evaluation.
- In general, property evaluation has no well-defined finite endpoint.

There are two mechanisms for passing the value of a local variable out of an instance of a named sequence. The first is to pass the value out through an argument local variable of direction output or inout. The following rules apply to named sequences with argument local variables of direction output or inout and their instances:

- 1. The entire actual argument bound to an argument local variable of direction output or inout must itself be a local variable to whose type the type of the formal argument can be cast. The actual argument is called the *receiver local variable* for the corresponding formal argument.
- 2. In a given sequence instance, a local variable may not be referenced more than once as a receiver local variable.

- 3. The structure of the declaration of the named sequence must guarantee that each argument local variable of direction output or inout be assigned at the completion of a match of the instance of the named sequence.¹⁰
- 4. The instance of the named sequence must not admit empty match.

If these conditions are satisfied, then at the endpoint of any match of the sequence instance, the values of the argument local variables of direction output or inout are cast-converted and assigned to the corresponding receiver local variables. If there are multiple matches of the sequence instance, then each match results in an ensuing thread of evaluation in the instantiation context with its own copies of the receiver local variables, and for each such match the receiver local variables are assigned the values of the corresponding argument local variables for that match. Rule 2 ensures that the result of these assignments is independent of the order in which they are performed. Rules 3 and 4 ensure that each receiver local variable is assigned upon match of the instance of the sequence.

As an example, suppose that we need to count the number of occurrences of dataValid that are strictly after start and not later than complete, perhaps so that a validity check can be performed based on this number and the value of ttype that appeared with start. The code in Fig. 16.18 shows how this can be done using a sequence, some occurrences, with an argument local variable of

```
sequence s cnt occurrences(bit a, local output int num a);
1
       (1'b1, num a = a)
2
       ##1 (a[->1], num a++)[*]
3
       ##1 !a[*];
4
    endsequence
5
    property p num dataValid check;
6
       transType l_ttype;
       int num dataValid;
8
q
       (start, 1 ttype = ttype)
       ##1
10
11
          s cnt occurrences (.a(dataValid), .num a(num dataValid))
12
          intersect
13
          complete[->1]
14
       )
15
       |->
16
       num dataValid OK(l ttype, num dataValid);
17
18
    endproperty
    a num dataValid check: assert property (p num dataValid check);
19
```

Fig. 16.18 Checking the number of occurrences of dataValid using local variable output

¹⁰ In particular, each argument local variable of direction **output** or **inout** must flow out of every match of the sequence expression that results from the body sequence expression of the declaration by substituting actual arguments for formal arguments, as described in the rewriting algorithms of Annex F.4 of the SystemVerilog 2009 LRM.

direction output. Is _cnt_occurrences monitors the argument a of type bit and accumulates the number of occurrences of a in the output argument local variable num_a. The sequence begins in line 2 by assigning the value of a to num_a, which accounts for an occurrence of a in the first cycle of match of the sequence. The sequence continues in line 3 with repetition of going to the next occurrence of a and incrementing num_a. This accounts for subsequent occurrences of a. The sequence ends with !a[*], which allows any number of cycles without occurrences of a at the end. Within property p_num_dataValid_check, an instance of s_cnt_occurrences, which binds dataValid to a and num_dataValid to num_a, is intersected with the goto complete[->1]. The intersection ensures that the instance of s_cnt_occurrences only counts those occurrences of dataValid that occur after start and not later than complete. In line 17, a function (or property) num_dataValid_OK is called to check that the number of occurrences of dataValid is allowable for the given transaction type captured in 1 ttype in line 9.

The second mechanism for passing out values of local variables uses untyped formal arguments. This mechanism is discouraged unless the flexibility of untyped arguments is required. If an untyped formal argument of a named sequence is used an Ivalue in a local variable assignment, then that formal argument is understood to represent a local variable. The entire actual argument passed to such a formal argument must be a local variable (the receiver local variable). The formal argument behaves like an untyped version of an argument local variable of direction either output or inout. The following variant encoding of the sequence s_cnt_occurrences exhibits this style and can be substituted in Fig. 16.18 to achieve an equivalent effect:

```
sequence s_cnt_occurrences(bit a, untyped num_a);

(1'b1, num_a = a)

##1 (a[->1], num_a++)[*0:$]

##1 !a[*0:$];
endsequence
```

The value of a local variable can be output from an instance of a named sequence to which a sequence method (triggered or matched) is applied. The rules above apply, with the additional condition that argument local variables of direction input or inout cannot appear in the declaration of such a named sequence.

Exercises

16.1. A default actual argument for an input argument local variable may reference preceding arguments in the port list of the sequence or property provided that none of the arguments referenced is an output argument local variable. Explain the rationale for this restriction.

¹¹ For formal verification, the **int** type of num_a and num_dataValid should be replaced with the type of smallest bitwidth needed for the counters.

16.2. For each of the following sequences, explain why the syntax is not legal and give an example of a legal sequence that, arguably, captures the same intent as the illegal one.

```
1. sequence s1(bit a, b, c);
      bit 1 b;
      (a, l b = b) throughout c[->1];
   endsequence
2. sequence s2(bit a, b, c);
      bit 1 b;
      a throughout (c, l_b = b)[->1];
   endsequence
sequence s3;
      byte 1 numBeats;
      (start, 1 numBeats = numBeats) ##1
         (dataValid[->1])[*l numBeats] ##1 !dataValid[*]
         intersect
         complete[->1]
      );
   endsequence
```

16.3. Explain why the following is not legal:

```
sequence s_illegal(local input bit l_a, l_b = l_a);
bit l_c, l_d = l_c;
(t, l_c = l_a) ##1 {l_a,l_b} != {l_c,l_d};
endsequence
```

16.4. For each of the following declarations, analyze the local variable flow and determine whether any references to local variables are illegal. Use rules of local variable flow to justify your analysis.

```
    sequence s1;

      byte 1 v;
      a ##1 (b, l_v \&= e);
   endsequence
property p2;
      byte 1 v;
      (a, 1 v = e)
      |->
      s nexttime s eventually (b == 1 v);
   endproperty
property p3;
      byte 1 v;
      (a, l_v = e)
      implies
      s nexttime s eventually (b == 1 v);
   endproperty
```

```
4. property p4;
    bit [1:0] l_v = e;
    a |=>
    case(l_v[0])
        1'b1: s_eventually(b == l_v);
        1'b0: c != l_v;
    endcase;
endproperty

5. sequence s5;
    byte l_v;
    (
        ( (a[->1], l_v = e) and b[->1] )
        or
        (c, l_v = f)[*1:2] ##1 !c
    )
    ##1 (d == l_v);
endproperty
```

16.5. The nonoverlapped followed-by operator #=# is defined such that for a sequence R and a property P, the passing or failing of the following two properties is equivalent:

```
    R #=# P.
    not (R |=> not P).
```

Use flow rules to show that local variable flows through these two properties is also equivalent.

- **16.6.** Use rules of local variable flow to show that v flows out of R[*0:1] iff both of the following two conditions are satisfied:
- 1. \forall flows into R[*0:1].
- 2. If v flows into R, then v flows out of R.

What can you say about the conditions for v to flow out of R[*0:n], where n is positive? What about R[*]?

16.7. Consider the following variant of p ttype check:

```
property p_ttype_check;
1
       transType 1 ttype;
2
       (start && (ttype == INV || ttype == PRG), 1 ttype = ttype)
3
       |=>
4
5
          (1'b1, l_ttype = ttype)
6
7
          #-#
          p no repeat ttype (
8
              .varying_ttype(ttype), .captured_ttype(l_ttype)
10
11
       );
    endproperty
```

Explain the local variable flow. Does the assignment in line 6 affect the instance of p_no_repeat_ttype? Compare or contrast the behavior of this property with the encoding that results by replacing #-# with and.

- **16.8.** Give a legal encoding of the intent of p_illegal_causality from Sect. 16.5.1.
- **16.9.** Recode the example of Fig. 16.18 so that the antecedent of |-> in property p_num_dataValid_check is replaced by an instance of a named sequence to which method triggered is applied. In this instance, the local variables 1_ttype and num dataValid should both be bound to output argument local variables.

Chapter 17 Recursive Properties

There is repetition everywhere, and nothing is found only once in the world.

- Johann Wolfgang von Goethe

SystemVerilog allows named properties to be recursive. A named property is recursive if its declaration instantiates itself. More generally, a set of named properties may be *mutually recursive*, which means that there is a cyclic dependency in the way that they instantiate themselves and one another. Recursion provides a very flexible framework for coding properties. In general, from a flow diagram for a desired check an encoding can be created in which certain nodes of the flow diagram correspond to named properties. If the flow diagram contains cycles, then some of the named properties will be recursive or mutually recursive. This situation occurs, for example, if the check involves retry scenarios. Unlike recursion in programming languages, property recursion does not return. It simply specifies that a thread of evaluation should begin executing the named property again. As a result, there is no stack associated with property recursion, and infinite property recursion is possible on an infinite trace. As a theoretical matter, an instance of a recursive property can be rewritten to avoid recursion. However, for complex properties, it is often simpler to write and maintain a recursive encoding, either because it is more succinct or because the assertion writer can think about the properties in a more procedural way.

17.1 Overview of Recursion

This section gives an intuitive overview of recursion based on examples.

A named property is *recursive* if its declaration instantiates itself. Figure 17.1 shows a simple example. The instance my_always(p) behaves equivalently to always p. Whenever evaluation of my_always(p) begins, line 2 causes alignment with the incoming clock, followed by evaluation of p. Line 4 has a recursive instance

¹ An instance of a recursive property can be rendered as an alternating automaton. See [34] for a sketch; restrictions on the actual arguments to recursive instances play a role. LTL augmented with regular expressions is known to be as expressive as alternating automata (see [10], e.g.).

```
property my_always (property p);
(nexttime[0] p)
and
nexttime my_always (p);
endproperty
```

Fig. 17.1 Recursive encoding of always

```
property ranged always(int unsigned low, high, property p);
1
       ranged always recur(low, high, 0, p);
2
    endproperty
3
4
    property ranged_always_recur(
       local input int unsigned low, high, cnt,
5
6
       property p
    );
7
       if (cnt <= high)</pre>
8
9
10
           (if (cnt >= low) p)
          and
11
          nexttime ranged always recur(low, high, cnt+1, p)
12
       );
13
    endproperty
```

Fig. 17.2 Recursive encoding of ranged always allowing non-constant range bounds

and causes evaluation of $my_always(p)$ to begin again after advancing to the next occurrence of the incoming clock. The use of nexttime[0] in line 2 ensures that the first evaluation of p begins after alignment with a tick of the incoming clock. From the beginning of an evaluation of $my_always(p)$, property p is checked starting at each tick of the incoming clock. Indeed, the following is an unrolling of the instances of the recursive form:

```
nexttime[0] p
and nexttime[1] p
and nexttime[2] p
```

Checking this is exactly the same as checking always p. In particular, the recursion need not end: on a trace with infinitely many ticks of the incoming clock, there are infinitely many recursive evaluations.

Suppose now that we want to get the effect of always [low:high] p in a situation where low and high are not constants. In such a case, always cannot be used. Instead, we can use a recursive property and capture the values of the expressions defining the range bounds into local variables when the property begins. Figure 17.2 shows an encoding. The recursive property ranged always recur is called from

² Alignment with a tick of the incoming clock is necessary for equivalence of my_always (p) and always p in case p has one or more leading clocks that differ from the incoming clock.

```
property my_until(property p, q);
(nexttime[0] q)
or
((nexttime[0] p) and nexttime my_until(p, q));
endproperty
```

Fig. 17.3 Recursive encoding of until

the wrapper property ranged_always, which passes its arguments through and passes 0 as actual argument to cnt. The wrapper is not necessary, but it hides cnt, simplifying instantiation and usage. In the recursive property, low, high, and cnt are argument local variables. As a result, the values of the actual arguments passed to low and high are captured when evaluation of the wrapper begins. If low and high were not local variables, then changes to their actual arguments would affect the meaning of the range while evaluation of the recursive property was underway (see Exercise 17.1). cnt is an incrementing counter that keeps track of the number of cycles that have elapsed. Line 8 checks that cnt has not yet exceeded high. When it does, the recursion ends. When cnt reaches low, checking of p is caused by line 10. The recursive instance in line 12 increments cnt in the actual argument expression.

Figure 17.3 shows a recursive encoding of until. Each time evaluation of my_until begins, either property q must evaluate to true (line 2) or both property p must evaluate to true and also evaluation of my_until must start again in the next cycle (line 4). The use of nexttime [0] in lines 2 and 4 ensures that the first evaluations of q and p begin after alignment with a tick of the incoming clock. Satisfaction of q results in satisfaction of my_until without evaluation of the recursive instance in line 4, and so it allows the recursion to stop. Until q is satisfied, line 4 must be satisfied, which implies that p must be satisfied. It is possible that q is never satisfied, in which case p must be satisfied always. Thus, my_until (p,q) has the same semantics as p until q.

Suppose that we need to check a ranged form of p until q, in which satisfaction of q must occur within a range [low:high] of cycles from the start of the evaluation. Let us denote this property p until [low:high] q. Note that this is not legal SVA code, just a notation. The property p until [low:high] q is satisfied iff there exists k, low $\leq k \leq \text{high}$, such that q is satisfied in the kth cycle from the start of evaluation and p is satisfied in every prior cycle from the start of evaluation. Figure 17.4 shows a recursive encoding of this property.

Line 2 requires low to be at most high. If low exceeds high, then the required k does not exist and ranged_until fails. Otherwise, ranged_until_recur is called in line 4. This recursive property is an adaptation of the ideas of the encoding of ranged always from Fig. 17.2 to the recursive form of my_until in Fig. 17.3. cnt is an incrementing counter of the cycle number, and it is initialized to 0 by the actual argument in line 4. Lines 13–15 mimic lines 2–4 of my until. Line 13 adds the

```
property ranged until(int unsigned low, high, property p, q);
1
       if (low > high) 1'b0 // required k does not exist
2
       else
3
          ranged until recur(low, high, 0, p, q);
5
    endproperty
   property ranged until recur (
6
       local input int unsigned low, high, cnt,
8
       property p, q
    );
9
       if (cnt == high) q // last chance to satisfy q
10
       else
11
          (q and (cnt >= low))
13
          (p and nexttime ranged until recur(low,high,cnt+1,p,q))
15
       );
    endproperty
```

Fig. 17.4 Recursive encoding of ranged until

```
property even;
(nexttime[0] p) and nexttime odd;
endproperty
property odd;
q and nexttime even;
endproperty
```

Fig. 17.5 Mutually recursive encoding of even-odd checks

Fig. 17.6 Recursive encoding of even-odd checks

condition cnt >= low. This ensures that satisfaction of q discharges the evaluation only if cnt is in the range [low:high]. Line 10 requires q to be satisfied no later than the last cycle of this range.

For the next example, suppose that we want to check that p holds in every even tick of the incoming clock and q holds in every odd tick of the incoming clock, both reckoned from the start of evaluation.

Figure 17.5 shows an encoding with two *mutually recursive* properties. Property even checks p, after alignment with the incoming clock, and in the next cycle calls property odd. Property odd checks q and in the next cycle calls property even. Figure 17.6 shows a single recursive property that performs the same check as property even.

```
property even_odd_stall(property p, q);
if (stall) nexttime even_odd_stall(p, q)
else
    p and nexttime even_odd_stall(q, p);
endproperty
```

Fig. 17.7 Recursive encoding of even-odd checks with stall

```
property p_fifo_data_check;
dataType data;
bit [0:$clog2(MAX_OUTSTANDING)] numAhead;
(start, data = dataIn, numAhead = outstanding)
##1 (numAhead > 0 ##0 complete[->1], numAhead--)[*]
##1 (numAhead == 0 ##0 complete[->1])
|->
dataOut == data;
endproperty
```

Fig. 17.8 Encoding of FIFO protocol data check using local variables

Suppose now that we want to modify the check so that cycles in which stall is true are skipped – i.e., no new check of p or q is started in such a cycle and it does not count for the reckoning of even and odd cycles. Figure 17.7 shows an encoding.

The remaining examples of this section give recursive encodings of several checks for the FIFO protocol from Sect. 15.3. Recall that the FIFO protocol requires dataIn at an occurrence of start to equal dataOut at the corresponding occurrence of complete. According to FIFO ordering, the *n*th occurrence of start corresponds to the *n*th occurrence of complete. An auxiliary variable outstanding (see Fig. 15.6) keeps track of the number of outstanding transactions, i.e., the difference between the number of preceding occurrences of start and the number of preceding occurrences of complete. The encoding of the FIFO protocol data check property from Fig. 15.9 is repeated here for reference in Fig. 17.8.

A drawback of this encoding is that the management of the local variable numAhead in lines 5 and 6 involves a somewhat tricky pattern. Figure 17.9 shows a recursive encoding of the same property.

p_fifo_data_check_recur has argument local variables data and numAhead. The instance of this property in line 2 initializes data to the value of dataIn and numAhead to the value of outstanding. Line 8 advances to the nearest strictly future occurrence of complete. At that point, if numAhead is zero, then dataOut is compared to data (line 11). Otherwise, the evaluation recurs, decrementing numAhead in the actual argument in line 13. The overall encoding of Fig. 17.9 occupies more lines than the nonrecursive encoding, but the pattern in the body of the recursive property (lines 8–13) may be more accessible than the trickier pattern in lines 5 and 6 of the nonrecursive encoding.

```
property p fifo data check;
       start | -> p fifo data check recur(dataIn, outstanding);
2
    endproperty
3
    property p_fifo_data_check recur(
       local input dataType data,
5
       local input bit [0:$clog2(MAX OUTSTANDING)] numAhead
6
7
    );
       ##1 complete[->1]
       l - >
       if (numAhead == 0)
10
          dataOut == data;
11
       else
          p fifo data check recur(data, numAhead--);
13
    endproperty
```

Fig. 17.9 Recursive encoding of FIFO protocol data check

```
typedef bit [0:$clog2(MAX_OUTSTANDING)] counterType;
1
2
    property p fifo data check(local input counterType numAhead);
       dataType data = dataIn;
3
       ##1 (numAhead > 0 ##0 complete[->1], numAhead--)[*]
       ##1 (numAhead == 0 ##0 complete[->1])
5
6
       |->
       dataOut == data;
7
    endproperty
    property p fifo all checks;
       counterType outstanding, nextOutstanding = '0;
10
11
          (start | complete) [->1],
12
          outstanding = nextOutstanding,
13
14
          nextOutstanding += start - complete
       )[+]
15
       |->
       if (start) (
17
          (!complete && outstanding < MAX OUTSTANDING)
          and p_fifo_data_check(.numAhead(outstanding))
19
       ) else ( // complete
20
          !start && outstanding > 0
21
       );
    endproperty
23
24
    initial
       a fifo all checks: assert property (
25
          p_fifo_all_checks
26
```

Fig. 17.10 Encoding of all FIFO protocol checks using only local variables

Figure 17.10 is a copy of Fig. 15.15 for reference. It shows the encoding from Sect. 15.5 of all of the FIFO protocol checks using only local variables. This encoding is subtle in the use of two local variables of type counterType

in p_fifo_all_checks. Because outstanding is managed as a local variable and updated in the repetition of lines 11–15, it is necessary to have it shadow nextOutstanding so that the appropriate value will still be available for use in the consequent (lines 17–22).

With recursion, there is more flexibility in where local variables are updated. As a result, the shadow variable can be eliminated. A recursive encoding is given in Fig. 17.11. Property p_fifo_data_check_recur is the same as in Fig. 17.9, except that the user-defined type counterType is used for numAhead. The main recursive property is p_fifo_all_checks_recur. It has a single argument local variable, outstanding, which is initialized to '0 in the instance in line 32. Line 16 advances to the next occurrence of start or complete. Lines 18–21 of the consequent update outstanding and, in the next cycle, recur with the new value of outstanding. This part of the code keeps the ongoing check running. Rules of local variable flow

```
1
    typedef bit [0:$cloq2(MAX OUTSTANDING)] counterType;
    property p_fifo_data_check_recur(
2
       local input dataType data,
3
       local input counterType numAhead
4
    );
5
       ##1 complete[->1]
6
7
        l - >
       if (numAhead == 0)
8
           dataOut == data;
9
       else
10
           p fifo data check recur(data, numAhead--);
11
12
    endproperty
    property p fifo all checks recur (
13
       local input counterType outstanding
14
    );
15
        (start | complete)[->1]
16
        |->
17
        (
18
           (1'b1, outstanding += start - complete)
19
           |=> p fifo all checks recur (outstanding)
20
       )
21
       and
       if (start) (
23
           (!complete && outstanding < MAX OUTSTANDING)
24
           and p fifo data check recur (dataIn, outstanding)
25
       ) else ( // complete
26
           !start && outstanding > 0
2.7
       );
28
29
    endproperty
    initial
30
       a fifo all checks: assert property (
31
           p fifo all checks recur('0)
32
```

Fig. 17.11 Recursive encoding of all FIFO protocol checks using only local variables

(see Sect. 16.4) ensure that the new value of outstanding from line 19 is not visible in lines 23–28. This is how the shadow variable is eliminated. Lines 23–28 perform the same checks as lines 17–22 of the nonrecursive encoding. Again, the overall number of lines is a bit greater in the recursive case, but the code patterns are easier to understand.

17.2 Retry Protocol

This section presents a write protocol with retry. The protocol involves complex checks that are handled well with recursive properties. The protocol is a variant of the retry protocol from Sect. 16.13.17 of the SystemVerilog 2009 LRM. The LRM version includes transaction tags, which allow multiple write transactions to be in flight concurrently, distinguished by their tags. Tags have already been discussed at a high level in the Tag Protocol of Sect. 15.4. The tags are orthogonal to the retry, so they have been abstracted away for simplicity. As a result, the present protocol is sequential, meaning that a new transaction cannot start while the previous transaction remains in flight. We assume that the protocol is clocked at posedge clk, as specified by default clocking. Here are the English rules:

- 1. start, dataValid, complete, and retry are signals of type logic. data is a signal of the integral type dataType.
- 2. Start of a write transaction is signaled by occurrence of start.
- 3. A write transaction has between one and MAX_BEATS data beats, where MAX_BEATS is a positive integer parameter. Data for a single beat is of type dataType.
- 4. At an occurrence of start, expected data for the associated write transaction is available in the array dataModel. dataModel is an unpacked array of MAX_BEATS entries, each of type dataType. It is declared as

```
dataType dataModel [MAX BEATS];
```

The beats of the transaction must transfer the data in the sequence dataModel[0], dataModel[1],....

- 5. Subsequent to start, an occurrence of dataValid signals a data beat. Data beats do not have to be consecutive. In a cycle in which dataValid occurs, the data for the beat is carried on the signal data.
- 6. The last data beat for the data transfer is signaled by occurrence of complete together with dataValid. complete is meaningful only together with dataValid. If complete occurs without dataValid, then it is ignored. dataValid may not occur in the cycle after the last data beat.
- 7. At any time subsequent to start and no later than the cycle after the last data beat, an occurrence of retry signals that the data transfer is forced to retry. This means that no further data beats in the current sequence may be transferred, and the data transfer must begin the sequence again, starting with dataModel[0]. The transaction itself does not restart after retry, only the data transfer.

17.2 Retry Protocol 381

Specifically, the transaction does not reassert start and dataModel is not observable after retry. There is no limit to the number of times the data transfer may be forced to retry.

- 8. The overall write transaction completes in the cycle after the last data beat provided retry does not occur in that cycle. A write transaction is said to be *in flight* beginning in the cycle after start and continuing up to and including the cycle that the transaction completes.
- 9. Write transactions must be sequential. More precisely, start must not occur while a write transaction is in flight.
- 10. If dataValid, complete, or retry occurs while no write transaction is in flight, then it is ignored.

Figure 17.12 shows a waveform for the control signals of the retry protocol. A transaction starts at time 20. Two data beats occur at times 30 and 40, and complete is signaled at time 40. At time 50, retry occurs, so the data transfer must start again. Two data beats are repeated at times 70 and 90, and complete is signaled at time 90. Since retry does not occur again, the transaction completes at time 100.

Note that the protocol makes no requirement on the number of data beats in a retried data transfer. A retried data transfer might have fewer or more data beats than a previous data transfer, even if the previous data transfer signaled complete. However, for each beat that occurs in a retried data transfer, the data must match the value predicted by dataModel.

Figure 17.13 shows a flow diagram to check the retry protocol. The flow begins with start. In the cycle of start, dataModel is captured. The flow then advances to the next cycle and invokes synchronous reject on start. If start occurs while the check is ongoing, then the check fails (rule 9). The counter i is then initialized to zero, indicating that the check expects the first data beat. The flow then advances to the nearest occurrence of dataValid or retry. If retry occurs, the flow advances to the next cycle and resets i to zero to begin the data transfer again. Otherwise, the flow checks that data equals dataModel[i]. If complete has not




Fig. 17.12 Waveform for retry protocol




Fig. 17.13 Flow diagram for retry protocol checks

also occurred, then the flow increments i, checks that the result is not too big in comparison with MAX_BEATS, advances a cycle, and returns to look for the next dataValid or retry. If complete has also occurred, then the data transfer is complete and the flow advances one more cycle, where it checks that dataValid does not occur and checks for retry at the last opportunity. If retry does not occur, then the flow is done. Otherwise, the flow advances a cycle and resets i to zero to begin the data transfer again.

Figure 17.14 shows a recursive encoding of the retry protocol checks. The encoding follows closely the flow diagram of Fig. 17.13. The outer property

17.2 Retry Protocol 383

```
property p retry check;
1
2
       dataType l dataModel [MAX BEATS];
       (start, 1 dataModel = dataModel)
3
       sync reject on(start) p retry check recur(dataModel, 0);
5
    endproperty
6
7
    property p_retry_check_recur(
       local input dataType l dataModel [MAX BEATS],
8
       local input int unsigned {\rm i}
9
    );
10
       (dataValid | retry)[->1]
11
       |->
       (dataValid | -> data == l dataModel[i]) and
13
          nexttime p_retry_check_recur(l dataModel, 0)
15
       else if (complete)
          nexttime (
17
              !dataValid and
              if (retry)
19
                 nexttime p retry check recur(l dataModel, 0)
20
           )
21
       else (
22
           (i < MAX BEATS-1) and
23
          nexttime p_retry_check_recur(l_dataModel, i+1)
24
       );
25
26
    endproperty
    a_retry_check:
                     assert property (p_retry_check);
2.7
```

Fig. 17.14 Recursive encoding of retry protocol checks

p_retry_check corresponds to the whole diagram, beginning from the start figure. The recursive property p_retry_check_recur corresponds to the subflow that is downstream from the node "goto dataValid or retry". There are three cycles in the flow diagram, and these correspond to the three recursive instances of p_retry_check_recur. The cycle on the left of the flow diagram corresponds to the recursive instance on line 24. The smaller cycle on the right of the flow diagram corresponds to the recursive instance on line 15. And the larger cycle on the right of the flow diagram corresponds to the recursive instance on line 20. Note that management of the counter i is accomplished in the actual arguments to the instances of p_retry_check_recur. With careful study of these correspondences, the reader should gain an appreciation for the simplicity of encoding flow diagrams into sets of properties, where cycles correspond to recursion.

The remainder of this section provides an alternative, nonrecursive encoding of the retry protocol checks. The encoding is shown in Fig. 17.15. The main property, p_retry_check_non_rec, is similar to p_retry_check. It captures the data model into a local variable when start occurs. Evaluation of the consequent begins in the next cycle, where sync_reject_on(start) is invoked and two properties are instantiated and conjoined.

```
property p check data xfer (
1
2
       local input dataType l dataModel [MAX BEATS]
    );
3
       int unsigned j = 0;
4
5
           (!retry && !(dataValid && complete))
6
           throughout dataValid[->1],
       ) [*]
       ##1 (!retry && !dataValid)[*]
       ##1 (dataValid, j++)
11
        |->
        (
13
          j <= MAX BEATS
          and data == l_dataModel[j-1]
15
          and if (!retry && complete)
              nexttime !dataValid
17
       );
    endproperty
19
    property p check retried data xfer (
20
       local input dataType l_dataModel [MAX_BEATS]
21
22
    );
23
           (!(dataValid && complete) throughout retry[->1] )
24
          or
25
26
              (!retry && !(dataValid && complete))[*]
2.7
              ##1 dataValid && complete
              ##0 first match(##[0:1] retry)
29
30
       ) [+]
31
       |=> p_check_data_xfer(l_dataModel);
32
33
    endproperty
34
    property p_retry_check_non_rec;
       dataType l dataModel [MAX BEATS];
35
        (start, l dataModel = dataModel)
36
        |=>
37
       sync reject on (start)
38
39
          p check data xfer(l dataModel)
40
          p_check_retried_data_xfer(l_dataModel)
42
       );
43
    endproperty
44
    a_retry_check_non_rec: assert property(p_retry_check_non_rec);
```

Fig. 17.15 Nonrecursive encoding of retry protocol checks

The first property is p_check_data_xfer, which checks the current data transfer up to its completion or to an occurrence of retry. The antecedent of |-> in lines 5 to 11 is crafted to match at each occurrence of dataValid in the current data transfer that is not strictly subsequent to an occurrence of retry or an occurrence of

dataValid && retry. Lines 5–9 match zero or more occurrences of dataValid, none together with complete. Throughout match of these lines, retry must not occur. Lines 10 and 11 match one more occurrence of dataValid. In these lines, retry must not occur strictly before dataValid. The consequent of |-> checks that the counter j has not grown too large and that data is correct. Also, it checks that if dataValid and complete occur without retry, then dataValid does not occur in the next cycle.

The second property is p_check_retried_data_xfer. This property is responsible for restarting p_check_data_xfer each time a data transfer is forced to retry. The overall antecedent of |=> is a repetition of one or more matches of the sequence in lines 24 to 30. That sequence encodes the condition that a data transfer is forced to retry. The occurrence of retry may be strictly before dataValid && complete, which matches line 24. Or the occurrence of retry may be concurrent with or in the cycle after dataValid && complete. These cases match lines 27 to 29. The antecedent has been arranged to avoid multiple matches, which could result in redundant checking of the consequent. The consequent of |=> simply instantiates p_check_data_xfer to begin checking the data transfer again.

It should be clear that the sequential conditions in the antecedents of these two properties are complex and prone to error in comparison with the recursive encoding.

17.3 Restrictions on Recursive Properties

The coding flexibility afforded by recursive properties is tempered by four restrictions on their use. The restrictions are intended to avoid recursive declarations and instances that are problematic or whose semantics involves subtleties that are beyond the scope of the current semantic framework for recursion. This section quotes the restrictions from the LRM and elaborates briefly on the rationale for them.

17.3.1 Negation and Strong Operators

RESTRICTION 1: The negation operator not and the strong operators s_nexttime, s_eventually, s_always, s_until, and s_until_with cannot be applied to any property expression that instantiates a recursive property.

In view of the Rewriting Algorithms in Annex F.4 of the LRM, this restriction also forbids the application of these operators to an expression that, through instances of nonrecursive properties, ultimately depends on an instance of a recursive property.

Restriction 1 avoids the subtle interplay between negation and recursion. Consider the following example:

```
property confounding;
   nexttime not confounding;
endproperty
```

A naïve approach to the semantics of this property leads to contradiction. For simplicity, consider the unclocked semantics (see Chap. 20) of confounding over an infinite trace $w = \ell^{\omega}$, where ℓ is a normal letter (i.e., $\ell \notin \{\top, \bot\}$). Then also $w^{1...} = \ell^{\omega} = w$ and $\bar{w} = w$. Naïvely,

```
w \models \text{confounding}

iff w \models \text{nexttime not} confounding

iff w^{1...} \models \text{not} confounding

iff [w^{1...} = w]

w \models \text{not} confounding

iff [\bar{w} = w]

w \not\models \text{confounding}
```

Clearly, something is wrong with this argument.³ SVA currently avoids the problem by imposing Restriction 1.

The strong operators are related to negation because negation interchanges weak and strong. For example, s_eventually can be defined as a derived operator according to

```
s_eventually p \equiv \text{not always not } p
```

Creating a framework for recursion that interacts well with the strong operators involves dealing with negation and liveness in recursive forms. Again, SVA currently avoids these issues through Restriction 1.

17.3.2 Disable Clause

RESTRICTION 2: disable iff cannot be used in the declaration of a recursive property.

 $^{^3}$ [34] provides an approach to negation and recursion that allows their free interplay. Additional information is provided in the declarations of recursive forms that enables the interpretation of satisfaction using either a co-Büchi or Büchi acceptance criterion. With this approach, negation need not result in language complementation. For co-Büchi acceptance, one gets $w \not\models \text{confounding}$ and $w \not\models \text{not}$ confounding. For Büchi acceptance, one gets $w \models \text{confounding}$ and $w \models \text{not}$ confounding. [34] gives sufficient conditions on recursive forms to ensure that co-Büchi and Büchi acceptance are equivalent and that negation results in language complementation. Of course, confounding does not satisfy these conditions.

disable iff cannot be nested, so its use within a recursive property declaration is forbidden. If a disable clause is needed, it should be put in a wrapper property around the recursive property or in an assertion statement. For example, the following is illegal:

```
property illegal_disable(logic b, property p);
   disable iff (b)
   p and nexttime illegal_disable(b, p);
endproperty
```

The effect of the disable can be obtained using a wrapper, as in

```
property always_with_disable(logic b, property p);
    disable iff (b)
    my_always(p);
endproperty
```

where my_always is the recursive property from Fig. 17.1.

17.3.3 Time Advance

RESTRICTION 3: If p is a recursive property, then, in the declaration of p, every instance of p must occur after a positive advance in time. In the case of mutually recursive properties, all recursive instances must occur after positive advances in time.

Briefly, recursion must occur after a positive advance in time. This restriction is intended to avoid recursive forms that get "stuck" at a single point in time. For example, the following is illegal:

```
property illegal_stuck(property p);
   p and nexttime[0] illegal_stuck(p);
endproperty
```

nexttime [0] does not guarantee an advance in time, and infinitely many evaluations of p are specified beginning in the same time-step.

17.3.4 Actual Arguments

RESTRICTION 4: For every recursive instance of property ${\tt q}$ in the declaration of property ${\tt p}$, each actual argument expression ${\tt e}$ of the instance satisfies at least one of the following conditions:

- e is a formal argument of p.
- No formal argument of p appears in e.
- e is bound to a local variable formal argument of q.

This restriction is intended to avoid problematic recursive instances that result from passing compound actual argument expressions. Such instances can lead to an explosion of distinct actual argument expressions as the recursion unfolds. Such explosion has undesirable consequences for the complexity and tractability of checking the properties.

As an example of a problematic recursive instance, consider the following example that violates Restriction 4:

```
property illegal_arg(longint unsigned u, v, w);
    u == v*w and nexttime illegal_arg(u, v+w, v*w);
endproperty
```

Since the formal arguments of illegal_arg are not local variables, they are treated as reference arguments. This means that successive recursive instances require composition of the compound actual argument expressions. Tracking the evolution of the recursion, the comparison u = v*w expands to

and so on, where the arithmetic is performed modulo 2^{64} , as specified by the unsigned longint type of the formal arguments and the rules for bitwidths in expressions. Even though the data type is bounded, the management of these expressions quickly gets out of hand.⁴

Having seen how recursion can get out of hand when Restriction 4 is violated, let us consider the intuition for why it does not when at least one of the three conditions is satisfied by each actual argument expression in a recursive instance.

If the first condition is satisfied, then the actual argument ${\tt e}$ is itself a formal argument of the declaration of ${\tt p}$. In this situation, ${\tt e}$ is simply being passed into the recursive instance of ${\tt q}$, modified at most by being cast to the type of the associated formal argument of ${\tt q}$. Iterated castings can involve some complexity, but it is benign compared to expression explosion described above.

If the second condition is satisfied, then the actual argument e makes no reference to any formal argument of p. As a result, e is composed of references to local

⁴ See [17] for an example, due to D. Bustan, that shows how a recursive form violating the restrictions can represent a language that is not omega-regular.

variables of p and references to entities outside of the declaration of p. Those entities could be static variables, named sequences or properties, functions, etc. In any case, whatever the local variables or external entities are, the meanings of references to them are the same every time the recursive instance of q is encountered. Of course the value stored in a local variable or an external static variable, e.g., may be different, but the way in which these terms are combined to form e is not changing. There is, thus, no expression explosion associated with e.

Finally, if the third condition is satisfied, then the formal argument to which e is passed is an argument local variable. Argument local variables do not have the expression explosion problem because they behave like value arguments, not reference arguments. At each recursive instance, the value of the actual argument expression is computed and stored in the corresponding argument local variable, after which the form of the actual argument can be forgotten.

Exercises

17.1. The following is a variant of the encoding of ranged always from Fig. 17.2:

```
property ranged always(int unsigned low, high, property p);
       ranged_always_recur(low, high, 0, p);
2
    endproperty
3
    property ranged always recur (
4
       int unsigned low, high,
5
       local input int unsigned cnt,
6
       property p
    );
8
       if (cnt <= high)
q
10
          (if (cnt >= low) p)
11
          nexttime ranged always recur(low, high, cnt+1, p)
13
       );
14
    endproperty
```

In this encoding, the arguments low and high of the recursive property are not local variables. How does this difference affect the meaning of the property?

- 17.2. Recode the property ranged_always of Fig. 17.2 as a single recursive property with argument local variables low and high and no other local variables. [Hint: Manage low and high as decrementing counters instead of using the incrementing local variable cnt.]
- 17.3. Recode the property ranged_until of Fig. 17.4 as a single recursive property with argument local variables low and high and no other local variables. [Hint: Manage low and high as decrementing counters instead of using the incrementing local variable cnt.]

- **17.4.** Figure 17.4 gives a recursive encoding of p until [low:high] q for general properties p and q. Give a nonrecursive encoding under the restriction that p and q are Booleans. Try to find a nonrecursive encoding for general properties p and q.
- **17.5.** Write a recursive property (or a set of mutually recursive properties) to check that properties p0, p1, and p2 hold in cycles from the start of evaluation that are congruent to 0, 1, and 2 modulo 3, respectively.
- **17.6.** Write a nonrecursive property to perform the check of property even_odd from Fig. 17.6. Write a nonrecursive property to perform the check of property even_odd_stall from Fig. 17.7.
- 17.7. Explain why p_fifo_data_check_recur in Fig. 17.9 becomes illegal if ##1 is deleted from line 11. Assuming that ##1 is deleted from line 11, explain how and why the property can be repaired by adding nexttime in line 13. [Hint: Use the fact that start and complete are mutually exclusive.]
- **17.8.** Modify the recursive encoding of the retry protocol in Fig. 17.14 so that there is a failure if dataValid, complete, or retry occurs while no write transaction is in flight. Also, check that there is never an occurrence of complete without dataValid while a write transaction is in flight.
- **17.9.** Make the same modifications specified in Exercise 17.8 for the nonrecursive encoding in Fig. 17.15.
- **17.10.** Let a and b be Booleans. Determine whether any of the following declarations or instances violates the restrictions on recursive properties.

```
property p1;
         a |-> p2;
2
      endproperty
3
      property p2;
4
         p4 and (b | -> p1);
      endproperty
6
7
      property p3;
         disable iff (reset)
8
         p4 and nexttime(a | -> p2);
      endproperty
10
      property p4;
11
         reject on (bad)
         a |=> not p1;
13
      endproperty
```

Which properties are recursive and which are nonrecursive?

17.11. Let a and b be Booleans. Determine whether any of the following declarations or instances violates the restrictions on recursive properties.

```
property p1 (sequence s, property p);
          s |=> p;
2
      endproperty
3
      property p2 (property q);
4
          q or p1(a, q or p1(b, p2(q)));
5
      endproperty
6
7
      property p3(sequence s);
          s \mid \Rightarrow p2(\mathbf{weak}(s)) \text{ and } p3(s \# 1 s);
8
      endproperty
```

Which properties are recursive and which instances are recursive?

17.12. Explain why the following code is illegal:

```
property fib(int unsigned a, b, n, sig);

if (n > 0)

sig == a and nexttime fib(b, a+b, n-1, sig);
endproperty
```

How can the declaration be modified to make it legal, while preserving the intent of the original code?

Chapter 18 Coverage

Verification may not ever be complete, but we should know what was verified.

Unknown.

An important mechanism for determining whether design validation sufficiently verified the design on hand is to collect "coverage" information, both structural and functional. This chapter describes how assertions can be used to gather functional coverage information using cover property and cover sequence statements. It is mainly suitable to collect information about the occurrences (or not) of some sequences of events. System Verilog provides another mechanism for collecting coverage, called *covergroups*. They are particularly suitable for gathering information about the occurrence of data patterns and their cross correlation. Often, it is important to detect a particular sequence of events and then initiate collecting coverage on data patterns. This can be achieved by combining assertion coverage with that of covergroups.

As we have seen, assertions and assumptions provide a precise way to state functional specification of a design and its environment. While these assertion statements may nonvacuously pass in our tests, we may still find that the design contains errors. Why is that? The answer is quite simple: In simulation, we may have not exercised all functional modes of the design, and the bugs may be hiding there. In formal verification which is exhaustive with respect to each assertion, the problem may lie in the fact that the assumptions representing the behavior of the environment are more strict than the actual usage of the design, or because the search space was restricted due to memory limitations. In either situation, we should have means to determine the extent to which the design functionality has been exercised. There are essentially two main methods for measuring this extent: Code Coverage and Functional Coverage. Code coverage is concerned with measuring the percentage of lines of code executed, which conditional blocks were executed and caused by which conditions, etc. These measures indicate how much the implementation was structurally exercised. It does not tell us whether some functionality is missing. Functional coverage, however, derives for the most part its coverage targets from the functional specification of the design.

18.1 Immediate and Deferred Coverage

The simplest form of functional coverage measurement can be obtained using immediate and deferred <code>cover</code> statements. Like the immediate and deferred <code>assert</code> statements, they can be placed in procedural code. The immediate <code>cover</code> is useful in high-level functional models and test benches, while the deferred form is preferred in RTL models because of its ability to filter out 0-width glitches. Given that the argument to a <code>cover</code> statement is a Boolean expression and is associated with the design model, it is mostly suitable to measure whether some specific expression values, or their combinations have been encountered in the model. That is, like immediate and deferred assert statements, they are closer to the implementation level than to the purely functional level.

The syntactic form of the immediate and deferred cover statements is as follows:

```
cover ( expression )statement_or_null
and
cover #0 ( expression )statement or null
```

Notice that the action block is limited to an optional pass action block since there is no notion of failure. In addition, as in deferred assertions, the action block of a deferred cover statement is limited to a single subroutine call; that is, it cannot be a block of statements. The coverage database will record the total number of evaluations of the statement and the number of times it succeeded (i.e., the expression evaluated true). The coverage database and the analysis and presentation tools built around it play an important role in assessing the quality of verification of the design. The tools usually provide means to merge coverage information from different tests, indicate which areas of the design have not yet been verified (or have no coverage collection statements), display the trend in coverage over different tests and time, and present the information in a concise and graphical manner.

In immediate covers, the statement in the pass action block executes immediately upon success of the cover statement. In deferred cover statements, however, the pass statement is limited to a single subroutine and is scheduled to execute in the Reactive region following the evaluation of the cover statement. Why is that so different from the simpler immediate cover? This is due to the glitch filtering mechanism inherent in deferred assertions. In any given simulation time-step, if a particular cover instance evaluates several times without exiting a scheduling region (Active or Reactive), only the last result upon entry to the following Observed region is reported. The pass action subroutine is scheduled in the subsequent Reactive region. For more details on simulation semantics, see Sect. 2.12. The semantics of immediate and deferred cover statements is the same as for the corresponding assert statements. See also Sect. 3.7.

¹ In fact, this should specify "subroutine call or null" due to the restrictions placed on action blocks in deferred assertions.

П

18.2 Sequence and Property Coverage

Assertion coverage statements come in two forms: cover sequence and cover property. Let us first consider the former.

18.2.1 Sequence Coverage

The syntactical form of this statement is defined in Sect. 3.7.

The body of cover sequence must be a sequence expression; that is, it may only contain an expression constructed using clock specifications, Boolean expressions, sequence instances, sequence operators, and possibly sequence match items. It may optionally contain a disable iff specification. A clocking event is optional because it can be inferred from the context. The optional pass action is executed when the sequence matches. In this case, the pass action may be any procedure and is not limited to a single subroutine call.

Example 18.1. Detect that a is followed by b within 100 clock ticks.

```
default clocking ck @(posedge clk);
endclocking
int my_count = 0;
seq_cov: cover sequence(
   disable iff (reset) a ##[1:100] b)
begin
   my_count++;
   $display("match of seq_cov at time %t",
   $time);
end
```

In simulation, an evaluation attempt is started at every tick of the clocking event, posedge clk. If a is true, then the evaluation will continue searching for all occurrences of b being true within 100 clock ticks. For each such occurrence of b a match is recorded in the coverage database. It is important to note that each match of b will be recorded as a cover for seq_cov. The simulator will also record how many attempts were started. What happens if either a is false at the beginning of an attempt or b is false throughout the range? In that case, there is no match and the match count is not incremented in the database. Thus, unlike with assert statements, failures are ignored.

The body of cover sequence may have a disable iff (expression) at the top. Like with assert property statements, the evaluation of the expression is asynchronous to the evaluation of the sequence and uses the current values of the variables appearing in the expression. Whenever the expression is true, all the evaluation attempts currently in flight or starting are disabled and record no match. In other words, in cover statements, disable iff behaves similarly to accept_on (Chap. 13), but unlike accept_on it does not use sampled values and a success is reported as "disabled".

In the above Example 18.1, whenever the sequence a ##[1:100] b matches, and provided that reset is false, the increment of my_count and the \$display statement are scheduled to execute in the Reactive region.

Despite its powerful expressive power, one has to be careful when writing such cover sequence statements. This is because the total coverage count of the matches includes multiple matches for a single attempt whenever they occur, and thus get mixed with matches from other attempts in the total coverage count. In the above example, consider a situation where a occurs at the first and then at every 5th clock tick, and b at every 10th clock tick. Suppose that there are 101 clock ticks. How many matches will be recorded? The attempts associated with the first two occurrences of a will match each 10 times, on all the occurrences of b. The subsequent 2 occurrences of a will match 9 times, etc. It can be easily seen that the total number of matches will considerably exceed the number of attempts. Furthermore, the same occurrence of b being true will account for several matches. When looking at the final count in the coverage database, the result may be difficult to interpret.

A more useful case of coverage determination is whether a was followed by a b within 100 clock ticks without any other intervening occurrence of a. The result of the coverage in Example 18.1 does not provide this information.

The coverage database for coverage on a sequence contains the number of evaluation attempts started and the total number of sequence matches. This total number of matches does not distinguish among the attempts, hence even if the total number of matches exceeds the total number of evaluation attempts, there could be attempts that had no match. Simulation tools may optionally provide a count of first matches, in which case it is possible to see whether there were evaluation attempts that were disabled or had no match.

The question is then where is the cover sequence statement useful? Our experience suggests that it is useful when an action needs to be taken for all the matches. For example to trigger evaluation of some tasks or increment counts used elsewhere in the test bench.

Efficiency Tip Unless necessary, avoid using cover sequence on sequence expressions that may result in multiple matches, such as those containing delay and repetition ranges or sequence disjunction (or).

If the total number of matches is not of interest, the cover statement can be stated using cover property as discussed next (Sect. 18.2.2).

18.2.2 Property Coverage

The syntax of this statement is **cover property** (*property_spec*) *statement_or_null* We have seen a description of **assert property** in Sect. 3.4. Similarly, the body of **cover property** may consist of a **disable iff** specification, a clocking event, and a property expression. If the property expression is a sequence, it is *promoted* to a property, meaning that the first occurring match of the sequence is transformed

into a success of the property for that particular evaluation attempt, and any further evaluation within that attempt is curtailed.

The coverage from Example 18.1 is rewritten using cover property in the following example.

Example 18.2.

```
default clocking ck @(posedge clk);
endclocking
int my_count = 0;
prop_cov1: cover property(
   disable iff (reset) a ##[1:100] b)
begin
   my_count++;
   $display("success of prop_cov1 at time %t", $time);
end
```

In this case, my_count will be incremented and the \$display statement will be executed for only the first match of the sequence in any evaluation attempt. The total number of recorded successes will thus be less than or equal to the number of evaluation attempts of the cover property. Contrast this with the behavior of cover sequence, for which the total number of recorded matches can exceed the number of evaluation attempts.

Property successes are classified as *vacuous* and *nonvacuous* (see Chap. 8 for discussion of vacuous and nonvacuous successes). Vacuous and nonvacuous successes are recorded separately in the coverage database. Therefore, the information obtained from the coverage database consists of the number of evaluation attempts started, the number of attempts in which the property succeeded nonvacuously, and the number of attempts in which the property succeeded vacuously. Attempts that were *disabled* are not counted as either vacuous or nonvacuous successes. A simulation tool may optionally provide a separate count for disabled attempts.

While much can be expressed using sequences only, property operators can provide additional expressive power. The combination of (simple) sequences and property operators helps to state clearly the intent of the coverage statement.

Example 18.3. Cover with a property expression:

```
prop_cov2: cover property(disable iff (reset)
  @(posedge clk) a |-> s_eventually[1:100] b)
begin
  my_count++;
  $display("success of prop_cov2 at time %t", $time);
end
```

The disadvantage of this form is that when a is false, there is a vacuous success of the property. Coverage of vacuous successes is not useful. The property can be reformulated using the *followed-by* operator, which is better suited for this purpose.

Example 18.4.

```
prop_cov3: cover property(disable iff (reset)
    @(posedge clk) a #-# s_eventually[1:100] b)
begin
    my_count++;
    $display("success of prop_cov2 at time %t", $time);
end
```

This example illustrates two ideas: 1) the use of the operator *followed-by* #-# for concatenating sequences with properties (the Boolean a on the left-hand side of #-# is a simple sequence), and 2) the use of strong bounded eventuality requiring the simple sequence b (implicitly cast to property) to occur within 100 clock ticks after a.

Efficiency Tip Use cover property unless all matches are absolutely needed.

Avoid using implications in **cover property** statements. Instead, either use sequences or replace the implication with a followed-by operator.

The followed-by operator is necessary when the consequent is expected to be a property or when you wish to indicate clearly the trigger sequence in the antecedent. Followed-by is particularly useful in checker libraries where the checker arguments may not be restricted to sequences only.

It is often of interest to obtain information on the conditions under which a particular coverage scenario occurred. For instance, in the above example it may be of interest to know which of the delays between a and b occurred. A simple solution is to place the coverage statement in a generate loop spanning the 100 possible delay values:

Example 18.5.

```
for (genvar i = 1; i <= 100; i++) begin : loop_delays
  prop_cov3: cover property(disable iff (reset)
  @(posedge clk) a #-# s_nexttime[i] b)
  $display(
      "success of prop_cov3 at time %t, delay i", $time, i);
  end : loop_delays</pre>
```

There will be 100 cover property statements to evaluate, each one triggering on a and then searching for the occurrence of b at the exact time specified by s_nexttime[i]. For small delay range values this is an acceptable solution. However, for larger values, like in this example, it rapidly degrades the performance in simulation. For FV, the performance impact may not be as heavy, as the individual covers become targets for reachability analysis.

For simulation there is an alternative, simpler solution. We can combine the power of temporal properties to detect patterns of signals over time with covergroups to record data and characteristics of the signal patterns. First we provide a brief introduction to the covergroup construct.

18.2.3 Covergroup

Coverage on properties and sequences is an excellent mechanism for detecting the occurrence of some specific series of Boolean values. It is not as useful for collecting data values, delays, etc. For that purpose the covergroup object is available in SystemVerilog. Not only does it allow collecting information from simple temporal sequences, but its main power is in collecting and correlating information from multiple data points. The information sampling is triggered either by some clocking event or by calling the sample method of the covergroup.

We do not present a detailed account of all the features of the covergroup object. The reader can find further details in the LRM and also in [15, 52]. We only introduce a small set of features by means of an example to illustrate the usage of covergroups jointly with cover properties to achieve an efficient implementation of coverage collection with data. The coverage collection is triggered by the successes of a cover property, and data collected from within the evaluation attempt of the property is stored using a covergroup. First let us see an example of a covergroup where sampling is triggered by a clock.

Example 18.6.

```
covergroup cover_delay @(posedge clk);
  dl_pt: coverpoint delay {
    bins delays [100]: {[10:110]};
  }
  dt_pt: coverpoint data;
  dlXdt: cross dt_pt, dl_pt;
endgroup
cover delay cover delay inst = new();
```

The covergroup definition is named cover_delay. The covergroup tracks two variables, delay and data. They are identified by using the keyword coverpoint and by labeling them dl_pt and dt_pt, respectively. The variable values are read whenever the clocking event @(posedge clk) occurs and are recorded into individual bins according to their values.

For dl_pt, there is an array delays of 100 bins into which the occurrence counts of values of delay in the range [10:110] are maintained. In other words, when the recorded value of delay is 10 the bin delays [0] is incremented; if it is, say, 100 then the bin delays [90] is incremented; etc.

For dt_pt, the bins are allocated automatically. By default, there are at most 64 bins, but that value can be changed by an optional specification auto_bin_max=number of the covergroup. If the value range of the sampled variable is less than the specified maximum, the number of bins is that of the variable range. If the range is larger than the maximum, then the variable values are uniformly distributed over the bins.

The cross correlation dlxdt of the values of delay and data is specified using the keyword cross. This defines a set of pairs of values consisting of the Cartesian product of the sets of bins of coverpoints of dl pt and dt pt. In this way, the

user can observe the correlated pairs of values of data and delay that occurred during the simulation.

The clocking event can be replaced by an interface definition of the sample method as follows:

In this case, the coverage is triggered when the method sample is called. The actual arguments must be type-compatible with the formal arguments of the method. Note that the formal argument names must match exactly those of the coverpoint variables delay and data. In this way, the same covergroup instance can read different variables passed as actuals to instances of the sample function and collect the coverage information in the same bins. Using the method is especially helpful when new instances of the variables are created over and over, as in the example in the following section where local variables are passed to a covergroup instance. When no clocking event or sample method is explicitly specified, the default sample method is available to trigger sampling of coverpoint variable values.

There are many variations on how to define parameterized covergroups, bins, crosses, conditional selection, etc. They are beyond the scope of this book, but the information provided here should be sufficient to illustrate their combined power with assertions.

18.2.4 Combining Covergroups and Assertions

We can use a **covergroup** to collect information on the delays in Example 18.5. The generate loop in that example can be disposed of as follows:

```
Example 18.7.
default clocking ck @(posedge clk);
endclocking
covergroup delay cg
 with function sample (int unsigned delay);
 dl pt: coverpoint delay {
    bins delays [100]: {[1:100]};
endgroup
delay cg delay cg inst = new();
property p_delay_coverage;
  int unsigned ticks 1;
 disable iff (reset)
  (a, ticks l = 0)
 #-#
  (ticks l <= 100, ticks l++)[1:$] ##1
  (b, delay cg inst.sample(tick 1),
    $display("prop_cov4 success, time %t, delay %d",
             $time, ticks_l)); // match item
endproperty
prop cov4: cover property(p delay coverage);
```

The main components of this form of coverage collection are:

- covergroup delay_cg definition that specifies a coverpoint on the formal argument of the method sample.
- A covergroup instance delay cg inst that creates the actual coverage object.
- A cover on property p_delay_coverage, which uses a local variable ticks_l of
 the same type as the formal argument of the sample method to count the number
 of clock ticks until b matches.
- When b matches, sample is called to classify the current value of the local variable in the coverage database.

Whenever prop_cov4 is triggered by the occurrence of a, the local variable ticks_1 is initialized to 0. ticks_1 is incremented at each clock tick thereafter until b occurs, provided it is within 100 clock ticks. When b matches, sampling of tick_1 by the covergroup takes place. The coverage database thus has two entries, one for prop_cov4 that records the total number of successes of the property and a second one for the cover point dl_pt of the covergroup instance delay_cg_inst. dl pt has 100 bins, one for each value in the delay range [1:100].

Note that in this formulation of the property, the property operator followedby #-# could have been replaced by the overlapping sequence concatenation ##0 because the consequent of #-# is a sequence. The effect is the same.

When should one use one or the other? We believe that this depends on the property to be covered. If the consequent is a sequence, use ##0 and ##1. If it is a property, use #-#, and #=#, respectively. Followed-by is also useful even with sequences when it is desired to identify clearly the trigger condition (the antecedent of followed-by) in the cover property statement.

We cannot simply substitute <code>s_eventually</code> in place of the sequence operators. The reason is that <code>s_eventually</code> provides no way to increment the local variable when the clock advances. We can still extend the formulation with <code>s_eventually</code> by adding extra code to keep a global count of clock ticks outside the assertion. We initialize the local variable to the current count of the global counter when a matches, and when <code>b</code> matches we pass the difference between the global counter and the local variable value to the sample function call. This is shown in the next example.

Example 18.8.

```
default clocking ck @(posedge clk);
endclocking
int unsigned tick_counter = 0;
covergroup delay_cg with function sample(int unsigned delay);
  dl_pt: coverpoint delay {
    bins delays [100]: {[1:100]};
  }
endgroup
delay_cg delay_cg_inst new();
always @ck
  tick_counter<=tick_counter+1;
property p_delay_coverage;</pre>
```

```
int unsigned start_tick;
disable iff (reset) @(posedge clk)
   (a, start_tick = tick_counter)
   #-#
   s_eventually[1:100]
    (b, sample(tick_counter-start_tick),
        $display("prop_cov5 success at time %t, delay %d",
        $time, tick_counter-start_tick));
endproperty
prop cov5: cover property(p delay coverage);
```

The compression of many generated cover property statements into one together with a covergroup can be applied in other situations too. For example, it is common to write the same cover statement on all bits of a vector. Instead, we can use a generalized cover property on the vectors, save the bit indices that were triggered in a local variable, and finally update the database using a covergroup. This is illustrated in the next example, where first we show the coverage collection using a generate loop and then rewrite it using a covergroup.

Example 18.9. On 32-bit vectors, cover that a rising transition on x[i] is eventually followed by y[i] asserted.

```
Solution: Using generate:
bit [31:0] x, y; bit clk;
default clocking ck @(posedge clk);
endclocking
for (genvar i=0; i<32; i++) begin : loopi</pre>
  prop cov6: cover property(
    !x[i] ##1 x[i] ##1 y[i][->1]);
end : loopi
Solution: Using a covergroup:
default clocking ck @(posedge clk);
endclocking
covergroup cg vect
  with function (bit [31:0] covered);
  vct: coverpoint covered {
    bins x0 = {covered[0]};
    ... // enumerate all bit positions
    bins x31 = {covered[31]};
endgroup
cg_vect cg_inst = new();
property p_vector_cov;
  bit [31:0] changed x, to cover, covered;
  (1, changed x=x, to cover=0, covered=0) ##1
  (1, changed x=~changed x&x) ##0
  (|changed_x, to_cover=changed_x) ##1
  (y&changed x&to cover[->1],
    covered=covered y&changed x,
    to cover=changed x&~covered) [*1:$] ##0
```

```
(covered==changed_x, sample(covered));
endproperty prop_cov7: cover property (p_vector_cov);
```

Property p_vector_cov is much more complex than the one used in prop_cov6. There are 3 local variables: change_x to record the bits that had a rising transition; to_cover to maintain information about those bits that had a rising transition and whose counterpart bit in y has not yet been set; and finally covered, which maintains the set of bits that have been covered so far. At the end, covered == changed_x. When that occurs, the covered bits are sent to the covergroup instance and recorded.

There are two issues with this encoding that need some remedy. First, if for one of the bits of x that had a rising transition the counterpart bit of y is never asserted, then no coverage is recorded. It is better always to sample when some match occurs inside the repetition loop. The second issue is in the declaration of the covergroup. There is no way to "generate" a set of bins in a loop; they must be enumerated. To remedy this issue, a task can be created that decodes which bits are set in covered, and then calls method sample for each such bit, passing its index. The task is then called from the property in place of the sample method. The covergroup must be modified so that the index into the vector is the coverpoint variable and it has as many bins as the width of the vector. Both of these improvements are left as an exercise at the end of the chapter.

In the following section, we examine effects of strong and weak properties in cover property statements.

18.3 Coverage on Weak and Strong Properties

An important enhancement to SystemVerilog Assertions is the explicit notion of property *strength* (see Chaps. 8 and 11). In simulation, the impact of strength is seen on the result of property evaluation at the end of simulation, or more specifically, when there is no further clock tick. In the case of cover property statements, an evaluation attempt of a strong property for which there are not enough clock ticks to reach a definitive decision yields the result *not covered*. This is unlike in assert property statements, where such a situation leads to a failure of the evaluation attempt.

When a sequence s is implicitly promoted to a property by using it in the statement cover property(s), the interpretation is as cover property(strong(s)). It means that if the first match of the sequence is not reached when the last clock tick occurs, that attempt is not counted as covered. Recall that the statement assert property(s) interpretation is as assert property (weak(s)), meaning that if a match is not reached when clock ticks stop, the result is a success of the assertion.

An interesting situation occurs if a cover property statement is placed in a conditional branch of an always procedure, as shown in the following example.

Example 18.10. Cover in an always procedure

```
always @(posedge clk) begin
  if (!en) ... some code...;
  else begin
    c: cover property(a ##1 b);
    ... some other code ...
  end
end
```

The cover property is sampled using posedge clk, but an evaluation attempt will only start when control reaches the location of c in the procedure. That may or may not ever happen, hence the overall effect of the cover within the procedural code is similar to having written a static cover containing the property s_eventually(a ##1 b). The eventuality occurs when the procedure does execute the corresponding branch.

The next and final section provides two more complex examples.

18.4 Examples

Example 18.11. Recall the specification from Chap. 1, Fig. 1.6:

The system consists of a transmitter and a receiver connected by a point-to-point duplex channel. The transmitter sends to the receiver packets and gets an acknowledgment from the receiver upon the packet receipt. The packet contains a header and a body. The header consists of 8 bits, and the two most significant bits contain information about the transaction type: data (10), control (01), or void (00). The remaining six bits of the header contain the transaction tag in case of a data transaction, and are 0 in case of a control transaction. For void packets the tag field may contain any value. The packet body consists of three bytes; these bytes contain raw data for data transactions and commands for control transactions

Upon receipt of a data or a control packet the receiver sends back to the transmitter an acknowledgment signal. The acknowledgment consists of 7-bits: the most significant bit is set to 1, and the remaining 6 bits contain the tag of the received packet. If a void packet is received, its contents are ignored and no acknowledgment is sent ...

The transmitter is not allowed to send a new packet before an acknowledgment is received. If timeout is reached, the transmitter sends the same packet again. If after three retries it does not get an acknowledgment, it asserts the error signal and requires a manual reset.

We can now enhance the checker in Fig. 1.6 to include collection of coverage information to make sure that the behavior of the design is sufficiently exercised by simulation tests. The enhancements are shown in Fig. 18.1.

Property tx_rx_ack describes a situation in which a packet sent of the type kind_t having a particular tag eventually receives an acknowledgment. The correspondence between the sending packet tag and the acknowledged tag is assured by using the local variable tag in the property. It is assigned the tag of the transmitted packet at the time when sent is true and then checked when an acknowledgment arrives. Only when the tags match does the property succeed, and then the coverage count in the database is incremented.

18.4 Examples 405

```
typedef enum { kind info = 2'b10, kind control = 2'b01,
         kind void = 2'b00, kind forbid = 2'b11 } kind t;
     typedef logic [5:0] tag_t;
2
     typedef logic [23:0] data t;
3
     typedef struct { kind t kind; tag t tag; data t data; }
4
         packet t;
     typedef struct { logic ack received, tag t tag } ack t;
5
6
     checker spec (
       packet t tx packet, // Packet to be transmitted
                            // Last received packet
       rx packet,
9
                            // Packet sent
       logic sent,
10
                           // Acknowledge
       ack_t ack,
11
                           // Timeout active
       logic timeout,
12
                           // Error signal
       logic err,
13
                            // System clock
       event clk,
                            // Reset
       logic rst);
15
       default clocking @clk; endclocking
17
       default disable iff rst;
18
19
    ...same as before...
20
21
     // coverage of different packet types
22
     let packet sent type(packet t packet, kind t kind) =
23
       sent && packet.kind == kind;
24
     cov_kinds_tx_info: cover property(
25
       packet_sent_type(tx_packet, info));
26
     cov_kinds_tx_void: cover property(
27
       packet_sent_type(tx_packet, void));
28
29
     cov kinds tx control: cover property (
       packet sent type(tx packet, control));
30
31
    // coverage of packet types transmission and acknowledgment.
32
     property tx rx ack(kind t kind);
33
       tag t tag;
34
       (sent && tx packet.kind == kind, tag = tx packet.tag) #=#
35
           s eventually(ack.ack received && ack.tag == tag);
36
     endproperty
37
38
     cov sent ack info: cover property(tx rx ack(info));
     cov_sent_ack_void: cover property(tx_rx_ack(void));
40
     cov sent ack control: cover property(tx rx ack(control));
41
42
     endchecker : spec
```

Fig. 18.1 System specification with coverage

The next example illustrates another important point regarding the combined power of cover property and the covergroup construct. It shows that this scheme can save on coding effort, reduce simulation time, and consolidate reporting. The example uses a simplified $N \times N$ switch.

Example 18.12. A switching device has $N \le 256$ 8-bit input ports and $N \le 256$ 8-bit output ports arranged in packed arrays:

```
logic [N-1:0] [7:0] dataIn;
logic [N-1:0] [7:0] dataOut;
```

A packet consists of 256 8-bit bytes. Each packet enters the switch on one of the input ports and leaves the switch on one of the output ports. Packet data is transmitted one byte at a time across a port. The first byte of a packet contains the source ID where the packet originated. The second byte contains the destination ID where the packet is to be routed after it leaves the output port. A 1-bit signal is associated with each input and output port indicating the start of a packet. Vector bit [N-1:0] startIn is used for input ports, while bit [N-1:0] startOut is used for output ports. Bit i of either port is set to one when the first byte arrives. At all other times the bits are set to 0. The incoming data are all synchronized to posedge clkout. There is a delay of at least 2 clkIn cycles before a packet can emerge on an output port. For

```
parameter N = 4;
1
   property path cover(inIdx, outIdx, sourceId, destId);
2
       @(posedge clkIn)
3
            (startIn[inIdx] && sourceId == dataIn[inIdx]) ##1
4
                (destId == dataIn[inIdx])
5
            ##0
6
       @(posedge clkOut)
7
            (startOut[outIdx] && dataOut[outIdx] == sourceId) ##1
8
                 (dataOut[outIdx] == destId);
   endproperty
10
11
   generate
     for (genvar pIn = 0; pIn < N; pIn++) begin : PORT IN</pre>
13
       for (genvar pOut = 0; pOut < N; pOut++) begin : PORT_OUT</pre>
14
15
          for (genvar sId = 0; sId < 256; sId++) begin : SOURCE ID</pre>
            for (genvar dId = 0; dId < 256; dId++) begin : DEST ID</pre>
16
              cover path:
17
              cover property(path_cover(pIn, pOut, sId, dId));
18
            end
          end
20
21
       end
     end
22
   endgenerate
```

Fig. 18.2 Coverage using generate loops

18.4 Examples 407

simplicity, we assume more specifically that the first byte of a packet will appear on one of the output ports at the first posedge of clkOut at or after the posedge of clkIn when the second byte of the packet appeared on its input port.

It is required to construct a coverage collection system such that correlated information is collected about which source ID and destination ID appeared in a packet, together with the input port and output port through which the packet was routed in the switch.

```
parameter N = 4;
1
   covergroup pathCg with function sample
2
    (bit [7:0] inIdx, outIdx, logic [7:0] sourceId, destId);
3
     cross inIdx, outIdx, sourceId, destId;
4
5
   endgroup
   pathCg pathCg inst = new();
   task samplePathInfo(
     bit [N-1:0] inIdx lv,
8
     bit [7:0] outIdx,
     logic [N-1:0][7:0] sourceId_lv, destId_lv); logic [7:0]
10
         outSourceId lv, outDestId lv;
     int i;
11
     for (i=0; i<N; i++) begin
12
       if (inIdx_lv[i] && (sourceId_lv[i] == outSourceId_lv)) begin
13
                         && (destId lv[i] == outDestId lv)
14
         pathCg inst.sample(i, outIdx, sourceId lv[i], destId lv[i
15
              1);
         break;
16
       end
17
     end
18
   endtask
   property path cover(outIdx);
20
     logic [N-1:0][7:0] sourceId lv, destId lv;
21
       bit [N-1:0] inIdx lv; logic [7:0] outSourceId lv;
22
       @(posedge clkIn)
23
          ((|startIn), inIdx lv = startIn,
24
                       sourceId lv = dataIn) ##1
25
            (1'b1, destId_lv = dataIn)
26
          ##0
27
       @(posedge clkOut)
28
          (startOut[outIdx], outSourceId_lv = dataOut) ##1
29
             (1'b1, samplePathInfo(inIdx lv, outIdx,
30
                                    sourceId lv, destId lv,
31
                                    outSourceId lv, dataOut));
32
   endproperty
33
   generate
34
     for (genvar i = 0; i < N; i++) begin : PORT OUT</pre>
35
       cover_path: cover property(path_cover(i));
36
     end
37
   endgenerate
38
```

Fig. 18.3 Coverage of packet paths using a cover property and a cover group

Discussion: A simple approach is to define a property that characterizes one path of a packet from one input port to one output port, and use a generate loop to build as many instances of a cover property as there are possible combinations of paths through the switch and IDs. This is shown in Fig. 18.2.

While the definition of this coverage model is quite concise and simple encode, it will impose a heavy burden on the simulator and will most likely produce a coverage report that is long and difficult to analyze. Even with a small N=4, the packet path coverage for this 4×4 switch will generate $4\times 4\times 256\times 256=2^{20}$ cover properties, all running at the same time.

Perhaps it is not necessary to track all source and destination IDs, hence the number of cover properties can be reduced. Still, the overhead may be large. A better and more elegant solution can be obtained by combining N cover property statements, one for each output port of the switch, with a covergroup that collects the coverage of paths. This is shown in Fig. 18.3.

The combination of N cover properties with a single covergroup provides a speed up of up to 2^{18} for a 4x4 switch over the simplistic solution using nested generate loops. Furthermore, the coverage report generated for the covergroup will nicely summarize which paths were covered and how many times. This is due to the cross statement in the covergroup.

Exercises

- **18.1.** For Example 18.11, write a cover property that records that a retry occurred.
- **18.2.** For Example 18.11, write several cover property statements that record the number of retries that occurred (from 1 to 3).
- **18.3.** Write a single cover property that records the same information as 18.2 with the help of a covergroup.
- **18.4.** Write a cover property and a covergroup that record which tags were used with which tx packet kind.
- **18.5.** Modify the cover property and the covergroup in Example 18.8 to remedy the two issues raised there.
- **18.6.** Write two cover property statements that record whether between two conditions, a and b, where b follows a by some indefinite number of clock ticks, the condition c occurred and not occurred, respectively.

Chapter 19 Debugging Assertions and Efficiency Considerations

If everything seems to be going well, you have obviously overlooked something.

- Steven Wright

Properties and sequences allow us to describe complex behaviors in a very compact declarative form. That form is quite different from the procedural style used for writing RTL and other design models as well as test benches. Thus, assertions may also need a different style for debugging them. Issues related to the runtime and memory overheads for complex temporal assertions also need to be addressed. The same behavior may be expressed using different assertions. Each may have different efficiency in formal verification and simulation. We discuss both debugging and efficiency in this chapter.

There are two kinds of situations to consider (see also [15]):

- A failure for an assertion from a checker library or a user-written one. Failure of
 an assertion from a library usually points to a problem in the design under verification, assuming that the library was validated. User-written assertion failure
 may be due to a design error or an incorrect formulation of the assertion.
- A failure for an assertion under development or during regression that needs to be analyzed. Failure of an assertion under development usually means a failure during specific simulation tests created to validate the assertion before use in verifying a design. Failure during regression is more likely to be due to an error in the design, assuming that the assertion was validated.

Developing assertion-based checkers uses similar techniques for the development as for custom assertions. The main difference is that the testing and documentation must be quite extensive as demonstrated, for example, in the Accellera OVL checker library [8]. In either situation, effective means must be provided to pinpoint the source of the problem. Verification tool vendors often provide various tools to view and debug assertions, however, in this book we are tool-agnostic and assume only that tools generally provide waveforms for viewing with some marking that identifies the start time and the end time of an evaluation attempt. To gather a more insightful view of the failure, we rely on means within the SV language to provide us with further information on the progress of the failing attempt. Debugging is usually done in simulation, even though the assertion may be developed for or may have failed in formal verification.

In the following sections, we address two scenarios: one, for debugging an assertion during its development, and the other, for debugging a failing assertion in a regression test for a design.

19.1 Debugging An Assertion Under Development

The starting point of any debugging effort while developing a custom assertion is a good requirement specification that states the trigger conditions and the sequence of signal combinations that must hold following the trigger. Based on this information, a simple test bench should be developed. If the assertion is complex, a random test bench is preferable, since a completely exhaustive test may be impractical. This guideline is similar to developing a test bench for verifying a design. While inspecting the results from simulating the assertion with the test bench, we must be careful to identify and verify any unwanted vacuous successes and incomplete evaluations.

The next step is to change the test bench to generate erroneous situations that induce assertion failures, while avoiding the acceptable ones as much as possible. This step is much harder, because the number of possibilities of failure may be quite large and the resulting test bench may unavoidably contain acceptable situations in which the assertion succeeds. It is these successes that must be scrupulously analyzed for validity.

Suppose that either an invalid success or failure is detected. Now, one needs to isolate the particular invalid attempt so as to not clutter the debugging information by data from other attempts, and to observe the progress of the evaluation of that attempt. Since most simulators provide information about the start time of a failing/succeeding attempt, that time can be used to control the starting and stopping of the assertion using the control system tasks \$assertoff and \$asserton (see Chap. 6). Assuming that the test bench is repeatable, the assertion should be stopped from time 0 using \$assertoff till just before the start time of the attempt of interest at which point it should be started using \$assertoff for just one clock tick, and thereupon stopped again using \$assertoff. This will start exactly the single attempt of interest.

Once the invalid attempt is isolated, we can instrument the assertion by adding local variables for collecting data, using match items in sequences to assign and display signal values, and use action blocks to display any additional information about the failure or success of the assertion. The number of possibilities is quite large to describe it in all generality; therefore, we shall illustrate the process using an example.

Suppose that we need to debug an assertion written according to the following requirements: When req becomes asserted for one clock cycle it is associated with a transaction id req_tag, the acknowledgment ack is also associated with a similar id ack_tag that establishes correspondence with the request having the same id. ack must arrive no later than 18 cycles after the req. Acknowledgments can arrive out of the requesting order.

П

Let us assume that the assertion has the following form:

Clock ticks occur at times 1, 3, 5, An unexpected failure happened for the attempt starting at 105, ending at 141. That is, the failure occurred at the limit of 18 clock cycles after req was received. Is the failure genuine?

Making association between the failure and the sequence of values is laborious, so we opt for instrumenting the assertion and the test bench.

```
Example 19.2. default clocking ck @(posedge clk);
endclocking
initial begin // add to the test
 $assertoff():
 #104;
 // start assertion just before
 // the start time of failure
 $asserton();
 #2;
 // stop assertion right after
 // the failing attempt at time 105
 $assertoff();
end
property p;
 logic [3:0] tag;
  (req, tag = req tag, // make sure it triggered
   $display("[%t] req asserted, tag %0d", $time, tag))
      s eventually [1:18] (ack && (ack tag == tag));
endproperty
a: assert property (p);
property p_cover;
    logic [3:0] tag;
    (req, tag = req tag,
    $display("[%t] req asserted, tag %0d", $time, tag))
      ##[0:$]
        (ack && tag == ack tag,
        $display("[%t] ack asserted, ack_tag %0d",
                 $time, ack tag));
endproperty
c: cover property (p cover);
```

The additional code stops the assertion at the beginning, starts it for one clock tick, and then again stops it. We added \$display to the assertion to make sure that it does trigger (and fail) as observed originally. Finally, we added a cover property that

searches for ack with the matching tag indefinitely from the time of the occurrence of req. The objective is to see whether ack ever arrives.

After running the simulation, we observe that the assertion and the cover triggered as expected, the assertion failed and the cover matched very quickly on the next clock tick at time 107. Assuming that the test is generating legal situations only, it suggests that the assertion missed the arrival of ack associated with the matching req. By examining the assertion, we can see that in fact the bounded eventuality starts checking only 2 cycles after the req arrival due to the one cycle delay introduced by |=>, and then another cycle by the lower bound of 1 in s_eventually. An easy correction is as follows:

```
Example 19.3. property p;
logic [3:0] tag;
(req, tag = req_tag)
    |=>
        s_eventually [0:18] (ack && (ack_tag == tag));
endproperty
a: assert property (p);
```

The solution brings out a question: Can the acknowledgment arrive with 0 delay? The requirement specification did not mention anything about the earliest arrival. This issue has to be clarified. If the answer is that the acknowledgment can be generated combinatorially with 0 clock tick delay, then |=> should be replaced by |-> in the assertion. What should happen if ack arrives at the same time as req and with the same ack_tag value as the value of req_tag? If this situation is illegal, then the assertion should be modified to reject it as shown in the next example.

```
Example 19.4. property p;
  logic [3:0] tag;
  (req, tag = req_tag)
    (
      s_eventually [1:18] (ack && (ack_tag == tag))
      (!(ack && (ack tag == tag)))
    );
endproperty
a: assert property (p);
                                                                   Or even more simply as
property p;
  logic [3:0] tag;
  (req, tag = req tag)
    ->
    strong(
      !(ack && (ack_tag == tag)) ##1
      ##[1:18] (ack && (ack tag == tag))
    );
endproperty
                                                                   П
a: assert property (p);
```

An alternative that may be more efficient with formal verification tools is to separate the two cases into two independent assertions.

```
Example 19.5. property p1;
  logic [3:0] tag;
  (req, tag = req tag)
    |->
    (
      s_eventually [1:18] (ack && (ack_tag == tag))
    );
endproperty
property p2;
    logic [3:0] tag;
    @(posedge clk) (req, tag = reg tag)
        !(ack && (ack tag == tag));
endproperty
al: assert property (p1);
a2: assert property (p2);
```

Finally, what if the lower bound is greater than 1 clock cycle, e.g., 3? A possible solution to eliminate the unwanted early arrivals is to use a bounded always operator as follows:

This could again be written using a strong sequence as follows:

```
property p;
  logic [3:0] tag;
  (req, tag = req_tag)
    |->
    strong(
      !(ack && (ack_tag == tag))[*2] ##[1:16]
      (ack && (ack_tag == tag))
    );
endproperty
a: assert property (p);
```

An option is to separate the two clauses into two independent assertions as shown in Example 19.5.

In the following section, we briefly discuss debugging assertion failures that occur during a test of a design.

19.2 Debugging Assertion Failures of a Test

Without specialized debugging tools that vendors may provide, a similar technique to the one in the preceding section can be used. The failure can be due to either an incorrect assertion or an error in the design. One difference in debugging is that there may be many assertions (that fail or not) and that rerunning the test may become quite demanding on resources and time. In this scenario, we do not construct a new test bench, but continue with the same failing test.

Assuming that rerunning the test either with its original design or from a saved signal dump is possible, we can concentrate on the particular assertion failure. If there are more than one failure of the same assertion in the run, we start with the first one that is not due to some clearly apparent reason like neglecting to stop the assertion during the reset phase.

There are three possible ways to approach the debugging problem:

- 1. To concentrate on that failure, we should stop all assertions at time 0, and then start only the one of interest just before the clock tick associated with the start time of the failing attempt. We will thus need to specify the complete path to the assertion in the call to \$asserton as well as to the subsequent \$assertoff that shuts it off just after the attempt started. These calls can be placed in a new top-level module that is used only for this assertion control. We also instrument the assertion following the ideas shown in Example 19.2.
- 2. An alternative is to shut off all assertions and add a copy of the instrumented failing assertion into the new top-level module. The actual arguments then must be stated as hierarchical references to the signals in the original assertion. This approach has the advantage that we do not modify the design in any way.
- 3. Alternately, we could make the new control module with ports that correspond to the signals used in the assertion, and instrument the same assertion but referring to these ports. We bind the new control module to the module instance that contains the failing assertion. Care must be taken to control just the instrumented assertion using the \$asserton and \$assertoff calls.

19.3 Efficiency Considerations

Depending on whether an implementation of assertions in simulation takes the attempt-based view, different forms of assertions expressing the same requirements may have different compile-time and run-time performance. Each simulator may have different forms of implementation; nevertheless, there are some general situations that can be exposed. We base this exposition on three abstract implementations of the assertions:

1. Assertion is an observer that issues only the fail result with no information about attempt start time of failure. No failure in simulation means success.

- 2. Assertion issues only the fail result with information about the earliest or latest attempt start time of the failure at a specific time (more than one attempt can reach a failure at the same time by the same condition). No failure in simulation means success.
- 3. Assertion is evaluated by maintaining information about all attempts, their start times and fail/pass times.

An abstract implementation of the first kind may be achieved by compiling the assertion into a single automaton of the negated property, as typically done for formal tools (Sect. 11.4.1). When the automaton is evaluated it may only provide information on the first failure detected and its failure time and perhaps the earliest/latest start time as indicated by the 2nd bullet above. Only on Boolean assertions of the form assert property (expr); both times would be exact.

For the third kind of implementation, it is possible to compile the assertion into processes that interpret the syntactic form of the property. An evaluation attempt would start at every tick of the leading clock, noting its time and then, when it succeeds or fails, it would report the result and the start and fail times.

Naturally, these are descriptions of abstract implementations, and a particular simulator may have a mixture of approaches. For example, there may be a different algorithm to evaluate Boolean concurrent assertions than that for evaluating complex or recursive properties (Chaps. 8 and 17). Local variables may be another dimension to the implementation spectrum (Chap. 15).

When local variables are involved, the purely automaton-based evaluation may not be feasible for at least two reasons. First, determinizing the automaton may not always be practically feasible, and second, evaluating a nondeterministic automaton requires keeping track of which transitions are to be combined with the same set of local variable values.

Compile-Time Performance

In general, the complexity of the automaton needed in implementations (1) and (2) can grow exponentially with the size of the property as measured by the number of operators and expressions in the property. However, implementation (3) based on the interpretation of the syntactic structure remains linear in size. This implies that form (1) for really complex properties involving nested property and sequence operators may take prohibitive time to generate. The final representation may also consume large amounts of memory, especially when large delay ranges are involved or there is a large set of choices due to an or operation or large ranges. This is one of the important efficiency considerations for formal verification to limit the size of ranges of delays (##) and repetitions of all kinds ([*[..]]) (see Sect. 11.4.1).

Run-Time Performance

In general, evaluation based on automata, especially if the automata are determinized, will yield higher performance, because there is minimum work involved in evaluating an expression and then advancing to the next state. When failure is detected, the simulator just reports the result and aborts further evaluation.

For the evaluation that keeps track of attempts, the simulator must maintain information about attempt start times, the local variable values if any, as well as information about multiple threads of evaluation within an attempt. This consumes both time and memory.

In the following, we examine several typical cases that may have different runtime performance based on the algorithm scheme used for the implementation. In the preceding chapters, we often raised performance issues as "efficiency tips". We thus revisit some of them and provide explanation why it is so based on the abstract implementations.

• Fixed delay or repetition values ##N as well as [*N] for some large N.

In an automaton-based implementation, large values used in these operators that also include [->N], [=N] create at least N states with transitions arranged in a similar way as in counters. If used within other operators such as intersect, within, and, or the memory requirements both at compilation and at run time can rapidly grow.

In a process-based implementation, compilation may not be costly, but if such structures are part of an assertion that can create many overlapping attempts or threads then the result can be a growing number of concurrent processes and/or data structures that have to be allocated and evaluated at runtime.

• Ranges ## [M:N] b as well as [*M:N], for some large N>M

The problem is similar to the preceding case, yet somewhat worse because of the implied nondeterminism representing a disjunction of fixed delay or repetition ranges. In this case, not only the value of N is of importance but also the span N-M+1 of the range itself. The consequences on compilation and run-time performance are significant.

• Unbounded delay at the beginning of an antecedent ##[*] s |-> p

The interpretation of this property reads as follows: Upon each occurrence of sequence s, property p must hold. If this property is used in an assertion outside an initial procedure, the assertion will evaluate the whole implication at every clock tick.

In an implementation that does not keep track of attempts and reports failures only, it may not cause problems since the multitude of evaluation threads that have equivalent next states is collapsed into one evaluation. However, the assertion evaluation may not complete in simulation if it does not fail in one of the evaluation

attempts of p. The presence of a local variable further complicates the task of reducing the number evaluation threads, as the value of the local variable may not be the same in all threads.

The situation is quite different in process-based evaluation that does keep track of attempts. Here, if s and p are of temporal nature spanning several clock ticks, there can be a rapid accumulation of processes, each doing essentially the same thing, but needing to keep track of the attempt start times. Notice that unless p fails all attempts will keep evaluating till the end of simulation.

Possible solutions are:

- Place the assertion into an initial procedure thus creating only one evaluation attempt. Only the first failure will be reported.
- Remove ##[*] from the antecedent because it is redundant for assertions that trigger at every clock tick.

Another problematic case is the occurrence of large delays in \$past:

• Sampled value function \$past (exp, N), for some large N.

The sampled value function can be viewed as a shift register of length N. The first stage is loaded by the sampled value of \exp at every clock tick. The last stage provides the value of the function past . Therefore, the number of state bits is equal to $\operatorname{bits}(\exp) * N$. This may create a large state space for formal verification (Chap. 11). For simulation, the issue is more related to the cost of updating the N registers.

• Using \$rose(exp, \$global_clock) or \$rising_gclk(exp)

As the names of these functions imply, they differ by the clock tick at which they indicate that the least significant bit of exp changed to 1'b1. \$rose evaluates to true at the clock tick when the least significant bit of exp has risen, while the future value function \$rising_gclk evaluates to true at the tick that precedes the tick when the signal rises, i.e., when the least significant bit of exp is to rise.

Future value functions are more efficient in FV because in the automata representation of the overall property, the next-state is already encoded in the automaton. If past-value functions, e.g., \$rose are used, then the implied past-value register is created independently of the property automaton and thus adds one state bit to the overall state space. If many such functions are used, it may impact the performance of FV. For future-value functions, no such extra registers are needed. Furthermore, the future value functions often simplify the formulation of stability properties, make them more easily understandable, e.g., Example 6.30.

In simulation however, the effect on performance can be quite different. Simulation cannot know the value a signal will have at the next clock tick, it can only evaluate the present and store the past values. Therefore, if a future value function is used in a property, the compiler must shift the entire property evaluation by one global clock tick into the past. Furthermore, the reported failure times must be adjusted to values as if the evaluations were actually based on the future value functions, i.e., shifted by one clock period of the global clock. However, in general

that global clock period is not known and must be computed by the simulator. This processing adds overhead in simulation.

• Ranges in always [M:N] p as well as eventually [M:N] p, for some large N>M (see Chap. 8).

As before, large upper bounds N and large span N-M+1 increase the state space, and, in an attempt-based evaluation, if the assertion retriggers while previous evaluations are still in progress, the run-time performance can be significantly affected.

• Trigger by level req |-> p or by value change \$rose (req) |-> p

In many situations, \$rose(req) is a more efficient form as it only triggers evaluation on a change.

As mentioned earlier, the use of sampled value functions implies additional registers. However, to avoid false firing at time 0, it may be necessary to shift the antecedent as ##1 \$rose(req) (see Chap. 6).

• Property and versus sequence and in seq 1 and seq 2 (see Chap. 8)

In an automata-based implementation, sequence and requires performing intersection of the argument sequences. Depending on the complexity of these sequences, the resulting automaton may be quite large, thus requiring more memory to represent, as well as slowing down the compilation. Therefore, if and is the top-level operator in the consequent property then it is more efficient in both simulation and formal verification to replace the sequence and with a property and. It is also likely that the verification tool, formal or simulator, does the replacement automatically.

• Properties ending with open-ended intervals such as

```
##[M:$] s and s eventually p.
```

An open-ended interval in a property implies that the tool will be searching for satisfying the arguments s and p, till the end of evaluation. If it cannot be satisfied in simulation it will run till the end. Depending on the strength of the operator, it will report a success (weak property) or failure (strong property). That is, the property cannot fail (if at all) until the end of simulation. If the evaluation of such an openended operator is repeatedly retriggered, this will cause accumulation of attempts and threads. In simulation, open-ended intervals should be replaced by a reasonably bounded range, while in FV, open ranges are much preferred because they add only few states to the automaton.

Exercises

19.1. Assertion a: assert property (en ##1 !y[+] | -> x) had attempts start at 1, 2, 3, 4 all of which succeeded at time 5, but the attempt that started at time 5

failed at time 6. What could be the problem? Is it a problem in the design or in the assertion formulation? Explain each of the cases.

- **19.2.** Assertion a: assert property(trig |-> s_eventually(sig)); failed at the end of simulation for several attempts. What is the reason for the failure and what could be the remedy(ies)?
- **19.3.** The example in Chap. 17, Fig. 17.14 fails. How would you debug the failure in simulation?
- **19.4.** If a checker like the assert_handshake in Chap. 23 fails, how could you approach debugging the failure (a) if you have access to the source code of the checker, and (b) if you do not have access to the source code.
- **19.5.** Suppose that the assertion in Exercise 19.1 failed in formal verification by model checking. What means you may have to debug it?
- 19.6. Will property req |-> s_eventually ack be efficiently evaluated in simulation if it is required to provide full attempt information (start and fail/success times)? Does it depend on the protocol? That is, when req is a single clock tick pulse vs. when req should hold asserted until and including the assertion of ack? How would it perform in formal verification?
- **19.7.** In the preceding problem, if req is to remain asserted until ack is asserted, is it important to you that an assertion using the preceding property reports all the start times of attempts that succeeded at the same time when ack is asserted? Should it report the earliest or the latest such start time only?
- **19.8.** Suppose that req must remain asserted until and including ack is asserted, how could you modify the property in Exercise 19.6 to trigger only once for a given req ack pair?
- **19.9.** Can you identify other properties that may have impact on simulation performance depending on the form of evaluation and the amount of detail provided about the start and fail times of succeeding and failing attempts of the associated assertion(s)?

Chapter 20 Formal Semantics

I don't want to get bogged down in semantics causing problems.

- Pervez Musharraf

To enable formal verification of assertions, the assertions must be formally defined: it must be possible to unambiguously tell whether a specific DUT behavior satisfies a given assertion or not. The formal definition of the meaning of an assertion is called its *formal semantics*. Our intuition works well for simple assertions, but to understand the exact meaning of complex assertions requires knowledge of the formal semantics. This chapter is dedicated to the description of the formal semantics of sequences, properties, and assertions.

This chapter can be skipped on the first reading, but those who wish to obtain deep insight into SystemVerilog assertions need to carefully study it. Some of the aspects of this chapter are useful primarily to people who deal with formal verification, but others are important also for simulation. Throughout this chapter, unless otherwise specified, we make the same notational assumptions as in Chap. 11. We also continue to assume that variables and expressions are 2-state and that global clocking applies to all properties unless otherwise specified.

20.1 Formal Semantics of Properties

We have seen that a property defines its own language, we now need to describe this language precisely for every property that can be expressed in SVA. The formal definition of the language is called the *formal semantics* of the property. Understanding the formal semantics of each SVA property is important to understanding the exact meaning of each temporal formula. In Chaps. 4 and 8 we described the semantics of the properties informally. In this chapter, we provide the formal description.

We use the following notation:

- w is a (finite or infinite) word, or trace, over alphabet $\Sigma = 2^V$.
- Each letter in the word w is numbered by a nonnegative integer number; the i^{th} letter is denoted as w^i . The numbering starts from 0, so that the first letter is w^0 .
- If w is a finite word, its length is denoted as |w|.

• The empty word is denoted as ε . The empty word does not contain any letters, and its length is 0.

- w^{i} is the suffix of the word w starting from the letter w^{i} . More precisely, w^{i} is the word obtained from w by deleting its first i letters. If $|w| \le i$ then $w^{i} = \varepsilon$.
- $w^{i,j}$, where $i \leq j$ is the finite segment of the word w starting from the letter w^i and ending at the letter w^j . More precisely, $w^{i,j}$ is the finite word obtained from the word w by deleting its i first letters and also deleting all its letters after the i+1st.

We also use symbolic notation for the letters. For example, assuming that $V = \{a, b\}$, then $w^0 = a \land \neg b$ means that in the first position of the word (trace) a is 1 and b is 0.

To denote that the word w satisfies the property p, we write $w \models p$. In the context of property satisfaction, w is assumed to be infinite. Finally, we assume that all the properties in this section are unclocked (or governed by the global clock).

20.1.1 Basic Property Forms

We consider first basic SVA property operators: Boolean property, negation, conjunction, nexttime, and s_until. Their formal semantics is defined recursively, starting from the Boolean property.

20.1.1.1 Boolean Property

The Boolean property e, where e is a Boolean expression over variables in V is satisfied on all words such that e holds on their first letter:

$$w \models e \text{ iff } w^0 \rightarrow e.$$

 $w^0 \to e$ means that if the values of the variables of V specified in w^0 are substituted into e, then the result is true. Equivalently, $w^0 \to e$ means that this Boolean formula is a tautology over valuations of the variables in V. In this case, we also write $w^0 \models e$.

For example, if $w^0 = a \land \neg b$ then $w \models a$, and $w \models a \lor b$, but $w \not\models a \land b$.

In what follows, we assume that we know the formal semantics of each subproperty, and thus we define the semantics of compound properties recursively in terms of the semantics of their components.

20.1.1.2 Negation Property

The property not p holds on w iff the property p does not hold on w:

$$w \models \text{not } p \text{ iff } w \not\models p.$$

In the research literature, **not** p is usually denoted as $\neg p$. We continue the discussion on the formal semantics of negation in Sect. 20.3.4.

20.1.1.3 Conjunction Property

The property p and q holds on w iff both properties p and q hold on w:

$$w \models p \text{ and } q \text{ iff } w \models p \text{ and } w \models q.$$

In the research literature, p and q is usually denoted as $p \wedge q$.

20.1.1.4 Nexttime Property

The property **nexttime** p holds on w iff the property p holds on w^{1} ...

$$w \models \texttt{nexttime} \ p \ \text{iff} \ w^{1..} \models p$$

In the research literature, nexttime p is usually denoted either as Xp or as $\bigcirc p$.

20.1.1.5 Strong Until Property

The property p **s_until** q holds on w iff there exists $i \ge 0$ such that p holds in all positions of w up until, but not including, position i, and q holds in position i:

 $w \models p \text{ s_until } q \text{ iff there exists } i \text{ so that } w^i \models q \text{ and for every } 0 \le j < i, w^{j...} \models p.$

In the research literature, p suntil q is usually denoted 1 as pUq.

20.1.2 Derived Properties

The rest of the SVA property operators that do not operate on sequences are derived. They can be expressed through the basic operators defined in Sect. 20.1.1. In this section, we provide the list of these operators, except for the operators if and case because their derivation was explained in Chap. 8.

20.1.2.1 Boolean Connectives

In addition to and, SVA defines the Boolean property connectives or, implies, and iff.

¹ In the literature, the operator **s_until** is called simply *until*, and the operator **until** is called *weak until*.

Disjunction Property: $w \models p \text{ or } q \text{ iff either } w \models p \text{ or } w \models q. p \text{ or } q \text{ is a shortcut notation for not (not } p \text{ and not } q)$. In the research literature, p or q is usually denoted as $p \lor q$.

Implication Property: $w \models p$ implies q iff either $w \not\models p$ or $w \models q$. p implies q is a shortcut notation for not(p or not q). In the research literature, p implies q is usually denoted as $p \rightarrow q$.

Given an assertion p, an assumption q, and a model M, it is possible to rewrite the relation $M||q \models p$ using an implication property as $M \models q \rightarrow p$. Indeed, the first formula means that all words satisfying both M and q also satisfy p, and the second formula means that all words satisfying M either satisfy p or do not satisfy q.

Example 20.1. Consider the following assertion statements:

```
m1: assume property (a);
a1: assert property (b);
a2: assert property (a implies b);
```

Assertion all together with assumption ml are *not* equivalent to assertion all if they are not in the scope of an initial procedure. The reason is that assertions and assumptions out of scope of an initial procedure are interpreted as having an implicit outermost always operator. At module level, for example, all together with ml is equivalent to the following:

```
initial a3: assert property ((always a) implies (always b));
Assertion a3 is weaker than a2.
```

Equivalence Property $w \models p$ iff q iff either both $w \models p$ and $w \models q$, or $w \not\models p$ and $w \not\models q$. p iff q is a shortcut notation for (p implies q) and (q implies p). In the research literature, p implies q is usually denoted as $p \leftrightarrow q$ or as $p \equiv q$.

20.1.2.2 Until Properties

The property p until q holds on w iff either (1) there exists $i \geq 0$ such that p holds in all positions of w up until, but not including, position i, and q holds in position i, or (2) p holds in all positions of w. p until q is a shortcut for $(p \text{ s_until } q)$ or always p. The remaining two properties from until family are also simple shortcuts:

- p until_with q is a shortcut for p until (p and q).
- p s_until_with q is a shortcut for p s_until (p and q).

20.1.2.3 Eventually Property

The property s_eventually p holds on w iff the property p holds on w^{i} for some $i \geq 0$. s_eventually p is a shortcut for **true** s_until p. Indeed, since the property

true holds on any trace, **true s_until** p only checks that p eventually holds. In the research literature, **s_eventually** p is usually denoted as Fp or as $\Diamond p$.

20.1.2.4 Always Property

The property always p holds on w iff the property p holds on $w^{i\cdots}$ for every $i \geq 0$. always p is a shortcut for not seventually not p. Indeed, p always holds iff the fact that not p holds at some time is false. The property always p can also be directly expressed through until as p until false. Since false never holds, p must always hold. In the research literature, always p is usually denoted as Gp or as $\Box p$.

20.2 Formal Semantics of Sequences

Like a property, a sequence defines a language, namely, the set of words (traces) that match the sequence. Unlike the language of a property, the language of a sequence is finitary.

Example 20.2. Given the set of variables $V = \{a,b\}$, the sequence a[*2] # 1 b defines the language $\{aab\}$ over the alphabet $\Sigma = 2^V$. aab is a shortcut for the following traces: $\{a\}\{a\}\{b\}, \{ab\}\{a\}\{b\}, \{a\}\{ab\}\{ab\}, \{ab\}\{ab\}\{ab\}, \{ab\}\{ab\}\{ab\}, \{ab\}\{ab\}, \{ab\}\{$

We say that sequence s is *tightly satisfied* on word w, and write $w \models s$, iff w matches s. In Chaps. 5 and 9, we have informally defined a match for each type of sequence. Here, we provide the formal semantics of sequence match. As in the case of properties, the formal semantics of sequences is defined recursively from the base case of a Boolean sequence. We describe here only the formal semantics of the basic sequence forms. The derived sequence forms have been defined as shortcuts in Chaps. 5 and 9.

In the context of sequence tight satisfaction, we assume that w is a finite word. By Σ^* , we understand the language consisting from all finite words over the alphabet Σ .

Boolean Sequence: The Boolean sequence e is tightly satisfied on w iff |w| = 1 and e is true on w:

$$w \models e \text{ iff } (|w| = 1) \text{ and } (w^0 \models e).$$

Concatenation: The concatenation r ##1 s of the sequences r and s is tightly satisfied on the word w iff it is possible to break w into two words x and y such that r is tightly satisfied on x and s is tightly satisfied on y:

 $w \models r \# 1 s \text{ iff there exist } x, y \text{ so that } w = xy, \text{ and } x \models r \text{ and } y \models s.$

Fusion: The fusion r # 0 s of the sequences r and s is tightly satisfied on the word w iff it is possible to break w into three words x, y, and z, where the size of y is 1, such that r is tightly satisfied on xy and s is tightly satisfied on yz:

 $w \models r \# 0 s$ iff there exist x, y, z so that w = xyz and |y| = 1, and $xy \models r$ and $yz \models s$.

Disjunction: The disjunction r or s of the sequences r and s is tightly satisfied on the word w iff either sequence is tightly satisfied on w:

$$w \models r \text{ or } s \text{ iff } (w \models r) \text{ or } (w \models s).$$

Intersection: The intersection r intersect s of the sequences r and s is tightly satisfied on the word w iff both sequences are tightly satisfied on w:

$$w \models r$$
 intersect s iff $(w \models r)$ and $(w \models s)$.

Empty Sequence: The empty sequence s[*0] is tightly satisfied on the word w iff w is empty:

$$w \models s [\star 0] \text{ iff } |w| = 0.$$

Iteration: The sequence s[+] (also written as s[*1:\$]) is tightly satisfied on the word w iff it is possible to break w into one or more words so that each of them tightly satisfies s:

 $w \models s$ [+] iff there exist words w_1, w_2, \dots, w_j $(j \ge 1)$ so that $w = w_1 w_2 \dots w_j$ and for every i so that $0 < i \le j$ $w_i \models s$.

First Match: The first match $first_{match}(s)$ of the sequence s is tightly satisfied on the word w iff s is tightly satisfied on some prefix x of w then the suffix y of w must be empty:

 $w \models \mathtt{first_match}(s)$ iff $w \models s$ and there exist x, y so that w = xy and $\bar{x} \models s$ then $y = \varepsilon(\bar{x} \text{ is explained in } 20.3.2).$

20.3 Formal Semantics: Sequences and Properties

In Sect. 20.1, we defined how to build up the semantics of properties recursively, starting from Boolean properties. However, from Chap. 5 we know that properties are built on top of sequences and that the sequential property serves as the basic building block for other properties. In this section, we define the formal semantics of the properties built on top of sequences.

20.3.1 Strong Sequential Property

The definition of the formal semantics of a strong sequence is straightforward:

$$w \models \mathtt{strong}(s)$$
 iff there exists $i \ge 0$ so that $w^{0,i} \models s$.

Note the condition $i \ge 0$ – tight satisfaction on the empty word does not make the strong sequential property hold.

Example 20.3. If e is a Boolean expression, the property strong(e[*]) does not hold on the trace $w = \neg e^{\omega}$ where at each position e evaluates to 0. The only match of sequence e on a prefix of w is empty, but for property satisfaction a nonempty match is required.

20.3.2 Extension of Alphabet

Before we proceed to the definition of the formal semantics of weak sequential properties, we need to revisit the alphabet definition. In Sect. 11.2.2, we defined the model alphabet as the set of all variable valuations: $\Sigma = 2^V$. For the purposes of the weak sequence definition discussed in Sect. 20.3.3, and of the reset definition discussed in Chap. 13, we need to extend the alphabet Σ with two special letters: \top and \bot . The letter \top satisfies every Boolean expression, even **false**, and the letter \bot does not satisfy any Boolean expression, not even **true**. In other words, for any Boolean e, $\top \models e$ and $\bot \not\models e$. These letters are mathematical devices useful only for defining the formal semantics; there are no corresponding SystemVerilog constructs to express them directly.

Example 20.4. Let s denote the sequence ##1 a [*2]. s is tightly satisfied on the trace $w_1 = \neg aa \top$, but it is not tightly satisfied on the traces $w_2 = \neg a \neg a \top$ and $w_3 = \bot aa$.

Note that $w_1^0 = \neg a \models \mathbf{true}$, as \mathbf{true} is satisfied by every letter except \bot . Also, $w_1^1 = a \models a$. And $w_1^2 = \top \models a$ since \top satisfies every Boolean expression. Therefore, $w_1 \models s$.

 $w_2 \not\models s$ since $w_2^1 = \neg a \not\models a$. The \top at time 2 does not help match the sequence. At time 1, we already have the evidence that the sequence s cannot be matched regardless the trace content at future time moments.

 $w_3 \not\models s$ since $w_3^0 = \bot \not\models \text{true}$: \bot does not satisfy any Boolean, not even **true**. The sequence started with unary ##1. The important point is that this does not simply mean to skip the first letter. Rather, the first letter must satisfy **true**.

Example 20.5. Let s denote the sequence a ##1 0. Sequence s is tightly satisfied on the trace $w = a \top$, i.e., $w \models s$, since $w^0 = a \models a$ and $w^1 = \top \models 0$. The latter

holds because \top satisfies every Boolean expression, even 0 (or, **false**). Note that the sequence *s* cannot be tightly satisfied on any trace that does not contain \top since no other letter satisfies **false**.

Example 20.6. The property a until b is satisfied on the trace $a \land \neg b \top \neg a \land \neg b \dots$ Indeed, at time 0 a is true, and at time 1 all expressions are satisfied.

Example 20.7. The property always a holds on the trace $w = a \top \neg a \dots$ because always a is a shortcut for a until 0 and 0 (or false) is satisfied by \top (see Example 20.6), even though a does not hold in time 2.

20.3.3 Weak Sequential Property

Now that we have defined the extension of the alphabet, we are ready to define the formal semantics of weak sequences:

$$w \models \text{weak}(s) \text{ iff for every } i \geq 0 \ w^{0,i} \top^{\omega} \models \text{strong}(s).$$

Informally, this definition means that no finite prefix of the trace can be evidence that the sequence cannot match.

Example 20.8. weak (a[*2]) is satisfied on any trace of the form $aa \dots$ Indeed, the sequence a[*2] is tightly satisfied on the traces $a \top$ and aa where the match of the sequence a[*2] can be witnessed.

However, weak (a[*2]) is not satisfied on the trace $a \neg a \dots$, as the sequence a[*2] is not tightly satisfied on the trace $a \neg a$.

Consider an infinite trace and suppose that there is some time T such that any prefix matching the sequence is of length at most T. Then there is no difference between the weak and the strong satisfaction of the sequence on the trace. This is the case of bounded sequences described in Sect. 5.2.

For instance, the sequence a [*2] from Example 20.8 satisfies these conditions, provided it is controlled by the global clock since only traces of length 2 may match it. Therefore, there is no difference between the properties weak (a [*2]) and strong (a [*2]) when they are controlled by the global clock.

Example 20.9. The property weak (##[*] a) holds on any trace without any special letter \top or \bot . Indeed, since $\top \models a$, $w^{0,i} \top \models \#\#[*]$ a for any $w \in \Sigma^{\omega}$ and for any i (recall that Σ^{ω} is an infinite sequence of the letters from the alphabet of the language defined by the FV model, see Sect. 11.2.2). However, property strong (##[*] a) is equivalent to s_eventually a.

The property weak (##[*] a ##1 0) also holds on any infinite trace without any special letter \top or \bot . Since $\top \models a$ and $\top \models \mathbf{false}(=0)$, $w^{0,i} \top \top \models \#\#[*] \ a \#\#1 \ 0$ for any $w \in \Sigma^*$ and any i. On the contrary, the property $\mathtt{strong}(\#\#[*] \ a \#\#1 \ 0)$ is a contradiction, as **false** does not match any letter from the original unextended alphabet.

20.3.4 Property Negation

In Sect. 20.1.1.2, we gave the following definition of property negation:

$$w \models \mathsf{not}\ p \ \mathsf{iff}\ w \not\models p.$$

This definition is only correct if w does not contain special letters \top or \bot . According to that definition, if $w = \top^{\omega}$ then, for any $a, w \models a$, and thus $w \not\models \text{not } a$. This is counterintuitive since we expect not a to behave the same way as !a when the property is controlled by the global clock. !a is satisfied on w since \top satisfies every Boolean expression.

We need to modify the formal semantics of negation to eliminate this counterintuitive behavior. Given a word w we build the word \overline{w} by interchanging the letters \top and \bot in w and leaving all other letters unmodified. Then we can define the formal semantics of property negation as follows:

$$w \models \mathtt{not} \ p \ \mathrm{iff} \ \overline{w} \not\models p.$$

Example 20.10. If $w = T^{\omega}$, then $\overline{w} = \bot^{\omega} \not\models a$ for any a. Therefore, according to this modified definition, $w \models \text{not } a$.

Example 20.11. $w \models \text{not weak} (\# [*] \text{ a}) \text{ iff } \overline{w} \not\models \text{weak} (\# [*] \text{ a}). \text{ The latter means that there exists } i \geq 0 \text{ such that } \overline{w}^{0,i} \top^{\omega} \not\models \text{strong} (\# [*] \text{ a}).$ This is impossible if w does not contain special letters. Therefore, we have that not weak (# [*] a) cannot hold on a trace without special letters, which agrees with our intuition.

 $w \models \text{not strong}(\#\#[*] \text{ a}) \text{ iff } \overline{w} \not\models \text{strong}(\#\#[*] \text{ a}).$ The latter means that the sequence ##[*] a does not match any finite prefix of \overline{w} . Assuming that w has no special letter, this is equivalent to $w^i \not\models a$ for all i, or, equivalently, to $w^i \models a$ for all i. This, in turn, means that always a holds on a. This is not surprising, since a strong a is equivalent to a eventually a, and the negation of a eventually a is always a for Boolean a (Chap. 4).

20.3.5 Suffix Implication

The formal semantics of suffix implication is as follows:

$$w \models s \mid \neg p \text{ iff for every } i \ge 0, \ (\overline{w}^{0,i} \models s) \to (w^{i \cdot \cdot} \models p).$$

This definition means that for each finite prefix of trace w matching sequence s, the suffix of the trace satisfies property p. The prefix and the suffix overlap at the letter i. This definition agrees with the informal definition of the overlapping suffix implication from Sect. 5.4.

Note the interchange of the letters \top and \bot in the antecedent. This is necessary to make the formal semantics intuitive, as illustrated in the following examples.

Example 20.12. It is natural to expect that $a \mid -> b$ behaves the same as a implies b when a and b are Booleans. Assume that $|w| \ge 1$. Then $w \models a$ implies b iff $w \models \text{not } a \text{ or } b$ iff $\overline{w} \not\models a$ or $w \models b$ iff $\overline{w}^{0,0} \models a$ implies $w^{0,...} \models b$.

Example 20.13. Given the trace $w = a \land \neg b \top a \land \neg b \dots$ and the property a [*3] |-> b we can see that b does not belong to the first three letters of the trace. However, the property holds on w, as $\overline{w} = a \land \neg b \bot a \land \neg b \dots$, and a [*3] does not match any finite prefix of \overline{w} .

This example is important for understanding the behavior of implication under reset discussed in Chap. 13. \Box

Is the sequence in the antecedent of a suffix implication strong or weak? The question is malformed since weak and strong sequences are *properties*, whereas the antecedent of a suffix implication is a *sequence*.

As explained in Sect. 5.4, nonoverlapping implication is a shortcut:

$$(s \mid => p) \equiv (s \# 1 \mid -> p).$$

20.3.6 Suffix Conjunction: Followed-by

The formal semantics of followed-by (also called suffix conjunction) is as follows:

$$w \models s \# - \# p \text{ iff for some } i \ge 0, \ w^{0,i} \models s \text{ and } w^{i..} \models p.$$

Followed-by and suffix implication are dual operations (Chap. 8.3):

$$(s #-# p) \equiv (not(s | -> not p)).$$

Indeed, property $s \mid \neg > p$ is false iff at some tight satisfaction point of sequence s property p does not hold.

Nonoverlapping followed-by is defined as a shortcut:

$$(s #=# p) \equiv (s ##1 #-# p).$$

20.4 Formal Semantics of Clocks

The following notations, with and without subscripts, are used throughout this section: b, c, d, x, y, and z denote Boolean expressions; e denotes an event expression; r denotes a sequence; p denotes a property; v denotes a local variable (see Chap. 15); h denotes an expression.

The formal semantics treats clocks like Boolean expressions. If e is a clocking event, then $\tau(e)$ denotes the associated Boolean expression. The semantics of $\tau(e)$ is that $\ell \models \tau(e)$ iff there is a tick of e in letter ℓ . In this way, the question of whether e occurs at a particular tick of the global clock is transformed into the question of whether the Boolean expression $\tau(e)$ is true at that tick of the global clock. τ is defined as follows:

- C1: If e is a named event, then $\tau(e)$ is assumed to be understood as a Boolean expression at the granularity of the global clock.²
- C2: $\tau(\$global_clock) = 1'b1$.
- C3: $\tau(b) = \frac{1}{2} \cosh \frac{1}{2} \operatorname{clock}$.
- C4: $\tau(posedge\ b) = rising_gclk(b)$.
- C5: $\tau(\text{negedge } b) = \text{\$falling_gclk}(b)$.
- C6: $\tau(\text{edge }b) = \tau(\text{posedge }b) \mid \mid \tau(\text{negedge }b)$.
- C7: $\tau(e \text{ iff } b) = \tau(e) \&\& b$.
- C8: $\tau(e_1 \text{ or } e_2) = \tau(e_1) \mid \mid \tau(e_2)$.
- C9: $\tau(e_1, e_2) = \tau(e_1) \mid | \tau(e_2)$.

For example,

```
\tau(posedge clk iff enable) = rising_gclk(clk) && enable
```

After transforming clocking events into Boolean expressions, the formal semantics eliminates the clocking event controls by folding the associated Boolean expressions into the underlying sequences and properties. The resulting unclocked sequences and properties are then interpreted over traces (i.e., finite and infinite words). The elimination of the clocking event controls is accomplished by a system of clock rewrite rules. The rewrite rules define a function \mathcal{T}^s that transforms a sequence and the Boolean expression for a clock into an unclocked sequence. They also define a function \mathcal{T}^p for transforming properties similarly. The clock rewrite rules are as follows, where c denotes a clocking event:

- SCR0: $\mathscr{T}^s((r), c) = (\mathscr{T}^s(r, c))$.
- SCR1: $\mathcal{T}^s(b, c) = |c| * | ##1 c && b.$
- SCR2: $\mathcal{T}^s((1, v = h), c) = \mathcal{T}^s(1, c) \# (1, v = h)$.
- SCR3: $\mathcal{T}^{s}(@(c_2)r, c_1) = \mathcal{T}^{s}(r, c_2)$.
- SCR4: $\mathscr{T}^s(r_1 \ op \ r_2, \ c) = \mathscr{T}^s(r_1, \ c) \ op \ \mathscr{T}^s(r_2, \ c)$, where op can be any of the operators ##0, ##1, or, and intersect.
- SCR5: $\mathcal{I}^s(\text{first_match}(r), c) = \text{first_match}(\mathcal{I}^s(r, c))$.
- SCR6: $\mathscr{T}^s(r[*n], c) = \mathscr{T}^s(r, c)[*n]$. The same rule applies to ranged repetition operators.
- PCR0: $\mathcal{T}^p((p), c) = (\mathcal{T}^p(p, c))$.
- PCR1: $\mathcal{T}^p(op(r), c) = op(\mathcal{T}^s(r, c))$, where op is either strong or weak.

² The formal semantics does not attempt to expand the meaning of a named event in terms of the various code that may trigger the event.

- PCR2: $\mathcal{I}^p(@(c_2) p, c_1) = \mathcal{I}^p(p, c_2)$.
- PCR3: $\mathcal{T}^p(op\ p,\ c) = op\ \mathcal{T}^p(p,\ c)$, where op is any of not, disable iff (b), accept_on (b), and reject_on (b).
- PCR4: $\mathcal{T}^p(p_1 \ op \ p_2, \ c) = \mathcal{T}^p(p_1, \ c) \ op \ \mathcal{T}^p(p_2, \ c)$, where op can be any of the operators and, or, implies, and iff.
- PCR5: $\mathcal{T}^p(\text{sync_accept_on}(b) \ p, c) = \text{accept_on}(b \&\& c) \ \mathcal{T}^p(p, c)$. An analogous rule applies to rewrite the synchronous reject in terms of the asynchronous reject.
- PCR6: $\mathcal{T}^p(r \ op \ p, \ c) = \mathcal{T}^s(r, \ c) \ op \ \mathcal{T}^p(p, \ c)$, where op is any of |->, |=>, #-#, and #=#.
- PCR7: $\mathcal{T}^p(\text{nexttime } p, c) = \\ !c \text{ until } (c \text{ and nexttime } (!c \text{ until } (c \text{ and } \mathcal{T}^p(p, c)))).$
- PCR8: $\mathcal{T}^p(p_1 \text{ until } p_2, c) = (c \text{ implies } \mathcal{T}^p(p_1, c)) \text{ until } (c \text{ and } \mathcal{T}^p(p, c)).$

Rule PCR7 is the most complicated. It contains two alignments to c, performed by the idiomatic subproperty !c until c. The first brings evaluation to alignment with a tick of c, and the second performs the advance to the next tick of c, as specified by nexttime (see Sect. 12.2.5.1). The first alignment is needed to get the proper semantics when the clock is changing. If evaluation of nexttime p begins in a tick of c, then the first alignment does not advance time.

The clock rewrite rules above cover all the primitive operators and a number of derived operators. For other derived operators, rewrite rules are obtained by applying the rules above to the definition of the derived operator in terms of more primitive operators.

Example 20.14. Calculate a clock rewrite rule for b = -1.

Solution: b = -1 is defined to be equivalent to b = 1 ##1 b. Therefore,

Example 20.15. Calculate a clock rewrite rule for r_1 within r_2 .

Solution: r_1 within r_2 is defined to be equivalent to

```
(1[*] ##1 r_1 ##1 1[*]) intersect r_2
```

Therefore,

Example 20.16. Calculate a clock rewrite rule for always p.

Solution: always p is defined to be equivalent to p until 1'b0. Boolean operands of a weak operator like until are automatically weakened, as though they were within implicit instances of weak. Therefore

Example 20.17. Show that the following equivalence is preserved under $\mathcal{T}^p(\cdot, c)$:

$$r #-\# p \equiv not(r \mid -> not p) \tag{*}$$

Solution: Compute:

It is important to understand that the clock rewrite rules do not account for scoping of clocks as defined by the clock flow rules. The addition of clocking event controls consistent with the clock flow rules may be necessary before the clock rewrite rules may be applied.

Example 20.18. Assume that c is the incoming clock to x ##1 @(d) y => z. Show that application of $\mathcal{T}^p(\cdot, c)$ to this property does not correctly account for clock flow. Add clocking event controls to the property so that application of $\mathcal{T}^p(\cdot, c)$ yields the correct rewrite.

Solution: By CF3, CF7, and CF8, d governs y and z, while the incoming clock c governs x. Compute

Thus, according to the rewrite, d governs only y, while c governs x and z. To fix the problem, add the clocking event control @(d) after |=>:

20.5 Formal Semantics of Resets

The special letters \top and \bot play an important role in the formal semantics of resets. If a reset condition occurs at some point in a trace w, then the disposition of the evaluation depends on replacement of the suffix of w beginning at that point by \top^{ω} , \bot^{ω} , or both, depending on the particular reset. The intuition is that all properties hold on \top^{ω} , while no properties hold on \bot^{ω} . Therefore, replacing a suffix of w by \top^{ω} precludes failure after the point of replacement, while replacing the suffix by \bot^{ω} forces success to be complete prior to the point of replacement. Abort operators of the "accept" kind replace the suffix beginning at the occurrence of the abort condition by \top^{ω} , whereas abort operators of the "reject" kind replace the suffix by \bot^{ω} . For disable iff, the disposition on occurrence of the disable condition is neither "pass" nor "fail", but "disabled", so the formal semantics uses both replacements: the replacement of the suffix by \top^{ω} confirms that failure did not occur before the

³ There are some theoretical subtleties involved. It is possible to write a sequence that does not match any word, even when interpreted over the alphabet extended with \top and \bot . An example is a sequence involving a length mismatch, such as r=1'bl intersect (1'bl ##1 1'bl). From r, one can create a property, such as weak (r), that is not satisfiable, even by the word \top^ω . However, by restricting each maximal sequence appearing in a concurrent assertion to be non-degenerate, i.e., to match at least one nonempty finite word when interpreted over the extended alphabet, this problem is avoided. The SystemVerilog LRM requires maximal sequences to be nondegenerate in the appropriate circumstances to avoid such problematic cases.

disable condition, whereas the replacement of the suffix by \perp^{ω} confirms that success also did not occur before the disable condition.

Exposition of the semantics is simplified by the fact that only disable iff and accept_on need be treated as primitive operators. The other resets are derived by the following rules:

```
• reject_on(b) p \equiv \text{not accept\_on}(b) not p.

• sync_reject_on(b) p \equiv \text{not sync\_accept\_on}(b) not p.

• \mathcal{T}^p(\text{sync\_accept\_on}(b) \ p, c) = \text{accept\_on}(b \&\& c) \ \mathcal{T}^p(p, c).
```

The formal semantics of accept_on is simpler than that of disable iff because it involves only the two dispositions "pass" and "fail". It is defined as follows:

```
w \models \mathtt{accept\_on}(b) \ p iff either w \models p or there exists 0 \le i < |w| such that w^i \models b and w^{0,i-1} \top^{\omega} \models p.
```

The first case allows w to satisfy accept_on (b) p if w satisfies p itself, regardless of the abort condition. The second case accounts for an occurrence of the abort condition and replaces the suffix of w beginning at the letter where the abort condition occurs by \top^{ω} before checking for satisfaction of the underlying property p.

Example 20.19. Derive direct semantics for reject_on(b) p.

Solution:

```
\begin{array}{ll} w \models \mathtt{reject\_on}(b) \ p \\ \mathrm{iff} \ w \models \mathtt{not} \ \mathtt{accept\_on}(b) \ \mathtt{not} \ p \\ \mathrm{iff} \ \bar{w} \not\models \mathtt{accept\_on}(b) \ \mathtt{not} \ p \\ \mathrm{iff} \ \mathrm{both} \\ \qquad \bar{w} \not\models \mathtt{not} \ p \\ \mathrm{and} \\ \qquad \mathrm{for} \ \mathrm{all} \ 0 \leq i < |w| \ \mathrm{such} \ \mathrm{that} \ \bar{w}^i \models b : \bar{w}^{0,i-1} \top^\omega \not\models \mathtt{not} \ p \\ \mathrm{iff} \ \mathrm{both} \\ \qquad w \models p \\ \mathrm{and} \\ \qquad \mathrm{for} \ \mathrm{all} \ 0 \leq i < |w| \ \mathrm{such} \ \mathrm{that} \ \bar{w}^i \models b : w^{0,i-1} \bot^\omega \models p \\ \end{array}
```

The "pass" and "fail" dispositions of a disable iff are defined formally as follows:

```
w \models \mathtt{disable\ iff}(b)\ p iff either w \models p and no letter of w satisfies b or for some i, w^i \models b, and w^{0,i-1} \bot^{\omega} \models p for the least such i.
```

The "disabled" disposition of a disable iff is defined formally as follows:

```
w \models^d \text{ disable iff}(b) p iff for some i, w^i \models b, and for the least such i, both w^{0,i-1} \top^{\omega} \models p and w^{0,i-1} \bot^{\omega} \not\models p.
```

Intuitively, the requirement that $w^{0,i-1} \top^{\omega} \models p$ ensures that p has not failed prior to the occurrence of the disable condition, while the requirement that $w^{0,i-1} \bot^{\omega} \not\models p$ ensures that p has not succeeded prior to the occurrence of the disable condition.

20.6 Formal Semantics of Local Variables

This section gives an overview of the formal semantics of local variables. For more details, see the SystemVerilog 2009 LRM. The technical report [35] is another good reference, covering details of theoretical results that are not presented in the LRM. [19] presents complexity results for local variables. Only the unclocked semantics is discussed here. As usual, the clocked semantics is obtained by first transforming to unclocked forms using the clock rewrite rules and then applying the unclocked semantics.

20.6.1 Formalizing Local Variable Flow

If X is a set of local variables and r is a sequence, let flow(X, r) denote the set of local variables that flow out of r given that the local variables in X flow into r. From the local variable flow rules in Sect. 16.4.1, one obtains the following recursive representation of flow(X, r):

- SF1: flow(X, b) = X. Analogous equalities hold for Boolean repetitions b = -n, b = n, etc.
- SF2: $flow(X, (r, v = e)) = flow(X, r) \cup \{v\}.$
- SF3: flow(X, r # n s) = flow(flow(X, r), s). Analogous equalities hold for variants of the binary concatenation operator.
- SF4: $flow(X, r \text{ or } s) = flow(X, r) \cap flow(X, s)$.
- SF5: flow(X, r) and $s) = (flow(X, r) assign(s)) \cup (flow(X, s) assign(r))$. Here assign(r) (resp., assign(s)) denotes the set of local variables assigned anywhere within r (resp., s). Analogous equalities hold for intersect and within.
- SF6: flow(X, b throughout r) = flow(X, r).
- SF7: $flow(X, first_match(r)) = flow(X, r)$.
- SF8: flow(X, r[*0]) = X.

SF9: flow(X, r[+]) = flow(X, r[*n]) = flow(X, r), provided n is positive.
 Analogous equalities apply to ranged forms of the repetition operator, provided the lower range is positive. If the lower range is zero, then the flow rule is obtained by decomposing r[*0:n] as r[*0] or r[*1:n] (n positive or \$).

20.6.2 Local Variable Contexts

The principal technical device introduced to define the semantics of local variables is the local variable context. A *local variable context* is a partial function mapping local variables to values. It can be written as a set of ordered pairs:

$$L = \{(v_1, a_1), (v_2, a_2), \dots, (v_n, a_n)\}\$$

L specifies that for each i, $1 \le i \le n$, the local variable v_i is assigned and has the value a_i . It is customary to say that $\{v_1, v_2, ..., v_n\}$ is the *domain* of L, written dom(L). Thus, the domain of a local variable context is the set of local variables that are assigned in that context. Any local variable not in the domain of the local variable context is unassigned in that context. A local variable context may be empty, in which case its domain is also empty and all local variables are unassigned in that context.

If $D \subseteq \text{dom}(L)$, then $L|_D$ denotes the local variable context obtained by restricting L to the domain D. For example, with L as above and $D = \{v_1, v_3\}$,

$$L|_D = \{(v_1, a_1), (v_3, a_3)\}$$

 $L \setminus v$ denotes $L|_{\text{dom}(L)-\{v\}}$. It is the local variable context that results from L by removing v from the domain, if it was there to begin with.

20.6.3 Sequence Semantics with Local Variables

The semantics of matching (i.e., tight satisfaction) of unclocked sequences can now be defined as a four-way relation:

$$w, L_0, L_1 \models r$$

The relation holds if r matches the finite word w starting with incoming local variable context L_0 and resulting in outgoing local variable context L_1 . Whenever the relation holds, $dom(L_1) = flow(dom(L_0), r)$. This fact is proved in [35]. The substance of defining the relation is to capture how the local variable contexts evolve, as a result of assignments to local variables, local variables becoming unassigned

according to the flow rules, and inductively through intermediate local variable contexts. Here are the definitions for basic sequence operators:

- $w, L_0, L_1 \models b$ iff |w| = 1 and $w^0 \models b[L_0]$ and $L_1 = L_0$. Here, $b[L_0]$ denotes the expression obtained by substituting values from L_0 for any references in b to local variables in dom (L_0) .
- $w, L_0, L_1 \models (r, v = e)$ iff there exists L such that $w, L_0, L \models r$ and $L_1 = L \setminus v \cup \{v, e[L, w^0]\}$. Here, $e[L, w^0]$ denotes the expression obtained by substituting values from L_0 for any references in e to local variables in $dom(L_0)$ and then using values from w^0 to evaluate remaining references in e. If w^0 is a special letter \top or \bot , then $e[L, w^0]$ can be any value.
- $w, L_0, L_1 \models r \# 1 \text{ s iff there exist } x, y, L \text{ such that } w = xy \text{ and } x, L_0, L \models r \text{ and } y, L, L_1 \models s.$
- $w, L_0, L_1 \models r \# 0$ s iff there exist x, y, z, L such that w = xyz and |y| = 1 and $xy, L_0, L \models r$ and $yz, L, L_1 \models s$.
- $w, L_0, L_1 \models r \text{ or } s \text{ iff there exists } L \text{ such that both}$
 - either $w, L_0, L \models r$ or $w, L_0, L \models s$, and
 - $L_1 = L|_D$, where $D = flow(dom(L_0), r \text{ or } s)$.
- $w, L_0, L_1 \models r$ intersect s iff there exist L, L' such that $w, L_0, L \models r$ and $w, L_0, L' \models s$ and $L_1 = L|_D \cup L'|_{D'}$, where
 - $-D = flow(dom(L_0), r) assign(s)$
 - $-D' = flow(dom(L_0), s) assign(r)$
- $w, L_0, L_1 \models \texttt{first_match}(r)$ iff both
 - $w, L_0, L_1 \models r$, and
 - if there exist x, y, L such that w = xy and $\bar{x}, L_0, L \models r$, then y is empty.
- $w, L_0, L_1 \models r \text{ [*0]} \text{ iff } |w| = 0 \text{ and } L_1 = L_0.$
- $w, L_0, L_1 \models r$ [+] iff there exist $L_{(0)} = L_0, w_1, L_{(1)}, \dots, w_k, L_{(k)} = L_1, k \geq 1$, such that $w = w_1 \cdots w_k$ and $w_i, L_{(i-1)}, L_{(i)} \models r$ for every $i, 1 \leq i \leq k$.

20.6.4 Property Semantics with Local Variables

Local variables do not flow out of properties, so the semantics of property satisfaction with local variables is simpler than that of sequence matching. The relation is three-way:

$$w, L_0 \models p$$

The relation holds if p is satisfied by word w starting with the incoming local variable context L_0 . Here are the definitions for the basic property operators:

- $w, L_0 \models \text{not } p \text{ iff } \bar{w}, L_0 \not\models p.$
- $w, L_0 \models \operatorname{strong}(r)$ iff there exists $0 \le j < |w|$ and L such that $w^{0,j}, L_0, L \models r$.

- $w, L_0 \models \text{weak}(r) \text{ iff for every } 0 \leq j < |w|, w^{0,j} \top^{\omega}, L_0 \models \text{strong}(r).$
- $w, L_0 \models r \mid -> p$ iff for every $0 \le j < |w|$ and L such that $\bar{w}^{0,j}, L_0, L \models r$, $w^{j,.}, L \models p$.
- $w, L_0 \models p$ or q iff either $w, L_0 \models p$ or $w, L_0 \models q$.
- $w, L_0 \models p$ and q iff both $w, L_0 \models p$ and $w, L_0 \models q$.
- $w, L_0 \models \text{nexttime } p \text{ iff either } |w| = 0 \text{ or } w^{1..}, L_0 \models p.$
- $w, L_0 \models p$ suntil q iff there exists $0 \le j < |w|$ such that $w^{j..}, L_0 \models q$ and for every $0 \le i < j, w^{i..}, L_0 \models p$.
- $w, L_0 \models \mathtt{accept_on}(b)$ p iff either
 - $w, L_0 \models p$ and no letter of w satisfies b, or
 - for some $0 \le i < |w|$, $w^i \models b$ and $w^{0,i-1} \top^{\omega}$, $L_0 \models p$.⁴

It is worth noting that in the rule for |->, the intermediate local variable context L is universally quantified. This is how the formal semantics specifies that multiple matches over the same interval that result in distinct values of the local variables must be treated as separate matches, each obligating a check of the consequent with the corresponding local variable values.

20.7 Formal Semantics of Recursive Properties

This section gives a brief description of the formal semantics of recursive properties. The main idea is to define the semantics of a recursive property in terms of the semantics of associated nonrecursive properties. Intuitively, these nonrecursive properties are approximations to greater and greater depth of the unrolling of the recursion. There is some subtlety to the definition because recursive properties may instantiate nonrecursive properties and vice versa. This section presumes that the semantics of instantiation of nonrecursive properties is understood, at least at the intuitive level of substituting actual arguments for formal arguments, while avoiding aliasing that is contrary to the rules of name resolution. For further discussion, see Annex F.4 of the LRM.

First, let us say more precisely what constitutes a recursive property and a recursive instance. Consider the source code for a SystemVerilog model. Within it are finitely many declarations of named properties and finitely many instances of named properties. The *dependency digraph* is the directed graph $\langle V, E \rangle$ formed as follows. The node set V consists of the named properties that appear in the source code. Each named property has a unique name, where the name may be expanded as a hierarchical name, e.g., as needed for disambiguation. If p and q are two named properties, then there is a directed edge from p to q in the edge set E iff there is an instance of q within the declaration of p. A named property is said to be *recursive* iff it belongs to a nontrivial strongly connected component of the dependency digraph. An instance of a named property p is said to be *recursive* iff it appears

⁴ In case i = 0, $w^{0,-1}$ is understood to denote the empty word.


within the declaration of a named property q such that p and q belong to the same nontrivial strongly connected component of the dependency digraph. This condition is satisfied iff there is a loop in the dependency digraph that has at least one arc and that passes through both p and q.⁵

Example 20.20. Compute the dependency digraph for the following named property declarations:

```
property p1;
   a and nexttime p2(p2(p3));
endproperty
property p2(property p)
   eventually[0:1] p;
endproperty
property p3;
   b and nexttime p1;
endproperty
```

Identify which named properties are recursive and which instances are recursive.

Solution: The node set of the dependency digraph is $V = \{p1, p2, p3\}$. The declaration of p1 instantiates p2 (twice) and p3, so there are directed edges p1 \rightarrow p2 and p1 \rightarrow p3 in the edge set E. Similarly, there is a directed edge p3 \rightarrow p1 in E. Below is a graphical representation of the dependency digraph.



There is a single nontrivial strongly connected component in the digraph consisting of the nodes $\{p1, p3\}$. Therefore, p1 and p3 are recursive properties. The instance of p3 in the declaration of p1 and the instance of p1 in the declaration of p3 are both recursive instances. p2 is a nonrecursive property. It is worth noting that, under rewriting, the instance p2(p2(p3)) expands to

```
eventually[0:1] eventually[0:1] p3,
```

which is equivalent to eventually [0:2] p3.

For $k \ge 0$, the k-fold approximation to a named property p is denoted p[k] and is defined as follows:

- p[0] is a named property whose declaration is obtained from that of p by replacing the body property by 1'b1.
- For k > 0, p[k] is a named property whose declaration is obtained from that of p by the following replacements:

⁵ In case p = q, the loop can be a self-loop on p.

- Each instance of a recursive property q in the declaration of p is replaced by the instance of q[k-1] obtained by passing the same actual arguments.
- Each instance of a nonrecursive property q in the declaration of p is replaced by the instance of q[k] obtained by passing the same actual arguments.

For any property π , the k-fold approximation to π is denoted $\pi[k]$ and is obtained from π by replacing each instance of a named property p by the instance of p[k] obtained by passing the same actual arguments. For a trace w and a local variable context L, unclocked satisfaction of π is defined by $w, L \models \pi$ iff $w, L \models \pi[k]$ for all k > 0.

Several examples are given below to illustrate how these definitions work.

Example 20.21. Show that for k > 0, my_always [k] (q) is equivalent to

```
(always [0:k-1] q) and nexttime [k] 1'b1,
```

where my_always is as declared in Fig. 17.1.

Solution: The definitions above imply the following declarations:

```
property my_always[0] (property p);
    1'b1;
endproperty
property my_always[k] (property p);
    (nexttime[0] p) and nexttime my_always[k-1](p);
endproperty
```

for k positive. Then we get

```
\begin{split} \text{my\_always} & \texttt{[1]} \; (q) \equiv (\text{nexttime} \; \texttt{[0]} \; \; q) \; \; \text{and} \; \; \text{nexttime} \; \; \texttt{1'b1} \\ & \equiv (\text{always} \; \texttt{[0:0]} \; \; q) \; \; \text{and} \; \; \text{nexttime} \; \texttt{[1]} \; \; \texttt{1'b1} \end{split}
```

Suppose inductively that

```
my_always[k](q) \equiv (always[0:k-1] \ q) and nexttime[k] \ 1'b1
```

Then

Example 20.22. Let $\pi = \text{my_always}(a)$, where a is a Boolean. Show that for w a word without any special letter \top or \bot , $w \models \pi$ iff $w \models \texttt{always}(a)$ a in the unclocked semantics.

Solution: By definition, $w \models \pi$ iff for all k > 0, $w \models \pi$ [k]. Also by definition,

$$\pi$$
 [k] = my_always[k](a)

By the preceding example, for all k > 0,

```
my_always[k](a) \equiv (always[0:k-1] a) and nexttime[k] 1'b1
```

Since w has no special letter, $w \models nexttime[k]$ 1'b1 for all k > 0, and so

$$w \models \pi$$
 iff for all $0 \le i < |w|, w^i \models a$

On the contrary, always a is formally defined as a until 0 in Annex F of the LRM. Since w has no special letter, $w^{i...} \not\models 0$ for all $0 \le i < |w|$. Therefore,

$$w \models \texttt{always} \text{ a iff for all } 0 \le i < |w|, w^i \models \texttt{a}$$

Example 20.23. Let a and b be Booleans, and let q be declared by

```
property q(property p);
   a |-> p;
endproperty
```

Determine the unclocked formal semantics of the property

$$\pi = q(my_always(q(b)))$$

Solution: By definition, $w \models \pi$ iff for all k > 0, $w \models \pi$ [k]. Also by definition,

$$\pi[k] = q[k] \text{ (my_always[k] (q[k] (b)))}$$

The declaration of q instantiates no named property, so for all k > 0, q[k] = q. Therefore, for all k > 0,

```
\begin{split} \pi & [k] \equiv q(\text{my\_always}[k] (q(b))) \\ & \equiv a \mid -> \text{my\_always}[k] (a \mid -> b) \\ & \equiv a \mid -> ((\text{always}[0:k-1] \ a \mid -> b) \ \text{and nexttime}[k] \ 1'b1) \end{split}
```

 $w \models \mathtt{nexttime}\, [\mathtt{k}]$ 1'b1 iff either $|w| < \mathtt{k} \text{ or } w^\mathtt{k} \neq \bot.$ Therefore, $w \models \pi$ iff either

1.
$$|w| = 0$$
, or

П

- 2. $\bar{w}^0 \not\models a$, or
- 3. both
 - a. for all $0 \le i < |w|$ such that $\bar{w}^i \models a, w^i \models b$, and
 - b. for all $0 < i < |w|, w^i \neq \bot$.

Exercises

- **20.1.** Write the explicit formal semantics for the operators or, always, s eventually, until, until with, and s until with.
- **20.2.** Prove the following semantic equivalences:
- (a) not (p until q) \equiv (not q)s_until_with (not p)
- (b) not (p s_until q) \equiv (not q)until_with (not p).
- **20.3.** Write the explicit formal semantics for the following sequences: s[*n], s[*], ##[*] s, r ##[*] s. Here r and s are sequences, and n is a positive integer number.
- **20.4.** Prove that c[->1] ##0 $c[->1] \equiv c[->1]$ as unclocked sequences.
- **20.5.** Prove that s_n exttime $p \equiv not$ nexttime not p as unclocked properties.
- **20.6.** Define the clock rewriting rules for the operators until_with and s until with.
- **20.7.** For each of the event expressions below, compute the Boolean expression that results from applying τ .
- 1. $qlobal_clock$ iff b.
- 2. (posedge c) or (negedge d).
- 3. (edge c), b.
- 4. (negedge c) or (negedge d iff b).
- **20.8.** Compute clock rewrite rules for the following derived forms:
- 1. $b[->n] \equiv (b[->1])[*n]$.
- 2. $b[=n] \equiv (b[->n] \# 1 ! b[*].$
- 3. $(1, v_1 = h_1, v_2 = h_2) \equiv (1, v_1 = h_1) \# (1, v_2 = h_2).$
- 4. b throughout $r \equiv b[\star]$ intersect r.
- 5. r_1 and $r_2 \equiv$

```
((r_1 \# 1 1[*]) \text{ intersect } r_2) \text{ or } (r_1 \text{ intersect } (r_2 \# 1 1[*])).
```

- 6. s_eventually $p \equiv \text{not always not } p$.
- 7. s_nexttime $p \equiv \text{not nexttime not } p$.
- 8. if (b) p_1 else $p_2 \equiv (b \mid -> p_1)$ and (weak(b) or p_2).

20.9. Show that the following equivalences are preserved under $\mathcal{I}^p(\cdot, c)$:

```
1. r \#=\# p \equiv \operatorname{not}(r \mid => \operatorname{not} p).

2. \operatorname{reject\_on}(b) p \equiv \operatorname{not} \operatorname{accept\_on}(b) \operatorname{not} p.

3. p_1 implies p_2 \equiv (p_1 implies p_2) and (p_2 implies p_1).
```

20.10. The following facts about the SVA formal semantics can be proved:

- a. If $w \models p$ and w' results from w by changing zero or more letters to \top , then $w' \models p$.
- b. If $w \models p$ and w' results from w by changing zero or more letters away from \bot , then $w' \models p$.

Use these facts to prove the following:

```
1. If 0 \le i < j < |w| and w^{0,j-1} \top^{\omega} \models p, then w^{0,i-1} \top^{\omega} \models p.

2. If 0 \le i < j < |w| and w^{0,i-1} \bot^{\omega} \models p, then w^{0,j-1} \bot^{\omega} \models p.
```

How do these implications relate to the formal semantics of resets?

20.11. Let a, b, and c be Booleans. Determine the dependency digraph for the following declarations.

```
property p1;
         case(a)
2
             1'b0: p2;
3
             1'b1: p3;
         endcase
      endproperty
6
      property p2;
7
         p4 or (b and nexttime p1);
8
      endproperty
9
      property p3;
10
         p4 and nexttime (a | -> p2);
11
12
      endproperty
      property p4;
13
         a |=> c;
      endproperty
```

Which properties are recursive and which are nonrecursive?

20.12. Let my_until be as declared in Fig. 17.3. Let a and b be Booleans. Show that for k > 0, my_until [k] (a,b) is equivalent to

```
weak( (a[*0:k-1] ##1 b) or (a[*k] ##1 1) )
```

Show that my_until(a,b) is equivalent to

```
weak(a[*] ##1 b)
```

20.13. Let a be a Boolean. Show that for any word w, including special letters \top and \bot , $w \models my_always(a)$ implies $w \models a$ until 0. Show that the converse can fail if \top is a letter in w. (cf. Example 20.22.)

Part III Checkers and Assertion Libraries

Chapter 21 Checkers

Contradictions do not exist. Whenever you think you are facing a contradiction, check your premises. You will find that one of them is wrong.

— Ayn Rand

In this chapter, we introduce checkers, units for packaging assertion-based verification code. On the one hand, checkers are similar to modules and interfaces: they define their own hierarchical scope, they may contain procedures and many other constructs allowed in modules and interfaces. On the other hand, checkers generalize properties and sequences: they are instantiated "in place", their arguments may be sequences, properties, and edge sensitive events. One can also say that checkers generalize assertions, since they behave as one complex assertion. In the subsequent sections, we elaborate the checker definition and instantiation, checker variables, covergroup support in checkers, and checker simulation semantics.

Using checkers makes the RTL cleaner: most instrumentation code in modules may be moved to checkers, which improves the code modularity, makes module code more readable and less error prone. Synthesis tools are normally supposed to ignore checkers, thus there is no need in conditional compilation statements to isolate the instrumentation code for the synthesis tools.

Although synthesis tools ignore checkers, checkers are synthesizable by their nature. They may be synthesized for hardware emulation and even in the silicon, if so desired. Since the FV tools work on the synthesis model, checkers are FV-friendly. The only nonsynthesizable constructs in checker bodies are covergroups and final procedures, but they are targeted only for simulation.

21.1 An Apology for Checkers

We start with an example of a system containing several devices that communicate with each other by sending commands. Each command contains the opcode, data, and the address of the destination device. When signal go is asserted, one device sends the command to the hub, and several cycles later the hub sends this command to the destination device. Between two consecutive activations of go, only one device may send a command. When this command is sent to the hub, it should be

448 21 Checkers

```
property start before(sequence en, in, out);
     en | -> not strong(out) until with in;
2
   endproperty : start_before
3
  module hub(input logic clk, rst, go, iready,
5
     logic [2:0] idest, logic [31:0] idata, ...,
     output logic oready, logic [2:0] odest, logic [31:0] odata);
     default disable iff rst;
     //...
     always @(posedge clk) begin
       odest <= ...;
11
       odata <= ...;
       oready <= ...;
13
       check protocol: assert property (
14
         start before(go, iready[*2], oready[*2]))
15
         else $error("Output request issued without corresponding
16
              input request");
17
     end
19
     //...
   endmodule : hub
```

Fig. 21.1 Hub implementation

resent to the destination device by the hub before the next occurrence of go. Should the device transmit a command, it asserts signal iready for two clock ticks. Should the hub forward the command to the destination device, it asserts signal oready for two clock cycles.

A fragment of the code implementing module hub is shown in Fig. 21.1. This fragment contains assertion <code>check_protocol</code> verifying that the hub does not send an output command without receiving one as input.

By analyzing this implementation, we can observe the following advantages of assertions:

Assertion locality The assertion check_protocol is embedded into the always procedure (lines 10–18), and it is written close to the assignment of oready that it checks.

Context inference The assertion infers its clock from the clock control of the always procedure (line 10), and its reset from the default disable iff statement (line 8).

Sequences as property arguments Sequences iready [*2] and oready [*2] are passed to the property start_before as its actual arguments. The type of en (line 1) is also a sequence, and the actual triggering condition of this property may be an arbitrary sequence.

Is the assertion <code>check_protocol</code> sufficient to check the entire communication protocol? Of course, not. It does not check the following features:

- There may be at most one request between two consecutive go.
- iready and oready may not be asserted continuously over more than two consecutive clock ticks.

- If a command is sent by a device, it should be repeated by the hub before the next qo.
- The destination device address and the data transmitted by the hub should be identical to the address and the data issued by the source device.

It is also a good idea to collect information on clock ticks when the device commands are issued. This may be done by adding a cover property statement.

A solution is to implement the missing properties and insert appropriate assertions after line 17, but this solution has many drawbacks:

- A large amount of assertions will negatively affect the module readability and obscure the design intent.
- When the protocol is refined, the code of module hub would also have to be modified to refine the assertions, even if the RTL code of the module did not change.
- The RTL code is written by a designer, while the assertions verifying the communication protocol may be written by a validator. It would be inconvenient if they both share the same file.
- There may be several implementations of module hub. The same assertions have to be replicated in each of these implementations.

It is clear that the right solution is to group all the assertions verifying the protocol behavior together. One option is to collect these assertions in a separate file and to include this file into the desired place in the module hub. But this option is obviously bad: to make this solution work, all signal names have to be hard coded. Also, the included file does not define any internal scope, consequently the names introduced there are visible after the point of its insertion.

Modules as Assertion Containers The only alternative available until SystemVerilog 2009 for packaging such assertions was to use modules or interfaces. Let us explore this alternative closer. We create a module hub_protocol (Fig. 21.2) containing all the required assertions. Figure 21.3 presents the modified module hub containing an invocation of hub_protocol. For simplicity, we omit checking that iready and oready are not asserted for more than two consecutive clock ticks, and defer it to Exercise 21.1. See also Exercise 21.2 for discussion about property at_most_one_req.

Note the problems that are inherent to this module-based implementation:

• Modules cannot be instantiated in procedural code; therefore, the instantiation of hub_protocol had to be moved out of the always procedure (Fig. 21.3, line 26). The locality that existed in the case of a single assertion is lost.¹

¹ In this case, one could argue that it is more natural to place hub_protocol module invocation close to hub module beginning or end, as we only check the global behavior of hub. However, when the local behavior is checked, instantiation should be close to implementation. We do not provide additional examples to not overload the book contents.

450 21 Checkers

```
module hub protocol
1
2
     #(ADDR SIZE=8, DATA SIZE=64)
     (input logic clk, rst, en, inreq, outreq,
3
     logic [ADDR SIZE-1:0] inaddr, outaddr,
     logic [DATA SIZE-1:0] indata, outdata);
5
     default clocking @(posedge clk); endclocking
     default disable iff rst;
     property start_before(en, first, second);
       en |-> !second until with first;
10
     endproperty : start before
11
     property at_most_one_req(en, req);
13
       en |-> if (req) (##1 !req[*] ##1 en)
14
              else (##1 req[=0:1] ##1 en);
15
     endproperty : at most one req
17
     property same data(in, out, indata, outdata);
       type(indata) data;
19
       (in, data = indata) ##1 out[->1] |-> outdata == data;
20
     endproperty : same_data
2.1
22
23
     no sporadic out reqs:
     assert property (start_before(en, inreq, outreq))
     else $error("Output request issued without input request");
25
26
     too many in reqs:assert property (at most one req(en, inreq))
2.7
     else $error("More than one input request in the same frame");
28
29
     too many out reqs:
30
     assert property (at most one req(en, outreq))
31
     else $error("More than one output request in the same frame");
32
33
     data integrity:
34
     assert property (same data(inreq, outreq,
35
       {inaddr, indata}, {outaddr, outdata}))
36
       else $error("Data corrupted");
37
38
     cover req: cover property (inreq);
39
40
   endmodule : hub protocol
```

Fig. 21.2 Module with hub protocol specification

- There is no context inference in modules. This means that clk and rst have to be passed explicitly through ports.
- It is possible to pass an event expression such as posedge clk to properties, but not to modules. Therefore, clk is passed as a signal. Should the assertions be controlled by the negative edge of the clock, !clk would have to

```
module hub(input logic clk, rst, go, iready, logic [2:0] idest,
        logic [31:0] idata, ...
     output logic oready, logic [2:0] odest, logic [31:0] odata);
2
     default disable iff rst;
3
4
     //...
     always @(posedge clk) begin
       odest <= ...;
6
       odata <= ...;
       oready <= ...;
8
     end
     // Instrumentation code
10
     logic prev iready, ireq, prev oready, oreq;
11
     always @(posedge clk or posedge rst) begin
12
       if (rst) begin
13
         prev iready = '0;
14
         prev oready = '0;
16
       prev iready <= iready;</pre>
17
       prev oready <= oready;
18
19
20
     always comb begin
21
       ireq = prev iready && iready;
22
       oreq = prev_iready && oready;
23
24
     end
25
     //...
     hub_protocol #(3, 32) check_hub protocol(
26
       clk, rst, go, ireq, oreq, idest, odest, idata, odata);
27
   endmodule : hub
```

Fig. 21.3 Module hub with invocation of module hub_protocol

be passed to hub_protocol. Furthermore, if the assertions were to be controlled by edge clk, another version of hub protocol would have to be created.

• It is possible to pass a sequence iready [*2] to an assertion, but not to a module. We could try to define

```
sequence twice(sig);
  sig[*2];
endsequence : twice
```

and pass twice(iready).triggered to hub_protocol. This solution would produce no errors, but the result is incorrect. The reason is that twice(iready).triggered is executed in the Observed region, while inreq in all concurrent assertions within hub_protocol is sampled in the Preponed region. Therefore, twice(iready).triggered always has value 0 (see Sect. 9.2.1.1). To work around this problem, an instrumentation code has to be provided to compute the equivalent of the sequence evaluation (Fig. 21.3, lines 10-24).

 Another annoying problem with this implementation is the need to specify the size of the address and data as module parameters. The parameter specification may be an additional source of errors, and it also makes the invocation more verbose.

This example clearly shows that modules are not a good solution for assertion containers. They sometimes introduce more problems than they solve. Using interfaces for this purpose has the same drawbacks.

Checkers To resolve the problems of assertion packaging, SystemVerilog has a special construct called **checker**. We introduce checkers informally in this section, while providing detailed description in the section that follows. Figures 21.4 and 21.5 show how a checker can be used for the hub protocol assertion packaging.

The advantages of the checker-based implementation can be clearly seen on this example:

- Checkers, like assertions can be instantiated in procedural code (Fig. 21.5, line 10), thus the locality principle is preserved.
- Checkers can infer clock and reset from the instantiation context. In our example, the checker inherits clock from the clock control of the always procedure (line 6), and reset from the default disable iff statement (line 4).
- Clock is passed as an event (Fig. 21.4, line 4). This may be any event expression:
 posedge, negedge, edge, or conditional event, hence checker hub_protocol
 does not need any modification to support complex clocks like edge iff cond.
- Sequences (and properties) may be passed to a checker as arguments (Fig. 21.5, line 11); consequently, no instrumentation code is required in module hub.
- Checkers are instantiated "in place", similar to property instantiations in assertions. They can have untyped formal arguments (Fig. 21.4, line 4). Therefore, there is no need for passing the size of the address and data to hub_protocol (Fig. 21.5, line 10). The checker invocation actually is even more compact than a concurrent assertion (Fig. 21.1, line 14) because the error message is embedded in the body of the checker.

Checkers have also other important features that are covered in the following sections. In the rest of this section, we provide a commentary about the implementation of the checker hub_protocol. The goal is to help the reader understand this example, and to ease the understanding of the following sections.

A Tour Through hub_protocol Checker Figure 21.5, lines 10–11. The checker instantiation syntax is similar to module instantiation. hub_protocol is the name of the checker, check_hub_protocol is the name of the checker instance. Checkers do not have parameters, only ports. Checker instantiation semantics is similar to property instantiation in an assertion. All argument types that can be used with a property, can also be used with a checker. In this example, we can see that it is possible to pass sequences iready [*2] and oready [*2] to the checker.

Figure 21.4, lines 1–4, and 48. The checker definition syntax is similar to module definition, instead of module – endmodule the keywords checker – endchecker

```
checker hub protocol (
2
     sequence en, inreq, outreq,
     untyped inaddr, indata, outaddr, outdata,
3
     event clk = $inferred clock,untyped rst = $inferred disable);
     default clocking @clk; endclocking
5
     default disable iff rst;
     property start before (sequence en, first, second);
       en | -> not strong(second) until with first;
     endproperty : start before
10
11
     property at most one req(sequence en, untyped req);
       en |-> if (req) (##1 !req[*] ##1 en)
13
         else (##1 req[=0:1] ##1 en);
14
     endproperty : at_most_one_req
15
16
     property same data(sequence in,untyped out, indata, outdata);
17
       type(indata) data;
       (in, data = indata) ##1 out[->1] |-> outdata == data;
19
     endproperty : same data
20
21
     sequence seq with rst (sequence s);
22
       @clk !rst throughout s;
23
     endsequence
24
25
     let en end = seq with rst(en).triggered;
26
     let inreq end = seq with rst(inreq).triggered;
2.7
     let outreq end = seq with rst(outreq).triggered;
28
29
     no sporadic out reqs:
30
     assert property (start before (en, inreq, outreq))
31
       else $error("Output request without corresponding input
32
           request");
33
     too_many_in_reqs:
34
       assert property (at most one req(en, inreq end))
35
         else $error("More than one input request in the same
36
              frame");
37
     too many out reqs:
38
       assert property (at most one req(en, outreq end))
         else $error("More than one output request in the same
40
             frame");
41
     data integrity:
42
       assert property (same data(inreq, outreq end,
43
         {inaddr, indata}, {outaddr, outdata}))
         else $error("Data corrupted");
45
     cover_req: cover property (inreq);
47
   endchecker : hub_protocol
```

Fig. 21.4 Checker with hub protocol specification

```
module hub(input logic clk, rst, go, iready, logic [2:0] idest,
1
2
     logic [31:0] idata, ...
     output logic oready, logic [2:0] odest, logic [31:0] odata);
3
     default disable iff rst;
5
     always @(posedge clk) begin
6
       odest <= ...;
7
       odata <= ...;
       oready <= ...;
       hub protocol check hub protocol (
10
         go, iready[*2], oready[*2], idest, idata, odest, odata);
11
     end
     //...
13
  endmodule : hub
```

Fig. 21.5 Module hub with invocation of checker hub protocol

are used. The semantics of checker formal arguments is similar to the semantics of property arguments, and almost all formal argument types allowed in properties are also allowed in checkers.² In this example, we have arguments of types sequence and event, and also untyped arguments. As in properties, it is legal to use \$inferred_clock and \$inferred_disable system functions for checker argument initialization (see Sect. 7.3): these functions return the inferred values of the clock and reset from the checker *instantiation* context. As a result of this initialization, clk contains the inferred clock from the checker instantiation context, and rst contains the inferred reset, as no explicit values are provided to these arguments in the checker instantiation (Fig. 21.5, lines 10–11).

Lines 5–6. These default statements define clk and rst as default clock and reset for checker assertions. As a result, the values of the clock and reset inferred at the checker instantiation become known inside the checker. Without these statements, no clock and reset inference can be achieved inside the checker.

Lines 8–10. Property start_before has been explained at the beginning of this section.

Lines 12–15. Property at_most_one_req checks that between two activations of en there may be at most one request req.

Lines 17–20. Property same_data checks that when out is asserted for the first time after in completion, outdata should have the same value as in_data at the moment when in completes. This property is implemented using the local variable data. To make this property generic, the type (indata) construct is used to define data of the same type as indata (line 18).

Lines 22–24. seq_with_rst is an auxiliary sequence that takes an arbitrary sequence as argument and applies synchronous reset to it. The sequence accounts for a reset when sequence match methods are used (Sect. 9.2.1).

² Except arguments with local qualifier, see Sect. 16.2.

21.2 Checker Declaration 455

Lines 26–28 contain let declarations that provide compact names to the triggered methods of the sequences. Some properties described above require Boolean arguments. To make them work with arbitrary sequences, a sequence method triggered should be passed to the property for such formal Boolean arguments. To avoid specifying the exact type of the formal argument (e.g., logic or bit), we leave the formal argument untyped.

Lines 30–47 contain assertions using properties defined in lines 8–20.

Note that checker hub_protocol allows en, inreq, and outreq to be arbitrary sequences. This makes it generic and thus reusable in situations where these signals are not just simple Boolean expressions. The corresponding implementation as a module (Fig. 21.2) allows for only Boolean values, hence it lacks the let declarations for triggering conditions of sequences found in the checkers. Also, the assertions appear simpler because they need to process only Boolean values. This comes, of course, at the expense of generality as mentioned earlier.

21.2 Checker Declaration

The checker declaration has the following syntax:

```
checker checker_name (checker_formal_arguments);
...
endchecker
```

If a checker has no arguments, the parentheses may be omitted. endchecker may be qualified with a label of the checker name, similar to other compound constructs in SystemVerilog. Specifying the checker name with endchecker is a good idea as it makes the code clearer, and allows the compiler to check that the beginning and end of the checker match.

Example 21.1. The following checker consists of a single assertion verifying that request req is granted in the following clock tick.

```
checker request_granted(req, gnt, clk, rst);
  al: assert property(@clk disable iff (rst) req |=> gnt);
endchecker : request granted
```

In this example, all checker formal arguments are untyped.

21.2.1 Checker Formal Arguments

Default Arguments Checker formal arguments may have default values, similarly as formal arguments of properties and sequences (Sect. 7.2).

Example 21.2. Write the following checker: request req is granted (gnt asserted) in n clock ticks. By default n = 1.

Solution:

```
checker request_granted(req, gnt, n = 1, clk, rst);
  al: assert property(@clk disable iff (rst)
    req |-> nexttime[n] gnt);
endchecker : request granted
```

Discussion: Even though n is untyped, the actual argument must be an elaboration time constant because it is used in the property operator nextime[n].

Context Inference As in the case of properties, there are two special default argument values: \$inferred_clock and \$inferred_disable. These system functions return the clocking event and the reset inferred from the checker *instantiation* context. Section 7.3 explains the context inference rules. We will get back to these context inference functions in Sect. 21.3 where we discuss checker instantiation (see also the checker motivation example in Sect. 21.1).

Example 21.3. Same example as Example 21.2, with default values for clock and reset.

```
checker request_granted(req, gnt, n = 1,
   clk = $inferred_clock, rst = $inferred_disable);
   al: assert property(@clk disable iff (rst)
     req |-> nexttime[n] gnt);
endchecker : request_granted
```

Note that \$inferred_clock and \$inferred_disable provide default actual arguments to the formal arguments clk and rst only. There is no inference of clock and reset from these functions in the checker assertions.

Example 21.4. Let us try to omit the clock and reset specifications in assertion at in Example 21.3:

```
checker request_granted(req, gnt, n = 1, clk = $inferred_clock,
    rst = $inferred_disable);
    al_wrong: assert property(req |-> nexttime[n] gnt);
endchecker : request granted
```

Assertion al_wrong will not compile since it does not have an explicitly specified clock, and there is no clock to infer: The clock inference rules inside checkers are the same as in modules. clk is initialized by default with <code>sinferred_clock</code>, but there is no clock specification <code>@clk</code> in al wrong.

If clock and reset inference is desired in a checker, default clocking and default disable iff statements must be specified, as in the case of modules and interfaces.

Example 21.5. Clock and reset inference in checkers.

```
checker request_granted(req, gnt, n = 1,
   clk = $inferred_clock, rst = $inferred_disable);
   default clocking @clk; endclocking
   default disable iff rst;
```

21.2 Checker Declaration 457

```
a1: assert property(req |-> nexttime[n] gnt);
endchecker : request granted
```

In this example, clock and the reset are inferred for assertion all from the default declarations; consequently, the assertion is equivalent to

```
assert property(@clk disable iff (rst) req |-> nexttime[n] gnt);
```

The clock and reset inference rules in concurrent assertions inside checkers are the same as the inference rules in modules. They are resolved in the scope of the checker definition, not in the scope of its instantiation.

21.2.1.1 Checker Argument Types

The main use of a checker is to be an observer – to follow the DUT behavior and to verify its correctness. Therefore, all checker formal arguments are input, hence their explicit direction cannot be specified. It is still possible to modify DUT variables from a checker, for example, in the action blocks of its assertions. However, an explicit reference to a design variable limits the reuse of the checker.

Checker formal arguments may be of the same types as property arguments (Chap. 7), but they cannot have local qualifier. In addition, they may be strings and reals. The syntax of the checker formal argument is the same as for properties and sequences. Unlike module ports, checker formal arguments may not be interfaces.

In the examples in Sect. 21.5, the type of the checker arguments was not specified, that is, all arguments were untyped. Untyped arguments are flexible, but can lead to uninformative error messages. Example 21.6 illustrates using both typed and untyped formal arguments in a checker.

Example 21.6. We modify the checker from Example 21.3 by ascribing types to its formal arguments, and by passing it an error message.

```
checker request_granted(sequence req, property gnt,
  untyped n = 1, string msg = "",
  event clk = $inferred_clock, untyped rst = $inferred_disable);
  default clocking @clk; endclocking
  default disable iff rst;
  al: assert property(req |-> nexttime[n] gnt) else $error(msg);
endchecker : request_granted
```

What would happen if we pass a property expression nexttime go to the formal argument req? It is likely that we would get an error message similar to the following one:

The formal argument req of checker request_granted is of sequence type, while the actual argument nexttime go is an expression nexttime go of property type.

Consider the message we might get if the req argument were untyped, as in Example 21.3:

Type mismatch in a1: assert property(req | -> nexttime[n] gnt) else \$error(msg); req is of property type, while sequence type is expected.

The user understands the first error message, since it explains the problem in terms of the interface of the checker. However, the second error message is confusing because it mentions the checker *internals*, which are normally hidden from the user.

Unfortunately, it is not always possible or desirable to provide a specific type for a checker argument. Although it seems natural to declare n as int, doing so would exclude the possibility of passing the checker an infinite upper bound \$, since only untyped formal arguments may receive \$. In our example, we have to explicitly declare n as untyped, otherwise its type would be taken from the previous argument (gnt) that is of type property. We also have to leave rst untyped because providing a specific type, say, logic, would require type conversion when the actual argument is of a different type. This may affect checker correctness or slow down the simulation.

Always specify an explicit type for checker formal arguments that are used as sequences, properties, events, or strings. Specifying a type for formal arguments used as Booleans or integral expressions usually limits checker generality.

21.2.2 Checker Contents

Checker contents are more restricted than those of a module. A checker may contain:³

- default clocking and default disable iff statements.
- generate constructs.
- always, initial, and final procedures.
- Variable and type declarations.
- · Assertions.
- Let, sequence, property, and function declarations.
- Covergroups.

Note that all procedural conditional and loop statements, such as if, case, for, etc., as well as continuous assignments, are **not** allowed in checkers.

³ This list is not complete. For a complete list, consult the LRM.

21.2 Checker Declaration 459

Checker Body When we talk about checker contents, we mean only the main body of the checker. The constructs in a checker body can have subconstructs, and these subconstructs follow different rules. For example, immediate assertions are not allowed in the checker body, but they are allowed in action blocks of concurrent assertions placed in the checker. This distinction should always be taken into account, although we do not explicitly mention it in what follows.

Let, Sequences, and Properties Let, sequence and property declarations may be freely used in checkers. Their meaning in checkers is the same as in modules, the difference is in the methodology. As a rule, it is recommended to avoid sequence and property declarations in modules: most sequences and properties used in modules are general enough, they should be defined in some global place, for example, in a package, to be also accessible to different modules. If a module uses several specific sequences and properties, it is better to encapsulate them in a checker to keep the module code clean. Unlike modules, checkers are natural containers for sequence and property encapsulation.

As continuous assignments are not allowed in checkers, let declarations are the first-class citizens in checkers. let statements may successfully replace continuous assignments in many cases by assigning a name to an expression. Sometimes they are also safer (see, for example, Sect. 9.2.1.1).

Checker Assertions A checker may contain only concurrent and deferred assertions. Immediate assertions are allowed only in action blocks of checker assertions and in its final procedures. Section 21.1 provides an example of using concurrent assertions, while Sect. 21.3.2.1 discusses deferred assertions in checkers.

21.2.2.1 Generate Constructs

Generate constructs in SystemVerilog are used to perform elaboration time actions to enable flexible tuning of the design at the elaboration time, as described in Sect. 2.11. In checkers, the same generate constructs may be used, and the same rules as everywhere else apply.

Since procedural conditional and looping statements are not allowed in checkers, all if, case, and for statements in the checker body must always be generate statements or be placed in functions.

Example 21.7. What happens if we pass the value of -1 to n in checker request_granted (Example 21.3)? Apparently, we should get an error message about assertion at saying that ##-1 is wrong syntax. Since the user is not necessarily familiar with the checker internals, it may be confusing. It would be much clearer if we report the error message relative to the checker interface. We can do that using a generate if statement as follows:

```
checker request_granted(
   sequence req, property gnt, untyped n = 1, ...);
   if (!$isunbounded(n) && n < 0)</pre>
```

```
$error("Delay value n cannot be negative", n);
//...
al: assert property(req |-> nexttime[n] gnt) else $error(msg);
endchecker : request granted
```

\$isunbounded (n) is a system function returning *true* if its argument is \$. We need this function to isolate the situation when the unbounded value is provided for n: in that case we cannot compare \$ with 0. When the checker is instantiated with the negative value for n the error message is issued at elaboration time.

Use generate statements and elaboration system tasks to perform custom elaboration-time checks and to issue custom elaboration error messages.

Ability to use generate statements is an important advantage of checkers over bare assertions: checkers are more flexible and tunable. Therefore, it makes sense to use checkers even when they consist of a single assertion.

Example 21.8. We mentioned in Sect. 9.1.4 that simulation performance degrades when the antecedents have distant matches, or remain unfinished. If in the checker request_granted, req is a long sequence or if there are incomplete pending requests, the simulation time may be negatively affected. It is possible to truncate the antecedent to k clock ticks by intersecting it with 1[*1:k], as explained in Example 9.16. This truncation is very inefficient in FV, and it should be avoided there. We can add an optional argument truncate to the checker request_granted: when a nonzero value, say, 10, is passed to it, the antecedent req will be truncated after 10 clock ticks, and when \$ is passed, no truncation is performed. The resulting checker is shown in Fig. 21.6.

```
checker request granted (sequence req, property gnt,
1
     untyped n = 1, string msg = "",
2
3
     event clk = $inferred clock, untyped rst = $inferred disable,
     untyped truncate = $);
4
     default clocking @clk; endclocking
5
     default disable iff rst;
6
     if ($isunbounded(truncate))
7
       sequence ante;
8
         req;
       endsequence : ante
10
     else if (truncate < 1)</pre>
11
       $error("truncate value should be positive");
12
14
       sequence ante;
         req intersect 1[*1:truncate];
15
       endsequence : ante
16
     al:assert property (ante | -> nexttime[n] gnt)else $error(msg);
17
   endchecker : request granted
```

Fig. 21.6 Optional antecedent truncation

21.2 Checker Declaration 461

If truncate has a value \$, the conditional generate if in line 7 will yield the sequence ante (antecedent) from lines 8 to 10 in the elaboration model. If truncate is positive, it will be the sequence ante from lines 14 to 16. If truncate has a nonpositive value, an error message is issued.

The reader may wonder why we suggested this solution instead of always defining the antecedent of assertion at as req intersect 1[*1:truncate]. This is, of course, correct, but both formal and simulation tools may implement req intersect $1[*1:$^{\circ}]$ less efficiently than just req.

21.2.2.2 Checker Procedures

A checker may contain similar kinds of processes as a module: initial, always, and final, but the statements that are legal in these procedures in modules and in checkers are different.

Initial Procedure In checkers, initial procedures may contain concurrent or deferred assertions and a procedural event control statement @. All other statements are forbidden there. The only purpose of initial procedures in checkers is to enable assertions that execute a single evaluation attempt starting at the first tick of their leading clock.

Example 21.9. Write a checker verifying that reset rst is initially high, then eventually goes low and remains low forever.

Solution:

```
checker simple_reset(rst);
  initial
    al: assert property (@$global_clock rst[+] #=# always !rst);
endchecker : simple_reset
```

Discussion: We need to check only the first evaluation attempt of a1, hence it should be placed in the scope of an initial procedure. We do not wish to associate the behavior of rst with any specific clock; therefore, we chose the global clock, the fastest clock of the system, to control this assertion. See Exercise 21.4 for further discussion.

Always Procedure An always procedure in checkers may contain only concurrent and deferred assertions, checker variable assignments, and a procedural timing control statement @.

Clock Inference in Checker Procedures Consider the following checker:

```
checker mycheck(a, event clk = $inferred_clock);
  always @clk begin
    al: assert property (a);
  end
endchecker : mycheck
```

The checker does not have a default clocking declaration. Will it compile? It depends on the actual value of its formal argument clk. If the actual value of clk is an event expression of the form posedge, negedge or edge, clk will be inferred as a clocking event of assertion al; otherwise, it will not and the resulting unclocked assertion will lead to a compilation error.

The reason for this behavior is that, when the checker is instantiated clk is substituted by its actual argument, as explained in Sect. 21.3. If, for example, the actual argument of clk is posedge clock then always @clk becomes always @(posedge clock). From Chap. 14 it follows that in this case the assertion infers its clocking event from the always procedure. If the actual argument of clk is just clock, then always @clk becomes always @clock after substitution, and the assertion clock cannot be inferred.

Final Procedure final procedures in checkers are not different from final procedures in modules (see Sect. 2.5). They are executed at the end of simulation. Their main purpose is to print statistical information and to check the final state of the simulation.

final procedures may contain everything that functions may contain. Therefore, checker final procedures may only use *immediate* assertions.

Example 21.10. We can add a final procedure to the checker request_granted defined in Example 21.4 to check that at the end of simulation there is no outstanding request. For simplicity, we assume that both req and gnt are Boolean, and that the request remains asserted until granted.

Solution:

It is possible to write an entire checker consisting only of the final procedure. Its purpose would be to check the quiescent state at the end of simulation to verify that there are no outstanding transactions, and that some important scenarios were observed at least once.

21.2.3 Scoping Rules

Checkers may be declared at the top level, i.e., in the scope of a compilation unit. All the preceding checker examples in this chapter were top-level checkers.

21.2 Checker Declaration 463

Checkers may also be declared in other scopes: in modules, interfaces, programs, generate blocks, packages, and in other checkers. The reason for declaring checkers in smaller scopes is to make them local to these scopes, and to make the objects declared in these scopes and in the higher-level scopes visible inside the checker. Another reason is to hide the checker from other parts of the design.

Example 21.11. Figure 21.7 shows nested checkers: checker check2 is declared inside checker check1.

Even though checker check2 does not have arguments, the arguments and the other objects of checker check1 are visible in its scope. For example, arguments a, b, c, and d of check1, and property p2 declared in check1 are used in check2. Property p1 used in assertion a1 (line 16) is a local property of check2 (lines 13–15), and not the property p1 declared in checker check1(lines 5–7). Property p1 of check1 cannot be directly referenced in check2 because property p1 of check2 masks the visibility of property p1 of check1. If we needed to instantiate property p1 of check1 in check2, we have to reference it by its hierarchical name check1.p1.

Checker check2 also inherits the default clocking and default reset definitions from checker check1 (lines 3-4), hence clocking event @clk and reset rst are inferred in assertions at and a2.

All objects referenced in a checker are resolved in the scope of the checker definition, and not in the scope of its instantiation.

```
checker check1(a, b, c, d,
1
     event clk = $inferred clock,untyped rst = $inferred disable);
2
     default clocking @clk; endclocking
3
     default disable iff rst;
4
     property p1(x, y);
5
       x[*2] \mid -> y;
     endproperty : p1
7
     property p2(x, y);
8
       x \mid -> y[*2];
     endproperty : p2
10
     // ...
11
     checker check2;
       property p1(x, y);
13
         x[*2] \mid -> y[*2];
14
       endproperty : p1
15
       a1: assert property (p1(a, b));
16
       a2: assert property (p2(c, d));
17
     endchecker : check2
18
     check2 check cd;
19
   endchecker : check1
```

Fig. 21.7 Nested checkers

Example 21.12. The checker mycheck will not compile, even though this checker is instantiated in module m:

```
checker mycheck(event clk = $inferred_clock);
  al: assert property (@clk a);
endchecker : mycheck
module m(input logic clk, ...);
  logic a = ...;
  mycheck check(posedge clk);
  //...
endmodule : m
```

This is because a referred to in assertion a1 is resolved in the scope of the checker definition where no a is declared, and not in the scope of the checker instantiation where a is visible (see also Example 21.4).

If the hierarchical name of a specific instance of module m is top.unit1.block2 then the checker mycheck could be rewritten as follows to reference a by its hierarchical name:

```
checker mycheck(event clk = $inferred_clock);
   al: assert property (@clk top.unit1.block2.a);
endchecker : mycheck
```

Of course, a cleaner solution would be to pass a as an argument to the checker. This should be done for small checkers like mycheck. Referencing design signals in a checker by their hierarchical names is useful in big checkers verifying behavior of large pieces of hardware, however, it limits their reusability in other designs.

21.2.3.1 Checkers in Packages

Checkers are natural candidates for units of standard or project-wide verification libraries. The question is how to package several checkers in a reusable unit. Another problem is a possible name collision: The name of a library checker may be the same as a name of another checker or module.

SystemVerilog package construct is well suited for both tasks: it can contain several checkers (also properties, sequences, let, constants, etc., see Chap. 2), and it also introduces its own name space.

Example 21.13. We can place checker request_granted from Example 21.3 in a package named check_lib as follows:

```
package check_lib;
  checker request_granted(sequence req, property gnt,
    untyped n = 1,
    event clk = $inferred_clock, untyped rst = $inferred_disable);
    al: assert property(@clk disable iff (rst)
        req |-> nexttime[n] gnt);
  endchecker : request_granted
  // Other checkers ...
endpackage : check lib
```

21.3 Checker Instantiation 465

To instantiate the checker in a module it is necessary to import the package contents first:

```
module m(logic clk, rst, send, ack, ...);
  import check_lib::*;
  //...
  request_granted ack_received(send, ack, 1, posedge clk, rst);
endmodule : m
```

The statement import check_lib::* makes the entire contents of the package visible in m. Instead of importing the entire contents, we could import only this specific checker using import check_lib::request_granted. It is also possible to use the fully qualified name of the checker when instantiating it:

```
check_lib::request_granted ack_received(
  send, ack, 1, posedge clk, rst);
```

without importing the package contents to avoid name collision.

Checkers in packages cannot refer to the data that do not belong to the scope of the package. Thus, (the corrected version of) checker mycheck in Example 21.12 cannot be placed in a package, since it refers to data top.unit1.block2.a in a module. This is forbidden in packages.

21.3 Checker Instantiation

A checker may be instantiated in any place where a concurrent assertion may appear, except for fork...join blocks. This means that checkers may be instantiated both outside and *inside* procedural code. This is one of the important differences between checkers and modules, as modules may be instantiated only outside procedural code. Checker instantiation in procedural code is called a *procedural* checker instance, while the checker instantiation outside procedural code is called a *static* checker instance.

21.3.1 Connecting Checker Arguments

The association of checker actual arguments with its formal arguments has the same syntax as module port association. The argument association may be positional or named, and the name association may be explicit, implicit, and may use wildcards, the same way as modules, properties, and other similar constructs in SystemVerilog. Different argument association forms may be mixed.

Example 21.14. We illustrate different ways of checker argument associations on the instantiation of checker request granted from Example 21.3.

Positional Association In the module m1 below, the actual arguments of the checker are passed according to the order of the corresponding formal arguments. The default values passed to n and clk are identified by commas, one comma for each unspecified actual argument. Were these default arguments the last arguments in the list, there would be no need for these commas. Positional argument association is really convenient only when the number of checker arguments is small.

```
module m1(input logic clk, rst, send, ack, ...);
  default clocking @(posedge clk); endclocking
  //...
  request_granted check(send, ack,,, rst);
endmodule : m1
```

Explicit Named Association In module m2 below, the actual arguments of the checker are passed by an explicit indication of the formal argument names. In the case of the named association, the order of the actual arguments is not important. Omitting default values does not require any additional notation. A named association is convenient when the number of checker arguments is large, or when the default values are passed to the arguments in the middle of the argument list.

```
module m2(input logic clk, rst, send, ack, ...);
  default clocking @(posedge clk); endclocking
  //...
  request_granted check(.rst(rst), .req(send), .gnt(ack));
endmodule : m2
```

Implicit Named Association When the names of actual and formal arguments coincide, there is no need to repeat the argument names. In module m3, argument rst is passed by implicit named association.

```
module m3(input logic clk, rst, send, ack, ...);
  default clocking @(posedge clk); endclocking
  //...
  request_granted check(.rst, .req(send), .gnt(ack));
endmodule : m3
```

Wildcard Named Association When the names of several actual and formal arguments coincide, as in module m4 below, it is convenient to use a wildcard association making all actual and formal arguments to be connected implicitly by name. Note that in our case it is incorrect to use only the wildcard association because the clocking event passed to the checker request_granted check would be clk, and not posedge clk as intended. We need to explicitly leave the formal argument clk unconnected to allow using the default value \$inferred_clock. We could also explicitly specify clk (posedge clk) instead.

```
module m4(input logic clk, rst, req, gnt, ...);
  default clocking @(posedge clk); endclocking
  //...
  request_granted check(.*, .clk());
endmodule : m4
```

21.3 Checker Instantiation 467

21.3.2 Instantiation Semantics

Roughly speaking, checkers are "inlined" at their instantiation point – the checker contents are inserted in the place of the checker instance. This is similar to sequence and property instantiation, but different from a module instantiation and from a task call.

Actually, checker instantiation is more complicated than straightforward inlining, hence we need to describe all its subtleties. In this section, we concentrate on static checker instances, while the peculiarities of procedural checker instances are discussed in Sect. 21.3.3.

A static checker is instantiated by substitution "in place" with reservations concerning checker object naming, clock and reset inference, name resolution, argument sampling, and checker variable semantics. We discuss checker argument sampling in Sect. 21.3.2.1, and defer the discussion about checker variables until Sect. 21.4.

Object Naming

Example 21.15. Consider the following code:

```
checker check(a, b, event clk);
  al: assert property (@clk a |=> b);
endchecker : check
module ml(input logic clock, req, ack);
  //...
  check mycheck(req, ack, posedge clock);
endmodule : ml
```

Instance mycheck of checker check in module m1 is not exactly equivalent to

```
module m1(logic clock, req, ack);
   //...
   a1: assert property (@(posedge clock) req |=> ack);
endmodule : m1
```

This is because the true name of the assertion upon the <code>check</code> instantiation in <code>m1</code> is <code>mycheck.al</code>, and not just <code>al</code>. The checker introduces its own scope. Since assigning a hierarchical name, such as <code>mycheck.al</code> to an assertion directly in the module is illegal, the checker instantiation "in place" is rather conceptual than real.

Context Inference and Name Resolution As mentioned in Sects. 21.2.1 and 21.2.3, name resolution and context inference are done at the point of the checker declaration and not of its instantiation.

Example 21.16. Consider instantiation of checker check from Example 21.15 in module m2:

```
module m2(input logic clock, rst, req, ack);
  default disable iff rst;
  //...
  check mycheck(req, ack, posedge clock);
endmodule : m2
```

The inferred reset in assertion all of checker check is 0, and not rst, because reset is resolved at the declaration point. Thus, assertion all is equivalent to

```
al: assert property (@(posedge clock) disable iff (0)
  req |=> ack);
```

If the checker were *defined* in module m2 (see Sect. 21.2.3), then rst would be inferred from the default disable iff statement in m2, which is visible in the *declaration* of check.

```
module m2(input logic clock, rst, req, ack);
  default disable iff rst;

checker check(a, b, event clk);
   al: assert property (@clk a |=> b);
  endchecker : al
  //...
  check mycheck(req, ack, posedge clock);
endmodule : m2
```

The assertion would be equivalent to

```
a1: assert property (@(posedge clock) disable iff (rst)
  req |=> ack);
```

When a concurrent assertion appears in a checker procedure, inference of the assertion clock depends on the event control of the procedure (Sect. 14.2). To infer the clocking event form the procedure event control, the first event expression should be edge expression.⁴ Unlike in modules, this decision is made based on the checker actual arguments, as described in Sect. 21.2.2.2.

Example 21.17. In the following checker, the inferred clock for assertion at is posedge clk.

```
checker check1(a, clk);
  always @(posedge clk)
    al: assert property(a);
endchecker : check1
```

This inference is due to the structure of the checker itself. The event control of the checker procedure is an edge expression posedge clk.

Example 21.18. Consider checker check2 and its instantiations c1, c2, c3:

```
checker check2(a, event clk = $inferred_clock);
  always @clk
    a2: assert property(a);
endchecker : check2
module m(input logic clock, b, ...);
  // ...
  check2 cl(b, posedge clock);
  check2 c2(b, clock); // Illegal
```

⁴ There are additional conditions necessary for clock inference, see details in Sect. 14.2.

21.3 Checker Instantiation 469

```
check2 c3(b, edge clock);
endmodule : m
```

The clock of assertion a2 inferred in the instance c1 is clk, since the actual argument corresponding to clk is posedge clock which is an edge expression.

Instance c2 will not compile, since the actual argument corresponding to clk is clock. The actual event expression of the checker procedure thus becomes clock, and no clock inference can be made for assertion a2.

The clock of assertion a2 inferred in instance c3 is edge c1k, since the actual argument corresponding to c1k is edge clock, which is an edge expression.

Note that from the simulation point of view there is almost no difference between <code>@clock</code> and <code>@(edge clock)⁵</code> as both of them mean execution of the procedure body when clock changes. However, from the clock inference point of view, these two event controls are different: there is clock inference in the case of <code>@(edge clock)</code>, but there is no inference in the case of <code>@clock</code>.

21.3.2.1 Argument Sampling

The rule is that the checker arguments are sampled. Of course, this applies only to those argument types that can be sampled. For example, the notion of sampling is not applicable to sequences, properties, strings, and events. Automatic variables cannot be sampled either. There are several other exceptions to this rule that we are going to discuss in the following paragraphs.

Action Blocks of Concurrent Assertions One of the advantages of checker argument sampling is the convenience of getting sampled values directly for checker arguments used in action blocks of concurrent assertions.

As discussed in Sect. 6.2.1.1, variable values in the action block of concurrent assertions have to be explicitly sampled to report data values that occurred at the moment of the assertion success/failure. When the assertion is contained in a checker, this explicit variable sampling becomes redundant.

Example 21.19. In Example 6.8, we presented the following assertion:

```
a1: assert property (@(posedge clk) a)
else $error("Error: a = \%b.", $sampled(a));
```

The value of a in the assertion action block had to be explicitly sampled to be consistent with the value of a observed in the assertion property.

It is redundant to explicitly sample the values of a in the action block of assertion a2 because the value of a is already sampled by the checker.

```
checker check(a, clk = $inferred_clock);
  a2: assert property (@clk a)
    else $error("Error: a = %b.", a);
endchecker : check
```

 $^{^5}$ More precisely, edge clock is a shortcut for posedge clock or negedge clock.

Deferred Assertions in Checkers As stated earlier, the operands of deferred assertions are not sampled (Sect. 3.3). However, since checker arguments are sampled then deferred assertions in checkers receive values that are already sampled, unless the assertions explicitly refer to design variables by their hierarchical names.

Example 21.20. Deferred assertion al in checker mutex uses sampled values of arg and rst:

```
checker mutex(arg, rst);
  assert #0 (!rst -> $onehot0(arg));
endchecker : mutex
```

Deferred assertion a2 in checker m_bus_mutex accesses design variables top.unit1.block2.reset and top.unit1.block2.bus directly; therefore, its arguments are not sampled:

```
checker m_bus_mutex;
  assert #0 (
    top.unit1.block2.reset -> $onehot0(top.unit1.block2.bus));
endchecker : m_bus_mutex
```

Of course, to get meaningful results, mixing checker arguments and design variables in the same deferred assertion in a checker should be avoided, otherwise some arguments of the deferred assertion will be sampled, and others will not. Furthermore, reusability of the checker is jeopardized.

Do not mix checker arguments and design variables in deferred assertions in checkers.

We assume in the rest of this section that checkers do not reference any design variables directly.

Sampling of checker arguments makes deferred assertions in checkers behave as concurrent assertions controlled by the simulation clock, that is, by a clock ticking in each simulation time step. 6

Main Reset Sampling in Concurrent Assertions Sampling of checker arguments affects not only deferred assertion, but concurrent assertions too. Recall that the condition of disable iff clause in concurrent assertions is not sampled. However, since all checker arguments are sampled, the reset condition of concurrent assertions in a checker is also sampled. Usually, in race-free designs this difference is not very important. In fact, using sampled values in disable iff make more sense because it aligns with the values seen by the assertion property.

⁶ If there is a global clock ticking in each simulation time-step, then the checker deferred assertions become equivalent to corresponding concurrent assertions controlled by global clock.

21.3 Checker Instantiation 471

Example 21.21. The behavior of assertions at and at may be different:

```
checker check(a,
    event clk = $inferred_clock, untyped rst = $inferred_disable);
    al: assert property (@clk disable iff (rst) a);
endchecker : check
module m(input logic clock, reset, sig, ...);
    //...
    check mycheck(sig, posedge clock, reset);
    a2: assert property (@(posedge clock) disable iff (reset) sig);
endmodule : m
```

The disable iff condition in assertion al is sampled, while in assertion al it is not!

Clock Sampling Since checker arguments are sampled, passing a clock as a Boolean signal and not as an event to a checker does not work as expected. For example, in assertion al of checker check, event posedge clk is delayed by one simulation time-step relative to what we could expect.

```
checker check(a, clk);
  al: assert property (@(posedge clk) a);
endchecker : check

module m(input logic clock, b,...);
  // ...
  check cl(b, clock);
endmodule : m
```

Suppose that at simulation time 499 the value of clock is 0, it becomes 1 at simulation time 500, and remains 1 for several more time steps. However, event posedge clk is only observed at simulation time 501, and not at 500 because the sampled value of the clk is used in this event. The sampled value becomes 1 only at time 501. This also means that the values of variables in the assertion property as sampled by the clock are delayed and may have changed as compared to the case where the clock is not sampled.

Pass a clock to a checker as an event and not as a variable.

Passing Nonsampled Values to Checker As in the case of concurrent assertions (Chap. 14), it is possible to leave a checker argument nonsampled by applying a const' cast to its actual argument.

Example 21.22. The actual argument passed to the formal argument b of the checker check is not sampled, since a const' cast is used.

```
checker check(input a, b, event clk = $inferred_clock);
  al: assert property (@clk a);
  a2: assert #0 (b);
endchecker : check
```

```
module m(logic clock, c, d, ...);
   // ...
   check mycheck(c, const'(d), posedge clock);
endmodule
```

21.3.3 Procedural Checker Instance

The instantiation rules formulated for static checker instances hold also for procedural checker instances, but there are additional rules applicable to procedural instances.

Static Assertions Static assertions (i.e., those checker assertions that are not in the scope of any checker procedure) in the procedural checker instance become procedural assertions as the result of the checker instantiation.

Example 21.23. Assertion a1 is static in checker check:

```
checker check1(a, event clk = $inferred clock);
  al: assert property (@clk a);
endchecker : check1
  The checker check instantiation in module m
module m(input logic clock, b, en, ...);
  // ...
  always @(posedge clock) begin
    if (en) begin
      // ...
      check1 c1(b);
    end
  end
endmodule : m
is conceptually equivalent to
module m(input logic clock, b, ...);
  // ...
  always @(posedge clock) begin
   if (en) begin
      // ...
    al: assert property (@(posedge clock) b);
    end
endmodule : m
```

That is, the static assertion all in checker check behaves as a procedural assertion in checker instantiation of in module m.

 $^{^{7}}$ We use the term "conceptually" because of the hierarchical assertion naming in the checker, as explained in Sect. 21.3.2.

21.3 Checker Instantiation 473

Checker Procedures Straightforward inlining cannot work for checker procedures: it is illegal to have nested procedures in SystemVerilog. One should regard checker procedures as if they were instantiated outside the procedural code. Therefore, always procedures in checkers are sort of screens "protecting" their contents from the procedural code at the place of the checker instantiation.

Example 21.24. Consider the following checker check instantiated in module m.

```
checker check(a, event clk);
  always @clk
    al: assert property (@clk a);
endchecker : check
module m(input logic clock, b, en);
    // ...
    always @(posedge clock) begin
    if (en) begin
        // ...
        check mycheck(b, negedge clock);
    end
    end
endmodule : m
```

This checker instantiation is conceptually equivalent to the following code:

```
module m(input logic clock, b, en);
   // ...
   always @(posedge clock) begin
      if (en) begin
         // ...
      end
   end
   always @(negedge clock)
      al: assert property (@(negedge clock) b);
endmodule : m
```

The always procedure in the checker screens assertion at from the direct effect of the always procedure in the module: assertion at is controlled by negedge clock and does not depend on the value of en. This behavior is different from the behavior of static assertion at in checker check1 from Example 21.23. \Box

Example 21.25. Assertion at in the following checker is instantiated in the scope of an initial procedure.

```
checker check(a, event clk = $inferred_clock);
  initial
    al: assert property (@clk s_eventually a);
endchecker : check
module m(input logic clock, b, en);
    // ...
    always @(posedge clock) begin
    if (en) begin
        // ...
        check mycheck(b, negedge clock);
    end
```

```
end
endmodule : m
```

This checker instantiation is conceptually equivalent to the following code:

```
module m(input logic clock, b, en);
// ...
always @(posedge clock) begin
   if (en) begin
       // ...
   end
end
initial
   al: assert property (@(negedge clock) s_eventually b);
endmodule : m
```

Even though the checker is instantiated in an always procedure of module m, assertion al is monitored only once.

Assertion monitoring is done according to their placement in the checker, and not according to the checker instantiation in a module or in an interface.

Checker Instantiation in Procedural Loops Procedural loops are just a particular case of procedural code, and thus all the rules of checker instantiation in procedural code are applicable here too. Note, however, that if a checker actual argument depends on a loop variable, the loop variable should have automatic lifetime to prevent its sampling or const' cast should be applied to the actual argument.

Example 21.26. Consider the following checker instantiation:

According to the instantiation semantics in procedures, the checker instantiation is conceptually equivalent to

```
module m(input logic clock, logic [7:0] req, ack);
   // ...
   always @(posedge clock) begin
   for (int i = 0; i < 8; i ++)</pre>
```

21.3 Checker Instantiation 475

It is important that the loop variable $\underline{\iota}$ be automatic. If the loop in the module m were written as:

the resulting assertion would be

```
assert property(req[$sampled(i)] |=> ack[$sampled(i)]);
```

This is apparently not intended (see detailed discussion about assertion instantiation in loops in Sect. 14.4). If for some reason it is necessary to have the loop variable with static lifetime, the const' cast should be explicitly applied:

```
check mycheck(req[const'(i)], ack[const'(i)]);
```

Example 21.27. Consider now a checker that contains procedural assertions:

The checker instantiation is conceptually equivalent to the following code:

There is only one instance of each assertion a1, a2 regardless of the checker instantiation in the loop. However, if the instantiation of assertion a1 is meaningful, the instantiation of a2 is not because variable i is not visible in the assertion.

The code in checker always procedures should not depend on procedural loop control variables.

21.3.4 Checker Binding

Sometimes it is desirable to keep verification code separate from the design code. For example, a validator may want to write several checkers verifying DUT behavior without modifying RTL (see Sect. 1.2.2). SystemVerilog allows external checker binding to modules or interfaces using the bind directive. It is forbidden to bind anything to a checker, not even another checker.

It is possible either to bind a checker to all instances of a module or interface, or to choose only specific instances where the checker is to be bound as described in Sect. 2.10.

Example 21.28. Consider a module trans instantiated three times in the top-level module top:

```
module top;
  logic clock, snda, sndb, sndc, rcva, rcvb, rcvc;
  trans ta(clock, snda, rcva);
  trans tb(clock, sndb, rcvb);
  trans #(2) tc(clock, sndc, rcvc);
endmodule : top
module trans #(DEL=1) (input logic clock, in,
                        output logic out);
  if (DEL == 1) begin : b
    always @(posedge clock)
      out <= in;
  end
  else begin : b
    logic [DEL - 2: 0] tmp;
    always @(posedge clock) begin
      tmp[0] \ll in;
      for (int i = 1; i < DEL - 1; i++)</pre>
```

21.4 Checker Variables 477

```
tmp[i] <= tmp[i - 1];
  out <= tmp[DEL - 2];
  end
  end
endmodule : trans</pre>
```

This module generates signal out from signal in by delaying it by several clock cycles specified by the module parameter DEL. Note that the if statement in module trans is a generate if (see Sect. 2.11).

The following checker eventually_granted verifies that each request is eventually granted:

```
checker eventually_granted(sequence req, property gnt,
   event clk = $inferred_clock);
   assert property (@clk req |=> s_eventually gnt);
endchecker : eventually granted
```

We can bind this checker to module trans to verify that the high value of signal in of module trans is eventually transmitted to its output out:

```
bind trans eventually_granted
  check in2out(in, out, posedge clock);
```

The bind statement specifies that checker eventually_granted is bound to each instance of module m. It is equivalent to instantiating the checker at the end of module trans.

```
eventually granted check_in2out(in, out, posedge clock);
```

Checker eventually_granted is too general, as it does not check the exact timing. To make more specific checks, it is possible to use checker request granted:

```
checker request_granted(sequence req, property gnt, int n = 1,
    event clk = $inferred_clock, untyped rst = $inferred_disable);
    al: assert property(@clk disable iff (rst)
        req |-> nexttime[n] gnt);
endchecker : request_granted
```

This time we cannot bind the checker to all instances of module trans, since the specific delay values are different in each instance: we need to bind request_granted with the delay value of 1 to module instances ta and tb, and with the delay value of 2 to module instance tc:

П

```
bind trans: ta, tb request_granted
  delay1(in, out,, posedge clock);
bind trans: tc request_granted
  delay2(in, out, 2, posedge clock);
```

21.4 Checker Variables

Checkers may contain variable declarations and their assignments. The variables declared in the checker body are called *checker variables*. Declaring nets in the checker body is illegal. The only legal assignments to checker variables are their

initialization at declaration, and nonblocking assignment in an always procedure. The assignments to checker variables are executed in the Re-NBA queue of the Reactive region (See Sect. 2.12.3).

Checker variables provide means for carrying auxiliary computations in support of assertions, called *assertion modeling code*. Having modeling capability in checkers is important; it allows separating instrumentation code for assertions from the RTL code, thus keeping RTL clean and maintainable. This separation is also convenient for synthesis tools as it provides an easily identifiable distinction between RTL and the instrumentation code without the need of conditional compilation.

Example 21.29. Checker stable_for_two_ticks verifies that sig may change only in clock ticks 2, 4, ... after the reset rst becomes low, as shown in Fig. 21.8.

```
checker stable for two ticks(sig,
1
     event clk = $inferred_clock, untyped rst = $inferred_disable);
2
     default clocking @clk; endclocking
3
     default disable iff rst;
4
     bit toggle = 1'b0;
6
     always @clk
7
       toggle <= rst ? 1'b0 : !toggle;
8
     a1: assert property (!toggle |-> $stable(sig));
9
  endchecker : stable for two ticks
10
```

This checker works as follows. Variable toggle is initially low, and it becomes low each time rst is deasserted. Otherwise, at each clock tick the value of toggle is complemented. Assertion at allows sig to change only when toggle value is high.

For the waveform shown in Fig. 21.8 the value of rst on line 8 is becomes low at time 30 (recall that the value of rst is sampled in the checker), and in the next clock tick (time 40) the sampled value of toggle is low. Therefore, at time 40, the sampled value of sig must be stable: the sampled value of sig at time 30 is the same as its sampled value at time 40. At time 50, the sampled value of toggle becomes 0, and sig may change in this time-step, and so on.




Fig. 21.8 Signal stable for two clock ticks

21.4 Checker Variables 479

Example 21.30. In the checker from Example 21.29 it is illegal to replace

```
bit toggle = 1'b0;
with
bit toggle;
initial toggle = 1'b0;
```

Initial procedures in checkers may contain only concurrent assertions, but not checker variable assignments (see Sect. 21.2.2.2). Blocking assignment to a checker variable is also illegal.

It is also illegal to rewrite

```
always @clk
  toggle <= rst ? 1'b0 : !toggle;
as
always @clk begin
  if (rst)
    toggle <= 1'b0;
else
  toggle <= !toggle;</pre>
```

because procedural control statements are not allowed in the checker body.

There are several additional restrictions imposed on checker variable assignments:

П

- It is illegal to reference checker variables in assignments by their hierarchical names.
- It is illegal to assign the same bit of a checker variable more than once (Single Assignment Rule (SAR)).
- It is illegal to index a checker variable used as the target of an assignment with an expression that is not an elaboration-time constant.

Example 21.31. The following code is illegal as the checker variable a is referenced by its hierarchical name mycheck. a in the assignment of b.

```
checker check(...);
  bit a;
  // ...
endchecker : check

module m_illegal(...);
  // ...
  check mycheck(...);
  // ...
  wire b;
  assign b = mycheck.a;
endmodule : m
```

In other words, it is forbidden to assign or use checker variables from the outside of the checker. \Box

Example 21.32. The following code is illegal as it violates the single assignment rule:

```
checker illegal(logic [3:0] a, event clk = $inferred_clock);
logic b[3:0];
// ...
always @clk begin
   b[3:1] <= a[3:1];
   b[2:0] <= a[2:0];
end
endchecker : illegal</pre>
```

b[2:1] is assigned twice. Even though both times it is assigned the same value, the mere fact of the multiple assignment makes it illegal.

Example 21.33. Instantiation c1_illegal is illegal, while the instantiation c2 of the same checker is correct.

```
checker check(a, i, event clk = $inferred_clock);
  type(a) b;
  // ...
  always @clk
   b[i] <= a != '0;
endchecker : check
module m(input logic [7:0] data, logic[2:0] idx, logic clock);
  // ...
  check c1_illegal(data, idx, posedge clock);
  check c2(data, 3'b010, posedge clock);
endmodule : m</pre>
```

The actual argument idx passed to the formal argument i in instance c1 is not a constant. It is forbidden to index a checker variable in the left-hand side of an assignment with a nonconstant expression: b[i] <= a != '0. In c2, the value passed to i is 3'b010, thus the assignment target becomes b[3'b010] which is legal.

One may ask why there are so many limitations imposed on checker variables as compared to variables used in modules and in other SystemVerilog constructs. The general answer is to keep concurrent assertion behavior stable and well defined. For example, introducing continuous and blocking assignments to checker variables would enable races and contention between checker variables, enabling conditional statements would make it difficult to enforce the single assignment rule, and so on. All these issues become even more serious for free variables discussed in Sect. 22.1.

Using Functions in Checkers It might seem that the absence of basic modeling constructs, such as continuous assignments and procedural control statements, makes assertion modeling difficult. Fortunately, the situation is not that bad, since there is a good work-around: **let** statements may replace continuous assignments in most cases, and control flow may be placed into embedded functions.

Example 21.34. Consider a generalization of checker stable_for_two_ticks from Example 21.29 as shown in checker stable_for_n_ticks. It verifies that sig is stable during n cycles.

21.4 Checker Variables 481

To check the signal stability, we introduce a counter ctr, and we allow sig to change only when ctr is 0. The system function \$clog2 returns the number of bits necessary to store the value of n.

We use (ctr = n - 1)? 0 : ctr + 1 instead of (ctr + 1)% n because of efficiency considerations: when n is not a power of two, modulo operator % is expensive.

The inability to use procedural control statements in checkers yields poorly readable and clumsy expressions on the right-hand side of assignments, such as rst ? 1 : (ctr == n - 1)? 0 : ctr + 1. The recommended alternative is to define a local function in the checker to evaluate this expression, as shown in the following version of the checker stable for n ticks.

Function next_ctr evaluates the next value of ctr. Since the function body is not the checker body, procedural control statements are allowed there. Furthermore, function next_ctr is local to the checker stable_for_n_ticks, hence all data visible in the checker are also visible in this function.

Use let statements to assign names to integral expressions in checkers. Package assignment control flow statements into internal checker functions.

Efficiency Tip To make checkers efficient in FV, checker variables should be of the smallest size sufficient to store the desired values.

The following restrictions are imposed on functions used on the right-hand side of checker variable assignments:

- The functions should not contain output or ref arguments (const ref is allowed).
- The functions should be automatic and not preserve any state information in static variables. The functions cannot have side effects.

These restrictions are the same as imposed on function calls in concurrent assertions.

Checker Variables in final Procedures Checker variables may be used in final procedures, as illustrated in Example 21.35.

Example 21.35. In Example 21.10 to check for pending requests at the end of simulation, we assumed that req remains asserted until the reception of gnt. The checker may be modified to work properly even without this assumption. For this purpose, we introduce a checker variable intrans which is set to 1 between the assertions of req and its gnt, or more precisely, from the clock tick after req until the clock tick after gnt.

For simplicity, we assume again that both req and gnt are Boolean.

```
checker request granted(reg, gnt, n = 1, event clk =
    $inferred clock, rst = $inferred disable);
  default clocking @clk; endclocking
  default disable iff rst;
  bit intrans = 1'b0;
  function bit next intrans;
    if (rst || gnt) return 1'b0;
    if (req) return 1;
   return intrans;
  endfunction : next intrans
  always @clk
    intrans <= next_intrans();</pre>
  al: assert property (req | -> nexttime[n] gnt);
  final begin
    a2: assert (!rst -> gnt || !(req && intrans))
      else $error("Outstatnding request at the end of simulation");
  end
endchecker : request_granted
```

The triggered Method in Checker Variable Assignments In Sect. 9.2.1.1 we stated that using triggered sequence method on the right-hand side of a nonblocking assignment in modules is meaningless because the nonblocking assignment is performed in the NBA region, while the triggered method is evaluated only later in the Observed region.

21.4 Checker Variables 483

This is not true for checkers: the triggered sequence method may be safely used in checker variable assignments, because checker variables are assigned in the Re-NBA queue of the Reactive region, after the evaluation of triggered.

It is safe to use the triggered sequence method in checker variable assignments.

Example 21.36. Disable checking assertions in a checker between the match points of sequences stop_check and start_check.

Solution:

```
checker toggle_check(sequence stop_check, start_check,
    event clk = $inferred_clock);
bit rst = 1;
default clocking @clk; endclocking
default disable iff rst;

function next_rst;
    if (stop_check.triggered) return 1;
    if (start_check.triggered) return 0;
    return rst;
endfunction : next_rst

always @clk
    rst <= next_rst();

al: assert property(...);
// More assertions here ...
endchecker : toggle check</pre>
```

Discussion: We defined a checker variable rst which is 1 between the match point of sequence stop_check until the match point of sequence start_check. For example, if the stop sequence consists of two consecutive stop signals, and the start sequence consists of two consecutive start signals, then the actual checker arguments would be stop[*2] and start[*2].

Procedural Checkers with Checker Variables The behavior of procedural checkers containing checker variables complies with the rules described in Sect. 21.3.3: the always procedure in a checker remains a separate process after instantiation.

```
Example 21.37. Consider the following instantiation of checker
stable_for_two_ticks defined in Example 21.29:
module m(input logic clock, reset, logic [7:0] en, ...);
  default disable iff reset;

logic cond;
logic [7:0] driver;
// ...
```

```
always @(posedge clock) begin
    for (int i = 0; i < 7; i++) begin
      if (en[i] && cond) begin
        driver[i] <= ...;
        stable for two ticks check driver(driver[i]);
      end
    end
  end
endmodule : m
  This is roughly equivalent to the following code:
module m(input logic clock, reset, logic [7:0] en, ...);
  default disable iff reset;
  logic cond;
  logic [7:0] driver;
  bit toggle = 1'b0;
  always @(posedge clock) begin
    for (int i = 0; i < 7; i++) begin
      if (en[i] && cond) begin
        driver[i] <= ...;
        a1: assert property (!toggle |-> $stable(driver[i]));
      end
    end
  end
  always @(posedge clock)
    toggle <= reset ? 1'b0 : !toggle;
endmodule : m
```

As usual, the real names toggle and all have a different hierarchy than in the inlined version of the checker. Also, the non-blocking assignment to checker variable toggle is performed in the Reactive region, and not in the Active region as in modules.

The resulting assertion at remains in the scope of the <code>for-loop</code>. In fact, this assertion is checked for all indices i for which en[i] && cond is true. The assignment of the checker variable <code>toggle</code> is performed in a separate process, and does not depend on the values of i and the condition en[i] && cond.

Checker stable_for_two_ticks may be safely instantiated in a procedural loop because the checker variable does not depend on the loop control variables. Otherwise, the checker instantiation in the loop would be illegal.

If a checker is instantiated in procedural loop, its variables should not depend on the loop control variables.

21.5 Covergroups in Checkers

Checkers can also encapsulate coverage collection statements. In SystemVerilog, there are two main engines to collect functional coverage: assertion cover statement and functional coverage using covergroup constructs (see Chap. 18). Both these statements are allowed in checkers. We have shown an example of using cover statement in checkers in Fig. 21.4. In this section, we focus on covergroups.

Example 21.38. Check that all states of the FSM are visited. Let the FSM states be described by the following enumeration:

```
typedef enum {
   INIT,
   IDLE,
   SEND,
   WAIT,
   RECEIVE,
   TO
} state_t;
```

The following checker collects coverage information about FSM states.

```
checker cover_fsm(state_t state, event clk = $inferred_clock,
    untyped rst = $inferred_disable);
    covergroup cg_state @clk;
        coverpoint state iff (!rst);
        option.per_instance = 1;
    endgroup : cg_state;
    cg_state cg = new();
endchecker : cover fsm
```

This checker contains a covergroup cg_state triggered by the clocking event @clk. Coverage is collected in bins defined by the values of the enumeration type state_t, but only when rst is low. Recall that for actual coverage collection to take place, it is required to instantiate the covergroup using the new operator.

It is possible to use checker variables in covergroups contained in the same checker.

Example 21.39. Cover time interval distribution between request req and acknowledgment ack.

Solution:

```
if (n == 0) return 0;
  return n + 1;
endfunction : next_n;

always @clk
  n <= next_n();

covergroup cg_win @(clk);
  coverpoint n iff (ack && !rst);
endgroup : cg_win
  cg_win cg = new();
endchecker : req_ack_window2</pre>
```

Sampling of n in the covergroup happens when the clocking event @clk takes place, i.e., before n is reset to 0.

We mentioned earlier that for efficiency reasons in FV, checker variables should have the smallest possible size. In this example, n is defined as <code>int</code> of size 32 bits. One reason for this declaration is that we do not know the maximal size of the time window, yet we need to reserve a large enough upper bound. More importantly, the goal of this checker is to collect coverage information in the covergroup in simulation where <code>int</code> variables are efficient. The checker is not intended for use in FV. \square

Exercises

- **21.1.** Section 21.1 discusses checking of a hub protocol. Among other statements to be checked we stated that <code>iready</code> and <code>oready</code> should not be asserted continuously over more than two consecutive clock ticks, but we did not provide an implementation of this statement. The reason for omitting it was the desire to keep the IP generic: the most general hub protocol should allow any sequence to represent hub input and output requests. However, in our implementation of the hub protocol the assertions about <code>iready</code> and <code>oready</code> should also be checked. To reuse the existing implementation of the generic protocol verification, it is possible to instantiate the generic checker in a more specific one.
- (a) Implement assertions checking that iready and oready may not be asserted continuously over more than two consecutive clock ticks.
- (b) Implement a verification entity that checks the specific hub protocol as a module. To check the generic protocol, instantiate the module from Fig. 21.2 in this new module. Modify the code of module hub in Fig. 21.3 to invoke the new module verifying the more specific hub protocol.
- (c) Implement the verification entity checking the specific hub protocol as a checker. To check the generic protocol instantiate the checker from Fig. 21.4 in this new checker. Modify the code of module hub in Fig. 21.5 to invoke the new checker verifying the more specific hub protocol.
- **21.2.** Why cannot property at_most_one_req from Fig. 21.2 be implemented as en |-> req[=0:1] ##1 en?

- **21.3.** Write a checker verifying that each request is followed by a grant, and that the request happens at least once.
- **21.4.** Example 21.9 introduces a checker simple_reset to verify that the reset signal is initially low' then it eventually goes low and remains low forever.
- (a) Modify this checker to make it generic. The new checker should accept the assertion clock as an optional argument. This argument should default to \$global clock.
- (b) If the reset remains always high, the checker assertion will not fail in simulation. How the checker should be modified to ensure that a more meaningful scenario is exercised in simulation?
- (c) What will the checker verify if followed-by (suffix conjunction) #=# is replaced with suffix implication |=>?
- **21.5.** Which clocking event will be inferred in assertion at in the following checker? Explain.

```
checker mycheck(a, event clk1, clk2 = $inferred_clock);
  default clocking @clk1; endclocking
  always @clk2 al assert property (a);
endchecker : v

module m(...);
  logic x, y;
  //...
  always @(posedge clk) begin
    x <= y;
    mycheck cl(x, negedge clk);
  end
endmodule : m</pre>
```

- **21.6.** Write a checker verifying the FIFO protocol from Sect. 15.3. You can use local variables.
- **21.7.** Write a checker verifying the tag protocol from Sect. 15.4. You can use local variables.
- **21.8.** Write a checker verifying the sequential protocol from Sect. 15.2 without using local variables. Do you need to use the system function \$sampled in the checker modeling code?

Chapter 22 Checkers in Formal Verification

Hope is a great falsifier. Let good judgment keep her in check.

— Baltasar Gracian

In this chapter, we discuss applications of checkers to formal verification. As we mentioned in Chap. 21, all the content of the checker body, except for covergroups, is synthesizable and may be used in formal verification. There is an additional feature of checkers, important for FV, which was not described there – free variables. Free variables allow building of abstract nondeterministic models and reasoning about them. As was discussed in Chap. 10, abstract models are an over-approximation of the DUT, and if an assertion has been proven for them, then it also holds for the DUT. Good abstraction hides irrelevant details and yields a simpler model on which to conduct FV. For example, to reason about a pipeline latency, the exact data passed through the pipeline and the exact operations at specific pipeline stages may be immaterial and may be abstracted out. Checkers provide natural building blocks for these abstract models, and their usage in FV modeling is similar to the usage of module in RTL.

Checker free variables and rigid variables (i.e., constant free variables) described in this chapter also provide a viable alternative to assertion local variables. Both methods have their own advantages and disadvantages.

This chapter is written from the formal verification point of view; simulation plays only an auxiliary role here.

22.1 Free Variables

Free variables in checkers have the same syntax as regular checker variables, but they are prefixed with the keyword rand. If a free variable is unrestricted, it may assume any value at any time. In some sense, a free variable is similar to a primary input of the model.

22.1.1 Free Variables in Assertions

We will study first the behavior of free variables in an assertion context. The following statement characterizes the semantics of free variables:

The formal semantics of a free variable in an assertion context is obtained from universal quantification over its domain in each clock tick.

Example 22.1. Consider the following checker:

```
checker failure;
  default clocking @$global_clock; endclocking
  rand bit v;
  al: assert property(v);
endchecker : failure
```

Recall the formal semantics of the assertion **always** a, where a is a regular variable: $\forall i \ w^i \models a$, which means that a holds in each clock tick on the trace w. If we want to stress that the value of a depends on the clock tick i, we can rewrite this formula as $\forall i \ w^i \models a^i$. In this formula, we assume that a is well defined, that is the values of a are given in each clock tick. In our case, when v is a free variable, it may assume any value in any clock tick, and therefore the formal semantics of the assertion a1 is $\forall i \ \forall v^i \ w^i \models v^i$, which is apparently false. The important consideration here is that the formal semantics of the free variable is obtained from a universal quantification over its domain in each clock tick.

Example 22.2. The assertion a2 in the following checker passes:

```
checker success;
  default clocking @$global_clock; endclocking
  rand bit v;
  al: assert property(v || !v);
endchecker : success
```

The reason for the success of this assertion is that its underlying expression is a tautology: it holds for any values of v. The formal semantics of this assertion is $\forall i \forall v^i \ w^i \models v^i \lor \neg v^i$, and this formula is true.

If the same free variable is used in two assertions, it does not introduce any relation between these two assertions. We have the same situation as in first-order logic: the names of bound variables are not important. For example, both statements $\forall x \ x \le 0$ and $\forall x \ x > 0$ are false, though there is no x such that both $x \le 0$ and x > 0 hold.

¹ Ironically enough, bound variables in first-order logic correspond to free variables in SVA.

Example 22.3. In the following checker

```
checker check;
  default clocking @$global_clock; endclocking
  rand bit v;

al: assert property (s_eventually v);
  a2: assert property (s_eventually !v);
endchecker : check
```

both assertions a1 and a2 fail. One of the possible counterexamples for the assertion a1 is v=0, 0, ..., while a possible counterexample for a2 is v=1, 1, These two assertions do not have common counterexamples: either v or v should happen infinitely often on a given trace, but this fact does not prevent them both to fail. Recall that free variables are just a convenient representation of the universal quantification over their domains, and all assertions are quantified independently.

All occurrences of the same free variable referenced at that same time in the same assertion have consistent values, as explained in Example 22.2.

22.1.2 Free Variables in Assumptions

What happens if free variables are referenced within assumptions? To keep the notation clear, we will assume that there is one free variable v, two assumptions q_1 and q_2 and two assertions p_1 and p_2 . The assertion p_1 in the presence of the assumptions is equivalent to the property $q_1 \land q_2 \rightarrow p_1$ (see Sect. 20.1.2.1). Analogously, p_2 is equivalent to the property $q_1 \land q_2 \rightarrow p_2$. As we discussed in Sect. 22.1.1, the values of v in formulas $q_1 \land q_2 \rightarrow p_1$ and $q_1 \land q_2 \rightarrow p_2$ are taken independently. However, in order for both of these properties to hold, it is sufficient to check on a given trace that p_1 and p_2 hold for all values of v that satisfy both assumptions q_1 and q_2 .

Assumptions with free variables constrain the free variable domains for all assertions using these free variables.

Example 22.4. Consider the following checker:

```
checker check;
  default clocking @$global_clock; endclocking
  rand bit[5:0] v;
  m1: assume property (v > 2);
  m2: assume property (v < 7);
  a1: assert property (v > 1);
  a2: assert property (s_eventually v <= 5);
  a3: assert property (s_eventually v > 5);
endchecker : check
```

Assumptions m1 and m2 constrain the free variable v for all assertions such that v may only assume values 3, 4, 5, and 6 in all global clock ticks. This statement does not mean that v is not allowed to assume other values, but only that it is sufficient to check the assertions for these values of v. For all other values of v, all the assertions are vacuously true under the assumptions.

Assertion at holds since it holds for the constrained values of v. Assertions at and at fail, as explained in Example 22.3.

22.1.3 Free Variables in Cover Statements

As defined in Sect. 11.3.3, the property p is covered iff there is a trace that satisfies p. If p depends on a free variable v then in order for p to be covered it should be possible to choose such values of v in each position on the trace so that p becomes satisfied. Therefore, we come to the following characterization of free variables in the coverage context:

The formal semantics of a free variable in a coverage context is obtained from existential quantification over its domain in each clock tick.

Example 22.5. Consider the following checker:

```
checker check(bit a);
  default clocking @$global_clock; endclocking
  rand bit v;
  c1: cover property ((a && v)[*2]);
  c2: cover property ((a || v)[*2]);
endchecker: check
```

If a is always low, c1 is not covered, while c2 is. There are no values of v that could cause the sequence (a && v) [*2] to match. If v is 1 in clock ticks 0 and 1, the sequence (a | | v | *2 | has a match in clock tick 1.

If free variables are constrained with assumptions, these constraints should be taken into account when evaluating the coverage.

Example 22.6. Consider the following checker:

```
checker check;
  default clocking @$global_clock; endclocking
  rand bit v;
  m1: assume property ($steady_gclk(v));
  c1: cover property (v ##1 !v);
endchecker : check
```

Cover statement c1 cannot be covered because of assumption m1 imposed on the free variable v, which requires it to keep the same value all the time. Without m1, c1 is covered in clock tick 1: it is sufficient to choose the value of v to be 1 in clock tick 0 and 0 in clock tick 1. \Box

22.1.4 Building Abstract Models With Checkers

Checkers with free variables can be used to build nondeterministic models for FV.

Example 22.7. Consider a pipeline consisting of n stages. Each stage has its own enabler signal en[i], where i is the number of the stage. This signal en[i] is asserted when the i-th stage is ready to process the new data. When the data is ready at the pipeline input, the data_ready flag is asserted. We want to write a checker verifying that the pipeline latency (the number of clock ticks required to pass through the pipeline) does not exceed max latency.

The RTL implementing this model may be very complex, but the exact data and exact operations performed in the pipeline are not important for our purpose. We can build an abstract model as a checker that will only take into account the progress of the data in the pipeline. This checker is shown in Fig. 22.1.

At the beginning of the checker, there are definitions of the checker variables and several let-definitions provided for convenience.

ub(x) (line 7) defines an upper bound of a vector that can store the value x. The lower bound of the vector is understood to be 0. For example, if x = 5 then 3 bits are needed to store x. The upper bound of this vector will be 2 assuming that its lower bound is 0.

The variable stage (line 12) contains the number of the active stage, the first stage having the number of 1. The stage can also assume values of two dummy stages: stage 0, meaning that the data has not been sent to the pipeline yet, and the stage nstages (line 8), which exceeds the number of actual stages by 1, signaling that data has been fully processed by the pipeline.

The variable latency (line 13) keeps the current latency of the data. It is limited by max_latency + 1 (big_latency, line 10) - in our implementation, if the latency reaches this value, it is not incremented anymore, as the exact value of the latency is not important, only the fact that the latency has exceeded the maximal allowed value.

The main point in this checker is to understand when the transaction starts. There may be many simultaneous transactions in the system, different data may be simultaneously processed by different stages of the pipeline, and therefore, checking the condition data_ready alone is not sufficient for counting the stage and latency. The clue here is to introduce a free variable start (line 5) and to start counting each time when both start and data_ready become simultaneously true the first time. Thus, we effectively consider all combinations of possible attempts, and among them also all possible single attempts. For convenience, we introduce the name go (line 6) for the simultaneous occurrence of data_ready and start.

For example, assume that data_ready is high in clock ticks 10. The following scenarios are possible:

- 1. start is low in both clock ticks 10 and 20.
- 2. start is low in clock tick 10 and it is high in clock tick 20.
- 3. start is high in clock tick 10 and it is low in clock tick 20.
- 4. start is high in both clock ticks 10 and 20.

```
checker check latency(en, data ready, max latency, clk =
         $inferred clock, rst = $inferred disable);
       default clocking @clk; endclocking
2
       default disable iff rst;
3
4
       rand bit start;
       let go = data_ready && start;
6
       let ub(x) = $clog2(x + 1) - 1;
       let nstages = $bits(en) + 1;
8
       let stage ub = ub(nstages);
       let big latency = max latency + 1;
10
       let latency_ub = ub(big latency);
11
       bit [stage_ub:0] stage = '0;
12
       bit [latency ub:0] latency = '0;
13
14
       function type (stage) next stage;
         if (rst) return 0;
16
         if (stage == 0 && go) return 1;
17
         if (stage != 0 && stage != nstages && en[stage])
18
19
           return stage + 1;
         return stage;
20
       endfunction : next stage
21
22
       function type(latency) next_latency;
23
         if (rst || latency == 0 && !go) return 0;
24
         if (latency == big latency) return big latency;
25
         return latency + 1;
26
       endfunction : next latency
27
28
       always @clk begin
29
         stage <= next stage();
30
         latency <= next latency();</pre>
31
32
33
       al: assert property (
34
         $rose(stage == nstages) -> latency != big latency);
35
     endchecker: check latency
```

Fig. 22.1 Checking pipeline latency

In the first case, we never start counting, and do not check anything; in the second case, we check only the transaction starting in clock tick 20; in the third case, we check only the transaction starting in clock tick 10; and in the fourth case, we follow the transaction starting in clock tick 10, and when the second transaction comes in clock tick 20, it is ignored in the checker, since the checker follows only one transaction. Why? Essentially, in the fourth case we check the same scenario as in the third one, since a subsequent go does not restart counting. Since in FV we consider all four scenarios together, we will be able to detect a maximal latency violation for both transactions (if it happens): for the first one in the third and in the fourth cases, and for the second one in the second case.

Lines 15–21. Initially, stage is 0, and it is not incremented until go becomes 1, which may happen in an arbitrary clock tick when the data_ready is high, as start is a free variable. Otherwise, the stage number is incremented when the en control of the corresponding stage is asserted, provided the data has not passed through the entire pipe, i.e., provided stage != nstages.

Lines 23–27. Initially, the value of latency is 0, and it is not incremented until the free variable start is asserted and data_ready is high. Then it is incremented each clock tick until the max_latency is exceeded (the value of big_latency is reached). Then it remains stuck at the value of big_latency forever.

The assertion a1 (line 34) checks that when data leaves the pipeline, that is when stage becomes nstages for the first time, latency should not exceed max_latency. Note that in this case it is safe to use the sampled value function \$rose in the antecedent (see Sect. 6.2.1.3), since by construction, stage cannot assume the value nstage at the beginning or immediately after the rst deactivation. Note also that we chose latency != big_latency, and not latency < big_latency, since the synthesis model of the former expression is more efficient than that of the latter, and therefore the former expression is also more efficient in FV than the latter.

22.1.5 Constrained Free Variables

One way to constrain the values of free variables is to make them appear in assumptions (see Sect. 22.1.2).

Example 22.8. In Example 22.7, the free variable start was unconstrained, and as a result it could freely oscillate on the trace. Although, as we have seen, this oscillation does not affect FV correctness, it may affect FV performance,² as many redundant traces are considered. For instance, the fourth scenario in Example 22.7 is redundant, as was explained there. We can use the following assumption to get rid of these redundant scenarios:

```
m1: assume property (start | => always !start);
```

The assumption m1 says that start may be high at most in one clock tick.

We might want to get rid of other useless behaviors, those in which start does not happen at all or in which it is not synchronized with data_ready. This can be remedied with the following assumption:

initial

```
m2: assume property (s eventually(start && data ready));
```

Note, however, that the assumption m2 is likely to affect negatively the performance of most FV tools. \Box

² This is highly dependent on the specific tool.

Using assumptions, it is possible to assign values to the checker arguments, even though all checker arguments are input by definition (Sect. 21.2).

Example 22.9. Consider the following checker code:

```
checker check1(...);
  rand bit [7:0] v;
  // ...
  check2 mycheck(v);
endchecker : check1

checker check2(a);
  m1: assume #0 (a == 3);
endchecker : check2
```

The free variable v of the checker check1 is effectively assigned the value 3 in the checker check2, even though a is an input argument in that checker.

22.1.5.1 Random Choice

In FV modeling, it may be useful to define an expression that may assume only values from a specific set, for example, only values 2 and 5. The straightforward way to do this is to define a three-bit free variable and add an assumption constraining its value, such as:

```
rand bit [2:0] v; m1: assume property(@$global_clock v == 3'3 ||
    v
== 3'5);
```

However, a better solution would be to define a one-bit free variable and to use a let-expression instead:

```
rand bit x; let v = x ? 3'3 : 3'5;
```

In some cases, the let-expression may be written even more efficiently. For example, if it is needed to define an expression v assuming only values 3'2 and 3'6, it can be implemented as:

```
rand bit x; let v = \{x, 2'b10\};
```

Efficiency Tip Expressions with unconstrained free variables are usually more efficient than free variables constrained with assumptions.

22.1.5.2 Initialized Free Variables

Free variable initialization constrains only the initial value of the free variable; all its other values remain unconstrained.

Example 22.10. Consider the following checker:

```
checker check1;
  rand bit rst = 1'b1;
  bit a = 1'b0;
  bit b = 1'b0;

  default clocking @$global_clock; endclocking
  default disable iff rst;

  always @$global_clock
    a <= 1'b1;

  al: assert property (a);
  a2: assert property (b);
endchecker : check1</pre>
```

The first tick of the global clock happens at time 0, and both assertions al and al are disabled since the value of rst at time 0 is 1. At the next tick of the global clock, all either passes because the value of a has been set to 1 or is disabled. On the contrary, the assertion all fails because b is always 0 (it is not a free variable, so it keeps its value all the time until it is assigned), while rst is constrained only in the global clock tick 0. For example, the trace rst = 1, 0, ... violates assertion all.

Now, let us modify our checker to make it be controlled by some general clock:

```
checker check2(event clk);
  rand bit rst = 1'b1;
  bit a = 1'b0;
  bit b = 1'b0;

  default clocking @clk; endclocking
  default disable iff rst;

  always @clk a <= 1'b1;

  al: assert property (a);
  a2: assert property (b);
endchecker : check2</pre>
```

In checker check2, assertion a2 fails for the same reason as in checker check1. The behavior of assertion a1 now depends on the waveform of clk: if clk ticks for the first time at time 0 then assertion a1 will not fail, as in the checker check1. Otherwise, it will also fail, since the value of rst is constrained only in the global clock tick 0.

Formal Semantics of Free Variable Initialization A free variable initialization

```
rand some_type v = e;
is equivalent to the following assumption:
initial
  assume property (@$global clock v === e);
```

22.1.6 Free Variable Assignment

Free variables may be assigned.

Example 22.11. The following checker fragment defines a periodic clock, myclk:

```
rand bit myclk; always @$global_clock
  myclk <= !myclk;</pre>
```

In this example, myclk is assigned, but uninitialized. myclk ticks every tick of the global clock and matches its period, i.e., two ticks of the global clock. Nonetheless, this clock is nondeterministic: since it is uninitialized, it allows two patterns: 0101...and 1010....

22.1.6.1 Formal Semantics of Free Variable Assignment

```
The free variable assignment controlled by the global clock
```

```
rand some_type v; always @$global_clock v <= e;</pre>
```

has the same meaning as the assumption:

```
assume property (@$global clock $future gclk(v) === e);
```

For readability, we will extend the formal notation from Chap. 11: free variable assignment will be designated as $v' \leftarrow e$, meaning that the next state variable of v' is assigned the value e, which is just a shortcut notation for the invariant defined by the assumption: G(v'=e). This invariant defines a transition relation in which v' is uniquely defined by e. This transition relation happens to be a function: the next state variable is a function of the current state variables forming the expression e. This kind of transition relation is called a *next state function*. Because of its explicit unidirectionality, FV tools may handle free variable assignments more efficiently than equivalent assumptions.

```
Example 22.12. The assignment form Example 22.11 can be rewritten as
```

```
assume property (@$global_clock $changing_gclk(myclk));
```

but this version might be less efficient, since the explicit unidirectionality of the assignment of the free variable myclk is lost here.

The semantics of the free variable assignment $v' \leftarrow @(\texttt{edge}\ clk)\ e$, which is controlled by the clocking event $@(\texttt{edge}\ clk)$, is defined as $v' \leftarrow (clk \neq clk')$? e:v. This means that v gets the value e only when the clock ticks, and it stores its old value when the clock does not tick. In this case, we have a next state function $v \leftarrow f(e,v,clk,clk')$, where $f(e,v,clk,clk')=(clk \neq clk')$? e:v. This is a more general form than in the case of the global clock: there the right-hand side of the free variable assignment depended only on the current state variables, while here it depends also on the next state variable clk'. From a theoretical point of view, there is no issue in allowing next state variables in the right-hand side of the assignment. System Verilog does not, however, allow explicit specification of next

state variables in the right-hand side, and therefore they can be referenced there only implicitly through the event control.

Other forms in which the clocking event controls a free variable assignment are treated in similar ways (see Exercise 22.5).

Example 22.13. We revisit Example 22.11 to define the myclk to be synchronized by some specific clock clk:

```
rand bit myclk; always @clk
  myclk <= !myclk;</pre>
```

Here, myclk ticks every two ticks of clk. Since the initial value of myclk is undefined, the code allows two patterns: 0101... and 1010.... Note that according to the formal semantics of the free variable assignment, myclk keeps its value between two consecutive ticks of the clock clk.

It is possible to replace the assignment with the following equivalent assumption (which is less efficient):

```
m1: assume property (@$global_clock $future_gclk(myclk) ==
($changing gclk(clk) ? !myclk : myclk));
```

One might be tempted to write the following assumption m2 instead:

```
m2: assume property (@clk ##1 $changed(myclk));
```

m2 states that myclk changes from every tick of clk to the next,³ but assumption m2 *is not equivalent* to the free variable assignment. m2 only states that myclk has different values at consecutive ticks of clk, imposing no restrictions on the free variable behavior between the ticks of clk, while the assignment semantics requires keeping the free variable stable between them.

Efficiency Tip It is preferable to assign free variables than to constrain them with assumptions.

22.1.6.2 Fully Assigned Free Variables

As we have seen, free variable assignment leaves little freedom to them: only their initial value remains undefined. If we also initialize them, there remains no freedom introduced by these variables. Such free variables are called *fully assigned free variables*. Essentially, there is no difference between regular checker variables and fully assigned free variables.

Example 22.14. Consider the following code:

```
checker check1(a, b, event clk = $inferred_clock);
rand type(b) v = a;
```

³ Recall (Sect. 6.2.2) that it is illegal to use future sampled value functions with arbitrary clocks, so we have to use a past value function here delayed by one clock tick.

```
always @clk
   v <= b;
endchecker : check1</pre>
```

In the checker check1 the free variable v is fully assigned, and it may be replaced by a regular checker variable, as in the checker check2:

```
checker check2(a, b, event clk = $inferred_clock);
  type(b) v = a;
  always @clk
    v <= b;
endchecker : check2</pre>
```

Thus, regular checker variables can be considered a special case of free variables, and the formal semantics of their assignments is a special case of the formal semantics of free variable assignment (see Sect. 22.1.6).

22.1.6.3 Assigning Free Variables to Checker Variables

It is legal to assign an expression containing free variables to a regular checker variable; it is also possible to initialize a regular variable with an expression containing free variables. This means that the regular variables may also be nondeterministic. However, the regular variables don't introduce any new nondeterminism to the system; their values are completely defined by the values of the variables on which they depend.

Example 22.15. Consider the following checker fragment:

```
bit [3:0] a; rand bit [3:0] v;
always @clk a <= v;</pre>
```

If the value of v is nondeterministic, the value of a is nondeterministic also starting from clock tick 1. (The initial value of a is 0 by default – only a free variable can introduce nondeterminism through its initial value, and then only if it has not been explicitly initialized.) Nevertheless, a is deterministic in the following sense: its value is uniquely defined by the value of v; a does not introduce any new nondeterminism.

Example 22.16. Nondeterminism can also be introduced by an event control, as illustrated by the following checker fragment:

```
rand bit clk; bit [3:0] a; always @clk
  a <= e; // e - deterministic expression defined elsewhere</pre>
```

In this example, the clocking event @clk is nondeterministic, and so also is the value of a because the assignment is performed at nondeterministic time moments. However, a is deterministic in the sense that it does not introduce any new nondeterminism: its value is fully defined by the values of e and clk.

The nondeterminism associated with the clocking event is not of an essentially different kind because the effect of the clocking event can be pushed into the right-hand side of a checker variable assignment:

```
always @clk
  a <= e;
has the same formal semantics as
always @$global_clock
  a <= $changing_gclk(clk) ? e : a;</pre>
```

A situation similar to assignment of a free variable to a checker variable arises when a free variable of one checker is passed to another checker as an argument. Formal arguments of a checker can never be declared as free variables. All checker arguments are input, so they cannot introduce any additional nondeterminism.

Example 22.17. The checker check1 below defines a free variable v and passes it to the checker check2.

```
checker check1;
  rand bit v;
  check2 c2(v, $global_clock);
endchecker : check1

checker check2(a, clk = $inferred_clock);
  al: assert property (@clk not always a iff s_eventually !a);
endchecker : check2
```

In the checker, <code>check2</code> the formal argument a is untyped. We could define it to be of the type <code>bit</code>, but *not* of the type <code>rand bit</code> since formal checker arguments cannot be free variables.

22.1.7 Free Variables and Functions

Free variables cannot be declared in functions, but they can be referenced in the declaration of a function within a checker and they can also be passed as arguments to functions. We have already seen direct referencing of free variables in functions in Example 22.7, where functions next_stage and next_latency referenced the free variable start defined in the same checker. We could rewrite the checker check_latency from Example 22.7 so that the let expression go, which depends on the free variable start, is passed as an argument to these functions, as shown in Example 22.18.

Example 22.18. Figure 22.2 shows the checker check_latency from Example 22.7, recoded so that instead of referencing of the free variable start in functions (through 90), the let expression 90 is passed as an argument to these functions.

Note that the argument of the functions is declared as bit, and not as rand bit. As with assignment of free variables to regular checker variables, these functions do not introduce any additional nondeterminism.

```
checker check latency(en, data ready, max latency, clk =
2
   $inferred clock, rst = $inferred disable);
     default clocking @clk; endclocking
3
     default disable iff rst;
5
     let go = data ready && start;
6
     let ub(x) = $clog2(x + 1) - 1;
     let nstages = $bits(en) + 1;
     let stage_ub = ub(nstages);
     let big latency = max latency + 1;
10
     let latency ub = ub(big latency);
11
     bit [stage ub:0] stage = 0;
     bit [latency_ub:0] latency = 0;
13
     rand bit start;
14
15
     function type(stage) next stage(bit go);
       if (rst) return 0;
17
       if (stage == 0 && go) return 1;
       if (stage != 0 && stage != nstages && en[stage])
19
         return stage + 1;
20
       return stage;
2.1
     endfunction : next stage
22
23
     function type(latency) next_latency(bit go);
24
       if (rst | | latency == 0 && !go) return 0;
25
       if (latency == big latency) return big latency;
26
       return latency + 1;
2.7
     endfunction : next latency
28
29
     always @clk begin
30
       stage <= next stage (go);
31
       latency <= next latency(go);</pre>
32
33
34
     al: assert property (
35
       $rose(stage == nstages) -> latency != big latency);
36
   endchecker: check latency
```

Fig. 22.2 Passing a free variable to functions

22.1.8 Free Variables in Simulation

So far we have discussed the formal semantics of free variables. In this section, we discuss the behavior of free variables in simulation.

As their syntax suggests, free variables are randomized in simulation. All uninitialized free variables are randomized initially. Otherwise, only unassigned free variables are randomized. The following rules are applicable to all randomized free variables:

 A randomized free variable may change its value at most once during each simulation tick.

- If a randomized free variable gets a new random value in some simulation tick, this value becomes ready before the Observed region.
- The values of free variables are never sampled, even in concurrent assertions.

22.1.8.1 Checkers Without Assumptions

If there are no assumptions in a checker or any of its child checkers, then the checker free variables can get new values in any time-step.

Example 22.19. In Example 22.7, there are no assumptions, and so the simulator may assign the free variable start a new random value at any simulation step. One extreme case would be assigning it a random value only once, at its initialization, and then leaving it unchanged. The other extreme case would be assigning it a new random value at each simulation step. Both behaviors are legal. However, the first behavior is too "boring", while the second one is an overkill: there is no advantage in changing the value of start every simulation tick since all the assignments and the assertions where it is used are controlled by clk. Therefore, most simulators will assign start a new random value at every tick of clk.

22.1.8.2 Assigned Free Variables

If a free variable is assigned a value, then it is only randomized at its initialization, provided it is not initialized. If a free variable is unassigned, but initialized, it is randomized, but not at its initialization. If a free variable is both initialized and assigned, it is not randomized.⁴

Example 22.20. Consider the following code:

```
checker check(..., clk = $inferred_clock);
  rand bit v;
  rand bit w = 1'b0;

always @clk
  v <= ...;
  // ...
endchecker : check</pre>
```

⁴ If a free variable is of an aggregate data type – array or structure, some of its elements may be assigned, while others remain unassigned. The LRM defines that all elements of the singular data types (i.e., of all data types except unpacked ones) should be randomized monolithically, whereas different elements of the unpacked data types may be randomized independently: some elements may be randomized, while other may be not.

In the checker check, the free variable v is randomized at its initialization only, whereas the free variable w may be randomized at every simulation step except for step 0, where the value of w is 0.

22.1.8.3 Checkers With Assumptions

The set of all assumptions contained in a checker instance and in its child checkers is called the *assume set* of the checker instance.⁵ If the assume set of a checker instance is nonempty, then the unassigned free variables are randomized in each tick of any clock event used in any assumption of the assume set. The random values of the free variables should be chosen in a way to satisfy all the assumptions in the assume set, if possible – this means that no assumption from the set should fail at the simulation step when the new randomization values have been assigned if such values exist. However, lookahead analysis is not required in constraint solving. In time-steps that are not ticks of any clock in the assume set, the unassigned free variables may be randomized arbitrarily.

Example 22.21. The assumption set of the checker check1 consists of the single assumption m1. This assumption is clocked by two clocks, clk1 and clk2.

```
checker check1(sequence s, ..., event clk1, clk2);
  rand bit [3:0] v, w, r;
  // ...
  m1: assume property (@clk1 s |-> @clk2 v + w < 7);
endchecker : check1</pre>
```

There are three free variables v, w, and r in the checker, all of them uninitialized and unassigned. All three variables are randomized every tick of clkl and of clkl, even though r does not enter the assumption ml. The randomized values of r are unconstrained, whereas the randomized values of v and of w are constrained by the assumption ml.

Example 22.22. In the code fragment below, checker check1 from Example 22.21 is rewritten so that the assumption m1 has been moved to separate checker c2. Although there are no more assumptions in checker check1, the assumption set of checker check1 consists of assumption mycheck.m1, and the simulation of free variables v, w, and r is exactly the same as in Example 22.21.

```
checker check1(sequence s, ..., event clk1, clk2);
  rand bit [3:0] v, w, r;
  // ...
  check2 mycheck(s, v, w, clk1, clk2);
endchecker : check1
```

⁵ There are several subtleties concerning assumption set definition for procedural checker instantiations and for instances involving const cast of checker arguments. These are not covered here. Refer to the LRM [7] for the exact definitions.

П

П

Example 22.23. In the following checker

```
checker check1(sequence s, ..., event clk1, clk2);
  rand bit [3:0] v, w, r;
  // ...
  always @clk1
    w <= v + 1;
  m1: assume property (@clk1 s |-> @clk2 v + w < 7);
endchecker : check1</pre>
```

free variable w is randomized *only* at its initialization, as it is assigned a value. Free variables v and r are randomized every tick of the clocks clk1 and clk2. The random constraint imposed by assumption m1 is used to randomize the value of v. \Box

If the randomization constraint imposed by the checker assumptions cannot be solved, the free variables may be assigned arbitrary values, and the corresponding assumptions fail.

Example 22.24. In the following checker

```
checker check(..., event clk);
  default clocking @clk; endclocking
  rand bit [3:0] v, w;
  //...
  m1: assume property (v + w < 2);
  m2: assume property (v + w > 3);
endchecker : check
```

assumptions m1 and m2 cannot be satisfied together. Arbitrary values of v and w will be chosen in each clock tick, and the failure of an appropriate assumption will be reported. For example, if in clock tick 0 the value 0 was assigned to both v and w, assumption m1 would pass and assumption m2 would be violated. If in clock tick 1 v gets the value of 1 and w gets the value of 2, then both assumptions will be violated.

Example 22.25. In the following checker

```
checker check(..., event clk);
  rand bit v;
  //...
  m1: assume property (@clk v |-> ##3 1'b0);
endchecker : check
```

the value of the free variable v must always be low to satisfy assumption m1: if in some clock tick v is high, the assumption m1 will fail in three clock ticks. However, in simulation there is no obligation to satisfy the assumptions in future clock ticks, and your simulator can choose the value 1 for v in some clock tick, as it does not result in violation of the assumption in the same clock tick. Of course, in this case, assumption m1 will fail in three clock ticks.

If there are deferred assumptions in the assumption set, all checker free variables are randomized at every tick of a clock from a concurrent assumption from the assume set and, in addition, they may also be randomized in any other simulation time-step.⁶

Example 22.26. In the following checker

```
checker check(..., event clk);
  rand bit v, w;
  // ...
  m1: assume #0 ($onehot0({v,w}));
  m2: assume property (@clk v |=> w);
endchecker : check
```

free variables v and w must be randomized every tick of clk and, in addition, they may be randomized in any simulation tick.

Efficiency Tip Constraining free variables by assumptions significantly slows down the simulation and sometimes even leads to bogus assumption violations. It is always preferable to use unconstrained free variables and their assignments whenever possible. However, from a methodological point of view assumptions on the model interface may be desirable for assume-guarantee reasoning.

Free variable support in simulation does not provide correctness confidence even for a given simulation trace, but just shows one arbitrary realization of the free variables in time. In the presence of temporal assumptions, an assumption failure in simulation does not necessarily signify incorrectness of the implementation.

22.1.9 Free Variables Versus Local Variables

Sometimes it is possible to achieve the same goal by using sequence or property local variables instead of checker free variables. For instance, the checker described in Example 22.7 can be implemented as an assertion with local variables, as discussed in Exercise 22.1. Both approaches have their own advantages and drawbacks:⁷

• Processing of unconstrained free variables is straightforward for FV tools. Although free variables impose a heavy burden on FV, they are efficiently synthesized. Sophisticated assertions with local variables may be difficult to synthesize, and their synthesis may introduce substantial inefficiency *in addition* to the inefficiency introduced by free variables.

⁶ This is our interpretation of the standard. The standard is not explicit about free variable randomization with deferred assumptions.

⁷ We only consider a situation where the same specification cannot be straightforwardly implemented without using both local and free variables.

22.2 Rigid Variables 507

• If the modeling required for the abstract model is complex, it is difficult to keep the assertions with local variables of manageable size. Some modularity may be achieved by partitioning complex properties into subproperties. Splitting these assertions into several smaller assertions is also problematic, since different assertions cannot share their local variables, and one will have to duplicate many common parts of the modeling in different assertions. On the contrary, when using free variables the modeling can be shared.

- For manageable models, using local variables is more intuitive and readable than using free variables.
- Local variables can easily be checked in simulation, while simulation support of free variables is poor.

22.2 Rigid Variables

Free variables defined in Sect. 22.1 can assume any value at any simulation step. *Rigid variables* may assume any value initially, but their values do not change in time. In other words, rigid variables are just constant free variables, which is reflected in their syntax. For example,

```
rand const bit [3:0] r;
```

is a declaration of a rigid variable r. This variable may assume any 4-bit value, but this value remains unchanged all the time. Note that the rand qualifier must appear first; const rand is illegal.

It is easy to model rigid variables with free variables. For example, the above rigid variable r is equivalent to:

```
rand bit [3:0] r; assume property(@$global_clock $steady_gclk(r))
;
```

Rigid variable initialization is legal, but it renders the rigid variable equivalent to a non-free constant variable:

```
rand const bit [3:0] r = 4'd5;
is equivalent to
const bit [3:0] r = 4'd5;
```

We will always assume that rigid variables are uninitialized. Of course, it is illegal to assign a rigid variable, as it is illegal to assign any constant variable.

Example 22.27. The checker same1 verifies that two large data words contain the same value:

```
checker same1(bit [127:0] word1, word2,
  event clk = $inferred_clock);
  al: assert property (@clk word1 == word2);
endchecker : same1
```

This equality check is expensive as the size of the words is big. For some FV tools, ⁸ it might be more efficient to choose an arbitrary bit and check that its values in both words coincide. This may be achieved by introducing a rigid variable i that indicates which bit in the words to compare, as implemented in the checker same 2:

```
checker same2(bit [127:0] word1, word2,
  event clk = $inferred_clock);
  rand const bit [6:0] i;
  a2: assert property (@clk word1[i] == word2[i]);
endchecker : same2
```

Assertion a2 compares only one bit in two words instead of comparing 128 bits as in assertion a1. This comes, however, at a price of introducing a 7-bit rigid variable i.

Example 22.28. Checker data_consistency1 verifies that the output data out_data at the end of a transaction (end_t asserted) has the same value as the input data in_data at the beginning of the transaction (start_t asserted).

Assume for simplicity that both in_data and out_data are of type bit [1:0]. Then the assertion a1 is equivalent to the set of the four assertions:

```
a10: assert property (start_t && 2'b00 == in_data ##1 end_t[->1]
|-> out_data == 2'b00); a11: assert property (start_t && 2'b01 == in_data ##1 end_t[->1] |-> out_data == 2'b01); a12: assert
property (start_t && 2'b10 == in_data ##1 end_t[->1] |-> out_data == 2'b10); a13: assert property (start_t && 2'b11 == in_data ##1 end_t[->1] |-> out_data == 2'b10);
```

Thus, specifying the rigid variable data is equivalent to checking the data correspondence for all possible in_data values. 9

We can rewrite assertion a1 using local variables instead of rigid variables:

```
checker data_consistency2(start_t, end_t, in_data, out_data,
event clk = $inferred_clock, rst = $inferred_disable);
  default clocking @clk; endclocking
  default disable iff rst;

property data_consistent;
  type(in_data) data;
```

⁸ It highly depends on the specific tool.

⁹ In PSL, the construct similar to rigid variables is even called *forall*.

22.2 Rigid Variables 509

Using rigid variables in the checker data_consistency1 is even syntactically similar to local variables, only instead of assigning to a local variable, one should compare with a rigid variable. In this sense, local and rigid variables are interchangeable when in the beginning of the transaction they store a value of some data and then simply reference this value later in the transaction.

If transactions do not overlap, then the usage of both rigid and local variables in this example can be avoided; the checker can be implemented more efficiently as discussed in Exercise 22.3. The transactions in our example can overlap only if there are several start_t before the same end_t, and this is usually not a desired behavior since there is no way to tell which end_t corresponds to a given start_t. A more realistic example is discussed in Exercise 22.4.

22.2.1 Rigid Variable Support in Simulation

In simulation, rigid variables are randomly initialized, and then their values remain unchanged. If there are assumptions imposed on rigid variables, a simulator does not have any obligation to take these assumptions into consideration when assigning initial random values to rigid variables. Therefore, there is no guarantee to fulfill even straightforward assumptions imposed on the rigid variables.

The simulation of rigid variables does not fully reflect their nature. Instead of checking an assertion for all possible values of rigid variables, only one random value is checked. For instance, if in simulation of the checker same2 from Example 22.27, the variable i was initialized with the value 47, only equality of the 47-th bit in two words would be checked.

22.2.1.1 Rigid Variables Versus Local Variables

Rigid variables are typically used for latching: they effectively store a value at the beginning of a transaction, and then they check it at the transaction end, as shown in Example 22.28. This usage is also common for local variables. The advantage of rigid variables is their straightforward implementation in FV, while not all assertions with local variables are supported by FV tools. On the contrary, local variables have full support in simulation, while rigid variables have only partial support. The assertions themselves look very similar in both cases.

It is recommended to use local variables rather than rigid variables, unless there is a restriction on local variables imposed by an FV tool.

Efficiency Tip Rigid variables are expensive in FV, but they are significantly less expensive than the free variables of the same size. In a case where rigid variables may be used interchangeably with local variables, the efficiency of the rigid variables and of the local variables in FV is about the same, provided that the FV tool can handle local variables efficiently.

Exercises

- **22.1.** Implement the checker from Example 22.7 using local variables instead of checker variables.
- **22.2.** What is the difference between the behavior of checkers <code>check1</code> and <code>check2</code> (dotted parts are the same in both checkers)?

```
checker check1(...);
  bit [3:0] v = ...;
  // ...
endchecker : check1

checker check2(...);
  rand bit [3:0] v = ...;
  // ...
endchecker : check2
```

How should the checker check2 be modified to have the same behavior as the checker check1? The variable v should remain free in the check2.

- **22.3.** Implement checker data_consistency from Example 22.28 without using local, free, or rigid variables. This checker will be equivalent to data_consistency only if there are no overlapping transactions, which you can assume do not occur.
- **22.4.** The output data out_data at the end of transaction (end_t asserted) has the same value as the input data in_data at the beginning of the transaction (start_t asserted). With each transaction is associated a tag: the tag at the beginning of the transaction is contained in stag, and the tag at the end of the transaction is contained in etag. For the same transaction, stag and etag have the same values.

22.2 Rigid Variables 511

Implement this specification as a checker

- (a) using rigid variables, and
- (b) as an assertion with local variables.
- **22.5.** Define the formal semantics of a free variable assignment controlled by a clocking event of each of the following forms:

```
(a) @ (posedge clk),
(b) @ (negedge clk),
(c) @ (edge clk iff en),
(d) @ (posedge clk iff en),
(e) @ (negedge clk iff en).
```

Chapter 23 Checker Libraries

A room without books is like a body without a soul.

- G.K. Chesterton

The enhancements to the IEEE SystemVerilog language in the 2009 standard and, in particular, to the SystemVerilog Assertions (SVA) allow us to create much more useful and versatile checker libraries. In this chapter, we first identify the weaknesses of the current checker libraries by examining an example from the OVL library. We then provide a classification of *checkers*, and show how various forms of effective checker libraries can be created using the new constructs. We use the term *checker* and *checker library* in a broad sense to denote a verification unit and library, possibly assertion based. We refer to the SystemVerilog checker construct using checker.

There are many functional properties common to any design that are reusable modulo some expression changes. Therefore, to speed up the deployment of assertions without requiring extensive knowledge of the syntax and semantics of the SystemVerilog assertions language, it is essential to create libraries of checkers. Such checker libraries have been around for some time, such as the Accellera Open Verification Library (OVL) [8], and other checker libraries from EDA vendors. A similar approach was used even before the arrival of assertion languages by hiding procedural or RTL implementation of assertions in modules used as checkers. The initial implementation as well as the Verilog'95 implementation of OVL is in this form.

The enhancements to the SystemVerilog language in the 2009 standard and, in particular to the assertion features allow us to create much more useful and versatile checker libraries. They benefit primarily from the following features: New encapsulation, let declarations, clock and disable inference, deferred assertions, elaboration error tasks, and enhanced property operators. The new checker encapsulation can be used to replace the module. These enhancements in SVA provide a solution to many problems when designing a checker library. Let us recall the main new SVA features that help checker library development and deployment [20]:

- checker encapsulation is versatile for assertion libraries.
 - Argument specification is similar to that of properties.
 - checker can be instantiated in procedural code.

514 23 Checker Libraries

 Inference of clocking event, disable condition on the ports of the checker is possible.

- In an always and initial procedure, evaluation is triggered by control reaching the checker instance.
- Inference functions \$inferred_clock and \$inferred_disable can be used as
 default values on formal ports of checker, sequence and property declarations.
- global clocking and default disable iff declarations are possible.
- Free variables and modeling code in checkers is available with some restrictions:
 - Restricted assignment forms, but easier to analyze and synthesize.
 - Only nonblocking (NBA) assignments in clocked always procedures.
 - Must respect single assignment rule (SAR).
- let construct allows for making abstractions from expressions.
- Checking of configuration parameters at elaboration time.

23.1 Weaknesses of Existing Checker Libraries

To explain the current weaknesses, let us consider a simple checker assert_handshake inspired by its equivalent in the OVL library. The checker is reduced to include only its important excerpts. Details of included files are omitted. The user may wish to consult the OVL library for further details if necessary [8]. First, let us consider the checker interface.

Example 23.1. module-based assert_handshake checker interface

```
// Accellera Standard V2.4 Open Verification
// Library (OVL).
// Accellera Copyright (c) 2005-2009.
// All rights reserved.
'module ovl handshake (
 clock, reset_n, enable, req, ack, fire);
 parameter severity_level = 'OVL_SEVERITY_DEFAULT;
 parameter min_ack_cycle = 0;
 parameter max ack cycle = 0;
 parameter req drop = 0;
 parameter deassert_count = 0;
 parameter max ack length = 0;
 parameter property type = 'OVL PROPERTY DEFAULT;
 parameter msg = 'OVL MSG DEFAULT;
 parameter coverage level= 'OVL COVER DEFAULT;
 parameter clock edge = 'OVL CLOCK EDGE DEFAULT;
 parameter reset polarity = ' OVL RESET POLARITY DEFAULT;
 parameter gating_type = 'OVL_GATING_TYPE_DEFAULT;
 input clock, reset n, enable;
 input req;
 input ack;
```

П

```
output ['OVL_FIRE_WIDTH-1:0] fire;
   //...
'endmodule // ovl handshake
```

The macros 'module and 'endmodule resolve to either module and endmodule or interface and endinterface. This distinction is made so that the checker could also be instantiated in SV interfaces. In either case, the kinds of ports such checkers are allowed to have impose severe constraints on the deployment of the checker in a design:

- Clock port clock cannot be an event such as edge clk iff en.
- Clock, disabling condition reset_n, and the enabling condition cannot be inferred from the instantiation context.
- The checker cannot be instantiated inside a procedure.
- The ports req and ack must be expressions of type logic, they cannot be of type sequence or property.

The restrictions make the usage of the checker tedious. In particular, the last item makes the checker less flexible to use because if either the requests or the acknowledgments are more complex temporal sequences of signal values, additional modeling code must be added on the outside of the checker instance to detect such sequences. This code and the checker instance are usually not to be included in the synthesized code, hence enclosing them between <code>\iffndef - \iffndef = compilation</code> controls becomes necessary.

Before transforming the assert_handshake checker to its checker-based form, let us review the kinds of checkers and the main characteristics a library should possess.

23.2 Kinds of Checkers and Their Characteristics

Checkers can be classified according to four criteria:

- 1. Temporality: combinational (has no clock) vs. concurrent (requires a clock).
- 2. Encapsulation: checker vs. property (or let) based.
- 3. Packaging: in a Verilog library vs. in a SystemVerilog package.
- 4. Configurability: Local per-instance vs. global for all instances.

23.2.1 Temporality

Many interesting checkers can be stated as unclocked Boolean expressions. Often clock is not needed and the user may be interested in instantiating the checker in combinational always procedures or design modules that do not have access to any clock. Such checkers cannot use concurrent assertions because they would require a clocking event. For this purpose, deferred immediate assertions (Sect. 3.3) are the best candidates. When it is required to verify behaviors that are synchronous to

516 23 Checker Libraries

some clock, concurrent assertions need to be used. They can be Boolean expressions evaluating each attempt at a single clock tick or temporal properties evaluating their attempts over several clock ticks.

23.2.2 Encapsulation

property-based encapsulation for temporal checkers, and let-based encapsulation for combinational checkers are the simplest ones. They are easy to use, but they allow no modeling code and can encompass only a single assertion. They are usually part of relatively simple checker libraries. More complex checkers that may consist of several assertions, modeling code, and coverage items need encapsulation in module, interface or more importantly now in checker constructs.

23.2.3 Packaging

Packaging checker libraries as a series of files, one per checker, in a "library" directory that is included automatically during compilation is the most typical usage. This mechanism has been used with the various existing module-based checker libraries. checker, property and let encapsulations allow for a more robust use model by packaging them in the SystemVerilog package enclosure. In this way, the appropriate library can be "imported" only where it is needed. Therefore, even different checkers with the same names can be deployed in different parts of the design. Of course, there is always the third possibility by accessing checker definitions that are brought into the source code using the 'include directive. However, this method provides the least flexibility and we do not consider it further.

23.2.4 Configurability

Global configuration is achieved best by macros, for example, to accomplish the following:

- Enabling all assertions or all functional coverage or both.
- Exclusion of nonsynthesizable code like action block reporting tasks, covergroups or test-bench related items.

Local configuration on a per-instance basis is best achieved by elaboration-time constants and conditional generate blocks. This includes:

- Selection of specific functional coverage items or levels, from a combination of cover property and covergroup constructs.
- Selection of assert, restrict, or assume forms of assertions.
- Configuration and selection of subsets of assertions that should be active in a checker instance.

- Specification of minimal and maximal delay latencies and repetition counts in clock cycles.
- Specific user failure and success messages.
- Specification of severity level of assertion failure.

Elaboration-time constants must provide default values. For example,

- Most typical assertion usage (assertion kind, temporal delays and repetitions).
- Default failure message.
- Minimal useful functional coverage.

Functional coverage should provide several levels of detail whenever practically useful. Some may or may not be suitable for formal and synthesis tools and these should also be under global control. Here is a typical gradation:

- Minimal "did the checked behavior ever happen?"
- More detailed "which specific delay or data values were observed?"
- Corner cases "were min and max delays, and boundary data points ever encountered?"

It is often desirable to perform x/z value checks on signals used in a checker. There may be separate checkers that perform just that task and report a failure when an x or z is detected. However, even "regular" assertions may have to include such checks to disable the assertion from failing or forcing a failure. The choice depends on whether separate checks for these values are used. If yes, then there is no point in reporting a failure in regular assertions, they should just report a vacuous or disabled success. Usually, the detection of x/z is done using the system function sisunknown that returns true if an x or z is detected in the argument expression value.

The ease of using configuration capability is important when different test environments are used. For example, control may be provided over the following features:

- Choice of failure, success and information reporting integrated with the SystemVerilog test-bench verification methodologies (e.g., VMM [15] or OVM [31]), or only reporting using \$display, or using run-time error tasks, such as \$error, etc.
- Macro encapsulation over the checker such that it would automatically provide some of the keywords, thus simplifying instantiation (e.g., Example 23.6). It may also hide differences between checker, property, and module-based checkers.
- Validation of values of arguments used as elaboration-time constants at elaboration time. Using conditional generate statements to test the constant arguments, elaboration tasks can issue error messages at elaboration, rather than at a later time during simulation (possibly many hours after the start of the compilation of the design).

The checker instances should also be easily identifiable by synthesis and formal tools, without the need of <code>'ifndef - 'endif</code> enclosures around the checker instances. It is then left up to the tool to specify whether checkers should or should not be included in the process.

518 23 Checker Libraries

23.3 Examples of Typical Checker Kinds

We now examine examples of different forms of checkers, illustrating the various characteristics and limitations.

23.3.1 Simple Combinational Checker

The combinational checker shown in the following example is defined in a let declaration, which is then used in a deferred immediate assertion. Notice the configuration mechanism using 'ifdef SYNTHESIS for selecting a form that is suitable for synthesis and formal tools.

Example 23.2. let-based checker (in a package)

```
let onehot0 (sig, reset_n = 1'b1) =
    'ifdef SYNTHESIS
    // Selected for synthesis or formal
    !|reset_n || $onehot0(sig);
    'else

// Selected for 4-valued simulation
    |reset_n === 0 ||
        ($onehot0(sig) && !$isunknown(reset_n);
    'endif
```

Such a checker can be instantiated in a module (program or interface), and procedural scope as follows.

П

П

Example 23.3. let-based checker instantiation

Note the following features:

- A macro definition SYNTHESIS selects between two forms of let, one suitable for formal tools and synthesizable checkers, and the other one for 4-valued simulation. In the latter case, the assertion is enabled when reset_n is 1, disabled (success) when reset_n is 0, and it is forced to fail when reset_n is x, or z.
- Both positional (a1) and named (a2) argument association can be used.
- The system function <code>\$onehot0</code> could be used directly in the assertion, however, it would not provide for a disabling condition.

- The reset_n argument has a default actual argument 1'b1, meaning that when the actual is not provided in an instance, the resetting condition is false by default as shown in both a1 and a2.
- The assertion is in the deferred form, hence it filters out 0-width glitches on both reset n and sig actual arguments.
- The assertions can be instantiated in the module scope like a1, or in a procedure like a2.
- The disabling condition cannot be inferred in let instances. That is, \$inferred_disable may not be used as a default actual argument.

23.3.2 A Checker-Based Combinational Checker

Next we examine a more flexible combinational checker. We assume that the convention is that default disable iff provides an active low reset.

Example 23.4. Combinational checker

```
typedef enum {ASSERT, ASSUME, NONE} assert type;
typedef bit [15:0] cover_type
checker onehot.0
  (sig,
  assert type usage kind = ASSERT,
  cover type cover level = 1,
  reset n = $inferred disable,
   string msg = "", synthesis = 'SYNTHESIS);
if (cover level<16'b0 || cover level>16'b11)
// check valid coverage selection
  $error("Coverage level is invalid %d",
   cover level,
    "\nonly 1(level 0), 2(level 2), 3(both)",
   "or 0 (disabled) are allowed");
if (usage kind != ASSERT || usage kind != ASSUME)
  $warning({"No assert or assume selected");
if (synthesis) begin : SYNTH
 let check onehot0 (sig, reset n) =
    let cover onehot0 (sig, reset n) =
    ((|reset n) && $onehot0(sig));
end : SYNTH
else begin : NO SYNTH
 let check onehot0 (sig, reset n) =
    ((|reset n === 0) || $onehot0(sig) && !$isunknown(reset n));
 let cover onehot0 (sig, reset n) =
    ((|reset n === 1) && $onehot0(sig));
end : NO SYNTH
```

520 23 Checker Libraries

```
'ifdef ASSERT ON
if (usage kind == ASSERT) begin : ASSERT
 Assert onehot0:
    assert #0 (check onehot0(sig, reset n))
      else $error(msq);
end : ASSERT
else if (usage kind == ASSUME) begin : ASSUME
 Assume onehot0:
    assume #0 (check onehot0(siq, reset n))
      else $error(msg);
end : ASSUME
`endif
'ifdef COVER ON
if (cover level & 1) begin : COVER L1
 Cover onehot0 1:
    cover #0 (cover onehot0(sig, reset n));
end : COVER L1
if (!synthesis && (cover level & 2))
 begin : COVER L2
 function int position(logic $bits(sig) arg);
    for (int i = 0; i < $bits(sig); i++)</pre>
          if (sig[i] === 1) return i;
   return 0;
 endfunction // position
 covergroup cg_onehot0_2 with
    function sample(int index);
    coverpoint index;
 endgroup
 cg onehot0 2 onehot0 2 index = new();
 Cover onehot0 2:
    cover #0 (cover_onehot0(sig, reset n))
      onehot0_2_index.sample(position(sig));
end : COVER L2
'endif
endchecker : onehot0
```

This combinational checker illustrates many of the features that the checker encapsulation provides over the simpler let-based form:

П

- Coverage can be enabled globally for all checker instances by defining the symbol COVER_ON. Similarly, verification statements (assert or assume) can be globally enabled by defining ASSERT ON.
- Synthesizable form is selected by a conditional generate block controlled by the argument synthesis that has as default actual value the macro symbol SYNTHESIS. This allows overriding the global selection if so required.
- The reset condition may be inferred from a default disable iff declaration.
- Deferred assert (usage_kind == ASSERT) or assume (usage_kind == ASSUME) statement or none can be selected using the argument usage_kind.

П

- When an invalid value is provided for cover_level, no coverage is enabled in this instance and an error message is issued.
- When an invalid value (or NONE) is provided for usage_kind, no verification statement (assert or assume) is enabled in this instance and a warning message is issued.
- Two levels of functional coverage are provided, they can be individually enabled or disabled:
 - Level 1 when cover_level == 1 is selected, it collects information on how
 many times a one hot or 0 condition was encountered while not disabled by
 reset
 - Level 2 when cover_level == 2 is selected, the covergroup classifies the bit positions that are set to 1 when the one hot condition holds. A deferred cover statement is used to trigger sampling of the bit position index by calling the sample method of the covergroup in the pass action statement of the deferred cover statement.
 - Both levels can be selected by setting cover level == 3.

The **checker** can be instantiated in a simpler way than the one using a **let** declaration because the disable condition can be inferred:

Example 23.5. Combinational checker instantiation

There is, however, a difference between using this checker and the simple checker in Sect. 23.3.1 in that according to the checker specification in the LRM, all the variable inputs to the checker are sampled (the values are taken from the Preponed scheduling region), while the simple checker uses only the current values. This may make a difference when the checker is used in procedural code like the instance a2. The problem can be avoided by const casting of the actual arguments r1. The instance in the always procedure thus becomes:

```
always_comb begin
  r2 = r1;
  onehot0 a2(const'(r1)); // check output
end
```

¹ Note that reset in this checker will still be sampled.

522 23 Checker Libraries

The first instance, a1, may use sampled values because it does not depend on any current time condition in the module. It would report any violation one simulation time-step later than if it used the current value, but that is all. If we remove sampling even in instance a1, then we can encapsulate the checker instantiation statement in a macro and hide the const cast as follows:

Example 23.6. Macro encapsulation of checker definition

Unfortunately, due to the automatic sampling of checker arguments, we cannot use \$inferred_disable as a default value for reset_n. There is no way to place the const cast on the function. Therefore, using the macro encapsulation we have lost the ability to infer the reset condition.

As with the previous simple combinational checker, this more complex checker can still be instantiated both inside (instance a1) and outside (instance a2) a procedure. Both checker instances use default values for configuration constants and enable verification statement assert #0 because ASSERT_ON is defined and usage_kind default value of ASSERT is used. Coverage is globally disabled because COVER ON is not defined.

23.3.3 A Simple Property-Based Temporal Checker

We now turn our attention to checkers that verify behavior over time – temporal checkers.

Similarly as with the simple combinational checker and let declarations, we can define a simple temporal, clocked, checker using property declarations. As before, we assume that default disable iff defines an active low reset.

Example 23.7. property-based temporal checker

```
property time_interval_p
  (sequence trig, property cond,
   start_tick=1, end_tick=1,
  event clk = $inferred_clock,
  untyped rst_n = $inferred_disable);
    @clk disable iff (!bit'(|rst_n))
    trig |->
        always [start_tick:end_tick] cond;
endproperty : time_interval_p
```

Note that in the consequent of |-> we used the always operator instead of using the consecutive repetition cond[*start tick:end tick]. The reason is that we

П

obtain maximum generality as to the actual argument for the formal cond. It can not only be a Boolean or a sequence, but also any property expression.

The property verifies that when trig occurs cond holds true in the interval start_tick to end_tick clock ticks, unless it is disabled by rst_n being 1'b0. The property has the following characteristics:

- The actual argument for trig is restricted to the type sequence because it is used in the antecedent of |->. The actual argument for cond can be any property expression (Boolean, sequence or property). The actual argument for clk must be a clocking event, while rst_n is left untyped for the user to be able to pass any valid expression.
- trig and cond do not have default actual arguments, hence the user must supply valid arguments there.
- Both clk and rst can be inferred from the context because the inference functions are used as default actual arguments.
- The arguments start_tick and end_tick have the typical default value of 1. If used as in the following instantiation example, the property will check that cond holds true at the next clock tick after trig holds true.

A simple instantiation of property time_interval_p is illustrated in the next example.

Example 23.8. property-based checker instantiation

Except for the arguments that are used in the actual verification, all other ones use default values. The clock and the disabling condition are inferred from the always procedure and from the default disable iff declaration, respectively.

23.3.4 A Checker-Based Temporal Checker

The final example illustrates the full power of a checker-based temporal checker definition. We show a modified form of checker assert_handshake discussed at the beginning of this chapter (Sect. 23.1), but for reasons of brevity we include only those portions of the code that illustrate the differences.

524 23 Checker Libraries

The interface of the new checker is now as follows:

Example 23.9. assert handshake checker definition

```
import std ovl defines::*;
checker assert handshake (
 sequence req, sequence ack,
 //elaboration-time constants:
 int severity level = 'OVL SEVERITY DEFAULT,
 int min ack cycle = 0,
 int max ack cycle = 0,
 int req drop
              = 0, // these three arguments
 int deassert count = 0, // may not be needed
 int max_ack_length = 0, // since req is a sequence
 int property_type = 'OVL_PROPERTY_DEFAULT,
 string msg = 'OVL MSG DEFAULT,
 int coverage level = 'OVL COVER DEFAULT,
 int synthesis = 'SYNTHESIS'
);
generate // elaboration-time constant checks at compile time
  if (min ack cycle < 0)</pre>
    $error("min ack cycle is negative");
  if (max ack cycle < min ack cycle) $error(</pre>
    "max ack cycle is less than min ack cycle");
  if (req_drop < 0 || req_drop > 1) $warning(
    "req drop \%0d is not 0 or 1",
   req drop, "positive assumed 1,"
    "anything less than 1 assumed 0");
  // ... checks for other arguments ...
endgenerate
default clocking checker_clk @clk; endclocking
default disable iff (reset n);
//... Body of the checker ...
endchecker : assert handshake
```

The parameters from the original checker became regular arguments of the checker-based checker. It simplifies instantiation, although the user should be aware that these arguments must be elaboration-time constants. The argument values of constants are verified at elaboration time using a conditional generate and elaboration time error tasks. If the values are illegal, then an error message is issued, or if a reasonable alternative exists, then that value is used and a warning is issued.

П

The following parameters from the original checker are missing:

```
parameter clock_edge = 'OVL_CLOCK_EDGE_DEFAULT;
parameter reset_polarity = 'OVL_RESET_POLARITY_DEFAULT;
parameter gating_type = 'OVL_GATING_TYPE_DEFAULT;
```

This is because

- clock edge is not needed as the argument clk can be an event expression.
- reset_polarity is not needed because we can pass any expression to the checker and it can infer the appropriate default expression from the contextual default disable iff declaration.
- gating_type is omitted for the same reason as clock_edge - the actual clocking event provided for clk can contain iff enabling condition.

The formal arguments clk and reset_n were placed after the arguments that do not have defaults. This simplifies instantiation of the checker when all arguments use default values. The type of reset_n is left unspecified (the keyword untyped) to provide more flexibility as to the kind of the actual reset expression. As in the case of the checker based combinational checker, all variable arguments are sampled. This may not be desirable for reset_n, hence the actual argument for reset_n should have the const cast. Note that if the default is inferred it will be sampled.

The default value constants for the arguments are no more 'defines, but instead they are constants picked up from package std_ovl_defines as enum type values.

The type for req and ack is specified as **sequence** to allow Booleans and sequences, but prohibit supplying a property expression as the actual argument. This makes the checker more general, eliminating the need for modeling code to reduce a complex temporal behavior to a Boolean expression.

The body of the checker has to be modified to comply with restrictions on modeling code in checker constructs, and to use all the new features that help implementing and using checkers. The body of the checker-based checker is shown next. Refer to the OVL library to compare with the original checker body [8].

Only those portions as in the example of the original checker are shown that illustrate the differences with the original checker. The following piece of code shows the transformation needed in the modeling code of the checker.

Example 23.10. Body of assert handshake checker

```
'ifdef ASSERT_ON
logic first_req = 1'b0;

sequence s_req;
   req;
endsequence

function logic setFirstReq();
   if (!reset_n) return 1'b0;
   if((first_req ^ first_req) == 1'b0)
      return s_req.triggered;
   return 1'b0;
endfunction : setFirstReq

always @(clk) first req <= setFirstReq();</pre>
```

526 23 Checker Libraries

Since always procedures in checker cannot have any conditional statements, the function setFirstReq is defined to encapsulate the procedural code. The function is then called on the right-hand side of a nonblocking assignment. The variable first_req is used in a property in the following code fragment:

```
property ASSERT HANDSHAKE ACK MIN CYCLE P;
  s req |-> not s eventually [0:min ack cycle] ack;
endproperty
property
  ASSERT HANDSHAKE ACK WITHOUT REQ FIRST REQ P;
  (##1 ack) implies
    (first req or s req.triggered);
endproperty
// other properties ...
// this remains as before
case (property type)
  OVL ASSERT 2STATE, // defined as enum types
  OVL ASSERT: begin : ovl assert
    if (min_ack_cycle > 0)
    begin : a assert handshake ack min cycle
      A ASSERT HANDSHAKE ACK MIN CYCLE P:
        assert property (ASSERT HANDSHAKE ACK MIN CYCLE P)
      else ovl_error_t("...as before...");
    end
// other assert and assume statements
endcase
'endif //ASSERT ON
'ifdef COVER ON
generate
  if (coverage level != OVL COVER NONE) begin : ovl cover
    if (OVL_COVER_BASIC_ON)
    begin : ovl cover basic
      cover req asserted:
      cover property
        (reset_n throughout s_req))
          ovl cover t("req asserted covered");
    //... other cover statement ...
  end
endgenerate
'endif // COVER ON
```

Notice the following differences:

 Procedural conditional code is placed in a function to satisfy restrictions on assignments to checker variables. The always procedure contains a single assignment only.

- Case default values on parameters are removed since constant argument values are checked at compile time.
- Case item labels are predefined enum types rather than 'define symbols.
- The property expressions use property operators to allow sequences as the arguments and to make the assertions more efficient for formal tools. For example, in property ASSERT_HANDSHAKE_ACK_MIN_CYCLE_P, the sequence repetition is replaced by not s_eventually ... to accept a sequence expression for ack.
- A new sequence s_req is defined that instantiates req. This allows us to use the sequence method s req.triggered in the function.
- Since both req and ack can be sequences, \$rose had to be removed from both of these operands of the property. Thus, if the user wishes to use \$rose on a Boolean, the appropriate expression has to be passed as the actual argument.²

There is currently a restriction imposed on this form of checkers. There are no output and inout arguments allowed in checker encapsulation. That is, the output port fire of the original OVL checker is missing here. Therefore, the only way to chain several checker based checkers is to access some internal variable of one checker instance in some other checker instance using a cross checker reference. This makes it less flexible.

Note that by extending the type of the arguments to **sequence**, it is now impossible to include checks for the presence of x/z values in the variables involved in the actual arguments. If such checking is required, the best approach is to create specific checkers just for the purpose of verifying x/z on variables. An open question remains how to disable existing assertions within the checker in such cases. It requires either an enhancement to the SystemVerilog language to provide a function that detects x/z in sequences and properties, or an enhancement in the simulator to evaluate assertion in a pessimistic fashion.

The following is an example of instantiation of the new checker. For simplicity, all elaboration-time arguments take on default values.

² If a system function existed that allowed to distinguish Boolean expressions from temporal sequences and properties, a conditional generate could be used to construct different forms of properties depending on the actual argument.

528 23 Checker Libraries

```
assert_handshake chk_handshake_inst(
    .req($rose(request)),
    .ack(acknowledgment ##1 endtrans));
if (!rst_n) begin
    //... some design procedure ...
end
end
//... some design code ...
```

endmodule

The main points are:

• The checker instantiation syntax is similar to that of a module, except that there is no parameter section.

П

- It can be instantiated in an always procedure.
- The reset n argument is inferred from default disable declaration.
- The clocking event is inferred from the always procedure, hence even though
 default clocking is defined, the clock from the always procedure takes precedence.
- The actual argument for the formal argument req is \$rose(request); its clock is obtained from the default clocking defined in the module.
- The actual argument for ack is a sequence expression.

In the next and final section, we summarize the transformations to consider when converting the old-style module-based checkers into the new format based on checker encapsulation. This may be of interest when it is not desired to support two different formats of a checker library.

23.4 Converting Module-Based Checkers to the New Format

The set of transformations include the following items:

- Replace 'define for various constants by typedef declarations using an enum type whenever possible.
- Change modeling code to respect Single Assignment Rule (SAR) by introducing functions for evaluating the right-hand side expressions of assignments.
- Replace all continuous assignments by references to let statements.
- Create compile-time checks on elaboration-time constant values.
- Use initial procedures only for indicating that the enclosed assertions should have only one evaluation attempt. Initialize variables in their declaration.
- Change interface definition to include original parameters as regular arguments.
- Provide inference functions as default arguments to clock and reset.
- Provide default actual arguments wherever appropriate.
- Generalize the type of arguments to sequence or property wherever the checker properties can admit such operands.

- Checker instance identification task calls in initial procedures should be replaced by initial and an immediate assert statement on true, with a pass action statement displaying the required identification message.
- Consider using covergroup statements to provide more detailed coverage, selectable by an argument.
- Add default clocking and disable iff declarations and simplify assertions.
- Place the new checkers in a package for easy and controlled access from a design unit.

Exercises

- **23.1.** Suppose that your design contains some legacy code with module-based checker instances while new parts of the design should use a checker-based version of the same checkers. The latter have the same names as the old module based ones, but are enclosed in a package. How can you use both of these checkers but in different parts of the design without name clashes?
- **23.2.** The OVL checkers can be obtained from Accellera at [8]. Modify the OVL SVA checker assert_proposition into the **checker** form. What kind of assertion should it use, concurrent, immediate, or deferred?
- **23.3.** When transforming the OVL assert_handshake checker into the checker form, we omitted any discussion on x/z checking on the arguments req and ack. This is because the actual arguments can be temporal sequences in which case we cannot use \$isunknown on the argument to check for the presence of x/z. What would you provide as a solution to the user. Are any extensions to the SystemVerilog language necessary?
- **23.4.** List some extensions to the SystemVerilog language that would be useful to have for creating effective checker libraries.

Chapter 24 Future Enhancements

Prediction is very difficult, especially of the future.

- Niels Bohr

When the IEEE 1800–2009 SystemVerilog Standard was being completed, several issues and proposals in the assertions area remained unresolved due to time constraints and thus were not included. It is likely that a new version of the standard will be developed within a couple of years. Some of the unresolved proposals will make their way into that new version. Furthermore, as users and EDA community deploy the 2009 enhancements, requirements for new features will arise and will be addressed. To conclude our expose of the 2009 SystemVerilog Assertions, in this chapter we wish to mention at least some of the enhancements that we think should appear in any future standard without explicating details of syntax and semantics because it will likely emerge from the Standards committee in a different form. Most of the enhancements address the checker construct, and thus pertain to the creation of more effective checker libraries. As Niels Bohr stated, "prediction is difficult", hence the contents of this chapter should be taken with a grain of salt.

24.1 Language Enhancements

Variable Number of Arguments

The usage and development of checker libraries could be made easier if let, property, sequence, and checker declarations allowed variable number of arguments. This would greatly reduce the number of checker variants and configuration arguments. Variable number of arguments should also be made available for macro definitions to allow encapsulation of the generalized checkers in macros as we illustrated earlier in Chap. 23.

The variable part of arguments would essentially become a formal argument that is replaced in its instantiation by a list of actual arguments. Therefore, the language must also provide new elaboration-time system functions that manipulate such lists

532 24 Future Enhancements

of arguments. For example, functions similar to *map* and *reduce* functions in LISP could be used for generating expressions (sequence, property, let) that extend the functionality over the actual list of arguments.

Output and Inout Checker Arguments

Currently, only formal arguments of direction input are allowed in checker definitions. Checkers should also be allowed to drive output arguments. These can be used to chain several checkers to form more complex ones to set error registers when used in emulation, and to drive design signals when a checker acts as a constraint during random simulation and formal verification.

Tighter Coupling Between Sequences and Covergroups

As we showed in Chap. 18, cover property statements can be used to collect information in local variables while evaluating a property, and then save the contents of the local variables in coverage database by invoking the generalized sample function on a covergroup. This rather loose coupling could be made even more useful by allowing to declare SVA sequences with first-match semantics inside covergroups. The Boolean expressions would be defined in terms of the coverpoints. As the sequence is evaluated, the data of the coverpoints would be automatically collected, classified according to the bins and cross specifications, and then saved in the coverage database.

Mixed Level Model Assertions

There is already work in progress to extend SVA to assimilate mixed Analog–Digital models, to extend assertion semantics over analog features. The enhancements require melding, at least to some degree, Verilog AMS and SystemVerilog syntax and semantics to allow SVA to operate on real variables and be sensitive to analog events. Also, analog behavior is defined in real time; therefore, the assertions must also be extended over the real-time domain.

24.2 Usability Enhancements

The following items do affect the SVA language too, but they are meant to improve the usability of the exiting features rather than provide new ones.

Checker Argument Sampling

Currently, all checker arguments are automatically sampled in the Preponed region. This works correctly for static concurrent assertions and assignments to free variables, but when used with deferred assertions or with procedural concurrent assertions, a mechanism must be provided to disable sampling on some or all checker arguments in the formal argument definition.¹

Assignments in Checkers

Currently, only nonblocking synchronous assignments to free variables are allowed in checkers. In addition, this enhancement would permit continuous assignments, conditional assignments, and loops in synchronous always blocks. The let feature can continue to be used whenever it is efficient. The extension would bring the construction of synchronous always blocks closer to the form used in RTL code.

Simulation Semantics for Checkers as Constraints

The current LRM indicates that assumptions in checkers can be used as constraints on free variables, however, when output arguments are added that could be used to drive design signals, the exact simulation semantics is undefined but defining it is important for ensuring interoperability between simulators and formal tools.

Checkers in Functions and Tasks

Checkers containing deferred assertions are useful for defining functional checks in functions and tasks. However, currently checkers may not be instantiated within these constructs. This enhancement would extend the usefulness of checkers in this direction, albeit under some restrictions. For example, no concurrent assertions in the body of the checker after elaboration.

SVA Type Identification for Arguments

Currently, arguments to checkers, sequences, and properties can have the type sequence or property, but there is no means to detect the type of the argument within the body of the constructs. Similarly, there is no simple way to detect whether an argument is of some integral type. Extending the type function to provide such

¹ A mechanism for blocking sampling of actual arguments when instantiating a **checker** already exists using the **const** qualifier.

534 24 Future Enhancements

information would allow for efficient type checking, and for constructing more efficient properties using conditional generate blocks to select the most appropriate form depending on the argument type.

Allow \$inferred_disable as Default Argument in Let

Even though it is possible to create simple yet effective combinational checkers using let declarations as shown in Chap. 23, it is not currently possible to infer disabling condition from default disable iff declaration.

References

- 1. IEEE Standard VHDL Language Reference Manual (2000) IEEE Std 1076-2000, pp 1-290
- 2. IEEE Standard Verilog Hardware Description Language (2001) IEEE Std 1364-2001, pp 1-856
- 3. IEEE Standard for SystemVerilog Unified Hardware Design, Specification, and Verification Language (2005) IEEE Std 1800-2005, pp 1–648
- IEEE Standard for Verilog Hardware Description Language (2006) IEEE Std 1364-2005 (Revision of IEEE Std 1364-2001), pp 1–560
- 5. IEEE Standard SystemC Language Reference Manual (2006) IEEE Std 1666-2005, pp 1-423
- 6. IEC Standard for Property Specification Language (PSL) (Adoption of IEEE Std 1850-2005) (2007) IEC 62531:2007 (E), pp 1–156
- 7. IEEE Standard for SystemVerilog Unified Hardware Design, Specification, and Verification Language (2009) IEEE STD 1800-2009, pp C1–1285
- 8. Accellera (2009) Accellera Standard Open Verification Library (OVL) V2.4
- Armoni R, Egorov S, Fraer R, Korchemny D, Vardi M (2005) Efficient LTL compilation for SAT-based model checking. In: ICCAD: Proceedings of the 2005 IEEE/ACM International Conference on Computer-aided design, pp 877–884
- 10. Armoni R, Fix L, Flaisher A, Gerth R, Ginsburg B, Kanza T, Landver A, Mador-Haim S, Singerman E, Tiemeyer A, Vardi MY, Zbar Y (2002) The ForSpec temporal logic: a new temporal property-specification language. In: TACAS'02: Proceedings of the 8th International Conference on Tools and Algorithms for the Construction and Analysis of Systems. Springer, London, UK, pp 296–211
- Armoni R, Fix L, Flaisher A, Grumberg O, Piterman N, Tiemeyer A, Vardi MY (2003) Enhanced vacuity detection in linear temporal logic. In: CAV. pp 368–380
- 12. Ashar P, Dey S, Malik S (1995) Exploiting multicycle false paths in the performance optimization of sequential logic circuits. In: IEEE transactions on computer-aided design of integrated circuits and systems 14(9):1067–1075
- 13. Aziz A, Kukula J, Shiple T (1998) Hybrid verification using saturated simulation. In: Proceedings of the Design Automation Conference, pp 615–618
- 14. Baier C, Katoen J-P (2008) Principles of model checking. MIT Press
- 15. Bergeron J, Cerny E, Hunter A, Nightingale A (2006) Verification methodology manual for SystemVerilog. Springer, New York
- 16. Bernardo M, Cimatti A (2006) Formal methods for hardware verification: 6th International School on Formal Methods for the Design of Computer, Communication, and Software Systems, SFM ... Lectures (Lecture Notes in Computer Science). Springer, New York, Secaucus, NJ. USA
- Bustan D (2004) Mantis Item 290: Recursive properties can define non-regular languages, Erratum submitted to the IEEE 1800 SV-AC as part of the development and revision of IEEE 1800-2005
- Bustan D, Flaisher A, Grumberg O, Kupferman O, Vardi MY (2005) Regular vacuity. In: Proc. 13th Advanced Research Working Conference on Correct Hardware Design and Verification Methods, Lecture Notes in Computer Science, 3725:191–206

 Bustan D, Havlicek J (2006) Some complexity results for systemverilog assertions. In: CAV, Lecture Notes in Computer Science, 4144:205–218

- 20. Cerny E, Korchemny D, Piper L, Selingman E, Dudani S (2009) Verification case studies: evolution from sva 2005 to sva 2009. In: Design Verification Conference (DVCon)
- 21. Chadha R (2009) Static timing analysis for nanometer designs. Springer
- Claesen L, Schupp JP, Das P, Johannes P, Perremans S, De Man H (1989) Efficient false path elimination algorithms for timing verification by event graph preprocessing. Integr VLSI J 8(2):173–187
- 23. Clarke EM, Grumberg O, Peled DA (2008) Model checking, 6 edn. MIT Press
- 24. Cox B (1986) Object oriented programming. Addison-Wesley
- 25. Das A, Basu P, Banerjee A, Dasgupta P, Chakrabarti PP, Rama Mohan C, Fix L, Armoni R (2004) Formal verification coverage: computing the coverage gap between temporal specifications. In: ICCAD'04: Proceedings of the 2004 IEEE/ACM International conference on Computer-aided design. IEEE Computer Society, Washington, DC, USA. pp 198–203
- 26. Eisner C, Fisman D, Havlicek J (2005) A topological characterization of weakness. In: Annual ACM Symposium on Principles of Distributed Computing, pp 1–8
- Emerson EA (1990) Temporal and modal logic. In: van Leeuwen J (ed) Handbook of theoretical computer science. Elsevier, pp 996–1072
- 28. Emerson EA, Halpern JY (1982) Decision procedures and expressiveness in the temporal logic of branching time. In: STOC'82: Proceedings of the fourteenth annual ACM symposium on Theory of computing. ACM, New York, pp 169–180
- Fisman, D, Kupferman O, Seinvald S, Vardi M (2009) A framework for inherent vacuity, Lecture Notes in Computer Science, 5394:7–22
- 30. Foster H (2008) Assertion-based verification: Industry myths to realities (invited tutorial). In: CAV. pp 5–10
- 31. Glasser M (2009) Open verification methodology cookbook. Springer
- 32. Gosling J, Joy B, Steele G, Bracha G (2005) The Java language specification, 3rd edn. Addison-Wesley
- 33. Gulati K, Khatri SP (2010) Hardware acceleration of EDA algorithms. Custom ICs, FPGAs and GPUs. Springer
- 34. Havlicek J, Levi N, Miller H, Shultz K (2002) Extended CBV statement semantics, part of a proposal presented to the Accellera formal verification technical committee
- 35. Havlicek J, Shultz K, Armoni R, Dudani S, Cerny E (2004) Accellera Technical Report 2004.01: Notes on the Semantics of Local Variables in Accellera SystemVerilog 3.1 Concurrent Assertions
- 36. Hazelhurst S, Weissberg O, Kamhi G, Fix L (2002) A hybrid verification approach: getting deep into the design. In: DAC '02: Proceedings of the 39th conference on Design Automation. ACM, New York, pp 111–116
- Hennessy JL, Patterson DA (2006) Computer Architecture: A Quantitative Approach, 4th edn. Morgan Kaufmann Publishers, San Francisco, CA, USA
- 38. Ho CR, Theobald M, Batson B, Grossman J, Wang SC, Gagliardo J, Deneroff MM, Dror RO, Shaw DE (2009) Four pillars of assertion-based verification. In: Proceedings of the Design and Verification Conference and Exhibition, San Jose, California
- Kuehlmann A, van Eijk CAJ (2002) Combinational and sequential equivalence checking. Logic synthesis and verification, Kluwer International Series in Engineering and Computer Science Series, pp 343–372
- Kupferman O, Vardi MY (2001) Model checking of safety properties. Form Methods Syst Des 19(3):291–314
- Kupferman O, Vardi MY (2003) Vacuity detection in temporal model checking. Int J Softw Tools Technol Transfer 4(2):224–233
- 42. Lamport L (2002) Specifying systems, the TLA+ language and tools for hardware and software engineers. Addison-Wesley
- 43. Malik S (2005) A case for runtime validation of hardware. In: Haifa verification conference. pp 30–42

References 537

44. Microsoft Research (2001) http://research.microsoft.com/en-us/projects/asml. AsmL: abstract state machine language

- Mukhopadhyay R, Panda SK, Dasgupta P, Gough J (2009) Instrumenting ams assertion verification on commercial platforms. ACM Trans Des Autom Electron Syst 14(2):1–47
- 46. The Open Group (2009) http://adl.opengroup.org/about/index.html. Assertion definition language
- 47. Parker RH (2004) Caution: clock crossing. a prescription for uncontaminated data across clock domains. Chip design magazine
- 48. Pellauer M, Lis M, Baltus D, Nikhil R (2005) Synthesis of synchronous assertions with guarded atomic actions. In: 2nd ACM/IEEE International Conference on Formal Methods and Models for Co-Design. IEEE Computer Society, Washington, DC. pp 15–24
- 49. Reese RB, Thornton MA (2006) Introduction to logic synthesis using verilog HDL (synthesis lectures on digital circuits and systems). Morgan and Claypool
- 50. Rotithor H (2000) Postsilicon validation methodology for microprocessors. IEEE Des Test 17(4):77–88
- 51. Schubert T (2003) High-level formal verification of next-generation microprocessors. In: Proceedings of the Design Automation conference. IEEE/ACM, pp 1–6
- 52. Spear C (2008) SystemVerilog for verification, a guide to learning the testbench language features. Springer, Norwell, MA, USA
- 53. Stroustrup B (1991) The C++ programming language. Addison-Wesley
- 54. Sun Developer Network (2010) http://java.sun.com/. Java programming language, Java standard edition 6
- 55. Sutherland S, Davidman S, Flake P (2006) SystemVerilog for Design. Springer
- 56. Tabakov D, Vardi MY, Kamhi G, Singerman E (2008) A temporal language for systemc. In: FMCAD '08: Proceedings of the 2008 International Conference on Formal Methods in Computer-Aided Design, IEEE, Piscataway, NJ, USA, pp 1–9
- 57. Trakhtenbrot BA, Barzdin YM (1973) Finite automata: behaviour and synthesis. North-Holland
- 58. Wolfsthal Y (2004) Abstract for the isola special session on "industrial use of tools for formal analysis". In: ISoLA (Preliminary proceedings). pp 190–190
- 59. Yeung P (2004) Four pillars of assertion-based verification. In: Euro DesignCon
- 60. Yuan J, Albin K, Aziz A, Pixley C (2003) Constraint synthesis for environment modeling in functional verification. In: DAC. ACM, pp 296–299

1	
abort, 295, 296, 299	immediate, 18, 72–74, 77, 88, 172, 266,
accept_on, 183, 279, 283, 295, 299,	459, 515, 518
301, 356, 360, 435	static, 472
asynchronous, 286, 295, 299, 300, 303	assertion statement, 19, 71, 79, 87, 94, 141,
nested, 301, 303	154, 312, 313, 363, 387, 393, 424
reject_on, 183, 279, 283, 295, 299,	assertion-based verification, 13
301, 360, 395	associative array, 332, 334
sync_accept_on, 183, 283, 296, 299,	assume-guarantee, 239, 506
302, 356, 360	assumption, 17, 19, 91–94, 253
synchronous, 286, 295, 299, 302-304	assume #0,92
sync_reject_on, 183, 283, 296, 299,	assume property, 92
302, 360, 383	$\mathtt{assume}, 92$
abort condition, 279, 283, 286, 299-305, 356,	concurrent, 92
434	deferred, 92
ABV, 13, 18, 91	immediate, 92
action block, 72–78, 84, 85, 87, 88, 97, 145,	automatic variable, 279, 313
146, 154, 160, 278, 296, 302, 314,	
316, 354, 394, 410, 457, 459, 469,	
516	bad prefix, 255
antecedent, 122	bad state, 256
approximation, 231	binary relation, 244
argument	bit-stream casting, 34
const ref, 278	BMC, 231
ref, 278	Boolean
array	connective, 109
packed, 33	occurrence, 325
unpacked, 34	
assert, 252	Cartesian product, 244
assertion, 5, 18, 19, 72	\$changed, 153
assert #0,72	\$changed, 155 \$changed qclk, 155
assert property,72	\$changed_gcik, 155 \$changing qclk, 156
assert, 72	characteristic function, 249
analog, 17	checker, 26, 447, 452
concurrent, 18, 307, 309	assume set, 504
procedural concurrent assertion, 307	free variable, 489
deferred, 14, 18, 27, 72, 75, 77, 78, 146,	fully assigned, 499
162, 163, 168, 172, 266, 267, 307,	instantiation, 465
	The state of the s
332, 459, 461, 470, 513, 533	procedural, 465
report queue, 76	static, 465

procedure, 473	concurrent, 96
rigid variable, 507	deferred cover, 394
single assignment rule, 479	functional, 3, 27, 95, 393, 485, 516, 517,
variable, 477	521
checker library, 513	immediate, 95
checker-based combinational, 519	immediate cover, 394
checker-based temporal, 523	sample function, 400
let-based combinational, 518	coverage database, 97
property-based temporal, 522	coverage goal, 16
classification, 515	coverage point, 16, 97
configurability, 516	coverage statement, 19
encapsulation, 516	coverage-based verification, 16
packaging, 516	covergroup, 52, 355, 399
temporality, 515	sample method, 355
macro encapsulation, 522	current state variable, 250
module-based conversion, 528	cycle, 270
clock, 81, 269	
gated, 82, 149	
global, 83, see primary clock	
\$global_clock, 83, 157, 247, 248	data type, 30
primary, see global clock, 247	chandle, 87
system, see global clock, see primary clock	enum, 31
clock convergence	integral, 30
continuity, 290	string, 32
clock domain crossing, 17, 153	struct, 31
clock flow, 276, 282	typedef, 32
clock inferencing, 310	union, 31
clock rewrite rules, 431	debugging
clock scoping, 281	new assertion, 409
clock tick, 269	reused assertion, 409
clocking, 40	delay range, 135
default, 12, 41, 269, 272, 280	initial, 135
global, 83	design methodology, 4, 9, 229
LTL operators, 287	disable clause, 296
clocking block	disable condition, 296
declarations within, 292	disable iff, 14, 85, 295, 296
clocking event, 269, 271	default, 298
leading, 269, 270	nesting, 298
\$clog2,481,494,502	disable statement, 307, 321, 322
compilation unit, 48	disjunction property, see property operators,
conjunction property, see property operators,	or
and	dist, 93
consequent, 122	don't care, 230
const cast, 279	DUT, 71
counterexample, 230	201,71
spurious, 232	
\$countones, 142	
cover, 94–97, 253	empty match, 330, 350, 354
coverage, 230	empty model, 234, 253
cover #0,96	emulation, see hardware acceleration
deferred, 96	environment, 71
cover property, 96, 396	equivalence verification, 16
cover sequence, 96, 395	evaluation
cover, 95	disabled, 85

evaluation attempt, 80, 323 assertion control tasks, 159	hardware acceleration, 22 high-level model, 9
control of, 158	hybrid verification, 240
control of action block, 160	nyena vermeunen, 2 ve
efficiency, 414	
end time, 80	\$inferred clock, 273
start time, 80	\$inferred_clock, 454, 456
event control, 39, 270, 310	\$inferred disable, 454, 456
edge, 39, 310	interface, 44, 45
iff , 310, 311	modport, 47
negedge, 310	virtual, 47
posedge, 310	\$isunbounded,460
sequence, 222	\$isunknown, 143
iff, 39	
expression operators, 37	
equivalence, 39	Kripke structure, see formal verification model
implication, 39	<u>r</u>
inside, 37	
	language, 245
foil action 72	finitary, 245
fail action, 72 fairness, 109, 158	infinitary, 245
\$falling gclk, 156	leading clock, 276, 280
false negative, 23, 231	semantic, 282, 284
false path elimination, 17	lemma, 237
false positive, 231	let, 23, 163–173
\$fell, 151	arguments, 165
\$fell gclk, 155	scoping rules, 165
finite automaton, 245	letter, 244
acceptance, 245	liveness, 255
first-order logic, 490	general, 255
flow diagram, 382	local variable, 277, 323, 343
followed by, see property operators, suffix	argument, 335, 343, 347, 375, 377
conjunction	default actual, 350
for-loop, 314	direction, 348, 367
formal semantics, 421, 436	assignment, 324, 329, 330, 350
clocks, 430	within repetition, 353
resets, 434	become unassigned, 361
formal specification language, 7	body, 343, 344 context, 437
formal verification, 5, 22, 246, 332 formal verification flow, 236	declaration, 324, 336, 344, 347
formal verification method	declaration, 324, 330, 344, 347 declaration assignment, 336, 343, 344, 351
complete, 231	delay, 345
incomplete, 231	flow, 357, 436
free variable, 279	initialization assignment, 344, 351
function	input, 364
bit vector, 141	multiplicity of matching, 363
future enhancements, 531	output, 367
language, 531	receiver, 367
usability, 532	reference, 355
\$future_gclk, 155, 156	threads, 343, 351, 356
	unassigned, 345
	logical operator
glitch, 297	unclocked, 290

LRM, 30, 31, 35, 40, 44, 60, 127, 141, 163,	negation, 429
167–171, 198–200, 269, 282, 286,	next occurrence, 206
287, 297, 298, 304, 319, 344, 347,	recursive, 373
356, 359, 368, 380, 385, 399, 434,	restrictions, 385
436, 439, 442, 458, 503, 504, 521,	safety, 255
533	sequential, 117
	strong, 262
	weak, 262
matched, 221, 291, 304, 364, 366, 369	property coverage, 96
minterm, 249	
model, 246	property operators, 184 always, 105, 192
model checking, 255	
model language, 249	implicit, 106
model relation, 252	and, 186, 423
module, 449	Boolean connectives, 185
multicycle path, 17	bounded always, 196
multiply clocked, 269, 273	bounded eventually, 196
	bounded s_always , 197
	bounded s_eventually, 196
negation property, see property operators, not	case, 188
next state function, 498	if , 188
next state variable, 250	if-else, 188
next state variable, 250	iff , 187, 424
nexceime, 423	implies, 186, 424
	nexttime, 104, 194
d	not, 185, 422
\$onehot, 24, 142	
\$onehot0, 91, 141	or, 186, 424, 426
overapproximation, 231, 232	sequence property, 183
	s_eventually, 106, 192, 424
	s_nexttime, 194
package, 50	strong sequence, 184
pass action, 72	suffix conjunction, 190
\$past, 14, 146, 324	non-overlapping, 190
past temporal operators, 217	overlapping, 190
\$past_gclk, 155	suffix implication, 122, 189, 429, 430
PLI, 59	non-overlapping, 25, 122, 190
pop_front, 329	overlapping, 26, 122, 190
port	s until, 191, 423
implicit, 45	s until with, 192, 424
procedure, 42	until, 111, 191, 424
always_comb, 308	until with, 111, 192, 424
${ t always}, 308$	weak sequence, 184
initial, 308	protocol
final, 44	•
always_comb,42	FIFO, 327, 335, 377
$\mathtt{always_ff}, 42, 43$	pipeline, 323
$always_latch, 42, 43$	retry, 380
final, 42	sequential, 325, 355, 380
program, 40, 47, 222	tag, 331, 337
property, 25, 101, 173–176, 179–180	pruning, 235
Boolean, 102, 422	free, 235
hybrid, 255	set, 235
liveness, 107	PSL, 26, 80, 206, 323, 508
mutually recursive, 373, 376	push_back, 329

quantifier	empty, 128, 426
existential, 244	iteration, 426
universal, 244	match, 115
queue, 328	empty, 118, 134
procedural assertion, 279	method, 214–221
quiescent point, 21	multiply-clocked, 281
	unbounded, 138
	sequence coverage, 96
region, 60	sequence match item, 353
Active, 60, 62	sequence method, 291, 366
Observed, 62, 63	sequence operators
Postponed, 62	intersect, 208, 426
Preponed, 62, 270, 278	and , 211
Reactive, 62, 63, 278	concatenation, 118, 425
region queue	consecutive repetition, 128
Active, 60 Inactive, 60	disjunction, see or
	$first_match, 213, 426$
NBA, 60 relation	fusion, 121, 426
total, 246	goto repetition, 205
repetition range, 131	initial delay, 122
infinite, 131	nonconsecutive repetition, 207
reset, 295	or, 130, 426
asynchronous, 295	throughout, 203, 211
default, 12	within, 212
synchronous, 295	zero repetition, 128
reset condition, 295	sequence property, see sequential property
general, 304	simulation, 20
restriction, 94	glitch, 74, 75, 77, 82, 84, 85, 92
\$rising_gclk, 156	random, 3, 21, 93, 97, 240, 532
\$root, 48	singly clocked, 269
\$rose, 151	\$stable, 91, 153
\$rose gclk, 155	\$stable_gclk,155
RT, 16	starvation, 109
RTL, 3, 5, 9, 12–14, 17, 18, 23, 77, 91, 229,	state, 245
236–238, 246, 247, 256, 262, 334,	accepting, 245
394, 409, 447, 449, 476, 478, 489,	initial, 245
493, 513, 533	statement
, ,	bind, 52
	for loop, 35
\$sampled, 144, 278, 326	generate, 55, 57
sampled value function, 144	case, 56
global clocking, 155	for, 56
future, 155	if,56
past, 155	genvar, 56
sampling, 19, 21, 84, 270, 278	wait, 40, 223
satisfiability, 253	static variable, 313
semantic event, 59	\$steady_gclk,156
evaluation event, 59	subroutine
update event, 59	attached to sequence, 339, 354
sequence, 24, 115, 173–179	subsequence
Boolean, 116, 425	maximal singly clocked, 281
bounded, 117, 138	SVTB, 3
conjunction, 211	synchronizer, 273
disjunction, 426	unclocked, 290

synthesis, 9, 310 SystemC, 9, 13 tight satisfaction, <i>see</i> sequence, match, 425 time slot, 65 time-step, 66 timing verification, 17 TLA, 13 trace, 93, 101, <i>see</i> word transaction, 21 pending, 21 transition relation, 245, 498 triggered, 215, 278, 291, 304, 340, 364, 366, 369	vacuity, 127, 233 vacuous evaluation, 197 vacuous execution rules of nonvacuity, 198 vacuous success, 197 witness assertion, 198 validation post-silicon, 18 validity, 252 variable automatic, 35 static, 35 verification bound, 231 Verilog, 3 VPI, 29, 59
unclocked semantics, 431 underapproximation, 231, 233 \$unit, 48	word, 244 empty, 244 finite, 244 infinite, 244