- Inventory
  - /etc/ansible
  - Ansible-Palybook
    - YAML JSON
  - Playbook vars
  - Playbook vars\_files
  - Register
  - vars\_prompt

Playbook Ansible-Playbook

# **Inventory**

key debug Nginx debug

```
hosts

172.17.0.16 key=16
172.17.0.17 key=17
172.17.0.18 key=18
[nginx]
172.17.0.1[6:8]
[nginx:vars]
ansible_python_interpreter=/usr/bin/python2.7
```

### Playbook

```
variable.yaml
---
- hosts: all
  gather_facts: False
  tasks:
    - name: diplay Host Variable from hostfile
    debug: msg="The {{ inventory_hostname }} Vaule is {{ key }}"
```

# variable.yaml

\$ ansible-playbook variable.yaml -i hosts

Key

#### Hosts Key

```
#172.17.0.16 key=16
#172.17.0.17 key=17
#172.17.0.18 key=18
[nginx]
172.17.0.1[6:8]
[nginx:vars]
ansible_python_interpreter=/usr/bin/python2.7key=nginx
```

#### variable.yaml

\$ ansible-playbook variable.yaml -i hosts

### /etc/ansible

Yum Apt Ansible /etc/ansible host\_vars group\_vars

```
root@cicd:/etc/ansible# tree

ansible.cfg
group_vars

nosts

host_vars

172.17.0.16
172.17.0.17
172.17.0.18
roles

3 directories, 6 files
root@cicd:/etc/ansible# head host_vars/*
==> host_vars/172.17.0.16 <==
key: 172.17.0.16

==> host_vars/172.17.0.16 <==
key: 172.17.0.17

==> host_vars/172.17.0.18 <==
key: 172.17.0.18

=>> host_vars/172.17.0.18 <==
key: 172.17.0.18
```

#### Inventory

```
[nginx]
172.17.0.1[6:8]
[nginx:vars]
ansible_python_interpreter=/usr/bin/python2.7
```

#### variable.yaml

### variable.yaml

\$ ansible-playbook variable.yaml

#### Key host\_vars

```
variable.yaml
$ rm -rf /etc/ansible/host_vars/*
$ ansible-playbook variable.yaml
```

# **Ansible-Palybook**

# variable.yaml

\$ ansible-playbook variable.yaml -e "key=Nginx"

### YAML JSON

YAML

```
variable.yaml

$ echo -e "---\nkey: YAML" > var.yaml
$ ansible-playbook variable.yaml -e "@var.yaml"
```

JSON

```
variable.yaml
$ echo -e '---\n{"key": "JSON"}' > var.json
$ ansible-playbook variable.yaml -e "@var.json"
```

# Playbook vars

Playbook vars

Playbook

```
---
- hosts: all
gather_facts: False
vars:
    key: Ansible
tasks:
    - name: diplay Host Variable from hostfile
    debug: msg="The {{ inventory_hostname }} Vaule is {{ key }}"
```

# Playbook vars\_files

env file

Playbook

```
variable.yaml

---
- hosts: all
  gather_facts: False
  vars_files:
    - var.yaml
  tasks:
    - name: diplay Host Variable from hostfile
       debug: msg="The {{ inventory_hostname }} Vaule is {{ key }}"
```

:

# Register

Playbook task task task task task task task Ansible task register

```
variable.yaml
---
- hosts: 172.17.0.16:172.17.0.17
  gather_facts: False
  tasks:
    - name: register variable
     shell: hostname
     register: info
    - name: display variable
     debug: msg="The varibale is {{ info }}"
```

```
variable.yaml
```

```
$ ansible-playbook variable.yaml -1 172.17.0.17
```

#### debug info Key

```
variable.yaml
---
- hosts: 172.17.0.16:172.17.0.17
  gather_facts: False
  tasks:
    - name: register variable
      shell: hostname
      register: info
    - name: display variable
      debug: msg="The varibale is {{ info['stdout'] }}"
```

### vars\_prompt

Playbook vars\_prompt SHA512 MD5 passlib python

# variable.yaml - hosts: all gather\_facts: False vars\_prompt: - name: "one" prompt: "Please input one value" private: no - name: "two" prompt: "Pleass input two value" default: 'good' private: yes tasks: - name: display one value debug: msg="one value is {{ one }}" - name: display two value debug: msg="two value is {{ two }}"

\$ ansible-playbook variable.yaml -1 172.17.0.16

#### one two one two