"what constituencies of odisha legislative assembly are located in jajpur district"

14 pooled candidates from 8 agents, 7 gold answers; held-out fold 1

position $r_m(c)$ within that agent's own output

candidate c	nano L_m=11	DeepSeek L_m=7	Kimi L_m=7	MAI L_m=7	gpt-5.4 L_m=7	mini L_m=6	grok L_m=6	Cohere L_m=0	$\lvert S\rvert$	score p	gold	
dharmasala	4	5	4	3	2	4	6	·	7	0.83	●	
jajpur	1	1	5	4	1	5	3	·	7	0.80	●	
binjharpur	2	2	3	2	4	1	5	·	7	0.70	●	
sukinda	5	6	7	7	7	6	1	·	7	0.70	●	
bari	8	3	2	1	5	2	4	·	7	0.69	●	
korei	3	7	6	5	·	·	2	·	5	0.51	●	
barchana	10	·	1	·	6	3	·	·	4	0.35	●	
jajpur road	·	·	·	·	3	·	·	·	1	0.06	○	
rasulpur	·	·	·	6	·	·	·	·	1	0.06	○	
barachana	·	4	·	·	·	·	·	·	1	0.02	○	
kalinga nagar	11	·	·	·	·	·	·	·	1	0.01	○	
biridi	9	·	·	·	·	·	·	·	1	0.01	○	
chandikhol	6	·	·	·	·	·	·	·	1	0.01	○	
dhamnagar	7	·	·	·	·	·	·	·	1	0.01	○	

kept

$k^*(q) = 7$

dropped

The keep-count $k^*(q) = 7$ is computed per question from p and the predicted gold size $\hat{G}_q = 9.38$ alone (Sec. 3.4); the true count is 7.

A dot marks an agent that did not assert that candidate. Cohere returned nothing here, so $L_m = 0$; the omission feature clamps $\log L_m$ at $L_m = 1$.

barchana and barachana differ by one character and are graded as different entities, the effect discussed in Sec. 5.7.