

Ad. 5

# Welcome to FlaskBlog

```
127.0.0.1 - - [25/Mar/2024 17:47:04] "GET / HTTP/1.1" 200 -
$ curl http://127.0.0.1:5000/
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <title>FlaskBlog</title>
</head>
<body>
  <h1>welcome to FlaskBlog</h1>
</body>
</html>
```

# Hello, World!

```
127.0.0.1 - - [25/Mar/2024 17:47:05] "GET /hello/ HTTP/1.1" 200 -
$ curl http://127.0.0.1:5000/hello
<!doctype html>
<html lang=en>
<title>Redirecting...</title>
<h1>Redirecting...</h1>
<p>You should be redirected automatically to the target URL: <a href="http://127
.0.0.1:5000/hello/">http://127.0.0.1:5000/hello/</a>. If not, click the link.
```

# Hello <Kewin!

```
127.0.0.1 - - [25/Mar/2024 17:57:34] "GET /hello/kewin HTTP/1.1" 200 -$
curl http://127.0.0.1:5000/hello/kewin
<!doctype html>
<title>Hello from Flask</title>

  <h1>Hello kewin!</h1>
```

Ad.6

```
kewin@DESKTOP-75AKOU3 MINGW64 /c/Users
$ curl http://127.0.0.1:5000/hello/
<!doctype html>
<title>Hello from Flask</title>

  <h1>Hello KEWIN!</h1>
```

Teraz niezależnie od przekazanego parametru, odpowiedź zawsze będzie zawierać imię KEWIN zamiast zmiennej wartości.

Ad.9

```
kewin@DESKTOP-75AKOU3 MINGW64 /f/github_kevoo71/cw_praca_z_kodem (main)
```

```
$ make lint
```

```
pylint app.py
```

```
***** Module app
```

```
app.py:1:0: C0114: Missing module docstring (missing-module-docstring)
```

```
app.py:7:0: C0116: Missing function or method docstring (missing-function-docstring)
```

```
app.py:13:0: C0116: Missing function or method docstring (missing-function-docstring)
```

```
app.py:13:10: W0613: Unused argument 'name' (unused-argument)
```

```
app.py:2:0: W0611: Unused escape imported from markupsafe (unused-import)
```

```
-----
```

```
Your code has been rated at 2.86/10
```

Ad.10

W pliku README