

Probabilistic Primality Testing and Analysis of Probabilistic AKS

Emilie Ma

Summer Research School 2021

Apriltsi, Bulgaria

Introduction

Abstract

This paper aims to analyze the Fermat, the Euler (Solovay-Strassen), and the Miller-Rabin primality tests, three well-known probabilistic algorithms based on Fermat's little theorem. The Agarwal-Kayal-Saxena test, the first polynomial time deterministic primality test developed, is also discussed, as well as a proposal for a new probabilistic adaptation. This probabilistic AKS was found to deliver significant running time decreases, at the expense of eliminating determinism and passing a considerable amount of pseudoprimes.

Abstract

This paper aims to analyze the Fermat, the Euler (Solovay-Strassen), and the Miller-Rabin primality tests, three well-known probabilistic algorithms based on Fermat's little theorem. The Agarwal-Kayal-Saxena test, the first polynomial time deterministic primality test developed, is also discussed, as well as a proposal for a new probabilistic adaptation. This probabilistic AKS was found to deliver significant running time decreases, at the expense of eliminating determinism and passing a considerable amount of pseudoprimes.

- In layman's terms: looked at a variety of tests for checking if a number is prime, and analyzed their performance with regards to speed and accuracy

Primality Testing

Primality Testing

- Why is primality testing important?
 - Modern cryptography and cybersecurity
 - Used in verifying prime numbers
 - Generates a random number, runs through primality test, if prime, then OK for use

Primality Testing

- Why is primality testing important?
 - Modern cryptography and cybersecurity
 - Used in verifying prime numbers
 - Generates a random number, runs through primality test, if prime, then OK for use
- Well-known primality tests include the Fermat, Euler (Solovay-Strassen), Miller-Rabin, and Agarwal-Kayal-Saxena (AKS) tests

Probabilistic vs Deterministic

- The first three tests mentioned above (Fermat, Euler, and Solovay-Strassen) are probabilistic
 - *Probabilistic* \rightarrow element of randomness
 - *Deterministic* \rightarrow given the same input, always returns same output

Probabilistic vs Deterministic

- The first three tests mentioned above (Fermat, Euler, and Solovay-Strassen) are probabilistic
 - *Probabilistic* \rightarrow element of randomness
 - *Deterministic* \rightarrow given the same input, always returns same output
- Why wouldn't we always use deterministic tests?
 - Often much slower, especially as we'll see with the AKS test
 - High performance demands where 100% accuracy can be sacrificed

Probabilistic vs Deterministic

- The first three tests mentioned above (Fermat, Euler, and Solovay-Strassen) are probabilistic
 - *Probabilistic* \rightarrow element of randomness
 - *Deterministic* \rightarrow given the same input, always returns same output
- Why wouldn't we always use deterministic tests?
 - Often much slower, especially as we'll see with the AKS test
 - High performance demands where 100% accuracy can be sacrificed
- Research goal: how can we take the best of both worlds of probabilistic and deterministic tests?

Background Theory

- Assumes a basic knowledge of modular congruences
- All $\log n$ shown are $\log_2 n$ unless otherwise marked

Fermat Primality Test

- Relies on Fermat's Little Theorem: for any integer a and any prime p ,

$$a^p \equiv a \pmod{p} \leftrightarrow a^{(p-1)} \equiv 1 \pmod{p}$$

Fermat Primality Test

- Relies on Fermat's Little Theorem: for any integer a and any prime p ,

$$a^p \equiv a \pmod{p} \leftrightarrow a^{(p-1)} \equiv 1 \pmod{p}$$

- Fermat's primality test chooses k random integers a to run this congruence on
 - Passing higher k values indicates a higher probability that the number is prime

Fermat Primality Test

- Relies on Fermat's Little Theorem: for any integer a and any prime p ,

$$a^p \equiv a \pmod{p} \leftrightarrow a^{(p-1)} \equiv 1 \pmod{p}$$

- Fermat's primality test chooses k random integers a to run this congruence on
 - Passing higher k values indicates a higher probability that the number is prime
- However, certain composite numbers (like Carmichael numbers) pass Fermat's primality test
 - This means there's a chance a *pseudoprime* will be passed

Euler Primality Test

- Utilizes on Euler's Theorem: for any integer a and any prime p where a and p are coprime,

$$a^{\phi(n)} \equiv 1 \pmod{p}$$

- The $\phi(n)$ function is the totient function, which returns $p - 1$ for all prime p
- This is a generalization of Fermat's Little Theorem

Euler Primality Test

- Since $a^{\phi(n)} \equiv 1 \pmod{p}$:

$$a^{\phi(n)/2} \equiv \begin{cases} 1 \pmod{n} & \text{when } x \text{ s.t. } a \equiv x^2 \pmod{n} \\ -1 \pmod{n} & \text{when no such integer.} \end{cases}$$

Euler Primality Test

- Since $a^{\phi(n)} \equiv 1 \pmod{p}$:

$$a^{\phi(n)/2} \equiv \begin{cases} 1 \pmod{n} & \text{when } x \text{ s.t. } a \equiv x^2 \pmod{n} \\ -1 \pmod{n} & \text{when no such integer.} \end{cases}$$

- This forms the criteria for the Legendre symbol $\left(\frac{a}{p}\right)$, which is only defined for odd primes p
 - To allow the Euler primality test to be computed for nonprimes, the Jacobi symbol generalization is used

Euler Primality Test

- Since $a^{\phi(n)} \equiv 1 \pmod{p}$:

$$a^{\phi(n)/2} \equiv \begin{cases} 1 \pmod{n} & \text{when } x \text{ s.t. } a \equiv x^2 \pmod{n} \\ -1 \pmod{n} & \text{when no such integer.} \end{cases}$$

- This forms the criteria for the Legendre symbol $\left(\frac{a}{p}\right)$, which is only defined for odd primes p
 - To allow the Euler primality test to be computed for nonprimes, the Jacobi symbol generalization is used
- As with the Fermat test, k random bases a are tested
 - More accurate than Fermat, but there remains a chance a pseudoprime is passed

Miller-Rabin Primality Test

- The Miller-Rabin Primality test uses different congruences instead, checking for:

$$a^d \equiv 1 \pmod{n}$$

$$a^{(2^r \times d)} \equiv -1 \text{ for some } r \text{ such that } 0 \leq r < s$$

where n is rewritten as $2^s \times d + 1$ and $0 \leq a \leq n$.

- $n - 1 = 2^s \times d$, so if $a^d \equiv \pm 1 \pmod{n}$, n is a *strong probable prime*
- Strong probable \leftrightarrow Miller-Rabin verified

Miller-Rabin Primality Test

- The Miller-Rabin Primality test uses different congruences instead, checking for:

$$a^d \equiv 1 \pmod{n}$$

$$a^{(2^r \times d)} \equiv -1 \text{ for some } r \text{ such that } 0 \leq r < s$$

where n is rewritten as $2^s \times d + 1$ and $0 \leq a \leq n$.

- $n - 1 = 2^s \times d$, so if $a^d \equiv \pm 1 \pmod{n}$, n is a *strong probable prime*
- Strong probable \leftrightarrow Miller-Rabin verified
- This test passes far fewer pseudoprimes than Fermat or Euler tests

Agarwal-Kayal-Saxena Primality Test

- Notable for being the first deterministic primality that runs in polynomial time (bounds of $\tilde{O}(\log^{15/2} n)$)

Agarwal-Kayal-Saxena Primality Test

- Notable for being the first deterministic primality that runs in polynomial time (bounds of $\tilde{O}(\log^{15/2} n)$)
- Based on the theorem that for any a where a is coprime to n and where $n \geq 2$, the following holds within the polynomial ring $\mathbb{Z}[x]$:

$$(X + a)^n \equiv X^n + a \pmod{n}$$

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:
 - Ensure n is not a perfect power ($n = a^k$); if it is, n is composite

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:
 - Ensure n is not a perfect power ($n = a^k$); if it is, n is composite
 - Find smallest r such that $\text{ord}_r(n) \geq \log n^2$

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:
 - Ensure n is not a perfect power ($n = a^k$); if it is, n is composite
 - Find smallest r such that $\text{ord}_r(n) \geq \log n^2$
 - Check that no number a $2 \leq a \leq r$ divides n ; if a does, n is composite

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:
 - Ensure n is not a perfect power ($n = a^k$); if it is, n is composite
 - Find smallest r such that $\text{ord}_r(n) \geq \log n^2$
 - Check that no number a $2 \leq a \leq r$ divides n ; if a does, n is composite
 - Check $n \leq r$; if so, n is prime.

Agarwal-Kayal-Saxena Primality Test

- The test has 5 key steps:
 - Ensure n is not a perfect power ($n = a^k$); if it is, n is composite
 - Find smallest r such that $\text{ord}_r(n) \geq \log n^2$
 - Check that no number a $2 \leq a \leq r$ divides n ; if a does, n is composite
 - Check $n \leq r$; if so, n is prime.
 - Compute all $(X + a)^n \equiv X^n + a \pmod{n}$ for $1 \leq a \leq \lfloor \sqrt{\phi(r)} \log n \rfloor$; if n passes all these tests, it is prime, otherwise it is composite.

Probabilistic AKS Primality Test

- Step 5 in the AKS algorithm has very high bounds, and is very expensive computationally to check - how can we change these bounds to make AKS faster?

Probabilistic AKS Primality Test

- Step 5 in the AKS algorithm has very high bounds, and is very expensive computationally to check - how can we change these bounds to make AKS faster?
- Probabilistic AKS: this research project's proposal for a new variant of AKS
 - Instead of checking all a $1 \leq a \leq \lfloor \sqrt{\phi(r)} \log n \rfloor$, choose k random a values from that range to check
 - Similar idea as the random choice of a in the Fermat, Euler, and Miller-Rabin tests

Probabilistic AKS Primality Test

- Removing the determinism, but reducing the runtime

Probabilistic AKS Primality Test

- Removing the determinism, but reducing the runtime
 - Step 5 dominates the time taken, due to high numbers of computations depending on the value of r , bounded at $O(\log^3 n)$ [1]

Probabilistic AKS Primality Test

- Removing the determinism, but reducing the runtime
 - Step 5 dominates the time taken, due to high numbers of computations depending on the value of r , bounded at $O(\log^3 n)$ [1]
 - Each of the $(X + a)^n \equiv X^n + a \pmod{n}$ equations requires $O(r \times \log^2 n)$ computations

Probabilistic AKS Primality Test

- Removing the determinism, but reducing the runtime
 - Step 5 dominates the time taken, due to high numbers of computations depending on the value of r , bounded at $O(\log^3 n)$ [1]
 - Each of the $(X + a)^n \equiv X^n + a \pmod{n}$ equations requires $O(r \times \log^2 n)$ computations
 - Instead of having to check $\lfloor \sqrt{\phi(r)} \log n \rfloor$ calculations ($O(\sqrt{(\log^3 n)} \times \log n) = O(\log^{5/2} n)$), k equations can be checked, leading to a worst-case complexity of:

$$\tilde{O}(k \times r \times \log^2 n) = \tilde{O}(k \times \log^5 n)$$

Probabilistic AKS Primality Test

- Removing the determinism, but reducing the runtime
 - Step 5 dominates the time taken, due to high numbers of computations depending on the value of r , bounded at $O(\log^3 n)$ [1]
 - Each of the $(X + a)^n \equiv X^n + a \pmod{n}$ equations requires $O(r \times \log^2 n)$ computations
 - Instead of having to check $\lfloor \sqrt{\phi(r)} \log n \rfloor$ calculations ($O(\sqrt{(\log^3 n)} \times \log n) = O(\log^{5/2} n)$), k equations can be checked, leading to a worst-case complexity of:

$$\tilde{O}(k \times r \times \log^2 n) = \tilde{O}(k \times \log^5 n)$$

- With r 's lower bound proven as $2 + \log^2 n$ [13], this could be as low as $\tilde{O}(k \times \log^4 n)$

Analysis Methods

- To consistently analyze the four primality tests (AKS was not tested for pseudoprimes as it is proven correct and would have taken too long), integers in the range $10^5 \leq x \leq 10^6$ were randomly chosen
 - For the Fermat, Euler, and Miller-Rabin tests, 10^4 integers were chosen
 - For probabilistic AKS, 10^2 integers were chosen (as testing 10^4 integers over a large number of trials was infeasible time-wise for this analysis)

- To consistently analyze the four primality tests (AKS was not tested for pseudoprimes as it is proven correct and would have taken too long), integers in the range $10^5 \leq x \leq 10^6$ were randomly chosen
 - For the Fermat, Euler, and Miller-Rabin tests, 10^4 integers were chosen
 - For probabilistic AKS, 10^2 integers were chosen (as testing 10^4 integers over a large number of trials was infeasible time-wise for this analysis)
- Ran the primality test with a variety of k values

- Sympy's `isprime` function was used as a reference to test for primality

- Sympy's `isprime` function was used as a reference to test for primality
- All the data collected can be found at [kewbish/srs](#) on GitHub

Results

Probabilistic primality tests - accuracy

Figure 1: The effect of increasing the number of base trials k on pseudoprimes passed





Figure 2: Average pseudoprimes passed across all $1 \leq k \leq 50$ values per trial



- Fermat consistently passed more pseudoprimes

Probabilistic primality tests - accuracy

Figure 1: The effect of increasing the number of base trials k on pseudoprimes passed





Figure 2: Average pseudoprimes passed across all $1 \leq k \leq 50$ values per trial



- Fermat consistently passed more pseudoprimes
- Euler and Miller-Rabin appear to perform quite similarly but on average Euler will pass more pseudoprimes

Probabilistic primality tests - accuracy

Figure 1: The effect of increasing the number of base trials k on pseudoprimes passed





Figure 2: Average pseudoprimes passed across all $1 \leq k \leq 50$ values per trial



- Fermat consistently passed more pseudoprimes
- Euler and Miller-Rabin appear to perform quite similarly but on average Euler will pass more pseudoprimes
- Supported by the results of Pomerance, Selfridge, and Wagstaff, as well as by Monier's findings [7][5]

Probabilistic primality tests - runtime

Figure 3: The effect of increasing the number of base trials k on pseudoprimes passed






Figure 4: Average pseudoprimes passed across all $1 \leq k \leq 50$ values per trial



- A possible explanation for more efficient runtime of Euler and Miller-Rabin is the speed at which numbers are discarded as composite
 - The congruences used in the Euler and Miller-Rabin tests may do so more quickly - though this has not been theoretically verified yet

Projected pseudoprimes vs. k value


Figure 5: Projected average number of pseudoprimes passed by probabilistic AKS versus other tests



- Significant increase in number of projected pseudoprimes passed by probabilistic AKS compared to the existing tests (200 vs. <10)
 - Projection method: multiply pseudoprimes found by 10^2

Projected pseudoprimes vs. k value

Figure 5: Projected average number of pseudoprimes passed by probabilistic AKS versus other tests



- Significant increase in number of projected pseudoprimes passed by probabilistic AKS compared to the existing tests (200 vs. <10)
 - Projection method: multiply pseudoprimes found by 10^2
- Due to the relatively very low k values tested for probabilistic AKS

Table 1: Number of pseudoprimes passed at given k values

k-value	Pseudoprimes passed							Average pseudoprimes
	0	1	2	3	4	5	6	
100	0	1	2	1	3	0	2	3.4
200	1	0	4	0	3	0	0	2.6
300	3	0	4	1	1	0	0	1.7
400	4	0	4	2	0	0	0	1.4

- Downward trends for pseudoprimes passed also observed for probabilistic AKS
 - The k values required to pass low pseudoprimes are significantly higher than that of the existing probabilistic tests due to the nature of the deterministic AKS algorithm

Running time of probabilistic AKS

Figure 3: The effect of increasing the number of base trials k on pseudoprimes passed






Figure 7: Elapsed running time for probabilistic versus deterministic AKS



- Probabilistic AKS is considerably slower than the existing primality tests, but also significantly faster than deterministic AKS
 - Discrepancies in runtime from probabilistic AKS and existing primality tests can be attributed to time complexity

All pseudoprimes passed $10^5 \leq x \leq 10^6$

Figure 8: Distribution of pseudoprimes found between 10^5 and 10^6 for probabilistic primality tests



- AKS passes by far the greatest pseudoprimes (11524), followed by Fermat (274), Euler (81), and Miller-Rabin (63)
 - Contrasts with Pomerance et. al's findings, but may be attributed to base analysis differences [7]

Sources of Error

- Several possible sources of error were identified in this research project

Sources of Error

- Several possible sources of error were identified in this research project
 - Insufficient bounds of numbers tested; higher amounts of pseudoprimes are found with larger numbers

- Several possible sources of error were identified in this research project
 - Insufficient bounds of numbers tested; higher amounts of pseudoprimes are found with larger numbers
 - Inconsistent amount of numbers tested for each primality trial: the fifty trials of 10^4 with the Fermat, Euler, and Miller-Rabin tests versus the twenty of 10^2 for probabilistic AKS

- Several possible sources of error were identified in this research project
 - Insufficient bounds of numbers tested; higher amounts of pseudoprimes are found with larger numbers
 - Inconsistent amount of numbers tested for each primality trial: the fifty trials of 10^4 with the Fermat, Euler, and Miller-Rabin tests versus the twenty of 10^2 for probabilistic AKS
 - Potentially misleading `isprime` SymPy function used; also relies on probabilistic methods

- To address the sources of error discussed earlier, future research to be conducted includes:

- To address the sources of error discussed earlier, future research to be conducted includes:
 - Experimenting with larger bounds for each primality test; perhaps 10^7 to 10^9

- To address the sources of error discussed earlier, future research to be conducted includes:
 - Experimenting with larger bounds for each primality test; perhaps 10^7 to 10^9
 - Running additional trials with the full 10^4 numbers for probabilistic AKS, and increasing the number of trials run for the other primality tests as well

- To address the sources of error discussed earlier, future research to be conducted includes:
 - Experimenting with larger bounds for each primality test; perhaps 10^7 to 10^9
 - Running additional trials with the full 10^4 numbers for probabilistic AKS, and increasing the number of trials run for the other primality tests as well
 - Precomputing an array of deterministically verified (with AKS) values to check primality against

- To address the sources of error discussed earlier, future research to be conducted includes:
 - Experimenting with larger bounds for each primality test; perhaps 10^7 to 10^9
 - Running additional trials with the full 10^4 numbers for probabilistic AKS, and increasing the number of trials run for the other primality tests as well
 - Precomputing an array of deterministically verified (with AKS) values to check primality against
 - Adjusting the bounds of r in probabilistic AKS to further improve the theoretical runtime complexity

Conclusion

Conclusion

- Fermat: low efficiency, and low accuracy \rightarrow simple to implement, but not practical

Conclusion

- Fermat: low efficiency, and low accuracy \rightarrow simple to implement, but not practical
- Euler: high efficiency, and decent accuracy \rightarrow best in speed-driven scenarios

Conclusion

- Fermat: low efficiency, and low accuracy \rightarrow simple to implement, but not practical
- Euler: high efficiency, and decent accuracy \rightarrow best in speed-driven scenarios
- Miller-Rabin: relatively high efficiency, and higher accuracy than Euler \rightarrow recommended when practical accuracy is key

Conclusion

- Fermat: low efficiency, and low accuracy \rightarrow simple to implement, but not practical
- Euler: high efficiency, and decent accuracy \rightarrow best in speed-driven scenarios
- Miller-Rabin: relatively high efficiency, and higher accuracy than Euler \rightarrow recommended when practical accuracy is key
- Deterministic AKS: no pseudoprimes passed, and very slow to run \rightarrow good for applications where speed is irrelevant

Conclusion

- Fermat: low efficiency, and low accuracy \rightarrow simple to implement, but not practical
- Euler: high efficiency, and decent accuracy \rightarrow best in speed-driven scenarios
- Miller-Rabin: relatively high efficiency, and higher accuracy than Euler \rightarrow recommended when practical accuracy is key
- Deterministic AKS: no pseudoprimes passed, and very slow to run \rightarrow good for applications where speed is irrelevant
- Probabilistic AKS: high numbers of pseudoprimes passed at low k , much faster than deterministic AKS \rightarrow may provide a suitable alternative to deterministic AKS for more practical applications given high enough k values

Acknowledgements

- Many thanks to my mentor, Ms. Pressiana Marinova, for her unfailing guidance and support throughout SRS and the research process, her deep knowledge and clear explanations of new topics, and for always being there to answer all my questions.

Acknowledgements

- Many thanks to my mentor, Ms. Pressiana Marinova, for her unfailing guidance and support throughout SRS and the research process, her deep knowledge and clear explanations of new topics, and for always being there to answer all my questions.
- Much gratitude also to the Summer Research School and High School Student Institute of Mathematics and Informatics for making this research inquiry experience possible, and for hosting such an organized, fun summer program.

Manindra Agrawal, Neeraj Kayal, and Nitin Saxena. **PRIMES is in P.** *Annals of Mathematics*, 160(2):781–793, September 2004.

Richard P Brent. ***Primality Testing.*** Thesis, Australian National University, Mathematical Sciences Institute and College of Engineering and Computer Science, August 2010.

Hendrik Lenstra, Jr. and Carl Pomerance. **Primality testing with Gaussian periods.** July 2005.

Gary L. Miller. **Riemann's Hypothesis and tests for primality.** In *Proceedings of seventh annual ACM symposium on Theory of computing - STOC '75*, pages 234–239, Albuquerque, New Mexico, United States, 1975. ACM Press.

Louis Monier. **Evaluation and comparison of two efficient probabilistic primality testing algorithms.** *Theoretical Computer Science*, 12(1):97–108, September 1980.

Lalitha Kiran Nemana and V. Ch Venkaiah. **An empirical study towards refining the aks primality testing algorithm.** Technical Report 362, 2016.

Carl Pomerance, J. L. Selfridge, and Samuel S Wagstaff. **The Pseudoprimes to $25 \cdot 10^9$.** *Mathematics of Computation*, 35(151):1003–1026, July 1980.

Michael O Rabin. **Probabilistic algorithm for testing primality.** *Journal of Number Theory*, 12(1):128–138, February 1980.

Chris Rotella. **An Efficient Implementation of the AKS Polynomial-Time Primality Proving Algorithm.** Thesis, Carnegie Mellon University, May 2005.

R. Solovay and V. Strassen. **A Fast Monte-Carlo Test for Primality.** *SIAM Journal on Computing*, 6(1):84–85, March 1977.

Sophoclis Stephanou. **Ssophoclis/AKS-algorithm: Implementation of the AKS primality test algorithm in python.**, July 2020.

SymPy Development Team. **Number Theory — SymPy 1.8 documentation**, April 2021.

Tammy Terzian. *The AKS Primality Test*. Thesis, The California State University, October 2013.