



## Special applications: Face recognition & Neural style transfer

Quiz, 10 questions

8/10 points (80%)



**Congratulations! You passed!**

Next Item



1 / 1  
point

1.

Face verification requires comparing a new picture against one person's face, whereas face recognition requires comparing a new picture against K person's faces.

---



1 / 1  
point

2.

Why do we learn a function  $d(img1, img2)$  for face verification? (Select all that apply.)

---



1 / 1  
point

3.

In order to train the parameters of a face recognition system, it would be reasonable to use a training set comprising 100,000 pictures of 100,000 different persons.

---



1 / 1  
point  
Quiz, 10 questions

## Special applications: Face recognition & Neural style transfer


8/10 points (80%)

4.  
Which of the following is a correct definition of the triplet loss? Consider that  $\alpha > 0$ . (We encourage you to figure out the answer from first principles, rather than just refer to the lecture.)



1 / 1  
point

5.  
Consider the following Siamese network architecture:



The upper and lower neural networks have different input images, but have exactly the same parameters.



1 / 1  
point

## 6. ← Special applications: Face recognition & Neural style transfer

**8/10 points (80%)**

You train a ConvNet on a dataset with 100 different classes. You wonder if you can find a hidden unit which responds strongly to pictures of cats. (I.e., a neuron so that, of all the input/training images that strongly activate that neuron, the majority are cat pictures.) You are more likely to find this unit in layer 4 of the network than in layer 1.

---

0 / 1  
point

7.

Neural style transfer is trained as a supervised learning task in which the goal is to input two images ( $x$ ), and train a network to output a new, synthesized image ( $y$ ).

---

1 / 1  
point

8.

In the deeper layers of a ConvNet, each channel corresponds to a different feature detector. The style matrix  $G^{[l]}$  measures the degree to which the activations of different feature detectors in layer  $l$  vary (or correlate) together with each other.

---

0 / 1  
point

9.

In neural style transfer, what is updated in each iteration of the optimization algorithm?

---

1 / 1  
point

10.

You are working with 3D data. You are building a network layer whose input volume has size  $32 \times 32 \times 32 \times 16$  (this volume has 16 channels), and applies convolutions with  $4 \times 4 \times 4$  filters of dimension  $3 \times 3 \times 3$  (padding, stride 1). What is the resulting output volume?

Quiz, 10 questions

**8/10 points (80%)**

## Special applications: Face recognition & Neural style transfer

