

VAPT - IA1

Keyur Patel - 16010421073

Krishiv Patel - 16010421074


Batch : A2

Aim : Explain and fix an Insecure Direct Object Reference (IDOR) vulnerability in a Real Estate Listing Platform, specifying the relevant CWE: Insecure Direct Object Reference (CWE-639) and (CWE-353) Missing Support for Integrity Check.


Resources needed: Real Estate website , Burpsuite , Xampp

Real Estate Listing Platform


Home Page of website



About us



View Property of website



Create Account

MyHome post property

buy sell rent help saved account

Create An Account!

enter your name

enter your email

enter your password

confirm your password

already have an account? [Login now](#)

Register Now

123456789 home facebook

about

Contact Us

MyHome post property

buy sell rent help saved account

house

flat

shop

ready to move

furnished

Get In Touch

enter your name

enter your email

enter your number

enter your message

Send Message

SELECT

Vulnerability - 1 (CWE – 639 Insecure Direct Object Reference)

Insecure Direct Object Reference:-

Insecure Direct Object Reference refers to a vulnerability that occurs when a web application exposes a reference to an internal implementation object, such as a file, directory, database record, or key, in a way that allows unauthorized access to that object.

Procedure to Expose Vulnerability:

Step-1) This is the Create Account page where we are going to exposing the modification of user credential using burpsuite.

Step-2) Data stored for user in phpMyAdmin having database as 'realestate'.

	id	name	email	pass	c_pass
<input type="checkbox"/>	1	keyur patel	keyur.n.patel100@gmail.com	123456	123456
<input type="checkbox"/>	2	Krishiv Patel	krshiv.p@somaiya.edu	pass123	pass123

Step-3) Form code for account.

```
<form action="php echo $_SERVER['PHP_SELF']; ?" method="POST">
  <h3>create an account!</h3>
  <input type="text" name="name" required maxlength="50" placeholder="enter your name" class="box">
  <input type="email" name="email" required maxlength="50" placeholder="enter your email" class="box">
  <input type="password" name="pass" required maxlength="20" placeholder="enter your password" class="box">
  <input type="password" name="c_pass" required maxlength="20" placeholder="confirm your password" class="box">
  <p>already have an account? <a href="login.php">Login now</a></p>
  <input type="submit" value="register now" name="submit" class="btn">
</form>
```

Step-4) Form is submitted using post method in users table.

```
$conn = mysqli_connect('localhost','root','','realestate') or die('connection failed');


// Check connection
if ($conn->connect_error) {
    die("connection failed: " . $conn->connect_error);
}
?>

<?php
if ($_SERVER["REQUEST_METHOD"] == "POST") {
    $name = $_POST["name"];
    $email = $_POST["email"];
    $pass = $_POST["pass"];
    $c_pass = $_POST["c_pass"];

    // Check if passwords match
    if ($pass != $c_pass) {
        echo "Passwords do not match";
    } else {
        // Insert data into database
        $sql = "INSERT INTO users (name, email, pass,c_pass) VALUES ('$name', '$email', '$pass', '$c_pass')";

        if ($conn->query($sql) === TRUE) {
            echo "New record created successfully";
        } else {
            echo "Error: " . $sql . "<br>" . $conn->error;
        }
    }
}
?>
```

Step-5) Entering the credentials in burpsuite browser when intercept is switched off.



The screenshot displays a web browser window with the URL `localhost/real_estate_website/register.php`. The page shows a 'Create An Account!' form with fields for name (filled with 'aditi patil'), email (filled with 'aditi234@gmail.com'), and password (masked with dots). A 'Register Now' button is at the bottom. Below the form is a navigation bar with links: home, about, contact, and all listings.

On the right, the browser's developer tools are open to the 'Network' tab, showing an intercepted POST request to `http://localhost:80 [127.0.0.1]`. The request body is visible in the 'Inspector' pane, showing a JSON object with user details and a warning message.

```
user_id=
13Cbcr+2CF38c10D40A3C3b3EWarning!3C42Fb3E3A3+Undefined+variable+42C4user_id+in+13Cb3E3C3A3Scrampp5Chtcdocs5Creal_estate_website5Cregister.php!3C42Fb3E3+on+line+13Cb3E34013C42CFb3E3C3b3+1CF38c10D40A3C3b3Eaditc+ipatitl6email=aditc124@gmail.com+pass=hello1234c pass=hello1236submit=register+nov
```

Showing rows 0 - 2 (3 total, Query took 0.0003 seconds.)

SELECT * FROM `users`

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 ▼

Extra options

			id	name	email	pass	c_pass	
<input type="checkbox"/>	Edit	Copy	Delete	1	keyur patel	keyur.n.patel100@gmail.com	123456	123456
<input type="checkbox"/>	Edit	Copy	Delete	2	Krishiv Patel	krishiv.p@somaiya.edu	pass123	pass123
<input type="checkbox"/>	Edit	Copy	Delete	31	aditi patil	aditi2@gmail.com	hello123	hello123

☐ Check all
 With selected: Edit Copy Delete Export

Mitigation:


- ***Implement Access Control Checks:*** Ensure that every object a user tries to access is checked against the user's permissions. This means verifying that the user has the right to view or modify the object before allowing the action. This can be achieved by checking the user's session information against the object's ownership or permissions.
- ***Verify User Permissions:*** Every time an access attempt is made, verify the user's permission. This can be implemented structurally using the recommended approach for your web framework. For example, when looking up objects based on primary keys, ensure that the datasets users have access to are used.
- ***Use Prepared Statements for Database Queries:*** To prevent SQL Injection, which is a related vulnerability, use prepared statements for database queries. This ensures that user input is treated as data and not.

Vulnerability - 2 (CWE – 353 Missing Support for Integrity Check)

If integrity check values or "checksums" are omitted from a protocol, there is no way of determining if data has been corrupted in transmission. The lack of checksum functionality in a protocol removes the first application-level check of data that can be used. The end-to-end philosophy of checks states that integrity checks should be performed at the lowest level that they can be completely implemented. Excluding further sanity checks and input validation performed by applications, the protocol's checksum is the most important level of checksum, since it can be performed more completely than at any previous level and takes into account entire messages, as opposed to single packets.

Procedure to Expose Vulnerability:

Step-1) Go to Contact us webpage for users. Here we are going to expose integrity of data being tampered by attacker without any checksum provided.



Step-2) PHPCode for submission after entering the message which is then sent to database in phpMyAdmin using post method.

```
<?php
$conn = mysqli_connect('localhost', 'root', '', 'realestate') or die('connection failed');

if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

if ($_SERVER["REQUEST_METHOD"] == "POST") {
    $name = $_POST["name"];
    $email = $_POST["email"];
    $phone = $_POST["number"];
    $message = $_POST["message"];


    // Check if passwords match
    if (filter_var($email, FILTER_VALIDATE_EMAIL)) {
        // Email is valid
        echo "Email is valid: " . $email;
        // Here you can proceed with further processing, such as saving the email to a database or sending it via email
    } else {
        // Email is invalid
        echo "Invalid email address!";
        // You can display an error message or take other actions to handle the invalid email
    }

    $sql = "INSERT INTO contact_form (name, email, number, message) VALUES ('$name', '$email', '$phone', '$message')";


    if ($conn->query($sql) === TRUE) {
        echo "New record created successfully";
    } else {
        echo "Error: " . $sql . "<br>" . $conn->error;
    }

    $conn->close();
}
?>
```


Step-3) Enter the form details when intercept is off.



Step-4) Click on the Intercept option and then submit “get in touch” form.



Step-5) The Request is then redirected to burpsuite which shows what is sent by user.



Step-4) The Attacker modifies the message and tampers the integrity of message.

```
1 |
2 name=Archit+Saxena&email=archit21@somaiya.edu&number=
  9789324567&message=modified+text.&send=send+message
```

Step-5) Then forward the modified message to database. You will see that data is modified as “*modified text*”.

✓ Showing rows 0 - 2 (3 total, Query took 0.0005 seconds.)

SELECT * FROM `contact_form`

☐ Profiling [Edit inline] [Edit] [Explain SQL] [Create PHP code] [Refresh]

☐ Show all | Number of rows: 25 | Filter rows: Search this table | Sort by key: None

Extra options

			id	name	email	number	message
<input type="checkbox"/>	Edit	Copy	Delete	5	keyur patel	keyur.n.patel100@gmail.com	9769345213 I want to buy a 3BHK flat in versova.
<input type="checkbox"/>	Edit	Copy	Delete	6	keyur patel	keyur.n.patel100@gmail.com	9769345213 I want to buy a 3BHK flat in versova.
<input type="checkbox"/>	Edit	Copy	Delete	7	Archit Saxena	archit21@somaiya.edu	9789324567 modified text.

Mitigation:

Step-1) The modified PHP code having function for fetch and verify data which includes checksum and hashes the text for 'message'.

```
<?php
$conn = mysqli_connect('localhost', 'root', '', 'realestate') or die('connection failed');

if ($conn->connect_error) {
    die("Connection failed: " . $conn->connect_error);
}

if ($_SERVER["REQUEST_METHOD"] == "POST") {
    $name = $_POST["name"];
    $email = $_POST["email"];
    $phone = $_POST["number"];
    $message = $_POST["message"];

    // Generate checksum
    $data = $name . $email . $phone . $message;
    $checksum = hash('sha256', $data);

    // Prepare SQL statement
    $sql = "INSERT INTO contact_form (name, email, number, message, checksum) VALUES (?, ?, ?, ?, ?)";
    $stmt = $conn->prepare($sql);
    $stmt->bind_param("sssss", $name, $email, $phone, $message, $checksum);

    if ($stmt->execute()) {
        echo "New record created successfully";
    } else {
        echo "Error: " . $sql . "<br>" . $conn->error;
    }


    $stmt->close();
}
```

```
function fetchAndVerifyData($conn, $id) {
    $sql = "SELECT * FROM contact_form WHERE id = ?";
    $stmt = $conn->prepare($sql);
    $stmt->bind_param("i", $id);
    $stmt->execute();
    $result = $stmt->get_result();
    $retrievedData = $result->fetch_assoc();

    // Recalculate checksum
    $recalculatedChecksum = hash('sha256', $retrievedData['name'] . $retrievedData['email'] . $retrievedData['number'] . $retrievedData['message']);

    if ($recalculatedChecksum === $retrievedData['checksum']) {
        // Data is intact
        return $retrievedData;
    } else {
        // Data may have been tampered with
        return false;
    }
}
```

Step-2) Entering The form details when intercept is off.




Step-3) The checksum generated for “I want two flats in Andheri” is

Checksum:


8c89d822e1797b82b011b2b60a3ea377d9c43ab360805f25413171f008bc43c8

Copy Delete 16 rohit mehta rohit23@gmail.com 9876213456 I want two flats in Andheri. 8c89d822e1797b82b011b2b60a3ea377d9c43ab360805f2541...

Step-4) Then Click on the intercept option and send the message.



Step-4) Then the request is redirected to burpsuite where we will modify the text “I want two flats in Andheri” to “I want four flats in Andheri”.



```
name=rohit+mehta&email=rohit23@gmail.com&number=
9876213456&message=I+want+four+flats+in+Andheri.&send=
send+message
```

Step-5) The checksum generated for “I want four flats in Andheri” is

Checksum:

48767f98c35e3008cf41989e76e4e3c85a57b4ea7f339b005c61dd748fc023aa

<input type="checkbox"/>	Edit	Copy	Delete	17	rohit mehta	rohit23@gmail.com	9876213456	I want four flats in Andheri.	48767f98c35e3008cf41989e76e4e3c85a57b4ea7f339b005c...
<input type="checkbox"/>	Edit	Copy	Delete	18	rohit mehta	rohit23@gmail.com	9876213456	I want two flats in Andheri.	8c89d822e1797b82b011b2b60a3ea377d9c43ab360805f2541...

Thus we can determine if data integrity is modified through change in hash values and compare it with original text.