# TMP36 Temperature Sensor

## Introduction

The TMP36 is low voltage, precision centigrade temperature sensor. It provides a voltage output that is linearly proportional to the Celsius (Centigrade) temperature. The TMP36 does not require any external calibration to provide typical accuracies of ±1°C at +25°C and ±2°C over the –40°C to +125°C temperature range. The low output impedance of the TMP36 and its linear output and precise calibration simplify interfacing to temperature control circuitry and A/D converters. It is intended for single-supply operation from 2.7 V to 5.5 V maximum. Supply current runs well below 50 µA, providing very low self-heating—less than 0.1°C in still air. In addition, a shutdown function is provided to cut supply current to less than 0.5

µA.

The TMP36 is specified from –40°C to +125°C, provides a 750 mV output at 25°C, and operates to +125°C from a single 2.7 V supply. The TMP36 is functionally compatible with the LM50. The TMP36 has an output scale factor of 10 mV/°C and it is available in low cost 3-lead TO-92, SOIC-8, and 5-lead SOT-23 surface-mount packages.

## Features

1. Low Voltage Operation (2.7 V to 5.5 V)
2. Calibrated Directly in °C
3. 10 mV/°C Scale Factor (20 mV/°C on TMP37)
4. ±2°C Accuracy over Temperature (Typ)
5. ±0.5°C Linearity (Typ)
6. Stable with Large Capacitive Loads
7. Specified –40?C to +125°C, Operation to +150°C
8. Less than 50 ?A Quiescent Current
9. Shutdown Current 0.5µA Max
10. Low Self-Heating

## Applications

1. Environmental Control Systems
2. Thermal Protection
3. Industrial Process Control
4. Fire Alarms

5. Power System Monitors

6. CPU Thermal Management



## Component List

◆ Keywish Arduino UNO R3 mainboard

◆ Breadboard

◆ USB cable

◆ TMP36 module*1

◆ Some wires

## Wiring of Circuit

| Arduino Nano | TMP36 module |
|---|---|
| +5V | left |
| A0 | middle |
| GND | right |

## code

```
int sensorPin = A0; //the analog pin the TMP36's Vout (sense) pin is connected
to
                //the resolution is 10 mV / degree centigrade with a
                //500 mV offset to allow for negative temperatures
void setup()
{
  Serial.begin(9600);  //Start the serial connection with the computer
                    //to view the result open the serial monitor
}

void loop()
{
 int reading = analogRead(sensorPin);  //getting the voltage reading from
the temperature sensor
 float voltage = reading * 5.0;
 voltage= voltage /1024.0 -0.17;

 Serial.print(voltage); Serial.println(" volts");
 float temperatureC = (voltage - 0.5) * 100;  //converting from 10 mv per
degree wit 500 mV offset
                                //to degrees ((volatge - 500mV)
times 100)
 Serial.print(temperatureC);
```

```
Serial.println(" degrees C");
float temperatureF = (temperatureC * 9.0 / 5.0) + 32.0;
Serial.print(temperatureF);
Serial.println(" degrees F");
delay(1000);
}
```

## Experiment Result