



Esco Streamline® Closed Restricted Access Barrier System

Model SLC-RABS-4N1-S

# Streamline®

**Closed - Restricted Access  
Barrier System (Recirculating)**

*Ensuring Sterility for High Quality Compounding*



**ESCO**  
PHARMA®



Available in 1.2 and 1.8 meters models (4' and 6'). Esco Streamline® Closed Restricted Access Barrier System (Recirculating), Model SLC-RABS-4N is shown with optional sharps disposal system and optional hydraulic height adjustable stand.



## Main Features

- ULPA filters (as per IEST-RP-CC001.3 and HEPA (H14) filter as per EN 1822) with a typical efficiency of >99.995% at 0.1 to 0.3 microns, providing ISO Class 5 air cleanliness as per ISO 14644-1.
- Sentinel™ Gold Microprocessor controller supervises all functions and monitors airflow and pressures in real-time.
- For negatively pressured RABS, the work zone and pass-through chambers are under negative pressure to the room to maintain operator protection in the event of a breach in the system.
- Positively pressured configurations are under positive pressure to the room to ensure product protection.
- Robust dual-wall construction. The work zone is surrounded by negative pressure plenums at the sides and back. Unique Esco Dynamic Chamber™ plenum surrounds filter seals with negative pressure.
- Ergonomically angled front and oval gloveports improve reach and comfort.
- Safe-change cuff rings permit glove changing with zero risk of contaminating the work zone and/or pharmacy environment.
- Easy to clean one-piece work zone liner without any crevices.
- Esco **ISOCIDE™** antimicrobial coating on all painted surfaces to minimize contamination.
- Sharps disposal system and hydraulic height-adjustable stand are available as options.
- Instant-start 5000k LED lamps operate on electronic ballasts for energy efficiency.

## Streamline® Closed - Restricted Access Barrier System

### SLC-RABS-4CN3-S

Unit	Model	Nominal Width	Glove Port Design	Electrical Code	Pressure Scheme	Sharps Provision
Streamline® Closed - Restricted Access Barrier System	SLC-RABS	4 4 ft (1.2 m)	C Circular glove port (300 mm x 300 mm)	1 220-240 V, AC, 50 Hz, 1Ø	N Negative	0 No
		6 6 ft (1.8 m)	O Oval glove port (200 mm x 300 mm)	2 110-120 V, AC, 50 Hz, 1Ø	P Positive	S Yes
				3 220-240 V, AC, 60 Hz, 1Ø		

## Vertical Pass-through Door

The vertical pass-through door prevents ingress of contamination into the work zone during transfer procedures. The built-in electrical interlock prevents both doors from being opened at the same time.



## Horizontal Tray

The horizontal tray prevents operator fatigue during transfer procedures.



## Airlock Pass-through

The airlock pass-through ensures work zone remains sterile during material ingress and egress.



## Optional Sharps Disposal System

The sharps disposal system enables smoother work flow and minimizes transfers via disposal of waste through the work surface into the bins below; thus, minimizing contamination of the work zone.



## Adjustable Hydraulic Support Stand

The motorized hydraulic stand option, is adjustable to accommodate user preference for a sitting or standing work position.

Criteria	RABS	ISOLATOR
Decontamination	Manually disinfected	Quantifiable and high reproducible method by an automated system
Assurance of Separation	No complete physical separation	Quantifiable hourly leak rate (closed) and continuously controlled differential pressure
Surrounding Environment	Passive: ISO 5 Active: ISO 7	US cGMP: ISO 8 EU cGMP: Grade D
Containment Applications	Low capability	Quantifiable leakage tightness (ISO 10648-2)
Glove Leak Test	Not applicable	Mandatory; Quantifiable glove integrity
Capital Costs	Higher than conventional cleanroom (CCR); reduced with renovation and retrofit application	High equipment costs
Operating Costs	Higher than CCR	Cost saving in energy consumption (HVAC) and clothing
Toxic Containment	Low capability	Good reliability

## Closed Restricted Access Barrier Systems (cRABS)

As per USP <797> a restricted access barrier system (RABS) is an enclosure providing a HEPA-filtered ISO Class 5 unidirectional air that allows for the ingress and/or egress of materials through defined openings that have been designed and validated to prevent the risk for cross-contamination.

A closed RABS provide superior sterility as compared to open front clean air devices (laminar flow clean benches and Class II biological safety cabinets).

A pharmaceutical isolator on the other-hand is defined by USP <797> as an enclosure that provides HEPA-filtered ISO Class 5 unidirectional

air operated at a continuously higher pressure than the surrounding environment.

USP <800> states that a Compounding Aseptic Containment Isolator (CACI) is intended for the compounding of sterile Hazardous Drugs and is designed to provide operator, product, and environment protection.

For facilities that do not need to comply with the United States Pharmacopoeia (USP), then the system can still be called an isolator, however, it will not be in line with international cGMP guidelines.





#### Product, Operator and Environment Protection

Esco Streamline® Closed - Restricted Access Barrier System (Recirculating) Models, provide a safe and clean environment for sterile drug compounding in compliance with USP <797> criteria.

#### SLC-RABS: A Safe and Efficient Solution

SLC-RABS is a safe and efficient solution for the production of low-volume pharmaceuticals as well as with practices concerning:

- Operator aseptic technique training
- Expiration settings
- Product quality maintenance (once CSP leaves the pharmacy)

Furthermore, RABS can reduce operating and renovation costs by taking up less space than a traditional cleanroom facility.

Negatively pressured, recirculating SLC-RABS model is suitable for work involving non-volatile hazardous materials, antineoplastic, or cytotoxic compounding applications. The work zone and pass-through interchange are under negative pressure to the room to maintain operator protection in case of a breach in the system.


#### Product Sterility and Integrity

- SLC-RABS combination of downflow and exhaust H14 filters envelopes the main process chamber with ISO Class 5 air; providing operator and/or product protection in all configurations.
- Advanced mini-pleated supply H14 filters are tested to >99.999% efficiency for 0.3 micron particulates, significantly better than conventional filters.
- An improved mini-pleat separation technique maximizes filter surface area, improves efficiency, and extends filter.

- The supply filter provides clean air to the work surface in a gentle vertical laminar flow.
- Laminar airflow within the work zone and pass-through enables recovery of chamber atmosphere to ISO Class 5 conditions within 3 minutes following a worse-case contamination event.
- The entire work zone air is changed 20-30 times per minute.
- Laminar (unidirectional) airflow within work zone and pass-through enables recovery of chamber atmosphere to
- Airlock pass-through ensures work zone sterility during material ingress and egress.




#### Mini-pleat Separatorless Filter (left) vs. Conventional Aluminum Separator Filter (right)



Esco cabinets use Swedish Camfil Farr® mini-pleat filters without aluminum separators to increase filter efficiency, minimize the chance of leakage, and prolong filter life. Filters include a lightweight aluminum frame for structural stability and elimination of swelling common to conventional wood frames.

\* United States Pharmacopoeia (USP), Chapter 797(1), enacted January 1, 2004, presents the first enforceable standards for aseptic compounding. Following years of patient safety recommendations and professional guidelines, the intent of USP 797 is to set forth the procedural and practical requirements for safe compounding of aseptic preparations. The Chapter's requirements are applicable in all practice settings where aseptic preparations are compounded.

#### Esco Filter Efficiency



● Typical Penetration

Esco uses ULPA filters (as per IEST-RP-CC001.3 and HEPA (H14) filter as per EN 1822) with a typical efficiency of >99.999% at 0.3 microns, providing ISO Class 5 air cleanliness as per ISO 14644-1.

Enlarged, multi-line digital read-out with alpha-numeric display indicates all input, status and alarm functions.

Work zone, interchange pressures and downflow velocity are continuously measured and displayed. Integrated true airflow sensor is temperature compensated for improved accuracy.

Password-protected administration can be set to restrict access to main menu.

Color coded indicator lamps display green for fan operation; blue for LED lights and electrical outlet; and orange for AUX function ON.

Optional audible and visual alarms warn of unsafe conditions such as low chamber pressure.



Sentinel™ Microprocessor Control System, Programmable

- When programmed ON
- the start-up sequence confirms status with Air Safe and local time display.
- the Personal Identification Number (PIN) access restricts unauthorized adjustments.

- Vertical sliding door between the pass-through and work zone chambers minimizes ingress of particulates during transfer operations as compared with conventional swing door designs.
- Optional sharps disposal system enables smoother work flow and minimizes transfers to enhance patient protection and product sterility. Sharps disposal may be done in the work surface via the disposal bins, thus; minimizing work zone contamination.
- Safe-change cuff rings enable glove change.



The front visor opens up fully for maintenance access into the work zone.

### Cabinet Construction Designed for Easy Cleaning

- Robust construction and enhanced safety features qualify the unit for the most demanding laboratory applications. SLC-RABS is fully assembled and ready to install and operate when shipped.
- The cabinet interior is constructed of durable and pharmaceutical-grade 304 stainless steel.
- Single-piece stainless steel work tray is easy to clean. Raised edges on all sides contain spillages.
- Stainless steel drain pan below the work surface contains spills.
- Tray components lift and remove to provide easy access and encourage surface decontamination.
- The cabinet exterior structure is constructed of industrial-grade electro-galvanized steel.
- The downflow HEPA filter is protected by a diffuser which may be cleaned.
- Hinged window may be opened for thorough access into the work zone.
- External surfaces are coated with ISOCIDE™ antimicrobial coating to protect against surface contamination and inhibit bacterial growth. ISOCIDE™ eliminates 99.9% of surface bacteria within 24 hours of exposure.

### Sentinel™ Microprocessor Control, Monitoring System

The Esco Sentinel™ microprocessor-based control system supervises operation of all functions. Controls are configurable to meet user requirements. Features of the main control panel include:


- Work zone and pass-through pressures are monitored and displayed on the LCD screen.
- Continuous monitoring and display of cabinet laminar (downflow) airflow on large, easy-to-read LCD display.
- An optional alarm package (pressure and airflow) is available for users with more sophisticated requirements.

### Fan Efficiency

The unit's fan system is designed for maximum energy efficiency and minimal maintenance.

- Centrifugal, direct-drive, external rotor motors reduce operating costs.
- Unique Esco motor/fan orientations minimize noise and vibration.
- Built-in solid-state variable speed controllers are infinitely adjustable from Off to Maximum.

## Streamline® Closed - Restricted Access Barrier System (Recirculating)



- HEPA-filtered air
- Unfiltered / potentially contaminated air
- Room air / Inflow air

- Ambient air is pulled through the inlet pre-filter located on top of the SLC-RABS, which traps larger particles and extends the life of the supply HEPA filter. The pre-filter traps larger particles and extends the life of the supply HEPA filter.
- Air from the top inlet and from work zone is pulled by the main fan, which creates positive pressure on the plenum and thus, downflow.
- The work zone and pass-through interchange are under negative pressure to the room.
- The HEPA downflow filter creates a laminar and particle-free ISO Class 5 environment to protect the work material inside the main and pass-through.
- Air from the work zone and pass-through is quickly purged by the fans to keep the area clean. The main fan pulls approximately 90% of the purged air back to the plenum and after passing through the HEPA downflow filter again, it is recirculated back to the two chambers. The high rate of airflow recirculation helps to prolong filter life.
- Approximately 10% of the recirculated air is exhausted through a HEPA filter filter to prevent heat build-up inside the RABS.

Standards Compliance	Cabinet Performance	Air Quality	Filtration	Electrical Safety
	CETA CAG-001-2005, USA CETA CAG-002-2006, USA	ISO 14644-1 Class 3 (at rest), Class 5 (in operation), EU GMP Grade A, Worldwide JIS B9920, Class 3, Japan BS 5295, Class 1, UK	EN-1822, Europe IEST-RP-CC001.3, USA IEST-RP-CC007, USA IEST-RP-CC034.1, USA	IEC 61010-1, Worldwide EN 61010-1, Europe UL 61010-1, USA CAN/ CSA-22.2, No. 61010-1

6

### Safety and Certification

All components used in Esco products meet or exceed all applicable safety requirements.

- Each cabinet is individually factory tested for electrical safety.
- Documentation specific to the cabinet serial number is maintained on file.

### Warranty

Esco's Streamline® Closed - Restricted Access Barrier System (SLC-RABS) comes with a 1-year warranty excluding consumable parts and accessories. Contact your local sales representative for specific details.

### Accessories and Options

Esco's Streamline® Closed - Restricted Access Barrier System (SLC-RABS) is available as a standard bench top unit. Additional accessories are available for further enhancement.

### Electrical Outlets and Utility Fittings


- Electrical outlet, ground fault, North America
- Electrical outlet, Euro/Worldwide

### Support Stands

- Fixed height, available 711 mm (28") or 864 mm (34")

- With leveling feet,  $\pm 38.1$  mm (1.5") (SAL-\_\_0)
- With casters (SPC-\_\_0)
- Telescoping height stand for leveling
- feet (STL-\_\_0), nominal range 660 mm to 960 mm (26" to 37.8")
- Telescoping height stand for casters (STC-\_\_0), nominal range 660 mm to 880 mm (26" to 34.6")
  - Adjustable in 25.4 mm (1") increments
- Infinitely adjustable hydraulic stand, with casters, elevates to accommodate user preference for sitting or standing work surface height (SHM-\_A0)


### Esco Centrifugal Fan with External Rotor Motor (left) vs. Conventional Fan with Standard Motor (right)



- Esco cabinets use German made *ebm-papst*® permanently lubricated, centrifugal motor/fans with external rotor designs.
- Integrated blades narrow the profile and eliminate need for a motor shaft.
- Motors are selected for energy efficiency, compact design, and flat profile. The completely integrated assembly optimizes motor cooling.
- All rotating parts are unitized and balanced for smooth, quiet, vibration-free operation.



## ISOCIDE™ Antimicrobial Powder-Coating



All exterior painted surfaces are powder-coated with Esco ISOCIDE™, an antimicrobial inhibitor to minimize contamination. ISOCIDE™ is integrated into the coating substrate and cannot be washed out by repeated cleaning. Performance results are available upon request. Contact Esco or your Esco Sales Representative for details.

### Other Options and Accessories

- Electrical outlets
- All stainless steel construction
- UV lamp
- IV bar, with hooks
- Sharps disposal system
- Cleaning accessories
- Alarm package
- Exhaust carbon filter
- Thimble exhaust collar
- Perforated shelf to increase work zone space

- Particle Counts (Air Cleanliness Tests) verify air cleanliness in accordance with ISO 14644-1 criteria for both the main chamber and pass-through.
- Product Ingress and Egress Tests determine if the work zone can maintain ISO Class 5, during material transfers without the need to wait for purging time during the transfer process, when used outside an ISO Class 7 cleanroom (USP <797>).

- Recovery Time Test determines the amount of time the main chamber takes to recover to ISO Class 5 after an event such as a full window opening or large scale contamination.
- Gauntlet Breach Test determines product protection in case of a glove failure.
- Operator Comfort Tests include noise, light, and vibration.


### Validated Performance

Comprehensive design qualification and factory acceptance tests are performed on the Esco Streamline® Closed - Restricted Access Barrier System.

- Filter Leak Tests verify the integrity of the HEPA filters as-installed.
- Downflow Velocity Tests verify adequate laminar air flow velocities and air change rates in the two chambers.
- Dynamic Pressure Test determines if main and pass-through chambers pressures are adequate to aid in providing separation between the work zone and the ambient environment. Glove-pulls are simulated to ensure differential pressure is maintained during actual operation.




## Model SLC-RABS, Closed - Restricted Access Barrier System (Recirculating) Technical Specifications



**SLC-RABS-4\_- (2 Gloves)**

- |  |   |  |
|--|---|--|
| 1. Esco Sentinel™ microprocessor control system  | 6. Hydraulic height adjustable base stand with casters (optional) | 12. Exhaust fan                              |
| 2. Hinged front window   | 7. Sharps / garbage disposal system (optional)                    | 13. Main fan                                 |
| 3. Oval glove ports  | 8. Exhaust HEPA filter  | 14. Downflow HEPA filter                     |
| 4. Mechanical interlock  | 9. Intake HEPA filter   | 15. UV lamp retrofit kit provision           |
| 5. Electrical outlet retrofit kit provision (2 single outlet on the right side of work area) | 10. Exhaust collar  | 16. Staggered IV bar mounts                  |
|  | 11. Pre-filter  | 17. Pass-through inner door vertical sliding |
|  |   | 18. Removable paper catch                    |





**Model SLC-RABS-6\_ (3 Gloves)**

- |   |  |
|---|--|
| 1. Esco Sentinel™ microprocessor control system                   | 6. Pass-through, hinged outer door   |
| 2. Hinged front window  | 7. Electrical outlet Retrofit Kit provision (2 single outlet on the right side of work area) |
| 3. Oval glove ports   | 8. Exhaust HEPA filter   |
| 4. Hydraulic height adjustable base stand with casters (optional) | 9. Intake HEPA filter  |
| 5. Sharps / garbage disposal system (optional)                    |  |

## GENERAL SPECIFICATIONS

### Closed - Restricted Access Barrier System (Recirculating)

GENERAL SPECIFICATIONS Closed - Restricted Access Barrier System (Recirculating)		SLC-RABS-4N-_-	SLC-RABS-4P-_-	SLC-RABS-6N-_-	SLC-RABS-6P-_-
Nominal Size		1.2 meters (4')		1.8 meters (6')	
External Dimensions (W x D x H)	Witout Base Stand	1340 x 820 x 1320 mm (52.8" x 32.3" x 51.9")		1950 x 820 x 1320 mm (76.8" x 32.3" x 51.9")	
	With Base Stand (Min)	1522 x 820 x 1995 mm (59.9" x 32.3" x 78.5")		2132 x 820 x 1995 mm (83.9" x 32.3" x 78.5")	
	With Base Stand (Max)	1522 x 820 x 2250 (59.9" x 32.3" x 88.6")		2132 x 820 x 2250 mm (83.9" x 32.3" x 88.6")	
Main Chamber Work Zone (W x D x H)		840 x 610 x 670 mm (33.1" x 24.0" x 26.4")		1450 x 610 x 670 mm (57.1" x 24.0" x 26.4")	
Pass Through (W x D x H)		355 x 610 x 670 mm (13.9" x 24.0" x 26.4")		355 x 610 x 670 mm (13.9" x 24.0" x 26.4")	
Work Zone and Interchange Chamber Performance		ISO Class 5 (Class 1, Federal Standard 209E)			
Inlet Filter Type		80% efficienct pre-filters			
Downflow and Exhaust Filter Type		HEPA filter with integral metal guards and filter frame gaskets; fully compliant with EN 1822 (H14) and IEST-RP-CC001.3 requirements (each cabinet has individual downflow, exhaust filters and inlet filters).			
Typical Filter Efficiency		>99.995% for particle size between 0.1 to 0.3 micron			
Fluorescent Lamp Intensity		> 950 Lux (>88 foot candles)			
RABS Construction	Main Body	1.2 mm (0.05") 18 gauge electro-galvanized steel with white oven-baked epoxy-polyester antimicrobial powder-coated finish			
	Work Tray	1.5 mm (0.06") 16 gauge stainless steel, type 304, with 4B finish			
	Side Walls	1.2 mm (0.05") 18 gauge stainless steel, type 304, with 4B finish			
Electrical	220-240V, AC, 50Hz, 1Ø	SLC-RABS-4N1-_-	SLC-RABS-4P1-_-	SLC-RABS-6N1-_-	SLC-RABS-6P1-_-
	Cabinet Full Load Amps (FLA)	2.1 A	2 A	2.5 A	2 A
	Optional Outlets FLA	5 A	5 A	5 A	5 A
	Cabinet Nominal Power	295 W	301 W	440 W	345 W
	Cabinet BTU	1007	1027	1501	1177
	110-120V, AC, 60Hz, 1Ø	SLC-RABS-4N2-_-	SLC-RABS-4P2-_-	SLC-RABS-6N2-_-	SLC-RABS-6P2-_-
	Cabinet Full Load Amps (FLA)	6 A	4 A	8.2 A	7 A
	Optional Outlets FLA	5 A	5 A	5 A	5 A
	Cabinet Nominal Power	410 W	264 W	600 W	456 W
	Cabinet BTU	1399	901	2047	1556
	220-240V, AC, 60Hz, 1Ø	SLC-RABS-4N3-_-	SLC-RABS-4P3-_-	SLC-RABS-6N3-_-	SLC-RABS-6P3-_-
	Cabinet Full Load Amps (FLA)	2.1 A	2 A	2.5 A	2 A
	Optional Outlets FLA	5 A	5 A	5 A	5 A
	Cabinet Nominal Power	295 W	301 W	440 W	345 W
	Cabinet BTU	1007	1027	1501	1177
Shipping Dimensions, Maximum (W x D x H)		1590 x 990 x 2210 mm (62.6" x 39.0" x 87.0")		2150 x 950 x 2210 (84.6" x 37.4" x 87.0")	
Shipping Volume, Maximum*		3.48 m³ (122.9 cu.ft)		4.51 m³ (159.3 cu.ft)	

\* SLC-RABS only; excludes optional stand.

\*\* Cabinet and GFCI outlet operate on a single power cord.

#### Airflow Volume of Negative Pressure SLC-RABS (Recirculating)

	SLC-RABS-4N-_-	SLC-RABS-6N-_-
Required Exhaust with Optional Hard Ducting	190 m³/h (112 cfm)	286 m³/h (168 cfm)
Static Pressure for Optional Hard Ducting	27 Pa/0.10 in H <sub>2</sub> O	30 Pa/0.12 in H <sub>2</sub> O

\*\* If ordering RABS with sharps provisions, order the following to complete the selection.

Only **2 sharps containers** can be mounted per unit..

#### Sharps Disposal Containers

5170224	Sharps Disposal Container Complete With Mounting Base - 5.0qt (10.5" x 7.5"x 18")
---------	---

Contact Esco Sales Representative for more information.

## SAFE GLOVE CHANGE PROCEDURE: REPLACING DISPOSABLE GLOVES

.Safe change design system allows glove change at the middle of a process or when the equipment is in operation



**1** Pull the glove / sleeve outside the work zone. Check the material integrity of the two items.



**2** Fold the fingers of the gloves and move it towards the work zone to ensure containment during replacement procedures.



**3** Remove the outer O-ring from the cuff rings. This elastic ring is used to seal the gloves and sleeves together; preventing operator exposure.



**4** Remove the second O-ring towards the sleeves to easily remove the gloves at a later stage.



**5** Carefully roll the open end of the old glove from the middle groove to the outer groove of the cuff rings. Do not completely remove the glove to prevent exposure risk.



**6** Take the new glove and attach it to the last groove of the cuff ring. Ensure that the thumb is positioned at the top.



**7** Install the O-ring nearest the sleeves over the new gloves. This will tightly fasten the new gloves to the cuff rings while removing the old one.



**8** Verify that the thumb of the new glove is positioned on top. Afterwards, carefully loosen the old glove from the outer groove.



**9** Place the other O-ring back and position it on the outer groove of the cuff ring. This will fasten the new gloves with the sleeves.



**10** Put back the glove and sleeve into the work zone to properly discard the used glove without contaminating the outside environment.



**11** Working with the adjacent gloved hand, carefully remove the old glove and properly dispose of it inside.




**12** The procedure is now complete. Strict compliance to the process guarantees prevention from cross-contamination.



# ESCO GLOBAL NETWORK

## 42 Locations In 21 Countries All Over The World



- Global Offices
- Joint Ventures
- Licensee
- Distributors
- Factories
- R&D Centers
- Regional Distribution Centers



Air Shower  
Aseptic Containment Isolator (ACTI)  
Ceiling Laminar Airflow Units  
Cleanroom Transfer Hatch  
Containment Barrier Isolator (CBI)  
Downflow Booth (DFB)  
Dynamic Floor Label Hatch  
Dynamic Pass Box  
Evidence Drying Cabinet  
Garment Storage Cabinet  
General Processing Platform Isolator (GPPI)  
Laminar Flow Horizontal Trolley  
Laminar Flow Straddle Units, Single and Double  
Laminar Flow Vertical Trolley  
Pass Box  
Soft Wall Cleanroom  
Sputum Booth  
Ventilated Balance Enclosure (VBE)  
Weighing and Dispensing Containment Isolator (WDCI)

Since 1978, Esco has emerged as a leader in the development of controlled environment, laboratory and pharmaceutical equipment solutions. Products sold in more than 100 countries include biological safety cabinets, fume hoods, ductless fume hoods, laminar flow clean benches, animal containment workstations, cytotoxic cabinets, hospital pharmacy isolators, and PCR cabinets and instrumentation. With the most extensive product line in the industry, Esco has passed more tests, in more languages, for more certifications, throughout more countries than any biosafety cabinet manufacturer in the world. Esco remains dedicated to delivering innovative solutions for the clinical, life science, research and industrial laboratory community. [www.escoglobal.com](http://www.escoglobal.com).

# ESCO

PHARMA®

### Esco Pharma

21 Changi South Street 1 Singapore 486777 • Tel: +65 65420833

Fax: +65 65426920 • Email: [csis.pharma@escoglobal.com](mailto:csis.pharma@escoglobal.com)

### Esco Technologies, Inc.

2512 Metropolitan Drive, Suite 120 B

Feasterville- Trevose, PA 19053-6738

Tel: 215 322 2155 • Email: [eti.pharma@escoglobal.com](mailto:eti.pharma@escoglobal.com)

### Esco Gb Ltd

Unit 2 R-evolution @ Gateway 36, Kestrel Way, Barnsley, S70 5SZ

Tel: +44 (0) 1226 360 799 • Email: [egb.pharma@escoglobal.com](mailto:egb.pharma@escoglobal.com)

**Esco Global Offices:** Bangladesh | China | Denmark | Germany | Hong Kong | Indonesia | Italy | Lithuania | Malaysia | Myanmar | Philippines | Russia | Singapore | South Africa | South Korea | Taiwan | Thailand | UAE | UK | USA | Vietnam

