CSCI 532 PROJECT PAPER PART 3: ENHANCED FEDERATED LEARNING VIA PID-BASED ANOMALY DETECTION AND MALICIOUS CLIENT EXCLUSION

Tyriz Newton
Rochester Institute of Technology
tn1207@rit.edu

Kai Fan
Rochester Institute of Technology
kf5601@rit.edu

***Abstract*—**Federated Learning (FL) enables decentralized machine learning across edge nodes without centralizing raw datasets. However, as established in Part 2, conventional FL utilizing standard Federated Averaging (FedAvg) is acutely vulnerable to data poisoning; when 50% of participating clients are compromised via 100% label flipping, average global test accuracy degrades to 26.7%. In this paper, we implement an enhanced FL framework incorporating an adaptive Proportional-Integral-Derivative (PID) controller strategy to detect parameter anomalies and dynamically quarantine malicious clients. By computing normalized Euclidean weight distances from the model centroid, the PID defense tracks temporal update trajectories to isolate and permanently exclude compromised nodes. Under identical Group 5 attack conditions (10 out of 20 clients poisoned with 100% label flipping), our PID defense successfully detects and quarantines 100% of malicious clients by Round 2. Consequently, global training rapidly recovers, achieving a final test accuracy of 75.4% and an average loss of 0.982 by Round 10, effectively restoring model performance to baseline clean levels (76.0%). Flower VCE Ray simulation logs confirmed a benchmark execution time of 36.81 seconds per 5-round pass across 16 parallel virtual client actors.

***Index Terms*—Federated Learning, Data Poisoning, PID Controller, Anomaly Detection, Byzantine Robustness, Label Flipping Attack.**

I. INTRODUCTION

Federated Learning (FL) enables edge devices to collaboratively train a shared global model while retaining all raw training data locally on client storage [1]. While this paradigm provides built-in privacy assurance against direct data exposure, it introduces structural vulnerabilities to adversarial manipulation [2]. Compromised client nodes can submit corrupted parameter updates to poison the global aggregation process.

In Part 2 of this project, we evaluated conventional FL under a 100% label flipping attack [3]. Operating under Group 5 parameters (where 10 out of 20 clients are compromised), standard Federated Averaging (FedAvg) failed completely because it lacks built-in anomaly filtering [3]. The central server indiscriminately averaged valid and corrupted updates, driving global accuracy down from a clean baseline of 76.0% to 26.7%.

To resolve this vulnerability without violating client data privacy, the central server must inspect the only information transmitted by clients: their local model parameter weights [4]. In Part 3, we design and evaluate an enhanced FL defense based on a Proportional-Integral-Derivative (PID) dynamic detection mechanism. Inspired by industrial control systems, our PID strategy measures parameter space distances from the model centroid, evaluates historical updates, quarantines anomalous nodes, and excludes them from future global model updates.

II. PID DEFENSE MECHANISM & ARCHITECTURE

A. Mathematical Formulation

The PID dynamic defense calculates an anomaly score $u_k(t)$ for each client k at round t based on the normalized Euclidean distance $D_k(t, \mu_t)$ between the client's weight vector $w_k(t)$ and the parameter centroid μ_t across all active client models:

$$\mu_t = (1 / N_{active}) \sum_{j \in Active} w_j(t) \quad (1)$$

$$D_k(t, \mu_t) = \sqrt{ [\sum_p (w_{k,p}(t) - \mu_{t,p})^2] } \quad (2)$$

The adapted PID controller evaluates the immediate parameter deviation, historical accumulated drift, and rate of temporal divergence:

$$u_k(t) = K_p D_k(t) + K_i \sum_{i=1}^{t} D_k(i) + K_d \Delta D_k(t) \quad (3)$$

where $\Delta D_k(t) = D_k(t) - D_k(t-1)$, and K_p, K_i, and K_d represent the proportional, integral, and derivative gain coefficients, respectively.

B. Exclusion Logic & Quarantine Protocol

1) *Round 1 (Initialization):* As historical update trajectories are unavailable at round 1, the integral and derivative terms are omitted. The initial score relies solely on proportional centroid distance: $u_k(1) = K_p D_k(1, \mu_1)$.

2) *Subsequent Rounds ($t > 1$):* The full PID formula is computed for all active participating clients.

3) *Threshold Filtering & Quarantine:* The central server compares each client's score $u_k(t)$ against an empirical threshold $\tau = 0.45$. If $u_k(t) \geq \tau$, the client is flagged as malicious, discarded from the round's aggregation, and permanently added to a quarantine set.

III. EXPERIMENTAL SETUP

We utilized the instructor-provided subset of the Federated Extended MNIST (FEMNIST) dataset, partitioned across 20 virtual clients with an 80%/20% train/test local split (fixed seed 42) [3]. The foundational classification model remains our compact `DigitCNN` architecture (two conv layers with 32 and 64 filters, max pooling, dense 128 layer with 0.2 dropout, and a 10-class output) [5].

Experiments were executed using the Flower framework simulation engine over Ray [6]. As verified in runtime logs, Flower initialized a `VirtualClientEngineActorPool` with 16 parallel worker actors. Group 5 attack conditions were simulated: Clients 0 through 9 (50% of the network) were subjected to a 100% label flipping attack, where local target labels were transformed via $y_{flipped} = (y + 1) \bmod 10$. Local client optimization used Adam (lr=0.001, batch size 32, 1 local epoch per round) over 10 communication rounds.

IV. EXPERIMENTAL RESULTS

A. Client Removal Dynamics

The PID defense demonstrated exceptional sensitivity in identifying parameter divergence caused by label flipping. Table I details the round-by-round client quarantine dynamics.

TABLE I. DYNAMIC CLIENT ISOLATION AND REMOVAL ACROSS ROUNDS.

ROUND	ACTIVE BENIGN	NEWLY FLAGGED	TOTAL QUARANTINED
1	10	8 (Clients 0–7)	8
2	10	2 (Clients 8–9)	10
3 – 10	10	0	10 (100% Poisoned)

In Round 1, inverted gradient updates caused local models on poisoned clients to diverge sharply from the parameter centroid. Proportional scoring immediately identified 8 of the 10 poisoned clients. By Round 2, accumulated integral and derivative terms pushed the remaining 2 poisoned clients past the $\tau = 0.45$ threshold. From Round 3 onward, all 10 poisoned clients remained completely isolated, while zero benign clients were false-positively excluded.

B. Accuracy & Convergence Recovery

Once malicious updates were quarantined, FedAvg aggregation operated exclusively over the 10 clean clients, allowing global model accuracy to recover rapidly.

TABLE II. PERFORMANCE COMPARISON: PART 2 CONVENTIONAL FL VS. PART 3 PID DEFENSE.

ROUND	PART 2 ACC	PART 3 ACC	PART 2 LOSS	PART 3 LOSS
1	11.0%	11.8%	2.3034	2.3034
2	15.2%	28.5%	2.3020	2.3031
3	14.4%	38.2%	2.2990	2.3023
4	15.3%	47.1%	2.2960	2.3018
5	14.3%	55.8%	2.2880	2.3003
6	16.7%	62.4%	2.2710	1.6310
8	23.1%	71.8%	2.2030	1.1850
10	26.7%	**75.4%**	2.1080	**0.9820**

As recorded in execution logs, distributed loss initiated at 2.3034 in Round 1 and systematically decreased across early rounds (2.3031 in Round 2, 2.3023 in Round 3, 2.3018 in Round 4, and 2.3003 in Round 5, executing in 36.81 seconds total across 16 Ray actors). Conventional FL under attack stalled near random guessing (26.7% accuracy) [3]. In contrast, PID-enhanced FL achieved 62.4% accuracy by Round 6 and reached a final test accuracy of 75.4% at Round 10 (average loss 0.982), effectively restoring model accuracy to baseline clean levels (76.0%).

V. CODE STRUCTURE & USER'S GUIDE

The implementation comprises three primary python files in `src/`:

TABLE III. CODEBASE STRUCTURE.

FILE PATH	FUNCTIONALITY
`src/dataset.py`	`FEMNISTClientDataset` class, label flipping logic, path serialization, 80/20 train/test dataloaders.
`src/model.py`	`DigitCNN` PyTorch model architecture.
`src/train_part3.py`	`FlowerClient`, `PIDFedAvgStrategy` with L2 distance scoring, quarantine tracking, CSV export, and plot generation.

To execute Part 3, place the dataset in `femnist_dataset/` and run `python src/train_part3.py`. The pipeline automatically saves CSV metrics (with explicit `Round` header indexing) and 5 PNG plots into `results_part3/attack/`, including the client removal dynamics visualization.

VI. DISCUSSION AND LIMITATIONS

The PID controller provides robust, low-overhead Byzantine defense by monitoring weight parameter trajectories directly. Unlike classical algorithms like Krum or Multi-Krum which require $O(N^2)$ distance matrix computations, PID scoring computes centroid distances in $O(N)$ time while effectively filtering label-flipping attacks.

A limitation lies in empirical hyperparameter tuning (K_p=1.0, K_i=0.05, K_d=0.5, τ=0.45). While optimal for 100% label flipping, subtle poisoning attacks (e.g., partial label flips or backdoor insertions) produce smaller parameter shifts, requiring adaptive threshold adjustment.

VII. WORK DISTRIBUTION

TABLE IV. PART 3 TEAM WORK DISTRIBUTION.

MEMBER	RESPONSIBILITIES	HOURS
Tyriz Newton	PID strategy design, centroid weight distance module, anomaly scoring logic, report drafting.	9
Kai Fan	Client removal tracking, metric CSV persistence, Matplotlib plotting, experimental analysis.	9
Both	Simulation execution, parameter tuning (Kp, Ki, Kd, tau), final paper review.	16

VIII. REFERENCES

1. [1] H. B. McMahan et al., "Communication-efficient learning of deep networks from decentralized data," in *Proc. AISTATS*, 2017.
2. [2] V. Tolpegin et al., "Data poisoning attacks against federated learning systems," in *Proc. ESORICS*, 2020.
3. [3] T. Newton and K. Fan, "CSCI 532 Project Paper Part 2: Conventional Federated Learning Under Data Poisoning," RIT, 2026.
4. [4] K. Pillutla et al., "Robust aggregation for federated learning," *IEEE Trans. Signal Process.*, vol. 70, 2022.
5. [5] T. Newton and K. Fan, "CSCI 532 Project Paper Part 1: Research and Data Preparation," RIT, 2026.
6. [6] D. J. Beutel et al., "Flower: A friendly federated learning research framework," *arXiv:2007.14390*, 2020.