

Graph2D Library --- wxWidgets ---

Generated by Doxygen 1.8.19

1 Plot10 & Advanced Graphing II	1
1.0.0.1 How to build the library:	1
1.0.0.2 Using the library:	1
1.0.0.3 Hardcopies	1
2 Compilersettings for Windows	3
2.0.1 Setup of the Windows IDE	3
2.0.1.1 MingGW for Windows 32bit and 64bit	3
2.0.1.2 Settings for own Applications	3
3 Compilersettings for Linux	5
3.0.1 tbd.	5
4 Data Type Index	7
4.1 Class Hierarchy	7
5 Data Type Index	9
5.1 Data Types List	9
6 File Index	11
6.1 File List	11
7 Data Type Documentation	13
7.1 cTCScanvas Class Reference	13
7.1.1 Detailed Description	13
7.1.2 Constructor & Destructor Documentation	14
7.1.2.1 cTCScanvas()	14
7.1.2.2 ~cTCScanvas()	14
7.1.3 Member Data Documentation	14
7.1.3.1 AG2Sav	14
7.1.3.2 ClippingNotActive	14
7.1.3.3 DefaultBckColSav	14
7.1.3.4 DefaultLinColSav	15
7.1.3.5 DefaultTxtColSav	15
7.1.3.6 HardcopyFileSav	15
7.1.3.7 ID_TCSframe	15
7.1.3.8 ID_TCspanel	15
7.1.3.9 ID_TCSstatus	15
7.1.3.10 logWindow	16
7.1.3.11 sect0Sav	16
7.1.3.12 TCSbrush	16
7.1.3.13 TCSfont	16
7.1.3.14 TCSframe	16
7.1.3.15 TCSmouseButtonDown	16

7.1.3.16 TCSmouseX	17
7.1.3.17 TCSmouseY	17
7.1.3.18 TCSPanel	17
7.1.3.19 TCSPanelKeyPressed	17
7.1.3.20 TCSPen	17
7.1.3.21 TCSstatusBar	17
7.1.3.22 TekSav	18
7.1.3.23 xTCSJournal	18
7.2 TKTRNX Struct Reference	18
7.2.1 Detailed Description	19
7.2.2 Member Data Documentation	19
7.2.2.1 iBckCol	19
7.2.2.2 iLinCol	19
7.2.2.3 iTxtCol	19
7.2.2.4 kbeamx	19
7.2.2.5 kbeamy	19
7.2.2.6 khomey	20
7.2.2.7 khorsz	20
7.2.2.8 kitalc	20
7.2.2.9 klmrgn	20
7.2.2.10 kmaxsx	20
7.2.2.11 kmaxsy	20
7.2.2.12 kminsx	21
7.2.2.13 kminsy	21
7.2.2.14 krmrgn	21
7.2.2.15 kScrX	21
7.2.2.16 kScrY	21
7.2.2.17 ksizef	21
7.2.2.18 kStCol	22
7.2.2.19 kversz	22
7.2.2.20 tmaxvx	22
7.2.2.21 tmaxvy	22
7.2.2.22 tminvx	22
7.2.2.23 tminvy	22
7.2.2.24 trcosf	23
7.2.2.25 trscal	23
7.2.2.26 trsinf	23
7.2.2.27 xfac	23
7.2.2.28 xlog	23
7.2.2.29 yfac	23
7.2.2.30 ylog	24
7.3 wxTCSapp Class Reference	24

7.3.1 Detailed Description	24
7.3.2 Member Function Documentation	24
7.3.2.1 OnIdle()	24
7.3.2.2 OnInit()	25
7.4 xJournalEntry_typ Struct Reference	25
7.4.1 Detailed Description	25
7.4.2 Member Data Documentation	25
7.4.2.1 action	25
7.4.2.2 i1	25
7.4.2.3 i2	26
7.4.2.4 next	26
7.4.2.5 previous	26
8 File Documentation	27
8.1 AG2.for File Reference	27
8.1.1 Detailed Description	29
8.1.2 Function/Subroutine Documentation	30
8.1.2.1 ag2lev()	30
8.1.2.2 alfsetc()	30
8.1.2.3 bar()	30
8.1.2.4 binitt()	30
8.1.2.5 bsyms()	30
8.1.2.6 calcon()	31
8.1.2.7 calpnt()	31
8.1.2.8 check()	31
8.1.2.9 cmnmx()	31
8.1.2.10 coptim()	31
8.1.2.11 cplot()	32
8.1.2.12 datget()	32
8.1.2.13 dinitx()	32
8.1.2.14 dinity()	32
8.1.2.15 dlimx()	32
8.1.2.16 dlimy()	33
8.1.2.17 dsplay()	33
8.1.2.18 eformc()	33
8.1.2.19 esplit()	33
8.1.2.20 expoutc()	33
8.1.2.21 fformc()	34
8.1.2.22 filbox()	34
8.1.2.23 findge()	34
8.1.2.24 findle()	34
8.1.2.25 fonlyc()	35

8.1.2.26 frame()	35
8.1.2.27 gline()	35
8.1.2.28 grid()	35
8.1.2.29 hbarst()	35
8.1.2.30 iformc()	36
8.1.2.31 infin()	36
8.1.2.32 iother()	36
8.1.2.33 iubgc()	36
8.1.2.34 justerc()	36
8.1.2.35 keyset()	37
8.1.2.36 label()	37
8.1.2.37 leap()	37
8.1.2.38 line()	37
8.1.2.39 locge()	37
8.1.2.40 locle()	38
8.1.2.41 logtix()	38
8.1.2.42 loptim()	38
8.1.2.43 lwidth()	38
8.1.2.44 mnmx()	38
8.1.2.45 monpos()	39
8.1.2.46 notatec()	39
8.1.2.47 npts()	39
8.1.2.48 numsetc()	39
8.1.2.49 optim()	39
8.1.2.50 oubgc()	40
8.1.2.51 place()	40
8.1.2.52 remlab()	40
8.1.2.53 rescom()	40
8.1.2.54 rgchek()	40
8.1.2.55 roundd()	41
8.1.2.56 roundu()	41
8.1.2.57 savcom()	41
8.1.2.58 setwin()	41
8.1.2.59 sizel()	41
8.1.2.60 sizes()	42
8.1.2.61 slimx()	42
8.1.2.62 slimy()	42
8.1.2.63 spread()	42
8.1.2.64 stepl()	42
8.1.2.65 steps()	43
8.1.2.66 symb1()	43
8.1.2.67 symout()	43

8.1.2.68 teksym()	43
8.1.2.69 teksym1()	43
8.1.2.70 tset()	44
8.1.2.71 tset2()	44
8.1.2.72 typck()	44
8.1.2.73 vbarst()	44
8.1.2.74 vlablc()	44
8.1.2.75 width()	45
8.1.2.76 xden()	45
8.1.2.77 xetyp()	45
8.1.2.78 xfrm()	45
8.1.2.79 xlab()	45
8.1.2.80 xlen()	45
8.1.2.81 xloc()	46
8.1.2.82 xloctp()	46
8.1.2.83 xmfrm()	46
8.1.2.84 xmtcs()	46
8.1.2.85 xneat()	46
8.1.2.86 xtics()	46
8.1.2.87 xtype()	47
8.1.2.88 xwidth()	47
8.1.2.89 xzero()	47
8.1.2.90 yden()	47
8.1.2.91 yetyp()	47
8.1.2.92 yfrm()	47
8.1.2.93 ylab()	48
8.1.2.94 ylen()	48
8.1.2.95 yloc()	48
8.1.2.96 ylocrt()	48
8.1.2.97 ymdyd()	48
8.1.2.98 ymfrm()	49
8.1.2.99 ymtcs()	49
8.1.2.100 yneat()	49
8.1.2.101 ytics()	49
8.1.2.102 ytype()	49
8.1.2.103 ywidth()	49
8.1.2.104 yzero()	50
8.2 AG2.for	50
8.3 AG2Holerith.for File Reference	85
8.3.1 Detailed Description	86
8.3.2 Function/Subroutine Documentation	86
8.3.2.1 alfset()	86

8.3.2.2 comdmp()	86
8.3.2.3 comget()	87
8.3.2.4 comset()	87
8.3.2.5 eform()	87
8.3.2.6 expout()	87
8.3.2.7 fform()	87
8.3.2.8 fonly()	88
8.3.2.9 hlabel()	88
8.3.2.10 hstrin()	88
8.3.2.11 ibasec()	88
8.3.2.12 ibasex()	88
8.3.2.13 ibasey()	89
8.3.2.14 iform()	89
8.3.2.15 juster()	89
8.3.2.16 notate()	89
8.3.2.17 numset()	90
8.3.2.18 vlabel()	90
8.3.2.19 vstrin()	90
8.4 AG2Holerith.for	90
8.5 AG2uline.for File Reference	95
8.5.1 Detailed Description	96
8.5.2 Function/Subroutine Documentation	96
8.5.2.1 uline()	96
8.6 AG2uline.for	96
8.7 AG2umnmx.for File Reference	96
8.7.1 Detailed Description	96
8.7.2 Function/Subroutine Documentation	97
8.7.2.1 umnmx()	97
8.8 AG2umnmx.for	97
8.9 AG2upoint.for File Reference	97
8.9.1 Detailed Description	97
8.9.2 Function/Subroutine Documentation	97
8.9.2.1 upoint()	98
8.10 AG2upoint.for	98
8.11 AG2users.for File Reference	98
8.11.1 Detailed Description	98
8.11.2 Function/Subroutine Documentation	98
8.11.2.1 users()	98
8.12 AG2users.for	99
8.13 AG2useset.for File Reference	99
8.13.1 Detailed Description	99
8.13.2 Function/Subroutine Documentation	99

8.13.2.1 <code>usetset()</code>	99
8.14 <code>AG2usetset.for</code>	99
8.15 <code>AG2usetsetC.for</code> File Reference	100
8.15.1 Detailed Description	100
8.15.2 Function/Subroutine Documentation	100
8.15.2.1 <code>usetsetc()</code>	100
8.16 <code>AG2usetsetC.for</code>	100
8.17 <code>AG2UsrcSoftek.for</code> File Reference	101
8.17.1 Detailed Description	101
8.17.2 Function/Subroutine Documentation	101
8.17.2.1 <code>softek()</code>	101
8.18 <code>AG2UsrcSoftek.for</code>	101
8.19 <code>G2dAG2.fd</code> File Reference	101
8.19.1 Detailed Description	102
8.20 <code>G2dAG2.fd</code>	102
8.21 <code>GetHDC.for</code> File Reference	103
8.21.1 Detailed Description	103
8.21.2 Function/Subroutine Documentation	103
8.21.2.1 <code>gethdc()</code>	103
8.22 <code>GetHDC.for</code>	104
8.23 <code>Mainpage.dox</code> File Reference	105
8.24 <code>PlotHDC.f03</code> File Reference	105
8.24.1 Detailed Description	105
8.24.2 Function/Subroutine Documentation	106
8.24.2.1 <code>plothdc()</code>	106
8.25 <code>PlotHDC.f03</code>	106
8.26 <code>Strings.for</code> File Reference	107
8.26.1 Detailed Description	107
8.26.2 Function/Subroutine Documentation	107
8.26.2.1 <code>istringlen()</code>	107
8.26.2.2 <code>itrimlen()</code>	108
8.26.2.3 <code>printstring()</code>	108
8.26.2.4 <code>substitute()</code>	108
8.27 <code>Strings.for</code>	108
8.28 <code>TCS.for</code> File Reference	110
8.28.1 Detailed Description	111
8.28.2 Function/Subroutine Documentation	111
8.28.2.1 <code>ancho()</code>	111
8.28.2.2 <code>anstr()</code>	112
8.28.2.3 <code>baksp()</code>	112
8.28.2.4 <code>cartn()</code>	112
8.28.2.5 <code>dasha()</code>	112

8.28.2.6 dashr()	112
8.28.2.7 drawa()	113
8.28.2.8 drawr()	113
8.28.2.9 dwindo()	113
8.28.2.10 genflg()	113
8.28.2.11 home()	113
8.28.2.12 linef()	114
8.28.2.13 linhgt()	114
8.28.2.14 lintrn()	114
8.28.2.15 linwdt()	114
8.28.2.16 logtrn()	114
8.28.2.17 movea()	114
8.28.2.18 mover()	115
8.28.2.19 newlin()	115
8.28.2.20 newpag()	115
8.28.2.21 pointa()	115
8.28.2.22 pointr()	115
8.28.2.23 rel2ab()	116
8.28.2.24 rescal()	116
8.28.2.25 revcot()	116
8.28.2.26 rrotat()	116
8.28.2.27 rscale()	116
8.28.2.28 seetrm()	117
8.28.2.29 seetrn()	117
8.28.2.30 setmrg()	117
8.28.2.31 swindo()	117
8.28.2.32 twindo()	117
8.28.2.33 vcursr()	118
8.28.2.34 vwindo()	118
8.28.2.35 wincot()	118
8.29 TCS.for	118
8.30 TCSdrWXcpp.cpp File Reference	124
8.30.1 Detailed Description	126
8.30.2 Macro Definition Documentation	127
8.30.2.1 MAX_COLOR_INDEX	127
8.30.2.2 TMPSTRLEN	127
8.30.2.3 wxDEBUG_LEVEL	127
8.30.3 Typedef Documentation	127
8.30.3.1 ErrMsg	127
8.30.3.2 xJournalEntry_typ	127
8.30.4 Function Documentation	127
8.30.4.1 BCKCOL()	127

8.30.4.2 BELL()	127
8.30.4.3 CustomizeProgPar()	128
8.30.4.4 DBLSIZ()	128
8.30.4.5 DCURSR()	128
8.30.4.6 DEFAULTCOLOUR()	128
8.30.4.7 DRWABS()	128
8.30.4.8 DSHABS()	128
8.30.4.9 ERASE()	128
8.30.4.10 FINITT()	128
8.30.4.11 getCanvasID()	129
8.30.4.12 HDCOPY()	129
8.30.4.13 initt0()	129
8.30.4.14 initt1()	129
8.30.4.15 IOWAIT()	129
8.30.4.16 ITALIC()	129
8.30.4.17 ITALIR()	129
8.30.4.18 lib_movc3_()	129
8.30.4.19 LINCOL()	130
8.30.4.20 MOVABS()	130
8.30.4.21 NRMSIZ()	130
8.30.4.22 outgtext_()	130
8.30.4.23 outtext_()	130
8.30.4.24 PNTABS()	130
8.30.4.25 PresetProgPar()	130
8.30.4.26 RepaintBuffer()	130
8.30.4.27 RESTAT()	131
8.30.4.28 SVSTAT()	131
8.30.4.29 swind1_()	131
8.30.4.30 TCSGraphicError()	131
8.30.4.31 TINPUT()	131
8.30.4.32 TXTCOL()	131
8.30.4.33 winlbl0()	131
8.30.4.34 WINSELECT()	131
8.30.4.35 XMLreadProgPar()	132
8.30.5 Variable Documentation	132
8.30.5.1 ActiveCanvas	132
8.30.5.2 ActiveCanvasID	132
8.30.5.3 iHardcopyCount	132
8.30.5.4 OpenCanvases	132
8.30.5.5 szTCSErrorMsg	132
8.30.5.6 szTCSHardcopyFile	133
8.30.5.7 szTCSIniFile	133

8.30.5.8 szTCSsect0	133
8.30.5.9 szTCSstatWindowName	133
8.30.5.10 szTCSWindowName	133
8.30.5.11 TCSColorTable	133
8.30.5.12 TCSDefaultBckCol	133
8.30.5.13 TCSDefaultLinCol	133
8.30.5.14 TCSDefaultTxtCol	134
8.30.5.15 TCSErrorLev	134
8.30.5.16 TCWindowIniXrelpos	134
8.30.5.17 TCWindowIniXrelsiz	134
8.30.5.18 TCWindowIniYrelpos	134
8.30.5.19 TCWindowIniYrelsiz	134
8.31 TCSdrWXcpp.cpp	134
8.32 TCSdrWXcpp.hpp File Reference	154
8.32.1 Detailed Description	158
8.32.2 Macro Definition Documentation	158
8.32.2.1 ERR_EXIT	158
8.32.2.2 ERR_NOFNT	158
8.32.2.3 ERR_NOFNTFIL	158
8.32.2.4 ERR_UNKNAUDIO	158
8.32.2.5 ERR_UNKNGRAPHCARD	158
8.32.2.6 ERR_XMLOPEN	158
8.32.2.7 ERR_XMLPARSER	159
8.32.2.8 INIFILEXT	159
8.32.2.9 INIFILEXTTOKEN	159
8.32.2.10 MAX_HDCCOUNT	159
8.32.2.11 MAX_OPEN_CANVAS	159
8.32.2.12 MSG_HDCACT	159
8.32.2.13 MSG_MAXERRNO	159
8.32.2.14 MSG_NOMOUSE	159
8.32.2.15 MSG_USR	159
8.32.2.16 MSG_USR2	159
8.32.2.17 PROGDIRTOKEN	160
8.32.2.18 STAT_MAXROWS	160
8.32.2.19 TCS_FILE_NAMELEN	160
8.32.2.20 TCS_HDCFILE_NAME	160
8.32.2.21 TCS_INIDEF_BCKCOL	160
8.32.2.22 TCS_INIDEF_COPLCK	160
8.32.2.23 TCS_INIDEF_COPLCKL	160
8.32.2.24 TCS_INIDEF_COPMEM	160
8.32.2.25 TCS_INIDEF_COPMEML	160
8.32.2.26 TCS_INIDEF_EXIT	160

8.32.2.27 TCS_INIDEF_EXITL	161
8.32.2.28 TCS_INIDEF_HDCACT	161
8.32.2.29 TCS_INIDEF_HDCACTL	161
8.32.2.30 TCS_INIDEF_HDCOPN	161
8.32.2.31 TCS_INIDEF_HDCOPNL	161
8.32.2.32 TCS_INIDEF_HDCWRT	161
8.32.2.33 TCS_INIDEF_HDCWRTL	161
8.32.2.34 TCS_INIDEF_INI2	161
8.32.2.35 TCS_INIDEF_INI2L	161
8.32.2.36 TCS_INIDEF_JOUADD	161
8.32.2.37 TCS_INIDEF_JOUADDL	162
8.32.2.38 TCS_INIDEF_JOUCLR	162
8.32.2.39 TCS_INIDEF_JOUCLRL	162
8.32.2.40 TCS_INIDEF_JOUCREATE	162
8.32.2.41 TCS_INIDEF_JOUCREATEL	162
8.32.2.42 TCS_INIDEF_JOUMENTRY	162
8.32.2.43 TCS_INIDEF_JOUMENTRYL	162
8.32.2.44 TCS_INIDEF_JOUUNKWN	162
8.32.2.45 TCS_INIDEF_JOUUNKWNL	162
8.32.2.46 TCS_INIDEF_LINCOL	162
8.32.2.47 TCS_INIDEF_NOFNT	163
8.32.2.48 TCS_INIDEF_NOFNTFIL	163
8.32.2.49 TCS_INIDEF_NOFNTFILL	163
8.32.2.50 TCS_INIDEF_NOFNTL	163
8.32.2.51 TCS_INIDEF_STATPOSX	163
8.32.2.52 TCS_INIDEF_STATPOSY	163
8.32.2.53 TCS_INIDEF_STATSIZX	163
8.32.2.54 TCS_INIDEF_STATSIZY	163
8.32.2.55 TCS_INIDEF_TXTCOL	163
8.32.2.56 TCS_INIDEF_UNKNAUDIO	163
8.32.2.57 TCS_INIDEF_UNKNAUDIOL	164
8.32.2.58 TCS_INIDEF_UNKNGRAPHCARD	164
8.32.2.59 TCS_INIDEF_UNKNGRAPHCARDL	164
8.32.2.60 TCS_INIDEF_USR	164
8.32.2.61 TCS_INIDEF_USR2	164
8.32.2.62 TCS_INIDEF_USR2L	164
8.32.2.63 TCS_INIDEF_USRL	164
8.32.2.64 TCS_INIDEF_USRWRN	164
8.32.2.65 TCS_INIDEF_USRWRNL	164
8.32.2.66 TCS_INIDEF_WINPOSX	164
8.32.2.67 TCS_INIDEF_WINPOSY	165
8.32.2.68 TCS_INIDEF_WINSIZX	165

8.32.2.69 TCS_INIDEF_WINSIZY	165
8.32.2.70 TCS_INIDEF_XMLOPEN	165
8.32.2.71 TCS_INIDEF_XMLOPENL	165
8.32.2.72 TCS_INIDEF_XMLPARSER	165
8.32.2.73 TCS_INIDEF_XMLPARSERL	165
8.32.2.74 TCS_INIFILE_NAME	165
8.32.2.75 TCS_INISECT0	165
8.32.2.76 TCS_INISECT1	165
8.32.2.77 TCS_INISECT2	166
8.32.2.78 TCS_INISECT3	166
8.32.2.79 TCS_INIVAR_BCKCOL	166
8.32.2.80 TCS_INIVAR_COPLCK	166
8.32.2.81 TCS_INIVAR_COPLCKL	166
8.32.2.82 TCS_INIVAR_COPMEM	166
8.32.2.83 TCS_INIVAR_COPMEML	166
8.32.2.84 TCS_INIVAR_EXIT	166
8.32.2.85 TCS_INIVAR_EXITL	166
8.32.2.86 TCS_INIVAR_HDCACT	166
8.32.2.87 TCS_INIVAR_HDCACTL	167
8.32.2.88 TCS_INIVAR_HDCNAM	167
8.32.2.89 TCS_INIVAR_HDCOPN	167
8.32.2.90 TCS_INIVAR_HDCOPNL	167
8.32.2.91 TCS_INIVAR_HDCWRT	167
8.32.2.92 TCS_INIVAR_HDCWRTL	167
8.32.2.93 TCS_INIVAR_INI2	167
8.32.2.94 TCS_INIVAR_INI2L	167
8.32.2.95 TCS_INIVAR_JOUADD	167
8.32.2.96 TCS_INIVAR_JOUADDL	167
8.32.2.97 TCS_INIVAR_JOUCLR	168
8.32.2.98 TCS_INIVAR_JOUCLRL	168
8.32.2.99 TCS_INIVAR_JOUCREATE	168
8.32.2.100 TCS_INIVAR_JOUCREATEL	168
8.32.2.101 TCS_INIVAR_JOUMENTRY	168
8.32.2.102 TCS_INIVAR_JOUMENTRYL	168
8.32.2.103 TCS_INIVAR_JOUUNKWN	168
8.32.2.104 TCS_INIVAR_JOUUNKWNL	168
8.32.2.105 TCS_INIVAR_LINCOL	168
8.32.2.106 TCS_INIVAR_NOFNT	168
8.32.2.107 TCS_INIVAR_NOFNTFIL	169
8.32.2.108 TCS_INIVAR_NOFNTFILL	169
8.32.2.109 TCS_INIVAR_NOFNTL	169
8.32.2.110 TCS_INIVAR_STATNAM	169

8.32.2.111 TCS_INIVAR_STATPOSX	169
8.32.2.112 TCS_INIVAR_STATPOSY	169
8.32.2.113 TCS_INIVAR_STATSIZX	169
8.32.2.114 TCS_INIVAR_STATSIZY	169
8.32.2.115 TCS_INIVAR_TXTCOL	169
8.32.2.116 TCS_INIVAR_UNKNAUDIO	169
8.32.2.117 TCS_INIVAR_UNKNAUDIOL	170
8.32.2.118 TCS_INIVAR_UNKNGRAPHCARD	170
8.32.2.119 TCS_INIVAR_UNKNGRAPHCARDL	170
8.32.2.120 TCS_INIVAR_USR	170
8.32.2.121 TCS_INIVAR_USR2	170
8.32.2.122 TCS_INIVAR_USR2L	170
8.32.2.123 TCS_INIVAR_USRL	170
8.32.2.124 TCS_INIVAR_USRWRN	170
8.32.2.125 TCS_INIVAR_USRWRNL	170
8.32.2.126 TCS_INIVAR_WINNAM	170
8.32.2.127 TCS_INIVAR_WINPOSX	171
8.32.2.128 TCS_INIVAR_WINPOSY	171
8.32.2.129 TCS_INIVAR_WINSIZX	171
8.32.2.130 TCS_INIVAR_WINSIZY	171
8.32.2.131 TCS_INIVAR_XMLOPEN	171
8.32.2.132 TCS_INIVAR_XMLOPENL	171
8.32.2.133 TCS_INIVAR_XMLPARSER	171
8.32.2.134 TCS_INIVAR_XMLPARSERL	171
8.32.2.135 TCS_LINEWIDTH	171
8.32.2.136 TCS_MESSAGELEN	171
8.32.2.137 TCS_REL_CHR_HEIGHT	172
8.32.2.138 TCS_REL_CHR_SPACING	172
8.32.2.139 TCS_STATWINDOW_NAME	172
8.32.2.140 TCS_WINDOW_NAME	172
8.32.2.141 TCS_WINDOW_NAMELEN	172
8.32.2.142 TEK_XMAX	172
8.32.2.143 TEK_YMAX	172
8.32.2.144 WRN_COPYLOCK	172
8.32.2.145 WRN_COPYNOMEM	172
8.32.2.146 WRN_HDCFILOPN	172
8.32.2.147 WRN_HDCFILWRT	173
8.32.2.148 WRN_HDCINTERN	173
8.32.2.149 WRN_INI2	173
8.32.2.150 WRN_JOUADD	173
8.32.2.151 WRN_JOUCLR	173
8.32.2.152 WRN_JOUCREATE	173

8.32.2.153 WRN_JOENTRY	173
8.32.2.154 WRN_JOUUNKWN	173
8.32.2.155 WRN_NOMSG	173
8.32.2.156 WRN_USRPRESSANY	173
8.32.2.157 XACTION_ASCII	174
8.32.2.158 XACTION_BCKCOL	174
8.32.2.159 XACTION_CLIP	174
8.32.2.160 XACTION_CLIP1	174
8.32.2.161 XACTION_CLIP2	174
8.32.2.162 XACTION_DRWABS	174
8.32.2.163 XACTION_DSHABS	174
8.32.2.164 XACTION_DSHSTYLE	174
8.32.2.165 XACTION_ERASE	174
8.32.2.166 XACTION_FONTATTR	174
8.32.2.167 XACTION_GTEXT	175
8.32.2.168 XACTION_INITT	175
8.32.2.169 XACTION_LINCOL	175
8.32.2.170 XACTION_MOVABS	175
8.32.2.171 XACTION_NOOP	175
8.32.2.172 XACTION_PNTABS	175
8.32.2.173 XACTION_TXTCOL	175
8.33 TCSdrWXcpp.hpp	175
8.34 TCSdrWXfor.f08 File Reference	178
8.34.1 Detailed Description	178
8.34.2 Function/Subroutine Documentation	179
8.34.2.1 anmode()	179
8.34.2.2 csize()	179
8.34.2.3 drwrel()	179
8.34.2.4 dshrel()	179
8.34.2.5 graphicerror()	180
8.34.2.6 initt()	180
8.34.2.7 movrel()	180
8.34.2.8 pntrel()	180
8.34.2.9 seeloc()	180
8.34.2.10 statst()	180
8.34.2.11 tcslev()	180
8.34.2.12 toutpt()	180
8.34.2.13 toutst()	181
8.34.2.14 toutstc()	181
8.34.2.15 winlbl()	181
8.35 TCSdrWXfor.f08	181
8.36 Tktrnx.fd File Reference	184

8.36.1 Detailed Description	184
8.37 Tktrnx.fd	184
8.38 TKTRNX.hpp File Reference	185
8.38.1 Detailed Description	185
8.38.2 Variable Documentation	186
8.38.2.1 tktrnx_	186
8.39 TKTRNX.hpp	186
8.40 wxTCSmain.cpp File Reference	186
8.40.1 Detailed Description	186
8.40.2 Macro Definition Documentation	187
8.40.2.1 MainProgram	187
8.40.3 Function Documentation	187
8.40.3.1 _gfortran_set_args()	187
8.41 wxTCSmain.cpp	187
Index	189

Chapter 1

Plot10 & Advanced Graphing II

Graph2D is written in Fortran2008/FTN77 and ANSI C++11/C90. Compilation instructions are available for Windows (MinGW) under "Additional Information".

1.0.0.1 How to build the library:

After copying the source files by "\$getfiles.bat wx" into the /build subdirectory there are also the project files for CodeBlocks (Windows IDE) AND A LINUX BASHSCRIPT.

1.0.0.2 Using the library:

The main properties can be adjusted as follows:

- Initialization: By the WINLBL subroutine and/or *.xml files.
- Icons (Windows only): By linking a resource

1.0.0.3 Hardcopies

generate proprietary ASCII-journalfiles with the default extension *.hdc.

Chapter 2

Compiler settings for Windows

2.0.1 Setup of the Windows IDE

2.0.1.1 MingGW for Windows 32bit and 64bit

2.0.1.1.1 Basic Configuration (TDM and CodeBlocks) Install both TDM-Toolchains, for 32- and for 64-bit (e.g. in C:\UsrProg\TDM-GCC-64 and C:\UsrProg\TDM-GCC-32). Then edit the following entries in CodeBlocks at Settings -> Compiler:

- GNU GCC Compiler:
"Compiler Settings" -> "Compiler Flags" General\Target 64bit [-m64]
"Toolchain executables" : C:\UsrProg\TDM-GCC-64
- GNU Fortran Compiler:
"Compiler Settings" -> "Other Compiler options": -m64
"Toolchain executables" : C:\UsrProg\TDM-GCC-64

In order to build 32bit programs the global GCC settings have to be changed accordingly. The 32bit settings define new compilers and can now be distinguished from the 64bit versions when used inside the 32bit workspaces.

2.0.1.2 Settings for own Applications

2.0.1.2.1 Fortran 64bit Compilerswitches:

- tbd.

2.0.1.2.2 Link

- tbd.

Chapter 3

Compiler settings for Linux

3.0.1 tbd.

Chapter 4

Data Type Index

4.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

cTCSCanvas	13
TKTRNX	18
wxApp	
wxTCSapp	24
xJournalEntry_typ	25

Chapter 5

Data Type Index

5.1 Data Types List

Here are the data types with brief descriptions:

cTCScanvas	13
TKTRNX	18
wxTCSapp	24
xJournalEntry_typ	25

Chapter 6

File Index

6.1 File List

Here is a list of all files with brief descriptions:

AG2.for	Graph2D: Tektronix Advanced Graphing II Emulation	27
AG2Holerith.for	Graph2D: deprecated AG2 routines	85
AG2uline.for	Graph2D: Dummy User Routine	95
AG2umnmx.for	Graph2D: Dummy User Routine	96
AG2upoint.for	Graph2D: Dummy User Routine	97
AG2users.for	Graph2D: Dummy User Routine	98
AG2useset.for	Graph2D: Dummy User Routine	99
AG2usesetC.for	Graph2D: Dummy User Routine	100
AG2UsrSoftek.for	Graph2D: Dummy User Routine	101
G2dAG2.fd	Graph2D: AG2 Common Block G2dAG2	101
GetHDC.for	Restore Hardcopies	103
PlotHDC.f03	Utility: Plot Journalfiles	105
Strings.for	TCS: String functions	107
TCS.for	TCS: Tektronix Plot 10 Emulation	110
TCSdrWXcpp.cpp	WX Port: Low-Level Driver	124
TCSdrWXcpp.hpp	WX Port: Headerfile	154
TCSdrWXfor.f08	WX Port: High-Level Driver	178
Tktrnx.fd	WX Port: TCS Common Block TKTRNX	184

TKTRNX.hpp	
WX Port: TCS Common Block TKTRNX	185
wxTCSmain.cpp	
Initialization of wxWidgets	186

Chapter 7

Data Type Documentation

7.1 cTCScanvas Class Reference

Public Member Functions

- [cTCScanvas](#) (int iMode, wxFrame *parent, wxFrame *FrameToUse, wxStatusBar *StatusBarToUse)
- virtual [~cTCScanvas](#) ()

Public Attributes

- wxFrame * [TCSframe](#)
- wxPanel * [TCSpanel](#)
- wxLogWindow * [logWindow](#)
- wxStatusBar * [TCSstatusBar](#)
- wxWindowID [ID_TCSframe](#)
- wxWindowID [ID_TCSpanel](#)
- wxWindowID [ID_TCSstatus](#)
- wxPen [TCSpen](#)
- wxBrush [TCSbrush](#)
- wxFont [TCSfont](#)
- bool [ClippingNotActive](#) = true
- int [TCSpanelKeyPressed](#)
- int [TCSmouseButtonDown](#)
- int [TCSmouseX](#)
- int [TCSmouseY](#)
- [xJournalEntry_tpy](#) * xTCSJournal = NULL
- struct TKTRNX [TekSav](#)
- struct G2dAG2 [AG2Sav](#)
- int [DefaultLinColSav](#)
- int [DefaultTxtColSav](#)
- int [DefaultBckColSav](#)
- char [HardcopyFileSav](#) [TCS_FILE_NAMELEN]
- char [sect0Sav](#) [TCS_FILE_NAMELEN]

7.1.1 Detailed Description

Definition at line 74 of file [TCSdrWXcpp.cpp](#).

7.1.2 Constructor & Destructor Documentation

7.1.2.1 cTCScanvas()

```
cTCScanvas::cTCScanvas (
    int iMode,
    wxFrame * parent,
    wxFrame * FrameToUse,
    wxStatusBar * StatusBarToUse )
```

Definition at line 698 of file [TCSdrWXcpp.cpp](#).

7.1.2.2 ~cTCScanvas()

```
cTCScanvas::~~cTCScanvas ( ) [virtual]
```

Definition at line 779 of file [TCSdrWXcpp.cpp](#).

7.1.3 Member Data Documentation

7.1.3.1 AG2Sav

```
struct G2dAG2 cTCScanvas::AG2Sav
```

Definition at line 95 of file [TCSdrWXcpp.cpp](#).

7.1.3.2 ClippingNotActive

```
bool cTCScanvas::ClippingNotActive = true
```

Definition at line 91 of file [TCSdrWXcpp.cpp](#).

7.1.3.3 DefaultBckColSav

```
int cTCScanvas::DefaultBckColSav
```

Definition at line 99 of file [TCSdrWXcpp.cpp](#).

7.1.3.4 DefaultLinColSav

```
int cTCSCanvas::DefaultLinColSav
```

Definition at line 99 of file [TCSdrWXcpp.cpp](#).

7.1.3.5 DefaultTxtColSav

```
int cTCSCanvas::DefaultTxtColSav
```

Definition at line 99 of file [TCSdrWXcpp.cpp](#).

7.1.3.6 HardcopyFileSav

```
char cTCSCanvas::HardcopyFileSav[TCS_FILE_NAMELEN]
```

Definition at line 100 of file [TCSdrWXcpp.cpp](#).

7.1.3.7 ID_TCSframe

```
wxWindowID cTCSCanvas::ID_TCSframe
```

Definition at line 83 of file [TCSdrWXcpp.cpp](#).

7.1.3.8 ID_TCSpanel

```
wxWindowID cTCSCanvas::ID_TCSpanel
```

Definition at line 84 of file [TCSdrWXcpp.cpp](#).

7.1.3.9 ID_TCSstatus

```
wxWindowID cTCSCanvas::ID_TCSstatus
```

Definition at line 85 of file [TCSdrWXcpp.cpp](#).

7.1.3.10 logWindow

```
wxLogWindow* cTCScanvas::logWindow
```

Definition at line 80 of file [TCSdrWXcpp.cpp](#).

7.1.3.11 sect0Sav

```
char cTCScanvas::sect0Sav[TCS_FILE_NAMELEN]
```

Definition at line 100 of file [TCSdrWXcpp.cpp](#).

7.1.3.12 TCSbrush

```
wxBrush cTCScanvas::TCSbrush
```

Definition at line 88 of file [TCSdrWXcpp.cpp](#).

7.1.3.13 TCSfont

```
wxFont cTCScanvas::TCSfont
```

Definition at line 89 of file [TCSdrWXcpp.cpp](#).

7.1.3.14 TCSframe

```
wxFrame* cTCScanvas::TCSframe
```

Definition at line 78 of file [TCSdrWXcpp.cpp](#).

7.1.3.15 TCSmouseButtonDown

```
int cTCScanvas::TCSmouseButtonDown
```

Definition at line 93 of file [TCSdrWXcpp.cpp](#).

7.1.3.16 TCSmouseX

```
int cTCScanvas::TCSmouseX
```

Definition at line 93 of file [TCSdrWXcpp.cpp](#).

7.1.3.17 TCSmouseY

```
int cTCScanvas::TCSmouseY
```

Definition at line 93 of file [TCSdrWXcpp.cpp](#).

7.1.3.18 TCSPanel

```
wxPanel* cTCScanvas::TCSPanel
```

Definition at line 79 of file [TCSdrWXcpp.cpp](#).

7.1.3.19 TCSPanelKeyPressed

```
int cTCScanvas::TCSPanelKeyPressed
```

Definition at line 92 of file [TCSdrWXcpp.cpp](#).

7.1.3.20 TCSPen

```
wxPen cTCScanvas::TCSPen
```

Definition at line 87 of file [TCSdrWXcpp.cpp](#).

7.1.3.21 TCSStatusBar

```
wxStatusBar* cTCScanvas::TCSStatusBar
```

Definition at line 81 of file [TCSdrWXcpp.cpp](#).

7.1.3.22 TekSav

```
struct TKTRNX cTCSCanvas::TekSav
```

Definition at line 95 of file [TCSdrWXcpp.cpp](#).

7.1.3.23 xTCSJournal

```
xJournalEntry_typ* cTCSCanvas::xTCSJournal = NULL
```

Definition at line 95 of file [TCSdrWXcpp.cpp](#).

The documentation for this class was generated from the following file:

- [TCSdrWXcpp.cpp](#)

7.2 TKTRNX Struct Reference

```
#include <TKTRNX.hpp>
```

Public Attributes

- int [khomey](#)
- int [khorsz](#)
- int [kversz](#)
- int [kitalc](#)
- int [ksizef](#)
- int [klmrgn](#)
- int [krmrgn](#)
- int [kScrX](#)
- int [kScrY](#)
- int [kbeamx](#)
- int [kbeamy](#)
- int [kminsx](#)
- int [kminsy](#)
- int [kmaxsx](#)
- int [kmaxsy](#)
- float [tminvx](#)
- float [tminvy](#)
- float [tmaxvx](#)
- float [tmaxvy](#)
- float [trcosf](#)
- float [trsinf](#)
- float [trscal](#)
- float [xfac](#)
- float [yfac](#)
- float [xlog](#)
- float [ylog](#)
- int [kStCol](#)
- int [iLinCol](#)
- int [iBckCol](#)
- int [iTxtCol](#)

7.2.1 Detailed Description

Definition at line 18 of file [TKTRNX.hpp](#).

7.2.2 Member Data Documentation

7.2.2.1 iBckCol

```
int TKTRNX::iBckCol
```

Definition at line 33 of file [TKTRNX.hpp](#).

7.2.2.2 iLinCol

```
int TKTRNX::iLinCol
```

Definition at line 33 of file [TKTRNX.hpp](#).

7.2.2.3 iTxtCol

```
int TKTRNX::iTxtCol
```

Definition at line 33 of file [TKTRNX.hpp](#).

7.2.2.4 kbeamx

```
int TKTRNX::kbeamx
```

Definition at line 24 of file [TKTRNX.hpp](#).

7.2.2.5 kbeamy

```
int TKTRNX::kbeamy
```

Definition at line 24 of file [TKTRNX.hpp](#).

7.2.2.6 khomey

```
int TKTRNX::khomey
```

Definition at line 20 of file [TKTRNX.hpp](#).

7.2.2.7 khorsz

```
int TKTRNX::khorsz
```

Definition at line 21 of file [TKTRNX.hpp](#).

7.2.2.8 kitalc

```
int TKTRNX::kitalc
```

Definition at line 22 of file [TKTRNX.hpp](#).

7.2.2.9 klmrgn

```
int TKTRNX::klmrgn
```

Definition at line 23 of file [TKTRNX.hpp](#).

7.2.2.10 kmaxsx

```
int TKTRNX::kmaxsx
```

Definition at line 25 of file [TKTRNX.hpp](#).

7.2.2.11 kmaxsy

```
int TKTRNX::kmaxsy
```

Definition at line 25 of file [TKTRNX.hpp](#).

7.2.2.12 kminsx

```
int TKTRNX::kminsx
```

Definition at line 25 of file [TKTRNX.hpp](#).

7.2.2.13 kminsy

```
int TKTRNX::kminsy
```

Definition at line 25 of file [TKTRNX.hpp](#).

7.2.2.14 krmrgn

```
int TKTRNX::krmrgn
```

Definition at line 23 of file [TKTRNX.hpp](#).

7.2.2.15 kScrX

```
int TKTRNX::kScrX
```

Definition at line 23 of file [TKTRNX.hpp](#).

7.2.2.16 kScrY

```
int TKTRNX::kScrY
```

Definition at line 23 of file [TKTRNX.hpp](#).

7.2.2.17 ksizeof

```
int TKTRNX::ksized
```

Definition at line 22 of file [TKTRNX.hpp](#).

7.2.2.18 kStCol

```
int TKTRNX::kStCol
```

Definition at line 32 of file [TKTRNX.hpp](#).

7.2.2.19 kversz

```
int TKTRNX::kversz
```

Definition at line 21 of file [TKTRNX.hpp](#).

7.2.2.20 tmaxvx

```
float TKTRNX::tmaxvx
```

Definition at line 28 of file [TKTRNX.hpp](#).

7.2.2.21 tmaxvy

```
float TKTRNX::tmaxvy
```

Definition at line 28 of file [TKTRNX.hpp](#).

7.2.2.22 tminvx

```
float TKTRNX::tminvx
```

Definition at line 28 of file [TKTRNX.hpp](#).

7.2.2.23 tminvy

```
float TKTRNX::tminvy
```

Definition at line 28 of file [TKTRNX.hpp](#).

7.2.2.24 trcosf

```
float TKTRNX::trcosf
```

Definition at line 29 of file [TKTRNX.hpp](#).

7.2.2.25 trscal

```
float TKTRNX::trscal
```

Definition at line 29 of file [TKTRNX.hpp](#).

7.2.2.26 trsinf

```
float TKTRNX::trsinf
```

Definition at line 29 of file [TKTRNX.hpp](#).

7.2.2.27 xfac

```
float TKTRNX::xfac
```

Definition at line 30 of file [TKTRNX.hpp](#).

7.2.2.28 xlog

```
float TKTRNX::xlog
```

Definition at line 30 of file [TKTRNX.hpp](#).

7.2.2.29 yfac

```
float TKTRNX::yfac
```

Definition at line 30 of file [TKTRNX.hpp](#).

7.2.2.30 ylog

```
float TKTRNX::ylog
```


Definition at line 30 of file [TKTRNX.hpp](#).

The documentation for this struct was generated from the following file:

- [TKTRNX.hpp](#)

7.3 wxTCSapp Class Reference

Inheritance diagram for wxTCSapp:



Public Member Functions

- virtual bool [OnInit](#) ()
- virtual void [OnIdle](#) ()

7.3.1 Detailed Description

Definition at line 31 of file [wxTCSmain.cpp](#).

7.3.2 Member Function Documentation

7.3.2.1 OnIdle()

```
void wxTCSapp::OnIdle ( ) [virtual]
```

Definition at line 58 of file [wxTCSmain.cpp](#).

7.3.2.2 OnInit()

```
bool wxTCSapp::OnInit ( ) [virtual]
```

Definition at line 43 of file [wxTCSmain.cpp](#).

The documentation for this class was generated from the following file:

- [wxTCSmain.cpp](#)

7.4 xJournalEntry_typ Struct Reference

Public Attributes

- struct [xJournalEntry_typ](#) * [previous](#)
- struct [xJournalEntry_typ](#) * [next](#)
- int [action](#)
- int [i1](#)
- int [i2](#)

7.4.1 Detailed Description

Definition at line 68 of file [TCSdrWXcpp.cpp](#).

7.4.2 Member Data Documentation

7.4.2.1 action

```
int xJournalEntry_typ::action
```

Definition at line 70 of file [TCSdrWXcpp.cpp](#).

7.4.2.2 i1

```
int xJournalEntry_typ::i1
```

Definition at line 70 of file [TCSdrWXcpp.cpp](#).

7.4.2.3 i2

```
int xJournalEntry_typ::i2
```

Definition at line 70 of file [TCSdrWXcpp.cpp](#).

7.4.2.4 next

```
struct xJournalEntry_typ* xJournalEntry_typ::next
```

Definition at line 69 of file [TCSdrWXcpp.cpp](#).

7.4.2.5 previous

```
struct xJournalEntry_typ* xJournalEntry_typ::previous
```

Definition at line 68 of file [TCSdrWXcpp.cpp](#).

The documentation for this struct was generated from the following file:

- [TCSdrWXcpp.cpp](#)

Chapter 8

File Documentation

8.1 AG2.for File Reference

Graph2D: Tektronix Advanced Graphing II Emulation.

Functions/Subroutines

- subroutine [ag2lev](#) (ilevel)
- subroutine [line](#) (ipar)
- subroutine [symbl](#) (ipar)
- subroutine [steps](#) (ipar)
- subroutine [infin](#) (par)
- subroutine [npts](#) (ipar)
- subroutine [stepl](#) (ipar)
- subroutine [sizes](#) (par)
- subroutine [sizel](#) (par)
- subroutine [xneat](#) (ipar)
- subroutine [yneat](#) (ipar)
- subroutine [xzero](#) (ipar)
- subroutine [yzero](#) (ipar)
- subroutine [xloc](#) (ipar)
- subroutine [yloc](#) (ipar)
- subroutine [xloctp](#) (ipar)
- subroutine [ylocrt](#) (ipar)
- subroutine [xlab](#) (ipar)
- subroutine [ylab](#) (ipar)
- subroutine [xden](#) (ipar)
- subroutine [yden](#) (ipar)
- subroutine [xtics](#) (ipar)
- subroutine [ytics](#) (ipar)
- subroutine [xlen](#) (ipar)
- subroutine [ylen](#) (ipar)
- subroutine [xfrm](#) (ipar)
- subroutine [yfrm](#) (ipar)
- subroutine [xmtcs](#) (ipar)
- subroutine [ymtcs](#) (ipar)
- subroutine [xmfrm](#) (ipar)

- subroutine [ymfrm](#) (ipar)
- subroutine [dlimx](#) (xmin, xmax)
- subroutine [dlimy](#) (ymin, ymax)
- subroutine [slimx](#) (ixmin, ixmax)
- subroutine [slimy](#) (iymin, iymax)
- subroutine [place](#) (ipar)
- subroutine [xtype](#) (ipar)
- subroutine [ytype](#) (ipar)
- subroutine [xwdth](#) (ipar)
- subroutine [ywdth](#) (ipar)
- subroutine [xetyp](#) (ipar)
- subroutine [yetyp](#) (ipar)
- subroutine [setwin](#)
- subroutine [dinitx](#)
- subroutine [dinity](#)
- subroutine [hbarst](#) (ishade, iwbar, idbar)
- subroutine [vbarst](#) (ishade, iwbar, idbar)
- subroutine [binitt](#)
- subroutine [check](#) (x, y)
- subroutine [typck](#) (ixy, arr)
- subroutine [rgchek](#) (ixy, arr)
- subroutine [mnmx](#) (arr, amin, amax)
- subroutine [cmnmx](#) (arr, amin, amax)
- subroutine [optim](#) (ixy)
- subroutine [loptim](#) (ixy)
- subroutine [coptim](#) (ixy)
- real function [calpnt](#) (arr, i)
- subroutine [calcon](#) (amin, amax, labtyp, ubgc)
- subroutine [ymdyd](#) (iJulYrOut, iJulDayOut, iGregYrIn, iGregMonIn, iGregDayIn)
- integer function [leap](#) (iyear)
- subroutine [iubgc](#) (iyear, iday, iubgcO)
- subroutine [oubgc](#) (iyear, iday, iubgcI)
- subroutine [frame](#)
- subroutine [dsplay](#) (x, y)
- subroutine [cplot](#) (x, y)
- subroutine [keyset](#) (array, key)
- real function [datget](#) (arr, i, key)
- subroutine [bar](#) (x, y, [line](#))
- subroutine [filbox](#) (minx, miny, maxx, maxy, ishade, lspace)
- subroutine [bsyms](#) (x, y, isym)
- subroutine [symout](#) (isym, fac)
- subroutine [teksym](#) (isym, amult)
- subroutine [teksym1](#) (istart, iend, incr, siz)
- subroutine [grid](#)
- subroutine [logtix](#) (nbase, start, tintvl, mstart, mend)
- subroutine [tset](#) (nbase)
- subroutine [tset2](#) (newloc, nfar, nlen, nfrm, kstart, kend)
- subroutine [monpos](#) (nbase, iy1, dpos, spos)
- subroutine [gline](#) (nbase, datapt, spos)
- subroutine [label](#) (nbase)
- subroutine [numsetc](#) (fnum, iwidth, nbase, outstr)
- subroutine [iformc](#) (fnum, iwidth, outstr)
- subroutine [fformc](#) (fnum, iwidth, idec, outstr)
- subroutine [fonlyc](#) (fnum, iwidth, idec, outstr)
- subroutine [eformc](#) (fnum, iwidth, idec, outstr)

- subroutine [esplit](#) (fnum, iwidth, idec, iexpon)
- subroutine [expoutc](#) (nbase, iexp, outstr)
- subroutine [alfsetc](#) (fnum, labtyp, string)
- subroutine [notatec](#) (ix, iy, string)
- subroutine [vlablc](#) (string)
- subroutine [justerc](#) (string, iPosFlag, iOff)
- subroutine [width](#) (nbase)
- subroutine [lwidth](#) (nbase)
- subroutine [remlab](#) (nbase, iloc, labtyp, ix, iy)
- subroutine [spread](#) (nbase)
- real function [findge](#) (val, tab, iN)
- real function [findle](#) (val, tab, iN)
- integer function [locge](#) (ival, itab, iN)
- integer function [locle](#) (ival, itab, iN)
- real function [roundd](#) (value, finterval)
- real function [roundu](#) (value, finterval)
- subroutine [savcom](#) (Array)
- subroutine [rescom](#) (Array)
- integer function [iother](#) (ipar)

8.1.1 Detailed Description

Graph2D: Tektronix Advanced Graphing II Emulation.

Version

(2023,135, x)

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Layer 2: scientific 2-D graphic subroutines

Note

The control character for exponent (originally -1) is now SOH=char(1) and for index (originally -2) STX=char(2).

```
Package:
- AG2.for:          chart plotting routines
- AG2Holerith.for:  deprecated routines
- AG2USR.for:       default user routines
- G2dAG2.fd:        commonblock
```

Definition in file [AG2.for](#).

8.1.2 Function/Subroutine Documentation

8.1.2.1 ag2lev()

```
subroutine ag2lev (  
    integer, dimension(3) ilevel )
```

Definition at line 94 of file [AG2.for](#).

8.1.2.2 alfsetc()

```
subroutine alfsetc (  
    real fnum,  
    integer labtyp,  
    character *(*) string )
```

Definition at line 2563 of file [AG2.for](#).

8.1.2.3 bar()

```
subroutine bar (  
    real x,  
    real y,  
    integer line )
```

Definition at line 1688 of file [AG2.for](#).

8.1.2.4 binitt()

```
subroutine binitt
```

Definition at line 714 of file [AG2.for](#).

8.1.2.5 bsyms()

```
subroutine bsyms (  
    real x,  
    real y,  
    integer isym )
```

Definition at line 1840 of file [AG2.for](#).

8.1.2.6 calcon()

```
subroutine calcon (
    real amin,
    real amax,
    integer labtyp,
    logical ubgc )
```

Definition at line [1326](#) of file [AG2.for](#).

8.1.2.7 calpnt()

```
real function calpnt (
    real, dimension(5) arr,
    integer i )
```

Definition at line [1271](#) of file [AG2.for](#).

8.1.2.8 check()

```
subroutine check (
    real, dimension(5) x,
    real, dimension(5) y )
```

Definition at line [798](#) of file [AG2.for](#).

8.1.2.9 cmnmx()

```
subroutine cmnmx (
    real, dimension(5) arr,
    real amin,
    real amax )
```

Definition at line [920](#) of file [AG2.for](#).

8.1.2.10 coptim()

```
subroutine coptim (
    integer ixy )
```

Definition at line [1115](#) of file [AG2.for](#).

8.1.2.11 cplot()

```
subroutine cplot (
    real, dimension(5) x,
    real, dimension(5) y )
```

Definition at line [1538](#) of file [AG2.for](#).

8.1.2.12 datget()

```
real function datget (
    real, dimension(5) arr,
    integer i,
    integer key )
```

Definition at line [1660](#) of file [AG2.for](#).

8.1.2.13 dinitx()

```
subroutine dinitx
```

Definition at line [644](#) of file [AG2.for](#).

8.1.2.14 dinity()

```
subroutine dinity
```

Definition at line [658](#) of file [AG2.for](#).

8.1.2.15 dlimx()

```
subroutine dlimx (
    real xmin,
    real xmax )
```

Definition at line [464](#) of file [AG2.for](#).

8.1.2.16 dlimy()

```
subroutine dlimy (
    real ymin,
    real ymax )
```

Definition at line 476 of file [AG2.for](#).

8.1.2.17 dsplay()

```
subroutine dsplay (
    real, dimension(5) x,
    real, dimension(5) y )
```

Definition at line 1524 of file [AG2.for](#).

8.1.2.18 eformc()

```
subroutine eformc (
    real fnum,
    integer iwidth,
    integer idec,
    character, dimension(*) outstr )
```

Definition at line 2434 of file [AG2.for](#).

8.1.2.19 esplit()

```
subroutine esplit (
    real fnum,
    integer iwidth,
    integer idec,
    integer iexpon )
```

Definition at line 2467 of file [AG2.for](#).

8.1.2.20 expoutc()

```
subroutine expoutc (
    integer nbase,
    integer iexp,
    character, dimension(*) outstr )
```

Definition at line 2487 of file [AG2.for](#).

8.1.2.21 fformc()

```
subroutine fformc (  
    real fnum,  
    integer iwidth,  
    integer idec,  
    character, dimension(*) outstr )
```

Definition at line [2375](#) of file [AG2.for](#).

8.1.2.22 filbox()

```
subroutine filbox (  
    integer minx,  
    integer miny,  
    integer maxx,  
    integer maxy,  
    integer ishade,  
    integer lspace )
```

Definition at line [1755](#) of file [AG2.for](#).

8.1.2.23 findge()

```
real function findge (  
    real val,  
    real, dimension(1) tab,  
    integer iN )
```

Definition at line [2922](#) of file [AG2.for](#).

8.1.2.24 findle()

```
real function findle (  
    real val,  
    real, dimension(1) tab,  
    integer iN )
```

Definition at line [2941](#) of file [AG2.for](#).

8.1.2.25 fonlyc()

```
subroutine fonlyc (
    real fnum,
    integer iwidth,
    integer idec,
    character, dimension(*) outstr )
```

Definition at line [2403](#) of file [AG2.for](#).

8.1.2.26 frame()

```
subroutine frame
```

Definition at line [1510](#) of file [AG2.for](#).

8.1.2.27 gline()

```
subroutine gline (
    integer nbase,
    real datapt,
    integer spos )
```

Definition at line [2173](#) of file [AG2.for](#).

8.1.2.28 grid()

```
subroutine grid
```

Definition at line [1956](#) of file [AG2.for](#).

8.1.2.29 hbarst()

```
subroutine hbarst (
    integer ishade,
    integer iwbar,
    integer idbar )
```

Definition at line [672](#) of file [AG2.for](#).

8.1.2.30 iformc()

```
subroutine iformc (
    real fnum,
    integer iwidth,
    character, dimension(*) outstr )
```

Definition at line 2343 of file [AG2.for](#).

8.1.2.31 infin()

```
subroutine infin (
    real par )
```

Definition at line 142 of file [AG2.for](#).

8.1.2.32 iother()

```
integer function iother (
    integer ipar )
```

Definition at line 3066 of file [AG2.for](#).

8.1.2.33 iubgc()

```
subroutine iubgc (
    integer iyear,
    integer iday,
    integer iubgc0 )
```

Definition at line 1473 of file [AG2.for](#).

8.1.2.34 justerc()

```
subroutine justerc (
    character, dimension(*) string,
    integer iPosFlag,
    integer iOff )
```

Definition at line 2666 of file [AG2.for](#).

8.1.2.35 keyset()

```
subroutine keyset (  
    real, dimension(1) array,  
    integer key )
```

Definition at line 1634 of file [AG2.for](#).

8.1.2.36 label()

```
subroutine label (  
    integer nbase )
```

Definition at line 2200 of file [AG2.for](#).

8.1.2.37 leap()

```
integer function leap (  
    integer iyear )
```

Definition at line 1459 of file [AG2.for](#).

8.1.2.38 line()

```
subroutine line (  
    integer ipar )
```

Definition at line 109 of file [AG2.for](#).

8.1.2.39 locge()

```
integer function locge (  
    integer ival,  
    integer, dimension(1) itab,  
    integer iN )
```

Definition at line 2963 of file [AG2.for](#).

8.1.2.40 locle()

```
integer function locle (  
    integer ival,  
    integer, dimension(1) itab,  
    integer iN )
```

Definition at line 2981 of file [AG2.for](#).

8.1.2.41 logtix()

```
subroutine logtix (  
    integer nbase,  
    real start,  
    real tintvl,  
    integer mstart,  
    integer mend )
```

Definition at line 2042 of file [AG2.for](#).

8.1.2.42 loptim()

```
subroutine loptim (  
    integer ixy )
```

Definition at line 988 of file [AG2.for](#).

8.1.2.43 lwidth()

```
subroutine lwidth (  
    integer nbase )
```

Definition at line 2732 of file [AG2.for](#).

8.1.2.44 mnmx()

```
subroutine mnmx (  
    real, dimension(5) arr,  
    real amin,  
    real amax )
```

Definition at line 881 of file [AG2.for](#).

8.1.2.45 monpos()

```
subroutine monpos (
    integer nbase,
    integer iyl,
    real dpos,
    integer spos )
```

Definition at line 2159 of file [AG2.for](#).

8.1.2.46 notatec()

```
subroutine notatec (
    integer ix,
    integer iy,
    character *(*) string )
```

Definition at line 2618 of file [AG2.for](#).

8.1.2.47 npts()

```
subroutine npts (
    integer ipar )
```

Definition at line 155 of file [AG2.for](#).

8.1.2.48 numsetc()

```
subroutine numsetc (
    real fnum,
    integer iwidth,
    integer nbase,
    character, dimension(*) outstr )
```

Definition at line 2316 of file [AG2.for](#).

8.1.2.49 optim()

```
subroutine optim (
    integer ixy )
```

Definition at line 971 of file [AG2.for](#).

8.1.2.50 oubgc()

```
subroutine oubgc (
    integer iyear,
    integer iday,
    integer iubgcI )
```

Definition at line [1487](#) of file [AG2.for](#).

8.1.2.51 place()

```
subroutine place (
    integer ipar )
```

Definition at line [512](#) of file [AG2.for](#).

8.1.2.52 remlab()

```
subroutine remlab (
    integer nbase,
    integer iloc,
    integer labtyp,
    integer ix,
    integer iy )
```

Definition at line [2807](#) of file [AG2.for](#).

8.1.2.53 rescom()

```
subroutine rescom (
    integer, dimension(1) Array )
```

Definition at line [3050](#) of file [AG2.for](#).

8.1.2.54 rgchek()

```
subroutine rgchek (
    integer ixy,
    real, dimension(5) arr )
```

Definition at line [854](#) of file [AG2.for](#).

8.1.2.55 roundd()

```
real function roundd (  
    value,  
    real, value finterval )
```

Definition at line [2999](#) of file [AG2.for](#).

8.1.2.56 roundu()

```
real function roundu (  
    value,  
    real, value finterval )
```

Definition at line [3015](#) of file [AG2.for](#).

8.1.2.57 savcom()

```
subroutine savcom (  
    integer, dimension(1) Array )
```

Definition at line [3034](#) of file [AG2.for](#).

8.1.2.58 setwin()

```
subroutine setwin
```

Definition at line [622](#) of file [AG2.for](#).

8.1.2.59 sizel()

```
subroutine sizel (  
    real par )
```

Definition at line [188](#) of file [AG2.for](#).

8.1.2.60 sizes()

```
subroutine sizes (  
    real par )
```

Definition at line 177 of file [AG2.for](#).

8.1.2.61 slimx()

```
subroutine slimx (  
    integer ixmin,  
    integer ixmax )
```

Definition at line 488 of file [AG2.for](#).

8.1.2.62 slimy()

```
subroutine slimy (  
    integer iymin,  
    integer ymax )
```

Definition at line 500 of file [AG2.for](#).

8.1.2.63 spread()

```
subroutine spread (  
    integer nbase )
```

Definition at line 2870 of file [AG2.for](#).

8.1.2.64 stepl()

```
subroutine stepl (  
    integer ipar )
```

Definition at line 166 of file [AG2.for](#).

8.1.2.65 steps()

```
subroutine steps (  
    integer ipar )
```

Definition at line 131 of file [AG2.for](#).

8.1.2.66 symbl()

```
subroutine symbl (  
    integer ipar )
```

Definition at line 120 of file [AG2.for](#).

8.1.2.67 symout()

```
subroutine symout (  
    integer isym,  
    real fac )
```

Definition at line 1857 of file [AG2.for](#).

8.1.2.68 teksym()

```
subroutine teksym (  
    integer isym,  
    real amult )
```

Definition at line 1882 of file [AG2.for](#).

8.1.2.69 teksym1()

```
subroutine teksym1 (  
    integer istart,  
    integer iend,  
    integer incr,  
    real siz )
```

Definition at line 1930 of file [AG2.for](#).

8.1.2.70 tset()

```
subroutine tset (  
    integer nbase )
```

Definition at line [2089](#) of file [AG2.for](#).

8.1.2.71 tset2()

```
subroutine tset2 (  
    integer newloc,  
    integer nfar,  
    integer nlen,  
    integer nfrm,  
    integer kstart,  
    integer kend )
```

Definition at line [2127](#) of file [AG2.for](#).

8.1.2.72 typck()

```
subroutine typck (  
    integer ixy,  
    real, dimension(5) arr )
```

Definition at line [823](#) of file [AG2.for](#).

8.1.2.73 vbarst()

```
subroutine vbarst (  
    integer ishade,  
    integer iwbar,  
    integer idbar )
```

Definition at line [692](#) of file [AG2.for](#).

8.1.2.74 vlablc()

```
subroutine vlablc (  
    character, dimension(*) string )
```

Definition at line [2643](#) of file [AG2.for](#).

8.1.2.75 width()

```
subroutine width (  
    integer nbase )
```

Definition at line [2691](#) of file [AG2.for](#).

8.1.2.76 xden()

```
subroutine xden (  
    integer ipar )
```

Definition at line [312](#) of file [AG2.for](#).

8.1.2.77 xetyp()

```
subroutine xetyp (  
    integer ipar )
```

Definition at line [596](#) of file [AG2.for](#).

8.1.2.78 xfrm()

```
subroutine xfrm (  
    integer ipar )
```

Definition at line [390](#) of file [AG2.for](#).

8.1.2.79 xlab()

```
subroutine xlab (  
    integer ipar )
```

Definition at line [290](#) of file [AG2.for](#).

8.1.2.80 xlen()

```
subroutine xlen (  
    integer ipar )
```

Definition at line [364](#) of file [AG2.for](#).

8.1.2.81 xloc()

```
subroutine xloc (  
    integer ipar )
```

Definition at line [246](#) of file [AG2.for](#).

8.1.2.82 xloctp()

```
subroutine xloctp (  
    integer ipar )
```

Definition at line [268](#) of file [AG2.for](#).

8.1.2.83 xmfrm()

```
subroutine xmfrm (  
    integer ipar )
```

Definition at line [438](#) of file [AG2.for](#).

8.1.2.84 xmtcs()

```
subroutine xmtcs (  
    integer ipar )
```

Definition at line [416](#) of file [AG2.for](#).

8.1.2.85 xneat()

```
subroutine xneat (  
    integer ipar )
```

Definition at line [202](#) of file [AG2.for](#).

8.1.2.86 xtics()

```
subroutine xtics (  
    integer ipar )
```

Definition at line [342](#) of file [AG2.for](#).

8.1.2.87 xtype()

```
subroutine xtype (  
    integer ipar )
```

Definition at line [544](#) of file [AG2.for](#).

8.1.2.88 xwidth()

```
subroutine xwidth (  
    integer ipar )
```

Definition at line [570](#) of file [AG2.for](#).

8.1.2.89 xzero()

```
subroutine xzero (  
    integer ipar )
```

Definition at line [224](#) of file [AG2.for](#).

8.1.2.90 yden()

```
subroutine yden (  
    integer ipar )
```

Definition at line [327](#) of file [AG2.for](#).

8.1.2.91 yetyp()

```
subroutine yetyp (  
    integer ipar )
```

Definition at line [609](#) of file [AG2.for](#).

8.1.2.92 yfrm()

```
subroutine yfrm (  
    integer ipar )
```

Definition at line [403](#) of file [AG2.for](#).

8.1.2.93 ylab()

```
subroutine ylab (  
    integer ipar )
```

Definition at line 301 of file [AG2.for](#).

8.1.2.94 ylen()

```
subroutine ylen (  
    integer ipar )
```

Definition at line 377 of file [AG2.for](#).

8.1.2.95 yloc()

```
subroutine yloc (  
    integer ipar )
```

Definition at line 257 of file [AG2.for](#).

8.1.2.96 ylocrt()

```
subroutine ylocrt (  
    integer ipar )
```

Definition at line 279 of file [AG2.for](#).

8.1.2.97 ymdyd()

```
subroutine ymdyd (  
    integer iJulYrOut,  
    integer iJulDayOut,  
    integer iGregYrIn,  
    integer iGregMonIn,  
    integer iGregDayIn )
```

entry subroutine YMDYD (iJulYrIn,iJulDayIn,iGregYrOut,iGregMonOut,iGregDayOut)

Definition at line 1404 of file [AG2.for](#).

8.1.2.98 ymfrm()

```
subroutine ymfrm (  
    integer ipar )
```

Definition at line [451](#) of file [AG2.for](#).

8.1.2.99 ymtcs()

```
subroutine ymtcs (  
    integer ipar )
```

Definition at line [427](#) of file [AG2.for](#).

8.1.2.100 yneat()

```
subroutine yneat (  
    integer ipar )
```

Definition at line [213](#) of file [AG2.for](#).

8.1.2.101 ytics()

```
subroutine ytics (  
    integer ipar )
```

Definition at line [353](#) of file [AG2.for](#).

8.1.2.102 ytype()

```
subroutine ytype (  
    integer ipar )
```

Definition at line [557](#) of file [AG2.for](#).

8.1.2.103 ywdth()

```
subroutine ywdth (  
    integer ipar )
```

Definition at line [583](#) of file [AG2.for](#).

8.1.2.104 yzero()

```
subroutine yzero (
    integer ipar )
```

Definition at line 235 of file [AG2.for](#).

8.2 AG2.for

```
00001 C> \file      AG2.for
00002 C> \brief      Graph2D: Tektronix Advanced Graphing II Emulation
00003 C> \version    (2023,135, x)
00004 C> \author     (C) 2022 Dr.-Ing. Klaus Friedewald
00005 C> \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 C>
00007 C> \~german
00008 C> Schicht 2: Unterprogramme zur Erzeugung wissenschaftlicher 2-D Graphiken
00009 C> \note
00010 C> Die Sonderzeichen Hochindex (alt: -1) und Index (alt: -2) sind jetzt
00011 C> SOH=char(1) (Hochindex) bzw. STX=char(2) (Index).
00012 C>
00013 C> \~english
00014 C> Layer 2: scientific 2-D graphic subroutines
00015 C> \note
00016 C> The control character for exponent (originally -1) is now SOH=char(1)
00017 C> and for index (originally -2) STX=char(2).
00018 C>
00019 C> \~
00020 C> \note \verbatim
00021 C> Package:
00022 C> - AG2.for:      chart plotting routines
00023 C> - AG2Holerith.for: deprecated routines
00024 C> - AG2USR.for:   default user routines
00025 C> - G2dAG2.fd:    commonblock
00026 C> \endverbatim
00027 C
00028 C
00029 C Tektronix Advanced Graphics 2 - Version 2.x
00030 C
00031 C
00032 C Neuer Code in Fortran 77. Die Verwendung der im Manual dokumentierten
00033 C Unterprogramme bleibt unverändert, die direkte Manipulation von
00034 C Variablen des zugrundeliegenden Commonblockes ist jedoch nicht mehr
00035 C empfehlenswert. IBASEX (iPar) und IBASEY(iPar) mit ipar <>0,
00036 C IBASEC, COMGET und COMSET sollten in neuen Programmen nicht verwendet
00037 C werden.
00038 C
00039 C Die Zwischenspeicherung der Statusvariablen ueber
00040 C SAVCOM und RESCOM
00041 C und die Achsensteuerung ueber
00042 C IBASEX(0), IBASEY(0) und IOTHER
00043 C werden weiterhin unterstuetzt.
00044 C
00045 C Die Implementation der Unterprogramme COMGET und COMSET setzt die gleiche
00046 C Laenge von REAL und INTEGER-Variablen voraus.
00047 C
00048 C Da Holerithvariablen von modernen Compilern uneinheitlich unterstuetzt
00049 C werden (4Habcd entweder als gepackte Integervariable oder als Character-
00050 C variable interpretiert), wurden die folgenden Routinen angepasst:
00051 C - subroutine PLACE (Lit): Lit wird nur noch als Ordnungszahl (1..13)
00052 C und nicht mehr alternativ als Literal ('STD', 'UPH') interpretiert.
00053 C
00054 C subroutine LEAP (iyear): Die Schaltjahrkorrektur erfolgt nicht mehr
00055 C als SUBROUTINE ueber einen Common-Block, sondern direkt als
00056 C integer function LEAP (iyear) != 1: Schaltjahr, sonst 0
00057 C
00058 C Die Sonderzeichen Hochindex (alt: -1) und Index (alt: -2) sind jetzt
00059 C SOH=char(1) (Hochindex) bzw. STX=char(2) (Index).
00060 C
00061 C Intern erfolgt die Stringverarbeitung ueber Charaktervariablen als
00062 C nullterminierte C-Strings.
00063 C
00064 C Der User-API wurden die folgenden Unterprogramme als Charaktervarianten
00065 C der Original-Holerithroutinen hinzugefuegt:
00066 C - subroutine NUMSETC (fnum,nbase, outstr,fillstr)
00067 C - subroutine FONLYC (fnum,iwidth,idec, outstr,fillstr)
00068 C - subroutine EFORMC (fnum,iwidth,idec, outstr,fillstr)
00069 C - subroutine EXPOUTC (nbase,iexp, outstr,fillstr)
00070 C - subroutine ALFSETC (fnum,iwidth,labtyp,outstr)
00071 C - subroutine NOTATEC (IX,IY,LENCHR,IARRAY)
```

```

00072 C      - subroutine JUSTERC
00073 C
00074 C      - subroutine USESETC (fnum, iwidth, nbase, labstr)
00075 C
00076 C      subroutine MONPOS (nbase,iyl,dpos, spos) ! spos ist INTEGER
00077 C      subroutine GLINE (nbase,datapt,spos) ! spos ist INTEGER
00078 C
00079 C      Der Code ab Version 2.0 wird nicht mehr fuer CP/M entwickelt. Letzte
00080 C      unter CP/M compilierbare Version: (2006, 013, 1)
00081 C
00082 C      Zugehoerige Module:
00083 C      - AG2.FOR:      Basisfunktionen
00084 C      - AG2Holerith:  Veraltete Unterprogramme zur Wahrung der Kompatibilitaet
00085 C                    (Unterstuetzung Holerithvariablen und vektorisierter Zu-
00086 C                    griff auf den Commonblock)
00087 C      - AG2USR.FOR:   Userroutinen
00088 C      - G2dAG2.fd:    Commonblockdefinition
00089 C
00090 C
00091 C
00092 C      Ausgabe der Softwareversion
00093 C
00094 C      subroutine ag2lev (ilevel)
00095 C      implicit none
00096 C      integer ilevel(3)
00097 C
00098 C      call tcslev (ilevel) ! level(3)= System aus TCS
00099 C      ilevel(1)=2023      ! Aenderungsjahr
00100 C      ilevel(2)= 135      ! Aenderungstag
00101 C      return
00102 C      end
00103 C
00104 C
00105 C
00106 C
00107 C      Setzen allgemeiner Commonvariablen
00108 C
00109 C      subroutine line (ipar)
00110 C      implicit none
00111 C      integer ipar
00112 C      include 'G2dAG2.fd'
00113 C
00114 C      cline= ipar
00115 C      return
00116 C      end
00117 C
00118 C
00119 C
00120 C      subroutine symb1 (ipar)
00121 C      implicit none
00122 C      integer ipar
00123 C      include 'G2dAG2.fd'
00124 C
00125 C      csymb1= ipar
00126 C      return
00127 C      end
00128 C
00129 C
00130 C
00131 C      subroutine steps (ipar)
00132 C      implicit none
00133 C      integer ipar
00134 C      include 'G2dAG2.fd'
00135 C
00136 C      csteps= ipar
00137 C      return
00138 C      end
00139 C
00140 C
00141 C
00142 C      subroutine infin (par)
00143 C      implicit none
00144 C      real par
00145 C      include 'G2dAG2.fd'
00146 C
00147 C      if (par .gt. 0.) then
00148 C        cinfin= par
00149 C      end if
00150 C      return
00151 C      end
00152 C
00153 C
00154 C
00155 C      subroutine npts (ipar)
00156 C      implicit none
00157 C      integer ipar
00158 C      include 'G2dAG2.fd'

```

```

00159
00160     cnpts= ipar
00161     return
00162 end
00163
00164
00165
00166     subroutine step1 (ipar)
00167     implicit none
00168     integer ipar
00169     include 'G2dAG2.fd'
00170
00171     cstep1= ipar
00172     return
00173 end
00174
00175
00176
00177     subroutine sizes (par)
00178     implicit none
00179     real par
00180     include 'G2dAG2.fd'
00181
00182     csizes= par
00183     return
00184 end
00185
00186
00187
00188     subroutine sizel (par)
00189     implicit none
00190     real par
00191     include 'G2dAG2.fd'
00192
00193     csizel= par
00194     return
00195 end
00196
00197
00198
00199 C
00200 C   Setzen der achsenbezogenen Commonvariablen
00201 C
00202     subroutine xneat (ipar)
00203     implicit none
00204     integer ipar
00205     include 'G2dAG2.fd'
00206
00207     cxyneat(1) = ipar .ne. 0
00208     return
00209 end
00210
00211
00212
00213     subroutine yneat (ipar)
00214     implicit none
00215     integer ipar
00216     include 'G2dAG2.fd'
00217
00218     cxyneat(2) = ipar .ne. 0
00219     return
00220 end
00221
00222
00223
00224     subroutine xzero (ipar)
00225     implicit none
00226     integer ipar
00227     include 'G2dAG2.fd'
00228
00229     cxyzzero(1) = ipar .ne. 0
00230     return
00231 end
00232
00233
00234
00235     subroutine yzero (ipar)
00236     implicit none
00237     integer ipar
00238     include 'G2dAG2.fd'
00239
00240     cxyzzero(2) = ipar .ne. 0
00241     return
00242 end
00243
00244
00245

```

```

00246      subroutine xloc (ipar)
00247      implicit none
00248      integer ipar
00249      include 'G2dAG2.fd'
00250
00251      cxyloc(1)= ipar
00252      return
00253      end
00254
00255
00256
00257      subroutine yloc (ipar)
00258      implicit none
00259      integer ipar
00260      include 'G2dAG2.fd'
00261
00262      cxyloc(2)= ipar
00263      return
00264      end
00265
00266
00267
00268      subroutine xloctp (ipar)
00269      implicit none
00270      integer ipar
00271      include 'G2dAG2.fd'
00272
00273      cxyloc(1)= ipar+abs(cxysmax(2)-cxysmin(2))
00274      return
00275      end
00276
00277
00278
00279      subroutine ylocrt (ipar)
00280      implicit none
00281      integer ipar
00282      include 'G2dAG2.fd'
00283
00284      cxyloc(2)= ipar + abs(cxysmax(1)-cxysmin(1))
00285      return
00286      end
00287
00288
00289
00290      subroutine xlab (ipar)
00291      implicit none
00292      integer ipar
00293      include 'G2dAG2.fd'
00294
00295      cxylab(1)= ipar
00296      return
00297      end
00298
00299
00300
00301      subroutine ylab (ipar)
00302      implicit none
00303      integer ipar
00304      include 'G2dAG2.fd'
00305
00306      cxylab(2)= ipar
00307      return
00308      end
00309
00310
00311
00312      subroutine xden (ipar)
00313      implicit none
00314      integer ipar
00315      include 'G2dAG2.fd'
00316
00317      if ((ipar .ge. 0) .and. (ipar .le. 10)) then
00318          cxyden(1)= ipar
00319          cxytics(1)= 0
00320          cxymtcs(1)= 0
00321      end if
00322      return
00323      end
00324
00325
00326
00327      subroutine yden (ipar)
00328      implicit none
00329      integer ipar
00330      include 'G2dAG2.fd'
00331
00332      if ((ipar .ge. 0) .and. (ipar .le. 10)) then

```

```
00333      cxyden(2)= ipar
00334      cxytics(2)= 0
00335      cxymtcs(2)= 0
00336      end if
00337      return
00338      end
00339
00340
00341
00342      subroutine xtics (ipar)
00343      implicit none
00344      integer ipar
00345      include 'G2dAG2.fd'
00346
00347      cxytics(1)= abs(ipar)
00348      return
00349      end
00350
00351
00352
00353      subroutine ytics (ipar)
00354      implicit none
00355      integer ipar
00356      include 'G2dAG2.fd'
00357
00358      cxytics(2)= abs(ipar)
00359      return
00360      end
00361
00362
00363
00364      subroutine xlen (ipar)
00365      implicit none
00366      integer ipar
00367      include 'G2dAG2.fd'
00368
00369      if (ipar .ge. 0) then
00370        cxylen(1)= ipar
00371      end if
00372      return
00373      end
00374
00375
00376
00377      subroutine ylen (ipar)
00378      implicit none
00379      integer ipar
00380      include 'G2dAG2.fd'
00381
00382      if (ipar .ge. 0) then
00383        cxylen(2)= ipar
00384      end if
00385      return
00386      end
00387
00388
00389
00390      subroutine xfrm (ipar)
00391      implicit none
00392      integer ipar
00393      include 'G2dAG2.fd'
00394
00395      if ((ipar .ge. 0) .and. (ipar .le. 6)) then
00396        cxyfrm(1)= ipar
00397      end if
00398      return
00399      end
00400
00401
00402
00403      subroutine yfrm (ipar)
00404      implicit none
00405      integer ipar
00406      include 'G2dAG2.fd'
00407
00408      if ((ipar .ge. 0) .and. (ipar .le. 6)) then
00409        cxyfrm(2)= ipar
00410      end if
00411      return
00412      end
00413
00414
00415
00416      subroutine xmtcs (ipar)
00417      implicit none
00418      integer ipar
00419      include 'G2dAG2.fd'
```



```

00420
00421     cxymtcs(1)= abs(ipar)
00422     return
00423 end
00424
00425
00426
00427     subroutine ymtcs (ipar)
00428     implicit none
00429     integer ipar
00430     include 'G2dAG2.fd'
00431
00432     cxymtcs(2)= abs(ipar)
00433     return
00434 end
00435
00436
00437
00438     subroutine xmfrm (ipar)
00439     implicit none
00440     integer ipar
00441     include 'G2dAG2.fd'
00442
00443     if ((ipar .ge. 0) .and. (ipar .le. 6)) then
00444         cxyxmfrm(1)= ipar
00445     end if
00446     return
00447 end
00448
00449
00450
00451     subroutine ymfrm (ipar)
00452     implicit none
00453     integer ipar
00454     include 'G2dAG2.fd'
00455
00456     if ((ipar .ge. 0) .and. (ipar .le. 6)) then
00457         cxyymfrm(2)= ipar
00458     end if
00459     return
00460 end
00461
00462
00463
00464     subroutine dlimx (xmin,xmax)
00465     implicit none
00466     real xmin,xmax
00467     include 'G2dAG2.fd'
00468
00469     cxydmin(1)= xmin
00470     cxydmax(1)= xmax
00471     return
00472 end
00473
00474
00475
00476     subroutine dlimy (ymin,ymax)
00477     implicit none
00478     real ymin,ymax
00479     include 'G2dAG2.fd'
00480
00481     cxydmin(2)= ymin
00482     cxydmax(2)= ymax
00483     return
00484 end
00485
00486
00487
00488     subroutine slimx (ixmin,ixmax)
00489     implicit none
00490     integer ixmin,ixmax
00491     include 'G2dAG2.fd'
00492
00493     cxysmin(1)= ixmin
00494     cxysmax(1)= ixmax
00495     return
00496 end
00497
00498
00499
00500     subroutine slimy (iymin,iymax)
00501     implicit none
00502     integer iymin,iymax
00503     include 'G2dAG2.fd'
00504
00505     cxysmin(2)= iymin
00506     cxysmax(2)= iymax

```

```

00507      return
00508      end
00509
00510
00511
00512      subroutine place (ipar)
00513      implicit none
00514      include 'G2dAG2.fd'
00515      integer ipar
00516
00517      integer postab (4,13)      ! Koordinaten des Zeichenbereiches
00518      data postab /150,900, 125,700,
00519      2      150,850, 525,700,
00520      3      150,850, 150,325,
00521      4      150,450, 525,700,
00522      5      650,950, 525,700,
00523      6      150,450, 150,325,
00524      7      650,950, 150,325,
00525      8      150,325, 525,700,
00526      9      475,650, 525,700,
00527      a      800,975, 525,700,
00528      1      150,325, 150,325,
00529      2      475,650, 150,325,
00530      3      800,975, 150,325/
00531      save postab
00532
00533      if ((ipar .ge. 1) .and. (ipar.le.13)) then
00534      cxysmin(1)= postab(1,ipar)
00535      cxysmax(1)= postab(2,ipar)
00536      cxysmin(2)= postab(3,ipar)
00537      cxysmax(2)= postab(4,ipar)
00538      end if
00539      return
00540      end
00541
00542
00543
00544      subroutine xtype (ipar)
00545      implicit none
00546      integer ipar
00547      include 'G2dAG2.fd'
00548
00549      if ((ipar .ge. 1) .and. (ipar .le. 8)) then
00550      cxytype(1)= ipar
00551      end if
00552      return
00553      end
00554
00555
00556
00557      subroutine ytype (ipar)
00558      implicit none
00559      integer ipar
00560      include 'G2dAG2.fd'
00561
00562      if ((ipar .ge. 1) .and. (ipar .le. 8)) then
00563      cxytype(2)= ipar
00564      end if
00565      return
00566      end
00567
00568
00569
00570      subroutine xwidth (ipar)
00571      implicit none
00572      integer ipar
00573      include 'G2dAG2.fd'
00574
00575      if (ipar .ge. 0) then
00576      cxywidth(1)= ipar
00577      end if
00578      return
00579      end
00580
00581
00582
00583      subroutine ywidth (ipar)
00584      implicit none
00585      integer ipar
00586      include 'G2dAG2.fd'
00587
00588      if (ipar .ge. 0) then
00589      cxywidth(2)= ipar
00590      end if
00591      return
00592      end
00593

```

```

00594
00595
00596     subroutine xetyp (ipar)
00597     implicit none
00598     integer ipar
00599     include 'G2dAG2.fd'
00600
00601     if ((ipar .ge. 0) .and. (ipar .le. 4)) then
00602         cxyetyp(1)= ipar
00603     end if
00604     return
00605 end
00606
00607
00608
00609     subroutine yetyp (ipar)
00610     implicit none
00611     integer ipar
00612     include 'G2dAG2.fd'
00613
00614     if ((ipar .ge. 0) .and. (ipar .le. 4)) then
00615         cxyetyp(2)= ipar
00616     end if
00617     return
00618 end
00619
00620
00621
00622     subroutine setwin
00623     implicit none
00624     include 'G2dAG2.fd'
00625
00626     call twindo (cxysmin(1),cxysmax(1), cxysmin(2),cxysmax(2))
00627     call dwindo (cxydmin(1),cxydmax(1), cxydmin(2),cxydmax(2))
00628     if (cxytype(1) .eq. 2) then
00629         if (cxytype(2) .eq. 2) then
00630             call logtrn (3)
00631         else
00632             call logtrn (1)
00633         end if
00634     else if (cxytype(2) .eq. 2) then
00635         call logtrn (2)
00636     else
00637         call llntrn
00638     end if
00639     return
00640 end
00641
00642
00643
00644     subroutine dinitx
00645     implicit none
00646     include 'G2dAG2.fd'
00647
00648     cxydmin(1)= 0.           ! Datenbereich
00649     cxydmax(1)= 0.
00650     cxywidth(1)= 0           ! Dezimalstellen
00651     cxydec(1)= 0             ! Dezimalstellen
00652     cxyepon(1)= 0           ! Exponent Label
00653     return
00654 end
00655
00656
00657
00658     subroutine dinity
00659     implicit none
00660     include 'G2dAG2.fd'
00661
00662     cxydmin(2)= 0.           ! Datenbereich
00663     cxydmax(2)= 0.
00664     cxywidth(2)= 0           ! Dezimalstellen
00665     cxydec(2)= 0             ! Dezimalstellen
00666     cxyepon(2)= 0           ! Exponent Label
00667     return
00668 end
00669
00670
00671
00672     subroutine hbarst (ishade,iwbar,idbar)
00673     implicit none
00674     integer ishade,iwbar,idbar
00675     include 'G2dAG2.fd'
00676
00677     cline= -3
00678     if ((ishade .ge. 0).and. (ishade .le. 15)) csymb1= ishade
00679     csizes= real(idbar)
00680     csizel= real(iwbar)

```

```

00681
00682     if (cxyfrm(2) .eq. 5) then
00683         cxyfrm(2)= 2
00684     else if (cxyfrm(2) .eq. 6) then
00685         cxyfrm(2)= 1
00686     end if
00687     return
00688 end
00689
00690
00691
00692 subroutine vbarst (ishade,iwbar,idbar)
00693 implicit none
00694 integer ishade,iwbar,idbar
00695 include 'G2dAG2.fd'
00696
00697 cline= -2
00698 if ((ishade .ge. 0) .and. (ishade .le. 15)) csymb1= ishade
00699 csizes= real(idbar)
00700 csizel= real(iwbar)
00701 if (cxyfrm(1) .eq. 5) then
00702     cxyfrm(1)= 2
00703 else if (cxyfrm(1) .eq. 6) then
00704     cxyfrm(1)= 1
00705 end if
00706 return
00707 end
00708
00709
00710
00711 C
00712 C Berechnung der Commonvariablen
00713 C
00714 subroutine binitt
00715 implicit none
00716 integer ih
00717 include 'G2dAG2.fd'
00718
00719 cline= 0
00720 csymb1= 0
00721 csteps= 1
00722 cinfin= 1.e30
00723 cnpts= 0
00724 cstepl= 1
00725 cnumbr= 0
00726 csizes= 1.
00727 csizel= 1.
00728
00729 cxyneat(1)= .true.
00730 cxyneat(2)= .true.
00731 cxyzero(1)= .true.
00732 cxyzero(2)= .true.
00733 cxyloc(1)= 0
00734 cxyloc(2)= 0
00735 cxylab(1)= 1
00736 cxylab(2)= 1
00737 cxyden(1)= 8
00738 cxyden(2)= 8
00739 cxytics(2)= 0
00740 cxytics(2)= 0
00741
00742 call csize (ih,cxylen(1))
00743 cxylen(2)= cxylen(1)
00744
00745 cxyfrm(1)= 5
00746 cxyfrm(2)= 5
00747 cxymtcs(1)= 0
00748 cxymtcs(2)= 0
00749 cxymfrm(1)= 2
00750 cxymfrm(2)= 2
00751 cxydec(1)= 0
00752 cxydec(2)= 0
00753 cxydmin(1)= 0.
00754 cxydmin(2)= 0.
00755 cxydmax(1)= 0.
00756 cxydmax(2)= 0.
00757
00758 cxysmin(1)= 150
00759 cxysmin(2)= 125
00760 cxysmax(1)= 900
00761 cxysmax(2)= 700
00762
00763 cxytype(1)= 1
00764 cxytype(2)= 1
00765 cxylsig(1)= 0
00766 cxylsig(2)= 0
00767 cxywidth(1)= 0

```

```

00768      cxywidth(2)= 0
00769      cxyepon(1)= 0
00770      cxyepon(2)= 0
00771      cxystep(1)= 1
00772      cxystep(2)= 1
00773      cxystag(1)= 1
00774      cxystag(2)= 1
00775      cxyetyp(1)= 0
00776      cxyetyp(2)= 0
00777      cxybeg(1)= 0
00778      cxybeg(2)= 0
00779      cxyend(1)= 0
00780      cxyend(2)= 0
00781      cxymbeg(1)= 0
00782      cxymbeg(2)= 0
00783      cxymend(1)= 0
00784      cxymend(2)= 0
00785      cxyamin(1)= 0.
00786      cxyamin(2)= 0.
00787      cxyamax(1)= 0.
00788      cxyamax(2)= 0.
00789      return
00790      end
00791
00792
00793
00794 C
00795 C  Datenanalyse
00796 C
00797
00798      subroutine check (x,y)
00799      implicit none
00800      real x(5),y(5)
00801      include 'G2dAG2.fd'
00802
00803      external SPREAD ! External wg. Namenskonflikt FTN90-Intrinsic
00804
00805      call typck (1,x)
00806      call rgchek(1,x)
00807      call optim (1)
00808      call width (1)
00809      if (cxystag(1) .eq. 1) call spread (1)
00810      call tset (1)
00811
00812      call typck (2,y)
00813      call rgchek(2,y)
00814      call optim(2)
00815      call width(2)
00816      if (cxystag(2) .eq. 1) call spread (2)
00817      call tset (2)
00818      return
00819      end
00820
00821
00822
00823      subroutine typck (ixy, arr)
00824      implicit none
00825      integer ixy
00826      real arr(5)
00827      integer i
00828      include 'G2dAG2.fd'
00829
00830      if ((cxytype(ixy) .lt. 3) .or. (nint(arr(1)) .lt. -1 )) then
00831      if ((cnpts .ne. 0) .or. (nint(arr(1)) .ne. -2) ) return
00832      i= nint(arr(3))
00833      if ( i .eq. 1) then
00834      cxytype(ixy)= 8
00835      else if ( i .eq. 4) then
00836      cxytype(ixy)= 7
00837      else if ( i .eq. 12) then
00838      cxytype(ixy)= 6
00839      else if ( i .eq. 13) then
00840      cxytype(ixy)= 5
00841      else if ( i .eq. 52) then
00842      cxytype(ixy)= 4
00843      else if ( i .eq. 365) then
00844      cxytype(ixy)= 3
00845      end if
00846      else
00847      cxytype(ixy)= 1
00848      end if
00849      return
00850      end
00851
00852
00853
00854      subroutine rgchek (ixy,arr)

```

```

00855      implicit none
00856      integer ixy
00857      real arr(5)
00858      real amin, amax
00859      include 'G2dAG2.fd'
00860
00861      if (cxydmax(ixy) .eq. cxydmin(ixy)) then ! Bereich schon bestimmt?
00862      if (cxyzzero(ixy)) then ! Nullpunktunterdrueckung?
00863      amin= cinfin
00864      else
00865      amin= 0.
00866      end if
00867      amax= -amin
00868      call mnmx (arr, amin, amax)
00869      if (amax .eq. amin) then
00870      amin= amin - 0.5
00871      amax= amax + 0.5
00872      end if
00873      cxydmin(ixy)= amin
00874      cxydmax(ixy)= amax
00875      end if
00876      return
00877      end
00878
00879
00880
00881      subroutine mnmx (arr,amin,amax)
00882      implicit none
00883      real arr(5), amin,amax, aminmax
00884      integer i, itype, nstart,nlim
00885      include 'G2dAG2.fd'
00886
00887      if (cnpts .eq. 0) then                                ! Tek Standard-Format
00888      nlim= nint(arr(1)) + 1
00889      nstart= 2
00890      else
00891      nlim= cnpts
00892      nstart= 1
00893      end if
00894      if ((arr(1) .lt. 0.) .and. (cnpts .eq. 0)) then ! Kurzformate
00895      itype= abs(arr(1))
00896      if (itype .eq. 1) then
00897      aminmax= arr(3) + (arr(2)-1.) * arr(4)
00898      amin= aminl(arr(3),aminmax,amin)
00899      amax= amaxl(arr(3),aminmax,amax)
00900      else if (itype .eq. 2) then
00901      call cmnmx (arr,amin,amax)
00902      else
00903      call umnmx (arr,amin,amax)
00904      end if
00905      else                                ! Langformate
00906      if (nstart .le. nlim) then
00907      do 100 i= nstart, nlim
00908      if (arr(i) .lt. cinfin) then
00909      if (arr(i).lt. amin) amin= arr(i)
00910      if (arr(i).gt. amax) amax= arr(i)
00911      end if
00912 100    continue
00913      end if
00914      end if
00915      return
00916      end
00917
00918
00919
00920      subroutine cmnmx (arr,amin,amax)
00921      implicit none
00922      real arr(5), amin, amax
00923      integer nTage, iStUBGC, nIntv, iadj, imin,imax
00924      integer minTg,minJr, maxTg,maxJr
00925
00926
00927      nintv= nint(arr(3))
00928      if ((nintv .eq. 52).or.(nintv .eq. 13).or.(nintv .eq. 4)) then
00929      if (nintv .eq. 52) then                                ! Wochen
00930      ntage=7
00931      else if (nintv .eq. 13) then                            ! 28 Tagemonat
00932      ntage= 28
00933      else if (nintv .eq. 4) then                            ! Quartal
00934      ntage=91
00935      end if
00936      call iubgc (nint(arr(4)),1, istubgc) ! Start: Jahr=arr(4), Tag=1
00937      iadj= mod(istubgc,7)
00938      if (iadj .gt. 3) iadj=iadj-7
00939      imin= istubgc-iadj + nint(arr(5))*ntage ! Min= f(Startjahr,StartIntervall)
00940      imax= imin + nint(arr(2))*ntage
00941

```

```

00942     else
00943         if (nintv .eq. 1) then ! Jahre
00944             mintg= 1
00945             maxtg= 1
00946             minjr= nint(arr(4))+1
00947             maxjr= nint(arr(4)+arr(2))
00948         else if ( nintv .eq. 12) then ! Monate
00949             call ymdyd (minjr,mintg, nint(arr(4)),nint(arr(5))+1,1)
00950             call ymdyd (maxjr,maxtg, nint(arr(4)),nint(arr(5)+arr(2)),1)
00951         else if ( nintv .eq. 365) then ! Tage
00952             minjr= nint(arr(4))
00953             mintg= nint(arr(5))
00954             maxjr= nint(arr(4))
00955             maxtg= nint(arr(5)+arr(2)) -1
00956         end if
00957         call iubgc (minjr,mintg, imin)
00958         call iubgc (maxjr,maxtg, imax)
00959     end if
00960     if (real(imax) .gt. amax) amax= real(imax)
00961     if (real(imin) .lt. amin) amin= real(imin)
00962     return
00963 end
00964
00965
00966
00967 C
00968 C   Ticmarkoptimierung
00969 C
00970
00971     subroutine optim (ixy)
00972     implicit none
00973     integer ixy
00974     include 'G2dAG2.fd'
00975
00976     if (cxytype(ixy) .eq. 2) cxylab(ixy)= 2
00977     if (cxylab(ixy) .eq. 2) cxylab(ixy)= cxytype(ixy)
00978     if (cxytype(ixy) .le. 2) then
00979         call loptim (ixy) ! Tic-Mark Optimierung fuer lineare und log. Daten
00980     else
00981         call coptim (ixy) ! Tic-Mark Optimierung fuer Kalenderdaten
00982     end if
00983     return
00984 end
00985
00986
00987
00988     subroutine loptim (ixy)
00989     implicit none
00990     integer ixy ,i, labtyp, ntics, lsig, mtcs
00991     real dataint, amin,amax, aminor,amaxor, sigfac
00992     integer idataint
00993     integer mintic
00994     integer LINWDT, LINHGT
00995     real ROUND, ROUNDU
00996     include 'G2dAG2.fd'
00997
00998     labtyp=abs( cxylab(ixy)) ! <0: Userlabel
00999     if (labtyp .le. 1) labtyp= cxytype(ixy) ! Default: Achsentyp = Datentyp
01000
01001     amin= cxydmin(ixy)
01002     amax= cxydmax(ixy)
01003     ntics= abs(cxytics(ixy)) ! Anzahl >=1, 0= Flag fuer autoscale
01004     mintic= 0
01005
01006     if (labtyp .eq. 2) then ! logarithmische Achsen
01007         amin= log10(max(amin,1./cinf)) + 1.e-7 ! > 0 => log10 definiert
01008         amax= log10(amax)
01009     end if
01010
01011     aminor= amin
01012     amaxor= amax
01013
01014     if (ntics .eq. 0) then ! = F( X-Achsenlaenge,Buchstabengroesse)
01015         if (ixy.eq.1) then
01016             i= linwdt(8) ! 100 + LINWDT(3)
01017         else
01018             i= linhgt(3) ! 50 + LINHGT(3)
01019         end if
01020         ntics= (cxysmax(ixy) - cxysmin(ixy)) / i
01021         if (ntics .lt. 1) ntics= 1
01022     end if
01023     dataint= abs(amax-amin) / real(ntics)
01024
01025 310 continue ! repeat...
01026     if (labtyp .eq. 2) dataint= roundu(dataint,1.) ! logarithmische Achsen
01027     lsig= roundd(log10(dataint),1.) ! Anzahl signifikanter Nachkommastellen
01028     sigfac=10.**(lsig)

```

```

01029      if (cxyneat(ixy)) then ! Achsenteilung aus Tabelle
01030      if (labtyp .ne. 2) then ! nicht bei log. Achsen
01031          if ((dataint/sigfac) .le. 1.) then
01032              dataint= 1. * sigfac
01033              mintic= 10
01034          else if ((dataint/sigfac) .le. 2.) then
01035              dataint= 2. * sigfac
01036              mintic= 2
01037          else if ((dataint/sigfac) .le. 2.5) then
01038              dataint= 2.5 * sigfac
01039              mintic= 5
01040              lsig=lsig-1
01041          else if ((dataint/sigfac) .le. 5.) then
01042              dataint= 5. * sigfac
01043              mintic= 5
01044          else if ((dataint/sigfac) .le. 10.) then
01045              dataint= 10. * sigfac
01046              mintic= 10
01047              lsig=lsig+1
01048          else
01049              dataint= cinfin
01050              mintic= 0
01051          end if
01052      end if ! log. Achse
01053      else ! .not. neat
01054          lsig=lsig-2
01055      end if
01056      if (lsig .ge. 0) lsig=lsig+1
01057      if (cxyneat(ixy) .or. (labtyp .eq. 2) ) then ! ... until
01058          amin= roundd(amin+.01*sigfac,dataint) !   runde auf TicIntervall
01059          amax= roundu(amax-.01*sigfac,dataint) ! .01*sigfac= Genauigkeit Plot
01060          ntics= int(abs(amax-amin)/dataint+.0001)
01061          if (cxytics(ixy) .ne. 0) then ! until: ntics nicht vorbesetzt oder = vorbesetzt
01062              if (abs(cxytics(ixy)) .lt. ntics) then
01063                  dataint= dataint * 1.1
01064                  amin=aminor
01065                  amax=amaxor
01066                  goto 310 ! noch eine Iterationsschleife
01067              else if (abs(cxytics(ixy)) .gt. ntics) then
01068                  ntics= abs(cxytics(ixy))
01069                  amax= amin + real(ntics) * dataint
01070              end if ! abs(cxytics(ixy)) .eq. ntics: no action
01071          end if
01072      end if
01073      cxytics(ixy)= ntics
01074
01075      if ((cxymtcs(ixy) .eq. 0) .and. (cxyden(ixy) .ge. 6)) then ! unbesetzt oder wenig TICS
01076          mtcs= mintic ! Bestimmung Minor TicMarcs
01077          if (mtcs .eq. 10) .or. (labtyp .eq. 2)) then
01078              if (cxyden(ixy) .lt. 9) mtcs=5
01079              if (cxyden(ixy) .lt. 7) mtcs=2
01080          if (labtyp .eq. 2) then ! log. Achsen
01081              idataint= nint(dataint)
01082              if (idataint .ne. 1) then ! mehrere Achsenintervalle
01083                  i= 1
01084 320          continue ! repeat...
01085                  mtcs= idataint/i
01086                  if ((mtcs*i .ne. idataint) .and. (i .lt. (idataint-1))) then ! ...until
01087                      i= i+1
01088                      goto 320
01089                  else if (mtcs .gt. 10 ) then
01090                      mtcs= 0 ! Failure
01091                  end if
01092              else ! einzelne logarithmische Dekade
01093                  if ((cxysmax(ixy) - cxysmin(ixy)) .ge. 100* ntics) mtcs=-1 ! logarithm. Tics
01094                  if ((cxysmax(ixy) - cxysmin(ixy)) .ge. 20* linhgt(1)) mtcs=-2 ! Label
01095              end if
01096          end if
01097      end if
01098      cxymtcs(ixy)= mtcs
01099  end if
01100
01101      cxylsig(ixy)= lsig
01102      cxyamin(ixy)= amin
01103      cxyamax(ixy)= amax
01104      if (labtyp .eq. 2) then ! logarithmische Achsen: Wiederherstellung der Originalwerte
01105          amax=10.**amax
01106          amin=10.**amin
01107      end if
01108      cxydmin(ixy)= amin
01109      cxydmax(ixy)= amax
01110      return
01111  end
01112
01113
01114
01115      subroutine coptim (ixy)

```



```

01116      implicit none
01117      integer ixy , labtyp, ntics
01118      real dataint, amin,amax, aminor,amaxor
01119      integer LINWDT
01120      real ROUND, ROUNDU
01121      include 'G2dAG2.fd'
01122
01123      if (cxytics(ixy) .eq. 1) cxytics(ixy)= 2 ! Minimum manuelle Ticwahl: 2
01124      labtyp=abs( cxylab(ixy)) ! <0: Userlabel
01125      if (labtyp .le. 1) labtyp= cxytype(ixy) ! Default: Achsentyp = Datentyp
01126      amin= cxydmin(ixy)
01127      amax= cxydmax(ixy)
01128      call calcon (amin,amax,labtyp,.true.) ! Konvertiere UBGC -> Labelzeiteinheit
01129      ntics= cxytics(ixy)
01130      aminor=amin
01131      amaxor=amax
01132      if (ntics .eq. 0) then ! = F( X-Achsenlaenge,Buchstabengroesse)
01133        ntics= (cxysmax(ixy) - cxysmin(ixy)) / (25 + linwdt(1))
01134        if (ntics .lt. 2) ntics= 2
01135      end if
01136      dataint= abs(amax-amin) / real(ntics)
01137
01138      if (cxyneat(ixy)) then ! Achsentheilung aus Tabelle
01139 310    continue ! repeat...
01140        if (cxytics(ixy) .eq. 0) then ! keine manuelle Belegung erfolgt
01141          if (labtyp.eq.3) then ! Labeltyp: Tage
01142            if (dataint .le. 1.) then
01143              dataint= 1.
01144            else if (dataint .le. 7.) then
01145              dataint= 7.
01146            else if (dataint .le. 14.) then
01147              dataint= 14.
01148            else if (dataint .le. 28.) then
01149              dataint= 28.
01150            else if (dataint .le. 56.) then
01151              dataint= 56.
01152            else if (dataint .le. 128.) then
01153              dataint= 128.
01154            end if ! dataint > 128 -> unveraendert
01155          else if (labtyp.eq.4) then ! Labeltyp: Wochen
01156            if (dataint .le. 1.) then
01157              dataint= 1.
01158            else if (dataint .le. 2.) then
01159              dataint= 2.
01160            else if (dataint .le. 4.) then
01161              dataint= 4.
01162            else if (dataint .le. 8.) then
01163              dataint= 8.
01164            else if (dataint .le. 16.) then
01165              dataint= 16.
01166            else if (dataint .le. 26.) then
01167              dataint= 26.
01168            else if (dataint .le. 52.) then
01169              dataint= 52.
01170            else if (dataint .le. 104.) then
01171              dataint= 104.
01172            end if ! dataint -> unveraendert
01173          else if (labtyp.eq.5) then ! Labeltyp: Kalenderabschnitte
01174            if (dataint .le. 1.) then
01175              dataint= 1.
01176            else if (dataint .le. 2.) then
01177              dataint= 2.
01178            else if (dataint .le. 13.) then
01179              dataint= 13.
01180            else if (dataint .le. 26.) then
01181              dataint= 26.
01182            else if (dataint .le. 52.) then
01183              dataint= 52.
01184            end if ! dataint -> unveraendert
01185          else if (labtyp.eq.6) then ! Labeltyp: Monate
01186            if (dataint .le. 1.) then
01187              dataint= 1.
01188            else if (dataint .le. 2.) then
01189              dataint= 2.
01190            else if (dataint .le. 3.) then
01191              dataint= 3.
01192            else if (dataint .le. 4.) then
01193              dataint= 4.
01194            else if (dataint .le. 6.) then
01195              dataint= 6.
01196            else if (dataint .le. 12.) then
01197              dataint= 12.
01198            else if (dataint .le. 24.) then
01199              dataint= 24.
01200            else if (dataint .le. 36.) then
01201              dataint= 36.
01202            end if ! dataint -> unveraendert

```

```

01203     else if (labtyp.eq.7) then ! Labeltyp: Quartale
01204         if (dataint .le. 1.) then
01205             dataint= 1.
01206         else if (dataint .le. 2.) then
01207             dataint= 2.
01208         else if (dataint .le. 4.) then
01209             dataint= 4.
01210         else if (dataint .le. 8.) then
01211             dataint= 8.
01212         else if (dataint .le. 12.) then
01213             dataint= 12.
01214         else if (dataint .le. 16.) then
01215             dataint= 16.
01216         else if (dataint .le. 24.) then
01217             dataint= 24.
01218         end if ! dataint -> unveraendert
01219     else if (labtyp.eq.8) then ! Labeltyp: Jahre
01220         if (dataint .le. 1.) then
01221             dataint= 1.
01222         else if (dataint .le. 2.) then
01223             dataint= 2.
01224         else if (dataint .le. 5.) then
01225             dataint= 5.
01226         else if (dataint .le. 10.) then
01227             dataint= 10.
01228         else if (dataint .le. 20.) then
01229             dataint= 20.
01230         else if (dataint .le. 50.) then
01231             dataint= 50.
01232         else if (dataint .le. 100.) then
01233             dataint= 100.
01234         end if ! dataint -> unveraendert
01235     end if ! labtyp 3..8
01236 end if ! manuelle Vorbesetzung
01237 amin= roundd(amin,dataint) ! runde auf TicIntervall
01238 amax= roundu(amax,dataint)
01239 ntics= ifix(abs(amax-amin)/dataint+.0001)
01240 if (ntics .eq. 0) ntics = 2
01241 if(cxytics(ixy) .ne. 0) then ! until: ntics nicht oder = vorbesetzt
01242     if(abs(cxytics(ixy)) .lt. ntics) then ! Verringere Ticanzahl
01243         dataint= dataint * 1.1
01244         amin=aminor
01245         amax=amaxor
01246         goto 310 ! noch eine Iterationsschleife
01247     else if (abs(cxytics(ixy)) .gt. ntics) then ! Vergroessere Ticanzahl
01248         ntics= abs(cxytics(ixy))
01249         amax= amin + real(ntics) * dataint
01250     end if ! abs(cxytics(ixy)) .eq. ntics: no action
01251 end if ! Ende der Schleife
01252 end if ! neat
01253 cxytics(ixy)= ntics
01254 cxylsig(ixy)= 0
01255 cxyamin(ixy)= amin
01256 cxyamax(ixy)= amax
01257 call calcon (amin,amax,labtyp,.false.) ! Labelzeiteinheit -> UBGC
01258 cxydmin(ixy)= amin
01259 cxydmax(ixy)= amax
01260 return
01261 end
01262
01263
01264
01265 C
01266 C Kalenderroutinen
01267 C
01268
01269
01270
01271 real function calpnt (arr,i)
01272 implicit none
01273 integer i
01274 real arr(5)
01275 integer iy,idays, itmp
01276 integer icltyp, istyr, istper, iubgl, iweekl, nodays
01277 save icltyp, istyr, istper, iubgl, iweekl, nodays
01278
01279 if (i .eq. 1) then ! 1. Datenpunkt: Formatanalyse, Parameterberechnung
01280     istyr= nint(arr(4))
01281     istper= nint(arr(5))
01282     itmp= nint(arr(3)) ! Laenge Intervall in Tagen
01283     if (itmp .eq. 12) then ! Zeitintervall Monat
01284         icltyp= 2
01285     else if (itmp .eq. 365) then ! Zeitintervall Tage
01286         icltyp=3
01287     call iubgc (istyr,istper,iubgl)
01288     else if (itmp .eq. 52) then ! Zeitintervall Wochen
01289         icltyp= 4

```

```

01290      nodays= 7
01291      else if (itmp .eq. 13) then ! Zeitintervall 4 Wochen
01292      icltyp= 5
01293      nodays= 28
01294      else if (itmp .eq. 4) then ! Zeitintervall Quartal
01295      icltyp= 6
01296      nodays= 91
01297      else ! Zeitintervall Jahre
01298      icltyp= 1
01299      end if
01300      if (icltyp .ge. 4) then
01301      call iubgc (istyr,1,iubg1)
01302      itmp= mod(iubg1+1,7)
01303      if(itmp .gt. 3) itmp= itmp-7
01304      iweek1= iubg1-itmp
01305      iubg1= iweek1+(istper-1)*nodays
01306      end if
01307      end if ! Ende Initialisierung, jetzt Berechnung
01308
01309      if (icltyp .eq. 1) then ! Zeitintervall Jahr
01310      call iubgc (istyr+i,1,iubg1)
01311      calpnt= iubg1
01312      else if (icltyp .eq. 2) then ! Zeitintervall Monat
01313      call ymdyd (iy,idades,istyr,istper+i,1)
01314      call iubgc (iy,idades,iubg1)
01315      calpnt= iubg1 ! Zeitintervall Tage
01316      else if (icltyp .eq. 3) then
01317      calpnt= iubg1+i-1
01318      else ! Zeitintervall Wochen oder 4 Wochen
01319      calpnt= iweek1+(istper-1+i)*nodays
01320      end if
01321      return
01322      end
01323
01324
01325
01326      subroutine calcon (amin,amax,labtyp,ubgc)
01327      implicit none
01328      real amin, amax
01329      integer labtyp
01330      logical ubgc
01331      integer iubg1, iubg2, iday1, iadj, id, month1,month2 , imin,imax
01332      real dimin, dimax
01333      integer iweek1
01334      real fnoday
01335      integer iy1,iy2, iy3,iy4, idays
01336      save iweek1, fnoday
01337      save iy1,iy2, iy3, iy4, idays
01338
01339      real ROUND, ROUNDU
01340
01341      if (labtyp .le. 3) return ! nicht Kalender, bzw.Tage: keine Transformation
01342
01343      if (ubgc) then ! Konvertierung UBGC in Labeltype
01344      if ( (labtyp .eq. 4).or.(labtyp .eq. 5).or.(labtyp .eq. 7) ) then
01345      if (labtyp .eq. 4) fnoday= 7.
01346      if (labtyp .eq. 5) fnoday= 28.
01347      if (labtyp .eq. 7) fnoday= 91.
01348      iubg1=amin
01349      iubg2=amax
01350      call iubgc (iy1,idades,iubg1) ! Wochenanfang der 1.KW Startjahr
01351      iday1=iubg1-idades+1
01352      iadj=mod(iday1+1,7)
01353      if(iadj .gt. 3) iadj=iadj-7
01354      iweek1= iday1-iadj ! Merken in iweek1
01355      dimin= roundd(real(iubg1-iweek1),fnoday)
01356      dimin= dimin/fnoday+1.
01357      call iubgc (iy2,idades,iubg2)
01358      dimax= roundu(real(iubg2-iweek1),fnoday)
01359      dimax= dimax/fnoday
01360      else if (labtyp .eq. 6) then
01361      call iubgc (iy1,idades,nint(amin))
01362      call ydymd (iy1,idades,iy3,month1,id)
01363      dimin= month1
01364      call iubgc (iy2,idades,nint(amax))
01365      call ydymd (iy2,idades,iy4,month2,id)
01366      dimax= (iy4-iy3)*12+month2
01367      if(id .gt. 1) dimax=dimax+1.
01368      else if (labtyp .eq. 8) then
01369      call iubgc (iy1,idades,nint(amin))
01370      dimin= iy1
01371      call iubgc(iy2,idades,nint(amax))
01372      dimax= iy2
01373      if(idays .gt. 1) dimax=dimax+1.
01374      end if
01375      amin= dimin-1.
01376      amax= dimax-1.

```

```

01377         return
01378
01379     else ! Konvertierung Labeltype in UBGC
01380         amin=amin+1.
01381         amax=amax+1.
01382         if ((labtyp .eq. 4).or.(labtyp .eq. 5).or.(labtyp .eq. 7)) then
01383             amin= iweek1 + (nint(amin)-1) * nint(fnoday)
01384             amax= iweek1+(nint(amax)-1)*nint(fnoday)
01385         else if (labtyp .eq. 6)then
01386             iy4= iy3
01387             call ymdyd (iy1,idays,iy3,nint(amin),1)
01388             call iubgc (iy1,idays,imin)
01389             amin= imin
01390             call ymdyd (iy2,idays,iy4,nint(amax),1)
01391             call iubgc (iy2,idays,imax)
01392             amax= imax
01393         else if (labtyp .eq. 8) then
01394             call iubgc (nint(amin),1,imin)
01395             amin= imin
01396             call iubgc (nint(amax),1,imax)
01397             amax= imax
01398         end if
01399     endif
01400     return
01401 end
01402
01403
01404 subroutine ymdyd (iJulYrOut,iJulDayOut,
01405 1 iGregYrIn,iGregMonIn,iGregDayIn)
01406 implicit none
01407 integer iJulYrOut,iJulDayOut, iGregYrIn,iGregMonIn,iGregDayIn
01408 integer iJulYrIn,iJulDayIn, iGregYrOut,iGregMonOut,iGregDayOut
01409 integer iMon, LEAP
01410 integer iDatTab(12)
01411 save idattab
01412 data idattab /0,31,59,90,120,151,181,212,243,273,304,334/
01413
01414 ijulyrout= igregyrin
01415 imon= igregmonin
01416 100 if (imon .lt. 1) then ! while iMon .not. in [1..12]
01417     imon= imon + 12
01418     ijulyrout= ijulyrout-1
01419     goto 100
01420 else if (imon .gt. 12) then
01421     imon= imon -12
01422     ijulyrout= ijulyrout+1
01423     goto 100
01424 end if
01425 ijuldayout= igregdayin + idattab(imon)
01426 if (imon .gt.2) ijuldayout= ijuldayout + leap(ijulyrout)
01427 return
01428
01429 C> entry subroutine YMDYD (iJulYrIn,iJulDayIn,iGregYrOut,iGregMonOut,iGregDayOut)
01430 entry ydynd(ijulyrin,ijuldayin,
01431 1 igregyrout,igregmonout,igregdayout)
01432
01433 igregdayout= ijuldayin
01434 igregyrout= ijulyrin
01435 110 if (igregdayout .lt. 1) then ! while iGregDayOut .not. in [1..365(366)]
01436     igregyrout= igregyrout-1
01437     igregdayout= igregdayout + 365 + leap(igregyrout)
01438     goto 110
01439 else if (igregdayout .gt. 365+ leap(igregyrout)) then
01440     igregyrout= igregyrout+1
01441     igregdayout= igregdayout - 365 - leap(igregyrout)
01442     goto 110
01443 end if
01444
01445 igregmonout= int( real(igregdayout)/29.5+1.)
01446 if (igregdayout .le. idattab(igregmonout)) then
01447     if ((igregmonout .le. 2) .or.
01448 1 (igregdayout.le.(idattab(igregmonout)+leap(igregyrout)))) then
01449         igregmonout= igregmonout-1
01450     end if
01451 end if
01452 igregdayout= igregdayout- idattab(igregmonout)
01453 if (igregmonout .gt. 2) igregdayout= igregdayout -leap(igregyrout)
01454 return
01455 end
01456
01457
01458
01459 integer function leap (iyear)
01460 implicit none
01461 integer iyear
01462 if ( (mod(iyear,4) .eq. 0) .and.
01463 1 ((mod(iyear,100).ne.0) .or. (mod(iyear,400).eq.0)) ) then

```

```

01464     leap= 1
01465     else
01466         leap= 0
01467     end if
01468     return
01469 end
01470
01471
01472
01473 subroutine iubgc(iyear,iday, iubgc0)
01474     implicit none
01475     integer iyear,iday,iubgc0
01476     integer iYr1
01477
01478     iyr1= iyear-1 ! Schaltjahreskorrektur erst nach Jahresabschluss
01479     iubgc0= 365* (iyear-1901) ! Verhinderung Overflow: Offset im Faktor
01480     iubgc0= iubgc0 + int(iyr1/4) - int(iyr1/100) + int(iyr1/400)
01481     iubgc0= iubgc0 + iday -460 ! Bezugsdatum 1.1.1901= 365*1901 + 460 Schalttage
01482     return
01483 end
01484
01485
01486
01487 subroutine oubgc(iyear,iday,iubgcI)
01488     implicit none
01489     integer iyear,iday,iubgcI
01490     integer iYr1
01491
01492     iyear= int( (real(iubgcI) + 694325.99) / 365.2425 )
01493 100 continue ! Schleife der evtl. Nachiteration
01494     iyr1= iyear-1 ! Schaltjahreskorrektur erst nach Jahresabschluss
01495     iday= iubgcI + 460 - 365*(iyear-1901)
01496     iday= iday + int(iyr1/100) - int(iyr1/4) - int(iyr1/400)
01497     if (iday .lt. 1) then ! Nachiteration?
01498         iyear= iyear-1
01499         goto 100
01500     end if
01501     return
01502 end
01503
01504
01505
01506 C
01507 C Zeichenroutinen
01508 C
01509
01510 subroutine frame
01511     implicit none
01512     include 'G2dAG2.fd'
01513
01514     call movabs (cxysmax(1),cxysmin(2))
01515     call drwabs (cxysmax(1),cxysmax(2))
01516     call drwabs (cxysmin(1),cxysmax(2))
01517     call drwabs (cxysmin(1),cxysmin(2))
01518     call drwabs (cxysmax(1),cxysmin(2))
01519     return
01520 end
01521
01522
01523
01524 subroutine dsplay (x,y)
01525     implicit none
01526     real x(5),y(5)
01527
01528     call setwin
01529     call cplot (x,y)
01530     call grid
01531     call label (1)
01532     call label (2)
01533     return
01534 end
01535
01536
01537
01538 subroutine cplot (x,y)
01539     implicit none
01540     real x(5),y(5)
01541     logical symbol
01542     integer i,il, keyx, keyy, lines, linsav, icount, imax
01543     real xpoint(1), ypoint(1)
01544     real DATGET
01545     include 'G2dAG2.fd'
01546
01547     call keyset (x,keyx)
01548     call keyset (y,keyy)
01549     if (keyx .eq. 1) then ! standard long
01550         imax= x(1)

```

```

01551     else if ((keyx .ge. 2) .and. (keyx .le. 4)) then ! short
01552         imax= x(2)
01553     else ! nonstandard
01554         imax= cnpts
01555     end if
01556     if (keyy .eq. 1) then ! standard long
01557         if (imax .lt. y(1)) imax= y(1)
01558     else if ((keyx .ge. 2) .and. (keyx .le. 4)) then ! short
01559         if (imax .lt. y(2)) imax= y(2)
01560     else ! nonstandard
01561         if (imax .lt. cnpts) imax= cnpts
01562     end if
01563
01564     symbol= (csymb1 .ne. 0) .and. (cline .ne.-2) .and. (cline .ne.-3)
01565
01566     i= 1 ! Suche Startpunkt
01567 100 continue ! repeat
01568         if (i .gt. imax) return ! kein Punkt zu zeichnen
01569         xpoint(1)= datget(x,i,keyx)
01570         ypoint(1)= datget(y,i,keyy)
01571         if ((xpoint(1) .ge. cfinf) .or. (ypoint(1) .ge. cfinf)) then ! while
01572             i= i+cstepl
01573             goto 100
01574         end if
01575
01576         call movea (xpoint(1),ypoint(1))
01577         if (cline .eq. -4) call pointa (xpoint(1),ypoint(1))
01578         if (cline .lt. -10) call uline (xpoint(1),ypoint(1),1)
01579         if (cline .eq.-2 .or. cline .eq.-3) then
01580             call bar (xpoint(1),ypoint(1),cline)
01581         end if
01582         if (symbol) call bsyms (xpoint(1),ypoint(1),csymb1)
01583
01584         if (cline .eq. -1) then
01585             lines= 2
01586         else if ((cline .eq. -2) .or. (cline .eq. -3)) then
01587             lines= 3
01588         else if (cline .eq. -4) then
01589             lines=4
01590         else if (cline .lt. -10) then
01591             lines=5
01592         else
01593             lines=1 ! bei cline = 0: dash ergibt durchgezogene Linie
01594         end if
01595
01596         il= i+cstepl
01597         if (il .ge. imax) return
01598         icount= csteps
01599         linsav= lines
01600
01601         do 900 i=il,imax,cstepl
01602             xpoint(1)= datget(x,i,keyx)
01603             ypoint(1)= datget(y,i,keyy)
01604             if ((xpoint(1) .ge. cfinf) .or. (ypoint(1) .ge. cfinf)) then
01605                 if (i.gt.imax-cstepl) return ! Der letzte Punkt ist ungueltig -> done
01606                 if ((cline .ne. -2) .and. (cline .ne. 3)) lines= 2
01607             else
01608                 if (lines .eq. 1 ) then
01609                     call dasha (xpoint(1),ypoint(1), cline) ! dashed or solid
01610                 else if (lines .eq. 2 ) then
01611                     call movea (xpoint(1),ypoint(1))
01612                     lines=linsav ! restore after missing data
01613                 else if (lines .eq. 3 ) then
01614                     call bar (xpoint(1),ypoint(1),0)
01615                 else if (lines .eq. 4 ) then
01616                     call pointa (xpoint(1),ypoint(1))
01617                 else
01618                     call uline (xpoint(1),ypoint(1),i)
01619                 end if
01620                 if (symbol) then
01621                     icount=icount-1
01622                     if(icount .le. 0) then
01623                         icount= csteps
01624                         call bsyms (xpoint(1),ypoint(1),csymb1)
01625                     end if
01626                 end if
01627             end if
01628 900 continue
01629         return
01630     end
01631
01632
01633
01634     subroutine keyset (array,key)
01635     implicit none
01636     integer key
01637     integer npts

```

```

01638     real array(1)
01639     include 'G2dAG2.fd'
01640
01641     if (cnpts .ne. 0) then          ! nonstandard array
01642         key= 5
01643     else
01644         npts= nint(array(1))
01645         if (npts .ge. 0) then      ! standard long
01646             key= 1
01647         else if (npts .eq. -1) then ! short
01648             key= 2
01649         else if (npts .eq. -2) then ! short calendar
01650             key= 3
01651         else                        ! short user
01652             key= 4
01653         end if
01654     end if
01655     return
01656 end
01657
01658
01659
01660     real function datget (arr,i,key)
01661     implicit none
01662     integer i, key
01663     real calpnt, upoint
01664     real arr(5) ! Dimension 5 sonst GNU-Compilerwarnung bei dat= ...arr(5)...
01665     real dat, olddat
01666     save olddat
01667
01668     if (key.eq.1) then ! standard long
01669         dat= arr(i+1)
01670     else if (key.eq.2) then ! standard short
01671         dat= arr(3) + arr(4)*real(i-1)
01672     else if (key.eq.3) then ! short calendar
01673         dat= calpnt(arr,i)
01674     else if (key.eq.4) then ! user
01675         dat= upoint(arr,i,olddat)
01676     else if (key.eq.5) then ! non standard
01677         dat= arr(i)
01678     endif
01679     olddat= dat
01680     datget= dat
01681     return
01682 end
01683
01684
01685
01686 C Balkendiagramme
01687
01688     subroutine bar (x,y,line)
01689     implicit none
01690     real x, y
01691     integer line
01692     integer key, ix,iy, ixl,iyl,ixh,iyh
01693     real xfac, yfac
01694     logical VerticalBar
01695     integer isymb, ihalf, lspace, minx,maxx,miny,maxy, ibegx,ibegy
01696     SAVE isymb, ihalf, lspace, minx,maxx,miny,maxy, ibegx,ibegy
01697     SAVE verticalbar
01698     include 'G2dAG2.fd'
01699
01700     if (line .ne. 0) then ! Erster Aufruf -> Parameterbestimmung
01701         verticalbar= line .ne. -3
01702         isymb= csymb1
01703         ihalf= .5 * csizel
01704         lspace= csizes
01705         if (lspace .le. 1) lspace=20 ! Default: 20 Pixel Schraffur
01706         if (ihalf .lt. 2) ihalf=20 ! Default: 40 Pixel Balkenbreite
01707         if (cxysmin(1) .le. cxysmax(1)) then
01708             minx= cxysmin(1)
01709             maxx= cxysmax(1)
01710         else
01711             minx= cxysmax(1)
01712             maxx= cxysmin(1)
01713         end if
01714         if (cxysmin(2) .le. cxysmax(2)) then
01715             miny= cxysmin(2)
01716             maxy= cxysmax(2)
01717         else
01718             miny= cxysmax(2)
01719             maxy= cxysmin(2)
01720         end if
01721
01722         call seetrn(xfac,yfac, key)
01723         if (key .eq. 2) then ! logarithmische Werte
01724             ibegx= cxysmin(1)

```

```

01725         ibegy= cxysmin(2)
01726     else
01727         call wincot (0.,0.,ibegx,ibegy)
01728     end if
01729 end if
01730
01731 call wincot (x,y,ix,iy)
01732 if (verticalbar) then ! vertikale Balken
01733     iyl= min0(ibegy,iy)
01734     iyh= max0(ibegy,iy)
01735     ixl= min0(ix-ihalf,ix+ihalf)
01736     ixh= max0(ix-ihalf,ix+ihalf)
01737 else ! horizontale Balken
01738     iyl= min0(iy-ihalf,iy+ihalf)
01739     iyh= max0(iy-ihalf,iy+ihalf)
01740     ixl= min0(ibegx,ix)
01741     ixh= max0(ibegx,ix)
01742 end if
01743 ixl=max0(ixl,minx)
01744 ixh=min0(ixh,maxx)
01745 iyl=max0(iyl,miny)
01746 iyh=min0(iyh,maxy)
01747 if ((ixh-ixl .ge. 2) .and. (iyh-iyl .ge. 2)) then ! mindestens 2x2 Pxl
01748     call filbox(ixl,iyl,ixh,iyh,isymb,lspace)
01749 end if
01750 return
01751 end
01752
01753
01754
01755 subroutine filbox (minx,miny,maxx,maxy,ishade,lspace)
01756 implicit none
01757 integer minx,miny,maxx,maxy,ishade,lspace
01758 integer iminx,imaxx,iminy,imaxy
01759 integer i, ishift, idely, iymax
01760 real ximin, ximax
01761 real savcom (60)
01762
01763 iminx= min0(minx,maxx)          ! zeichne Rechteck
01764 iminy= min0(miny,maxy)
01765 imaxx= max0(minx,maxx)
01766 imaxy= max0(miny,maxy)
01767
01768 call movabs (iminx,iminy)
01769 call drwabs (imaxx,iminy)
01770 call drwabs (imaxx,imaxy)
01771 call drwabs (iminx,imaxy)
01772 call drwabs (iminx,iminy)
01773
01774 if ((ishade .le.0) .or. (ishade .gt. 15)) return ! ohne Schraffur
01775
01776 ishift= ishade / 2
01777 if ((ishade-ishift*2) .ne. 0) then ! Bit0: horizontale Schraffur
01778     i= iminy
01779 100 continue ! repeat...
01780     i= i+lspace
01781     if (i .lt. imaxy) then
01782         call movabs (iminx,i)
01783         call drwabs (imaxx,i)
01784         goto 100 ! ... until
01785     end if
01786 end if ! horizontale Schraffur gezeichnet
01787
01788 if (mod(ishift,2) .ne. 0) then ! Bit1: vertikale Schraffur
01789     i= iminx
01790 110 continue ! repeat
01791     i= i+lspace
01792     if(i .lt. imaxx) then
01793         call movabs (i,iminy)
01794         call drwabs (i,imaxy)
01795         goto 110
01796     end if ! vertikale Schraffur gezeichnet
01797 end if
01798
01799 if (ishade .ge. 4) then ! diagonale Schraffuren
01800     ximin= real(iminx)
01801     ximax= real(imaxx)
01802     call svstat (savcom) ! verwende TCS-Clipping
01803     call lintrn
01804     call dwindo (ximin,ximax,real(iminy),real(imaxy))
01805     call twindo (iminx,imaxx,iminy,imaxy)
01806
01807     if (ishade .ge. 8) then ! Bit3: diagonal fallend
01808         idely= iminx-imaxx
01809         iymax= imaxy+imaxx-iminx
01810         i= iminy+lspace
01811 120 continue ! repeat ...

```



```

01812         call movea (xmin,real(i))
01813         call drawa (xmax,real(i+idely))
01814         i= i+lspace
01815         if (i .lt. ymax) goto 120 ! ... until
01816         ishift= ishade -8
01817     else
01818         ishift= ishade
01819     end if
01820
01821     if (ishift .ge. 4) then ! Bit2: diagonal steigend
01822         idely= imaxx-iminx
01823         ymax= real(imaxy)
01824         i= iminy - idely + lspace
01825 130    continue ! repeat...
01826         call movea (xmin,real(i))
01827         call drawa (xmax,real(i+idely))
01828         i= i+lspace
01829         if (i .lt. ymax) goto 130 ! ...until
01830     end if
01831     call restat (savcom)
01832 end if ! Diagonalen
01833 return
01834 end
01835
01836
01837
01838 C Zeichnen von Symbolen
01839
01840 subroutine bsyms (x,y,isym)
01841 implicit none
01842 real x,y
01843 integer isym
01844 include 'G2dAG2.fd'
01845
01846 if (isym .ge. 0) then
01847     call symout (isym, csizes)
01848 else
01849     call users (x,y,isym)
01850 end if
01851 call movea (x,y)
01852 return
01853 end
01854
01855
01856
01857 subroutine symout (isym,fac)
01858 implicit none
01859 integer isym
01860 real fac
01861 integer ix,iy, ihorz,ivert
01862
01863 call seeloc (ix,iy)
01864 if (isym .gt. 127) then
01865     call softek (isym)
01866 else if (isym .ge. 33) then
01867     call csize (ihorz,ivert)
01868     ihorz= int( real(ihorz)*.3572)
01869     ivert= int( real(ivert)*.3182)
01870     call movrel (-ihorz,-ivert)
01871     call alfmod
01872     call toutpt (isym)
01873 else if (isym .le. 11) then
01874     call teksym (isym,fac)
01875 end if
01876 call movabs (ix,iy)
01877 return
01878 end
01879
01880
01881
01882 subroutine teksym (isym,amult)
01883 implicit none
01884 integer isym
01885 real amult
01886 integer ihalf, ifull
01887
01888 ihalf= nint(8.* amult)
01889 ifull=ihalf * 2
01890 if (isym .eq. 1) then ! Kreis
01891     call teksym1 (0, 360, 30, 8.*amult)
01892 else if (isym .eq. 2) then ! X
01893     call movrel (ihalf,ihalf)
01894     call drwrel (-ifull,-ifull)
01895     call movrel (0,ifull)
01896     call drwrel (ifull,-ifull)
01897 else if (isym .eq. 3) then ! Dreieck
01898     call teksym1 (90, 450, 120, 8.*amult)

```

```

01899     else if (isym .eq. 4) then ! Quadrat
01900         call teksym1 (45, 405, 90, 8.*amult)
01901     else if (isym .eq. 5) then ! Stern
01902         call teksym1 (90, 810, 144, 8.*amult)
01903     else if (isym .eq. 6) then ! Raute
01904         call teksym1 (90, 450, 90, 8.*amult)
01905     else if (isym .eq. 7) then ! vertikaler Balken
01906         call teksym1 (90, 270, 180, 8.*amult)
01907     else if (isym .eq. 8) then ! Kreuz
01908         call movrel (0,ihalf)
01909         call drwrel (0,-ifull)
01910         call movrel (-ihalf,ihalf)
01911         call drwrel (ifull,0)
01912     else if (isym .eq. 9) then ! Pfeil nach oben
01913         call drwrel (-2,-6)
01914         call drwrel (4,0)
01915         call drwrel (-2,6)
01916         call drwrel (0,-ifull)
01917     else if (isym .eq. 10) then ! Pfeil nach unten
01918         call drwrel (-2,6)
01919         call drwrel (4,0)
01920         call drwrel (-2,-6)
01921         call drwrel (0,ifull)
01922     else if (isym .eq. 11) then ! Durchstreichung
01923         call teksym1 (270, 630, 120, 8.*amult)
01924     end if
01925     return
01926 end

01927
01928
01929
01930 subroutine teksym1 (istart, iend, incr, siz)
01931 implicit none
01932 integer istart, iend, incr
01933 real siz
01934 integer i, mx,my,mix,miy
01935 real b
01936
01937 b= real(istart)*.01745
01938 mx= nint(siz*cos(b))
01939 my= nint(siz*sin(b))
01940 call movrel (mx,my)
01941 do 100 i= istart+incr, iend, incr
01942     b= real(i)*.01745
01943     mix= nint(siz*cos(b))
01944     miy= nint(siz*sin(b))
01945     call drwrel (mix-mx,miy-miy)
01946     mx= mix
01947     my= miy
01948 100 continue
01949 return
01950 end

01951
01952
01953
01954 C Netz und Ticmarks
01955
01956 subroutine grid
01957 implicit none
01958 integer i, mlim
01959 real xyext,xyextm, tintvl,tmntvl
01960 include 'G2dAG2.fd'
01961
01962 if (cxyfrm(2) .ne. 0) then ! Zeichnen der y-Achse
01963     i= min0(cxysmin(1),cxysmax(1)) + cxyloc(2)
01964     call movabs (i, cxysmax(2))
01965     call drwabs (i, cxysmin(2))
01966     if (cxybeg(2) .ne. cxyend(2)) then ! Zeichnen y-Ticmarks
01967         i= cxylab(2) ! Labeltyp
01968         if (i .eq. 1) i= cxytype(2) ! =1: Typ entsprechend Daten
01969         if (i .ne. 6) then ! =6 (Monate): Tics durch GLINE zeichnen lassen
01970             if(cxytics(2) .ne. 0) then
01971                 tintvl= real(cxysmax(2)-cxysmin(2)) / real( cxytics(2))
01972             end if
01973             if (cxymtcs(2) .gt. 0) tmntvl= tintvl / real(cxymtcs(2))
01974             call movabs(cxybeg(2),cxysmin(2))
01975             call drwabs(cxyend(2),cxysmin(2))
01976             xyext= real(cxysmin(2))
01977             do 100, i=1,cxytics(2)
01978                 if (cxymbeg(2) .ne. cxymend(2)) then ! Zeichnen Minor Ticmarks
01979                     mlim= cxymtcs(2)-1
01980                     xyextm= xyext
01981 110 continue ! repeat...
01982                     if (mlim.gt.0) then ! ...until mlim <= 0
01983                         xyextm= xyextm+tmntvl
01984                         call movabs (cxymbeg(2), nint(xyextm))
01985                         call drwabs (cxymend(2), nint(xyextm))

```

```

01986         mlim=mlim-1
01987         goto 110
01988     else if (mlim.lt. 0) then
01989         call logtix (2,xyext,tintvl,cxybeg(2),cxymend(2))
01990     end if
01991 end if
01992 xyext= xyext+tintvl
01993 call movabs (cxybeg(2), nint(xyext))
01994 call drwabs (cxyend(2), nint(xyext))
01995 100 continue
01996     end if ! Labtyp=6: Monate
01997 end if ! Ende Zeichnen Ticmarks
01998 end if ! Ende Zeichnen der Achse
01999
02000 if (cxyfrm(1) .ne. 0) then ! Zeichnen der x-Achse
02001     i= min0(cxysmin(2),cxysmax(2)) + cxyloc(1)
02002     call movabs (cxysmin(1), i)
02003     call drwabs (cxysmax(1), i)
02004     if (cxybeg(1) .ne. cxyend(1)) then ! Zeichnen y-Ticmarks
02005         i= cxylab(1) ! Labeltyp
02006         if (i .eq. 1) i= cxytype(1) ! =1: Typ entsprechend Daten
02007         if (i .ne. 6) then ! =6 (Monate): Tics durch GLINE zeichnen lassen
02008             if(cxytics(1) .ne. 0) then
02009                 tintvl= real(cxysmax(1)-cxysmin(1)) / real( cxytics(1))
02010             end if
02011             if (cxymtcs(1) .gt. 0) tmntvl= tintvl / real(cxymtcs(1))
02012             call movabs(cxysmin(1), cxybeg(1))
02013             call drwabs(cxysmin(1), cxyend(1))
02014             xyext= real(cxysmin(1))
02015             do 120, i=1,cxytics(1)
02016                 if (cxymbeg(1) .ne. cxymend(1)) then ! Zeichnen Minor Ticmarks
02017                     mlim= cxymtcs(1)-1
02018                     xyextm= xyext
02019 130 continue ! repeat...
02020                     if (mlim.gt.0) then ! ...until mlim <= 0
02021                         xyextm= xyextm+tmntvl
02022                         call movabs (nint(xyextm), cxymbeg(1))
02023                         call drwabs (nint(xyextm), cxymend(1))
02024                         mlim=mlim-1
02025                         goto 130
02026                     else if (mlim.lt. 0) then
02027                         call logtix (1,xyext,tintvl,cxymbeg(1),cxymend(1))
02028                     end if
02029                 end if
02030                 xyext= xyext+tintvl
02031                 call movabs (nint(xyext), cxybeg(1))
02032                 call drwabs (nint(xyext), cxyend(1))
02033 120 continue
02034     end if ! Labtyp=6: Monate
02035     end if ! Ende Zeichnen Ticmarks
02036 end if ! Ende Zeichnen der Achse
02037 return
02038 end
02039
02040
02041
02042 subroutine logtix (nbase,start,tintvl,mstart,mend)
02043 implicit none
02044 integer nbase,mstart,mend
02045 real start, tintvl
02046 integer i, logtic, ihorz, ivert, idx,idy
02047 character*1 loglab
02048 include 'G2dAG2.fd'
02049
02050 call csize (ihorz,ivert)
02051 do 100 i=2,9
02052     write (unit=loglab,fmt='(i1)') i ! Unicodefaehig durch Compilerfeature
02053     logtic= nint(log10(real(i))*tintvl + start)
02054     if (nbase .eq. 1) then ! x-Achse
02055         idx= -ihorz/3
02056         if (mstart .gt. mend) then
02057             idy= ivert
02058         else
02059             idy= -ivert
02060         end if
02061         call movabs (logtic,mend)
02062         call drwabs (logtic,mstart)
02063         if (cxymtcs(nbase) .eq. -2) then ! numerisches Ticmarklabel
02064             call movrel (idx,idy)
02065             call toutstc (loglab)
02066         end if
02067     else if (nbase .eq. 2) then ! y-Achse
02068         if (mstart .gt. mend) then
02069             idx= ihorz
02070         else
02071             idx= -ihorz
02072         end if

```

```

02073         end if
02074         idy= -ivert / 3
02075         call movabs (mend,logtic)
02076         call drwabs (mstart,logtic)
02077     end if
02078
02079     if (cxymtcs(nbase) .eq. -2) then ! numerisches Ticmarklabel
02080         call movrel (idx,idy)
02081         call toutstc (loglab)
02082     end if
02083 100 continue
02084     return
02085 end
02086
02087
02088
02089 subroutine tset (nbase)
02090 implicit none
02091 integer nbase
02092 integer IOTHER
02093 integer otherbase, near, nfar, newloc, nlen
02094 include 'G2dAG2.fd'
02095
02096 otherbase= iother(nbase)
02097 near= min0(cxysmin(otherbase), cxysmax(otherbase))
02098 nfar= max0(cxysmin(otherbase), cxysmax(otherbase))
02099 newloc= near + cxyloc(nbase)
02100 if (cxyfrm(nbase) .ne. 1) then
02101     if (newloc .lt. ((nfarm+near)/2)) then
02102         nlen= cxylen(nbase)
02103     else
02104         nlen= -cxylen(nbase)
02105         nfar= near
02106     end if
02107     call tset2 (newloc,nfar,nlen,cxyfrm(nbase),
02108 1 cxybeg(nbase),cxyend(nbase))
02109 else
02110     cxybeg(nbase)= 0
02111     cxyend(nbase)= 0
02112 end if
02113
02114 if ((cxymfrm(nbase) .ne. 1) .and. (cxymtcs(nbase) .ne. 0)) then
02115     nlen= nlen / 2
02116     call tset2 (newloc,nfar,nlen,cxymfrm(nbase),
02117 1 cxymbeg(nbase),cxymend(nbase))
02118 else
02119     cxymbeg(nbase)= 0
02120     cxymend(nbase)= 0
02121 end if
02122 return
02123 end
02124
02125
02126
02127 subroutine tset2 (newloc,nfar,nlen,nfrm,kstart,kend)
02128 implicit none
02129 integer newloc,nfar,nlen,nfrm,kstart,kend
02130
02131 if (nfrm .eq. 3 .or. nfrm .eq. 6) then
02132     kstart= newloc
02133 else
02134     kstart=newloc-nlen
02135 end if
02136 if (kstart .lt. 0) then
02137     kstart= 0
02138 else if (kend .gt. 1023) then
02139     kstart= 1023
02140 end if
02141
02142 if (nfrm .eq. 2) then
02143     kend= newloc
02144 else if (nfrm .eq. 5 .or. nfrm .eq. 6) then
02145     kend = nfar
02146 else
02147     kend=newloc+nlen
02148 end if
02149 if (kend .lt. 0) then
02150     kend= 0
02151 else if (kend .gt. 1023) then
02152     kend= 1023
02153 end if
02154 return
02155 end
02156
02157
02158
02159 subroutine monpos (nbase,iy1,dpos, spos)

```

```

02160      implicit none
02161      integer nbase, iy1, spos
02162      integer iy, idays, iubgc1
02163      real dpos
02164
02165      call ymdyd (iy, idays, iy1, nint(dpos)+1, 1)
02166      call iubgc (iy, idays, iubgc1)
02167      call gline (nbase, real(iubgc1), spos)
02168      return
02169      end
02170
02171
02172
02173      subroutine gline (nbase, datapt, spos)
02174      implicit none
02175      integer nbase, spos
02176      real datapt
02177      integer i
02178      include 'G2dAG2.fd'
02179
02180      if (nbase .eq. 1) then ! x-Achsengrid
02181        call wincot (datapt, 1., spos, i)
02182        if (iabs(cxyend(1)-cxybeg(1)) .ge. 2) then
02183          call movabs(spos, cxybeg(1))
02184          call drwabs(spos, cxyend(1))
02185        end if
02186      else ! y-Achsengrid
02187        call wincot (1., datapt, i, spos)
02188        if (iabs(cxyend(2)-cxybeg(2)) .ge. 2) then
02189          call movabs(cxybeg(2), spos)
02190          call drwabs(cxyend(2), spos)
02191        end if
02192      end if
02193      return
02194      end
02195
02196
02197
02198      C Label
02199
02200      subroutine label (nbase)
02201      implicit none
02202      integer nbase
02203      logical even, stag
02204      integer i, icv, igap, iquadrant, labtyp, ilim, iposflag, ioff, iy
02205      integer ispos, isintv, iyear
02206      integer levell, level2
02207      real fnum, fac, dpos, dintv
02208      character *(255) labstr
02209      integer IOTHER
02210      include 'G2dAG2.fd'
02211
02212      labtyp= cxylob(nbase)
02213      if(labtyp .eq. 1) labtyp= cxytype(nbase) ! LabTyp=1: = dataType
02214      if (labtyp .eq. 0) return ! LabTyp=0: keine Label
02215
02216      fac= 10.**(-cxyepon(nbase))
02217
02218      dintv= real(cxystep(nbase)) / real(cxytics(nbase)) ! Zwischenergebnis
02219      isintv= nint(real(cxysmax(nbase)-cxysmin(nbase)) * dintv)
02220      dintv= (cxyamax(nbase)-cxyamin(nbase)) * dintv
02221
02222      call csiz (i, icv) ! nur icv = vertikale Hoehe benoetigt
02223      igap= icv / 3
02224      if (nbase.eq.1) igap= 2*igap
02225      if (iabs(cxysmax(iother(nbase))-cxysmin(iother(nbase)))
02226      1 .gt. 2* cxyloc(nbase)) then
02227        iquadrant= -1 ! untere Haelfte
02228      else
02229        iquadrant= +1
02230      end if
02231      levell= min0(cxysmax(iother(nbase)), cxysmin(iother(nbase)))
02232      1 - (igap-icv/3) + cxyloc(nbase)
02233      2 + isign(igap+cxylen(nbase), iquadrant)
02234      level2= levell + isign(icv+igap, iquadrant)
02235
02236      if (nbase .eq. 1) then ! Label links/zentriert/rechts?
02237        iposflag= 0 ! x-Achse: zentriert
02238      else
02239        iposflag= -iquadrant
02240      end if
02241
02242      stag= cxystag(nbase) .eq. 2 ! Verwendung in Schleife
02243      even= .false.
02244      ilim= cxytics(nbase) + 1
02245
02246      dpos= cxyamin(nbase)

```

```

02247      ispos= cxysmin(nbase)
02248
02249      if (iabs(labtyp) .ge. 3 .and. iabs(labtyp) .le. 8) then ! Kalenderdaten
02250          call oubgc (iyear,i,ifix(cxydmin(nbase))) ! i: Tag nicht benoetigt
02251          dpos= dpos+dintv ! 1. Tic ungelabelt
02252          ispos= ispos+isintv
02253          ilim=ilim-1
02254          if (nbase .eq. 1) iposflag= 1 ! x-Achse Kalender: rechtsbuendig
02255      end if
02256
02257      do 100 i=1,ilim, cxystep(nbase)
02258          if ((labtyp .le. 2) .or. (labtyp .ge. 8)) then
02259              fnum= dpos
02260          else ! Kalendertyp ohne Jahr
02261              if (labtyp.eq.3) then ! Tage
02262                  fnum= 7.
02263              else if (labtyp.eq.4) then ! Wochen
02264                  fnum= 52.
02265              else if (labtyp.eq.5) then ! Periods
02266                  fnum= 13.
02267              else if (labtyp.eq.6) then ! Monate
02268                  fnum= 12.
02269              else if (labtyp.eq.7) then ! Quartal
02270                  fnum= 4.
02271              end if ! Jahr wird wie linear behandelt
02272              fnum= amod(dpos-1.,fnum)+1.
02273          end if
02274
02275          if (labtyp .lt. 0) then
02276              call usesetc (fnum, cxywdth(nbase), nbase, labstr)
02277          else if ((labtyp .eq. 6) .OR. (labtyp .eq. 3)) then
02278              call alifsetc (fnum, labtyp, labstr)
02279              if (cxywdth(nbase) .lt. len(labstr)) then
02280                  labstr(cxywdth(nbase)+1:cxywdth(nbase)+1)= char(0)
02281              end if
02282              if (labtyp .eq. 6) call monpos (nbase,iyear,dpos,ispos)
02283          else
02284              call numsetc (fnum*fac,cxywdth(nbase),nbase,labstr)
02285          end if
02286          call justerc (labstr, iposflag, ioff)
02287
02288          if (nbase .eq. 1) then ! x-Achse
02289              iy= level1
02290              if (stag .and. even) iy= level2
02291              even= .not. even
02292              call notatec (ispos+ioff,iy, labstr)
02293          else ! y-Achse
02294              call notatec (level1+ioff,ispos-igap,labstr)
02295          end if
02296          dpos= dpos+dintv
02297          ispos= ispos+isintv
02298 100 continue ! end do
02299
02300      if ((labtyp .ne. 2) .and. (cxyetyp(2) .ge. 0)) then ! nicht logarithm.
02301          if (nbase .eq. 1) then ! x-Achse
02302              if (stag) level2= level2 + isign(icv+igap,iquadrant)
02303              i=(cxysmin(nbase)+cxysmax(nbase))/2.
02304              iy=level2
02305          else
02306              i= level1
02307              iy= max0(cxysmin(nbase),cxysmax(nbase)) +icv+igap
02308          end if
02309          call remlab (nbase,cxyloc(nbase),labtyp,i,iy)
02310      end if
02311      return
02312  end
02313
02314
02315
02316      subroutine numsetc (fnum,iwidth,nbase, outstr)
02317      implicit none
02318      real fnum
02319      integer iwidth,nbase
02320      character outstr *(*)
02321      integer iexp
02322      include 'G2dAG2.fd'
02323
02324      if (cxytype(nbase) .eq. 2) then
02325          if (fnum .gt. 0.) then
02326              iexp= fnum + .00005
02327          else if (fnum .lt. 0.) then
02328              iexp= fnum - .00005
02329          else
02330              iexp= 0
02331          end if
02332          call expoutc (nbase,iexp, outstr)
02333      else if ((cxytype(nbase).eq.1) .and. (cxydec(nbase).gt.0)) then

```

```

02334     call fformc (fnum,iwidth, cxydec(nbase), outstr)
02335 else
02336     call iformc (fnum,iwidth, outstr)
02337 end if
02338 return
02339 end
02340
02341
02342
02343 subroutine iformc (fnum,iwidth, outstr)
02344 implicit none
02345 real fnum
02346 integer iwidth
02347 character outstr *(*)
02348 character fmtstr *(11)
02349
02350 if (iwidth .le. 0) then ! iwidth=0: ohne Label
02351     outstr= char(0)
02352     return
02353 end if
02354
02355 if (iwidth .gt. 99) goto 200 ! ErrorHandler
02356 write (unit=fmtstr,fmt=100, err=200) iwidth
02357 if (len(outstr) .gt. iwidth) then
02358     write (unit= outstr, fmt=fmtstr, err=200) nint(fnum),0 ! 0: End of String
02359 else
02360     write (unit= outstr, fmt=fmtstr, err=200) nint(fnum) ! evtl. ohne EoS?
02361 end if
02362
02363 return
02364
02365 200 continue ! Error Handler
02366 outstr= '???'
02367 if (iwidth.lt.len(outstr)) outstr(iwidth+1:iwidth+1)= char(0)
02368 return
02369
02370 100 format ('(SS,I' ,i2.2, ',A1)')
02371 end
02372
02373
02374
02375 subroutine fformc (fnum,iwidth,idec, outstr)
02376 implicit none
02377 real fnum
02378 integer iwidth,idec
02379 character outstr *(*)
02380 integer nDgtM
02381 real fa
02382 include 'G2dAG2.fd'
02383
02384 ndgtm= iwidth-idec
02385 if (fnum .ge. 0.) then
02386     ndgtm= ndgtm -1 ! Ziffern Mantisse
02387 else
02388     ndgtm= ndgtm-2 ! 1 Ziffer Vorzeichen
02389 end if
02390 fa= abs(fnum) ! Skalierung mindestens 2 signifikante Stellen: .1*abs(fnum)
02391
02392 if ( ((fa .lt. 10./cinf) .or. (fa .gt. .1*idec))
02393 1 .and. (fa .lt. 10.**ndgtm)) then
02394     call fonlyc (fnum,iwidth,idec, outstr)
02395 else
02396     call eformc (fnum,iwidth,idec, outstr)
02397 end if
02398 return
02399 end
02400
02401
02402
02403 subroutine fonlyc (fnum,iwidth,idec, outstr)
02404 implicit none
02405 real fnum
02406 integer iwidth,idec
02407 character outstr *(*)
02408 character fmtstr *(14)
02409
02410 if (iwidth .le. 0) then ! iwidth=0: ohne Label
02411     outstr= char(0)
02412     return
02413 end if
02414
02415 if ((idec .gt. iwidth-1) .or. (iwidth .gt. 99)) goto 200 ! ErrorHandler
02416 write (unit=fmtstr,fmt=100, err=200) iwidth,idec
02417 if (len(outstr) .gt. iwidth) then
02418     write (unit= outstr, fmt=fmtstr, err=200) fnum,0 ! 0: End of String
02419 else
02420     write (unit= outstr, fmt=fmtstr, err=200) fnum ! evtl. ohne EoS?

```

```

02421     end if
02422     return
02423
02424 200  continue ! Error Handler
02425     outstr= '???'
02426     if (iwidth.lt.len(outstr)) outstr(iwidth+1:iwidth+1)= char(0)
02427     return
02428
02429 100  format ('(SS,F' ,i2.2,'.', i2.2,' ,A1)')
02430     end
02431
02432
02433
02434  subroutine eformc (fnum,iwidth,idec, outstr)
02435     implicit none
02436     real fnum
02437     integer iwidth,idec
02438     character outstr *(*)
02439     integer iexpon
02440     character fmtstr *(18)
02441
02442     if (iwidth .le. 0) then ! iwidth=0: ohne Label
02443         outstr= char(0)
02444         return
02445     end if
02446
02447     call esplit (fnum,iwidth,idec,iexpon)
02448     if ((idec .gt. iwidth-7) .or. (iwidth .gt. 99)) goto 200 ! ErrorHandler
02449     write (unit=fmtstr,fmt=100, err=200) iwidth-idec-6,iwidth,iwidth-7
02450     if (len(outstr) .gt. iwidth) then
02451         write (unit= outstr, fmt=fmtstr, err=200) fnum,0 ! 0: End of String
02452     else
02453         write (unit= outstr, fmt=fmtstr, err=200) fnum ! evt1. ohne EoS?
02454     end if
02455     return
02456
02457 200  continue ! Error Handler
02458     outstr= '???'
02459     if (iwidth.lt.len(outstr)) outstr(iwidth+1:iwidth+1)= char(0)
02460     return
02461
02462 100  format ('(SS,' ,i2.2,'P,E' ,i2.2,'.', i2.2,' ,A1)')
02463     end
02464
02465
02466
02467  subroutine esplit (fnum,iwidth,idec,iexpon)
02468     implicit none
02469     real fnum
02470     integer iwidth,idec,iexpon
02471     real fabs
02472     include 'G2dAG2.f.d'
02473
02474     fabs= abs(fnum)
02475     if (fabs .ge. 1.) then
02476         iexpon= ifix( alog10(fabs)+1.000005) - iwidth+idec+6 ! 6: Vorz.-Pkt-Exp(4)
02477     else if (fabs .ge. 10./cinf) then
02478         iexpon= alog10(fabs)
02479     else
02480         iexpon= -alog10(cinf)
02481     end if
02482     return
02483     end
02484
02485
02486
02487  subroutine expoutc (nbase,iexp, outstr)
02488     implicit none
02489     integer nbase,iexp, i, iL, nexp
02490     character outstr *(*), tmpstr *(4)
02491     include 'G2dAG2.f.d'
02492
02493     iL= len(outstr)
02494     nexp= abs(iexp)
02495
02496     if ( ( cxyetyp(nbase).eq.2) .and. (iL.gt. 5)
02497 1      .and. (mod(nexp,3) .eq. 0)
02498 2      .and. (iexp.ge.1) .and. (iexp.le.9) ) then ! MMMs
02499         do 20 i=3,nexp,3
02500             outstr(i/3:i/3)= 'M'
02501 20      continue
02502         outstr(nexp/3+1:)= char(39) // 'S' // char(0)
02503
02504     else if ( ( cxyetyp(nbase).eq.3) .and. (iL.gt.17)
02505 1      .and. (iexp.ge.1) .and. (iexp.le.6) ) then ! TENS
02506         if (nexp .eq. 1) then
02507             outstr= 'TENS' // char(0)

```



```

02508     else if (nexp .eq. 2) then
02509         outstr= 'HUNDREDS' // char(0)
02510     else if (nexp .eq. 3) then
02511         outstr= 'THOUSANDS' // char(0)
02512     else if (nexp .eq. 4) then
02513         outstr= 'TEN THOUSANDS' // char(0)
02514     else if (nexp .eq. 5) then
02515         outstr= 'HUNDRED THOUSANDS' // char(0)
02516     else if (nexp .eq. 6) then
02517         outstr= 'MILLIONS' // char(0)
02518     end if
02519     else if ( (cxyetyp(nbase).eq.4) ! 10000
02520 1         .and. (iexp.ge.1) .and. (iexp.le.9)
02521 2         .and. (il.ge.nexp+2)) then
02522         do 30 i=2,nexp+1
02523             outstr(i:i)= '0'
02524 30     continue
02525             outstr(1:1)= '1'
02526             outstr(nexp+2:)= char(0)
02527
02528     else if (il .gt. 7) then ! Default: Superscript EXP
02529         if (iexp .ne. 1) then
02530             if (nexp .lt. 10) then
02531                 i=1
02532             else
02533                 i=2
02534             end if
02535             if (iexp .lt. 0) then
02536                 i= i+1
02537             end if
02538             call iformc (real(iexp), i, tmpstr)
02539         else
02540             tmpstr= char(0) ! 10 wird ohne Exponenten 1 ausgegeben
02541         end if
02542         if (iexp .ne. 0) then
02543             if (cxytype(nbase) .ne. 2) then
02544                 outstr(1:1)= 'x'
02545                 i= 2
02546             else
02547                 i= 1
02548             end if
02549             outstr(i:)= '10' // char(1) ! Index UP
02550             outstr(i+3:)= tmpstr ! char(0) wird bei IFORMC angehaengt
02551         else
02552             outstr(1:)= '1' // char(0) ! 1 wird nicht als 10**0 ausgegeben
02553         end if
02554     else ! outstr zu kurz
02555         outstr= '???'
02556     end if
02557
02558     return
02559 end
02560
02561
02562
02563 subroutine alfsetc (fnum, labtyp, string)
02564 implicit none
02565 integer inum, labtyp
02566 real fnum
02567 character *(*) string
02568
02569 inum= fnum + .001 ! truncate real to integer
02570 if (labtyp .eq. 3) then ! Tage
02571     if ((inum .eq. 0) .or. (inum .eq. 7)) then
02572         string= 'MONDAY' // char(0)
02573     else if (inum .eq. 1) then
02574         string= 'TUESDAY' // char(0)
02575     else if (inum .eq. 2) then
02576         string= 'WEDNESDAY' // char(0)
02577     else if (inum .eq. 3) then
02578         string= 'THURSDAY' // char(0)
02579     else if (inum .eq. 4) then
02580         string= 'FRIDAY' // char(0)
02581     else if (inum .eq. 5) then
02582         string= 'SATURDAY' // char(0)
02583     else if (inum .eq. 6) then
02584         string= 'SUNDAY' // char(0)
02585     end if
02586 else if (labtyp .eq. 6) then ! Monate
02587     if (inum .eq. 1) then
02588         string= 'JANUARY' // char(0)
02589     else if (inum .eq. 2) then
02590         string= 'FEBRUARY' // char(0)
02591     else if (inum .eq. 3) then
02592         string= 'MARCH' // char(0)
02593     else if (inum .eq. 4) then
02594         string= 'APRIL' // char(0)

```

```

02595     else if (inum .eq. 5) then
02596         string= 'MAY' // char(0)
02597     else if (inum .eq. 6) then
02598         string= 'JUNE' // char(0)
02599     else if (inum .eq. 7) then
02600         string= 'JULY' // char(0)
02601     else if (inum .eq. 8) then
02602         string= 'AUGUST' // char(0)
02603     else if (inum .eq. 9) then
02604         string= 'SEPTEMBER' // char(0)
02605     else if (inum .eq. 10) then
02606         string= 'OCTOBER' // char(0)
02607     else if (inum .eq. 11) then
02608         string= 'NOVEMBER' // char(0)
02609     else if (inum .eq. 12) then
02610         string= 'DECEMBER' // char(0)
02611     end if
02612 end if
02613 return
02614 end
02615
02616
02617
02618 subroutine notatec (ix,iy, string)
02619 implicit none
02620 integer ix, iy
02621 character *(*) string
02622 integer i, iv, is
02623 integer ISTRINGLEN
02624
02625 call csize(i,iv)      ! nur iv benoetigt
02626 call movabs(ix,iy)
02627
02628 is= 1
02629 do 100 i=1, istringlen(string)
02630     if (string(i:i) .lt. char(31) ) then
02631         if (i.gt.is) call toutstc (string(is:i-is))
02632         if (string(i:i) .eq. char(1)) call movrel (0, iv/2) ! Hochindex
02633         if (string(i:i) .eq. char(2)) call movrel (0, -iv/2) ! Index
02634         is= i+1
02635     end if
02636 100 continue
02637 if (is .le. istringlen(string)) call toutstc (string(is:))
02638 return
02639 end
02640
02641
02642
02643 subroutine vlablc (string)
02644 C
02645 C Sollte in das TCS verlagert werden, um vertikale Schrift zu erzeugen
02646 C
02647 implicit none
02648 character string*(*)
02649 integer i, icy, ix,iy
02650 integer ISTRINGLEN
02651
02652 if (istringlen(string) .le. 0) return
02653 call csize (i,icy)
02654 call seeloc (ix,iy)
02655 do 100 i=1,istringlen(string)
02656     iy= iy-icy
02657     if (iy .lt. 0) return
02658     call movabs (ix,iy)
02659     call toutpt (ichar(string(i:i)))
02660 100 continue
02661 return
02662 end
02663
02664
02665
02666 subroutine justerc (string, iPosFlag, iOff)
02667 implicit none
02668 integer iPosFlag, iOff
02669 character string*(*)
02670 integer i, iLen, nCtrl
02671 integer ISTRINGLEN, LINWDT
02672
02673 iLen= istringlen(string)
02674 nctrl= 0 ! Zaehlen der Ctrlcharacter
02675 do 100 i=1, iLen
02676     if (string(i:i) .lt. char(31) ) nctrl= nctrl+1
02677 100 continue
02678
02679 if (iposflag .lt. 0) then ! linksbuendig
02680     ioff= 0
02681 else ! rechtsbuendig und zentriert

```

```

02682      ioff= -linwdt((ilen-nctrl)*8-2)/8      ! rechtsbuendig
02683      if (iposflag.eq.0) ioff= ioff / 2      ! zentriert
02684    end if
02685
02686    return
02687  end
02688
02689
02690
02691  subroutine width (nbase)
02692    implicit none
02693    integer nbase
02694    integer labtyp
02695    include 'G2dAG2.fd'
02696
02697    labtyp= cxylab(nbase)
02698    if(labtyp .eq. 1) labtyp= cxytype(nbase) ! LabTyp=1: = dataType
02699
02700    if ((cxywdth(nbase).ne.0) .and. (labtyp.ne.1)) return ! Manuelle Vorgabe nichtlinear
02701
02702    if (labtyp.le.1) then ! lineare Achsen und anwenderdefinierte Label
02703      call lwidth (nbase)
02704
02705    else if (labtyp .eq. 2) then ! logarithmische Achsen
02706      if (cxyetyp(nbase) .le. 1) then ! 10 mit Exponent
02707        cxywdth(nbase)= 6
02708      else if (cxyetyp(nbase) .eq. 2) then ! M, MM...
02709        cxywdth(nbase)= int(alog10(abs(cxydmax(nbase)))/3. ) + 6
02710      else if (cxyetyp(nbase) .eq. 3) then ! Ausgeschriebene Worte
02711        cxywdth(nbase)= 20
02712        cxystep(nbase)= 1
02713        cxystag(nbase)= 2
02714      else if (cxyetyp(nbase) .eq. 4) then ! 1 mit 0
02715        cxywdth(nbase)= max(abs(alog10(abs(cxydmin(nbase)))),
02716 1      abs(alog10(abs(cxydmin(nbase)))) ) + 2
02717      end if
02718
02719    else if (labtyp .gt. 2) then ! Kalenderachsen
02720      if ((labtyp .eq. 3) .or. (labtyp .eq. 6)) then ! Tage oder Monate
02721        cxywdth(nbase)= 9
02722      else
02723        cxywdth(nbase)= 4
02724      end if
02725    end if
02726
02727    return
02728  end
02729
02730
02731
02732  subroutine lwidth (nbase)
02733    implicit none
02734    integer nbase
02735    integer iadj, most, least, isign,iwidth, idelta, ndec, iexp
02736    real xmax
02737    real ROUNDDD
02738    include 'G2dAG2.fd'
02739
02740    iadj= 0
02741    xmax= amax1(abs(cxydmin(nbase)),abs(cxydmax(nbase)))
02742    if (xmax .gt. 1.) then
02743      most= int(alog10(xmax) + 1.00005) ! Position Most Significant Digit
02744      iadj= 1
02745    else if (xmax .eq. 1.) then
02746      most= 0
02747    else
02748      most= int(alog10(xmax) - 0.00005)
02749    end if
02750
02751    ndec= cxydec(nbase)
02752    if (cxydec(nbase) .ne. 0) then ! Anzahl Dezimalstellen vorgegeben
02753      least= -ndec ! Entspricht Position LeastSignificant Digit
02754    else
02755      least= cxylsig(nbase)
02756    end if
02757
02758    if (cxydmin(nbase) .lt. 0.) then
02759      isign=1 ! 1 Buchstabe Vorzeichen
02760    else
02761      isign=0
02762    end if
02763
02764    if ((most .lt. 0) .or. (least .ge. 0)) then
02765      iwidth= max0(1,most)- min0(0,least) + isign
02766      if (most .lt. 0) iwidth= iwidth+1 ! 1 Dezimalpunkt
02767      if ((iwidth .gt. 5) .and. (cxyetyp(nbase) .ge. 0)) then
02768        if (cxyetyp(nbase).eq.2) then

```

```

02769         iexp= int( roundd(real(most-iadj),3.))
02770     else
02771         iexp= int( roundd(real(most-iadj),1.))
02772     end if
02773     iwidth= most-least+isign+ 2
02774     ndec= max(0,iexp-least+iadj)
02775 else
02776     ndec= max(0,-least)
02777     iexp= 0
02778 end if
02779 else
02780     iexp= 0
02781     ndec= max(0,-least)
02782     iwidth= most-least+isign+1
02783     if (most .eq. 0) iwidth= iwidth+1 ! Einbezug fuehrende Null
02784 end if
02785
02786 if ((cxywdth(nbase) .ne. 0).and.(cxywdth(nbase).lt. iwidth)) then
02787     idelta= iwidth - cxywdth(nbase) - ndec
02788     if ((ndec .gt. 0) .and. (idelta .lt. 1) ) then
02789         ndec= max(0,-idelta)
02790         iwidth= cxywdth(nbase)
02791     else
02792         iexp= iexp+idelta
02793         if(ndec .gt. 0) iexp=iexp-1
02794         iwidth= cxywdth(nbase)
02795         ndec=0
02796     end if
02797 end if
02798
02799 cxywdth(nbase)= iwidth
02800 cxydec(nbase)= ndec
02801 cxyepon(nbase)= iexp
02802 return
02803 end
02804
02805
02806
02807 subroutine remlab (nbase,iloc,labtyp,ix,iy)
02808 implicit none
02809 integer nbase, iloc, labtyp, ix, iy
02810 integer iyear1,iday1, iyear2,iday2
02811 integer iyear,imon,iday, ioff, iposflag
02812 character label *(25)
02813 include 'G2dAG2.f'
02814
02815 if (iabs(labtyp) .eq. 1) then ! lineare Daten
02816     if (cxyepon(nbase) .eq. 0) return ! kein Exponent
02817     call expoutc (nbase,cxyepon(nbase), label)
02818 else ! Kalenderdaten
02819     if ((labtyp .ge. 4) .and. (labtyp.ne.6)) then ! Wochen, Quartale, Jahre
02820         ioff= 4 ! Überlappung der Jahre vermeiden
02821     else
02822         ioff= 0
02823     end if
02824     call oubgc (iyear1,iday1, nint(cxydmin(nbase))+ioff)
02825     call oubgc (iyear2,iday2, nint(cxydmax(nbase))-ioff)
02826     if (iday2 .le. 1) iyear2=iyear2-1
02827     iday2=iday2-1
02828     call ydynd(iyear1,iday1,iyear,imon,iday)
02829
02830 if (iabs(labtyp).eq. 3) then
02831     call iformc (real(iday), 2, label(1:2))
02832     label(3:3)= ' ' ! 'dd '
02833     call alfsetc (real(imon), 6, label(4:6)) ! labtyp 6= Monate, Laenge 3
02834     label(7:7)= ' ' ! 'dd mmm '
02835     call iformc (real(iyear), 4, label(7:10)) ! 'dd mm yyyy'
02836     label(11:11)= char(0) ! evtl. Labelende
02837     if (iyear1 .lt. iyear2) then ! bei Bedarf Start und Endjahr
02838         label(11:11)= '-' ! 'dd mm yyyy-'
02839         call ydynd(iyear2,iday2,iyear,imon,iday)
02840         call iformc (real(iday), 2, label(12:13)) ! 'dd'
02841         label(14:14)= ' ' ! 'dd mm yyyy-dd '
02842         call alfsetc (real(imon), 6, label(15:17)) ! 'dd mmm'
02843         label(18:18)= ' ' ! 'dd mm yyyy-dd mmm '
02844         call iformc (real(iyear), 4, label(19:22)) ! 'dd mm yyyy-'
02845         label(23:23)= char(0)
02846     end if
02847 else
02848     call iformc (real(iyear), 4, label(1:4)) ! 'yyyy'
02849     label(5:5)= char(0)
02850     if (iyear1 .lt. iyear2) then ! bei Bedarf Start und Endjahr
02851         label(5:5)= '-' ! 'yyyy-'
02852         call iformc (real(iyear2), 4, label(6:9)) ! 'yyyy-yyyy'
02853         label(10:10)= char(0)
02854     end if
02855 end if

```

```

02856     end if
02857
02858     if ((nbase.eq.1) .or. (iloc.eq.1)) then ! X-Achse oder y Zentriert
02859         iposflag= 0
02860     else
02861         iposflag= isign(1,1-iloc)
02862     end if
02863     call justerc (label, iposflag, ioff)
02864     call notatec (ix+ioff, iy,label)
02865     return
02866 end
02867
02868
02869
02870     subroutine spread (nbase)
02871     implicit none
02872     integer nbase
02873     integer ih, labtyp, iwidth, iMaxWid
02874     integer LINWDT
02875     include 'G2dAG2.fd'
02876
02877     if (cxystag(nbase) .ne. 1) return
02878
02879     labtyp= cxylab(nbase)
02880     if ((labtyp .eq. 1) .or. (labtyp .eq. 0)) labtyp= cxytype(nbase)
02881
02882 100    continue ! outer loop
02883         if (nbase .eq. 1) then ! x-Achse
02884             iwidth= linwdt(cxywdth(nbase))
02885         else
02886             call csize(ih, iwidth)
02887         end if
02888
02889         imaxwid= iabs(cxysmax(nbase)-cxysmin(nbase))- 2*iwidth
02890         imaxwid= imaxwid* cxystep(nbase)* cxystag(nbase) / cxytics(nbase)
02891
02892         cxystep(nbase)= 1
02893         cxystag(nbase)= 1
02894
02895         if (iwidth .lt. imaxwid) return ! exit loop
02896
02897         if (nbase .eq. 1) then ! x-Achse
02898             cxystag(nbase)= 2
02899         else
02900             cxystep(nbase)= cxystep(nbase) + 1
02901         end if
02902
02903 110    continue ! inner loop
02904         if (iwidth .lt. imaxwid) return ! exit loop
02905         if (cxystep(nbase) .gt. cxytics(nbase)) return ! exit loop
02906         if (labtyp .ne. 3 .and. labtyp .ne. 6) then ! cycle inner loop
02907             cxystep(nbase)= cxystep(nbase)+1
02908             goto 110
02909         else ! cycle outer loop
02910             if (cxywdth(nbase) .eq. 3) return
02911             cxywdth(nbase)=3
02912             goto 100
02913         end if ! cycle until force exit
02914     end
02915
02916
02917
02918 C
02919 C  Tabellensuche und Rundungen
02920 C
02921
02922     real function findge (val,tab,in)
02923     implicit none
02924     integer in
02925     real val, tab(1)
02926
02927 100    if (tab(in) .lt. val) goto 110 ! while
02928         in= in-1
02929         goto 100
02930 110    continue ! endwhile
02931
02932 120    continue ! repeat
02933         in= in+1
02934         if (tab(in) .lt. val) goto 120 ! end repeat
02935         findge= tab(in)
02936         return
02937     end
02938
02939
02940
02941     real function findle (val,tab,in)
02942     implicit none

```

```

02943     integer in
02944     real val, tab(1)
02945     real valeps
02946
02947     valeps= val+ 1.e-7 ! Vergleich um 0 ermoeeglichen (Rechengenauigkeit!)
02948
02949 100   if (tab(in) .le. valeps) goto 110 ! while
02950       in= in-1
02951       goto 100
02952 110   continue ! endwhile
02953
02954 120   continue ! repeat
02955       in= in+1
02956       if (tab(in) .lt. valeps) goto 120 ! end repeat
02957       findle= tab(in-1)
02958       return
02959   end
02960
02961
02962
02963 integer function locge (ival,itab,iN)
02964 implicit none
02965 integer ival, itab(1), in
02966
02967 100   if (itab(in) .lt. ival) goto 110 ! while
02968       in= in-1
02969       goto 100
02970 110   continue ! endwhile
02971
02972 120   continue ! repeat
02973       in= in+1
02974       if (itab(in) .lt. ival) goto 120 ! end repeat
02975       locge= itab(in)
02976       return
02977   end
02978
02979
02980
02981 integer function locle (ival,itab,iN)
02982 implicit none
02983 integer ival, itab(1), in
02984
02985 100   if (itab(in) .le. ival) goto 110 ! while
02986       in= in-1
02987       goto 100
02988 110   continue ! endwhile
02989
02990 120   continue ! repeat
02991       in= in+1
02992       if (itab(in) .le. ival) goto 120 ! end repeat
02993       locle= itab(in-1)
02994       return
02995   end
02996
02997
02998
02999 real function roundd (value,finterval)
03000 implicit none
03001 real value,finterval
03002 integer ifrac
03003 real frac
03004
03005 frac= value/finterval
03006 ifrac= int(frac)
03007 if (real(ifrac) .gt. frac) ifrac= ifrac-1 ! Abrunden bei frac neg.
03008 roundd = real(ifrac) * finterval
03009 if (roundd .gt. value) roundd= value
03010 return
03011 end
03012
03013
03014
03015 real function roundu (value,finterval)
03016 implicit none
03017 real value,finterval
03018 integer ifrac
03019 real frac
03020
03021 frac= value/finterval
03022 ifrac= int(frac)
03023 if (real(ifrac) .lt. frac) ifrac= ifrac+1 ! Aufrunden bei frac pos.
03024 roundu = real(ifrac) * finterval
03025 if (roundu .lt. value) roundu= value
03026 return
03027 end
03028
03029

```

```

03030
03031 C
03032 C  Generelle Manipulationen der Commonvariablen
03033 C
03034     subroutine savcom (Array)
03035     implicit none
03036     integer array(1)
03037     include 'G2dAG2.fd'
03038
03039     integer i
03040     integer arr(1)
03041     equivalence(arr(1),cline)
03042     do 10 i=1,g2dag2l
03043         array(i)= arr(i)
03044 10    continue
03045     return
03046 end
03047
03048
03049
03050     subroutine rescom (Array)
03051     implicit none
03052     integer array(1)
03053     include 'G2dAG2.fd'
03054
03055     integer i
03056     integer arr(1)
03057     equivalence(arr(1),cline)
03058     do 10 i=1,g2dag2l
03059         arr(i)= array(i)
03060 10    continue
03061     return
03062 end
03063
03064
03065
03066     integer function iother (ipar)
03067     implicit none
03068     integer ipar
03069
03070     if (mod(ipar,2) .eq. 1) then ! ungerader Parameter=x-Achse
03071         iother= ipar+1
03072     else
03073         iother= ipar-1
03074     end if
03075     return
03076 end

```

8.3 AG2Holerith.for File Reference

Graph2D: deprecated AG2 routines.

Functions/Subroutines

- subroutine [notate](#) (ix, iy, lenchr, iarray)
- subroutine [alfset](#) (fnum, kwidth, labtyp, ilabel)
- subroutine [numset](#) (fnum, iwidth, nbase, ilabel, ifill)
- subroutine [expout](#) (nbase, iexp, ilabel, nchars, ifill)
- subroutine [hstrin](#) (iString)
- subroutine [hlabel](#) (iLen, iString)
- subroutine [vstrin](#) (iarray)
- subroutine [vlabel](#) (iLen, iString)
- subroutine [juster](#) (iLen, iString, iposflag, ifill, lenchr, ioff)
- subroutine [eform](#) (fnum, iwidth, idec, ilabel, ifill)
- subroutine [fform](#) (fnum, iwidth, idec, ilabel, ifill)
- subroutine [fonly](#) (fnum, iwidth, idec, ilabel, ifill)
- subroutine [iform](#) (fnum, iwidth, ilabel, ifill)
- integer function [ibasec](#) (iPar)
- integer function [ibasex](#) (ipar)

- integer function [ibasey](#) (ipar)
- real function [comget](#) (iPar)
- subroutine [comset](#) (iPar, val)
- subroutine [comdmp](#)

8.3.1 Detailed Description

Graph2D: deprecated AG2 routines.

Version

2.2

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Compatibility routines dealing with holerith characters and direct manipulation of common variables.

Definition in file [AG2Holerith.for](#).

8.3.2 Function/Subroutine Documentation

8.3.2.1 [alfset\(\)](#)

```
subroutine alfset (  
    real fnum,  
    integer kwidth,  
    integer labtyp,  
    integer, dimension(kwidth) ilabel )
```

Definition at line [45](#) of file [AG2Holerith.for](#).

8.3.2.2 [comdmp\(\)](#)

```
subroutine comdmp
```

Definition at line [328](#) of file [AG2Holerith.for](#).

8.3.2.3 comget()

```
real function comget (  
    integer iPar )
```

Definition at line 271 of file [AG2Holerith.for](#).

8.3.2.4 comset()

```
subroutine comset (  
    integer iPar,  
    real val )
```

Definition at line 299 of file [AG2Holerith.for](#).

8.3.2.5 eform()

```
subroutine eform (  
    real fnum,  
    integer iwidth,  
    integer idec,  
    integer, dimension(iwidth) ilabel,  
    integer ifill )
```

Definition at line 173 of file [AG2Holerith.for](#).

8.3.2.6 expout()

```
subroutine expout (  
    integer nbase,  
    integer iexp,  
    integer, dimension(nchars) ilabel,  
    integer nchars,  
    integer ifill )
```

Definition at line 90 of file [AG2Holerith.for](#).

8.3.2.7 fform()

```
subroutine fform (  
    real fnum,  
    integer iwidth,  
    integer idec,  
    integer, dimension(255) ilabel,  
    integer ifill )
```

Definition at line 189 of file [AG2Holerith.for](#).

8.3.2.8 fonly()

```
subroutine fonly (
    real fnum,
    integer iwidth,
    integer idec,
    integer, dimension(iwidth) ilabel,
    integer ifill )
```

Definition at line 205 of file [AG2Holerith.for](#).

8.3.2.9 hlabel()

```
subroutine hlabel (
    integer iLen,
    integer, dimension(iLen) iString )
```

Definition at line 121 of file [AG2Holerith.for](#).

8.3.2.10 hstrin()

```
subroutine hstrin (
    integer, dimension(2) iString )
```

Definition at line 112 of file [AG2Holerith.for](#).

8.3.2.11 ibasec()

```
integer function ibasec (
    integer iPar )
```

Definition at line 241 of file [AG2Holerith.for](#).

8.3.2.12 ibasex()

```
integer function ibasex (
    integer ipar )
```

Definition at line 251 of file [AG2Holerith.for](#).

8.3.2.13 ibasey()

```
integer function ibasey (  
    integer ipar )
```

Definition at line 261 of file [AG2Holerith.for](#).

8.3.2.14 iform()

```
subroutine iform (  
    real fnum,  
    integer iwidth,  
    integer, dimension(iwidth) ilabel,  
    integer ifill )
```

Definition at line 221 of file [AG2Holerith.for](#).

8.3.2.15 juster()

```
subroutine juster (  
    integer iLen,  
    integer, dimension(iLen) iString,  
    integer iposflag,  
    integer ifill,  
    integer lenchr,  
    integer ioff )
```

Definition at line 154 of file [AG2Holerith.for](#).

8.3.2.16 notate()

```
subroutine notate (  
    integer ix,  
    integer iy,  
    integer lenchr,  
    integer, dimension(lenchr) iarray )
```

Definition at line 30 of file [AG2Holerith.for](#).

8.3.2.17 numset()

```
subroutine numset (
    real fnum,
    integer iwidth,
    integer nbase,
    integer, dimension(iwidth) ilabel,
    integer ifill )
```

Definition at line 67 of file [AG2Holerith.for](#).

8.3.2.18 vlabel()

```
subroutine vlabel (
    integer iLen,
    integer, dimension(ilen) iString )
```

Definition at line 139 of file [AG2Holerith.for](#).

8.3.2.19 vstrin()

```
subroutine vstrin (
    integer, dimension(2) iarray )
```

Definition at line 130 of file [AG2Holerith.for](#).

8.4 AG2Holerith.for

```
00001 C> \file      AG2Holerith.for
00002 C> \version   2.2
00003 C> \author    (C) 2022 Dr.-Ing. Klaus Friedewald
00004 C> \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00005 C> \~german
00006 C> \brief     Graph2D: obsolete AG2 Routinen
00007 C> \~english
00008 C> \brief     Graph2D: deprecated AG2 routines
00009 C> \~
00010 C>
00011 C> \~german
00012 C>     Unterprogramme zur Behandlung von Holerithvariablen und direkter
00013 C>     Manipulation des Commonblocks
00014 C>
00015 C> \~english
00016 C>     Compatibility routines dealing with holerith characters
00017 C>     and direct manipulation of common variables.
00018 C>
00019 C
00020 C
00021 C   Tektronix Advanced Graphics 2 - Version 2.x
00022 C
00023 C       Optionale Unterprogramme
00024 C
00025 C
00026 C
00027 C   Stringfunktionen fuer Holerithvariablen
00028 C
00029 C
00030     subroutine notate (ix,iy,lenchr,iarray)
00031     implicit none
```

```

00032      integer ix,iy,lenchr, iarray(lenchr)
00033      integer i
00034      character *(255) buf
00035
00036      do 100 i=1,lenchr
00037          buf(i:i)= char(iarray(i))
00038 100  continue
00039      call notatec (ix,iy,buf(1:lenchr))
00040      return
00041  end
00042
00043
00044
00045      subroutine alfset (fnum,kwidth,labtyp,ilabel)
00046      implicit none
00047      integer kwidth,labtyp, ilabel(kwidth)
00048      real fnum
00049      integer i, buflen
00050      character *(255) buf
00051      integer ISTRINGLEN
00052
00053      call alfsetc (fnum, labtyp, buf)
00054      buflen= istringlen(buf)
00055      do 100 i=1,kwidth
00056          if (i .le. buflen) then
00057              ilabel(i)= ichar(buf(i:i))
00058          else
00059              ilabel(i)= ichar(' ')
00060          end if
00061 100  continue
00062      return
00063  end
00064
00065
00066
00067      subroutine numset (fnum,iwidth,nbase,ilabel,ifill)
00068      implicit none
00069      integer iwidth,nbase,ilabel(iwidth),ifill
00070      real fnum
00071      integer i, iLeadFill
00072      character *(255) buf
00073      integer ISTRINGLEN
00074
00075      call numsetc (fnum,iwidth,nbase, buf)
00076      ileadfill= max(0,iwidth-istringlen(buf))
00077      do 100 i=1,iwidth
00078          ilabel(ileadfill+i)= ichar(buf(i:i))
00079 100  continue
00080      i=1 ! iLabel ist rechtsjustiert!
00081      if (i.gt.ileadfill) goto 110 ! while
00082          ilabel(i)= ifill
00083          i= i+1
00084 110  continue ! endwhile
00085      return
00086  end
00087
00088
00089
00090      subroutine expout (nbase,iexp,ilabel,nchars,ifill)
00091      implicit none
00092      integer nbase,iexp, nchars, ilabel(nchars), ifill
00093      integer i, iLeadFill
00094      character *(255) buf
00095      integer ISTRINGLEN
00096
00097      call expoutc (nbase,iexp, buf(1:nchars))
00098      ileadfill= max(0,nchars-istringlen(buf))
00099      do 100 i=1,nchars
00100          ilabel(ileadfill+i)= ichar(buf(i:i))
00101 100  continue
00102      i=1 ! iLabel ist rechtsjustiert!
00103      if (i.gt.ileadfill) goto 110 ! while
00104          ilabel(i)= ifill
00105          i= i+1
00106 110  continue ! endwhile
00107      return
00108  end
00109
00110
00111
00112      subroutine hstrin (iString)
00113      implicit none
00114      integer iString(2)
00115      call anstr (istring(1),istring(2))
00116      return
00117  end
00118

```

```

00119
00120
00121     subroutine hlabel (iLen, iString)
00122     implicit none
00123     integer iLen, iString(iLen)
00124     call anstr (ilen, istring)
00125     return
00126     end
00127
00128
00129
00130     subroutine vstrin (iarray)
00131     implicit none
00132     integer iarray(2)
00133     call vlabel (iarray(1),iarray(2))
00134     return
00135     end
00136
00137
00138
00139     subroutine vlabel (iLen,iString)
00140     implicit none
00141     integer iLen, iString(iLen)
00142     integer i
00143     character *(255) buf
00144     integer ISTRINGLEN
00145     do 100 i=1, ilen
00146         buf(i:i)= char(istring(i))
00147 100    continue
00148     call vlabelc (buf(:ilen))
00149     return
00150     end
00151
00152
00153
00154     subroutine juster (iLen,iString,iposflag,ifill,lenchr, ioff)
00155     implicit none
00156     integer iLen,iString(iLen), iposflag,ifill, lenchr, ioff
00157     integer i
00158     character *(255) buf
00159
00160     lenchr= 0
00161     do 100 i=1, ilen
00162         if ( (i .gt. 1) .or. (istring(i) .ne. ifill) ) then ! Ueberlese Startfillchars
00163             lenchr= lenchr+1
00164             buf(lenchr:lenchr)= char(abs(istring(i))) ! Tek Index -1,-2 -> char(1),char(2)
00165         end if
00166 100    continue
00167     call justerc (buf, iposflag, ioff)
00168     return
00169     end
00170
00171
00172
00173     subroutine eform (fnum,iwidth,idec,ilabel,ifill)
00174     implicit none
00175     integer iwidth,idec, ilabel(iwidth), ifill
00176     real fnum
00177     integer i
00178     character *(255) buf
00179
00180     call eformc (fnum,iwidth,idec, buf)
00181     do 100 i=1,iwidth
00182         ilabel(i)= ichar(buf(i:i))
00183 100    continue
00184     return
00185     end
00186
00187
00188
00189     subroutine fform (fnum,iwidth,idec,ilabel,ifill)
00190     implicit none
00191     integer iwidth,idec, ilabel(255), ifill
00192     real fnum
00193     integer i
00194     character *(255) buf
00195
00196     call fformc (fnum,iwidth,idec, buf)
00197     do 100 i=1,iwidth
00198         ilabel(i)= ichar(buf(i:i))
00199 100    continue
00200     return
00201     end
00202
00203
00204
00205     subroutine fonly (fnum,iwidth,idec,ilabel,ifill)

```

```

00206      implicit none
00207      integer iwidth,idec, ilabel(iwidth), ifill
00208      real fnum
00209      integer i
00210      character *(255) buf
00211
00212      call fonlyc (fnum,iwidth,idec, buf)
00213      do 100 i=1,iwidth
00214         ilabel(i)= ichar(buf(i:i))
00215 100    continue
00216      return
00217      end
00218
00219
00220
00221      subroutine iform (fnum,iwidth,ilabel,ifill)
00222      implicit none
00223      integer iwidth,idec, ilabel(iwidth), ifill
00224      real fnum
00225      integer i
00226      character *(255) buf
00227
00228      call iformc (fnum,iwidth,idec, buf)
00229      do 100 i=1,iwidth
00230         ilabel(i)= ichar(buf(i:i))
00231 100    continue
00232      return
00233      end
00234
00235
00236
00237 C
00238 C   Direkte Manipulation des Commonblocks
00239 C
00240
00241      integer function ibasec (iPar)
00242      implicit none
00243      integer ipar
00244
00245      ibasec= -1-ipar
00246      return
00247      end
00248
00249
00250
00251      integer function ibasex (ipar)
00252      implicit none
00253      integer ipar
00254
00255      ibasex= 1 + 2*ipar
00256      return
00257      end
00258
00259
00260
00261      integer function ibasey (ipar)
00262      implicit none
00263      integer ipar
00264
00265      ibasey= 2 + 2*ipar
00266      return
00267      end
00268
00269
00270
00271      real function comget (ipar)
00272      implicit none
00273      integer ipar
00274      include 'G2dAG2.fd'
00275
00276      integer iarr(1), iarr2(1)
00277      real arr(1), arr2(1)
00278      equivalence(iarr(1),cline), (iarr2(1),cxyneat)
00279      equivalence(arr(1),cline), (arr2(1),cxyneat)
00280
00281      if ((ipar.lt.0) .and. (ipar.ge. -9))then
00282         if ((ipar .eq. -4) .or. (ipar .le. -8)) then
00283            comget= arr(-ipar)
00284         else
00285            comget= real(iarr(-ipar))
00286         end if
00287      else if ((ipar.gt.0) .and. (ipar.le.56)) then
00288         if ((ipar.le.22) .or. ((ipar .ge. 27).and.(ipar.le.52))) then
00289            comget= real(iarr2(ipar))
00290         else
00291            comget= arr2(ipar)
00292         end if

```

```

00293     end if
00294     return
00295 end
00296
00297
00298
00299 subroutine comset (iPar,val)
00300 implicit none
00301 integer iPar
00302 real val
00303 include 'G2dAG2.fd'
00304
00305 integer iarr(1), iarr2(1)
00306 real arr(1), arr2(1)
00307 equivalence(iarr(1),cline), (iarr2(1),cxyneat)
00308 equivalence(arr(1),cline), (arr2(1),cxyneat)
00309
00310 if ((ipar.lt.0) .and. (ipar.ge. -9))then
00311   if ((ipar.eq.-4) .or. (ipar.le. -8)) then
00312     arr(-ipar)= val
00313   else
00314     iarr(-ipar)= int(val)
00315   end if
00316 else if ((ipar.gt.0) .and. (ipar.le.56)) then
00317   if ((ipar.le.22) .or. ((ipar.ge. 27).and.(ipar.le.52))) then
00318     iarr2(ipar)= int(val)
00319   else
00320     arr2(ipar)= val
00321   end if
00322 end if
00323 return
00324 end
00325
00326
00327
00328 subroutine comdmp
00329 implicit none
00330 integer i
00331 character *80 buf
00332 include 'G2dAG2.fd'
00333
00334 call erase
00335 call home
00336
00337 write (unit= buf,fmt=600, err=200) (cxyneat(i),i=1,2), cline
00338 600 format (1x,' 0: cxneat(1)=' ,i14,' , (2)=' ,i14,' , cline=' ,i14)
00339 call toutstc (buf)
00340 call newlin
00341 write (unit= buf,fmt=601, err=200) (cxyzero(i),i=1,2), csymb1
00342 601 format (1x,' 1: cxyzero(1)=' ,i14,' , (2)=' ,i14,' , csymb1=' ,i14)
00343 call toutstc (buf)
00344 call newlin
00345 write (unit= buf,fmt=602, err=200) (cxyloc(i),i=1,2), csteps
00346 602 format (1x,' 2: cxyloc(1)=' ,i14,' , (2)=' ,i14,' , csteps=' ,i14)
00347 call toutstc (buf)
00348 call newlin
00349 write (unit= buf,fmt=603, err=200) (cxylab(i),i=1,2), cfinfin
00350 603 format (1x,' 3: cxylab(1)=' ,i14,' , (2)=' ,i14,' , cfinfin=' ,e14.7)
00351 call toutstc (buf)
00352 call newlin
00353 write (unit= buf,fmt=604, err=200) (cxyden(i),i=1,2), cnpts
00354 604 format (1x,' 4: cxyden(1)=' ,i14,' , (2)=' ,i14,' , cnpts=' ,i14)
00355 call toutstc (buf)
00356 call newlin
00357 write (unit= buf,fmt=605, err=200) (cxytics(i),i=1,2), cstepl
00358 605 format (1x,' 5: cxytics(1)=' ,i14,' , (2)=' ,i14,' , cstepl=' ,i14)
00359 call toutstc (buf)
00360 call newlin
00361 write (unit= buf,fmt=606, err=200) (cxylen(i),i=1,2), cnumbr
00362 606 format (1x,' 6: cxylen(1)=' ,i14,' , (2)=' ,i14,' , cnumbr=' ,i14)
00363 call toutstc (buf)
00364 call newlin
00365 write (unit= buf,fmt=607, err=200) (cxyfrm(i),i=1,2), csizes
00366 607 format (1x,' 7: cxyfrm(1)=' ,i14,' , (2)=' ,i14,' , csizes=' ,e14.7)
00367 call toutstc (buf)
00368 call newlin
00369 write (unit= buf,fmt=608, err=200) (cxymtcs(i),i=1,2), csizel
00370 608 format (1x,' 8: cxymtcs(1)=' ,i14,' , (2)=' ,i14,' , csizel=' ,e14.7)
00371 call toutstc (buf)
00372 call newlin
00373 write (unit= buf,fmt=609, err=200) (cxymfrm(i),i=1,2)
00374 609 format (1x,' 9: cxymfrm(1)=' ,i14,' , (2)=' ,i14)
00375 call toutstc (buf)
00376 call newlin
00377 write (unit= buf,fmt=610, err=200) (cxydec(i),i=1,2)
00378 610 format (1x,' 10: cxydec(1)=' ,i14,' , (2)=' ,i14)
00379 call toutstc (buf)

```



```

00380      call newlin
00381      write (unit= buf,fmt=611, err=200) (cxydmin(i),i=1,2)
00382 611 format (1x,'11: cxydmin(1)=' ,e14.7,' , (2)=' ,e14.7)
00383      call toutstc (buf)
00384      call newlin
00385      write (unit= buf,fmt=612, err=200) (cxydmax(i),i=1,2)
00386 612 format (1x,'12: cxydmax(1)=' ,e14.7,' , (2)=' ,e14.7)
00387      call toutstc (buf)
00388      call newlin
00389      write (unit= buf,fmt=613, err=200) (cxysmin(i),i=1,2)
00390 613 format (1x,'13: cxysmin(1)=' ,i14,' , (2)=' ,i14)
00391      call toutstc (buf)
00392      call newlin
00393      write (unit= buf,fmt=614, err=200) (cxysmax(i),i=1,2)
00394 614 format (1x,'14: cxysmax(1)=' ,i14,' , (2)=' ,i14)
00395      call toutstc (buf)
00396      call newlin
00397      write (unit= buf,fmt=615, err=200) (cxytype(i),i=1,2)
00398 615 format (1x,'15: cxytype(1)=' ,i14,' , (2)=' ,i14)
00399      call toutstc (buf)
00400      call newlin
00401      write (unit= buf,fmt=616, err=200) (cxylsig(i),i=1,2)
00402 616 format (1x,'16: cxylsig(1)=' ,i14,' , (2)=' ,i14)
00403      call toutstc (buf)
00404      call newlin
00405      write (unit= buf,fmt=617, err=200) (cxywdth(i),i=1,2)
00406 617 format (1x,'17: cxywdth(1)=' ,i14,' , (2)=' ,i14)
00407      call toutstc (buf)
00408      call newlin
00409      write (unit= buf,fmt=618, err=200) (cxyepon(i),i=1,2)
00410 618 format (1x,'18: cxyepon(1)=' ,i14,' , (2)=' ,i14)
00411      call toutstc (buf)
00412      call newlin
00413      write (unit= buf,fmt=619, err=200) (cxystep(i),i=1,2)
00414 619 format (1x,'19: cxystep(1)=' ,i14,' , (2)=' ,i14)
00415      call toutstc (buf)
00416      call newlin
00417      write (unit= buf,fmt=620, err=200) (cxystag(i),i=1,2)
00418 620 format (1x,'20: cxystag(1)=' ,i14,' , (2)=' ,i14)
00419      call toutstc (buf)
00420      call newlin
00421      write (unit= buf,fmt=621, err=200) (cxyetyp(i),i=1,2)
00422 621 format (1x,'21: cxyetyp(1)=' ,i14,' , (2)=' ,i14)
00423      call toutstc (buf)
00424      call newlin
00425      write (unit= buf,fmt=622, err=200) (cxybeg(i),i=1,2)
00426 622 format (1x,'22: cxybeg(1)=' ,i14,' , (2)=' ,i14)
00427      call toutstc (buf)
00428      call newlin
00429      write (unit= buf,fmt=623, err=200) (cxyend(i),i=1,2)
00430 623 format (1x,'23: cxyend(1)=' ,i14,' , (2)=' ,i14)
00431      call toutstc (buf)
00432      call newlin
00433      write (unit= buf,fmt=624, err=200) (cxymbeg(i),i=1,2)
00434 624 format (1x,'24: cxymbeg(1)=' ,i14,' , (2)=' ,i14)
00435      call toutstc (buf)
00436      call newlin
00437      write (unit= buf,fmt=625, err=200) (cxymend(i),i=1,2)
00438 625 format (1x,'25: cxymend(1)=' ,i14,' , (2)=' ,i14)
00439      call toutstc (buf)
00440      call newlin
00441      write (unit= buf,fmt=626, err=200) (cxyamin(i),i=1,2)
00442 626 format (1x,'26: cxyamin(1)=' ,e14.7,' , (2)=' ,e14.7)
00443      call toutstc (buf)
00444      call newlin
00445      write (unit= buf,fmt=627, err=200) (cxyamax(i),i=1,2)
00446 627 format (1x,'27: cxyamax(1)=' ,e14.7,' , (2)=' ,e14.7)
00447      call toutstc (buf)
00448
00449      call graphicerror (11,char(0))
00450      call erase
00451
00452 200 continue
00453      return
00454      end

```

8.5 AG2uline.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [uline](#) (x, y, i)

8.5.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2uline.for](#).

8.5.2 Function/Subroutine Documentation

8.5.2.1 [uline\(\)](#)

```
subroutine uline (
    x,
    y,
    i )
```

Definition at line 10 of file [AG2uline.for](#).

8.6 AG2uline.for

```
00001 C> \file      AG2uline.for
00002 C> \brief      Graph2D: Dummy User Routine
00003 C
00004 C  Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C      User Subroutinen
00007 C
00008
00009
00010      subroutine uline (x,y,i)
00011      return
00012      end
00013
```

8.7 AG2umnmx.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [umnmx](#) (array, amin, amax)

8.7.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2umnmx.for](#).

8.7.2 Function/Subroutine Documentation

8.7.2.1 umnmx()

```
subroutine umnmx (
    array,
    amin,
    amax )
```

Definition at line 9 of file [AG2umnmx.for](#).

8.8 AG2umnmx.for

```
00001 C> \file      AG2umnmx.for
00002 C> \brief     Graph2D: Dummy User Routine
00003 C
00004 C   Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C       User Subroutinen
00007 C
00008
00009     subroutine umnmx (array,amin,amax)
00010     return
00011     end
00012
```

8.9 AG2upoint.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- real function [upoint](#) (arr, ii, oldone)

8.9.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2upoint.for](#).

8.9.2 Function/Subroutine Documentation

8.9.2.1 upoint()

```
real function upoint (
    arr,
    ii,
    oldone )
```

Definition at line 9 of file [AG2upoint.for](#).

8.10 AG2upoint.for

```
00001 C> \file    AG2upoint.for
00002 C> \brief   Graph2D: Dummy User Routine
00003 C
00004 C Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C    User Subroutinen
00007 C
00008
00009     real function upoint (arr,ii,oldone)
00010     upoint=0.
00011     return
00012     end
```

8.11 AG2users.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [users](#) (x, y, i)

8.11.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2users.for](#).

8.11.2 Function/Subroutine Documentation

8.11.2.1 users()

```
subroutine users (
    x,
    y,
    i )
```

Definition at line 9 of file [AG2users.for](#).

8.12 AG2users.for

```

00001 C> \file      AG2users.for
00002 C> \brief     Graph2D: Dummy User Routine
00003 C
00004 C Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C      User Subroutinen
00007 C
00008
00009      subroutine users (x,y,i)
00010      return
00011      end

```

8.13 AG2useset.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [useset](#) (fnum, iwidth, nbase, labeli)

8.13.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2useset.for](#).

8.13.2 Function/Subroutine Documentation

8.13.2.1 useset()

```

subroutine useset (
    real fnum,
    integer iwidth,
    integer nbase,
    integer, dimension(1) labeli )

```

Definition at line 9 of file [AG2useset.for](#).

8.14 AG2useset.for

```

00001 C> \file      AG2useset.for
00002 C> \brief     Graph2D: Dummy User Routine
00003 C
00004 C Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C      User Subroutinen
00007 C
00008
00009      subroutine useset (fnum,iwidth,nbase,labeli)
00010      implicit none
00011      real fnum
00012      integer iwidth, nbase
00013      integer labeli(1)
00014      integer i
00015
00016      do 100 i=1, iwidth
00017          labeli(i)= 32 ! Blank
00018 100      continue
00019      return
00020      end
00021

```

8.15 AG2usesetC.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [usesetc](#) (fnum, iwidth, nbase, labstr)

8.15.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2usesetC.for](#).

8.15.2 Function/Subroutine Documentation

8.15.2.1 usesetc()

```
subroutine usesetc (
    real fnum,
    integer iwidth,
    integer nbase,
    character *(*) labstr )
```

Definition at line 9 of file [AG2usesetC.for](#).

8.16 AG2usesetC.for

```
00001 C> \file      AG2usesetC.for
00002 C> \brief      Graph2D: Dummy User Routine
00003 C
00004 C  Tektronix Advanced Graphics 2 - Version 2.0
00005 C
00006 C      User Subroutinen
00007 C
00008
00009      subroutine usesetc (fnum,iwidth, nbase, labstr)
00010      implicit none
00011      real fnum
00012      integer iwidth, nbase
00013      character *(*) labstr
00014      integer labeli(20)
00015      integer i, il, iw, ISTRINGLEN
00016
00017      iw= min(20, iwidth, istringlen(labstr))
00018      call useset (fnum,iw,nbase,labeli)
00019
00020      il= 0
00021      do 100 i=1,iw
00022          il= il+1
00023          labstr(il:il)= char(labeli(i))
00024 100 continue
00025      if (il .lt. iw) labstr(il+1:il+1)= char(0)
00026      return
00027      end
00028
```

8.17 AG2UsrSoftek.for File Reference

Graph2D: Dummy User Routine.

Functions/Subroutines

- subroutine [softek](#) (isym)

8.17.1 Detailed Description

Graph2D: Dummy User Routine.

Definition in file [AG2UsrSoftek.for](#).

8.17.2 Function/Subroutine Documentation

8.17.2.1 [softek\(\)](#)

```
subroutine softek (  
    isym )
```

Definition at line 9 of file [AG2UsrSoftek.for](#).

8.18 AG2UsrSoftek.for

```
00001 C> \file      AG2UsrSoftek.for  
00002 C> \brief      Graph2D: Dummy User Routine  
00003 C  
00004 C Tektronix Advanced Graphics 2 - Version 2.0  
00005 C  
00006 C      User Subroutinen  
00007 C  
00008  
00009      subroutine softek (isym)  
00010      return  
00011      end
```

8.19 G2dAG2.fd File Reference

Graph2D: AG2 Common Block G2dAG2.

8.19.1 Detailed Description

Graph2D: AG2 Common Block G2dAG2.

Version

2.0

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Definition in file [G2dAG2.fd](#).

8.20 G2dAG2.fd

```

00001 C> \file          G2dAG2.fd
00002 C> \brief        Graph2D: AG2 Common Block G2dAG2
00003 C> \version      2.0
00004 C> \author       (C) 2022 Dr.-Ing. Klaus Friedewald
00005 C> \copyright    GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 C
00007 C Da die folgende Definition kein Bestandteil eines Moduls
00008 C ist versagt der DOXYGEN-Parser bei der Kombination von
00009 C COMMON und integer. Workaround: \\cond ... \\endcond
00010 C> \cond
00011
00012 C Common Block G2dAG2, Version 2.0 für AG2
00013 C Die Funktion der Variablen entspricht dem Tektronix AG2 User-Manual,
00014 C jedoch sind die achsenbezogenen Variablen in einem Feld zusammenge-
00015 C fasst. Die x-Achse wird durch Index=1, y durch Index=2 beschrieben.
00016 C
00017 integer      cline,csymbl,csteps ! ibase+ 0..2
00018 real         cfinfin ! 3
00019 integer      cnpts,cstepl,cnumbr ! 4..6
00020 real         csizes,csizel ! 7,8
00021
00022 logical      cxyneat(2),cxyzero(2) ! nbase+ 0, 1
00023 integer      cxyloc(2),cxylab(2),cxyden(2),cxytics(2) ! nbase+ 2..5
00024 integer      cxylen(2),cxyfrm(2),cxymtcs(2),cxymfrm(2),cxydec(2) ! 6..10
00025 real         cxydmin(2),cxydmax(2) ! 11,12
00026 integer      cxysmin(2),cxysmax(2),cxytype(2) ! 13..15
00027 integer      cxylsig(2),cxywdth(2),cxyepon(2) ! 16..18
00028 integer      cxystep(2),cxystag(2),cxyetyp(2) ! 19..21
00029 integer      cxybeg(2),cxyend(2),cxymbeg(2),cxymend(2) ! 22..25
00030 real         cxyamin(2),cxyamax(2) ! 26,27
00031
00032 common /g2dag2/
00033 C & extent,cvectr,xvectr,yvectr,
00034 C & xtentc,xtentx,xtenty,
00035 C
00036 C & cline,csymbl,csteps,
00037 C & cfinfin,
00038 C & cnpts,cstepl,cnumbr,csizes,csizel,
00039 C
00040 C & cxyneat,cxyzero,cxyloc,cxylab,cxyden,cxytics,
00041 C & cxylen,cxyfrm,cxymtcs,cxymfrm,cxydec,
00042 C & cxydmin,cxydmax,cxysmin,cxysmax,cxytype,
00043 C & cxylsig,cxywdth,cxyepon,cxystep,cxystag,cxyetyp,
00044 C & cxybeg,cxyend,cxymbeg,cxymend,cxyamin,cxyamax
00045 C
00046 C & reserv(8)
00047 save /g2dag2/
00048
00049 integer G2dAG2L ! Benötigt von SAVCOM, RESCOM
00050 parameter(g2dag2l=65) ! integer, real und logical gleich lang!
00051 C> \endcond

```


8.21 GetHDC.for File Reference

Restore Hardcopies.

Functions/Subroutines

- logical function [gethdc](#) (Filnam)

8.21.1 Detailed Description

Restore Hardcopies.

Version

1.2

Author

(C) 2023 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Read and plot hardcopies

Temporary input unit: 41. If already used, an other channel will be searched.

Definition in file [GetHDC.for](#).

8.21.2 Function/Subroutine Documentation

8.21.2.1 [gethdc\(\)](#)

```
logical function gethdc (  
    character *(*) Filnam )
```

Parameters

<i>FilNam</i>	Hardcopyfie
---------------	-------------

Returns

(optional) .true. -> Error

Definition at line 15 of file [GetHDC.for](#).

8.22 GetHDC.for

```

00001 C> \file      GetHDC.for
00002 C> \brief     Restore Hardcopies
00003 C> \version    1.2
00004 C> \author     (C) 2023 Dr.-Ing. Klaus Friedewald
00005 C> \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 C> \~german
00007 C> Einlesen und Zeichnen von Hardcopydateien\n
00008 C> Verwendete temporaeres Ein/Ausgabeunit: 41. Falls bereits belegt, wird ein freier Kanal gesucht
00009 C> \~english
00010 C> Read and plot hardcopies\n
00011 C> Temporary input unit: 41. If already used, an other channel will be searched.
00012 C> \~
00013 C
00014
00015     logical function gethdc (Filnam)
00016 C> \param FilNam: Hardcopyfie
00017 C> \result (optional) .true. -> Error
00018     include 'Tktrnx.fd'
00019     integer tcs_mesagelen, iunit
00020     parameter(tcs_mesagelen=132)
00021     character *(*) filnam
00022     logical iunitused
00023     character *(TCS_MESSAGELEN+1) txtstring
00024
00025     integer ios, idash, iprntlen, iactlen
00026     integer action, il, i2
00027
00028     iunit= 40
00029     gethdc= .true.
00030
00031 5     continue ! repeat
00032         iunit= iunit+1
00033         inquire (unit=iunit, opened= iunitused)
00034         if (iunitused) goto 5
00035
00036         open (iunit,file=filnam,status='old',iostat=ios,form='formatted')
00037         if (ios.ne.0) then
00038             call graphicerror (6, ' ')
00039             return
00040         end if
00041
00042 10    continue ! repeat
00043         read (iunit, fmt='(i2,lx,i4,lx,i3)', iostat=ios) action, il, i2
00044         if (ios.gt.0) then ! Error, not EOF
00045             call graphicerror (8, ' ')
00046             return
00047         end if
00048         if (action.eq.1) then ! XACTION_INITT
00049             call defaultcolour()
00050             call erase ()
00051         else if (action.eq.2) then ! XACTION_ERASE
00052             call erase ()
00053         else if (action.eq.3) then ! XACTION_MOVABS
00054             call movabs (il,i2)
00055         else if (action.eq.4) then ! XACTION_DRWABS
00056             call drwabs (il,i2)
00057         else if (action.eq.5) then ! XACTION_DSHSTYLE
00058             idash= il
00059         else if (action.eq.6) then ! XACTION_DSHABS
00060             call dshabs (il,i2,idash)
00061         else if (action.eq.7) then ! XACTION_PNTABS
00062             call pntabs (il,i2)
00063         else if (action.eq.8) then ! XACTION_GTEXT
00064             iprntlen= il
00065             if (iprntlen.gt.tcs_mesagelen) iprntlen= tcs_mesagelen
00066             txtstring(1:1)= char(i2)
00067             if (iprntlen.eq.1) then
00068                 txtstring= txtstring(1:1) // char(0)
00069                 call toutstc (txtstring)
00070             else
00071                 iactlen= 1
00072             end if
00073         else if (action.eq.9) then ! XACTION_ASCII
00074             if (iactlen.lt.iprntlen) then
00075                 iactlen= iactlen+1
00076                 txtstring(iactlen:iactlen)= char(i1)
00077             end if
00078             if (iactlen.lt.iprntlen) then
00079                 iactlen= iactlen+1

```

```

00080         txtstring(iactlen:iactlen)= char(i2)
00081     end if
00082     if (iactlen.ge.iprntlen) then
00083         txtstring(iactlen+1:iactlen+1) = char(0)
00084         call toutstc (txtstring)
00085     end if
00086     else if (action.eq.10) then ! XACTION_BCKCOL
00087         call bckcol(i1)
00088     else if (action.eq.11) then ! XACTION_LINCOL
00089         call lincol (i1)
00090     else if (action.eq.12) then ! XACTION_TXTCOL
00091         call txtcol (i1)
00092     else if (action.eq.13) then ! XACTION_FONTATTR
00093         if (i1.eq.0) call italir()
00094         if (i1.eq.1) call italic()
00095         if (i2.eq.0) call nrmsiz()
00096         if (i2.eq.1) call dblsiz()
00097     else if (action.eq.14) then ! XACTION_NOOP
00098         continue
00099     else if (action.eq.15) then ! XACTION_CLIP
00100         if (i1.eq.0) then ! clipping not active
00101             kminsx= 0
00102             kminsy= 0
00103             kmaxsx= 1023 ! TEK_XMAX
00104             kmaxsy= 780 ! TEK_YMAX
00105             call swindl(kminsx,kminsy,kmaxsx,kmaxsy) ! Set bool ClippingNotActive
00106         end if
00107     else if (action.eq.16) then ! XACTION_CLIP1
00108         kminsx= i1
00109         kminsy= i2
00110         call swindl(kminsx,kminsy,kmaxsx,kmaxsy)
00111     else if (action.eq.17) then ! XACTION_CLIP2
00112         kmaxsx= i1
00113         kmaxsy= i2
00114         call swindl(kminsx,kminsy,kmaxsx,kmaxsy)
00115     else ! unknown
00116         continue
00117     end if
00118     if (ios.eq.0) goto 10 ! until EOF
00119
00120     close (iunit)
00121     gethdc= .false.
00122     return
00123 end

```

8.23 Mainpage.dox File Reference

8.24 PlotHDC.f03 File Reference

Utility: Plot Journalfiles.

Functions/Subroutines

- program [plothdc](#)

8.24.1 Detailed Description

Utility: Plot Journalfiles.

Version

1.0-GCC

Author

(C) 2023 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Utility to draw journal-hardcopies from SDL2 and wX programs. With cut/paste they could be used by other MS-win programs. Program parameters are obtained by calling ISO Fortran 2003 intrinsic procedures.

Note

```
Invoke by:
$> plothdc FileName
```

Definition in file [PlotHDC.f03](#).

8.24.2 Function/Subroutine Documentation

8.24.2.1 plothdc()

```
program plothdc
```

Definition at line 26 of file [PlotHDC.f03](#).

8.25 PlotHDC.f03

```
00001 !> \file      PlotHDC.f03
00002 !> \brief     Utility: Plot Journalfiles
00003 !> \version    1.0-GCC
00004 !> \author      (C) 2023 Dr.-Ing. Klaus Friedewald
00005 !> \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 !>
00007 !> \~german
00008 !> Hilfsprogramm zur Anzeige von Journal-Hardcopies von SDL2 und wX-Programmen.
00009 !> Diese koennen dann ueber Cut/Paste in andere Windowsprogramme uebernommen werden.
00010 !> Die Abfrage der Programmparameter erfolgt durch ISO-Portran 2003 Intrinsics.
00011 !> \note \verbatim
00012 !>     Aufruf durch:
00013 !>     $> plothdc FileName
00014 !> \endverbatim
00015 !>
00016 !> \~english
00017 !> Utility to draw journal-hardcopies from SDL2 and wX programs.
00018 !> With cut/paste they could be used by other MS-win programs.
00019 !> Program parameters are obtained by calling ISO Fortran 2003 intrinsic procedures.
00020 !> \note \verbatim
00021 !>     Invoke by:
00022 !>     $> plothdc FileName
00023 !> \endverbatim
00024 !> \~
00025 !>
00026     program plothdc
00027     implicit none
00028     integer itrimlen
00029     integer ipar
00030     character * 128 filnam
00031
00032     call initt (0)
00033     ipar = command_argument_count() ! FTN03 Standard
00034     call get_command_argument (1,filnam)
00035     if (ipar.gt.0) then
00036         call gethdc (filnam(1:itrimlen(filnam))//char(0))
00037     else
00038         call graphicerror (9, 'Please invoke by: PlotHDC FileName')
00039     end if
00040     call finitt
00041     end
```

8.26 Strings.for File Reference

TCS: String functions.

Functions/Subroutines

- subroutine [substitute](#) (Source, Destination, Old1, New1)
- integer function [istringlen](#) (String)
- character *(*) function [printstring](#) (String)
- integer function [itrimlen](#) (string)

8.26.1 Detailed Description

TCS: String functions.

Version

1.26

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

Fortran utility functions for string processing

Definition in file [Strings.for](#).

8.26.2 Function/Subroutine Documentation

8.26.2.1 istringlen()

```
integer function istringlen (  
    character *(*) String )
```

Definition at line 94 of file [Strings.for](#).

8.26.2.2 itrimlen()

```
integer function itrimlen (
    character *(*) string )
```

Definition at line 133 of file [Strings.for](#).

8.26.2.3 printstring()

```
character*(*) function printstring (
    character, dimension(*) String )
```

Definition at line 114 of file [Strings.for](#).

8.26.2.4 substitute()

```
subroutine substitute (
    character *(*) Source,
    character *(*) Destination,
    character *(*) Old1,
    character *(*) New1 )
```

Definition at line 30 of file [Strings.for](#).

8.27 Strings.for

```
00001 C> \file      Strings.for
00002 C> \brief     TCS: String functions
00003 C> \version   1.26
00004 C> \author    (C) 2022 Dr.-Ing. Klaus Friedewald
00005 C> \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 C> \~german
00007 C> Hilfsfunktionen zur Fortran Stringverarbeitung
00008 C> \~english
00009 C> Fortran utility functions for string processing
00010 C> \~
00011 C>
00012 C
00013 Cccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccc
00014 C
00015 C Unterprogramme zur Behandlung von Fortran-Strings.
00016 C Die Stringenden werden entweder durch CHAR(0) markiert oder
00017 C ueber die Deklaration ermittelt.
00018 C
00019 C 9.11.88 K. Friedewald
00020 C
00021 C Ergaenzungen:
00022 C iTrimLen
00023 C
00024 C 7.12.01 K. Friedewald
00025 C
00026 C Version: 1.26
00027 C
00028 Cccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccccc
00029
00030 subroutine substitute (Source, Destination, Old1, New1)
00031 C
00032 C Durchsucht SOURCE nach den Substrings OLD, ersetzt sie durch NEW
00033 C und uebergibt das Ergebniss in DESTINATION. Wenn New=CHAR(0), werden
00034 C die vorkommenden OLD nur geloescht.
```

```

00035 C
00036 C Stringenden koennen durch CHAR(0) markiert werden.
00037 C
00038     implicit none
00039     integer iNext, iNext2, TempLen
00040     integer iStringLen
00041     character *(*) Source, Destination, Old1, New1
00042     character*255 temp, old, new
00043
00044     if (istringlen(old1).le.0) return
00045     if (istringlen(source) .le. 0) then
00046         destination= char(0)
00047         return
00048     end if
00049
00050     old= old1 // char(0)           ! old evtl. = Destination
00051     new= new1 // char(0)          ! => retten!
00052
00053     temp= source(1:istringlen(source)) // char(0) ! evtl. Ueberlappung!
00054     destination= temp
00055     inext= index( destination(:istringlen(destination)),
00056 1                                old(:istringlen(old)) )
00057     do while (inext.gt.0)
00058         if (inext.eq.1) then
00059             temp= destination
00060             if (new.eq.char(0)) then
00061                 destination= temp(istringlen(old)+1:)
00062             else
00063                 destination= new(:istringlen(new)) // temp(istringlen(old)+1:)
00064             end if
00065         else
00066             temp= destination(1:inext-1)
00067             tempLen= inext-1
00068             if (new.ne.char(0)) then
00069                 temp= temp(1:tempLen)//new
00070                 tempLen= tempLen+istringlen(new)
00071             end if
00072             if (inext+istringlen(old).lt.len(destination)) then
00073                 temp= temp(1:tempLen)//destination(inext+istringlen(old):)
00074             end if
00075             destination= temp
00076         end if
00077         inext2= inext+istringlen(new)
00078         if (inext2.lt.len(destination)) then
00079             inext2= index(destination(inext2:), old(:istringlen(old)) )
00080         else
00081             inext2=0
00082         end if
00083         if (inext2.gt.0) then
00084             inext= inext+istringlen(new)+inext2-1
00085         else
00086             inext=0
00087         end if
00088     end do
00089     return
00090 end
00091
00092
00093
00094     function istringlen (String)
00095 C
00096 C Ermittelt die Stringlänge bei durch char(0) abgeschlossenen STRINGS.
00097 C Falls kein char(0) vorhanden ist, wird die Gesamtlänge übergeben.
00098 C
00099     implicit none
00100     character *(*) string
00101     integer istringlen, i
00102
00103     i= index(string,char(0))-1
00104     if (i.ge.0) then
00105         istringlen=i
00106     else
00107         istringlen= len(string)
00108     end if
00109     return
00110 end
00111
00112
00113
00114     character*(*) function printstring (String)
00115 C
00116 C Kopiert STRING in einen variabel langen PRINTSTRING. Hierdurch wird
00117 C der Ausdruck von Nullstrings (Fortran-Fehler!) vermieden.
00118 C
00119     implicit none
00120     character string *(*)
00121     integer istringlen

```

```

00122
00123     if (istringlen(string).gt.0) then
00124         printstring= string(1:istringlen(string))
00125     else
00126         printstring= ' '
00127     end if
00128     return
00129 end
00130
00131
00132
00133     integer function itrimlen (string)
00134 C
00135 C   Bestimmt die Länge des Strings ohne angehängte Leerzeichen.
00136 C   Bei Bedarf wird ein Char(0) angehaengt. Es darf in Ftn77 nie ein
00137 C   Nullstring erzeugt werden, da sonst die RTL-Library abstuerzt. Deswegen
00138 C   ist der kleinste erzeugte String ein Blank ' '.
00139 C
00140     implicit none
00141     character *(*) string
00142     integer i, istringlen
00143
00144     i=istringlen(string) +1
00145
00146 10  continue
00147     i= i-1
00148     if (i.ge.1) then
00149         if (string(i:i).eq.' ') goto 10
00150     end if
00151     itrimlen=i
00152     if ((i.lt.len(string)).and.(len(string).gt.1)) then
00153         string(i+1:i+1)= char(0) ! .gt.1: Achtung, nie Nullstring erzeugen!
00154     end if
00155     return
00156 end
00157

```

8.28 TCS.for File Reference

TCS: Tektronix Plot 10 Emulation.

Functions/Subroutines

- subroutine [vcursr](#) (IC, X, Y)
- subroutine [drawr](#) (X, Y)
- subroutine [mover](#) (X, Y)
- subroutine [pointr](#) (X, Y)
- subroutine [dashr](#) (X, Y, iL)
- subroutine [rel2ab](#) (Xrel, Yrel, Xabs, Yabs)
- subroutine [drawa](#) (X, Y)
- subroutine [movea](#) (X, Y)
- subroutine [pointa](#) (X, Y)
- subroutine [dasha](#) (X, Y, iL)
- subroutine [wincot](#) (X, Y, IX, IY)
- subroutine [revcot](#) (IX, IY, X, Y)
- subroutine [anstr](#) (NChar, IStrin)
- subroutine [ancho](#) (ichar)
- subroutine [newlin](#)
- subroutine [cartn](#)
- subroutine [linef](#)
- subroutine [baksp](#)
- subroutine [newpag](#)
- function [linhgt](#) (Numlin)
- function [linwdt](#) (NumChr)

- subroutine [lintrn](#)
- subroutine [logtrn](#) (IMODE)
- subroutine [twindo](#) (IX1, IX2, IY1, IY2)
- subroutine [swindo](#) (IX, LX, IY, LY)
- subroutine [dwindo](#) (X1, X2, Y1, Y2)
- subroutine [vwindo](#) (X, XL, Y, YL)
- subroutine [rescal](#)
- subroutine [rrotat](#) (Grad)
- subroutine [rscale](#) (Faktor)
- subroutine [home](#)
- subroutine [setmrg](#) (Mlinks, Mrecht)
- subroutine [seetrm](#) (IBaud, lterm, ICSIZE, MaxScr)
- subroutine [seetrn](#) (xf, yf, key)
- logical function [genflg](#) (ITEM)

8.28.1 Detailed Description

TCS: Tektronix Plot 10 Emulation.

Version

4.0

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

System independent subroutines

Definition in file [TCS.for](#).

8.28.2 Function/Subroutine Documentation

8.28.2.1 ancho()

```
subroutine ancho (  
    ichar )
```

Definition at line [315](#) of file [TCS.for](#).

8.28.2.2 anstr()

```
subroutine anstr (
    NChar,
    dimension(1) IStrin )
```

Definition at line 305 of file [TCS.for](#).

8.28.2.3 baksp()

```
subroutine baksp
```

Definition at line 360 of file [TCS.for](#).

8.28.2.4 cartn()

```
subroutine cartn
```

Definition at line 341 of file [TCS.for](#).

8.28.2.5 dasha()

```
subroutine dasha (
    X,
    Y,
    iL )
```

Definition at line 266 of file [TCS.for](#).

8.28.2.6 dashr()

```
subroutine dashr (
    X,
    Y,
    iL )
```

Definition at line 212 of file [TCS.for](#).

8.28.2.7 drawa()

```
subroutine drawa (  
    X,  
    Y )
```

Definition at line [233](#) of file [TCS.for](#).

8.28.2.8 drawr()

```
subroutine drawr (  
    X,  
    Y )
```

Definition at line [188](#) of file [TCS.for](#).

8.28.2.9 dwindo()

```
subroutine dwindo (  
    X1,  
    X2,  
    Y1,  
    Y2 )
```

Definition at line [438](#) of file [TCS.for](#).

8.28.2.10 genflg()

```
logical function genflg (  
    ITEM )
```

Definition at line [534](#) of file [TCS.for](#).

8.28.2.11 home()

```
subroutine home
```

Definition at line [494](#) of file [TCS.for](#).

8.28.2.12 linef()

```
subroutine linef
```

Definition at line [350](#) of file [TCS.for](#).

8.28.2.13 linhgt()

```
function linhgt (  
    NumLin )
```

Definition at line [376](#) of file [TCS.for](#).

8.28.2.14 lintrn()

```
subroutine lintrn
```

Definition at line [394](#) of file [TCS.for](#).

8.28.2.15 linwdt()

```
function linwdt (  
    NumChr )
```

Definition at line [384](#) of file [TCS.for](#).

8.28.2.16 logtrn()

```
subroutine logtrn (  
    IMODE )
```

Definition at line [404](#) of file [TCS.for](#).

8.28.2.17 movea()

```
subroutine movea (  
    X,  
    Y )
```

Definition at line [244](#) of file [TCS.for](#).

8.28.2.18 mover()

```
subroutine mover (
    X,
    Y )
```

Definition at line 196 of file [TCS.for](#).

8.28.2.19 newlin()

```
subroutine newlin
```

Definition at line 333 of file [TCS.for](#).

8.28.2.20 newpag()

```
subroutine newpag
```

Definition at line 368 of file [TCS.for](#).

8.28.2.21 pointa()

```
subroutine pointa (
    X,
    Y )
```

Definition at line 255 of file [TCS.for](#).

8.28.2.22 pointr()

```
subroutine pointr (
    X,
    Y )
```

Definition at line 204 of file [TCS.for](#).

8.28.2.23 rel2ab()

```
subroutine rel2ab (  
    Xrel,  
    Yrel,  
    Xabs,  
    Yabs )
```

Definition at line 220 of file [TCS.for](#).

8.28.2.24 rescal()

```
subroutine rescal
```

Definition at line 457 of file [TCS.for](#).

8.28.2.25 revcot()

```
subroutine revcot (  
    IX,  
    IY,  
    X,  
    Y )
```

Definition at line 290 of file [TCS.for](#).

8.28.2.26 rrotat()

```
subroutine rrotat (  
    Grad )
```

Definition at line 477 of file [TCS.for](#).

8.28.2.27 rscale()

```
subroutine rscale (  
    Faktor )
```

Definition at line 486 of file [TCS.for](#).

8.28.2.28 seetrm()

```
subroutine seetrm (
    IBaud,
    Iterm,
    ICSize,
    MaxScr )
```

Definition at line 512 of file [TCS.for](#).

8.28.2.29 seetrn()

```
subroutine seetrn (
    xf,
    yf,
    key )
```

Definition at line 523 of file [TCS.for](#).

8.28.2.30 setmrg()

```
subroutine setmrg (
    Mlinks,
    Mrecht )
```

Definition at line 503 of file [TCS.for](#).

8.28.2.31 swindo()

```
subroutine swindo (
    IX,
    LX,
    IY,
    LY )
```

Definition at line 426 of file [TCS.for](#).

8.28.2.32 twindo()

```
subroutine twindo (
    IX1,
    IX2,
    IY1,
    IY2 )
```

Definition at line 419 of file [TCS.for](#).


```

00028 C      - DeletePen -> DeleteObject
00029 C      - DeleteBrush -> DeleteObject
00030 C      - GetStockBrush -> GetStockObject
00031 C      - DeleteRgn -> DeleteObject
00032 C      - SelectFont -> SelectObject
00033 C      - DeleteFont -> DeleteObject
00034 C
00035 C      27.03.13 Version 3.0
00036 C      Anpassung an Windows 7 und OpenWatcom 1.9
00037 C      Anpassung an gfortran anstelle von g77 der GCC
00038 C
00039 C      22.12.05 Version 2.19
00040 C      Elimination berechnetes GOTO in LOGTRN
00041 C
00042 C      18.10.05 Version 2.18
00043 C      Anpassung der Windowsversionen zur gemeinsamen Verwendung SDL2:
00044 C      TCSdrWIN.for
00045 C      TCSdWINc.h
00046 C      - Überfuehrung der Deklaration aus TCSdWIN.c nach *.h:
00047 C      GraphicError und CreateMainWindow_IfNecessary
00048 C      - Definition der Fehlernummern als Konstante statt enum
00049 C      Abhaengigkeit Watcom-Defaultwindowssystem eliminiert
00050 C      - TCSdWINc.c: Kein Abbruch bei OpenWatcom > 1.3 und
00051 C      definiertem Symbol trace_calls
00052 C
00053 C      26.10.04 Version 2.17
00054 C      Bugfix Windows-System: Größe und Defaultposition des Status-
00055 C      fensters wird bei der Erzeugung berechnet -> 1. RESTORE nach
00056 C      Verkleinern des Graphikfensters entspricht dem vorherigen
00057 C      Bild. 2. Angleichung des Verhaltens von 16- und 32bit Windows
00058 C      Bei Definition des Symbols STAT_WINDOW_PRIVATE erhält das
00059 C      Statusfenster einen privaten Devicekontext.
00060 C      Zusammenfuehrung Initialisierung der Windows-Library und
00061 C      Windows-DLL -> zusaetzliche Sourcefiles
00062 C      TCSinitt.for, CreateMainWindow.c, GetMainInstance.c
00063 C
00064 C      23.06.04 Version 2.16:
00065 C      Anpassungen an GNU-Compiler fuer Win32. Zusätzliches Sourcefile
00066 C      fuer die GNU-Version: WinMain.c
00067 C      CSIZE in Windows-Version: Korrektur Rundungsfehler
00068 C
00069 C      08.06.04 Version 2.15:
00070 C      Umbenennung lib$movc3 in lib_movc3 (entsprechend ANSI-Fortran)
00071 C      Modul STRINGS.FOR: Version 1.24
00072 C
00073 C      27.06.03 Version 2.14:
00074 C      Verarbeitung Steuerzeichen in ANCHO
00075 C
00076 C      21.10.02 Version 2.13:
00077 C      Einheitliche Version CPM/DOS/Windows
00078 C
00079 C      CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
00080 C
00081 C      Grundversion fuer C128 / Version 1.0:
00082 C
00083 C      Zugehoerige Module:
00084 C      TKTRNX.FOR      Common-Block TKTRNX
00085 C      TCSBASIC.ASM    Low-Level Routinen in Bank 0, C128 spezifisch
00086 C      TCSDRIVR.ASM    Treiber fuer TCSBASIC
00087 C      TCSGIN.ASM      Treiber des Gin-Cursors
00088 C
00089 C      20.4.88      Dr.-Ing. K. Friedewald
00090 C      4000 Duesseldorf 1
00091 C      Gerresheimerstr. 84
00092 C
00093 C      21.10.02 Version 2.13:
00094 C      Vereinheitlichung CPM/DOS/Windowsversion
00095 C      Zusätzliches Modul: TCSdrCPM.FOR: früher Teil von TCS.FOR
00096 C      Ausschließliche Verwendung von durch grosses "C" eingeleiteten
00097 C      Kommentaren zur Kompatibilität mit FORTRAN 4
00098 C      Umbenennung des Includefiles in Tktrnx.fd. So kann unter CP/M
00099 C      das als Teil des Filenamens interpretierte "" der INCLUDE-
00100 C      Anweisung entsprechend der 8.3 Filenamen umgesetzt werden.
00101 C      Implementierung Unterprogramm TCSLEV
00102 C      Bugfix: Kommentar in Tktrnx.fd wurde falsch gekennzeichnet
00103 C      (c statt C) -> SVSTAT und RESTAT fehlerhaft, da nicht
00104 C      erkannte Kommentare zusaetzliche Variablen erzeugten.
00105 C
00106 C      TBD: Implementierung vertikale Auflösung von 400 Pixeln
00107 C
00108 C      CCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCCC
00109 C
00110 C      Anpassung an DOS:
00111 C
00112 C      Änderungen gegenüber CP/M-Version:
00113 C      SEELOC, DCURSR, SVSTAT, RESTAT, CSIZE in TCSdrDOS.FOR
00114 C      Bugfix: DASHA, DASHR - Korrektur Parameterliste

```



```

00202
00203
00204     subroutine pointr (X,Y)
00205     call rel2ab (x,y,xabs,yabs)
00206     call pointa (xabs,yabs)
00207     return
00208     end
00209
00210
00211
00212     subroutine dashr (X,Y, iL)
00213     call rel2ab (x,y,xabs,yabs)
00214     call dasha (xabs,yabs, iL)
00215     return
00216     end
00217
00218
00219
00220     subroutine rel2ab (Xrel, Yrel, Xabs, Yabs)
00221     include 'Tktrnx.fd'
00222     call seeloc (ix,iy)
00223     call revcot (ix,iy,xabs,yabs)
00224     xabs= (( xrel*trcosf - yrel*trsinf)*trscal)+xabs
00225     yabs= (( xrel*trsinf + yrel*trcosf)*trscal)+yabs
00226     return
00227     end
00228
00229 C
00230 C Virtuelles Zeichnen, absolut
00231 C
00232
00233     subroutine drawa (X,Y)
00234     include 'Tktrnx.fd'
00235     call wincot (x,y,ix,iy)
00236     call swindl (kminsx,kminsy,kmaxsx,kmaxsy)
00237     call drwabs (ix,iy)
00238     call swindl (0,0,1023,780)
00239     return
00240     end
00241
00242
00243
00244     subroutine movea (X,Y)
00245     include 'Tktrnx.fd'
00246     call wincot (x,y,ix,iy)
00247     call swindl (kminsx,kminsy,kmaxsx,kmaxsy)
00248     call movabs (ix,iy)
00249     call swindl (0,0,1023,780)
00250     return
00251     end
00252
00253
00254
00255     subroutine pointa (X,Y)
00256     include 'Tktrnx.fd'
00257     call wincot (x,y,ix,iy)
00258     call swindl (kminsx,kminsy,kmaxsx,kmaxsy)
00259     call pntabs (ix,iy)
00260     call swindl (0,0,1023,780)
00261     return
00262     end
00263
00264
00265
00266     subroutine dasha (X,Y, iL)
00267     include 'Tktrnx.fd'
00268     call wincot (x,y,ix,iy)
00269     call swindl (kminsx,kminsy,kmaxsx,kmaxsy)
00270     call dshabs (ix,iy, iL)
00271     call swindl (0,0,1023,780)
00272     return
00273     end
00274
00275
00276
00277     subroutine wincot (X,Y,IX,IY)
00278     include 'Tktrnx.fd'
00279     dx= x-tminvx
00280     dy= y-tminvy
00281     if ((xlog.lt.255.).and.(x.gt.0.)) dx=alog(x)-xlog
00282     if ((ylog.lt.255.).and.(y.gt.0.)) dy=alog(y)-ylog
00283     ix= ifix(dx*xfac+.5)+kminsx
00284     iy= ifix(dy*yfac+.5)+kminsy
00285     return
00286     end
00287
00288

```

```

00289
00290     subroutine revcot (IX,IY,X,Y)
00291     include 'Tktrnx.fd'
00292     dx= float(ix-kminsx) / xfac
00293     dy= float(iy-kminsy) / yfac
00294     x= dx + tminvx
00295     y= dy + tminvy
00296     if (xlog.lt.255.) x= 2.718282**(dx+xlog)
00297     if (ylog.lt.255.) y= 2.718282**(dy+ylog)
00298     return
00299     end
00300
00301 C
00302 C Alphanumerische Ausgabe
00303 C
00304
00305     subroutine anstr (NChar, IStrin)
00306     dimension istrin(1)
00307     do 10 i=1,nchar
00308         call ancho (istrin(i))
00309 10    continue
00310     return
00311     end
00312
00313
00314
00315     subroutine ancho (ichar)
00316     include 'Tktrnx.fd'
00317
00318     if (ichar.gt.31) goto 10
00319     if (ichar.eq.7) call bell
00320     if (ichar.eq.10) call linef
00321     if (ichar.eq.13) call cartn
00322     return
00323
00324 10    call seeloc (ix,k)
00325     call csize (ixlen,k)
00326     if (ix.gt.krmrgn-ixlen) call newlin
00327     call toutpt (ichar)
00328     return
00329     end
00330
00331
00332
00333     subroutine newlin
00334     call cartn
00335     call linef
00336     return
00337     end
00338
00339
00340
00341     subroutine cartn
00342     include 'Tktrnx.fd'
00343     call seeloc (ix,iy)
00344     call movabs (klmrgn,iy)
00345     return
00346     end
00347
00348
00349
00350     subroutine linef
00351     call seeloc (j,iy)
00352     call csize (j,iylen)
00353     if (iy.lt.iylen) call home
00354     call movrel (0,-iylen)
00355     return
00356     end
00357
00358
00359
00360     subroutine baksp
00361     call csize (ix,iy)
00362     call movrel (-ix,0)
00363     return
00364     end
00365
00366
00367
00368     subroutine newpag
00369     call erase
00370     call home
00371     return
00372     end
00373
00374
00375

```

```

00376     function linhgt (Numlin)
00377     call csize (ix,iy)
00378     linhgt= numlin*iy
00379     return
00380     end
00381
00382
00383
00384     function linwdt (NumChr)
00385     call csize (ix,iy)
00386     linwdt= numchr*ix
00387     return
00388     end
00389
00390 C
00391 C Initialisierungsroutinen
00392 C
00393
00394     subroutine lintrn
00395     include 'Tktrnx.fd'
00396     xlog= 255.
00397     ylog= 255.
00398     call rescal
00399     return
00400     end
00401
00402
00403
00404     subroutine logtrn (IMODE)
00405     include 'Tktrnx.fd'
00406     call lintrn
00407     if ((imode .eq. 1) .or. (imode .eq. 3)) then
00408         xlog= 0.
00409     end if
00410     if ((imode .eq. 2) .or. (imode .eq. 3)) then
00411         ylog= 0.
00412     end if
00413     call rescal
00414     return
00415     end
00416
00417
00418
00419     subroutine twindo (IX1,IX2,IY1,IY2)
00420     call swindo (ix1,ix2-ix1,iy1,iy2-iy1)
00421     return
00422     end
00423
00424
00425
00426     subroutine swindo (IX,LX,IY,LY)
00427     include 'Tktrnx.fd'
00428     kminsx= ix
00429     kmaxsx= ix+lX
00430     kminsy= iy
00431     kmaxsy= iy+LY
00432     call rescal
00433     return
00434     end
00435
00436
00437
00438     subroutine dwindo (X1,X2,Y1,Y2)
00439     call vwindo (x1,x2-x1,y1,y2-y1)
00440     return
00441     end
00442
00443
00444
00445     subroutine vwindo (X,XL,Y,YL)
00446     include 'Tktrnx.fd'
00447     tminvx= x
00448     tmaxvx= x+XL
00449     tminvy= y
00450     tmaxvy= y+YL
00451     call rescal
00452     return
00453     end
00454
00455
00456
00457     subroutine rescal
00458     include 'Tktrnx.fd'
00459     xfac= 0.
00460     yfac= 0.
00461     if ((tmaxvx.eq.tminvx) .or. (tmaxvy.eq.tminvy)) return
00462     dx= tmaxvx-tminvx

```

```

00463     dy= tmaxvy-tminvy
00464     if ((xlog.eq.255.).or.(amin1(tminvx,tmaxvx).le.0.)) goto 10
00465     xlog= alog(tminvx)
00466     dx= alog(tmaxvx)-xlog
00467 10    if ((ylog.eq.255.).or.(amin1(tminvy,tmaxvy).le.0.)) goto 20
00468     ylog= alog(tminvy)
00469     dy= alog(tmaxvy)-ylog
00470 20    xfac= float(kmaxsx-kminsx) / dx
00471     yfac= float(kmaxsy-kminsy) / dy
00472     return
00473 end
00474
00475
00476
00477     subroutine rrotat (Grad)
00478     include 'Tktrnx.fd'
00479     trsinf= sin(grad/57.29578)
00480     trcosf= cos(grad/57.29578)
00481     return
00482 end
00483
00484
00485
00486     subroutine rscale (Faktor)
00487     include 'Tktrnx.fd'
00488     trscal= faktor
00489     return
00490 end
00491
00492
00493
00494     subroutine home
00495     include 'Tktrnx.fd'
00496 C     call movabs(klrmgn,750) Fuer CP/M (kein khomey verfuegbar, -> !=750)
00497     call movabs(klrmgn,khomey)
00498     return
00499 end
00500
00501
00502
00503     subroutine setmrg (Mlinks, Mrecht)
00504     include 'Tktrnx.fd'
00505     klrmgn= mlinks
00506     krmrgn= mrecht
00507     return
00508 end
00509
00510
00511
00512     subroutine seetrm (IBaud, Iterm, ICSIZE, MaxScr)
00513     include 'Tktrnx.fd'
00514     ibaud= 0
00515     iterm= 1
00516     icsize= 1
00517     maxscr= 1023
00518     return
00519 end
00520
00521
00522
00523     subroutine seetrn (xf,yf,key)
00524     include 'Tktrnx.fd'
00525     xf= xfac
00526     yf= yfac
00527     key= 1
00528     if ((xlog.lt.255.).or.(ylog.lt.255.)) key=2
00529     return
00530 end
00531
00532
00533
00534     logical function genflg (ITEM)
00535     genflg= item.eq.0
00536     return
00537 end
00538

```

8.30 TCSdrWXcpp.cpp File Reference

wX Port: Low-Level Driver

```

#include <wx/frame.h>
#include <wx/panel.h>
#include <wx/sizer.h>
#include <wx/dc.h>
#include <wx/dcclient.h>
#include <wx/log.h>
#include <wx/msgdlg.h>
#include <wx/stdpaths.h>
#include <wx/filename.h>
#include <wx/xml/xml.h>
#include <wx/file.h>
#include "sglib.h"
#include "TCSdrWXcpp.hpp"
#include "TKTRNX.hpp"
#include "G2dAG2.hpp"
#include "graph2d.h"

```

Classes

- struct [xJournalEntry_tpy](#)
- class [cTCScanvas](#)

Macros

- #define [wxDEBUG_LEVEL](#) 2
- #define [MAX_COLOR_INDEX](#) 15
- #define [TMPSTRLEN](#) [TCS_FILE_NAMELEN](#)

Typedefs

- typedef struct [xJournalEntry_tpy](#) [xJournalEntry_tpy](#)
- typedef char [ErrMsg](#)[[TCS_MESSAGELEN](#)]

Functions

- void [initt0](#) ()
- wxWindowID [getCanvasID](#) (wxWindowID win2search)
- void [RepaintBuffer](#) (wxDC &dc)
- void [PresetProgPar](#) ()
- void [CustomizeProgPar](#) ()
- void [XMLreadProgPar](#) (const char *filename)
- void [winlb10](#) (const char PloWinNam[], const char StatWinNam[], const char IniFilNam[])
- bool [WINSELECT](#) (wxWindowID *iD)
- void [initt1](#) (int iMode, wxFrame *parent, wxFrame *FrameToUse, wxStatusBar *StatusBarToUse)
- void [FINITT](#) (int *ix, int *iy)
- void [IOWAIT](#) (int *iWait)
- void [swind1_](#) (int *ix1, int *iy1, int *ix2, int *iy2)
- void [ERASE](#) (void)
- void [MOVABS](#) (int *ix, int *iy)
- void [DRWABS](#) (int *ix, int *iy)
- void [DSHABS](#) (int *ix, int *iy, int *iMask)

- void [PNTABS](#) (int *ix, int *iy)
- void [BCKCOL](#) (int *iCol)
- void [LINCOL](#) (int *iCol)
- void [TXTCOL](#) (int *iCol)
- void [DEFAULTCOLOUR](#) (void)
- void [outgtext_](#) (char strng[])
- void [ITALIC](#) (void)
- void [ITALIR](#) (void)
- void [DBLSIZ](#) (void)
- void [NRMSIZ](#) (void)
- void [BELL](#) (void)
- void [outtext_](#) (char strng[])
- void [TCSGraphicError](#) (int iErr, const char *msg)
- void [DCURSR](#) (int *ic, int *ix, int *iy)
- void [TINPUT](#) (int *ic)
- void [HDCOPY](#) (void)
- void [SVSTAT](#) (char dst[])
- void [RESTAT](#) (char src[])
- void [lib_movc3_](#) (int *len, char sou[], char dst[])

Variables

- static char [szTCSWindowName](#) [TCS_WINDOW_NAMELEN] = TCS_WINDOW_NAME
- static char [szTCSstatWindowName](#) [TCS_WINDOW_NAMELEN] = TCS_STATWINDOW_NAME
- static char [szTCSIniFile](#) [TCS_FILE_NAMELEN] = TCS_INIFILE_NAME
- static char [szTCSHardcopyFile](#) [TCS_FILE_NAMELEN] = TCS_HDCFILE_NAME
- static char [szTCSsect0](#) [TCS_FILE_NAMELEN] = TCS_INISECT0
- static int [TCSwindowIniXrelpos](#) = TCS_INIDEF_WINPOSX
- static int [TCSwindowIniYrelpos](#) = TCS_INIDEF_WINPOSY
- static int [TCSwindowIniXrelsiz](#) = TCS_INIDEF_WINSIZX
- static int [TCSwindowIniYrelsiz](#) = TCS_INIDEF_WINSIZY
- static int [TCSDefaultLinCol](#) = TCS_INIDEF_LINCOL
- static int [TCSDefaultTxtCol](#) = TCS_INIDEF_TXTCOL
- static int [TCSDefaultBckCol](#) = TCS_INIDEF_BCKCOL
- static int [iHardcopyCount](#) = 1
- static [ErrMsg](#) [szTCSErrorMsg](#) [(int) MSG_MAXERRNO+1]
- static int [TCSErrorLev](#) [(int) MSG_MAXERRNO+1]
- static wxColour [TCSColorTable](#) [MAX_COLOR_INDEX+1]
- static [cTCScanvas](#) * [ActiveCanvas](#) = NULL
- static wxWindowID [ActiveCanvasID](#) = 0
- static [cTCScanvas](#) * [OpenCanvases](#) [MAX_OPEN_CANVAS] = {}

8.30.1 Detailed Description

wX Port: Low-Level Driver

Version

0.9

Author

(C) 2023 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

system-specific subroutines of the Tektronix emulation

Note

1. ToDo

Definition in file [TCSdrWXcpp.cpp](#).

8.30.2 Macro Definition Documentation

8.30.2.1 MAX_COLOR_INDEX

```
#define MAX_COLOR_INDEX 15
```

Definition at line 217 of file [TCSdrWXcpp.cpp](#).

8.30.2.2 TMPSTRLEN

```
#define TMPSTRLEN TCS_FILE_NAMELEN
```

8.30.2.3 wxDEBUG_LEVEL

```
#define wxDEBUG_LEVEL 2
```

Definition at line 26 of file [TCSdrWXcpp.cpp](#).

8.30.3 Typedef Documentation

8.30.3.1 ErrMsg

```
typedef char ErrMsg[TCS_MESSAGELEN]
```

Definition at line 156 of file [TCSdrWXcpp.cpp](#).

8.30.3.2 xJournalEntry_typ

```
typedef struct xJournalEntry_typ xJournalEntry_typ
```

8.30.4 Function Documentation

8.30.4.1 BCKCOL()

```
void BCKCOL (  
    int * iCol )
```

Definition at line 1284 of file [TCSdrWXcpp.cpp](#).

8.30.4.2 BELL()

```
void BELL (  
    void )
```

Definition at line 1487 of file [TCSdrWXcpp.cpp](#).

8.30.4.3 CustomizeProgPar()

```
void CustomizeProgPar ( )
```

Definition at line 540 of file [TCSdrWXcpp.cpp](#).

8.30.4.4 DBLSIZ()

```
void DBLSIZ (
    void )
```

Definition at line 1434 of file [TCSdrWXcpp.cpp](#).

8.30.4.5 DCURSR()

```
void DCURSR (
    int * ic,
    int * ix,
    int * iy )
```

Definition at line 1550 of file [TCSdrWXcpp.cpp](#).

8.30.4.6 DEFAULTCOLOUR()

```
void DEFAULTCOLOUR (
    void )
```

Definition at line 1340 of file [TCSdrWXcpp.cpp](#).

8.30.4.7 DRWABS()

```
void DRWABS (
    int * ix,
    int * iy )
```

Definition at line 1220 of file [TCSdrWXcpp.cpp](#).

8.30.4.8 DSHABS()

```
void DSHABS (
    int * ix,
    int * iy,
    int * iMask )
```

Definition at line 1239 of file [TCSdrWXcpp.cpp](#).

8.30.4.9 ERASE()

```
void ERASE (
    void )
```

Definition at line 1153 of file [TCSdrWXcpp.cpp](#).

8.30.4.10 FINITT()

```
void FINITT (
    int * ix,
    int * iy )
```

Definition at line 1067 of file [TCSdrWXcpp.cpp](#).

8.30.4.11 getCanvasID()

```
wxWindowID getCanvasID (
    wxWindowID win2search )
```

Definition at line 284 of file [TCSdrWXcpp.cpp](#).

8.30.4.12 HDCOPY()

```
void HDCOPY (
    void )
```

Definition at line 1594 of file [TCSdrWXcpp.cpp](#).

8.30.4.13 initt0()

```
void initt0 ( )
```

Definition at line 254 of file [TCSdrWXcpp.cpp](#).

8.30.4.14 initt1()

```
void initt1 (
    int iMode,
    wxFrame * parent,
    wxFrame * FrameToUse,
    wxStatusBar * StatusBarToUse )
```

Definition at line 972 of file [TCSdrWXcpp.cpp](#).

8.30.4.15 IOWAIT()

```
void IOWAIT (
    int * iWait )
```

Definition at line 1097 of file [TCSdrWXcpp.cpp](#).

8.30.4.16 ITALIC()

```
void ITALIC (
    void )
```

Definition at line 1398 of file [TCSdrWXcpp.cpp](#).

8.30.4.17 ITALIR()

```
void ITALIR (
    void )
```

Definition at line 1416 of file [TCSdrWXcpp.cpp](#).

8.30.4.18 lib_movc3_()

```
void lib_movc3_ (
    int * len,
    char sou[],
    char dst[] )
```

Definition at line 1654 of file [TCSdrWXcpp.cpp](#).

8.30.4.19 LINCOL()

```
void LINCOL (
    int * iCol )
```

Definition at line 1303 of file [TCSdrWXcpp.cpp](#).

8.30.4.20 MOVABS()

```
void MOVABS (
    int * ix,
    int * iy )
```

Definition at line 1201 of file [TCSdrWXcpp.cpp](#).

8.30.4.21 NRMSIZ()

```
void NRMSIZ (
    void )
```

Definition at line 1457 of file [TCSdrWXcpp.cpp](#).

8.30.4.22 outgtext_()

```
void outgtext_ (
    char strng[] )
```

Definition at line 1357 of file [TCSdrWXcpp.cpp](#).

8.30.4.23 outtext_()

```
void outtext_ (
    char strng[] )
```

Definition at line 1496 of file [TCSdrWXcpp.cpp](#).

8.30.4.24 PNTABS()

```
void PNTABS (
    int * ix,
    int * iy )
```

Definition at line 1265 of file [TCSdrWXcpp.cpp](#).

8.30.4.25 PresetProgPar()

```
void PresetProgPar ( )
```

Definition at line 516 of file [TCSdrWXcpp.cpp](#).

8.30.4.26 RepaintBuffer()

```
void RepaintBuffer (
    wxDC & dc )
```

Definition at line 301 of file [TCSdrWXcpp.cpp](#).

8.30.4.27 RESTAT()

```
void RESTAT (
    char src[] )
```

Definition at line 1637 of file [TCSdrWXcpp.cpp](#).

8.30.4.28 SVSTAT()

```
void SVSTAT (
    char dst[] )
```

Definition at line 1626 of file [TCSdrWXcpp.cpp](#).

8.30.4.29 swind1_()

```
void swind1_ (
    int * ix1,
    int * iy1,
    int * ix2,
    int * iy2 )
```

Definition at line 1113 of file [TCSdrWXcpp.cpp](#).

8.30.4.30 TCSGraphicError()

```
void TCSGraphicError (
    int iErr,
    const char * msg )
```

Definition at line 1509 of file [TCSdrWXcpp.cpp](#).

8.30.4.31 TINPUT()

```
void TINPUT (
    int * ic )
```

Definition at line 1572 of file [TCSdrWXcpp.cpp](#).

8.30.4.32 TXTCOL()

```
void TXTCOL (
    int * iCol )
```

Definition at line 1322 of file [TCSdrWXcpp.cpp](#).

8.30.4.33 winlbl0()

```
void winlbl0 (
    const char PlWinNam[],
    const char StatWinNam[],
    const char IniFilNam[] )
```

Definition at line 872 of file [TCSdrWXcpp.cpp](#).

8.30.4.34 WINSELECT()

```
bool WINSELECT (
    wxWindowID * iD )
```

Definition at line 931 of file [TCSdrWXcpp.cpp](#).

8.30.4.35 XMLreadProgPar()

```
void XMLreadProgPar (
    const char * filename )
```

Definition at line 573 of file [TCSdrWXcpp.cpp](#).

8.30.5 Variable Documentation

8.30.5.1 ActiveCanvas

```
cTCScanvas* ActiveCanvas = NULL [static]
```

Definition at line 241 of file [TCSdrWXcpp.cpp](#).

8.30.5.2 ActiveCanvasID

```
wxWindowID ActiveCanvasID = 0 [static]
```

Definition at line 242 of file [TCSdrWXcpp.cpp](#).

8.30.5.3 iHardcopyCount

```
int iHardcopyCount = 1 [static]
```

Definition at line 148 of file [TCSdrWXcpp.cpp](#).

8.30.5.4 OpenCanvases

```
cTCScanvas* OpenCanvases[MAX_OPEN_CANVAS] = {} [static]
```

Definition at line 243 of file [TCSdrWXcpp.cpp](#).

8.30.5.5 szTCSErrorMsg

```
ErrMsg szTCSErrorMsg[(int) MSG_MAXERRNO+1] [static]
```

Initial value:

```
=
    {"Element 0 unused", "DOS",
    TCS_INIDEF_UNKNGRAPHCARD,
    TCS_INIDEF_NOFNFTIL,
    TCS_INIDEF_NOFNT,
    "DOS",
    TCS_INIDEF_HDCOPN,
    TCS_INIDEF_HDCWRT,
    "DOS",
    TCS_INIDEF_USR,
    TCS_INIDEF_HDCACT,
    TCS_INIDEF_USRWRN,
    TCS_INIDEF_EXIT,
    "Windows",
    "Windows",
    TCS_INIDEF_JOUCREATE,
    TCS_INIDEF_JOUMENTRY,
    TCS_INIDEF_JOUADD,
    TCS_INIDEF_JOUCLR,
    TCS_INIDEF_JOUUNKWN,
    TCS_INIDEF_XMLPARSER,
    TCS_INIDEF_XMLOPEN,
    TCS_INIDEF_UNKNAUDIO,
    TCS_INIDEF_USR2,
    TCS_INIDEF_INI2,
    "Maxerr only for internal Use" }
```

Definition at line 157 of file [TCSdrWXcpp.cpp](#).

8.30.5.6 szTCSHardcopyFile

```
char szTCSHardcopyFile[TCS_FILE_NAMELEN] = TCS_HDCFILE_NAME [static]
```

Definition at line 130 of file [TCSdrWXcpp.cpp](#).

8.30.5.7 szTCSIniFile

```
char szTCSIniFile[TCS_FILE_NAMELEN] = TCS_INIFILE_NAME [static]
```

Definition at line 129 of file [TCSdrWXcpp.cpp](#).

8.30.5.8 szTCSsect0

```
char szTCSsect0[TCS_FILE_NAMELEN] = TCS_INISECT0 [static]
```

Definition at line 134 of file [TCSdrWXcpp.cpp](#).

8.30.5.9 szTCSstatWindowName

```
char szTCSstatWindowName[TCS_WINDOW_NAMELEN] = TCS_STATWINDOW_NAME [static]
```

Definition at line 128 of file [TCSdrWXcpp.cpp](#).

8.30.5.10 szTCSWindowName

```
char szTCSWindowName[TCS_WINDOW_NAMELEN] = TCS_WINDOW_NAME [static]
```

Definition at line 127 of file [TCSdrWXcpp.cpp](#).

8.30.5.11 TCSColorTable

```
wxColour TCSColorTable[MAX_COLOR_INDEX+1] [static]
```

Initial value:

```
= {
    { 240, 240, 240, wxALPHA_OPAQUE },
    { 0, 0, 0, wxALPHA_OPAQUE },
    { 240, 80, 80, wxALPHA_OPAQUE },
    { 80, 240, 80, wxALPHA_OPAQUE },
    { 80, 240, 240, wxALPHA_OPAQUE },
    { 80, 80, 240, wxALPHA_OPAQUE },
    { 240, 240, 80, wxALPHA_OPAQUE },
    { 160, 160, 160, wxALPHA_OPAQUE },
    { 240, 80, 240, wxALPHA_OPAQUE },
    { 160, 0, 0, wxALPHA_OPAQUE },
    { 0, 160, 0, wxALPHA_OPAQUE },
    { 0, 0, 160, wxALPHA_OPAQUE },
    { 0, 160, 160, wxALPHA_OPAQUE },
    { 160, 80, 0, wxALPHA_OPAQUE },
    { 80, 80, 80, wxALPHA_OPAQUE },
    { 160, 0, 160, wxALPHA_OPAQUE }
}
```

Definition at line 219 of file [TCSdrWXcpp.cpp](#).

8.30.5.12 TCSDefaultBckCol

```
int TCSDefaultBckCol = TCS_INIDEF_BCKCOL [static]
```

Definition at line 147 of file [TCSdrWXcpp.cpp](#).

8.30.5.13 TCSDefaultLinCol

```
int TCSDefaultLinCol = TCS_INIDEF_LINCOL [static]
```

Definition at line 145 of file [TCSdrWXcpp.cpp](#).

8.30.5.14 TCSDefaultTxtCol

int TCSDefaultTxtCol = TCS_INIDEF_TXTCOL [static]
 Definition at line 146 of file TCSdrWXcpp.cpp.

8.30.5.15 TCSErrorLev

int TCSErrorLev[(int) MSG_MAXERRNO+1] [static]

Initial value:

```
=
    {10,10,
      TCS_INIDEF_UNKNGRAPHCARDL,
      TCS_INIDEF_NOFNTHILL,
      TCS_INIDEF_NOFNTHL,
      10,
      TCS_INIDEF_HDCOPNL,
      TCS_INIDEF_HDCWRTL,
      10,
      TCS_INIDEF_USRL,
      TCS_INIDEF_HDCACTL,
      TCS_INIDEF_USRWRNL,
      TCS_INIDEF_EXITL,
      10,
      10,
      TCS_INIDEF_JOUCREATEL,
      TCS_INIDEF_JOUMENTRYL,
      TCS_INIDEF_JOUADDL,
      TCS_INIDEF_JOUCLRL,
      TCS_INIDEF_JOUUNKWNL,
      TCS_INIDEF_XMLPARSERL,
      TCS_INIDEF_XMLOPENL,
      TCS_INIDEF_UNKNAUDIOL,
      TCS_INIDEF_USR2L,
      TCS_INIDEF_INI2L,
      10}
```

Definition at line 184 of file TCSdrWXcpp.cpp.

8.30.5.16 TCSwindowIniXrelpos

int TCSwindowIniXrelpos = TCS_INIDEF_WINPOSX [static]

Definition at line 137 of file TCSdrWXcpp.cpp.

8.30.5.17 TCSwindowIniXrelsiz

int TCSwindowIniXrelsiz = TCS_INIDEF_WINSIZX [static]

Definition at line 139 of file TCSdrWXcpp.cpp.

8.30.5.18 TCSwindowIniYrelpos

int TCSwindowIniYrelpos = TCS_INIDEF_WINPOSY [static]

Definition at line 138 of file TCSdrWXcpp.cpp.

8.30.5.19 TCSwindowIniYrelsiz

int TCSwindowIniYrelsiz = TCS_INIDEF_WINSIZY [static]

Definition at line 140 of file TCSdrWXcpp.cpp.

8.31 TCSdrWXcpp.cpp

```
00001 /** *****
00002 \file      TCSdrWXcpp.cpp
00003 \brief     wX Port: Low-Level Driver
00004 \version   0.9
00005 \author    (C) 2023 Dr.-Ing. Klaus Friedewald
```



```

00006 \copyright  GNU LESSER GENERAL PUBLIC LICENSE Version 3
00007 \~german
00008     Systemnahe Graphikroutinen für die Tektronix Emulation
00009 \note \verbatim
00010     1. ToDo
00011 \endverbatim
00012 \~english
00013     system-specific subroutines of the Tektronix emulation
00014 \note \verbatim
00015     1. ToDo
00016 \endverbatim
00017 \~
00018 ***** */
00019
00020
00021 /*
00022 ----- Debug Switches -----
00023 */
00024
00025 // #define wxDEBUG_LEVEL 0
00026 #define wxDEBUG_LEVEL 2 // Debug: Output into the status window
00027 // #define TRACE_CALLS // additional debug output: journalpointer
00028
00029 /*
00030 ----- Headerfiles -----
00031 */
00032
00033 // #include <wx/intl.h>
00034 // #include <wx/string.h>
00035
00036 #include <wx/frame.h> // needed for: class cTSCanvas
00037 #include <wx/panel.h>
00038 #include <wx/sizer.h>
00039 // #include <wx/display.h>
00040 // #include <wx/gdicmn.h>
00041
00042 #include <wx/dc.h> // needed for: subroutine RepaintBuffer
00043 #include <wx/dcclient.h>
00044
00045 #include <wx/log.h> // needed for: subroutine TCSGraphicError
00046 #include <wx/msgdlg.h>
00047
00048 #include <wx/stdpaths.h> // needed for: winlbl
00049 #include <wx/filename.h>
00050
00051 #include <wx/xml/xml.h> // Read inifiles
00052
00053 #include <wx/file.h>
00054
00055 #include "sglib.h" // Journal for repaint / hardcopy
00056
00057 #include "TCSdrWXcpp.hpp" // program configuration
00058 #include "TKTRNX.hpp" // common block TCS
00059 #include "G2dAG2.hpp" // common block AG2
00060 #include "graph2d.h" // contains forward declarations
00061
00062
00063
00064 /*
00065 ----- Declarations -----
00066 */
00067
00068 typedef struct xJournalEntry_typ {struct xJournalEntry_typ * previous;
00069                                 struct xJournalEntry_typ * next;
00070                                 int action; int i1; int i2;}
00071                                 xJournalEntry_typ;
00072
00073
00074 class cTSCanvas
00075 {
00076     public:
00077
00078         wxFrame* TCSframe; // windows
00079         wxPanel* TCSpaanel;
00080         wxLogWindow* logWindow;
00081         wxStatusBar* TCSstatusBar;
00082
00083         wxWindowID ID_TCSframe;
00084         wxWindowID ID_TCSpaanel;
00085         wxWindowID ID_TCSstatus;
00086
00087         wxPen TCSpen; //resources
00088         wxBrush TCBrush;
00089         wxFont TCFont;
00090
00091         bool ClippingNotActive = true; // drawing status
00092         int TCSpaanelKeyPressed;

```

```

00093     int TCSmouseButtonDown, TCSmouseX, TCSmouseY;
00094
00095     xJournalEntry_typ* xTCSJournal = NULL; // journal used as a drawing metafile
00096
00097     struct TKTRNX TekSav; // notepad for changing instances
00098     struct G2dAG2 AG2Sav;
00099     int DefaultLinColSav, DefaultTxtColSav, DefaultBckColSav;
00100     char HardcopyFileSav[TCS_FILE_NAMELEN], sect0Sav[TCS_FILE_NAMELEN];
00101
00102     cTCSCanvas(int iMode, wxFrame* parent, wxFrame* FrameToUse, wxStatusBar* StatusBarToUse);
00103     virtual ~cTCSCanvas();
00104
00105     protected:
00106
00107     private:
00108
00109     void CompleteCanvas (wxSize UseScreen, wxPoint PosScreen, wxSize MinScreen); // Add sizers,
    menus etc.
00110
00111     void OnTCSClose(wxCloseEvent& event); // event handlers
00112     void OnTCSPanelPaint(wxPaintEvent& event);
00113     void OnTCSPanelResize(wxSizeEvent& event);
00114     void OnTCSPanelKey(wxKeyEvent& event);
00115     void OnTCSmouseLeft(wxMouseEvent& event);
00116     void OnTCSmouseMiddle(wxMouseEvent& event);
00117     void OnTCSmouseRight(wxMouseEvent& event);
00118
00119 };
00120
00121
00122
00123 /*
00124 ----- Global Variables -----
00125 */
00126
00127 static char szTCSWindowName[TCS_WINDOW_NAMELEN] = TCS_WINDOW_NAME,
00128 szTCSstatWindowName[TCS_WINDOW_NAMELEN] = TCS_STATWINDOW_NAME,
00129 szTCSIniFile[TCS_FILE_NAMELEN] = TCS_INIFILE_NAME,
00130 szTCSHardcopyFile[TCS_FILE_NAMELEN] = TCS_HDCFILE_NAME,
00131 /* 129 szTCSGraphicFont[TCS_FILE_NAMELEN] = TCS_INIDEF_FONT,
00132 130 szTCSSysFont[TCS_FILE_NAMELEN] = TCS_INIDEF_SYSFONT,
00133 */
00134 szTCSsect0[TCS_FILE_NAMELEN] = TCS_INISECT0;
00135
00136
00137 static int TCSwindowIniXrelpos = TCS_INIDEF_WINPOSX, // window size/position
00138 TCSwindowIniYrelpos = TCS_INIDEF_WINPOSY, // at initt in % of Screen
00139 TCSwindowIniXrelsiz = TCS_INIDEF_WINSIZX,
00140 TCSwindowIniYrelsiz = TCS_INIDEF_WINSIZY,
00141 // TCSstatWindowIniXrelpos = TCS_INIDEF_STATPOSX, // dito
00142 // TCSstatWindowIniYrelpos = TCS_INIDEF_STATPOSY, // Statusfenster
00143 // TCSstatWindowIniXrelsiz = TCS_INIDEF_STATSIZX,
00144 // TCSstatWindowIniYrelsiz = TCS_INIDEF_STATSIZY,
00145 TCSDefaultLinCol = TCS_INIDEF_LINCOL,
00146 TCSDefaultTxtCol = TCS_INIDEF_TXTCOL,
00147 TCSDefaultBckCol = TCS_INIDEF_BCKCOL,
00148 iHardcopyCount = 1; // Zähler zur Erzeugung Filenamen
00149
00150
00151
00152 /*
00153 Assign error numbers to error messages
00154 */
00155
00156 typedef char ErrMsg[TCS_MESSAGELEN];
00157 static ErrMsg szTCSErrorMsg[(int) MSG_MAXERRNO+1] =
00158 { "Element 0 unused", "DOS",
00159 TCS_INIDEF_UNKNGRAPHCARD, // Errno 2
00160 TCS_INIDEF_NOFNFTIL, // Errno 3
00161 TCS_INIDEF_NOFNT, // Errno 4
00162 "DOS",
00163 TCS_INIDEF_HDCOPN, // Errno 6
00164 TCS_INIDEF_HDCWRT, // Errno 7
00165 "DOS",
00166 TCS_INIDEF_USR, // Errno 9
00167 TCS_INIDEF_HDCACT, // Errno 10
00168 TCS_INIDEF_USRWRN, // Errno 11
00169 TCS_INIDEF_EXIT, // Errno 12
00170 "Windows",
00171 "Windows",
00172 TCS_INIDEF_JOUCREATE, // Errno 15
00173 TCS_INIDEF_JOUMENTRY, // Errno 16
00174 TCS_INIDEF_JOUADD, // Errno 17
00175 TCS_INIDEF_JOUCLR, // Errno 18
00176 TCS_INIDEF_JOUUNKWN, // Errno 19
00177 TCS_INIDEF_XMLPARSER, // Errno 20
00178 TCS_INIDEF_XMLOPEN, // Errno 21

```

```

00179         TCS_INIDEF_UNKNAUDIO,      // Errno 22
00180         TCS_INIDEF_USR2,           // Errno 23
00181         TCS_INIDEF_INI2,           // Errno 24
00182         "Maxerr only for internal Use" };
00183
00184 static int      TCSErrorLev[(int) MSG_MAXERRNO+1] =
00185 {10,10,
00186   TCS_INIDEF_UNKNGRAPHCARDL, // Errno 2
00187   TCS_INIDEF_NOFNTFILL,      // Errno 3
00188   TCS_INIDEF_NOFNTL,         // Errno 4
00189   10,
00190   TCS_INIDEF_HDCOPNL,        // Errno 6
00191   TCS_INIDEF_HDCWRTL,        // Errno 7
00192   10,
00193   TCS_INIDEF_USRL,           // Errno 9
00194   TCS_INIDEF_HDCACTL,        // Errno 10
00195   TCS_INIDEF_USRWRNL,        // Errno 11
00196   TCS_INIDEF_EXITL,          // Errno 12
00197   10,
00198   10,
00199   TCS_INIDEF_JOUCREATEL,     // Errno 15
00200   TCS_INIDEF_JOENTRYL,       // Errno 16
00201   TCS_INIDEF_JOUADDL,        // Errno 17
00202   TCS_INIDEF_JOUCLRL,        // Errno 18
00203   TCS_INIDEF_JOUUNKWNL,      // Errno 19
00204   TCS_INIDEF_XMLPARSERL,     // Errno 20
00205   TCS_INIDEF_XMLOPENL,       // Errno 21
00206   TCS_INIDEF_UNKNAUDIOL,     // Errno 22
00207   TCS_INIDEF_USR2L,          // Errno 23
00208   TCS_INIDEF_INI2L,          // Errno 24
00209   10};
00210
00211
00212 /*
00213     Assign colour numbers VGA palette coordinates
00214 */
00215
00216
00217 #define MAX_COLOR_INDEX 15
00218
00219 static wxColour TCSColorTable[MAX_COLOR_INDEX+1] = {
00220     {240,240,240,wxALPHA_OPAQUE }, /* iCol= 00: weiss (DOS: 01) */
00221     { 0, 0, 0,wxALPHA_OPAQUE }, /* iCol= 01: schwarz (DOS:00) */
00222     {240, 80, 80,wxALPHA_OPAQUE }, /* iCol= 02: rot */
00223     { 80,240, 80,wxALPHA_OPAQUE }, /* iCol= 03: gruen */
00224     { 80,240,240,wxALPHA_OPAQUE }, /* iCol= 04: blau */
00225     { 80, 80,240,wxALPHA_OPAQUE }, /* iCol= 05: lila */
00226     {240,240, 80,wxALPHA_OPAQUE }, /* iCol= 06: gelb */
00227     {160,160,160,wxALPHA_OPAQUE }, /* iCol= 07: grau */
00228     {240, 80,240,wxALPHA_OPAQUE }, /* iCol= 08: violett */
00229     {160, 0, 0,wxALPHA_OPAQUE }, /* iCol= 09: mattrot */
00230     { 0,160, 0,wxALPHA_OPAQUE }, /* iCol= 10: mattgruen */
00231     { 0, 0,160,wxALPHA_OPAQUE }, /* iCol= 11: mattblau */
00232     { 0,160,160,wxALPHA_OPAQUE }, /* iCol= 12: mattlila */
00233     {160, 80, 0,wxALPHA_OPAQUE }, /* iCol= 13: orange */
00234     { 80, 80, 80,wxALPHA_OPAQUE }, /* iCol= 14: mattgrau */
00235     {160, 0,160,wxALPHA_OPAQUE } /* iCol= 15: mattviolett */
00236 };
00237
00238
00239 // static int      TCSEventFilterData; // Userdata, z.Zt. nicht verwendet
00240
00241 static cTCSCanvas*   ActiveCanvas = NULL;
00242 static wxWindowID     ActiveCanvasID = 0;
00243 static cTCSCanvas*   OpenCanvases[MAX_OPEN_CANVAS] = {};
00244
00245
00246
00247 // ----- Internal subroutines -----
00248
00249
00250 /*
00251     Initialization COMMON TKTRNX before creating new object of class cTCSCanvas
00252 */
00253
00254 void initt0 ()
00255 {
00256     tktrnx_.iLinCol= TCSDefaultLinCol; // reset colours
00257     tktrnx_.iTxtCol= TCSDefaultTxtCol;
00258     tktrnx_.iBckCol= TCSDefaultBckCol;
00259
00260     tktrnx_.ksizef = 0; // Reset FONT
00261     tktrnx_.kitalc = 0;
00262
00263     tktrnx_.xlog= 255.; // call LINTRN
00264     tktrnx_.ylog= 255.;
00265     tktrnx_.kminsx= 0; // call SWINDO (0,1023,0,780)

```

```

00266 tktrnx_.kmaxsx= (int) TEK_XMAX;
00267 tktrnx_.kminsy= 0;
00268 tktrnx_.kmaxsy= (int) TEK_YMAX;
00269 tktrnx_.tminvx= 0.; // call VWINDO (0.,1023.,0.,780.)
00270 tktrnx_.tmaxvx= TEK_XMAX;
00271 tktrnx_.tminvy= 0.;
00272 tktrnx_.tmaxvy= TEK_YMAX;
00273 tktrnx_.xfac= 1.; // subroutine RESCAL, called from LINTRN...VWINDO
00274 tktrnx_.yfac= 1.;
00275 tktrnx_.trsinf= 0.; // call RROTAT (0.)
00276 tktrnx_.trcosf= 1.;
00277 tktrnx_.trscal= 1.; // call RSCALE (1.)
00278
00279 tktrnx_.klmrgn= 0; // call SETMRG (0,1023)
00280 tktrnx_.krmrgn= (int) TEK_XMAX;
00281 }
00282
00283
00284 wxWindowID getCanvasID (wxWindowID win2search)
00285 {
00286     int i;
00287
00288     i= MAX_OPEN_CANVAS-1;
00289     while (i >= 0) {
00290         if (OpenCanvases[i] != nullptr) {
00291             if ( (OpenCanvases[i]->ID_TCSframe == win2search) ||
00292                 (OpenCanvases[i]->ID_TCSpanel == win2search) ) return i;
00293         }
00294         i--;
00295     }
00296     return i; // i<0 -> window is not a member of any canvas
00297 }
00298
00299
00300
00301 void RepaintBuffer (wxDC& dc)
00302 {
00303     xJournalEntry_typ * xJournalEntry;
00304     int DashStyle;
00305     wxCoord w,h;
00306     int iStringLen, iStringActual;
00307     char szString [TCS_MESSAGELEN+1];
00308
00309     wxLogDebug ( wxT("RepaintBuffer> called"));
00310 #ifndef TRACE_CALLS
00311     wxLogDebug ( wxT("RepaintBuffer> xTCSJournal: Ptr= %p / Current Entry: Ptr= %p"),
00312                 ActiveCanvas->xTCSJournal, xJournalEntry);
00313 #endif // TRACE_CALLS
00314
00315     SGLIB_DL_LIST_GET_LAST(xJournalEntry_typ, ActiveCanvas->xTCSJournal, previous, next,
00316                             xJournalEntry)
00317     while (xJournalEntry != NULL) {
00318 #ifndef TRACE_CALLS
00319         wxLogDebug ( wxT("RepaintBuffer> xTCSJournal: Ptr= %p"), ActiveCanvas->xTCSJournal);
00320         wxLogDebug ( wxT("RepaintBuffer> Current Entry: Ptr= %p / previous: Ptr= %p / next: Ptr= %p"),
00321                     xJournalEntry, xJournalEntry->previous, xJournalEntry->next);
00322         wxLogDebug ( wxT("RepaintBuffer> XACTION_??? = %i (i1= %i, i2= %i)",
00323                     xJournalEntry->action, xJournalEntry->i1, xJournalEntry->i2 );
00324 #endif // TRACE_CALLS
00325
00326         switch (xJournalEntry->action) {
00327             case XACTION_INITT: {
00328                 initt0 ();
00329
00330                 ActiveCanvas->TCSpen.SetColour (TCSColourTable[tktrnx_.iLinCol]);
00331                 ActiveCanvas->TCSpen.SetStyle (wxPENSTYLE_SOLID);
00332                 dc.SetPen(ActiveCanvas->TCSpen); // Umbedingt Initialstift setzen !!!
00333
00334                 tktrnx_.kbeamx = tktrnx_.klmrgn; // call HOME, first guess khomey in INITT1()
00335                 tktrnx_.kbeamy = tktrnx_.khomey;
00336             } // continue with Erase
00337             case XACTION_ERASE: {
00338                 ActiveCanvas->TCSbrush.SetColour (TCSColourTable[tktrnx_.iBckCol]);
00339                 dc.SetBrush (ActiveCanvas->TCSbrush);
00340                 dc.SetBackground (ActiveCanvas->TCSbrush);
00341                 dc.Clear();
00342
00343                 ActiveCanvas->TCSfont = wxFont(wxFONTSIZE_MEDIUM, wxFONTFAMILY_TELETYPE,
00344                                                 wxFONTSTYLE_NORMAL, wxFONTWEIGHT_NORMAL, false);
00345                 ActiveCanvas->TCSfont.SetFractionalPointSize
00346                 (TEK_YMAX*TCS_REL_CHR_HEIGHT*(1+tktrnx_.ksizef));
00347                 dc.SetFont (ActiveCanvas->TCSfont);
00348
00349                 dc.GetTextExtent ("MMMMMMMMMM", &w, &h);
00350                 tktrnx_.khorsz = (int) (w*0.1+0.5);
00351                 tktrnx_.kversz = h;

```

```

00350         tktrnx_.khomey= (int) TEK_YMAX - tktrnx_.kversz;
00351
00352         break; // Erase don't change the cursor position
00353     }
00354     case XACTION_MOVABS: {
00355         tktrnx_.kbeamx= xJournalEntry->i1;
00356         tktrnx_.kbeamy= xJournalEntry->i2;
00357         break;
00358     }
00359     case XACTION_DRWABS: {
00360         if (!ActiveCanvas->ClippingNotActive) {
00361             dc.SetClippingRegion(tktrnx_.kminsx, tktrnx_.kminsy,
00362                 tktrnx_.kmaxsx-tktrnx_.kminsx, tktrnx_.kmaxsy-tktrnx_.kminsy);
00363         }
00364         dc.DrawLine (tktrnx_.kbeamx,tktrnx_.kbeamy ,
00365             xJournalEntry->i1, xJournalEntry->i2);
00366         tktrnx_.kbeamx= xJournalEntry->i1;
00367         tktrnx_.kbeamy= xJournalEntry->i2;
00368         dc.DrawPoint (tktrnx_.kbeamx, tktrnx_.kbeamy); // Set last point of line
00369         if (!ActiveCanvas->ClippingNotActive) dc.DestroyClippingRegion();
00370         break;
00371     }
00372     case XACTION_DSHSTYLE: {
00373         switch (xJournalEntry->i1) {
00374             case 0: DashStyle= wxPENSTYLE_SOLID;
00375                 break;
00376             case 1: DashStyle= wxPENSTYLE_DOT;
00377                 break;
00378             case 2: DashStyle= wxPENSTYLE_DOT_DASH;
00379                 break;
00380             case 3: DashStyle= wxPENSTYLE_LONG_DASH;
00381                 break;
00382             default: DashStyle= wxPENSTYLE_SOLID;
00383         }
00384         break;
00385     }
00386     case XACTION_DSHABS: {
00387         ActiveCanvas->TCSpen.SetStyle (DashStyle);
00388         dc.SetPen(ActiveCanvas->TCSpen);
00389         if (!ActiveCanvas->ClippingNotActive) {
00390             dc.SetClippingRegion(tktrnx_.kminsx, tktrnx_.kminsy,
00391                 tktrnx_.kmaxsx-tktrnx_.kminsx, tktrnx_.kmaxsy-tktrnx_.kminsy);
00392         }
00393         dc.DrawLine (tktrnx_.kbeamx,tktrnx_.kbeamy ,
00394             xJournalEntry->i1, xJournalEntry->i2);
00395         if (!ActiveCanvas->ClippingNotActive) dc.DestroyClippingRegion();
00396         ActiveCanvas->TCSpen.SetStyle (wxPENSTYLE_SOLID);
00397         dc.SetPen(ActiveCanvas->TCSpen); // reset to SOLID
00398
00399         tktrnx_.kbeamx= xJournalEntry->i1;
00400         tktrnx_.kbeamy= xJournalEntry->i2;
00401         break;
00402     }
00403     case XACTION_PNTABS: {
00404         tktrnx_.kbeamx= xJournalEntry->i1;
00405         tktrnx_.kbeamy= xJournalEntry->i2;
00406         if (!ActiveCanvas->ClippingNotActive) {
00407             dc.SetClippingRegion(tktrnx_.kminsx, tktrnx_.kminsy,
00408                 tktrnx_.kmaxsx-tktrnx_.kminsx, tktrnx_.kmaxsy-tktrnx_.kminsy);
00409         }
00410         dc.DrawPoint (tktrnx_.kbeamx, tktrnx_.kbeamy);
00411         if (!ActiveCanvas->ClippingNotActive) dc.DestroyClippingRegion();
00412         break;
00413     }
00414     case XACTION_BCKCOL: {
00415         tktrnx_.iBckCol= xJournalEntry->i1;
00416         ActiveCanvas->TCSbrush.SetColour (TCSColorTable[tktrnx_.iBckCol]);
00417         dc.SetBrush (ActiveCanvas->TCSbrush);
00418         dc.SetBackground (ActiveCanvas->TCSbrush);
00419         break;
00420     }
00421     case XACTION_LINCOL: {
00422         tktrnx_.iLinCol= xJournalEntry->i1;
00423         ActiveCanvas->TCSpen.SetColour (TCSColorTable[tktrnx_.iLinCol]);
00424         dc.SetPen(ActiveCanvas->TCSpen);
00425         break;
00426     }
00427     case XACTION_TXTCOL: {
00428         tktrnx_.iTxtCol= xJournalEntry->i1;
00429         dc.SetTextForeground (TCSColorTable[tktrnx_.iTxtCol]);
00430         break;
00431     }
00432     case XACTION_FONTATTR: {
00433         tktrnx_.kitalc= xJournalEntry->i1;
00434         if (tktrnx_.kitalc > 0) {
00435             ActiveCanvas->TCSfont.SetStyle (wxFONTSTYLE_ITALIC);
00436         } else {

```

```

00437         ActiveCanvas->TCSfont.SetStyle (wxFONTSTYLE_NORMAL);
00438     }
00439
00440     if (tktrnx_.ksizef != xJournalEntry->i2) {
00441         tktrnx_.ksizef= xJournalEntry->i2;
00442         if (tktrnx_.ksizef > 0) {
00443             ActiveCanvas->TCSfont.SetFractionalPointSize (2.0* TEK_YMAX*TCS_REL_CHR_HEIGHT);
00444         } else {
00445             ActiveCanvas->TCSfont.SetFractionalPointSize (TEK_YMAX *TCS_REL_CHR_HEIGHT);
00446         }
00447     }
00448     dc.SetFont(ActiveCanvas->TCSfont);
00449     dc.GetTextExtent ("MMMMMMMMMM", &w, &h);
00450     tktrnx_.khorsz = (int) (w*0.1+0.5);
00451     tktrnx_.kversz = h;
00452     tktrnx_.khomey= TEK_YMAX - tktrnx_.kversz;
00453     break;
00454 }
00455 case XACTION_GTEXT: {
00456     iStringActual= 0;
00457     iStringLen= xJournalEntry->i1;
00458     if (iStringLen > TCS_MESSAGELEN) iStringLen= TCS_MESSAGELEN;
00459     if (iStringLen == 0) break;
00460     szString[iStringActual++]= xJournalEntry->i2;
00461     if (iStringLen == 1) {
00462         szString[iStringActual]= '\\0';
00463         dc.GetTextExtent (szString, &w, &h);
00464         dc.DrawText (szString, tktrnx_.kbeamx, tktrnx_.kbeamx+ TCS_REL_CHR_SPACING*h); // +h:
Plot text from UPPER left corner
00465         tktrnx_.kbeamx += w; // move cursor to End of String
00466     }
00467     break;
00468 }
00469 case XACTION_ASCII: {
00470     if (iStringActual < iStringLen) {
00471         szString[iStringActual++]= xJournalEntry->i1;
00472         if (iStringActual < iStringLen) szString[iStringActual++]= xJournalEntry->i2;
00473         if (iStringActual >= iStringLen) {
00474             szString[iStringActual]= '\\0';
00475             dc.GetTextExtent (szString, &w, &h);
00476             dc.DrawText (szString, tktrnx_.kbeamx, tktrnx_.kbeamx+ TCS_REL_CHR_SPACING*h);
00477             tktrnx_.kbeamx += w;
00478         }
00479     }
00480     break;
00481 }
00482 case XACTION_NOOP: {
00483     break;
00484 }
00485 case XACTION_CLIP: {
00486     ActiveCanvas->ClippingNotActive= (xJournalEntry->i1 == 0);
00487     break;
00488 }
00489 case XACTION_CLIP1: {
00490     tktrnx_.kminsx= xJournalEntry->i1;
00491     tktrnx_.kminsy= xJournalEntry->i2;
00492     break;
00493 }
00494 case XACTION_CLIP2: {
00495     tktrnx_.kmaxsx= xJournalEntry->i1;
00496     tktrnx_.kmaxsy= xJournalEntry->i2;
00497     break;
00498 }
00499 default: {
00500     wxLogDebug (wxT("RepaintBuffer> XACTION_XXX"));
00501     break;
00502 }
00503 }
00504 xJournalEntry= xJournalEntry -> previous;
00505 }
00506 #ifdef TRACE_CALLS
00507     wxLogDebug ( wxT("RepaintBuffer> xTCSJournal: Ptr= %p / Last Entry: Ptr= %p"),
ActiveCanvas->xTCSJournal, xJournalEntry);
00508 #endif // TRACE_CALLS
00509 }
00510
00511
00512 /*
00513     Setting default values before reading the initialization files
00514 */
00515
00516 void PresetProgPar ()
00517 {
00518     TCSDefaultLinCol= TCS_INIDEF_LINCOL;
00519     TCSDefaultTxtCol= TCS_INIDEF_TXTCOL;
00520     TCSDefaultBckCol= TCS_INIDEF_BCKCOL;
00521

```

```

00522     TCSwindowIniXrelpos= TCS_INIDEF_WINPOSX;
00523     TCSwindowIniYrelpos= TCS_INIDEF_WINPOSY;
00524     TCSwindowIniXrelsiz= TCS_INIDEF_WINSIZX;
00525     TCSwindowIniYrelsiz= TCS_INIDEF_WINSIZY;
00526
00527     strncpy (szTCSWindowName, TCS_WINDOW_NAME, TCS_WINDOW_NAMELEN);
00528     strncpy (szTCSStatWindowName, TCS_STATWINDOW_NAME, TCS_WINDOW_NAMELEN);
00529     strncpy (szTCSIniFile, "", TCS_FILE_NAMELEN);
00530     strncpy (szTCSsect0, TCS_INISECT0, TCS_FILE_NAMELEN);
00531
00532     // No Reset of Hardcopyname and Counter
00533
00534     // Error messages should be changed only once
00535
00536 }
00537
00538
00539
00540 void CustomizeProgPar ()
00541 #if (TCS_WINDOW_NAMELEN <= TCS_FILE_NAMELEN) // Get a safe buffer
00542     #define TMPSTRLEN TCS_FILE_NAMELEN
00543 #else
00544     #define TMPSTRLEN TCS_WINDOW_NAMELEN
00545 #endif
00546 {
00547     size_t iL;
00548     char* szTemp;
00549     char TmpStr[TMPSTRLEN];
00550     wxString wxTmpStr;
00551     wxFileName wxTmpFilNam;
00552
00553     szTemp= strstr (szTCSWindowName, PROGDIRTOKEN); // Default ProgDir?
00554     if (szTemp != NULL) {
00555         strncpy (TmpStr, szTCSWindowName, TMPSTRLEN);
00556         wxTmpFilNam= wxStandardPaths::Get().GetExecutablePath();
00557         wxTmpStr= wxTmpFilNam.GetFullName();
00558         iL= szTemp-szTCSWindowName;
00559         if ((TCS_WINDOW_NAMELEN-iL) > 1) {
00560             strncpy (szTemp, wxTmpStr, TCS_WINDOW_NAMELEN-iL);
00561             if ((TCS_WINDOW_NAMELEN-iL-wxTmpStr.length()) > 1) {
00562                 strncpy (&szTCSWindowName[iL+wxTmpStr.length()],
00563                     &TmpStr[iL+strlen(PROGDIRTOKEN)], TCS_WINDOW_NAMELEN-iL-wxTmpStr.length());
00564             }
00565         }
00566         szTCSWindowName[TCS_WINDOW_NAMELEN-1]= '\0'; // just in case...
00567     }
00568 #undef TMPSTRLEN
00569 }
00570
00571
00572
00573 void XMLreadProgPar (const char * filename)
00574 {
00575     wxXmlDocument xmlDoc;
00576     wxXmlNode *node, *node1, *NodeSect0;
00577
00578     size_t iL;
00579
00580     long longTmp;
00581     wxString wxTmpStr;
00582
00583
00584     if (filename[0] != '\0') {
00585         if (!wxFileExists(filename)) {
00586             TCSGraphicError (ERR_XMLOPEN, filename); // No input file
00587             return; // give warning and continue with defaults
00588         }
00589         if (!xmlDoc.Load(filename)) {
00590             TCSGraphicError (ERR_XMLOPEN, filename); // Unknown file error
00591             return; // unexpected file error -> handle error in any case
00592         }
00593         if (xmlDoc.GetRoot() == nullptr) {
00594             TCSGraphicError (ERR_XMLOPEN, filename); // No root node
00595             return;
00596         }
00597         NodeSect0= nullptr;
00598         if (xmlDoc.GetRoot()->GetName().IsSameAs(TCS_INISECT0)) {
00599             NodeSect0= xmlDoc.GetRoot();
00600         } else {
00601             node= xmlDoc.GetRoot()->GetChildren();
00602             while (node != nullptr) {
00603                 if (node->GetName().IsSameAs(TCS_INISECT0)) {
00604                     NodeSect0= node;
00605                     break;
00606                 }
00607                 node= node->GetNext();
00608             }

```

```

00609     }
00610     if (NodeSect0 != nullptr) {
00611         node1= NodeSect0->GetChildren();
00612         while (node1 != nullptr) {
00613             if (node1->GetName().IsSameAs(TCS_INISECT1)) {
00614                 node= node1->GetChildren();
00615                 while (node != nullptr) {
00616                     if (node->GetName().IsSameAs(TCS_INIVAR_WINNAM)) {
00617                         iL= node->GetNodeContent().length();
00618                         if (iL > 0) {
00619                             wxTmpStr= node->GetNodeContent().Truncate(TCS_WINDOW_NAMELEN);
00620                             strncpy (szTCSWindowName, wxTmpStr.c_str(), TCS_WINDOW_NAMELEN);
00621                         }
00622                     } else if (node->GetName().IsSameAs(TCS_INIVAR_STATNAM)) {
00623                         iL= node->GetNodeContent().length();
00624                         if (iL > 0) {
00625                             wxTmpStr= node->GetNodeContent().Truncate(TCS_WINDOW_NAMELEN);
00626                             strncpy (szTCSstatWindowName, wxTmpStr.c_str(), TCS_WINDOW_NAMELEN);
00627                         }
00628                     }
00629                     node= node->GetNext();
00630                 } // end dataloop TCS_INISECT1
00631             }
00632             } else if (node1->GetName().IsSameAs(TCS_INISECT2)) { // TCS_INISECT2: Layout
00633                 node= node1->GetChildren();
00634                 while (node != nullptr) {
00635                     wxTmpStr= node->GetNodeContent();
00636                     if (node->GetName().IsSameAs(TCS_INIVAR_WINPOSX)) {
00637                         if (wxTmpStr.IsNumber()) {
00638                             TCSwindowIniXrelpos= wxAtoi(wxTmpStr);
00639                         }
00640                     } else if (node->GetName().IsSameAs(TCS_INIVAR_WINPOSY)) {
00641                         if (wxTmpStr.IsNumber()) {
00642                             TCSwindowIniYrelpos= wxAtoi(wxTmpStr);
00643                         }
00644                     } else if (node->GetName().IsSameAs(TCS_INIVAR_WINSIZX)) {
00645                         if (wxTmpStr.IsNumber()) {
00646                             TCSwindowIniXrelsiz= wxAtoi(wxTmpStr);
00647                         }
00648                     } else if (node->GetName().IsSameAs(TCS_INIVAR_WINSIZY)) {
00649                         if (wxTmpStr.IsNumber()) {
00650                             TCSwindowIniYrelsiz= wxAtoi(wxTmpStr);
00651                         }
00652                     }
00653                 } else if (node->GetName().IsSameAs(TCS_INIVAR_STATPOSX)) {
00654                     if (wxTmpStr.IsNumber()) {
00655                         TCSstatWindowIniXrelpos= wxAtoi(wxTmpStr);
00656                     }
00657                 } else if (node->GetName().IsSameAs(TCS_INIVAR_STATPOSY)) {
00658                     if (wxTmpStr.IsNumber()) {
00659                         TCSstatWindowIniYrelpos= wxAtoi(wxTmpStr);
00660                     }
00661                 } else if (node->GetName().IsSameAs(TCS_INIVAR_STATSIZX)) {
00662                     if (wxTmpStr.IsNumber()) {
00663                         TCSstatWindowIniXrelsiz= wxAtoi(wxTmpStr);
00664                     }
00665                 } else if (node->GetName().IsSameAs(TCS_INIVAR_STATSIZY)) {
00666                     if (wxTmpStr.IsNumber()) {
00667                         TCSstatWindowIniYrelsiz= wxAtoi(wxTmpStr);
00668                     }
00669                 }
00670             } else if (node->GetName().IsSameAs(TCS_INIVAR_LINCOL)) {
00671                 if (wxTmpStr.IsNumber()) {
00672                     TCSDefaultLinCol= wxAtoi(wxTmpStr);
00673                 }
00674             } else if (node->GetName().IsSameAs(TCS_INIVAR_TXTCOL)) {
00675                 if (wxTmpStr.IsNumber()) {
00676                     TCSDefaultTxtCol= wxAtoi(wxTmpStr);
00677                 }
00678             } else if (node->GetName().IsSameAs(TCS_INIVAR_BCKCOL)) {
00679                 if (wxTmpStr.IsNumber()) {
00680                     TCSDefaultBckCol= wxAtoi(wxTmpStr);
00681                 }
00682             }
00683             node= node->GetNext();
00684         } // end dataloop TCS_INISECT2
00685     }
00686     node1= node1->GetNext();
00687 }
00688 }
00689 }
00690 }
00691 }
00692 }
00693 }
00694 }
00695 /* ----- Object cTCScanvas ----- */

```



```

00696
00697
00698 cTCSCanvas::cTCSCanvas(int iMode, wxFrame* parent, wxFrame* FrameToUse, wxStatusBar* StatusBarToUse)
00699 {
00700     wxRect Screen;
00701     wxSize UseScreen, MinScreen;
00702     wxPoint PosScreen;
00703
00704     if (iMode == 0) return;
00705
00706     if (FrameToUse == nullptr) {
00707         ID_TCSframe = wxNewId(); // TCSframe->GetID()
00708         TCSframe = new wxFrame(parent, ID_TCSframe, szTCSWindowName, wxDefaultPosition, wxDefaultSize,
wxDEFAULT_FRAME_STYLE, wxString::Format(wxT("%i"), ID_TCSframe));
00709         TCSstatusBar = TCSframe->GetStatusBar();
00710     } else {
00711         TCSframe = FrameToUse; // Use given plot frame
00712         ID_TCSframe = FrameToUse->GetId();
00713     }
00714
00715     TCSstatusBar = StatusBarToUse;
00716     if (StatusBarToUse != nullptr) {
00717         ID_TCSstatus = TCSstatusBar->GetId();
00718     } else {
00719         ID_TCSstatus = wxID_NONE;
00720     }
00721
00722     if (iMode <= 2) { // New window: use screensize/title from TCS initialization
00723         Screen = wxGetClientDisplayRect (); // usable screen size
00724         if (TCSwindowIniYrelsiz > 0) {
00725             UseScreen.x = TCSwindowIniXrelsiz * Screen.width / 100;
00726             UseScreen.y = TCSwindowIniYrelsiz * Screen.height / 100; // TCSframe->GetMaxClientSize()
00727             PosScreen.x = TCSwindowIniXrelpos * Screen.width / 100;
00728             PosScreen.y = TCSwindowIniYrelpos * Screen.height / 100; // TCSframe->GetScreenPosition()
00729             MinScreen = wxSize(-1,-1); // No restriction
00730         }
00731         if (strlen(szTCSWindowName)>0) TCSframe->SetLabel(szTCSWindowName); // only for iMode=2 relevant
00732
00733         if (TCSstatusBar == nullptr) {
00734             ID_TCSstatus = wxNewId();
00735             TCSstatusBar = new wxStatusBar(TCSframe, ID_TCSstatus, wxSTB_DEFAULT_STYLE,
wxString::Format(wxT("%i"), ID_TCSstatus));
00736             TCSstatusBar->SetFieldsCount(1);
00737             TCSframe->SetStatusBar(TCSstatusBar);
00738         }
00739     } else { // keep current screensize and title
00740         UseScreen = TCSframe->GetClientSize ();
00741         PosScreen = wxPoint(-1,-1); // x < 0 -> don't touch position
00742         MinScreen = UseScreen; // don't allow screensize 0
00743     }
00744     CompleteCanvas(UseScreen, PosScreen, MinScreen);
00745 }
00746
00747
00748
00749 void cTCSCanvas::CompleteCanvas (wxSize UseScreen, wxPoint PosScreen, wxSize MinScreen)
00750 {
00751     wxBoxSizer* TCSBoxSizer;
00752     ID_TCSpanel = wxNewId();
00753     TCSpanel = new wxPanel(TCSframe, ID_TCSpanel, wxDefaultPosition, UseScreen, wxTAB_TRAVERSAL,
wxString::Format(wxT("%i"), ID_TCSpanel));
00754     TCSpanel->SetMinSize(MinScreen);
00755     TCSpanel->SetMaxSize(wxSize(-1,-1));
00756     TCSBoxSizer = new wxBoxSizer(wxHORIZONTAL);
00757     TCSBoxSizer->Add(TCSpanel, 1, wxALL|wxEXPAND, 5);
00758     TCSframe->SetSizer(TCSBoxSizer);
00759     TCSBoxSizer->Fit(TCSframe);
00760     TCSBoxSizer->SetSizeHints(TCSframe);
00761
00762     TCSframe->SetClientSize(UseScreen);
00763     if (PosScreen.x > 0) {
00764         TCSframe->Move(PosScreen);
00765     }
00766
00767     TCSframe->Connect(wxID_ANY, wxEVT_CLOSE_WINDOW, (wxObjectEventFunction) &cTCSCanvas::OnTCSClose);
00768
00769     TCSpanel->Connect(wx.EVT_PAINT, (wxObjectEventFunction) &cTCSCanvas::OnTCSpanelPaint, 0, this->TCSframe);
00770     TCSpanel->Connect(wx.EVT_SIZE,
(wxObjectEventFunction) &cTCSCanvas::OnTCSpanelResize, 0, this->TCSframe);
00771     TCSpanel->Connect(wx.EVT_KEY_DOWN, (wxObjectEventFunction) &cTCSCanvas::OnTCSpanelKey);
00772     TCSpanel->Connect(wx.EVT_LEFT_DOWN, (wxObjectEventFunction) &cTCSCanvas::OnTCSmouseLeft);
00773     TCSpanel->Connect(wx.EVT_MIDDLE_DOWN, (wxObjectEventFunction) &cTCSCanvas::OnTCSmouseMiddle);
00774     TCSpanel->Connect(wx.EVT_RIGHT_DOWN, (wxObjectEventFunction) &cTCSCanvas::OnTCSmouseRight);
00775 }
00776
00777

```

```

00778
00779 cTCSCanvas::~cTCSCanvas()
00780 {
00781     finitt_ (NULL, NULL); // -> Destroy ();
00782 }
00783
00784
00785 void cTCSCanvas::OnTCSClose(wxCloseEvent& event)
00786 {
00787     if ((event.GetId() == ActiveCanvas->ID_TCSframe) ||
00788         (event.GetId() == ActiveCanvas->ID_TCSpanel)) {
00789         finitt_ (NULL, NULL); // -> Destroy ();
00790     }
00791 }
00792
00793
00794 void cTCSCanvas::OnTCSpanelPaint(wxPaintEvent& event)
00795 {
00796     wxWindowID RequestingWindowID, WorkWindowID;
00797
00798     WorkWindowID = ActiveCanvasID; // store for further plotting
00799     RequestingWindowID = getCanvasID (event.GetId());
00800     if (RequestingWindowID >= 0) { // requested window belongs to a TCSCanvas
00801         if (RequestingWindowID != WorkWindowID) WINSELECT (&RequestingWindowID);
00802         wxPaintDC dc (ActiveCanvas->TCSpanel);
00803         dc.GetSize (&tktrnx_.kScrX, &tktrnx_.kScrY);
00804         dc.SetAxisOrientation (true, true); // y-axis bottom->up
00805         dc.SetDeviceOrigin (0., tktrnx_.kScrY); // (0,0) lower left corner
00806         dc.SetLogicalScale (tktrnx_.kScrX/TEK_XMAX, tktrnx_.kScrY/TEK_YMAX);
00807         RepaintBuffer (dc);
00808         if (RequestingWindowID != WorkWindowID) WINSELECT (&WorkWindowID);
00809     }
00810 }
00811
00812
00813
00814 void cTCSCanvas::OnTCSpanelResize(wxSizeEvent& event)
00815 {
00816     wxWindowID RequestingWindowID;
00817
00818     RequestingWindowID = getCanvasID (event.GetId());
00819     if (RequestingWindowID >= 0) { // requesting window belongs to a TCSCanvas
00820         OpenCanvases[RequestingWindowID]->TCSpanel->Refresh (); // Redraw with new scale -> wxEVT_PAINT
00821     } // Only OnTCSpanelPaint() switches windows
00822 }
00823
00824
00825
00826 void cTCSCanvas::OnTCSpanelKey(wxKeyEvent& event)
00827 {
00828     ActiveCanvas->TCSpanelKeyPressed= event.GetKeyCode();
00829     if ((!event.m_shiftDown) && (ActiveCanvas->TCSpanelKeyPressed > 0x40)
00830         && (ActiveCanvas->TCSpanelKeyPressed < 0x5b) ) {
00831         ActiveCanvas->TCSpanelKeyPressed+= 0x20; // lower case ASCII
00832     }
00833 }
00834
00835
00836
00837 void cTCSCanvas::OnTCSmouseLeft(wxMouseEvent& event)
00838 {
00839     ActiveCanvas->TCSmouseButtonDown= 1;
00840     event.GetPosition(&ActiveCanvas->TCSmouseX, &ActiveCanvas->TCSmouseY);
00841     ActiveCanvas->TCSmouseX= ActiveCanvas->TCSmouseX * TEK_XMAX/tktrnx_.kScrX;
00842     ActiveCanvas->TCSmouseY= TEK_YMAX - (ActiveCanvas->TCSmouseY * TEK_YMAX/tktrnx_.kScrY);
00843 }
00844
00845
00846
00847 void cTCSCanvas::OnTCSmouseMiddle(wxMouseEvent& event)
00848 {
00849     ActiveCanvas->TCSmouseButtonDown= 4; // same as in DOS-port
00850     event.GetPosition(&ActiveCanvas->TCSmouseX, &ActiveCanvas->TCSmouseY);
00851     ActiveCanvas->TCSmouseX= ActiveCanvas->TCSmouseX * TEK_XMAX/tktrnx_.kScrX;
00852     ActiveCanvas->TCSmouseY= TEK_YMAX - (ActiveCanvas->TCSmouseY * TEK_YMAX/tktrnx_.kScrY);
00853 }
00854
00855
00856 void cTCSCanvas::OnTCSmouseRight(wxMouseEvent& event)
00857 {
00858     ActiveCanvas->TCSmouseButtonDown= 2;
00859     event.GetPosition(&ActiveCanvas->TCSmouseX, &ActiveCanvas->TCSmouseY);
00860     ActiveCanvas->TCSmouseX= ActiveCanvas->TCSmouseX * TEK_XMAX/tktrnx_.kScrX;
00861     ActiveCanvas->TCSmouseY= TEK_YMAX - (ActiveCanvas->TCSmouseY * TEK_YMAX/tktrnx_.kScrY);
00862 }
00863
00864

```

```

00865
00866 /*
00867 ----- User routines: Initialization -----
00868 */
00869
00870
00871 extern "C" {
00872     void winlb10 (const char PloWinNam[], const char StatWinNam[], const char IniFilNam[])
00873     {
00874         size_t iL;
00875         char* szTemp;
00876         char tmpstr[TCS_FILE_NAMELEN], PathSeparator[2];
00877
00878         iL= strlen(PloWinNam);
00879         if (iL > (TCS_WINDOW_NAMELEN-1)) iL= TCS_WINDOW_NAMELEN-1;
00880         if (iL > 0) {
00881             strncpy( szTCSWindowName, PloWinNam, iL); // Destination is zero-padded
00882             szTCSWindowName[iL]= '\0'; // just in case iL>= TCS_WINDOW_NAMELEN
00883         }
00884
00885         iL= strlen(StatWinNam);
00886         if (iL > (TCS_WINDOW_NAMELEN-1)) iL= TCS_WINDOW_NAMELEN-1;
00887         if (iL > 0) {
00888             strncpy( szTCSstatWindowName, StatWinNam, iL);
00889             szTCSstatWindowName[iL]= '\0';
00890         }
00891
00892         iL= strlen(IniFilNam);
00893         if (iL > (TCS_FILE_NAMELEN-1)) iL= TCS_FILE_NAMELEN-1;
00894         if (iL > 0) {
00895             strncpy( szTCSIniFile, IniFilNam, iL);
00896             szTCSIniFile[iL]= '\0';
00897             szTemp= strstr (szTCSIniFile, "@"); // section Level0?
00898             if (szTemp != 0) {
00899                 strncpy (szTCSsect0, &szTemp[1], iL); // len(szSect0)=TCS_FILE_NAMELEN --> iL o.k.
00900                 szTemp[0]= '\0'; // cut of @Section0 in szTCSIniFile
00901             }
00902         }
00903         iL= strlen(szTCSIniFile); // perhaps shortened by @ processing
00904         if (iL > 0) {
00905             szTemp= strstr (szTCSIniFile, INIFILEXTOKEN); // Default extension?
00906             if (szTemp != 0) {
00907                 strncpy (szTemp, INIFILEXT, iL); // Sideeffect: szTCSIniFile with extension
00908                 szTCSIniFile[TCS_FILE_NAMELEN-1]= '\0'; // just in case...
00909             }
00910         }
00911         iL= strlen(szTCSIniFile); // perhaps extended by .% processing
00912         if (iL > 0) {
00913             szTemp= strstr (szTCSIniFile, PROGDIRTOKEN); // Default ProgDir?
00914             if (szTemp != 0) {
00915                 strncpy (tmpstr, szTCSIniFile, TCS_FILE_NAMELEN);
00916                 strncpy (szTCSIniFile, wxStandardPaths::Get().GetDataDir(), TCS_FILE_NAMELEN);
00917                 PathSeparator[0]= wxFileName::GetPathSeparator();
00918                 PathSeparator[1]= char (0);
00919                 strncpy (&szTCSIniFile[iL], PathSeparator, TCS_FILE_NAMELEN-iL);
00920                 iL= strlen(szTCSIniFile);
00921                 strncpy (&szTCSIniFile[iL], &tmpstr[strlen(PROGDIRTOKEN)], TCS_FILE_NAMELEN-iL);
00922                 szTCSIniFile[TCS_FILE_NAMELEN-1]= '\0'; // just in case...
00923             }
00924         }
00925     }
00926 }
00927
00928
00929
00930 extern "C" {
00931     bool WINSELECT (wxWindowID* iD)
00932     {
00933         size_t numbytes;
00934
00935         if (*iD >= MAX_OPEN_CANVAS) {
00936             TCSGraphicError (WRN_INI2, " ");
00937             return true; // Error handling !?
00938         } else {
00939             if (ActiveCanvas != nullptr) { // already active -> save status
00940                 numbytes= sizeof (struct TKTRNX); // save TKTRNX
00941                 memmove (&ActiveCanvas->TekSav.khomey, &tktrnx.khomey, numbytes);
00942                 numbytes= sizeof (struct G2dAG2); // save AG2
00943                 memmove (&ActiveCanvas->AG2Sav.cline, &g2dag2_.cline, numbytes);
00944
00945                 ActiveCanvas->DefaultLinColSav = TCSDefaultLinCol;
00946                 ActiveCanvas->DefaultTxtColSav = TCSDefaultTxtCol;
00947                 ActiveCanvas->DefaultBckColSav = TCSDefaultBckCol;
00948                 memmove (ActiveCanvas->HardcopyFileSav, szTCSHardcopyFile, TCS_FILE_NAMELEN);
00949                 memmove (ActiveCanvas->sect0Sav, szTCSsect0, TCS_FILE_NAMELEN);
00950             }
00951             if (OpenCanvases[*iD] != nullptr) { // restore TKTRNX

```

```

00952         numbytes= sizeof (struct G2dAG2);
00953         memmove (&tktrnx_.khomey, &OpenCanvases[*iD]->TekSav.khomey, numbytes);
00954         numbytes= sizeof (struct G2dAG2);
00955         memmove (&g2dag2_.cline, &OpenCanvases[*iD]->AG2Sav.cline, numbytes);
00956
00957         TCSDefaultLinCol = OpenCanvases[*iD]->DefaultLinColSav;
00958         TCSDefaultTxtCol = OpenCanvases[*iD]->DefaultTxtColSav;
00959         TCSDefaultBckCol = OpenCanvases[*iD]->DefaultBckColSav;
00960         memmove (szTCSHardcopyFile,&OpenCanvases[*iD]->HardcopyFileSav, TCS_FILE_NAMELEN);
00961         memmove (szTCSsect0, &OpenCanvases[*iD]->sect0Sav, TCS_FILE_NAMELEN);
00962     }
00963     ActiveCanvasID= *iD;
00964     ActiveCanvas= OpenCanvases[*iD];
00965 }
00966 return (OpenCanvases[*iD] == nullptr);
00967 }
00968 }
00969
00970
00971 extern "C" {
00972 void initt1 (int iMode, wxFrame* parent, wxFrame* FrameToUse, wxStatusBar* StatusBarToUse)
00973 {
00974     wxSize UseScreen;
00975     xJournalEntry_typ * xJournalEntry;
00976
00977     PresetProgPar(); // restore initialization after finitt()
00978     XMLreadProgPar (szTCSIniFile);
00979     CustomizeProgPar (); // substitute %: with program directory
00980     initt0(); // initialize COMMON TKTRNX
00981
00982     if (ActiveCanvas != NULL) { // Reset journal
00983         SGLIB_DL_LIST_MAP_ON_ELEMENTS (xJournalEntry_typ, ActiveCanvas->xTCSJournal,
00984             xJournalEntry,previous,next, { free (xJournalEntry);}); // free all
00985         ActiveCanvas->xTCSJournal= NULL;
00986         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
00987         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUCREATE,"");
00988         xJournalEntry->action= XACTION_NOOP; // mark beginning of the list with NOOP
00989         xJournalEntry->i1= 0;
00990         xJournalEntry->i2= 0;
00991         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
00992             next)
00993         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
00994         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUENTRY,"");
00995         xJournalEntry->action= XACTION_INITT;
00996         xJournalEntry->i1= 0;
00997         xJournalEntry->i2= 0;
00998         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
00999             next)
01000         return; // Remaining reset will be done during redraw due to XACTION_INITT
01001     }
01002
01003     ActiveCanvas = new cTCScanvas (iMode, parent, FrameToUse, StatusBarToUse);
01004     OpenCanvases[ActiveCanvasID] = ActiveCanvas;
01005
01006     ActiveCanvas->TCSpen = wxPen(TCSColorTable[tktrnx_.iLinCol], TCS_LINEWIDTH,
01007         wxPENSTYLE_SOLID);
01008     ActiveCanvas->TCSbrush = wxBrush (TCSColorTable[tktrnx_.iBckCol], wxBRUSHSTYLE_SOLID);
01009     ActiveCanvas->TCSfont = wxFont(wxFONTSIZE_MEDIUM, wxFONTFAMILY_TELETYPE,
01010         wxFONTSTYLE_NORMAL, wxFONTWEIGHT_NORMAL, false);
01011
01012     UseScreen = ActiveCanvas->TCSpanel->GetClientSize ();
01013     tktrnx_.kversz = (int) (TEK_YMAX *TCS_REL_CHR_HEIGHT +0.5); // first guess
01014     tktrnx_.khorsz = (int) ((float)UseScreen.y/(float)UseScreen.x*(float)tktrnx_.kversz +0.5);
01015     ActiveCanvas->TCSfont.SetFractionalPointSize (TEK_YMAX *TCS_REL_CHR_HEIGHT);
01016
01017     tktrnx_.khomey= TEK_YMAX - tktrnx_.kversz;
01018     tktrnx_.kbeamx = tktrnx_.klmrgn; // call HOME
01019     tktrnx_.kbeamy = tktrnx_.khomey;
01020
01021     ActiveCanvas->TCSframe->Show();
01022
01023     // Logging Window
01024
01025     ActiveCanvas->logWindow = new wxLogWindow(ActiveCanvas->TCSframe, szTCSstatWindowName, false,
01026         false);
01027     wxLog::SetActiveTarget(ActiveCanvas->logWindow);
01028     wxLog::SetTimestamp(""); // don't write timestamps before messages
01029     wxLogStatus (""); // without a first message wxLog::show() will crash
01030
01031     // Create journal
01032
01033     ActiveCanvas->xTCSJournal = (xJournalEntry_typ*) NULL;
01034     wxLogDebug ( wxT("INITT1> xTCSJournal initialisiert: Ptr= %p"), ActiveCanvas->xTCSJournal);
01035
01036     xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01037     if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUCREATE,"");
01038 #ifdef TRACE_CALLS

```

```

01035         wxLogDebug ( wxT("INITT1> Nach 1. malloc: xJournalEntry: Ptr= %p"), xJournalEntry);
01036 #endif // TRACE_CALLS
01037
01038         xJournalEntry->action= XACTION_NOOP; // mark beginning of the list with NOOP
01039         xJournalEntry->i1= 0;
01040         xJournalEntry->i2= 0;
01041         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01042             next)
01043 #ifdef TRACE_CALLS
01044         wxLogDebug ( wxT("INITT1> LIST_ADD=Create Journal: xTCSJournal: Ptr= %p / xJournalEntry: Ptr=
01045             %p"), ActiveCanvas->xTCSJournal, xJournalEntry);
01046         wxLogDebug ( wxT("INITT1> previous: Ptr= %p / next: Ptr= %p"), xJournalEntry -> previous,
01047             xJournalEntry -> next);
01048         wxLogDebug ( wxT("INITT1> XACTION_??? = %i (i1= %i, i2= %i)"), xJournalEntry->action,
01049             xJournalEntry->i1, xJournalEntry->i2 );
01050 #endif // TRACE_CALLS
01051
01052         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01053         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOENTRY, "");
01054         xJournalEntry->action= XACTION_INITT;
01055         xJournalEntry->i1= 0;
01056         xJournalEntry->i2= 0;
01057         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01058             next)
01059 #ifdef TRACE_CALLS
01060         wxLogDebug ( wxT("INITT1> Nach 2. LIST_ADD=Create Journal: xTCSJournal: Ptr= %p /
01061             xJournalEntry: Ptr= %p"), ActiveCanvas->xTCSJournal, xJournalEntry);
01062         wxLogDebug ( wxT("INITT1> previous: Ptr= %p / next: Ptr= %p"), xJournalEntry -> previous,
01063             xJournalEntry -> next);
01064         wxLogDebug ( wxT("INITT1> XACTION_??? = %i (i1= %i, i2= %i)"), xJournalEntry->action,
01065             xJournalEntry->i1, xJournalEntry->i2 );
01066 #endif // TRACE_CALLS
01067
01068         return;
01069     }
01070 }
01071
01072 extern "C" {
01073     void FINITT (int* ix, int* iy)
01074     {
01075         cTCSCanvas* CanvasToKill;
01076         xJournalEntry_typ * xJournalEntry;
01077
01078         if (ActiveCanvas == NULL) return;
01079         CanvasToKill = ActiveCanvas; // Window could be changed due to user action
01080         do {
01081             if (ActiveCanvas == CanvasToKill) {
01082                 TCSGraphicError (ERR_EXIT, ""); // User can accept or change window here
01083             } else {
01084                 wxYield(); // Allow processing in case of a changed window
01085             }
01086         } while (ActiveCanvas != CanvasToKill); // Don't kill a wrong window
01087
01088         SGLIB_DL_LIST_MAP_ON_ELEMENTS (xJournalEntry_typ, ActiveCanvas->xTCSJournal,
01089             xJournalEntry, previous, next, { free (xJournalEntry); }); // free all
01090         ActiveCanvas->xTCSJournal= nullptr;
01091
01092         ActiveCanvas->TCSframe->Destroy();
01093         ActiveCanvas = nullptr;
01094         OpenCanvases[ActiveCanvasID] = nullptr;
01095
01096         return;
01097     }
01098 }
01099
01100 extern "C" {
01101     void IOWAIT (int* iWait)
01102     {
01103         ActiveCanvas->TCSpanel->Refresh(); // wxEVT_PAINT will be executed after wxYield()
01104         wxYield(); // process event loop -> be aware of recursive loops!
01105     }
01106 }
01107
01108 /*
01109 ----- TCS API: Drawing -----
01110 */
01111
01112 extern "C" {
01113     void swindl_ (int* ix1, int* iy1, int* ix2, int* iy2)

```

```

01114     {
01115         xJournalEntry_typ * xJournalEntry;
01116
01117         ActiveCanvas->ClippingNotActive = (*ix1==0) && (*iy1==0) &&
01118             (*ix2==TEK_XMAX) && (*iy2==TEK_YMAX);
01119         /* Same meaning of bool variable in DOS, SDL2 ... */
01120
01121         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01122         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01123         xJournalEntry->action= XACTION_CLIP;
01124         if (ActiveCanvas->ClippingNotActive) {
01125             xJournalEntry->i1= 0;
01126         } else {
01127             xJournalEntry->i1= 1;
01128         }
01129         xJournalEntry->i2= 0;
01130         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01131 next)
01132
01133         if (!ActiveCanvas->ClippingNotActive) {
01134             xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01135             if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01136             xJournalEntry->action= XACTION_CLIP1;
01137             xJournalEntry->i1= *ix1;
01138             xJournalEntry->i2= *iy1;
01139             SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01140 next)
01141
01142             xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01143             if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01144             xJournalEntry->action= XACTION_CLIP2;
01145             xJournalEntry->i1= *ix2;
01146             xJournalEntry->i2= *iy2;
01147             SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01148 next)
01149         }
01150     }
01151
01152 extern "C" {
01153     void ERASE (void)
01154     {
01155         xJournalEntry_typ * xJournalEntry;
01156
01157         SGLIB_DL_LIST_MAP_ON_ELEMENTS (xJournalEntry_typ, ActiveCanvas->xTCSJournal,
01158             xJournalEntry,previous,next, {free (xJournalEntry);}); // free all
01159         ActiveCanvas->xTCSJournal= NULL; // create new journal
01160
01161         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01162         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01163         xJournalEntry->action= XACTION_NOOP; // root element without predecessor;
01164         xJournalEntry->i1= 0;
01165         xJournalEntry->i2= 0;
01166         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01167 next)
01168
01169         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01170         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01171         xJournalEntry->action= XACTION_LINCOL;
01172         xJournalEntry->i1= tktrnx_.iLinCol;
01173         xJournalEntry->i2= 0;
01174         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01175 next)
01176
01177         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01178         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01179         xJournalEntry->action= XACTION_TXTCOL;
01180         xJournalEntry->i1= tktrnx_.iTxtCol;
01181         xJournalEntry->i2= 0;
01182         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01183 next)
01184
01185         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01186         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01187         xJournalEntry->action= XACTION_BCKCOL;
01188         xJournalEntry->i1= tktrnx_.iBckCol;
01189         xJournalEntry->i2= 0;
01190         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01191 next)
01192
01193         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01194         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01195         xJournalEntry->action= XACTION_ERASE;
01196         xJournalEntry->i1= 0;
01197         xJournalEntry->i2= 0;

```

```

01194     SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01195     next)
01196 }
01197
01198
01199
01200 extern "C" {
01201     void MOVABS (int* ix,int* iy)
01202     {
01203         xJournalEntry_typ * xJournalEntry;
01204
01205         tktrnx_.kbeamx= *ix;
01206         tktrnx_.kbeamy= *iy;
01207
01208         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01209         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01210         xJournalEntry->action= XACTION_MOVABS;
01211         xJournalEntry->i1= *ix;
01212         xJournalEntry->i2= *iy;
01213         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01214         next)
01215     }
01216 }
01217
01218
01219 extern "C" {
01220     void DRWABS (int* ix,int* iy)
01221     {
01222         xJournalEntry_typ * xJournalEntry;
01223
01224         tktrnx_.kbeamx= *ix;
01225         tktrnx_.kbeamy= *iy;
01226
01227         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01228         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01229         xJournalEntry->action= XACTION_DRWABS;
01230         xJournalEntry->i1= *ix;
01231         xJournalEntry->i2= *iy;
01232         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01233         next)
01234     }
01235 }
01236
01237
01238 extern "C" {
01239     void DSHABS (int* ix,int* iy, int* iMask)
01240     {
01241         xJournalEntry_typ * xJournalEntry;
01242
01243         tktrnx_.kbeamx= *ix;
01244         tktrnx_.kbeamy= *iy;
01245
01246         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01247         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01248         xJournalEntry->action= XACTION_DSHSTYLE;
01249         xJournalEntry->i1= *iMask;
01250         xJournalEntry->i2= 0;
01251         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01252         next)
01253
01254         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01255         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01256         xJournalEntry->action= XACTION_DSHABS;
01257         xJournalEntry->i1= *ix;
01258         xJournalEntry->i2= *iy;
01259         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01260         next)
01261     }
01262 }
01263
01264 extern "C" {
01265     void PNTABS (int* ix,int* iy)
01266     {
01267         xJournalEntry_typ * xJournalEntry;
01268
01269         tktrnx_.kbeamx= *ix;
01270         tktrnx_.kbeamy= *iy;
01271
01272         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01273         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01274         xJournalEntry->action= XACTION_PNTABS;
01275         xJournalEntry->i1= *ix;

```

```

01276         xJournalEntry->i2= *iy;
01277         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
next)
    }
01278 }
01279 }
01280
01281
01282
01283 extern "C" {
01284     void BCKCOL (int* iCol)
01285     {
01286         xJournalEntry_typ * xJournalEntry;
01287
01288         tktrnx_.iBckCol= *iCol;
01289         if (*iCol > MAX_COLOR_INDEX) tktrnx_.iBckCol= MAX_COLOR_INDEX;
01290
01291         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01292         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD, "");
01293         xJournalEntry->action= XACTION_BCKCOL;
01294         xJournalEntry->i1= tktrnx_.iBckCol;
01295         xJournalEntry->i2= 0;
01296         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
next)
    }
01297 }
01298 }
01299
01300
01301
01302 extern "C" {
01303     void LINCOL (int* iCol)
01304     {
01305         xJournalEntry_typ * xJournalEntry;
01306
01307         tktrnx_.iLinCol= *iCol;
01308         if (*iCol > MAX_COLOR_INDEX) tktrnx_.iLinCol= MAX_COLOR_INDEX;
01309
01310         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01311         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD, "");
01312         xJournalEntry->action= XACTION_LINCOL;
01313         xJournalEntry->i1= tktrnx_.iLinCol;
01314         xJournalEntry->i2= 0;
01315         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
next)
    }
01316 }
01317 }
01318
01319
01320
01321 extern "C" {
01322     void TXTCOL (int* iCol)
01323     {
01324         xJournalEntry_typ * xJournalEntry;
01325
01326         tktrnx_.iTxtCol= *iCol;
01327         if (*iCol > MAX_COLOR_INDEX) tktrnx_.iTxtCol= MAX_COLOR_INDEX;
01328
01329         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01330         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD, "");
01331         xJournalEntry->action= XACTION_TXTCOL;
01332         xJournalEntry->i1= tktrnx_.iTxtCol;
01333         xJournalEntry->i2= 0;
01334         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
next)
    }
01335 }
01336 }
01337
01338
01339 extern "C" {
01340     void DEFAULTCOLOUR (void)
01341     {
01342         lincol_ (&TCSDefaultLinCol);
01343         txtcol_ (&TCSDefaultTxtCol);
01344         bckcol_ (&TCSDefaultBckCol);
01345     }
01346 }
01347
01348
01349
01350 /*
01351 ----- TCS API: Graphic text output -----
01352 */
01353
01354
01355
01356 extern "C" {
01357     void outgtext_ (char strng[] )
01358     {

```



```

01359     int i, iL;
01360     struct xJournalEntry_typ    * xJournalEntry;
01361
01362     iL= strlen(strng);
01363     tktrnx_.kbeamx+= iL*tktrnx_.khorsz;
01364
01365     xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01366     if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01367     xJournalEntry->action=  XACTION_GTEXT;
01368     xJournalEntry->i1= iL;
01369     xJournalEntry->i2= strng[0];
01370     SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01371 next)
01372
01371     i= 1;
01372     while (i < iL) {
01373         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01374         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01375         xJournalEntry->action=  XACTION_ASCII;
01376         xJournalEntry->i1= strng [i++];
01377         if ( i<iL ) {
01378             xJournalEntry->i2= strng[i++];
01379         } else {
01380             xJournalEntry->i2= 0;
01381         }
01382         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01383 next)
01384     }
01385
01386     xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01387     if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01388     xJournalEntry->action=  XACTION_MOVBAS;
01389     xJournalEntry->i1= tktrnx_.kbeamx;
01390     xJournalEntry->i2= tktrnx_.kbeamy;
01391     SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01392 next)
01393 }
01394
01395
01396
01397 extern "C" {
01398     void ITALIC (void)
01399     {
01400         struct xJournalEntry_typ    * xJournalEntry;
01401
01402         tktrnx_.kitalc = 1;
01403
01404         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01405         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01406         xJournalEntry->action=  XACTION_FONTATTR;
01407         xJournalEntry->i1= tktrnx_.kitalc;
01408         xJournalEntry->i2= tktrnx_.ksizef;
01409         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01410 next)
01411     }
01412 }
01413
01414
01415 extern "C" {
01416     void ITALIR (void)
01417     {
01418         struct xJournalEntry_typ    * xJournalEntry;
01419
01420         tktrnx_.kitalc = 0;
01421
01422         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01423         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01424         xJournalEntry->action=  XACTION_FONTATTR;
01425         xJournalEntry->i1= tktrnx_.kitalc;
01426         xJournalEntry->i2= tktrnx_.ksizef;
01427         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01428 next)
01429     }
01430 }
01431
01432
01433 extern "C" {
01434     void DBLSIZ (void)
01435     {
01436         struct xJournalEntry_typ    * xJournalEntry;
01437
01438         if (tktrnx_.ksizef == 0) {
01439             tktrnx_.khorsz = tktrnx_.khorsz * 2;
01440             tktrnx_.kversz = tktrnx_.kversz * 2;

```

```

01441         tktrnx_.khomey= TEK_YMAX - tktrnx_.kversz;
01442     }
01443     tktrnx_.ksizef = 1;
01444
01445     xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01446     if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01447     xJournalEntry->action= XACTION_FONTATTR;
01448     xJournalEntry->i1= tktrnx_.kitalc;
01449     xJournalEntry->i2= tktrnx_.ksizef;
01450     SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01451         next)
01452     }
01453 }
01454
01455 extern "C" {
01456     void NRMSIZ (void)
01457     {
01458         struct xJournalEntry_typ * xJournalEntry;
01459
01460         if (tktrnx_.ksizef == 1) {
01461             tktrnx_.khorsz = tktrnx_.khorsz / 2;
01462             tktrnx_.kversz = tktrnx_.kversz / 2;
01463             tktrnx_.khomey= TEK_YMAX - tktrnx_.kversz;
01464         }
01465         tktrnx_.ksizef = 0;
01466
01467         xJournalEntry= (xJournalEntry_typ *) malloc (sizeof (xJournalEntry_typ));
01468         if (xJournalEntry == NULL) TCSGraphicError (WRN_JOUADD,"");
01469         xJournalEntry->action= XACTION_FONTATTR;
01470         xJournalEntry->i1= tktrnx_.kitalc;
01471         xJournalEntry->i2= tktrnx_.ksizef;
01472         SGLIB_DL_LIST_ADD (xJournalEntry_typ, ActiveCanvas->xTCSJournal, xJournalEntry, previous,
01473             next)
01474     }
01475 }
01476
01477
01478
01479
01480 /*
01481 ----- TCS API: Messages -----
01482 */
01483
01484
01485 extern "C" {
01486     void BELL (void)
01487     {
01488         wxBell();
01489     }
01490 }
01491
01492
01493
01494 extern "C" {
01495     void outtext_ (char strng[] )
01496     {
01497         if (ActiveCanvas != nullptr) {
01498             if (ActiveCanvas->TCSstatusBar != nullptr) {
01499                 ActiveCanvas->TCSstatusBar->SetStatusText(strng);
01500             }
01501         }
01502     }
01503 }
01504
01505
01506
01507 extern "C" {
01508     void TCSGraphicError (int iErr, const char* msg)
01509     {
01510         char cBuf[TCS_MESSAGELEN];
01511         int i; // Dummyparameter
01512
01513         snprintf( cBuf, TCS_MESSAGELEN, szTCSErrorMsg[iErr], msg );
01514         if (ActiveCanvas == nullptr) {
01515             wxLogStatus (cBuf); // TCS not initialized
01516         } else {
01517             if (ActiveCanvas->TCSstatusBar == nullptr) {
01518                 wxLogStatus (cBuf); // no own space for logging
01519             } else {
01520                 if (TCSErrorLev[iErr] > 0) {
01521                     wxBell ();
01522                     ActiveCanvas->TCSstatusBar->SetStatusText(cBuf);
01523                     if (TCSErrorLev[iErr] < 5) return;
01524                     if ((TCSErrorLev[iErr] == 5) || (TCSErrorLev[iErr] == 10)) {

```

```

01526         tinput_ (&i); // Press Any Key
01527         ActiveCanvas->TCSstatusBar->SetStatusText("");
01528     } else if ((TCSerrorLev[iErr]==8) || (TCSerrorLev[iErr]==12)) {
01529         wxMessageBox (cBuf, szTCSstatWindowName, wxOK|wxICON_ERROR,
ActiveCanvas->TCSpanel,wxDefaultCoord);
01530     }
01531     if (TCSerrorLev[iErr] < 10) return;
01532     if (iErr != ERR_EXIT) { // Error-Level of finitt() can be changed by XML-Initfile
01533         finitt_ (&i,&i); // Forced exit for all Levels >= 10 over finitt()
01534     }
01535     }
01536     }
01537 }
01538 }
01539 }
01540
01541
01542
01543 /*
01544 ----- TCS API: User Input -----
01545 */
01546
01547
01548
01549 extern "C" {
01550     void DCURSR (int *ic,int* ix,int* iy)
01551     {
01552         ActiveCanvas->TCSmouseButtonDown= 0; // don't use old mouseclicks
01553         ActiveCanvas->TCSpanelKeyPressed= 0; // or old keystrokes
01554         ActiveCanvas->TCSpanel->Refresh(); // wxEVT_PAINT will be executed after wxYield()
01555         ActiveCanvas->TCSpanel->SetFocus();
01556         do {
01557             wxYield(); // process event loop -> be aware of recursive loops!
01558             wxMilliSleep(100); // wait for MOUSE_BUTTON_DOWN event
01559         } while ((ActiveCanvas->TCSmouseButtonDown == 0) && (ActiveCanvas->TCSpanelKeyPressed == 0));
01560         *ic= ActiveCanvas->TCSmouseButtonDown;
01561         if (*ic == 0) {
01562             *ic= ActiveCanvas->TCSpanelKeyPressed;
01563         }
01564         *ix= ActiveCanvas->TCSmouseX;
01565         *iy= ActiveCanvas->TCSmouseY;
01566     }
01567 }
01568
01569
01570
01571 extern "C" {
01572     void TINPUT (int *ic)
01573     {
01574         ActiveCanvas->TCSpanelKeyPressed= 0; // don't use old keystrokes
01575         ActiveCanvas->TCSpanel->Refresh(); // wxEVT_PAINT will be executed after wxYield()
01576         ActiveCanvas->TCSpanel->SetFocus();
01577         do {
01578             wxYield(); // process event loop -> be aware of recursive loops!
01579             wxMilliSleep(100); // wait for KEY_DOWN event
01580         } while (ActiveCanvas->TCSpanelKeyPressed == 0);
01581         *ic= ActiveCanvas->TCSpanelKeyPressed;
01582     }
01583 }
01584
01585
01586
01587 /*
01588 ----- TCS API: Hardcopy -----
01589 */
01590
01591
01592
01593 extern "C" {
01594     void HDCOPY (void)
01595     {
01596         wxString FilNam, TmpString;
01597         wxFile HDCfile;
01598         struct xJournalEntry_typ *xJournalEntry;
01599
01600         do {
01601             FilNam.Printf(szTCSHardcopyFile,iHardcopyCount++);
01602         } while ((iHardcopyCount < MAX_HDCCOUNT) && (wxFileExists(FilNam)) );
01603         if (iHardcopyCount >= MAX_HDCCOUNT) {
01604             TCSGraphicError (WRN_HDCFILOPN, "???"); // no unused filename
01605         }
01606         if (!HDCfile.Open (FilNam, wxFile::write, wxS_DEFAULT) ) {
01607             TCSGraphicError (WRN_HDCFILOPN, FilNam.c_str()); // error during open
01608         };
01609
01610         TCSGraphicError (MSG_HDCACT, FilNam.c_str());
01611         SGLIB_DL_LIST_GET_LAST(xJournalEntry_typ, ActiveCanvas->xTCSJournal, previous, next,

```

```

    xJournalEntry)
01612     while (xJournalEntry != NULL) {
01613         TmpString.Printf("%02i#%04i-%03i\n", xJournalEntry->action, xJournalEntry->i1,
xJournalEntry->i2);
01614         if (!HDCfile.Write (TmpString) ) {
01615             TCSGraphicError (WRN_HDCFILWRT, FilNam.c_str());
01616         }
01617         xJournalEntry= xJournalEntry -> previous;
01618     }
01619     HDCfile.Close();
01620 }
01621 }
01622
01623
01624
01625 extern "C" {
01626     void SVSTAT (char dst[])
01627     {
01628         size_t numbytes;
01629         numbytes= sizeof (struct TKTRNX);
01630         memmove (dst, &tktrnx_.khomey, numbytes);
01631     }
01632 }
01633
01634
01635
01636 extern "C" {
01637     void RESTAT (char src[])
01638     {
01639         size_t numbytes;
01640         numbytes= sizeof (struct TKTRNX);
01641         memmove (&tktrnx_.khomey, src, numbytes);
01642         movabs_ (&tktrnx_.kbeamx, &tktrnx_.kbeamy);
01643     }
01644 }
01645
01646
01647
01648 /*
01649 ----- subroutine LIB_MOVC3 -----
01650 Subroutine is not used here, for downward compatibility only
01651 */
01652
01653 extern "C" {
01654     void lib_movc3_ (int *len,char sou[],char dst[])
01655     {
01656         memmove (dst, sou, (size_t) *len);
01657     }
01658 }

```

8.32 TCSdrWXcpp.hpp File Reference

WX Port: Headerfile.

Macros

- #define [TEK_XMAX](#) 1023.0
- #define [TEK_YMAX](#) 780.0
- #define [TCS_LINEWIDTH](#) 1
- #define [MAX_OPEN_CANVAS](#) 20
- #define [STAT_MAXROWS](#) 1
- #define [TCS_REL_CHR_HEIGHT](#) 0.018f
- #define [TCS_REL_CHR_SPACING](#) 0.7f
- #define [TCS_WINDOW_NAMELEN](#) 50
- #define [TCS_FILE_NAMELEN](#) 132
- #define [TCS_MESSAGELEN](#) 132
- #define [MAX_HDCCOUNT](#) 1000
- #define [TCS_INIFILE_NAME](#) ""
- #define [INIFILEXT](#) ".XML"
- #define [INIFILEXTTOKEN](#) "%."
- #define [PROGDIRTOKEN](#) "%:"
- #define [XACTION_INITT](#) 1

- #define [XACTION_ERASE](#) 2
- #define [XACTION_MOVABS](#) 3
- #define [XACTION_DRWABS](#) 4
- #define [XACTION_DSHSTYLE](#) 5
- #define [XACTION_DSHABS](#) 6
- #define [XACTION_PNTABS](#) 7
- #define [XACTION_GTEXT](#) 8
- #define [XACTION_ASCII](#) 9
- #define [XACTION_BCKCOL](#) 10
- #define [XACTION_LINCOL](#) 11
- #define [XACTION_TXTCOL](#) 12
- #define [XACTION_FONTATTR](#) 13
- #define [XACTION_NOOP](#) 14
- #define [XACTION_CLIP](#) 15
- #define [XACTION_CLIP1](#) 16
- #define [XACTION_CLIP2](#) 17
- #define [WRN_NOMSG](#) 1
- #define [ERR_UNKNGRAPHCARD](#) 2
- #define [ERR_NOFNTFIL](#) 3
- #define [ERR_NOFNT](#) 4
- #define [MSG_NOMOUSE](#) 5
- #define [WRN_HDCFILOPN](#) 6
- #define [WRN_HDCFILWRT](#) 7
- #define [WRN_HDCINTERN](#) 8
- #define [MSG_USR](#) 9
- #define [MSG_HDCACT](#) 10
- #define [WRN_USRPRESSANY](#) 11
- #define [ERR_EXIT](#) 12
- #define [WRN_COPYNOMEM](#) 13
- #define [WRN_COPYLOCK](#) 14
- #define [WRN_JOUCREATE](#) 15
- #define [WRN_JOUMENTRY](#) 16
- #define [WRN_JOUADD](#) 17
- #define [WRN_JOUCLR](#) 18
- #define [WRN_JOUUNKWN](#) 19
- #define [ERR_XMLPARSER](#) 20
- #define [ERR_XMLOPEN](#) 21
- #define [ERR_UNKNAUDIO](#) 22
- #define [MSG_USR2](#) 23
- #define [WRN_INI2](#) 24
- #define [MSG_MAXERRNO](#) 25
- #define [TCS_INISECT0](#) "Graph2D"
- #define [TCS_INISECT1](#) "Names"
- #define [TCS_INIVAR_WINNAM](#) "G2dGraphic"
- #define [TCS_WINDOW_NAME](#) "Graphics"
- #define [TCS_INIVAR_STATNAM](#) "G2dStatus"
- #define [TCS_STATWINDOW_NAME](#) "System Messages"
- #define [TCS_INIVAR_HDCNAM](#) "G2dHardcopy"
- #define [TCS_HDCFILE_NAME](#) "HDC%03i.HDC"
- #define [TCS_INISECT2](#) "Layout"
- #define [TCS_INIVAR_WINPOSX](#) "G2dGraphicPosX"
- #define [TCS_INIDEF_WINPOSX](#) 1
- #define [TCS_INIVAR_WINPOSY](#) "G2dGraphicPosY"
- #define [TCS_INIDEF_WINPOSY](#) 3
- #define [TCS_INIVAR_WINSIZX](#) "G2dGraphicSizeX"

- #define TCS_INIDEF_WINSIZX 98
- #define TCS_INIVAR_WINSIZY "G2dGraphicSizeY"
- #define TCS_INIDEF_WINSIZY 85
- #define TCS_INIVAR_STATPOSX "G2dStatusPosX"
- #define TCS_INIDEF_STATPOSX 1
- #define TCS_INIVAR_STATPOSY "G2dStatusPosY"
- #define TCS_INIDEF_STATPOSY 91
- #define TCS_INIVAR_STATSIZX "G2dStatusSizeX"
- #define TCS_INIDEF_STATSIZX 98
- #define TCS_INIVAR_STATSIZY "G2dStatusSizeY"
- #define TCS_INIDEF_STATSIZY 3
- #define TCS_INIVAR_LINCOL "G2dLinCol"
- #define TCS_INIDEF_LINCOL 1
- #define TCS_INIVAR_TXTCOL "G2dTxtCol"
- #define TCS_INIDEF_TXTCOL 1
- #define TCS_INIVAR_BCKCOL "G2dBckCol"
- #define TCS_INIDEF_BCKCOL 0
- #define TCS_INISECT3 "Messages"
- #define TCS_INIVAR_UNKNGRAPHCARD "G2dGraphCard"
- #define TCS_INIDEF_UNKNGRAPHCARD "GRAPH2D Video System: Error %s."
- #define TCS_INIVAR_UNKNGRAPHCARDL "G2dGraphCardL"
- #define TCS_INIDEF_UNKNGRAPHCARDL 10
- #define TCS_INIVAR_NOFNTFIL "G2dFntfilOpen"
- #define TCS_INIDEF_NOFNTFIL "GRAPH2D SDLTTF: Error opening Fontfile %s."
- #define TCS_INIVAR_NOFNTFILL "G2dFntfilOpenL"
- #define TCS_INIDEF_NOFNTFILL 10
- #define TCS_INIVAR_NOFNT "G2dFntfilOpen"
- #define TCS_INIDEF_NOFNT "GRAPH2D SDLTTF: Error -> %s."
- #define TCS_INIVAR_NOFNTL "G2dFntfilOpenL"
- #define TCS_INIDEF_NOFNTL 10
- #define TCS_INIVAR_HDCOPN "G2dHdcOpen"
- #define TCS_INIDEF_HDCOPN "GRAPH2D HARDCOPY: Error during OPEN."
- #define TCS_INIVAR_HDCOPNL "G2dHdcOpenL"
- #define TCS_INIDEF_HDCOPNL 5
- #define TCS_INIVAR_HDCWRT "G2dHdcWrite"
- #define TCS_INIDEF_HDCWRT "GRAPH2D HARDCOPY: Error during WRITE."
- #define TCS_INIVAR_HDCWRTL "G2dHdcWritel"
- #define TCS_INIDEF_HDCWRTL 5
- #define TCS_INIVAR_USR "G2dUser"
- #define TCS_INIDEF_USR "%s"
- #define TCS_INIVAR_USRL "G2dUserL"
- #define TCS_INIDEF_USRL 5
- #define TCS_INIVAR_HDCACT "G2dHdcActive"
- #define TCS_INIDEF_HDCACT "Hardcopy in progress: File %s created."
- #define TCS_INIVAR_HDCACTL "G2dHdcActiveL"
- #define TCS_INIDEF_HDCACTL 1
- #define TCS_INIVAR_USRWRN "G2dPressAny"
- #define TCS_INIDEF_USRWRN "Press any key to continue."
- #define TCS_INIVAR_USRWRNL "G2dPressAnyL"
- #define TCS_INIDEF_USRWRNL 5
- #define TCS_INIVAR_EXIT "G2dExit"
- #define TCS_INIDEF_EXIT "Press any key to exit program."
- #define TCS_INIVAR_EXITL "G2dExitL"
- #define TCS_INIDEF_EXITL 10
- #define TCS_INIVAR_COPMEM "G2dNoMemory"

- #define `TCS_INIDEF_COPMEM` "GRAPH2D Clipboard Manager: Out of Memory."
- #define `TCS_INIVAR_COPMEML` "G2dNoMemoryL"
- #define `TCS_INIDEF_COPMEML` 1
- #define `TCS_INIVAR_COPLCK` "G2dClipLock"
- #define `TCS_INIDEF_COPLCK` "GRAPH2D Clipboard Manager: ClipBoard locked."
- #define `TCS_INIVAR_COPLCKL` "G2dClipLockL"
- #define `TCS_INIDEF_COPLCKL` 1
- #define `TCS_INIVAR_JOUCREATE` "G2dJouCreate"
- #define `TCS_INIDEF_JOUCREATE` "GRAPH2D Error Creating Journal. Error-No: %s."
- #define `TCS_INIVAR_JOUCREATEL` "G2dJouCreateL"
- #define `TCS_INIDEF_JOUCREATEL` 5
- #define `TCS_INIVAR_JOUENTRY` "G2dJouEntry"
- #define `TCS_INIDEF_JOUENTRY` "GRAPH2D Error Creating Journal Entry."
- #define `TCS_INIVAR_JOUENTRYL` "G2dJouEntryL"
- #define `TCS_INIDEF_JOUENTRYL` 5
- #define `TCS_INIVAR_JOUADD` "G2dJouAdd"
- #define `TCS_INIDEF_JOUADD` "GRAPH2D Error Appending Journal Entry."
- #define `TCS_INIVAR_JOUADDL` "G2dJouAddL"
- #define `TCS_INIDEF_JOUADDL` 5
- #define `TCS_INIVAR_JOUCLR` "G2dJouClr"
- #define `TCS_INIDEF_JOUCLR` "GRAPH2D Error Clearing Journal Entry."
- #define `TCS_INIVAR_JOUCLRL` "G2dJouClrL"
- #define `TCS_INIDEF_JOUCLRL` 5
- #define `TCS_INIVAR_JOUUNKWN` "G2dJouEntryUnknwn"
- #define `TCS_INIDEF_JOUUNKWN` "GRAPH2D Unknown Journal Entry."
- #define `TCS_INIVAR_JOUUNKWNL` "G2dJouEntryUnknwnL"
- #define `TCS_INIDEF_JOUUNKWNL` 5
- #define `TCS_INIVAR_XMLPARSER` "G2dXMLerror"
- #define `TCS_INIDEF_XMLPARSER` "GRAPH2D Error parsing XML-File: %s"
- #define `TCS_INIVAR_XMLPARSERL` "G2dXMLerrorL"
- #define `TCS_INIDEF_XMLPARSERL` 8
- #define `TCS_INIVAR_XMLOPEN` "G2dXMLopen"
- #define `TCS_INIDEF_XMLOPEN` "GRAPH2D Error opening %s"
- #define `TCS_INIVAR_XMLOPENL` "G2dXMLerrorL"
- #define `TCS_INIDEF_XMLOPENL` 1
- #define `TCS_INIVAR_UNKNAUDIO` "G2dAudio"
- #define `TCS_INIDEF_UNKNAUDIO` "GRAPH2D Audio System: Error %s."
- #define `TCS_INIVAR_UNKNAUDIOL` "G2dAudioL"
- #define `TCS_INIDEF_UNKNAUDIOL` 5
- #define `TCS_INIVAR_USR2` "G2dUser2"
- #define `TCS_INIDEF_USR2` "%s"
- #define `TCS_INIVAR_USR2L` "G2dUser2L"
- #define `TCS_INIDEF_USR2L` 5
- #define `TCS_INIVAR_INI2` "G2dInitt"
- #define `TCS_INIDEF_INI2` "Error creating windows in subroutine INITT"
- #define `TCS_INIVAR_INI2L` "G2dInittL"
- #define `TCS_INIDEF_INI2L` 1

8.32.1 Detailed Description

WX Port: [Headerfile](#).

Version

0.5

Author

Dr.-Ing. Klaus Friedewald

Headerfile for [TCSdrWXcpp.cpp](#)

Note

- Configuration of the library
- Defining default values

Definition in file [TCSdrWXcpp.hpp](#).

8.32.2 Macro Definition Documentation

8.32.2.1 ERR_EXIT

```
#define ERR_EXIT 12
```

Definition at line [87](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.2 ERR_NOFNT

```
#define ERR_NOFNT 4
```

Definition at line [79](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.3 ERR_NOFNTFIL

```
#define ERR_NOFNTFIL 3
```

Definition at line [78](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.4 ERR_UNKNAUDIO

```
#define ERR_UNKNAUDIO 22
```

Definition at line [97](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.5 ERR_UNKNGRAPHCARD

```
#define ERR_UNKNGRAPHCARD 2
```

Definition at line [77](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.6 ERR_XMLOPEN

```
#define ERR_XMLOPEN 21
```

Definition at line [96](#) of file [TCSdrWXcpp.hpp](#).

8.32.2.7 ERR_XMLPARSER

```
#define ERR_XMLPARSER 20
```

Definition at line 95 of file [TCSdrWXcpp.hpp](#).

8.32.2.8 INIFILEXT

```
#define INIFILEXT ".XML"
```

Definition at line 46 of file [TCSdrWXcpp.hpp](#).

8.32.2.9 INIFILEXTTOKEN

```
#define INIFILEXTTOKEN ".%"
```

Definition at line 47 of file [TCSdrWXcpp.hpp](#).

8.32.2.10 MAX_HDCCOUNT

```
#define MAX_HDCCOUNT 1000
```

Definition at line 43 of file [TCSdrWXcpp.hpp](#).

8.32.2.11 MAX_OPEN_CANVAS

```
#define MAX_OPEN_CANVAS 20
```

Definition at line 32 of file [TCSdrWXcpp.hpp](#).

8.32.2.12 MSG_HDCACT

```
#define MSG_HDCACT 10
```

Definition at line 85 of file [TCSdrWXcpp.hpp](#).

8.32.2.13 MSG_MAXERRNO

```
#define MSG_MAXERRNO 25
```

Definition at line 100 of file [TCSdrWXcpp.hpp](#).

8.32.2.14 MSG_NOMOUSE

```
#define MSG_NOMOUSE 5
```

Definition at line 80 of file [TCSdrWXcpp.hpp](#).

8.32.2.15 MSG_USR

```
#define MSG_USR 9
```

Definition at line 84 of file [TCSdrWXcpp.hpp](#).

8.32.2.16 MSG_USR2

```
#define MSG_USR2 23
```

Definition at line 98 of file [TCSdrWXcpp.hpp](#).

8.32.2.17 PROGDIRTOKEN

```
#define PROGDIRTOKEN "%:"
```

Definition at line 48 of file [TCSdrWXcpp.hpp](#).

8.32.2.18 STAT_MAXROWS

```
#define STAT_MAXROWS 1
```

Definition at line 34 of file [TCSdrWXcpp.hpp](#).

8.32.2.19 TCS_FILE_NAMELEN

```
#define TCS_FILE_NAMELEN 132
```

Definition at line 40 of file [TCSdrWXcpp.hpp](#).

8.32.2.20 TCS_HDCFILE_NAME

```
#define TCS_HDCFILE_NAME "HDC%03i.HDC"
```

Definition at line 114 of file [TCSdrWXcpp.hpp](#).

8.32.2.21 TCS_INIDEF_BCKCOL

```
#define TCS_INIDEF_BCKCOL 0
```

Definition at line 148 of file [TCSdrWXcpp.hpp](#).

8.32.2.22 TCS_INIDEF_COPLCK

```
#define TCS_INIDEF_COPLCK "GRAPH2D Clipboard Manager:  ClipBoard locked."
```

Definition at line 192 of file [TCSdrWXcpp.hpp](#).

8.32.2.23 TCS_INIDEF_COPLCKL

```
#define TCS_INIDEF_COPLCKL 1
```

Definition at line 194 of file [TCSdrWXcpp.hpp](#).

8.32.2.24 TCS_INIDEF_COPMEM

```
#define TCS_INIDEF_COPMEM "GRAPH2D Clipboard Manager:  Out of Memory."
```

Definition at line 188 of file [TCSdrWXcpp.hpp](#).

8.32.2.25 TCS_INIDEF_COPMEML

```
#define TCS_INIDEF_COPMEML 1
```

Definition at line 190 of file [TCSdrWXcpp.hpp](#).

8.32.2.26 TCS_INIDEF_EXIT

```
#define TCS_INIDEF_EXIT "Press any key to exit program."
```

Definition at line 184 of file [TCSdrWXcpp.hpp](#).

8.32.2.27 TCS_INIDEF_EXITL

```
#define TCS_INIDEF_EXITL 10
```

Definition at line 186 of file [TCSdrWXcpp.hpp](#).

8.32.2.28 TCS_INIDEF_HDCACT

```
#define TCS_INIDEF_HDCACT "Hardcopy in progress: File %s created."
```

Definition at line 176 of file [TCSdrWXcpp.hpp](#).

8.32.2.29 TCS_INIDEF_HDCACTL

```
#define TCS_INIDEF_HDCACTL 1
```

Definition at line 178 of file [TCSdrWXcpp.hpp](#).

8.32.2.30 TCS_INIDEF_HDCOPN

```
#define TCS_INIDEF_HDCOPN "GRAPH2D HARDCOPY: Error during OPEN."
```

Definition at line 164 of file [TCSdrWXcpp.hpp](#).

8.32.2.31 TCS_INIDEF_HDCOPNL

```
#define TCS_INIDEF_HDCOPNL 5
```

Definition at line 166 of file [TCSdrWXcpp.hpp](#).

8.32.2.32 TCS_INIDEF_HDCWRT

```
#define TCS_INIDEF_HDCWRT "GRAPH2D HARDCOPY: Error during WRITE."
```

Definition at line 168 of file [TCSdrWXcpp.hpp](#).

8.32.2.33 TCS_INIDEF_HDCWRTL

```
#define TCS_INIDEF_HDCWRTL 5
```

Definition at line 170 of file [TCSdrWXcpp.hpp](#).

8.32.2.34 TCS_INIDEF_INI2

```
#define TCS_INIDEF_INI2 "Error creating windows in subroutine INITT"
```

Definition at line 232 of file [TCSdrWXcpp.hpp](#).

8.32.2.35 TCS_INIDEF_INI2L

```
#define TCS_INIDEF_INI2L 1
```

Definition at line 234 of file [TCSdrWXcpp.hpp](#).

8.32.2.36 TCS_INIDEF_JOUADD

```
#define TCS_INIDEF_JOUADD "GRAPH2D Error Appending Journal Entry."
```

Definition at line 204 of file [TCSdrWXcpp.hpp](#).

8.32.2.37 TCS_INIDEF_JOUADDL

```
#define TCS_INIDEF_JOUADDL 5
```

Definition at line 206 of file [TCSdrWXcpp.hpp](#).

8.32.2.38 TCS_INIDEF_JOUCLR

```
#define TCS_INIDEF_JOUCLR "GRAPH2D Error Clearing Journal Entry."
```

Definition at line 208 of file [TCSdrWXcpp.hpp](#).

8.32.2.39 TCS_INIDEF_JOUCLRL

```
#define TCS_INIDEF_JOUCLRL 5
```

Definition at line 210 of file [TCSdrWXcpp.hpp](#).

8.32.2.40 TCS_INIDEF_JOUCREATE

```
#define TCS_INIDEF_JOUCREATE "GRAPH2D Error Creating Journal. Error-No: %s."
```

Definition at line 196 of file [TCSdrWXcpp.hpp](#).

8.32.2.41 TCS_INIDEF_JOUCREATEL

```
#define TCS_INIDEF_JOUCREATEL 5
```

Definition at line 198 of file [TCSdrWXcpp.hpp](#).

8.32.2.42 TCS_INIDEF_JOUMENTRY

```
#define TCS_INIDEF_JOUMENTRY "GRAPH2D Error Creating Journal Entry."
```

Definition at line 200 of file [TCSdrWXcpp.hpp](#).

8.32.2.43 TCS_INIDEF_JOUMENTRYL

```
#define TCS_INIDEF_JOUMENTRYL 5
```

Definition at line 202 of file [TCSdrWXcpp.hpp](#).

8.32.2.44 TCS_INIDEF_JOUUNKWN

```
#define TCS_INIDEF_JOUUNKWN "GRAPH2D Unknown Journal Entry."
```

Definition at line 212 of file [TCSdrWXcpp.hpp](#).

8.32.2.45 TCS_INIDEF_JOUUNKWNL

```
#define TCS_INIDEF_JOUUNKWNL 5
```

Definition at line 214 of file [TCSdrWXcpp.hpp](#).

8.32.2.46 TCS_INIDEF_LINCOL

```
#define TCS_INIDEF_LINCOL 1
```

Definition at line 144 of file [TCSdrWXcpp.hpp](#).

8.32.2.47 TCS_INIDEF_NOFNT

```
#define TCS_INIDEF_NOFNT "GRAPH2D SDLTTF: Error -> %s."
```

Definition at line 160 of file [TCSdrWXcpp.hpp](#).

8.32.2.48 TCS_INIDEF_NOFNTFIL

```
#define TCS_INIDEF_NOFNTFIL "GRAPH2D SDLTTF: Error opening Fontfile %s."
```

Definition at line 156 of file [TCSdrWXcpp.hpp](#).

8.32.2.49 TCS_INIDEF_NOFNTFILL

```
#define TCS_INIDEF_NOFNTFILL 10
```

Definition at line 158 of file [TCSdrWXcpp.hpp](#).

8.32.2.50 TCS_INIDEF_NOFNTL

```
#define TCS_INIDEF_NOFNTL 10
```

Definition at line 162 of file [TCSdrWXcpp.hpp](#).

8.32.2.51 TCS_INIDEF_STATPOX

```
#define TCS_INIDEF_STATPOX 1
```

Definition at line 135 of file [TCSdrWXcpp.hpp](#).

8.32.2.52 TCS_INIDEF_STATPOSY

```
#define TCS_INIDEF_STATPOSY 91
```

Definition at line 137 of file [TCSdrWXcpp.hpp](#).

8.32.2.53 TCS_INIDEF_STATSIZX

```
#define TCS_INIDEF_STATSIZX 98
```

Definition at line 139 of file [TCSdrWXcpp.hpp](#).

8.32.2.54 TCS_INIDEF_STATSIZY

```
#define TCS_INIDEF_STATSIZY 3
```

Definition at line 141 of file [TCSdrWXcpp.hpp](#).

8.32.2.55 TCS_INIDEF_TXTCOL

```
#define TCS_INIDEF_TXTCOL 1
```

Definition at line 146 of file [TCSdrWXcpp.hpp](#).

8.32.2.56 TCS_INIDEF_UNKNAUDIO

```
#define TCS_INIDEF_UNKNAUDIO "GRAPH2D Audio System: Error %s."
```

Definition at line 224 of file [TCSdrWXcpp.hpp](#).

8.32.2.57 TCS_INIDEF_UNKNAUDIOL

```
#define TCS_INIDEF_UNKNAUDIOL 5
```

Definition at line 226 of file [TCSdrWXcpp.hpp](#).

8.32.2.58 TCS_INIDEF_UNKNGRAPHCARD

```
#define TCS_INIDEF_UNKNGRAPHCARD "GRAPH2D Video System: Error %s."
```

Definition at line 152 of file [TCSdrWXcpp.hpp](#).

8.32.2.59 TCS_INIDEF_UNKNGRAPHCARDL

```
#define TCS_INIDEF_UNKNGRAPHCARDL 10
```

Definition at line 154 of file [TCSdrWXcpp.hpp](#).

8.32.2.60 TCS_INIDEF_USR

```
#define TCS_INIDEF_USR "%s"
```

Definition at line 172 of file [TCSdrWXcpp.hpp](#).

8.32.2.61 TCS_INIDEF_USR2

```
#define TCS_INIDEF_USR2 "%s"
```

Definition at line 228 of file [TCSdrWXcpp.hpp](#).

8.32.2.62 TCS_INIDEF_USR2L

```
#define TCS_INIDEF_USR2L 5
```

Definition at line 230 of file [TCSdrWXcpp.hpp](#).

8.32.2.63 TCS_INIDEF_USRL

```
#define TCS_INIDEF_USRL 5
```

Definition at line 174 of file [TCSdrWXcpp.hpp](#).

8.32.2.64 TCS_INIDEF_USRWRN

```
#define TCS_INIDEF_USRWRN "Press any key to continue."
```

Definition at line 180 of file [TCSdrWXcpp.hpp](#).

8.32.2.65 TCS_INIDEF_USRWRNL

```
#define TCS_INIDEF_USRWRNL 5
```

Definition at line 182 of file [TCSdrWXcpp.hpp](#).

8.32.2.66 TCS_INIDEF_WINPOSX

```
#define TCS_INIDEF_WINPOSX 1
```

Definition at line 127 of file [TCSdrWXcpp.hpp](#).

8.32.2.67 TCS_INIDEF_WINPOSY

```
#define TCS_INIDEF_WINPOSY 3
```

Definition at line 129 of file [TCSdrWXcpp.hpp](#).

8.32.2.68 TCS_INIDEF_WINSIZX

```
#define TCS_INIDEF_WINSIZX 98
```

Definition at line 131 of file [TCSdrWXcpp.hpp](#).

8.32.2.69 TCS_INIDEF_WINSIZY

```
#define TCS_INIDEF_WINSIZY 85
```

Definition at line 133 of file [TCSdrWXcpp.hpp](#).

8.32.2.70 TCS_INIDEF_XMLOPEN

```
#define TCS_INIDEF_XMLOPEN "GRAPH2D Error opening %s"
```

Definition at line 220 of file [TCSdrWXcpp.hpp](#).

8.32.2.71 TCS_INIDEF_XMLOPENL

```
#define TCS_INIDEF_XMLOPENL 1
```

Definition at line 222 of file [TCSdrWXcpp.hpp](#).

8.32.2.72 TCS_INIDEF_XMLPARSER

```
#define TCS_INIDEF_XMLPARSER "GRAPH2D Error parsing XML-File: %s"
```

Definition at line 216 of file [TCSdrWXcpp.hpp](#).

8.32.2.73 TCS_INIDEF_XMLPARSERL

```
#define TCS_INIDEF_XMLPARSERL 8
```

Definition at line 218 of file [TCSdrWXcpp.hpp](#).

8.32.2.74 TCS_INIFILE_NAME

```
#define TCS_INIFILE_NAME ""
```

Definition at line 45 of file [TCSdrWXcpp.hpp](#).

8.32.2.75 TCS_INISECT0

```
#define TCS_INISECT0 "Graph2D"
```

Definition at line 106 of file [TCSdrWXcpp.hpp](#).

8.32.2.76 TCS_INISECT1

```
#define TCS_INISECT1 "Names"
```

Definition at line 108 of file [TCSdrWXcpp.hpp](#).

8.32.2.77 TCS_INISECT2

```
#define TCS_INISECT2 "Layout"
```

Definition at line 118 of file [TCSdrWXcpp.hpp](#).

8.32.2.78 TCS_INISECT3

```
#define TCS_INISECT3 "Messages"
```

Definition at line 150 of file [TCSdrWXcpp.hpp](#).

8.32.2.79 TCS_INIVAR_BCKCOL

```
#define TCS_INIVAR_BCKCOL "G2dBckCol"
```

Definition at line 147 of file [TCSdrWXcpp.hpp](#).

8.32.2.80 TCS_INIVAR_COPLCK

```
#define TCS_INIVAR_COPLCK "G2dClipLock"
```

Definition at line 191 of file [TCSdrWXcpp.hpp](#).

8.32.2.81 TCS_INIVAR_COPLCKL

```
#define TCS_INIVAR_COPLCKL "G2dClipLockL"
```

Definition at line 193 of file [TCSdrWXcpp.hpp](#).

8.32.2.82 TCS_INIVAR_COPMEM

```
#define TCS_INIVAR_COPMEM "G2dNoMemory"
```

Definition at line 187 of file [TCSdrWXcpp.hpp](#).

8.32.2.83 TCS_INIVAR_COPMEML

```
#define TCS_INIVAR_COPMEML "G2dNoMemoryL"
```

Definition at line 189 of file [TCSdrWXcpp.hpp](#).

8.32.2.84 TCS_INIVAR_EXIT

```
#define TCS_INIVAR_EXIT "G2dExit"
```

Definition at line 183 of file [TCSdrWXcpp.hpp](#).

8.32.2.85 TCS_INIVAR_EXITL

```
#define TCS_INIVAR_EXITL "G2dExitL"
```

Definition at line 185 of file [TCSdrWXcpp.hpp](#).

8.32.2.86 TCS_INIVAR_HDCACT

```
#define TCS_INIVAR_HDCACT "G2dHdcActive"
```

Definition at line 175 of file [TCSdrWXcpp.hpp](#).

8.32.2.87 TCS_INIVAR_HDCACTL

#define TCS_INIVAR_HDCACTL "G2dHdcActiveL"
Definition at line 177 of file [TCSdrWXcpp.hpp](#).

8.32.2.88 TCS_INIVAR_HDCNAM

#define TCS_INIVAR_HDCNAM "G2dHardcopy"
Definition at line 113 of file [TCSdrWXcpp.hpp](#).

8.32.2.89 TCS_INIVAR_HDCOPN

#define TCS_INIVAR_HDCOPN "G2dHdcOpen"
Definition at line 163 of file [TCSdrWXcpp.hpp](#).

8.32.2.90 TCS_INIVAR_HDCOPNL

#define TCS_INIVAR_HDCOPNL "G2dHdcOpenL"
Definition at line 165 of file [TCSdrWXcpp.hpp](#).

8.32.2.91 TCS_INIVAR_HDCWRT

#define TCS_INIVAR_HDCWRT "G2dHdcWrite"
Definition at line 167 of file [TCSdrWXcpp.hpp](#).

8.32.2.92 TCS_INIVAR_HDCWRTL

#define TCS_INIVAR_HDCWRTL "G2dHdcWriteL"
Definition at line 169 of file [TCSdrWXcpp.hpp](#).

8.32.2.93 TCS_INIVAR_INI2

#define TCS_INIVAR_INI2 "G2dInitt"
Definition at line 231 of file [TCSdrWXcpp.hpp](#).

8.32.2.94 TCS_INIVAR_INI2L

#define TCS_INIVAR_INI2L "G2dInittL"
Definition at line 233 of file [TCSdrWXcpp.hpp](#).

8.32.2.95 TCS_INIVAR_JOUADD

#define TCS_INIVAR_JOUADD "G2dJouAdd"
Definition at line 203 of file [TCSdrWXcpp.hpp](#).

8.32.2.96 TCS_INIVAR_JOUADDL

#define TCS_INIVAR_JOUADDL "G2dJouAddL"
Definition at line 205 of file [TCSdrWXcpp.hpp](#).

8.32.2.97 TCS_INIVAR_JOUCLR

#define TCS_INIVAR_JOUCLR "G2dJouClr"
Definition at line 207 of file [TCSdrWXcpp.hpp](#).

8.32.2.98 TCS_INIVAR_JOUCLRL

#define TCS_INIVAR_JOUCLRL "G2dJouClrL"
Definition at line 209 of file [TCSdrWXcpp.hpp](#).

8.32.2.99 TCS_INIVAR_JOUCREATE

#define TCS_INIVAR_JOUCREATE "G2dJouCreate"
Definition at line 195 of file [TCSdrWXcpp.hpp](#).

8.32.2.100 TCS_INIVAR_JOUCREATEL

#define TCS_INIVAR_JOUCREATEL "G2dJouCreateL"
Definition at line 197 of file [TCSdrWXcpp.hpp](#).

8.32.2.101 TCS_INIVAR_JOUEENTRY

#define TCS_INIVAR_JOUEENTRY "G2dJouEntry"
Definition at line 199 of file [TCSdrWXcpp.hpp](#).

8.32.2.102 TCS_INIVAR_JOUEENTRYL

#define TCS_INIVAR_JOUEENTRYL "G2dJouEntryL"
Definition at line 201 of file [TCSdrWXcpp.hpp](#).

8.32.2.103 TCS_INIVAR_JOUUNKWN

#define TCS_INIVAR_JOUUNKWN "G2dJouEntryUnknwn"
Definition at line 211 of file [TCSdrWXcpp.hpp](#).

8.32.2.104 TCS_INIVAR_JOUUNKWNL

#define TCS_INIVAR_JOUUNKWNL "G2dJouEntryUnknwnL"
Definition at line 213 of file [TCSdrWXcpp.hpp](#).

8.32.2.105 TCS_INIVAR_LINCOL

#define TCS_INIVAR_LINCOL "G2dLinCol"
Definition at line 143 of file [TCSdrWXcpp.hpp](#).

8.32.2.106 TCS_INIVAR_NOFNT

#define TCS_INIVAR_NOFNT "G2dFntfilOpen"
Definition at line 159 of file [TCSdrWXcpp.hpp](#).

8.32.2.107 TCS_INIVAR_NOFNTFIL

#define TCS_INIVAR_NOFNTFIL "G2dFntfilOpen"
Definition at line 155 of file [TCSdrWXcpp.hpp](#).

8.32.2.108 TCS_INIVAR_NOFNTFILL

#define TCS_INIVAR_NOFNTFILL "G2dFntfilOpenL"
Definition at line 157 of file [TCSdrWXcpp.hpp](#).

8.32.2.109 TCS_INIVAR_NOFNTL

#define TCS_INIVAR_NOFNTL "G2dFntfilOpenL"
Definition at line 161 of file [TCSdrWXcpp.hpp](#).

8.32.2.110 TCS_INIVAR_STATNAM

#define TCS_INIVAR_STATNAM "G2dStatus"
Definition at line 111 of file [TCSdrWXcpp.hpp](#).

8.32.2.111 TCS_INIVAR_STATPOSX

#define TCS_INIVAR_STATPOSX "G2dStatusPosX"
Definition at line 134 of file [TCSdrWXcpp.hpp](#).

8.32.2.112 TCS_INIVAR_STATPOSY

#define TCS_INIVAR_STATPOSY "G2dStatusPosY"
Definition at line 136 of file [TCSdrWXcpp.hpp](#).

8.32.2.113 TCS_INIVAR_STATSIZX

#define TCS_INIVAR_STATSIZX "G2dStatusSizeX"
Definition at line 138 of file [TCSdrWXcpp.hpp](#).

8.32.2.114 TCS_INIVAR_STATSIZY

#define TCS_INIVAR_STATSIZY "G2dStatusSizeY"
Definition at line 140 of file [TCSdrWXcpp.hpp](#).

8.32.2.115 TCS_INIVAR_TXTCOL

#define TCS_INIVAR_TXTCOL "G2dTxtCol"
Definition at line 145 of file [TCSdrWXcpp.hpp](#).

8.32.2.116 TCS_INIVAR_UNKNAUDIO

#define TCS_INIVAR_UNKNAUDIO "G2dAudio"
Definition at line 223 of file [TCSdrWXcpp.hpp](#).

8.32.2.117 TCS_INIVAR_UNKNAUDIOL

#define TCS_INIVAR_UNKNAUDIOL "G2dAudioL"
Definition at line 225 of file [TCSdrWXcpp.hpp](#).

8.32.2.118 TCS_INIVAR_UNKNGRAPHCARD

#define TCS_INIVAR_UNKNGRAPHCARD "G2dGraphCard"
Definition at line 151 of file [TCSdrWXcpp.hpp](#).

8.32.2.119 TCS_INIVAR_UNKNGRAPHCARDL

#define TCS_INIVAR_UNKNGRAPHCARDL "G2dGraphCardL"
Definition at line 153 of file [TCSdrWXcpp.hpp](#).

8.32.2.120 TCS_INIVAR_USR

#define TCS_INIVAR_USR "G2dUser"
Definition at line 171 of file [TCSdrWXcpp.hpp](#).

8.32.2.121 TCS_INIVAR_USR2

#define TCS_INIVAR_USR2 "G2dUser2"
Definition at line 227 of file [TCSdrWXcpp.hpp](#).

8.32.2.122 TCS_INIVAR_USR2L

#define TCS_INIVAR_USR2L "G2dUser2L"
Definition at line 229 of file [TCSdrWXcpp.hpp](#).

8.32.2.123 TCS_INIVAR_USRL

#define TCS_INIVAR_USRL "G2dUserL"
Definition at line 173 of file [TCSdrWXcpp.hpp](#).

8.32.2.124 TCS_INIVAR_USRWRN

#define TCS_INIVAR_USRWRN "G2dPressAny"
Definition at line 179 of file [TCSdrWXcpp.hpp](#).

8.32.2.125 TCS_INIVAR_USRWRNL

#define TCS_INIVAR_USRWRNL "G2dPressAnyL"
Definition at line 181 of file [TCSdrWXcpp.hpp](#).

8.32.2.126 TCS_INIVAR_WINNAM

#define TCS_INIVAR_WINNAM "G2dGraphic"
Definition at line 109 of file [TCSdrWXcpp.hpp](#).

8.32.2.127 TCS_INIVAR_WINPOSX

```
#define TCS_INIVAR_WINPOSX "G2dGraphicPosX"
```

Definition at line 126 of file [TCSdrWXcpp.hpp](#).

8.32.2.128 TCS_INIVAR_WINPOSY

```
#define TCS_INIVAR_WINPOSY "G2dGraphicPosY"
```

Definition at line 128 of file [TCSdrWXcpp.hpp](#).

8.32.2.129 TCS_INIVAR_WINSIZX

```
#define TCS_INIVAR_WINSIZX "G2dGraphicSizeX"
```

Definition at line 130 of file [TCSdrWXcpp.hpp](#).

8.32.2.130 TCS_INIVAR_WINSIZY

```
#define TCS_INIVAR_WINSIZY "G2dGraphicSizeY"
```

Definition at line 132 of file [TCSdrWXcpp.hpp](#).

8.32.2.131 TCS_INIVAR_XMLOPEN

```
#define TCS_INIVAR_XMLOPEN "G2dXMLopen"
```

Definition at line 219 of file [TCSdrWXcpp.hpp](#).

8.32.2.132 TCS_INIVAR_XMLOPENL

```
#define TCS_INIVAR_XMLOPENL "G2dXMLerrorL"
```

Definition at line 221 of file [TCSdrWXcpp.hpp](#).

8.32.2.133 TCS_INIVAR_XMLPARSER

```
#define TCS_INIVAR_XMLPARSER "G2dXMLerror"
```

Definition at line 215 of file [TCSdrWXcpp.hpp](#).

8.32.2.134 TCS_INIVAR_XMLPARSERL

```
#define TCS_INIVAR_XMLPARSERL "G2dXMLerrorL"
```

Definition at line 217 of file [TCSdrWXcpp.hpp](#).

8.32.2.135 TCS_LINEWIDTH

```
#define TCS_LINEWIDTH 1
```

Definition at line 31 of file [TCSdrWXcpp.hpp](#).

8.32.2.136 TCS_MESSAGELEN

```
#define TCS_MESSAGELEN 132
```

Definition at line 42 of file [TCSdrWXcpp.hpp](#).

8.32.2.137 TCS_REL_CHR_HEIGHT

```
#define TCS_REL_CHR_HEIGHT 0.018f
```

Definition at line 36 of file [TCSdrWXcpp.hpp](#).

8.32.2.138 TCS_REL_CHR_SPACING

```
#define TCS_REL_CHR_SPACING 0.7f
```

Definition at line 37 of file [TCSdrWXcpp.hpp](#).

8.32.2.139 TCS_STATWINDOW_NAME

```
#define TCS_STATWINDOW_NAME "System Messages"
```

Definition at line 112 of file [TCSdrWXcpp.hpp](#).

8.32.2.140 TCS_WINDOW_NAME

```
#define TCS_WINDOW_NAME "Graphics"
```

Definition at line 110 of file [TCSdrWXcpp.hpp](#).

8.32.2.141 TCS_WINDOW_NAMELEN

```
#define TCS_WINDOW_NAMELEN 50
```

Definition at line 39 of file [TCSdrWXcpp.hpp](#).

8.32.2.142 TEK_XMAX

```
#define TEK_XMAX 1023.0
```

Definition at line 24 of file [TCSdrWXcpp.hpp](#).

8.32.2.143 TEK_YMAX

```
#define TEK_YMAX 780.0
```

Definition at line 25 of file [TCSdrWXcpp.hpp](#).

8.32.2.144 WRN_COPYLOCK

```
#define WRN_COPYLOCK 14
```

Definition at line 89 of file [TCSdrWXcpp.hpp](#).

8.32.2.145 WRN_COPYNOMEM

```
#define WRN_COPYNOMEM 13
```

Definition at line 88 of file [TCSdrWXcpp.hpp](#).

8.32.2.146 WRN_HDCFILOPN

```
#define WRN_HDCFILOPN 6
```

Definition at line 81 of file [TCSdrWXcpp.hpp](#).

8.32.2.147 WRN_HDCFILWRT

```
#define WRN_HDCFILWRT 7
```

Definition at line 82 of file [TCSdrWXcpp.hpp](#).

8.32.2.148 WRN_HDCINTERN

```
#define WRN_HDCINTERN 8
```

Definition at line 83 of file [TCSdrWXcpp.hpp](#).

8.32.2.149 WRN_INI2

```
#define WRN_INI2 24
```

Definition at line 99 of file [TCSdrWXcpp.hpp](#).

8.32.2.150 WRN_JOUADD

```
#define WRN_JOUADD 17
```

Definition at line 92 of file [TCSdrWXcpp.hpp](#).

8.32.2.151 WRN_JOUCLR

```
#define WRN_JOUCLR 18
```

Definition at line 93 of file [TCSdrWXcpp.hpp](#).

8.32.2.152 WRN_JOUCREATE

```
#define WRN_JOUCREATE 15
```

Definition at line 90 of file [TCSdrWXcpp.hpp](#).

8.32.2.153 WRN_JOENTRY

```
#define WRN_JOENTRY 16
```

Definition at line 91 of file [TCSdrWXcpp.hpp](#).

8.32.2.154 WRN_JOUUNKWN

```
#define WRN_JOUUNKWN 19
```

Definition at line 94 of file [TCSdrWXcpp.hpp](#).

8.32.2.155 WRN_NOMSG

```
#define WRN_NOMSG 1
```

Definition at line 76 of file [TCSdrWXcpp.hpp](#).

8.32.2.156 WRN_USRPRESSANY

```
#define WRN_USRPRESSANY 11
```

Definition at line 86 of file [TCSdrWXcpp.hpp](#).

8.32.2.157 XACTION_ASCII

```
#define XACTION_ASCII 9
```

Definition at line 62 of file [TCSdrWXcpp.hpp](#).

8.32.2.158 XACTION_BCKCOL

```
#define XACTION_BCKCOL 10
```

Definition at line 63 of file [TCSdrWXcpp.hpp](#).

8.32.2.159 XACTION_CLIP

```
#define XACTION_CLIP 15
```

Definition at line 68 of file [TCSdrWXcpp.hpp](#).

8.32.2.160 XACTION_CLIP1

```
#define XACTION_CLIP1 16
```

Definition at line 69 of file [TCSdrWXcpp.hpp](#).

8.32.2.161 XACTION_CLIP2

```
#define XACTION_CLIP2 17
```

Definition at line 70 of file [TCSdrWXcpp.hpp](#).

8.32.2.162 XACTION_DRWABS

```
#define XACTION_DRWABS 4
```

Definition at line 57 of file [TCSdrWXcpp.hpp](#).

8.32.2.163 XACTION_DSHABS

```
#define XACTION_DSHABS 6
```

Definition at line 59 of file [TCSdrWXcpp.hpp](#).

8.32.2.164 XACTION_DSHSTYLE

```
#define XACTION_DSHSTYLE 5
```

Definition at line 58 of file [TCSdrWXcpp.hpp](#).

8.32.2.165 XACTION_ERASE

```
#define XACTION_ERASE 2
```

Definition at line 55 of file [TCSdrWXcpp.hpp](#).

8.32.2.166 XACTION_FONTATTR

```
#define XACTION_FONTATTR 13
```

Definition at line 66 of file [TCSdrWXcpp.hpp](#).

8.32.2.167 XACTION_GTEXT

```
#define XACTION_GTEXT 8
```

Definition at line 61 of file [TCSdrWXcpp.hpp](#).

8.32.2.168 XACTION_INITT

```
#define XACTION_INITT 1
```

Definition at line 54 of file [TCSdrWXcpp.hpp](#).

8.32.2.169 XACTION_LINCOL

```
#define XACTION_LINCOL 11
```

Definition at line 64 of file [TCSdrWXcpp.hpp](#).

8.32.2.170 XACTION_MOVABS

```
#define XACTION_MOVABS 3
```

Definition at line 56 of file [TCSdrWXcpp.hpp](#).

8.32.2.171 XACTION_NOOP

```
#define XACTION_NOOP 14
```

Definition at line 67 of file [TCSdrWXcpp.hpp](#).

8.32.2.172 XACTION_PNTABS

```
#define XACTION_PNTABS 7
```

Definition at line 60 of file [TCSdrWXcpp.hpp](#).

8.32.2.173 XACTION_TXTCOL

```
#define XACTION_TXTCOL 12
```

Definition at line 65 of file [TCSdrWXcpp.hpp](#).

8.33 TCSdrWXcpp.hpp

```
00001 /** *****
00002 \file    TCSdrWXcpp.hpp
00003 \brief   WX Port: Headerfile
00004 \version 0.5
00005 \author  Dr.-Ing. Klaus Friedewald
00006 \~german
00007         Headerfile zu TCSdrWXcpp.cpp
00008 \note
00009         - Konfiguration der Bibliothek
00010         - Definition der Defaultwerte
00011 \~english
00012         Headerfile for TCSdrWXcpp.cpp
00013 \note
00014         - Configuration of the library
00015         - Defining default values
00016 \~
00017
00018 ***** **/
00019
00020
00021
00022 /* ----- Drawing area in Tektronix coordinates ----- */
00023
00024 #define TEK_XMAX 1023.0 // Double precision because of
```

```

00025 #define TEK_YMAX 780.0    // use in wx::SetLogicalScale ()
00026
00027
00028
00029 /* ----- Program parameters ----- */
00030
00031 #define TCS_LINEWIDTH 1
00032 #define MAX_OPEN_CANVAS 20    // Maximum number of used canvases
00033
00034 #define STAT_MAXROWS 1        // Analogue to the other ports, not used here
00035
00036 #define TCS_REL_CHR_HEIGHT 0.018f // Define size / vertical spacing of graphic text
00037 #define TCS_REL_CHR_SPACING 0.7f
00038
00039 #define TCS_WINDOW_NAMELEN 50
00040 #define TCS_FILE_NAMELEN 132
00041
00042 #define TCS_MESSAGELEN 132
00043 #define MAX_HDCCOUNT 1000    // parameter is bound to TCS_HDCFILE_NAME
00044
00045 #define TCS_INIFILE_NAME ""
00046 #define INIFILEXT ".XML"
00047 #define INIFILEXTOKEN ".%"    // Token for parsing filenames
00048 #define PROGDIRTOKEN "%:"
00049
00050
00051
00052 /* Actioncodes of the journalfiles */
00053
00054 #define XACTION_INITT        1
00055 #define XACTION_ERASE        2
00056 #define XACTION_MOVABS        3
00057 #define XACTION_DRWABS        4
00058 #define XACTION_DSHSTYLE    5
00059 #define XACTION_DSHABS        6
00060 #define XACTION_PNTABS        7
00061 #define XACTION_GTEXT        8
00062 #define XACTION_ASCII        9
00063 #define XACTION_BCKCOL        10
00064 #define XACTION_LINCOL        11
00065 #define XACTION_TXTCOL        12
00066 #define XACTION_FONTATTR    13
00067 #define XACTION_NOOP        14
00068 #define XACTION_CLIP        15
00069 #define XACTION_CLIP1        16
00070 #define XACTION_CLIP2        17
00071
00072
00073
00074 /* Assign errornumbers */
00075
00076 #define WRN_NOMSG 1
00077 #define ERR_UNKNGRAPHCARD 2
00078 #define ERR_NOFNFTFIL 3
00079 #define ERR_NOFNT 4
00080 #define MSG_NOMOUSE 5
00081 #define WRN_HDCFILOPN 6
00082 #define WRN_HDCFILWRT 7
00083 #define WRN_HDCINTERN 8
00084 #define MSG_USR 9
00085 #define MSG_HDCACT 10
00086 #define WRN_USRPRESSANY 11
00087 #define ERR_EXIT 12
00088 #define WRN_COPYNOMEM 13
00089 #define WRN_COPYLOCK 14
00090 #define WRN_JOUCREATE 15
00091 #define WRN_JOUMENTRY 16
00092 #define WRN_JOUADD 17
00093 #define WRN_JOUCLR 18
00094 #define WRN_JOUUNKWN 19
00095 #define ERR_XMLPARSER 20
00096 #define ERR_XMLOPEN 21
00097 #define ERR_UNKNAUDIO 22
00098 #define MSG_USR2 23
00099 #define WRN_INI2 24
00100 #define MSG_MAXERRNO 25
00101
00102
00103
00104 /* Default initialization, can be changed by the ini-XML file */
00105
00106 #define TCS_INISECT0 "Graph2D" // Root-Section for XML, change with WINLBL()
00107
00108 #define TCS_INISECT1 "Names"
00109 #define TCS_INIVAR_WINNAM "G2dGraphic"
00110 #define TCS_WINDOW_NAME "Graphics"
00111 #define TCS_INIVAR_STATNAM "G2dStatus"

```

```

00112     #define TCS_STATWINDOW_NAME "System Messages"
00113     #define TCS_INIVAR_HDCNAM "G2dHardcopy"
00114     #define TCS_HDCFILE_NAME "HDC%03i.HDC"
00115
00116
00117
00118 #define TCS_INISECT2 "Layout"
00119 /* #define TCS_INIVAR_COPMEN "G2dSysMenuCopy"
00120     #define TCS_INIDEF_COPMEN "Copy"
00121     #define TCS_INIVAR_FONT "G2dGraphicFont"
00122     #define TCS_INIDEF_FONT PROGDIRTOKEN "graph2d"
00123     #define TCS_INIVAR_SYSFONT "G2dSystemFont"
00124     #define TCS_INIDEF_SYSFONT PROGDIRTOKEN "graph2d"
00125 */
00126 #define TCS_INIVAR_WINPOSX "G2dGraphicPosX"
00127     #define TCS_INIDEF_WINPOSX 1
00128 #define TCS_INIVAR_WINPOSY "G2dGraphicPosY"
00129     #define TCS_INIDEF_WINPOSY 3
00130 #define TCS_INIVAR_WINSIZX "G2dGraphicSizeX"
00131     #define TCS_INIDEF_WINSIZX 98
00132 #define TCS_INIVAR_WINSIZY "G2dGraphicSizeY"
00133     #define TCS_INIDEF_WINSIZY 85
00134 #define TCS_INIVAR_STATPOSX "G2dStatusPosX"
00135     #define TCS_INIDEF_STATPOSX 1
00136 #define TCS_INIVAR_STATPOSY "G2dStatusPosY"
00137     #define TCS_INIDEF_STATPOSY 91
00138 #define TCS_INIVAR_STATSIZX "G2dStatusSizeX"
00139     #define TCS_INIDEF_STATSIZX 98
00140 #define TCS_INIVAR_STATSIZY "G2dStatusSizeY"
00141     #define TCS_INIDEF_STATSIZY 3
00142
00143 #define TCS_INIVAR_LINCOL "G2dLinCol"
00144     #define TCS_INIDEF_LINCOL 1
00145 #define TCS_INIVAR_TXTCOL "G2dTxtCol"
00146     #define TCS_INIDEF_TXTCOL 1
00147 #define TCS_INIVAR_BCKCOL "G2dBckCol"
00148     #define TCS_INIDEF_BCKCOL 0
00149
00150 #define TCS_INISECT3 "Messages"
00151 #define TCS_INIVAR_UNKNGRAPHCARD "G2dGraphCard"
00152     #define TCS_INIDEF_UNKNGRAPHCARD "GRAPH2D Video System: Error %s."
00153     #define TCS_INIVAR_UNKNGRAPHCARDL "G2dGraphCardL"
00154     #define TCS_INIDEF_UNKNGRAPHCARDL 10
00155 #define TCS_INIVAR_NOFNTFIL "G2dFntfilOpen"
00156     #define TCS_INIDEF_NOFNTFIL "GRAPH2D SDLTTF: Error opening Fontfile %s."
00157     #define TCS_INIVAR_NOFNTFILL "G2dFntfilOpenL"
00158     #define TCS_INIDEF_NOFNTFILL 10
00159 #define TCS_INIVAR_NOFNT "G2dFntfilOpen"
00160     #define TCS_INIDEF_NOFNT "GRAPH2D SDLTTF: Error -> %s."
00161     #define TCS_INIVAR_NOFNTL "G2dFntfilOpenL"
00162     #define TCS_INIDEF_NOFNTL 10
00163 #define TCS_INIVAR_HDCOPN "G2dHdcOpen"
00164     #define TCS_INIDEF_HDCOPN "GRAPH2D HARDCOPY: Error during OPEN."
00165     #define TCS_INIVAR_HDCOPNL "G2dHdcOpenL"
00166     #define TCS_INIDEF_HDCOPNL 5
00167 #define TCS_INIVAR_HDCWRT "G2dHdcWrite"
00168     #define TCS_INIDEF_HDCWRT "GRAPH2D HARDCOPY: Error during WRITE."
00169     #define TCS_INIVAR_HDCWRTL "G2dHdcWriteL"
00170     #define TCS_INIDEF_HDCWRTL 5
00171 #define TCS_INIVAR_USR "G2dUser"
00172     #define TCS_INIDEF_USR "%s"
00173     #define TCS_INIVAR_USRL "G2dUserL"
00174     #define TCS_INIDEF_USRL 5
00175 #define TCS_INIVAR_HDCACT "G2dHdcActive"
00176     #define TCS_INIDEF_HDCACT "Hardcopy in progress: File %s created."
00177     #define TCS_INIVAR_HDCACTL "G2dHdcActiveL"
00178     #define TCS_INIDEF_HDCACTL 1
00179 #define TCS_INIVAR_USRWRN "G2dPressAny"
00180     #define TCS_INIDEF_USRWRN "Press any key to continue."
00181     #define TCS_INIVAR_USRWRNL "G2dPressAnyL"
00182     #define TCS_INIDEF_USRWRNL 5
00183 #define TCS_INIVAR_EXIT "G2dExit"
00184     #define TCS_INIDEF_EXIT "Press any key to exit program."
00185     #define TCS_INIVAR_EXITL "G2dExitL"
00186     #define TCS_INIDEF_EXITL 10
00187 #define TCS_INIVAR_COPMEM "G2dNoMemory"
00188     #define TCS_INIDEF_COPMEM "GRAPH2D Clipboard Manager: Out of Memory."
00189     #define TCS_INIVAR_COPMEML "G2dNoMemoryL"
00190     #define TCS_INIDEF_COPMEML 1
00191 #define TCS_INIVAR_COPLCK "G2dClipLock"
00192     #define TCS_INIDEF_COPLCK "GRAPH2D Clipboard Manager: ClipBoard locked."
00193     #define TCS_INIVAR_COPLCKL "G2dClipLockL"
00194     #define TCS_INIDEF_COPLCKL 1
00195 #define TCS_INIVAR_JOUCREATE "G2dJouCreate"
00196     #define TCS_INIDEF_JOUCREATE "GRAPH2D Error Creating Journal. Error-No: %s."
00197     #define TCS_INIVAR_JOUCREATEL "G2dJouCreateL"
00198     #define TCS_INIDEF_JOUCREATEL 5

```

```

00199 #define TCS_INIVAR_JOUEENTRY "G2dJouEntry"
00200 #define TCS_INIDEF_JOUEENTRY "GRAPH2D Error Creating Journal Entry."
00201 #define TCS_INIVAR_JOUEENTRYL "G2dJouEntryL"
00202 #define TCS_INIDEF_JOUEENTRYL 5
00203 #define TCS_INIVAR_JOUADD "G2dJouAdd"
00204 #define TCS_INIDEF_JOUADD "GRAPH2D Error Appending Journal Entry."
00205 #define TCS_INIVAR_JOUADDL "G2dJouAddL"
00206 #define TCS_INIDEF_JOUADDL 5
00207 #define TCS_INIVAR_JOUCLR "G2dJouClr"
00208 #define TCS_INIDEF_JOUCLR "GRAPH2D Error Clearing Journal Entry."
00209 #define TCS_INIVAR_JOUCLRL "G2dJouClrL"
00210 #define TCS_INIDEF_JOUCLRL 5
00211 #define TCS_INIVAR_JOUUNKWN "G2dJouEntryUnknwn"
00212 #define TCS_INIDEF_JOUUNKWN "GRAPH2D Unknown Journal Entry."
00213 #define TCS_INIVAR_JOUUNKWNL "G2dJouEntryUnknwnL"
00214 #define TCS_INIDEF_JOUUNKWNL 5
00215 #define TCS_INIVAR_XMLPARSER "G2dXMLerror"
00216 #define TCS_INIDEF_XMLPARSER "GRAPH2D Error parsing XML-File: %s"
00217 #define TCS_INIVAR_XMLPARSERL "G2dXMLerrorL"
00218 #define TCS_INIDEF_XMLPARSERL 8
00219 #define TCS_INIVAR_XMLOPEN "G2dXMLopen"
00220 #define TCS_INIDEF_XMLOPEN "GRAPH2D Error opening %s"
00221 #define TCS_INIVAR_XMLOPENL "G2dXMLerrorL"
00222 #define TCS_INIDEF_XMLOPENL 1
00223 #define TCS_INIVAR_UNKNAUDIO "G2dAudio"
00224 #define TCS_INIDEF_UNKNAUDIO "GRAPH2D Audio System: Error %s."
00225 #define TCS_INIVAR_UNKNAUDIOL "G2dAudioL"
00226 #define TCS_INIDEF_UNKNAUDIOL 5
00227 #define TCS_INIVAR_USR2 "G2dUser2"
00228 #define TCS_INIDEF_USR2 "%s"
00229 #define TCS_INIVAR_USR2L "G2dUser2L"
00230 #define TCS_INIDEF_USR2L 5
00231 #define TCS_INIVAR_INI2 "G2dInitt"
00232 #define TCS_INIDEF_INI2 "Error creating windows in subroutine INITT"
00233 #define TCS_INIVAR_INI2L "G2dInittL"
00234 #define TCS_INIDEF_INI2L 1

```

8.34 TCSdrWXfor.f08 File Reference

wX Port: High-Level Driver

Functions/Subroutines

- subroutine [tcslev](#) (LEVEL)
- subroutine [winlbl](#) (PloWinNam, StatWinNam, IniFilNam)
- subroutine [initt](#) (iDummy)
- subroutine [movrel](#) (iX, iY)
- subroutine [pntrel](#) (iX, iY)
- subroutine [drwrel](#) (iX, iY)
- subroutine [dshrel](#) (iX, iY, iMask)
- subroutine [seeloc](#) (IX, IY)
- subroutine [toutpt](#) (iChr)
- subroutine [toutst](#) (nChr, iChrArr)
- subroutine [toutstc](#) (String)
- subroutine [csize](#) (ixlen, iylen)
- subroutine [statst](#) (String)
- subroutine [graphicerror](#) (iErr, Mssg)
- subroutine [anmode](#)

Entry dummy routines.

8.34.1 Detailed Description

wX Port: High-Level Driver

Version

(2022,305,8)

Author

(C) 2022 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

wX specific subroutines**Note**

```
Supplement to Tektronix:
  subroutine TOUTSTC (String): Ausgabe Fortran-String
  subroutine LINCOL (iCol): Setzen Linienfarbe (iCol=0..15)
  subroutine TXTCOL (iCol): Setzen Textfarbe
  subroutine BCKCOL (iCol): Hintergrundfarbe (nach ERASE sichtbar)
  subroutine DefaultColour: Wiederherstellung Defaultfarben
```

Definition in file [TCSdrWXfor.f08](#).

8.34.2 Function/Subroutine Documentation

8.34.2.1 anmode()

```
subroutine anmode
```

Entry dummy routines.

AlfMod

pClipt

alpha

Definition at line [247](#) of file [TCSdrWXfor.f08](#).

8.34.2.2 csize()

```
subroutine csize (
    ixlen,
    iylen )
```

Definition at line [197](#) of file [TCSdrWXfor.f08](#).

8.34.2.3 drwrel()

```
subroutine drwrel (
    iX,
    iY )
```

Definition at line [114](#) of file [TCSdrWXfor.f08](#).

8.34.2.4 dshrel()

```
subroutine dshrel (
    iX,
    iY,
    iMask )
```

Definition at line [124](#) of file [TCSdrWXfor.f08](#).

8.34.2.5 graphicerror()

```
subroutine graphicerror (  
    integer iErr,  
    character *(*) Mssg )
```

Definition at line 224 of file [TCSdrWXfor.f08](#).

8.34.2.6 initt()

```
subroutine initt (  
    integer iDummy )
```

Definition at line 70 of file [TCSdrWXfor.f08](#).

8.34.2.7 movrel()

```
subroutine movrel (  
    iX,  
    iY )
```

Definition at line 94 of file [TCSdrWXfor.f08](#).

8.34.2.8 pntrel()

```
subroutine pntrel (  
    iX,  
    iY )
```

Definition at line 104 of file [TCSdrWXfor.f08](#).

8.34.2.9 seeloc()

```
subroutine seeloc (  
    IX,  
    IY )
```

Definition at line 138 of file [TCSdrWXfor.f08](#).

8.34.2.10 statst()

```
subroutine statst (  
    character *(*) String )
```

Definition at line 206 of file [TCSdrWXfor.f08](#).

8.34.2.11 tcslev()

```
subroutine tcslev (  
    integer, dimension(3) LEVEL )
```

Definition at line 39 of file [TCSdrWXfor.f08](#).

8.34.2.12 toutpt()

```
subroutine toutpt (  
    integer iChr )
```

Definition at line 151 of file [TCSdrWXfor.f08](#).

8.34.2.13 toutst()

```
subroutine toutst (
    nChr,
    integer, dimension (1) iChrArr )
```

Definition at line 169 of file [TCSdrWXfor.f08](#).

8.34.2.14 toutstc()

```
subroutine toutstc (
    character *(*) String )
```

Definition at line 180 of file [TCSdrWXfor.f08](#).

8.34.2.15 winlbl()

```
subroutine winlbl (
    character*(*) PloWinNam,
    character*(*) StatWinNam,
    character*(*) IniFilNam )
```

Definition at line 53 of file [TCSdrWXfor.f08](#).

8.35 TCSdrWXfor.f08

```
00001 !> \file      TCSdrWXfor.f08
00002 !> \brief     wX Port: High-Level Driver
00003 !> \version    (2022,305,8)
00004 !> \author     (C) 2022 Dr.-Ing. Klaus Friedewald
00005 !> \copyright   GNU LESSER GENERAL PUBLIC LICENSE Version 3
00006 !>
00007 !> \~german
00008 !> wX-spezifische TCS-Routinen
00009 !> \note \verbatim
00010 !>   Erweiterungen gegenüber Tektronix:
00011 !>   subroutine TOUTSTC (String): Ausgabe Fortran-String
00012 !>   subroutine LINCOL (iCol): Setzen Linienfarbe (iCol=0..15)
00013 !>   subroutine TXTCOL (iCol): Setzen Textfarbe
00014 !>   subroutine BCKCOL (iCol): Hintergrundfarbe (nach ERASE sichtbar)
00015 !>   subroutine DefaultColour: Wiederherstellung Defaultfarben
00016 !> \endverbatim
00017 !>
00018 !>
00019 !> \~english
00020 !> wX specific subroutines
00021 !> \note \verbatim
00022 !>   Supplement to Tektronix:
00023 !>   subroutine TOUTSTC (String): Ausgabe Fortran-String
00024 !>   subroutine LINCOL (iCol): Setzen Linienfarbe (iCol=0..15)
00025 !>   subroutine TXTCOL (iCol): Setzen Textfarbe
00026 !>   subroutine BCKCOL (iCol): Hintergrundfarbe (nach ERASE sichtbar)
00027 !>   subroutine DefaultColour: Wiederherstellung Defaultfarben
00028 !> \endverbatim
00029 !> \~
00030 !>
00031
00032
00033 ! FTN 77 linkbare Unterprogramme / Wrapper
00034
00035 !
00036 !   Ausgabe der Softwareversion
00037 !
00038
00039   subroutine tcslev(LEVEL)
00040   integer LEVEL(3)
00041   level(1)=2022      ! Aenderungsjahr
00042   level(2)= 305      ! Aenderungstag
00043   level(3)= 8        ! System= wX
00044   return
00045   end
00046
00047
00048
00049 !
00050 !   Initialization
```

```

00051 !
00052
00053     subroutine winlbl (PloWinNam, StatWinNam, IniFilNam)
00054     use, intrinsic :: iso_c_binding
00055     implicit none
00056
00057     character*(*) PloWinNam, StatWinNam, IniFilNam
00058     interface
00059         subroutine winlbl0 (PloWinNam0, StatWinNam0, IniFilNam0) bind(C, name='winlbl0')
00060             use, intrinsic :: iso_c_binding, only: c_char
00061             character(kind= c_char), dimension(*) :: PloWinNam0, StatWinNam0, IniFilNam0
00062         end subroutine winlbl0
00063     end interface
00064
00065     call winlbl0 (plowinnam//c_null_char, statwinnam//c_null_char, inifilnam//c_null_char)
00066     end
00067
00068
00069
00070     subroutine initt (iDummy)
00071     use, intrinsic :: iso_c_binding
00072     implicit none
00073
00074     integer iDummy
00075     integer (c_intptr_t), parameter :: NULLPTR = 0
00076     interface
00077         subroutine initt1 (iMode, iParent, iFrame, iStatus) bind(C)
00078             use, intrinsic :: iso_c_binding
00079             integer (c_int), value :: iMode
00080             integer (c_intptr_t), value :: iParent, iFrame, iStatus
00081         end subroutine initt1
00082     end interface
00083
00084     call initt1 (0, nullptr, nullptr, nullptr) ! 0 => no Parent Window
00085     return
00086     end
00087
00088
00089
00090 !
00091 ! Relative drawing
00092 !
00093
00094     subroutine movrel (iX, iY)
00095     include 'Tktrnx.fd'
00096     ixx= kbeamx + ix
00097     iyy= kbeamy + iy
00098     call movabs (ixx, iyy)
00099     return
00100     end
00101
00102
00103
00104     subroutine pntrel (iX, iY)
00105     include 'Tktrnx.fd'
00106     ixx= kbeamx + ix
00107     iyy= kbeamy + iy
00108     call pntabs (ixx, iyy)
00109     return
00110     end
00111
00112
00113
00114     subroutine drwrel (iX, iY)
00115     include 'Tktrnx.fd'
00116     ixx= kbeamx + ix
00117     iyy= kbeamy + iy
00118     call drwabs (ixx, iyy)
00119     return
00120     end
00121
00122
00123
00124     subroutine dshrel (iX, iY, iMask)
00125     include 'Tktrnx.fd'
00126     ixx= kbeamx + ix
00127     iyy= kbeamy + iy
00128     call dshabs (ixx, iyy, imask)
00129     return
00130     end
00131
00132
00133
00134 !
00135 ! Ersatz SEELoc der CP/M-Version (wie MS Windows, DOS)
00136 !
00137

```



```

00138      subroutine seeloc (IX,IY)
00139      include 'Tktrnx.fd'
00140      ix= kbeamx
00141      iy= kbeamy
00142      return
00143      end
00144
00145
00146
00147 !
00148 ! Graphic text output
00149 !
00150
00151      subroutine toutpt (iChr)
00152      use, intrinsic :: iso_c_binding
00153      implicit none
00154      integer iChr
00155
00156      interface
00157          subroutine outgtext (strng) bind(C, name='outgtext_')
00158              use, intrinsic :: iso_c_binding, only: c_char
00159              character(kind= c_char), dimension(*) :: strng
00160          end subroutine outgtext
00161      end interface
00162
00163      call outgtext (char(iChr)//c_null_char)
00164      return
00165      end
00166
00167
00168
00169      subroutine toutst (nChr, iChrArr)
00170      integer iChrArr (1)
00171      if (nchr.eq.0) return
00172      do 10 i=1,nchr
00173          call toutpt (ichrarr(i))
00174 10 continue
00175      return
00176      end
00177
00178
00179
00180      subroutine toutstc (String)
00181      implicit none
00182
00183      character *(*) String
00184      interface
00185          subroutine outgtext (strng) bind(C, name='outgtext_')
00186              use, intrinsic :: iso_c_binding, only: c_char
00187              character(kind= c_char), dimension(*) :: strng
00188          end subroutine outgtext
00189      end interface
00190
00191      call outgtext (string//char(0))
00192      return
00193      end
00194
00195
00196
00197      subroutine csize (ixlen,iylen)
00198      include 'Tktrnx.fd'
00199      ixlen= khorsz
00200      iylen= kversz
00201      return
00202      end
00203
00204
00205
00206      subroutine statst (String)
00207      use, intrinsic :: iso_c_binding
00208      implicit none
00209
00210      character *(*) String
00211      interface
00212          subroutine outtext (cString) bind(C, name='outtext_')
00213              use, intrinsic :: iso_c_binding, only: c_char
00214              character(kind= c_char), dimension(*) :: cString
00215          end subroutine outtext
00216      end interface
00217
00218      call outtext (string//c_null_char)
00219      return
00220      end
00221
00222
00223
00224      subroutine graphicerror (iErr,Mssg) ! Bis jetzt genutzt: TCSGraphicError in Cpp

```

```

00225      use, intrinsic :: iso_c_binding
00226      implicit none
00227
00228      integer iErr
00229      character *(*) Mssg
00230      interface
00231      subroutine tcsgraphicerror (i, cString) bind(C, name='TCSGraphicError')
00232      use, intrinsic :: iso_c_binding
00233      integer(kind=c_int), value :: i
00234      character(kind= c_char), dimension(*) :: cString
00235      end subroutine tcsgraphicerror
00236      end interface
00237
00238      call tcsgraphicerror (ierr,mssg//c_null_char)
00239      return
00240      end
00241
00242
00243
00244      !
00245      !> Entry dummy routines
00246      !
00247      subroutine anmode
00248      !> AlfMod
00249      entry      alfmod
00250      !> pClipt
00251      entry      pclipt
00252      !> alpha
00253      entry      alpha
00254      return
00255      end

```

8.36 Tktrnx.fd File Reference

wX Port: TCS Common Block [TKTRNX](#)

8.36.1 Detailed Description

wX Port: TCS Common Block [TKTRNX](#)

Version

1.0

Author

Dr.-Ing. Klaus Friedewald

Header belonging to [TKTRNX.hpp](#). The Source Format complies to the requirements of FTN77 Fixed Formar as well as Fortran08 Free Form.

Note

Because the following definition not being part of a module, the DOXYGEN parser is not able to handle the combination of COMMON and INTEGER declarations. Workaround: `\cond ... \endcond`.

Definition in file [Tktrnx.fd](#).

8.37 Tktrnx.fd

```

00001      !> \file Tktrnx.fd
00002      !> \brief   wX Port: TCS Common Block TKTRNX
00003      !> \version 1.0
00004      !> \author  Dr.-Ing. Klaus Friedewald
00005      !> \~german
00006      !> Header passend zu TKTRNX.hpp. Das Quelltextformat ist sowohl zum FTN77 Fixed
00007      !> Format als auch zum Ftn08 Free Format kompatibel.
00008      !> \note
00009      !> Da die folgende Definition kein Bestandteil eines Moduls
00010      !> ist, versagt der DOXYGEN-Parser bei der Kombination von
00011      !> COMMON und INTEGER. Workaraound: \\cond ... \\endcond.
00012      !> \~english
00013      !> Header belonging to TKTRNX.hpp. The Source Format complies to the
00014      !> requirements of FTN77 Fixed Formar as well as Fortran08 Free Form.
00015      !> \note

```

```

00016 !> Because the following definition not being part of a module, the
00017 !> DOXYGEN parser is not able to handle the combination of COMMON
00018 !> and INTEGER declarations. Workaround: \\cond ... \\endcond.
00019 !> \\~
00020 !> \\cond
00021
00022     use iso_c_binding, only: c_int, c_float, c_sizeof
00023
00024     integer (c_int)                                &
00025     & khomey,                                       &
00026     & khorsz,kversz,                               &
00027     & kitalc,ksizef,                               &
00028     & klmrgn,krmrgn, kScrX,kScrY,                 &
00029     & kbeamx,kbeamy,                               &
00030     & kminsx,kminsy,kmaxsx,kmaxsy                 &
00031     real (c_float)                                &
00032     & tminvx,tminvy,tmaxvx,tmaxvy,                 &
00033     & trcosf,trsinf,trscal,                       &
00034     & xfac,yfac,xlog,ylog                         &
00035     integer (c_int)                                &
00036     & kStCol,                                       &
00037     & iLinCol, iBckCol, iTxtCol
00038
00039
00040     COMMON /tktrnx/                                &
00041     & khomey,                                       &
00042     & khorsz,kversz,                               &
00043     & kitalc,ksizef,                               &
00044     & klmrgn,krmrgn, kscrx,kscry,                 &
00045     & kbeamx,kbeamy,                               &
00046     & kminsx,kminsy,kmaxsx,kmaxsy,tminvx,tminvy,tmaxvx,tmaxvy, &
00047     & trcosf,trsinf,trscal,                       &
00048     & xfac,yfac,xlog,ylog,kstcol,                 &
00049     & ilincol, ibckcol, itxtcol
00050
00051     SAVE /tktrnx/
00052     bind(c, name='tktrnx_') :: /tktrnx/
00053
00054 !> \\endcond
00055
00056

```

8.38 TKTRNX.hpp File Reference

wX Port: TCS Common Block [TKTRNX](#)

Classes

- struct [TKTRNX](#)

Variables

- struct [TKTRNX tktrnx_](#)

8.38.1 Detailed Description

wX Port: TCS Common Block [TKTRNX](#)

Version

1.0

Author

Dr.-Ing. Klaus Friedewald

C header belonging to TKTRNX.fd

Note

wX-Version auf Basis der SDL-Version 1.2

Definition in file [TKTRNX.hpp](#).

8.38.2 Variable Documentation

8.38.2.1 tktrnx_

```
struct TKTRNX tktrnx_
```

8.39 TKTRNX.hpp

```
00001 /** *****
00002 \file      TKTRNX.hpp
00003 \brief     wx Port: TCS Common Block TKTRNX
00004 \version  1.0
00005 \author   Dr.-Ing. Klaus Friedewald
00006 \~german
00007          C Header passend zu TKTRNX.fd
00008 \~english
00009          C header belonging to TKTRNX.fd
00010 \~
00011
00012 \note
00013     wx-Version auf Basis der SDL-Version 1.2
00014
00015 ***** */
00016
00017 extern "C" {
00018     extern struct TKTRNX {
00019         int
00020         khomey,
00021         khorsz,kversz,
00022         kitalc,ksizef,
00023         klmrgn,krmrgn, kScrX,kScrY,
00024         kbeamx,kbeamy,
00025         kminsx,kminsy,kmaxsx,kmaxsy;
00026
00027         float
00028         tminvx,tminvy,tmaxvx,tmaxvy,
00029         trcosf,trsinf,trscal
00030         ,xfac,yfac,xlog,ylog;
00031         int
00032         kStCol,
00033         iLinCol, iBckCol, iTxtCol;
00034     } tktrnx_; // use gfortran FTN77 name mangling
00035 }
00036
```

8.40 wxTCSmain.cpp File Reference

Initialization of wxWidgets.

```
#include <wx/wx.h>
#include "graph2d.h"
```

Classes

- class [wxTCSapp](#)

Macros

- #define [MainProgram](#) MAIN__

Functions

- void [_gfortran_set_args](#) (int argc, char *argv[])

8.40.1 Detailed Description

Initialization of wxWidgets.

Version

0.85

Author

(C) 2023 Dr.-Ing. Klaus Friedewald

Copyright

GNU LESSER GENERAL PUBLIC LICENSE Version 3

[wxTCSapp](#) for executing Fortran console programs
 Definition in file [wxTCSmain.cpp](#).

8.40.2 Macro Definition Documentation**8.40.2.1 MainProgram**

void MainProgram MAIN__

Definition at line 14 of file [wxTCSmain.cpp](#).**8.40.3 Function Documentation****8.40.3.1 _gfortran_set_args()**

```
void _gfortran_set_args (
    int argc,
    char * argv[] )
```

8.41 wxTCSmain.cpp

```
00001 /** *****
00002 \file      wxTCSmain.cpp
00003 \brief     Initialization of wxWidgets
00004 \version   0.85
00005 \author    (C) 2023 Dr.-Ing. Klaus Friedewald
00006 \copyright GNU LESSER GENERAL PUBLIC LICENSE Version 3
00007 \~german
00008      wxTCSapp zur Ausführung von Fortran-Konsolenprogrammen
00009 \~english
00010      wxTCSapp for executing Fortran console programs
00011 \~
00012 ***** */
00013
00014 #define MainProgram MAIN__
00015 // #define MainProgram ftnmain2sub_
00016
00017 #include <wx/wx.h>
00018 #include "graph2d.h"
00019
00020
00021 extern "C" {
00022     void MainProgram (); // subroutine plot f1
00023 }
00024
00025 extern "C" {
00026     void _gfortran_set_args (int argc, char *argv[]);
00027 }
00028
00029
00030
00031 class wxTCSapp : public wxApp
00032 {
00033 public:
00034     virtual bool OnInit();
00035     virtual void OnIdle();
```

```
00036 private:
00037     bool MainStarted = false;
00038     wxFrame* wxAppframe;
00039 };
00040
00041 IMPLEMENT_APP(wxTCSapp)
00042
00043 bool wxTCSapp::OnInit() // Build wx Event Loop
00044 {
00045     int i1,i2;
00046     wxAppframe = new wxFrame((wxFrame*) NULL, -1, GetAppDisplayName(),
00047                             wxDefaultPosition,wxDefaultSize, wxDEFAULT_FRAME_STYLE);
00047     wxAppframe->Show(true);
00048     SetTopWindow(wxAppframe);
00049
00050     _gfortran_set_args (wxAppConsole::argc, wxAppConsole::argv); // Initialize FTN command-line
00051     intrinsics
00052     Connect (wxEVT_IDLE, (wxObjectEventFunction)&wxTCSapp::OnIdle);
00053     inittl (2, nullptr, wxAppframe, nullptr); // use wxAppframe for plotting
00054
00055     return true;
00056 }
00057
00058 void wxTCSapp::OnIdle()
00059 {
00060     if (!MainStarted) {
00061         MainStarted= true; // 1st statement to avoid recursive invocation, e.g. due to wxYield() in
00062         tinput
00062         MainProgram();
00063         wxAppframe->Refresh();
00064     }
00065     return;
00066 }
```

Index

`_gfortran_set_args`
 `wxTCSmain.cpp`, 187
`~cTCSCanvas`
 `cTCSCanvas`, 14

`action`
 `xJournalEntry_typ`, 25

`ActiveCanvas`
 `TCSdrWXcpp.cpp`, 132

`ActiveCanvasID`
 `TCSdrWXcpp.cpp`, 132

`AG2.for`, 27

`ag2lev`, 30
 `alfsetc`, 30
 `bar`, 30
 `binitt`, 30
 `bsyms`, 30
 `calcon`, 30
 `calpnt`, 31
 `check`, 31
 `cmnmx`, 31
 `coptim`, 31
 `cplot`, 31
 `datget`, 32
 `dinitx`, 32
 `dinity`, 32
 `dlimx`, 32
 `dlimy`, 32
 `dsplay`, 33
 `eformc`, 33
 `esplit`, 33
 `expoutc`, 33
 `fformc`, 33
 `filbox`, 34
 `findge`, 34
 `findle`, 34
 `fonlyc`, 34
 `frame`, 35
 `gline`, 35
 `grid`, 35
 `hbarst`, 35
 `iformc`, 35
 `infin`, 36
 `iother`, 36
 `iubgc`, 36
 `justerc`, 36
 `keyset`, 36
 `label`, 37
 `leap`, 37
 `line`, 37

`locge`, 37
 `locle`, 37
 `logtix`, 38
 `loptim`, 38
 `lwidth`, 38
 `mnmx`, 38
 `monpos`, 38
 `notatec`, 39
 `npts`, 39
 `numsetc`, 39
 `optim`, 39
 `oubgc`, 39
 `place`, 40
 `remlab`, 40
 `rescom`, 40
 `rgchek`, 40
 `roundd`, 40
 `roundu`, 41
 `savcom`, 41
 `setwin`, 41
 `sizel`, 41
 `sizes`, 41
 `slimx`, 42
 `slimy`, 42
 `spread`, 42
 `stepl`, 42
 `steps`, 42
 `symbl`, 43
 `symout`, 43
 `teksym`, 43
 `teksym1`, 43
 `tset`, 43
 `tset2`, 44
 `typck`, 44
 `vbarst`, 44
 `vlablc`, 44
 `width`, 44
 `xden`, 45
 `xetyp`, 45
 `xfrm`, 45
 `xlab`, 45
 `xlen`, 45
 `xloc`, 45
 `xloctp`, 46
 `xmfrm`, 46
 `xmtcs`, 46
 `xneat`, 46
 `xtics`, 46
 `xtype`, 46

- xwidth, [47](#)
- xzero, [47](#)
- yden, [47](#)
- yetyp, [47](#)
- yfrm, [47](#)
- ylab, [47](#)
- ylen, [48](#)
- yloc, [48](#)
- ylocrt, [48](#)
- ymdyd, [48](#)
- ymfrm, [48](#)
- ymtcs, [49](#)
- yneat, [49](#)
- ytics, [49](#)
- ytype, [49](#)
- ywidth, [49](#)
- yzero, [49](#)
- AG2Holerith.for, [85](#)
 - alfset, [86](#)
 - comdmp, [86](#)
 - comget, [86](#)
 - comset, [87](#)
 - eform, [87](#)
 - expout, [87](#)
 - fform, [87](#)
 - fonly, [87](#)
 - hlabel, [88](#)
 - hstrin, [88](#)
 - ibasec, [88](#)
 - ibasex, [88](#)
 - ibasey, [88](#)
 - iform, [89](#)
 - juster, [89](#)
 - notate, [89](#)
 - numset, [89](#)
 - vlabel, [90](#)
 - vstrin, [90](#)
- ag2lev
 - AG2.for, [30](#)
- AG2Sav
 - cTCScanvas, [14](#)
- AG2uline.for, [95](#)
 - uline, [96](#)
- AG2umnmx.for, [96](#)
 - umnmx, [97](#)
- AG2upoint.for, [97](#)
 - upoint, [97](#)
- AG2users.for, [98](#)
 - users, [98](#)
- AG2useset.for, [99](#)
 - useset, [99](#)
- AG2usesetC.for, [100](#)
 - usesetc, [100](#)
- AG2UsrSoftek.for, [101](#)
 - softek, [101](#)
- alfset
 - AG2Holerith.for, [86](#)
- alfsetc
 - AG2.for, [30](#)
- ancho
 - TCS.for, [111](#)
- anmode
 - TCSdrWXfor.f08, [179](#)
- anstr
 - TCS.for, [111](#)
- baksp
 - TCS.for, [112](#)
- bar
 - AG2.for, [30](#)
- BCKCOL
 - TCSdrWXcpp.cpp, [127](#)
- BELL
 - TCSdrWXcpp.cpp, [127](#)
- binitt
 - AG2.for, [30](#)
- bsyms
 - AG2.for, [30](#)
- calcon
 - AG2.for, [30](#)
- calpnt
 - AG2.for, [31](#)
- cartn
 - TCS.for, [112](#)
- check
 - AG2.for, [31](#)
- ClippingNotActive
 - cTCScanvas, [14](#)
- cmnmx
 - AG2.for, [31](#)
- comdmp
 - AG2Holerith.for, [86](#)
- comget
 - AG2Holerith.for, [86](#)
- comset
 - AG2Holerith.for, [87](#)
- coptim
 - AG2.for, [31](#)
- cplot
 - AG2.for, [31](#)
- csize
 - TCSdrWXfor.f08, [179](#)
- cTCScanvas, [13](#)
 - ~cTCScanvas, [14](#)
 - AG2Sav, [14](#)
 - ClippingNotActive, [14](#)
 - cTCScanvas, [14](#)
 - DefaultBckColSav, [14](#)
 - DefaultLinColSav, [14](#)
 - DefaultTxtColSav, [15](#)
 - HardcopyFileSav, [15](#)
 - ID_TCSframe, [15](#)
 - ID_TCSpanel, [15](#)
 - ID_TCSstatus, [15](#)
 - logWindow, [15](#)
 - sect0Sav, [16](#)

- TCSbrush, [16](#)
- TCSfont, [16](#)
- TCSframe, [16](#)
- TCSmouseButtonDown, [16](#)
- TCSmouseX, [16](#)
- TCSmouseY, [17](#)
- TCSpanel, [17](#)
- TCSpanelKeyPressed, [17](#)
- TCSpen, [17](#)
- TCSstatusBar, [17](#)
- TekSav, [17](#)
- xTCSJournal, [18](#)
- CustomizeProgPar
 - TCSdrWXcpp.cpp, [127](#)
- dasha
 - TCS.for, [112](#)
- dashr
 - TCS.for, [112](#)
- datget
 - AG2.for, [32](#)
- DBLSIZ
 - TCSdrWXcpp.cpp, [128](#)
- DCURSR
 - TCSdrWXcpp.cpp, [128](#)
- DefaultBckColSav
 - cTCScanvas, [14](#)
- DEFAULTCOLOUR
 - TCSdrWXcpp.cpp, [128](#)
- DefaultLinColSav
 - cTCScanvas, [14](#)
- DefaultTxtColSav
 - cTCScanvas, [15](#)
- dinitx
 - AG2.for, [32](#)
- dinity
 - AG2.for, [32](#)
- dlimx
 - AG2.for, [32](#)
- dlimy
 - AG2.for, [32](#)
- drawa
 - TCS.for, [112](#)
- drawr
 - TCS.for, [113](#)
- DRWABS
 - TCSdrWXcpp.cpp, [128](#)
- drwrel
 - TCSdrWXfor.f08, [179](#)
- DSHABS
 - TCSdrWXcpp.cpp, [128](#)
- dshrel
 - TCSdrWXfor.f08, [179](#)
- dsplay
 - AG2.for, [33](#)
- dwindo
 - TCS.for, [113](#)
- eform
 - AG2Holerith.for, [87](#)
- eformc
 - AG2.for, [33](#)
- ERASE
 - TCSdrWXcpp.cpp, [128](#)
- ERR_EXIT
 - TCSdrWXcpp.hpp, [158](#)
- ERR_NOFNT
 - TCSdrWXcpp.hpp, [158](#)
- ERR_NOFNTFIL
 - TCSdrWXcpp.hpp, [158](#)
- ERR_UNKNAUDIO
 - TCSdrWXcpp.hpp, [158](#)
- ERR_UNKNGRAPHCARD
 - TCSdrWXcpp.hpp, [158](#)
- ERR_XMLOPEN
 - TCSdrWXcpp.hpp, [158](#)
- ERR_XMLPARSER
 - TCSdrWXcpp.hpp, [158](#)
- ErrMsg
 - TCSdrWXcpp.cpp, [127](#)
- esplit
 - AG2.for, [33](#)
- expout
 - AG2Holerith.for, [87](#)
- expoutc
 - AG2.for, [33](#)
- fform
 - AG2Holerith.for, [87](#)
- fformc
 - AG2.for, [33](#)
- filbox
 - AG2.for, [34](#)
- findge
 - AG2.for, [34](#)
- findle
 - AG2.for, [34](#)
- FINITT
 - TCSdrWXcpp.cpp, [128](#)
- fonly
 - AG2Holerith.for, [87](#)
- fonlyc
 - AG2.for, [34](#)
- frame
 - AG2.for, [35](#)
- G2dAG2.fd, [101](#)
- genflg
 - TCS.for, [113](#)
- getCanvasID
 - TCSdrWXcpp.cpp, [128](#)
- gethdc
 - GetHDC.for, [103](#)
- GetHDC.for, [103](#)
- gethdc, [103](#)
- gline
 - AG2.for, [35](#)
- graphicerror

- TCSdrWXfor.f08, 179
- grid
 - AG2.for, 35
- HardcopyFileSav
 - cTCScanvas, 15
- hbarst
 - AG2.for, 35
- HDCOPY
 - TCSdrWXcpp.cpp, 129
- hlabel
 - AG2Holerith.for, 88
- home
 - TCS.for, 113
- hstrin
 - AG2Holerith.for, 88
- i1
 - xJournalEntry_typ, 25
- i2
 - xJournalEntry_typ, 25
- ibasec
 - AG2Holerith.for, 88
- ibasex
 - AG2Holerith.for, 88
- ibasey
 - AG2Holerith.for, 88
- iBckCol
 - TKTRNX, 19
- ID_TCSframe
 - cTCScanvas, 15
- ID_TCSpanel
 - cTCScanvas, 15
- ID_TCSstatus
 - cTCScanvas, 15
- iform
 - AG2Holerith.for, 89
- iformc
 - AG2.for, 35
- iHardcopyCount
 - TCSdrWXcpp.cpp, 132
- iLinCol
 - TKTRNX, 19
- infin
 - AG2.for, 36
- INIFILEXT
 - TCSdrWXcpp.hpp, 159
- INIFILEXTTOKEN
 - TCSdrWXcpp.hpp, 159
- initt
 - TCSdrWXfor.f08, 180
- initt0
 - TCSdrWXcpp.cpp, 129
- initt1
 - TCSdrWXcpp.cpp, 129
- iother
 - AG2.for, 36
- IOWAIT
 - TCSdrWXcpp.cpp, 129
- istringlen
 - Strings.for, 107
- ITALIC
 - TCSdrWXcpp.cpp, 129
- ITALIR
 - TCSdrWXcpp.cpp, 129
- itrimlen
 - Strings.for, 107
- iTxtCol
 - TKTRNX, 19
- iubgc
 - AG2.for, 36
- juster
 - AG2Holerith.for, 89
- justerc
 - AG2.for, 36
- kbeamx
 - TKTRNX, 19
- kbeamy
 - TKTRNX, 19
- keyset
 - AG2.for, 36
- khomey
 - TKTRNX, 19
- khorsz
 - TKTRNX, 20
- kitalc
 - TKTRNX, 20
- klmrgn
 - TKTRNX, 20
- kmaxsx
 - TKTRNX, 20
- kmaxsy
 - TKTRNX, 20
- kminsx
 - TKTRNX, 20
- kminsy
 - TKTRNX, 21
- krmrgn
 - TKTRNX, 21
- kScrX
 - TKTRNX, 21
- kScrY
 - TKTRNX, 21
- ksizef
 - TKTRNX, 21
- kStCol
 - TKTRNX, 21
- kversz
 - TKTRNX, 22
- label
 - AG2.for, 37
- leap
 - AG2.for, 37
- lib_movc3_
 - TCSdrWXcpp.cpp, 129

- LINCOL
 - TCSdrWXcpp.cpp, [129](#)
- line
 - AG2.for, [37](#)
- linef
 - TCS.for, [113](#)
- linhgt
 - TCS.for, [114](#)
- lintrn
 - TCS.for, [114](#)
- linwdt
 - TCS.for, [114](#)
- locge
 - AG2.for, [37](#)
- locle
 - AG2.for, [37](#)
- logtix
 - AG2.for, [38](#)
- logtrn
 - TCS.for, [114](#)
- logWindow
 - cTCScanvas, [15](#)
- loptim
 - AG2.for, [38](#)
- lwidth
 - AG2.for, [38](#)
- Mainpage.dox, [105](#)
- MainProgram
 - wxTCSmain.cpp, [187](#)
- MAX_COLOR_INDEX
 - TCSdrWXcpp.cpp, [127](#)
- MAX_HDCCOUNT
 - TCSdrWXcpp.hpp, [159](#)
- MAX_OPEN_CANVAS
 - TCSdrWXcpp.hpp, [159](#)
- mnmx
 - AG2.for, [38](#)
- monpos
 - AG2.for, [38](#)
- MOVABS
 - TCSdrWXcpp.cpp, [130](#)
- movea
 - TCS.for, [114](#)
- mover
 - TCS.for, [114](#)
- movrel
 - TCSdrWXfor.f08, [180](#)
- MSG_HDCACT
 - TCSdrWXcpp.hpp, [159](#)
- MSG_MAXERRNO
 - TCSdrWXcpp.hpp, [159](#)
- MSG_NOMOUSE
 - TCSdrWXcpp.hpp, [159](#)
- MSG_USR
 - TCSdrWXcpp.hpp, [159](#)
- MSG_USR2
 - TCSdrWXcpp.hpp, [159](#)
- newlin
 - TCS.for, [115](#)
- newpag
 - TCS.for, [115](#)
- next
 - xJournalEntry_typ, [26](#)
- notate
 - AG2Holerith.for, [89](#)
- notatec
 - AG2.for, [39](#)
- npts
 - AG2.for, [39](#)
- NRMSIZ
 - TCSdrWXcpp.cpp, [130](#)
- numset
 - AG2Holerith.for, [89](#)
- numsetc
 - AG2.for, [39](#)
- OnIdle
 - wxTCSapp, [24](#)
- OnInit
 - wxTCSapp, [24](#)
- OpenCanvases
 - TCSdrWXcpp.cpp, [132](#)
- optim
 - AG2.for, [39](#)
- oubgc
 - AG2.for, [39](#)
- outgtext_
 - TCSdrWXcpp.cpp, [130](#)
- outtext_
 - TCSdrWXcpp.cpp, [130](#)
- place
 - AG2.for, [40](#)
- plothdc
 - PlotHDC.f03, [106](#)
- PlotHDC.f03, [105](#)
- plothdc, [106](#)
- PNTABS
 - TCSdrWXcpp.cpp, [130](#)
- pntrel
 - TCSdrWXfor.f08, [180](#)
- pointa
 - TCS.for, [115](#)
- pointr
 - TCS.for, [115](#)
- PresetProgPar
 - TCSdrWXcpp.cpp, [130](#)
- previous
 - xJournalEntry_typ, [26](#)
- printstring
 - Strings.for, [108](#)
- PROGDIRTOKEN
 - TCSdrWXcpp.hpp, [159](#)
- rel2ab
 - TCS.for, [115](#)

- remlab
 - AG2.for, [40](#)
- RepaintBuffer
 - TCSdrWXcpp.cpp, [130](#)
- rescal
 - TCS.for, [116](#)
- rescom
 - AG2.for, [40](#)
- RESTAT
 - TCSdrWXcpp.cpp, [130](#)
- revcot
 - TCS.for, [116](#)
- rgchek
 - AG2.for, [40](#)
- roundd
 - AG2.for, [40](#)
- roundu
 - AG2.for, [41](#)
- rrotat
 - TCS.for, [116](#)
- rscale
 - TCS.for, [116](#)
- savcom
 - AG2.for, [41](#)
- sect0Sav
 - cTCSCanvas, [16](#)
- seeloc
 - TCSdrWXfor.f08, [180](#)
- seetrm
 - TCS.for, [116](#)
- seetrn
 - TCS.for, [117](#)
- setmrg
 - TCS.for, [117](#)
- setwin
 - AG2.for, [41](#)
- szel
 - AG2.for, [41](#)
- sizes
 - AG2.for, [41](#)
- slimx
 - AG2.for, [42](#)
- slimy
 - AG2.for, [42](#)
- softek
 - AG2UsrSoftek.for, [101](#)
- spread
 - AG2.for, [42](#)
- STAT_MAXROWS
 - TCSdrWXcpp.hpp, [160](#)
- statst
 - TCSdrWXfor.f08, [180](#)
- stepl
 - AG2.for, [42](#)
- steps
 - AG2.for, [42](#)
- Strings.for, [107](#)
 - istringlen, [107](#)
 - itrimlen, [107](#)
 - printstring, [108](#)
 - substitute, [108](#)
- substitute
 - Strings.for, [108](#)
- SVSTAT
 - TCSdrWXcpp.cpp, [131](#)
- swind1_
 - TCSdrWXcpp.cpp, [131](#)
- swindo
 - TCS.for, [117](#)
- syml
 - AG2.for, [43](#)
- symout
 - AG2.for, [43](#)
- szTCSErrorMsg
 - TCSdrWXcpp.cpp, [132](#)
- szTCSHardcopyFile
 - TCSdrWXcpp.cpp, [132](#)
- szTCSIniFile
 - TCSdrWXcpp.cpp, [133](#)
- szTCSsect0
 - TCSdrWXcpp.cpp, [133](#)
- szTCSstatWindowName
 - TCSdrWXcpp.cpp, [133](#)
- szTCSWindowName
 - TCSdrWXcpp.cpp, [133](#)
- TCS.for, [110](#)
 - ancho, [111](#)
 - anstr, [111](#)
 - baksp, [112](#)
 - cartn, [112](#)
 - dasha, [112](#)
 - dashr, [112](#)
 - drawa, [112](#)
 - drawr, [113](#)
 - dwindo, [113](#)
 - genflg, [113](#)
 - home, [113](#)
 - linef, [113](#)
 - linhgt, [114](#)
 - lintrn, [114](#)
 - linwdt, [114](#)
 - logtrn, [114](#)
 - movea, [114](#)
 - mover, [114](#)
 - newlin, [115](#)
 - newpag, [115](#)
 - pointa, [115](#)
 - pointr, [115](#)
 - rel2ab, [115](#)
 - rescal, [116](#)
 - revcot, [116](#)
 - rrotat, [116](#)
 - rscale, [116](#)
 - seetrm, [116](#)
 - seetrn, [117](#)
 - setmrg, [117](#)

- swindo, [117](#)
- twindo, [117](#)
- vcursr, [117](#)
- vwindo, [118](#)
- wincot, [118](#)
- TCS_FILE_NAMELEN
 - TCSdrWXcpp.hpp, [160](#)
- TCS_HDCFILE_NAME
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_BCKCOL
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_COPLCK
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_COPLCKL
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_COPMEM
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_COPMEML
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_EXIT
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_EXITL
 - TCSdrWXcpp.hpp, [160](#)
- TCS_INIDEF_HDCACT
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_HDCACTL
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_HDCOPN
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_HDCOPNL
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_HDCWRT
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_HDCWRTL
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_INI2
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_INI2L
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_JOUADD
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_JOUADDL
 - TCSdrWXcpp.hpp, [161](#)
- TCS_INIDEF_JOUCLR
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUCLRL
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUCREATE
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUCREATEL
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUENTRY
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUENTRYL
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUUNKWN
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_JOUUNKWNL
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_LINCOL
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_NOFNT
 - TCSdrWXcpp.hpp, [162](#)
- TCS_INIDEF_NOFNTFIL
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_NOFNTFILL
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_NOFNTL
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_STATPOSX
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_STATPOSY
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_STATSIZX
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_STATSIZY
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_TXTCOL
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_UNKNAUDIO
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_UNKNAUDIOL
 - TCSdrWXcpp.hpp, [163](#)
- TCS_INIDEF_UNKNGRAPHCARD
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_UNKNGRAPHCARDL
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USR
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USR2
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USR2L
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USRL
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USRWRN
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_USRWRNL
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_WINPOSX
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_WINPOSY
 - TCSdrWXcpp.hpp, [164](#)
- TCS_INIDEF_WINSIZX
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIDEF_WINSIZY
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIDEF_XMLOPEN
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIDEF_XMLOPENL
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIDEF_XMLPARSER
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIDEF_XMLPARSERL
 - TCSdrWXcpp.hpp, [165](#)
- TCS_INIFILE_NAME

- TCSdrWXcpp.hpp, 165
- TCS_INISECT0
 - TCSdrWXcpp.hpp, 165
- TCS_INISECT1
 - TCSdrWXcpp.hpp, 165
- TCS_INISECT2
 - TCSdrWXcpp.hpp, 165
- TCS_INISECT3
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_BCKCOL
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_COPLCK
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_COPLCKL
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_COPMEM
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_COPMEML
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_EXIT
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_EXITL
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_HDCACT
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_HDCACTL
 - TCSdrWXcpp.hpp, 166
- TCS_INIVAR_HDCNAM
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_HDCOPN
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_HDCOPNL
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_HDCWRT
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_HDCWRTL
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_INI2
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_INI2L
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_JOUADD
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_JOUADDL
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_JOUCLR
 - TCSdrWXcpp.hpp, 167
- TCS_INIVAR_JOUCLRL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUCREATE
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUCREATEL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUENTRY
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUENTRYL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUUNKWN
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_JOUUNKWNL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_LINCOL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_NOFNT
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_NOFNTFIL
 - TCSdrWXcpp.hpp, 168
- TCS_INIVAR_NOFNTFILL
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_NOFNTL
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_STATNAM
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_STATPOSX
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_STATPOSY
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_STATSIZX
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_STATSIZY
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_TXTCOL
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_UNKNAUDIO
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_UNKNAUDIOL
 - TCSdrWXcpp.hpp, 169
- TCS_INIVAR_UNKNGRAPHCARD
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_UNKNGRAPHCARDL
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USR
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USR2
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USR2L
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USRL
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USRWRN
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_USRWRNL
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_WINNAM
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_WINPOSX
 - TCSdrWXcpp.hpp, 170
- TCS_INIVAR_WINPOSY
 - TCSdrWXcpp.hpp, 171
- TCS_INIVAR_WINSIZX
 - TCSdrWXcpp.hpp, 171
- TCS_INIVAR_WINSIZY
 - TCSdrWXcpp.hpp, 171
- TCS_INIVAR_XMLOPEN
 - TCSdrWXcpp.hpp, 171
- TCS_INIVAR_XMLOPENL

- TCSdrWXcpp.hpp, 171
- TCS_INIVAR_XMLPARSER
 - TCSdrWXcpp.hpp, 171
- TCS_INIVAR_XMLPARSERL
 - TCSdrWXcpp.hpp, 171
- TCS_LINEWIDTH
 - TCSdrWXcpp.hpp, 171
- TCS_MESSAGELEN
 - TCSdrWXcpp.hpp, 171
- TCS_REL_CHR_HEIGHT
 - TCSdrWXcpp.hpp, 171
- TCS_REL_CHR_SPACING
 - TCSdrWXcpp.hpp, 172
- TCS_STATWINDOW_NAME
 - TCSdrWXcpp.hpp, 172
- TCS_WINDOW_NAME
 - TCSdrWXcpp.hpp, 172
- TCS_WINDOW_NAMELEN
 - TCSdrWXcpp.hpp, 172
- TCSbrush
 - cTCScanvas, 16
- TCSColorTable
 - TCSdrWXcpp.cpp, 133
- TCSDefaultBckCol
 - TCSdrWXcpp.cpp, 133
- TCSDefaultLinCol
 - TCSdrWXcpp.cpp, 133
- TCSDefaultTxtCol
 - TCSdrWXcpp.cpp, 133
- TCSdrWXcpp.cpp, 124
 - ActiveCanvas, 132
 - ActiveCanvasID, 132
 - BCKCOL, 127
 - BELL, 127
 - CustomizeProgPar, 127
 - DBLSIZ, 128
 - DCURSR, 128
 - DEFAULTCOLOUR, 128
 - DRWABS, 128
 - DSHABS, 128
 - ERASE, 128
 - ErrMsg, 127
 - FINITT, 128
 - getCanvasID, 128
 - HDCOPY, 129
 - iHardcopyCount, 132
 - initt0, 129
 - initt1, 129
 - IOWAIT, 129
 - ITALIC, 129
 - ITALIR, 129
 - lib_movc3_, 129
 - LINCOL, 129
 - MAX_COLOR_INDEX, 127
 - MOVABS, 130
 - NRMSIZ, 130
 - OpenCanvases, 132
 - outgtext_, 130
 - outtext_, 130
 - PNTABS, 130
 - PresetProgPar, 130
 - RepaintBuffer, 130
 - RESTAT, 130
 - SVSTAT, 131
 - swind1_, 131
 - szTCSErrorMsg, 132
 - szTCSHardcopyFile, 132
 - szTCSIniFile, 133
 - szTCSsect0, 133
 - szTCSstatWindowName, 133
 - szTCSWindowName, 133
 - TCSColorTable, 133
 - TCSDefaultBckCol, 133
 - TCSDefaultLinCol, 133
 - TCSDefaultTxtCol, 133
 - TCSErrorLev, 134
 - TCSGraphicError, 131
 - TCSwindowIniXrelpos, 134
 - TCSwindowIniXrelsiz, 134
 - TCSwindowIniYrelpos, 134
 - TCSwindowIniYrelsiz, 134
 - TINPUT, 131
 - TMPSTRLEN, 127
 - TXTCOL, 131
 - winlbl0, 131
 - WINSELECT, 131
 - wxDEBUG_LEVEL, 127
 - xJournalEntry_typ, 127
 - XMLreadProgPar, 132
- TCSdrWXcpp.hpp, 154
 - ERR_EXIT, 158
 - ERR_NOFNT, 158
 - ERR_NOFNTFIL, 158
 - ERR_UNKNAUDIO, 158
 - ERR_UNKNGRAPHCARD, 158
 - ERR_XMLOPEN, 158
 - ERR_XMLPARSER, 158
 - INIFILEXT, 159
 - INIFILEXTTOKEN, 159
 - MAX_HDCCOUNT, 159
 - MAX_OPEN_CANVAS, 159
 - MSG_HDCACT, 159
 - MSG_MAXERRNO, 159
 - MSG_NOMOUSE, 159
 - MSG_USR, 159
 - MSG_USR2, 159
 - PROGDIRTOKEN, 159
 - STAT_MAXROWS, 160
 - TCS_FILE_NAMELEN, 160
 - TCS_HDCFILE_NAME, 160
 - TCS_INIDEF_BCKCOL, 160
 - TCS_INIDEF_COPLCK, 160
 - TCS_INIDEF_COPLCKL, 160
 - TCS_INIDEF_COPMEM, 160
 - TCS_INIDEF_COPMEML, 160
 - TCS_INIDEF_EXIT, 160

TCS_INIDEF_EXITL, 160
TCS_INIDEF_HDCACT, 161
TCS_INIDEF_HDCACTL, 161
TCS_INIDEF_HDCOPN, 161
TCS_INIDEF_HDCOPNL, 161
TCS_INIDEF_HDCWRT, 161
TCS_INIDEF_HDCWRTL, 161
TCS_INIDEF_INI2, 161
TCS_INIDEF_INI2L, 161
TCS_INIDEF_JOUADD, 161
TCS_INIDEF_JOUADDL, 161
TCS_INIDEF_JOUCLR, 162
TCS_INIDEF_JOUCLRL, 162
TCS_INIDEF_JOUCREATE, 162
TCS_INIDEF_JOUCREATEL, 162
TCS_INIDEF_JOUMENTRY, 162
TCS_INIDEF_JOUMENTRYL, 162
TCS_INIDEF_JOUUNKWN, 162
TCS_INIDEF_JOUUNKWNL, 162
TCS_INIDEF_LINCOL, 162
TCS_INIDEF_NOFNT, 162
TCS_INIDEF_NOFNTFIL, 163
TCS_INIDEF_NOFNTFILL, 163
TCS_INIDEF_NOFNTL, 163
TCS_INIDEF_STATPOX, 163
TCS_INIDEF_STATPOSY, 163
TCS_INIDEF_STATSIZX, 163
TCS_INIDEF_STATSIZY, 163
TCS_INIDEF_TXTCOL, 163
TCS_INIDEF_UNKNAUDIO, 163
TCS_INIDEF_UNKNAUDIOL, 163
TCS_INIDEF_UNKNGRAPHCARD, 164
TCS_INIDEF_UNKNGRAPHCARDL, 164
TCS_INIDEF_USR, 164
TCS_INIDEF_USR2, 164
TCS_INIDEF_USR2L, 164
TCS_INIDEF_USRL, 164
TCS_INIDEF_USRWRN, 164
TCS_INIDEF_USRWRNL, 164
TCS_INIDEF_WINPOX, 164
TCS_INIDEF_WINPOSY, 164
TCS_INIDEF_WINSIZX, 165
TCS_INIDEF_WINSIZY, 165
TCS_INIDEF_XMLOPEN, 165
TCS_INIDEF_XMLOPENL, 165
TCS_INIDEF_XMLPARSER, 165
TCS_INIDEF_XMLPARSERL, 165
TCS_INIFILE_NAME, 165
TCS_INISECT0, 165
TCS_INISECT1, 165
TCS_INISECT2, 165
TCS_INISECT3, 166
TCS_INIVAR_BCKCOL, 166
TCS_INIVAR_COPLCK, 166
TCS_INIVAR_COPLCKL, 166
TCS_INIVAR_COPMEM, 166
TCS_INIVAR_COPMEML, 166
TCS_INIVAR_EXIT, 166
TCS_INIVAR_EXITL, 166
TCS_INIVAR_HDCACT, 166
TCS_INIVAR_HDCACTL, 166
TCS_INIVAR_HDCNAM, 167
TCS_INIVAR_HDCOPN, 167
TCS_INIVAR_HDCOPNL, 167
TCS_INIVAR_HDCWRT, 167
TCS_INIVAR_HDCWRTL, 167
TCS_INIVAR_INI2, 167
TCS_INIVAR_INI2L, 167
TCS_INIVAR_JOUADD, 167
TCS_INIVAR_JOUADDL, 167
TCS_INIVAR_JOUCLR, 167
TCS_INIVAR_JOUCLRL, 168
TCS_INIVAR_JOUCREATE, 168
TCS_INIVAR_JOUCREATEL, 168
TCS_INIVAR_JOUMENTRY, 168
TCS_INIVAR_JOUMENTRYL, 168
TCS_INIVAR_JOUUNKWN, 168
TCS_INIVAR_JOUUNKWNL, 168
TCS_INIVAR_LINCOL, 168
TCS_INIVAR_NOFNT, 168
TCS_INIVAR_NOFNTFIL, 168
TCS_INIVAR_NOFNTFILL, 169
TCS_INIVAR_NOFNTL, 169
TCS_INIVAR_STATNAM, 169
TCS_INIVAR_STATPOX, 169
TCS_INIVAR_STATPOSY, 169
TCS_INIVAR_STATSIZX, 169
TCS_INIVAR_STATSIZY, 169
TCS_INIVAR_TXTCOL, 169
TCS_INIVAR_UNKNAUDIO, 169
TCS_INIVAR_UNKNAUDIOL, 169
TCS_INIVAR_UNKNGRAPHCARD, 170
TCS_INIVAR_UNKNGRAPHCARDL, 170
TCS_INIVAR_USR, 170
TCS_INIVAR_USR2, 170
TCS_INIVAR_USR2L, 170
TCS_INIVAR_USRL, 170
TCS_INIVAR_USRWRN, 170
TCS_INIVAR_USRWRNL, 170
TCS_INIVAR_WINNAM, 170
TCS_INIVAR_WINPOX, 170
TCS_INIVAR_WINPOSY, 171
TCS_INIVAR_WINSIZX, 171
TCS_INIVAR_WINSIZY, 171
TCS_INIVAR_XMLOPEN, 171
TCS_INIVAR_XMLOPENL, 171
TCS_INIVAR_XMLPARSER, 171
TCS_INIVAR_XMLPARSERL, 171
TCS_LINEWIDTH, 171
TCS_MESSAGELEN, 171
TCS_REL_CHR_HEIGHT, 171
TCS_REL_CHR_SPACING, 172
TCS_STATWINDOW_NAME, 172
TCS_WINDOW_NAME, 172
TCS_WINDOW_NAMELEN, 172
TEK_XMAX, 172

- TEK_YMAX, [172](#)
- WRN_COPYLOCK, [172](#)
- WRN_COPYNOMEM, [172](#)
- WRN_HDCFILOPN, [172](#)
- WRN_HDCFILWRT, [172](#)
- WRN_HDCINTERN, [173](#)
- WRN_INI2, [173](#)
- WRN_JOUADD, [173](#)
- WRN_JOUCLR, [173](#)
- WRN_JOUCREATE, [173](#)
- WRN_JOUMENTRY, [173](#)
- WRN_JOUUNKWN, [173](#)
- WRN_NOMSG, [173](#)
- WRN_USRPRESSANY, [173](#)
- XACTION_ASCII, [173](#)
- XACTION_BCKCOL, [174](#)
- XACTION_CLIP, [174](#)
- XACTION_CLIP1, [174](#)
- XACTION_CLIP2, [174](#)
- XACTION_DRWABS, [174](#)
- XACTION_DSHABS, [174](#)
- XACTION_DSHSTYLE, [174](#)
- XACTION_ERASE, [174](#)
- XACTION_FONTATTR, [174](#)
- XACTION_GTEXT, [174](#)
- XACTION_INITT, [175](#)
- XACTION_LINCOL, [175](#)
- XACTION_MOVABS, [175](#)
- XACTION_NOOP, [175](#)
- XACTION_PNTABS, [175](#)
- XACTION_TXTCOL, [175](#)
- TCSdrWXfor.f08, [178](#)
 - anmode, [179](#)
 - csize, [179](#)
 - drwrel, [179](#)
 - dshrel, [179](#)
 - graphicerror, [179](#)
 - initt, [180](#)
 - movrel, [180](#)
 - pntrel, [180](#)
 - seeloc, [180](#)
 - statst, [180](#)
 - tcslev, [180](#)
 - toutpt, [180](#)
 - toutst, [180](#)
 - toutstc, [181](#)
 - winlbl, [181](#)
- TCSerrorLev
 - TCSdrWXcpp.cpp, [134](#)
- TCSfont
 - cTCScanvas, [16](#)
- TCSframe
 - cTCScanvas, [16](#)
- TCSGraphicError
 - TCSdrWXcpp.cpp, [131](#)
- tcslev
 - TCSdrWXfor.f08, [180](#)
- TCSmouseButtonDown
 - cTCScanvas, [16](#)
- TCSmouseX
 - cTCScanvas, [16](#)
- TCSmouseY
 - cTCScanvas, [17](#)
- TCSpanel
 - cTCScanvas, [17](#)
- TCSpanelKeyPressed
 - cTCScanvas, [17](#)
- TCSpen
 - cTCScanvas, [17](#)
- TCSstatusBar
 - cTCScanvas, [17](#)
- TCSwindowIniXrelpos
 - TCSdrWXcpp.cpp, [134](#)
- TCSwindowIniXrelsiz
 - TCSdrWXcpp.cpp, [134](#)
- TCSwindowIniYrelpos
 - TCSdrWXcpp.cpp, [134](#)
- TCSwindowIniYrelsiz
 - TCSdrWXcpp.cpp, [134](#)
- TEK_XMAX
 - TCSdrWXcpp.hpp, [172](#)
- TEK_YMAX
 - TCSdrWXcpp.hpp, [172](#)
- TekSav
 - cTCScanvas, [17](#)
- teksym
 - AG2.for, [43](#)
- teksym1
 - AG2.for, [43](#)
- TINPUT
 - TCSdrWXcpp.cpp, [131](#)
- TKTRNX, [18](#)
 - iBckCol, [19](#)
 - iLinCol, [19](#)
 - iTxtCol, [19](#)
 - kbeamx, [19](#)
 - kbeamy, [19](#)
 - khomey, [19](#)
 - khorsz, [20](#)
 - kitalc, [20](#)
 - klmrgn, [20](#)
 - kmaxsx, [20](#)
 - kmaxsy, [20](#)
 - kminsx, [20](#)
 - kminsy, [21](#)
 - krmrgn, [21](#)
 - kScrX, [21](#)
 - kScrY, [21](#)
 - ksizef, [21](#)
 - kStCol, [21](#)
 - kversz, [22](#)
 - tmaxvx, [22](#)
 - tmaxvy, [22](#)
 - tminvx, [22](#)
 - tminvy, [22](#)
 - trcosf, [22](#)

- trscal, [23](#)
- trsinf, [23](#)
- xfac, [23](#)
- xlog, [23](#)
- yfac, [23](#)
- ylog, [23](#)
- Tktrnx.fd, [184](#)
- TKTRNX.hpp, [185](#)
 - tktrnx_, [186](#)
- tktrnx_
 - TKTRNX.hpp, [186](#)
- tmaxvx
 - TKTRNX, [22](#)
- tmaxvy
 - TKTRNX, [22](#)
- tminvx
 - TKTRNX, [22](#)
- tminvy
 - TKTRNX, [22](#)
- TMPSTRLEN
 - TCSdrWXcpp.cpp, [127](#)
- toutpt
 - TCSdrWXfor.f08, [180](#)
- toutst
 - TCSdrWXfor.f08, [180](#)
- toutstc
 - TCSdrWXfor.f08, [181](#)
- trcosf
 - TKTRNX, [22](#)
- trscal
 - TKTRNX, [23](#)
- trsinf
 - TKTRNX, [23](#)
- tset
 - AG2.for, [43](#)
- tset2
 - AG2.for, [44](#)
- twindo
 - TCS.for, [117](#)
- TXTCOL
 - TCSdrWXcpp.cpp, [131](#)
- typck
 - AG2.for, [44](#)
- uline
 - AG2uline.for, [96](#)
- umnmx
 - AG2umnmx.for, [97](#)
- upoint
 - AG2upoint.for, [97](#)
- users
 - AG2users.for, [98](#)
- useset
 - AG2useset.for, [99](#)
- usesetc
 - AG2usesetC.for, [100](#)
- vbarst
 - AG2.for, [44](#)
- vcursr
 - TCS.for, [117](#)
- vlabel
 - AG2Holerith.for, [90](#)
- vlablc
 - AG2.for, [44](#)
- vstrin
 - AG2Holerith.for, [90](#)
- vwindo
 - TCS.for, [118](#)
- width
 - AG2.for, [44](#)
- wincot
 - TCS.for, [118](#)
- winlbl
 - TCSdrWXfor.f08, [181](#)
- winlbl0
 - TCSdrWXcpp.cpp, [131](#)
- WINSELECT
 - TCSdrWXcpp.cpp, [131](#)
- WRN_COPYLOCK
 - TCSdrWXcpp.hpp, [172](#)
- WRN_COPYNOMEM
 - TCSdrWXcpp.hpp, [172](#)
- WRN_HDCFILOPN
 - TCSdrWXcpp.hpp, [172](#)
- WRN_HDCFILWRT
 - TCSdrWXcpp.hpp, [172](#)
- WRN_HDCINTERN
 - TCSdrWXcpp.hpp, [173](#)
- WRN_INI2
 - TCSdrWXcpp.hpp, [173](#)
- WRN_JOUADD
 - TCSdrWXcpp.hpp, [173](#)
- WRN_JOUCLR
 - TCSdrWXcpp.hpp, [173](#)
- WRN_JOUCREATE
 - TCSdrWXcpp.hpp, [173](#)
- WRN_JOUMENTRY
 - TCSdrWXcpp.hpp, [173](#)
- WRN_JOUUNKWN
 - TCSdrWXcpp.hpp, [173](#)
- WRN_NOMSG
 - TCSdrWXcpp.hpp, [173](#)
- WRN_USRPRESSANY
 - TCSdrWXcpp.hpp, [173](#)
- wxDEBUG_LEVEL
 - TCSdrWXcpp.cpp, [127](#)
- wxTCSapp, [24](#)
 - OnIdle, [24](#)
 - OnInit, [24](#)
- wxTCSmain.cpp, [186](#)
 - _gfortran_set_args, [187](#)
 - MainProgram, [187](#)
- XACTION_ASCII
 - TCSdrWXcpp.hpp, [173](#)
- XACTION_BCKCOL

- TCSdrWXcpp.hpp, [174](#)
- XACTION_CLIP
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_CLIP1
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_CLIP2
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_DRWABS
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_DSHABS
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_DSHSTYLE
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_ERASE
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_FONTATTR
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_GTEXT
 - TCSdrWXcpp.hpp, [174](#)
- XACTION_INITT
 - TCSdrWXcpp.hpp, [175](#)
- XACTION_LINCOL
 - TCSdrWXcpp.hpp, [175](#)
- XACTION_MOVABS
 - TCSdrWXcpp.hpp, [175](#)
- XACTION_NOOP
 - TCSdrWXcpp.hpp, [175](#)
- XACTION_PNTABS
 - TCSdrWXcpp.hpp, [175](#)
- XACTION_TXTCOL
 - TCSdrWXcpp.hpp, [175](#)
- xden
 - AG2.for, [45](#)
- xetyp
 - AG2.for, [45](#)
- xfac
 - TKTRNX, [23](#)
- xfrm
 - AG2.for, [45](#)
- xJournalEntry_typ, [25](#)
 - action, [25](#)
 - i1, [25](#)
 - i2, [25](#)
 - next, [26](#)
 - previous, [26](#)
 - TCSdrWXcpp.cpp, [127](#)
- xlab
 - AG2.for, [45](#)
- xlen
 - AG2.for, [45](#)
- xloc
 - AG2.for, [45](#)
- xloctp
 - AG2.for, [46](#)
- xlog
 - TKTRNX, [23](#)
- xmfrm
 - AG2.for, [46](#)
- XMLreadProgPar
 - TCSdrWXcpp.cpp, [132](#)
- xmtcs
 - AG2.for, [46](#)
- xneat
 - AG2.for, [46](#)
- xTCSJournal
 - cTCScanvas, [18](#)
- xtics
 - AG2.for, [46](#)
- xtype
 - AG2.for, [46](#)
- xwdth
 - AG2.for, [47](#)
- xzero
 - AG2.for, [47](#)
- yden
 - AG2.for, [47](#)
- yetyp
 - AG2.for, [47](#)
- yfac
 - TKTRNX, [23](#)
- yfrm
 - AG2.for, [47](#)
- ylab
 - AG2.for, [47](#)
- ylen
 - AG2.for, [48](#)
- yloc
 - AG2.for, [48](#)
- ylocrt
 - AG2.for, [48](#)
- ylog
 - TKTRNX, [23](#)
- ymdyd
 - AG2.for, [48](#)
- ymfrm
 - AG2.for, [48](#)
- ymtcs
 - AG2.for, [49](#)
- yneat
 - AG2.for, [49](#)
- ytics
 - AG2.for, [49](#)
- ytype
 - AG2.for, [49](#)
- ywdth
 - AG2.for, [49](#)
- yzero
 - AG2.for, [49](#)