

This part of the experiment is prepared with Online LaTeX Editor Overleaf. Visit the website for the source here:

<https://www.overleaf.com/read/khqgqbrzzvcn#466db0>

2. EXPERIMENT 2 - PRELIMINARY WORK

2.1 The Lissajous pattern shown in *Fig. 4* is observed on the CRT screen. Find the phase shift between the signals applied to the *X* and *Y* inputs of the scope.




Figure 4

Answer: The phase shift can be obtained by taking the arcsine of the ratio of the amplitude of the voltage function and the *y*-intercept of the Lissajous pattern. The semi-major axis of the ellipse has a positive slope.

$$\text{Phase shift: } \theta = \sin^{-1} \left(\frac{2}{4} \right) = [30^\circ]$$

2.2 *Fig. 5* shows a Lissajous pattern observed on the CRT screen. Determine the frequency relationship between the signals applied to the *X* and *Y* inputs of the scope.




Figure 5


Answer:

$$\frac{f_X}{f_Y} = \frac{\text{Number of vertical tangents}}{\text{Number of horizontal tangents}} = \frac{4}{6} \Rightarrow 3f_X = 2f_Y$$

2.3 Two sinusoidal inputs having the same amplitudes but different period are applied to the X and Y inputs of the CRO. Draw the Lissajous pattern that will be observed on the CRT, for $T_Y = 4T_X$.

Answer: Since $T_Y = 4T_X$, we have $4f_Y = f_X$, from which we can draw the Lissajous pattern.


$$\frac{f_X}{f_Y} = \frac{4}{1}$$



2.4 The signals V_1 and V_2 are applied to the X and Y inputs of the scope. Sketch the Lissajous pattern and calculate the phase difference between the two signals.

$$V_1 = 10 \cos(\omega t), \quad V_2 = 15 \sin(\omega t - 180^\circ)$$

Answer: $V_1 = 10 \cos(\omega t) = 10 \sin(\omega t + 90^\circ)$



$$\text{Phase angle: } 90^\circ - (-180^\circ) = 270^\circ.$$