



KubeCon



CloudNativeCon

North America 2019

# kubectl development workshop

*Sean Sullivan - Google*  
*co-chair SIG CLI*  
*github: seans3*  
*slack: seans*



# Goals



KubeCon



CloudNativeCon

North America 2019

**This workshop is intended to create a more thriving and knowledgeable kubectl development community. We hope to give developers interested in kubectl (and SIG CLI in general) the skills necessary to quickly become productive in this area.**

## kubectl development workshop

- A) **Basic Structure of a kubectl subcommand: Cobra/Options/Flags**  
**Codelab: Connect new kubectl subcommand**
- B) **Communicating with the APIServer and Converting Resources**  
**Codelab: Add a resource.Builder and resource.Helper**
- C) **Printing with Printers and the ResourcePrinter interface**  
**Codelab: Add printing to new kubectl subcommand**
- D) **kubectl Unit Testing**  
**Codelab: Add unit test to new kubectl subcommand**

# Part A: Structure of kubectl subcommand



CloudNativeCon

North America 2019

## Cobra/Options/Flags

```
// Also stores flag values
type FooOptions struct {}

// Returns a pointer to the structure encapsulating the command
func NewCmdFoo(factory, ioStreams) *cobra.Command {
    o := NewFooOptions()
    cmd := &cobra.Command{
        // usage and help fields: usage, short help, long help, examples
        Run : func (cmd *cobra.Command, args []string) error {
            o.Complete() // Fill in the options struct
            o.Validate() // Validate the options struct
            o.RunFoo()   // Run the command using the options values
        }
    }
    // Define flags the command understands; stores values in options
    cmd.Flags().StringVar(&o.flag, name, default, usage)
}
```

# Part A: Cobra.Command



KubeCon



CloudNativeCon

North America 2019

Cobra is a library providing a simple interface to create powerful modern CLI interfaces similar to git & go tools.

- Structures for subcommand-based CLIs
- Fully POSIX-compliant flags (including short & long versions)
- Nested subcommands
- Global, local and cascading flags
- Intelligent suggestions (app srver... did you mean app server?)
- Automatic help generation for commands and flags
- Automatic help flag recognition of -h, --help, etc.

<https://github.com/spf13/cobra>

# Part A: Parameters to kubectl subcommand



KubeCon



CloudNativeCon

North America 2019

## Factory/IOStreams

### Factory

// functions which return clients

```
factory cmdutil.Factory
```

```
// NewBuilder returns an object that assists in loading objects
```

```
// from both disk and the server and which implements
```

```
// patterns for CLI interactions with generic resources.
```

```
NewBuilder() *resource.Builder
```

### IOStreams

encapsulates stdin/stdout/stderr

```
var ioStreams genericclioptions.IOStreams
```

# Codelab: Preliminaries



KubeCon



CloudNativeCon

North America 2019

Go Version: `>= 1.13.4`

```
$ go version
```

Code location:

```
K8SROOT/staging/src/k8s.io/kubect1/  
K8SROOT/pkg/kubect1/  
K8SROOT/staging/src/k8s.io/cliruntime/
```

From K8SROOT:

```
bazel test //staging/src/k8s.io/kubect1/...  
bazel test //pkg/kubect1/...  
bazel build //cmd/kubect1
```

kubect1 binary location:

```
K8SROOT/bazel-bin/cmd/kubect1/linux_amd64_pure_stripped/kubect1
```

```
make kubect1  
make kubect1 WHAT=./pkg/kubect1
```

# Codelab: Preliminaries



KubeCon



CloudNativeCon

North America 2019

## Verifying the compiled kubectl

```
$ kubectl version
```

```
Client Version: version.Info{Major:"1", Minor:"18+",  
GitVersion:"v1.18.0-alpha.0.1000+5c54e4b6baf555-dirty",  
GitCommit:"5c54e4b6baf5557ddaf98024609282189274978a",  
GitTreeState:"dirty", BuildDate:"2019-11-15T05:02:45Z",  
GoVersion:"go1.13.4", Compiler:"gc", Platform:"linux/amd64"}  
Server Version: version.Info{Major:"1", Minor:"14+",  
GitVersion:"v1.14.7-gke.23",  
GitCommit:"81c87c699557fed991e292cd328b2129c2f242a2",  
GitTreeState:"clean", BuildDate:"2019-11-07T19:23:23Z",  
GoVersion:"go1.12.11b4", Compiler:"gc", Platform:"linux/amd64"}
```



# Codelab: Setup



KubeCon



CloudNativeCon

North America 2019

Option 1 From empty dir:

```
$ git clone
```

```
https://github.com/seankubecon/kubernetes.git
```

```
$ cd kubernetes
```

Option 2 From the K8SROOT:

```
$ git remote add kubecon-workshop
```

```
https://github.com/seankubecon/kubernetes.git
```

```
$ git fetch kubecon-workshop
```

Next:

```
$ git checkout kubecon-cs-workshop
```

```
$ ls staging/src/k8s.io/kubectrl/pkg/cmd/foo
```

```
BUILD  foo.go  foo_test.go
```

```
$ bazel build //cmd/kubectrl
```

# Codelab: Connect kubectl Foo Command



KubeCon



CloudNativeCon

North America 2019

- 1) Connect the NewCmdFoo() to other kubectl subcommands
- 2) `$ kubectl foo -h`
- 3) `$ kubectl foo options`

`K8SROOT/pkg/kubectl/cmd/cmd.go` (connect subcommands)

`K8SROOT/cmd/kubectl/kubectl.go` (main)

# Part B



KubeCon



CloudNativeCon

North America 2019

**Just enough APIMachinery to ~~get~~  
~~confused~~ develop kubectl**

# Part B: APIMachinery Layers



KubeCon



CloudNativeCon

North America 2019

## APIMachinery Layers

**resource.Builder, resource.Helper (wraps RESTClient)**

```
result := factory.NewBuilder().withScheme(...)  
helper := resource.NewHelper(restClient, RESTMapping)
```



**RESTClient (Wraps REST Calls)**

```
restClient.Post()...
```



**Rest Protocol/HTTP (Lowest Level)**

```
GET https://<ipaddr>/api/v1/namespaces/default/pod
```

# Part B: REST Request over HTTP



KubeCon



CloudNativeCon

North America 2019

## Example of what HTTP REST call looks like (Method, URL, Body)

```
GET https://<ipaddr>/api/v1/namespaces/default/pods?limit=500
```

Request Headers:

```
Accept: application/json;as=Table;v=v1beta1;g=meta.k8s.io,  
application/json
```

```
User-Agent: kubectl/v1.14.7 (linux/amd64) kubernetes/8fca2ec
```

Try:

```
$ kubectl get po -v=8
```

```
$ kubectl get po -v=10 -o yaml
```

# Part B: REST Response over HTTP



KubeCon



CloudNativeCon

North America 2019

## REST HTTP Response

### Response Headers:

```
Date: Fri, 08 Nov 2019 21:45:53 GMT
Audit-Id: 052a40f5-15ab-438b-b7c5-bd65b356bf5d
Content-Type: application/json
Content-Length: 3772
```

### Response Body:

```
{"kind": "Table", "apiVersion": "meta.k8s.io/v1beta1", "metadata": {"selfLink": "/api/v1/namespaces/default/pods", "resourceVersion": "6270266"}, "columnDefinitions":
```

...

# Part B: APIMachinery -- Why?



KubeCon



CloudNativeCon

North America 2019

**APIMachinery & all the structures and code is basically trying to transform JSON blob (resource YAML) into/out of a go lang struct for that type.**

## JSON bytes

Response Body: {"kind":"Pod","apiVersion":"v1", ...



## go lang struct

// Pod is a collection of containers that can run on a host. This resource is created

// by clients and scheduled onto hosts.

```
type Pod struct {  
    metav1.TypeMeta `json:",inline"`  
    ...
```

# Part B: APIMachinery



KubeCon



CloudNativeCon

North America 2019

## There is a significant amount of complexity here

### Glossary of APIMachinery structures:

GVK (Group/Version/Kind): just three strings

Example: `apps/v1/Deployment`, `core/v1/Pod`

GVR (Group/Version/Resource): basically the same as a GVK

RESTMapping: basically a GVK and/or a GVR with namespace scope

Scheme: All the GVK's that the app (kubectl) knows how to transform

Codec/Serializer

Encoder: Transform the go struct into JSON bytes

Decoder: Transform the JSON bytes into go struct



# Part B: clientgo.RESTClient



KubeCon



CloudNativeCon

North America 2019

```
// staging/src/k8s.io/client-go/rest/client.go
//
// Interface captures the set of operations for generically interacting
// with Kubernetes REST apis.
type Interface interface {
    GetRateLimiter() flowcontrol.RateLimiter
    Verb(verb string) *Request
    Post() *Request
    Put() *Request
    Patch(pt types.PatchType) *Request
    Get() *Request
    Delete() *Request
    APIVersion() schema.GroupVersion
}
```

# Part B: resource.RESTClient



KubeCon



CloudNativeCon

North America 2019

```
// K8SROOT/staging/src/k8s.io/cli-runtime/pkg/resource/interfaces.go
//
// This interface narrows the client-go RESTClient interface slightly.
type RESTClient interface {
    Get() *rest.Request
    Post() *rest.Request
    Patch(types.PatchType) *rest.Request
    Delete() *rest.Request
    Put() *rest.Request
}
```

# Part B: resource.RESTClient



KubeCon



CloudNativeCon

North America 2019

**Example of using a RESTClient. Most of the code is actually on the `rest.Request` object. The `rest.Request` uses the Builder pattern. The following creates the passed *obj* on the `APIServer`. The call will return a `rest.Result`:**

```
restClient.Post().
    NamespaceIfScoped(namespace, m.NamespaceScoped).
    Resource(resource).
    VersionedParams(options, metav1.ParameterCodec).
    Body(obj).
    Do().
    Get()
```

# Part B: resource Builder/Helper



KubeCon



CloudNativeCon

North America 2019

The following two structures are at the level of abstraction of the app (kubectl). You will see these two structures frequently in kubectl. These structures wrap the `resource.RESTClient`:

- 1) `resource.Builder` is used for retrieving/decoding resources, whether from the local file system (YAML files) or from the APIServer.
- 2) `resource.Helper` is a wrapper around the `RESTClient`. It is used for communicating with the APIServer.

# Codelab: resource Builder & Helper



KubeCon



CloudNativeCon

North America 2019

## 1) Add a resource Builder to the foo subcommand

- Builder will allow reading a local YAML file into a runtime.Object
- Look at other kubectl subcommands to see the necessary Builder params for reading a file off the local filesystem (e.g. FilenameOptions).

## 2) Add a resource Helper to create the resource (that was read with the Builder) on the API Server (e.g. helper.Create(...))

# Part C: kubectl printing



KubeCon



CloudNativeCon

North America 2019

`PrintFlags`



`Printer (ResourcePrinter)`



`printer.PrintObj(obj)`

# Part C: kubectl printing



KubeCon



CloudNativeCon

North America 2019

## Some kubectl print options:

```
$ kubectl get po -o name  
$ kubectl get po -o yaml  
$ kubectl get po -o json  
$ kubectl get po -o jsonpath=...
```

**Each one of these corresponds to a ResourcePrinter. These live at:**

`K8SROOT/staging/src/k8s.io/cli-runtime/pkg/printers`

**We get to use these standard printers by filling in PrintFlags:**

`K8SROOT/staging/src/k8s.io/cli-runtime/pkg/genericclioptions`

```
PrintFlags: genericclioptions.NewPrintFlags("op").WithDefaultOutput("name")
```

# Codelab: Add printing



KubeCon



CloudNativeCon

North America 2019

- 1) Add `genericclioptions.PrintFlags` to `FooOptions`
- 2) Create new `PrintFlags` with default output as “name” Printer
- 3) Create Printer from flags
- 4) Call `printer.PrintObj(obj)` on object created previously with Builder



# Part D: kubectl unit tests



KubeCon



CloudNativeCon

North America 2019

## Example Unit Test (delete\_test.go):

```
// Create a fake/test factory using the "test" namespace.
testfactory := cmdtesting.NewTestFactory().WithNamespace("test")
defer tf.Cleanup()

// Create a real Codec with the Scheme.
codec := scheme.Codecs.LegacyCodec(scheme.Scheme.PrioritizedVersionsAllGroups()...)

// Create a fake RESTClient, mocking the HTTP Response (based on HTTP Request).
testfactory.UnstructuredClient = &fake.RESTClient{...}

// Create fake IOStreams.
streams, _, buf, _ := genericclioptions.NewTestIOStreams()

// Create the kubectl subcommand, and pass some flags.
cmd := NewCmdDelete(tf, streams)
cmd.Flags().Set("namespace", "test")
cmd.Flags().Set("cascade", "false")
cmd.Flags().Set("output", "name")

// Execute the command, and check what was printed to the buffer.
cmd.Run(cmd, []string{"replicationcontrollers/redis-master-controller"})
if buf.String() != "replicationcontroller/redis-master-controller\n" {
    t.Errorf("unexpected output: %s", buf.String())
}
```

# Part D: kubectl unit tests



KubeCon



CloudNativeCon

North America 2019

## Example Fake RESTClient:

```
testfactory.UnstructuredClient = &fake.RESTClient{
    Client: fake.CreateHTTPClient(func(req *http.Request) (*http.Response, error) {
        switch p, m := req.URL.Path, req.Method; {

            // replication controller with cascade off
            case p == "/namespaces/test/replicationcontrollers/redis-master-controller" && m
== "DELETE":
                return &http.Response{StatusCode: http.StatusOK, Header:
cmdtesting.DefaultHeader(), Body: cmdtesting.ObjBody(codec, &rc.Items[0]\
)}, nil

            // secret with cascade on, but no client-side reaper
            case p == "/namespaces/test/secrets/mysecret" && m == "DELETE":
                return &http.Response{StatusCode: http.StatusOK, Header:
cmdtesting.DefaultHeader(), Body: cmdtesting.ObjBody(codec, &rc.Items[0]\
)}, nil

            default:
                // Ensures no GET is performed when deleting by name
                t.Fatalf("unexpected request: %#v\n%#v", req.URL, req)
                return nil, nil
        }
    }),
}
```

# Codelab: kubectl unit tests



KubeCon




CloudNativeCon

North America 2019

- 1) Write a unit test for the Builder to fake out the creation of the pod



**KubeCon**



**CloudNativeCon**

**North America 2019**

