



### CloudNativeCon





# Deep Dive: Cluster API



### Who are we?







Vince Prignano
Senior Software Engineer @VMware
@vincepri



Ashish Amarnath
Senior Software Engineer @Salesforce
@ashish-amarnath





- Project overview
- Walkthrough of v1alpha2 types, architecture
- Demo
- What's next and planned features
- How to get involved
- Q&A





# Overview



## Why Cluster API?






Cluster lifecycle management is difficult

- Ecosystem is fragmented
- Difficult to build higher order functionality
  - Managed control plane
  - Automation: autoscaling, repair, upgrades
  - Consistent cross-cloud cluster management

### What is Cluster API?








### Where does Cluster API fit?







### Where are we now?





- SIG Cluster-Lifecycle sub-project
- 200+ Contributors
- Alpha stage
  - v1alpha1: build an initial implementation
  - v1alpha2: solid foundations, infrastructure agnostic bootstrapping, improved extensibility
  - *v1alpha3*: new higher level primitives, QoL improvements, and more! (details on this later)

### Where do we want to be?





- Make managing the lifecycle of Kubernetes clusters boring
- Batteries included
  - High level tooling for the 80% use case
  - Ship with Kubeadm
  - Support target environments from development to cloud to bare metal
- Support advanced use cases: code, plugins, documentation
  - Security requirements
  - Different topologies
  - Complex scenarios





# Today: v1alpha2



## Cluster





```
apiVersion: cluster.x-k8s.io/v1alpha2
kind: Cluster
metadata:
  name: capi-quickstart
spec:
  clusterNetwork:
    pods:
      cidrBlocks: ["192.168.0.0/16"]
  infrastructureRef:
    apiVersion: infrastructure.cluster.x-k8s.io/v1alpha2
    kind: AWSCluster
    name: capi-quickstart
```

## InfraCluster





apiVersion: infrastructure.cluster.x-k8s.io/v1alpha2

kind: AWSCluster

name: capi-quickstart

spec:

metadata:

region: us-east-1

sshKeyName: default



### Machine





```
apiVersion: cluster.x-k8s.io/v1alpha2
kind: Machine
metadata:
  name: capi-quickstart-controlplane-0
  labels:
    cluster.x-k8s.io/control-plane: "true"
    cluster.x-k8s.io/cluster-name: "capi-quickstart"
spec:
  version: v1.15.3
  bootstrap:
    configRef:
      apiVersion: bootstrap.cluster.x-k8s.io/v1alpha2
      kind: KubeadmConfig
      name: capi-quickstart-controlplane-0
  infrastructureRef:
    apiVersion: infrastructure.cluster.x-k8s.io/v1alpha2
    kind: AWSMachine
    name: capi-quickstart-controlplane-0
```



## **InfraMachine**





North America 2019

```
apiVersion: infrastructure.cluster.x-k8s.io/v1alpha2
```

kind: AWSMachine

metadata:

name: capi-quickstart-controlplane-0

spec:

instanceType: t3.large

iamInstanceProfile: "control-plane.cluster-api-provider-aws"

sshKeyName: default



# **BootstrapConfig**

apiVersion: bootstrap.cluster.x-k8s.io/v1alpha2





```
kind: KubeadmConfig
metadata:
 name: capi-quickstart-controlplane-0
spec:
  initConfiguration:
    nodeRegistration:
      name: '{{ ds.meta_data.hostname }}'
      kubeletExtraArgs:
        cloud-provider: aws
  clusterConfiguration:
    apiServer:
      extraArgs:
        cloud-provider: aws
    controllerManager:
      extraArgs:
        cloud-provider: aws
```



# MachineDeployment





```
apiVersion: cluster.x-k8s.io/v1alpha2
kind: MachineDeployment
metadata:
  name: capi-quickstart-worker
  labels:
    cluster.x-k8s.io/cluster-name: capi-quickstart
    nodepool: nodepool-0
spec:
  replicas: 1
  selector:
   matchLabels:
      cluster.x-k8s.io/cluster-name: capi-quickstart
      nodepool: nodepool-0 [ . . . ]
```



# MachineDeployment






```
[ \ldots ]
metadata:
  labels:
    cluster.x-k8s.io/cluster-name: capi-quickstart
    nodepool: nodepool-0
spec:
  version: v1.15.3
  bootstrap:
    configRef:
      name: capi-quickstart-worker
      apiVersion: bootstrap.cluster.x-k8s.io/v1alpha2
      kind: KubeadmConfigTemplate
  infrastructureRef:
    name: capi-quickstart-worker
    apiVersion: infrastructure.cluster.x-k8s.io/v1alpha2
    kind: AWSMachineTemplate
```




### **Architecture**













# Demo







# Next: v1alpha3



### **Planned features**





North America 201!

### **Control plane management**

- Based on Kubeadm and Machines.
- Includes upgrading Kubernetes versions.

### **MachinePool**

Support high level primitives for cloud provider agnostic auto-scaling.

### Failure domains

Spread control plane machines and nodes across availability zones.

### Clusterctl v2

Improve user experience with a new high level tool.

### **Planned features**





North America 201

#### **Node remediation**

Detect failures and act on them.

### **Testing framework**

 Write end-to-end tests for Cluster API and its providers with a new simplified framework.

#### **Validation webhooks**

 Improve user experience, provide error reasons for configuration errors, force immutability.

### Load balancer providers

 Provide support for pluggable load balancer implementations, especially useful for on-prem.





# Get involved!



### How can you help?







#### Writing skills?

 Document our <u>Book</u>: <u>quick start</u>, <u>architecture diagrams</u>, <u>contracts</u>, troubleshooting sections, and so on!

### Product skills?

- Gather <u>use cases</u>, compile user pulse surveys, draw roadmaps.
- Work with project's maintainers and the community to shape our product.
- Help with backlog grooming, <u>maintain milestones</u>.

### Coding skills?

- Review <u>pull requests</u>, <u>become an approver</u>.
- Search for <u>help wanted</u>, or <u>good first issues</u> across our repositories.
- Other skills? Have feedback, use cases, demos, or questions?
  - Join weekly community meetings, slack, mailing list.
  - Open issues, bring the what and whys.





Q&A

