




# Nuclio : KubeFlow Serverless's component

---

Orit Nissan-Messing, VP R&D, Iguazio

# Data Science Teams Don't Do Data Science


## Effort Allocation



Source: Google Developers Launchpad

**The need: Simpler Solutions, Better Data Integration**

Develop/Experiment



Package



- Dependencies
- Parameters
- Run scripts
- Build



Scale-out



- Load-balance
- Data partitions
- Model distribution
- Hyper params



Tune



- Parallelism
- GPU support
- Query tuning
- Caching



Instrument



- Monitoring
- Logging
- Versioning
- Security



Automate



- CI/CD
- Workflows
- Rolling upgrades
- A/B testing

**Weeks** with one  
data scientist




**Months** with a large team of developers,  
scientists, data engineers and DevOps



Automate DevOps to Deploy Projects in  
**One Week as Opposed to Months!**

# Example: Real-time Product Recommendations



Elastic functions + integrated feature store = simplicity and scalability




# Nuclio: Taking Serverless to Data Intensive Apps

## Extreme Performance




- Non-blocking, parallel
- Zero copy, buffer reuse
- Up to 400K events/sec/proc
- **GPU** optimizations

## Advanced Data & AI Features



- Auto-rebalance, checkpoints
- Any source: Kafka, NATS, Kinesis, event-hub, iguazio, pub/sub, RabbitMQ, Cron, ..
- NVIDIA Rapids integration

## Statefulness



- Data bindings
- Shared volumes
- Context cache

**Natively integrated with Kubeflow and Jupyter Notebooks**

# Using Nuclio to Accelerate ETL and Streaming

**Simple code! Automated DevOps ! Any Source!**

(e.g. read JSON Stream + aggregate + dump to Parquet)

```
def init_context(context):
    os.makedirs(sink, exist_ok=True)

def handler(context, event):
    add_log_to_batch(context, event.body)

    if len(batch) > batch_len:
        df = _batch_to_df(context)
        if not df.empty:
            df = df.groupby(['log_ip']).agg({'feconn': 'mean',
                                             'beconn': 'mean',
                                             'time_backend_response': 'max',
                                             'time_backend_response': 'mean',
                                             'time_queue': 'mean',
                                             'time_duration': 'mean',
                                             'time_request': 'mean',
                                             'time_backend_connect': 'mean'
                                             })

        df_to_parquet(df)
        reset_batch()
```




**500 MB/s**

**Simple  
Python**

**18 MB/s**

**4X Faster model serving  
(Nuclio + PyTorch + GPUs)**

[illegible]

# Why Not Use Serverless for Training and Data Prep?

*What about Training and data prep ?*




	Serverless Today	Data Prep and Training
<b>Task lifespan</b>	Millisecs to mins	Secs to hours
<b>Scaling</b>	Load-balancer	Partition, shuffle, reduce, Hyper-params
<b>State</b>	Stateless	Stateful
<b>Input</b>	Event	Params, Datasets

**Serverless: resource elasticity (to Zero) and automated deployment and operations**




# Introducing Nuclio ML Functions

Access from your notebook, IDE, or KubeFlow



**Common  
APIs &  
Automation**

**Multiple  
Engines**



**Built-in Artifacts &  
Runs Tracking**

**Elastic Scaling**

# Demo: Fast and Serverless KubeFlow Pipeline





# Thank You

---

[oritn@iguazio.com](mailto:oritn@iguazio.com), [www.iguazio.com](http://www.iguazio.com)