Chapter 2

Instructions: Language of the Computer

Memory Layout

- Text: program code
- Static data: global variables
  - e.g., static variables in C, constant arrays and strings
  - $gp initialized to address allowing ±offsets into this segment
- Dynamic data: heap
  - E.g., malloc in C, new in Java
- Stack: automatic storage



32-bit Constants

- Most constants are small
  - 16-bit immediate is sufficient
- For the occasional 32-bit constant

  `lui rt, constant`
  - Copies 16-bit constant to left 16 bits of rt
  - Clears right 16 bits of rt to 0



Branch Addressing

- Branch instructions specify
  - Opcode, two registers, target address
- Most branch targets are near branch
  - Forward or backward

- PC-relative addressing
  - Target address = PC + offset × 4
  - PC already incremented by 4 by this time

Jump Addressing

- Jump (`j` and `jal`) targets could be anywhere in text segment
  - Encode full address in instruction



- (Pseudo)Direct jump addressing
  - Target address = $PC_{31...28}$: (address × 4)

Target Addressing Example

- Loop code from earlier example
  - Assume Loop at location 80000

```
Loop: sll  $t1, $s3, 2      80000
      add  $t1, $t1, $s6    80004
      lw   $t0, 0($t1)      80008
      bne  $t0, $s5, Exit   80012
      addi $s3, $s3, 1      80016
      j    Loop             80020
Exit: …                     80024
```

0	0	19	9	4	0
0	9	22	9	0	32
35	9	8	0		
5	8	21	2		
8	19	19	1		
2	20000				

Branching Far Away

- If branch target is too far to encode with 16-bit offset, assembler rewrites the code
- Example

```
        beq $s0,$s1, L1
              ↓
        bne $s0,$s1, L2
        j L1
L2:     …
```

Addressing Mode Summary