Chapter 4

The Processor

Stalls and Performance

The BIG Picture

- Stalls reduce performance
  - But are required to get correct results
- Compiler can arrange code to avoid hazards and stalls
  - Requires knowledge of the pipeline structure

Control Hazards

- Branch determines flow of control
  - Fetching next instruction depends on branch outcome
  - Pipeline can’t always fetch correct instruction
    - Still working on ID stage of branch
- In MIPS pipeline
  - Need to compare registers and compute target early in the pipeline
  - Add hardware to do it in ID stage

Dealing With Branch Hazards

- Hardware solutions
  - stall until you know which direction branch goes
  - guess which direction, start executing chosen path (but be prepared to undo any mistakes!)
    - static branch prediction: base guess on instruction type
    - dynamic branch prediction: base guess on execution history
  - reduce the branch delay

Stall on Branch

- Wait until branch outcome determined before fetching next instruction



Branch Prediction

- Longer pipelines can't readily determine branch outcome early
  - Stall penalty becomes unacceptable
- Predict outcome of branch
  - Only stall if prediction is wrong
- In MIPS pipeline
  - Can predict branches not taken
  - Fetch instruction after branch, with no delay

MIPS with Predict Not Taken

Prediction correct



Prediction incorrect



More-Realistic Branch Prediction

- Static branch prediction
  - Based on typical branch behavior
  - Example: loop and if-statement branches
    - Predict backward branches taken
    - Predict forward branches not taken
- Dynamic branch prediction
  - Hardware measures actual branch behavior
    - e.g., record recent history of each branch
  - Assume future behavior will continue the trend
    - When wrong, stall while re-fetching, and update history

Branch Hazards

- If branch outcome determined in MEM



Reducing Branch Delay

- Move hardware to determine outcome to ID stage
  - Target address adder
  - Register comparator
- Example: branch taken

```
36:   sub   $10, $4, $8
40:   beq   $1,  $3, 7
44:   and   $12, $2, $5
48:   or    $13, $2, $6
52:   add   $14, $4, $2
56:   slt   $15, $6, $7
      ...
72:   lw    $4, 50($7)
```

Example: Branch Taken



Example: Branch Taken