INTEGRATION GUIDE
- Integration Overview
- Server Environments
- Recommended Support/Administration Applications
- Fraud Management
- Common Use Cases
- eGift Fulfillment Options
- Onboarding and Offboarding Products

TUTORIALS - API REFERENCE
- eGift Issuance
- Balance Inquiry
- Redeem a Gift Card
- Reload a Gift Card
- Person Management Service
- Activation APIs

TUTORIALS - OFFLINE PROCESSES
- Offline Processes
- Product Catalog Management Service
- Product Line Management Service
- Product Management Service

TUTORIALS - LOCATING A STORE
- Locate a Store

FULFILLMENT MANAGEMENT SERVICES
- Overview
- Submit Fulfillment Order
- Get orders
- Get Order Details
- Get Lineitem details
- Get Card Information
- Get eGift Information
- Get Shipment Information
- Update Order Notification / Callback
- Order or Item Status Values
- Partner Domain Model Enhancements
- FAQs

ORDERING WITH FTP
- Dropship Ordering Overview
- Order Request File
- Order Confirmation File
- Shipment Notification File

DEVELOPMENT

# Locate a Store

## Introduction

The `Store Locators` API provides a list of participating locations where consumers can load funds, locate a product, or use their digital wallet to pay.

Users have the option to display the list of locations using the physical address or geographic coordinates.

## Locating a Participating Store

| Method | Service | Service Type |
|---|---|---|
| GET | locator | Synchronous |

- Post-Production URI: `https://api.certification.blackhawknetwork.com/locator/v1/stores`
- Production URI: `https://api.blackhawknetwork.com/locator/v1/stores`

## HTTP Header

The parameters below must be included in the header of the request:

| Name | Description | Type | Required | Allowed Values |
|---|---|---|---|---|
| `mid` | The merchant ID. A unique identifier issued by Blackhawk Network for the merchant who is making the call. | String | Y | Digits 0-9 or empty string (" ") |
| `tenant_id` | This is a unique identifier issued by Blackhawk Network for the tenant who is making the call. | String | Y | Digits 0-9, alpha (a-z, A-Z), or empty string (" ") |
| `trace_id` | A unique identifier for each request. Must not exceed 32 characters. | String | Y | Digits 0-9, alpha (a-z, A-Z), hyphen, and underscore |

Your header may look similar to the following example:

HTTP

```
Content-Type: application/json
mid: 60300112329
tenant_id: ZXF15KX4R6L9PK18NTL5B0KL70
trace_id: 2132r32r32
```

## Query Parameters

To retrieve a list of store locations, the following parameters can be included in the query:

| Parameter | Description | Type | Required | Default Value |
|---|---|---|---|---|
| `campaignId` | The campaign identification assigned to your account.<br><br>Max length: 45 characters | String | N | None |
| `lat` | The latitude of your **current** location. This takes priority over `zip`.<br><br>Requires the `lng` parameter. | String | N | None |
| `lng` | The longitude of your **current** location. This takes priority over `zip`.<br><br>Requires the `lat` parameter. | String | N | None |
| `page` | A pagination parameter.<br><br>Determines how many pages of records you receive, which you may opt to change after getting an initial list of results. | Integer | N | 0 |
| `pageSize` | A pagination parameter.<br><br>The number of records that are displayed on a page.<br><br>Max allowed value: 50 | Integer | N | 10 |
| `product` | A comma separated list of the product UPCs that should be located in participating stores.<br><br>Must not exceed 15 characters. | String | N | |
| `radius` | The maximum desired distance from the **current** location. Users can use the metric or imperial measurement system.<br><br>If no unit is added, results will default to `MI`.<br><br>Choose one of the following values:<br>• MI (miles)<br>• KM (kilometers)<br>• M (meters) | String | N | MI |

Guide to Header Attributes
Client Specific Identifiers
Forced Response Cards

| Parameter | Description | Type | Required | Default Value |
|---|---|---|---|---|
| `txn` | The transaction type you wish to locate. No more than 3 values are allowed.<br>Use the following values:<br>• ACTIVATION<br>• RELOAD<br>• REDEMPTION | String | N | None |
| `zip` | A valid 5-digit U.S. zip code.This field becomes required if `lat` and `lng` are not available. | String | N | None |

See Store Locators Response Object for an example request.

URI: `https://api.blackhawknetwork.com/locator/v1/stores?campaign=A8KVZCMG9Y49DB77B5HH3HTL7H&lat=37.7706&lng=-122.2648&page=0&pageSize=10&txn=Activation&product=987654321,987654322,987654323&radius=5000mi&trace_id=2132r32r32`

## Response

### Store Locators Response Object

The Store Locators API will return a response containing an HTTP status code in the header and a JSON object in the body. This response will tell us if the inquiry was successful and display the location information for participating stores.

Request Response

```
GET https://api.blackhawknetwork.com/locator/v1/stores?campaign=A8KVZCMG9Y49DB77B5HH3HTL7H&lat=37.7706&lng=-122.2648&page=0&pageSize=10&txn=Activa
Accept-Encoding: gzip,deflate
Connection: Keep-Alive
```

| Name | Description |
|---|---|
| `siteId` | The site identification number. |
| `siteName` | A descriptive name for the site. |
| `contactName` | The contact name for the location. |
| `addressLine1` | The first line of the location's address. |
| `addressLine2` | The second line of the location's address. |
| `addressLine3` | The third line of the location's address. |
| `city` | The location's city. |
| `state` | The location's state. |
| `zipCode` | The location's zip code. |
| `country` | The location's country. |
| `latitude` | The location's latitude. |
| `longitude` | The location's logitude. |
| `sort` | The distance of the participating store(s) from your current latitude and longitude. The results will be displayed in increasing order in the value specified in `radius`. |
| `phoneNumbers` | A JSON object with a list of the location's phone information. See Phone Numbers object for more information. |
| `productId` | Specifies which product is available at the site. |
| `size` | The total number of elements allowed to fit on the page, designated by the user. |
| `totalPages` | The total amount of pages that contain results. |
| `totalElements` | The total number of results from the query. |
| `numberOfElements` | The total number of results included on the page. |
| `number` | The number of pages included in the results. |
| `first` | Indicates whether the current page is first. |
| `last` | Indicates whether the current page is last. |

**Phone Numbers object**

| Name | Description |
|---|---|
| `number` | The phone number for a participating location. |
| `type` | The type of number listed for a participating location.<br>Value options:<br>• WORK<br>• HOME<br>• MOBILE<br>• FAX |

### HTTP Status Codes

HTTP response codes are used to indicate the outcome of the request.

The following table shows the HTTP codes and their meanings.

| HTTP Status Code | Status Code Description | Comments |
|---|---|---|
| 200 | OK | The request has been validated and processed. |
| 400 | Bad request | Check the body parameters to ensure they are correct and contain no special characters or spaces, then try again. |
| 403 | Forbidden request | The request is not supported for the user or user credentials. |
| 404 | Not Found | The server is unable to find the requested resources. |
| 500 | Server Error | The service is experiencing a technical error. Try again in a few minutes. |

Updated about 2 months ago

← Attributes Reference

Overview →

Did this page help you? Yes No

©2023 All rights reserved. Terms of Use | Cookie Policy | Privacy Policy | Partner Disclosure | Developer Agreement