INTEGRATION GUIDE
- Integration Overview
- Server Environments
- Recommended Support/Administration Applications
- Fraud Management
- Common Use Cases
- eGift Fulfillment Options
- Onboarding and Offboarding Products

TUTORIALS - API REFERENCE
- eGift Issuance
- Balance Inquiry
- Redeem a Gift Card
- Reload a Gift Card
- Person Management Service
- Activation APIs

TUTORIALS - OFFLINE PROCESSES
- Offline Processes
- Product Catalog Management Service
- Product Line Management Service
- Product Management Service

TUTORIALS - LOCATING A STORE
- Locate a Store

FULFILLMENT MANAGEMENT SERVICES
- Overview
- Submit Fulfillment Order
- Get orders
- Get Order Details
- Get Lineitem details
- Get Card Information
- Get eGift Information
- Get Shipment Information
- Update Order Notification / Callback
- Order or Item Status Values
- Partner Domain Model Enhancements
- FAQs

ORDERING WITH FTP
- Dropship Ordering Overview
- Order Request File
- Order Confirmation File
- Shipment Notification File

DEVELOPMENT

Locate a Store

Introduction

The `Store Locators` API provides a list of participating locations where consumers can load funds, locate a product, or use their digital wallet to pay.

You have the option to display the list of locations using the physical address or geographic coordinates.

Locating a Participating Store

Method	Service	Service Type
GET	locator	Synchronous

- Post-Production URI: `https://api.certification.blackhawknetwork.com/locator/v1/stores`
- Production URI: `https://api.blackhawknetwork.com/locator/v1/stores`

HTTP Header

The header of the request must include the following parameters:

Name	Description	Type	Required	Allowed Values
`mid`	The merchant ID. A unique identifier issued by Blackhawk Network for the merchant who is making the call.	String	Y	Digits 0-9 or empty string (" ")
`tenant_id`	This is a unique identifier issued by Blackhawk Network for the tenant who is making the call.	String	Y	Digits 0-9, alpha (a-z, A-Z), or empty string (" ")
`trace_id`	A unique identifier for each request. Must not exceed 32 characters.	String	Y	Digits 0-9, alpha (a-z, A-Z), hyphen, and underscore

Your header may look similar to the following example:

HTTP

```
Content-Type: application/json
mid: 60300112329
tenant_id: ZXF15KX4R6L9PK18NTL5B0KL70
trace_id: 2132r32r32
```

Query Parameters

Include the following parameters in the query to retrieve a list of store locations:

Parameter	Description	Type	Required	Default Value
`campaignId`	The campaign identification assigned to your account. Max length: 45 characters	String	N	None
`lat`	The latitude of your **current** location. This takes priority over `zip`. Requires the `lng` parameter.	String	N	None
`lng`	The longitude of your **current** location. This takes priority over `zip`. Requires the `lat` parameter.	String	N	None
`page`	A pagination parameter. Determines how many pages of records you receive, which you may opt to change after getting an initial list of results.	Integer	N	0
`pageSize`	A pagination parameter. The number of records that are displayed on a page. Max allowed value: 50	Integer	N	10
`product`	A comma separated list of the product UPCs that should be located in participating stores. Must not exceed 15 characters.	String	N	
`radius`	The maximum desired distance from the **current** location. Users can use the metric or imperial measurement system. If no unit is added, results will default to `MI`. Choose one of the following values: • MI (miles) • KM (kilometers) • M (meters)	String	N	MI

Guide to Header Attributes
Client Specific Identifiers
Forced Response Cards

Parameter	Description	Type	Required	Default Value
`txn`	The transaction type you wish to locate. No more than 3 values are allowed. Use the following values: • ACTIVATION • RELOAD • REDEMPTION	String	N	None
`zip`	A valid 5-digit U.S. zip code.This field becomes required if `lat` and `lng` are not available.	String	N	None

See Store Locators Response Object for an example request.

URI: `https://api.blackhawknetwork.com/locator/v1/stores?campaign=A8KVZCMG9Y49DB77B5HH3HTL7H&lat=37.7706&lng=-122.2648&page=0&pageSize=10&txn=Activation&product=987654321,987654322,987654323&radius=5000mi&trace_id=2132r32r32`

Response

Store Locators Response Object

The Store Locators API will return a response containing an HTTP status code in the header and a JSON object in the body. This response will tell us if the inquiry was successful and display the location information for participating stores.

Request Response

```
GET https://api.blackhawknetwork.com/locator/v1/stores?campaign=A8KVZCMG9Y49DB77B5HH3HTL7H&lat=37.7706&lng=-122.2648&page=0&pageSize=10&txn=Activa
Accept-Encoding: gzip,deflate
Connection: Keep-Alive
```

Name	Description
`siteId`	The site identification number.
`siteName`	A descriptive name for the site.
`contactName`	The contact name for the location.
`addressLine1`	The first line of the location's address.
`addressLine2`	The second line of the location's address.
`addressLine3`	The third line of the location's address.
`city`	The location's city.
`state`	The location's state.
`zipCode`	The location's zip code.
`country`	The location's country.
`latitude`	The location's latitude.
`longitude`	The location's logitude.
`sort`	The distance of the participating store(s) from your current latitude and longitude. The results will be displayed in increasing order in the value specified in `radius`.
`phoneNumbers`	A JSON object with a list of the location's phone information. See Phone Numbers object for more information.
`productId`	Specifies which product is available at the site.
`size`	The total number of elements allowed to fit on the page, designated by the user.
`totalPages`	The total amount of pages that contain results.
`totalElements`	The total number of results from the query.
`numberOfElements`	The total number of results included on the page.
`number`	The number of pages included in the results.
`first`	Indicates whether the current page is first.
`last`	Indicates whether the current page is last.

Phone Numbers object

Name	Description
`number`	The phone number for a participating location.
`type`	The type of number listed for a participating location. Value options: • WORK • HOME • MOBILE • FAX

HTTP Status Codes

HTTP response codes are used to indicate the outcome of the request.

The following table shows the HTTP codes and their meanings.

HTTP Status Code	Status Code Description	Comments
200	OK	The request has been validated and processed.
400	Bad request	Check the body parameters to ensure they are correct and contain no special characters or spaces, then try again.
403	Forbidden request	The request is not supported for the user or user credentials.
404	Not Found	The server is unable to find the requested resources.
500	Server Error	The service is experiencing a technical error. Try again in a few minutes.

Updated about 2 months ago

← Attributes Reference

Overview →

Did this page help you? Yes No

©2023 All rights reserved. Terms of Use | Cookie Policy | Privacy Policy | Partner Disclosure | Developer Agreement