

# Amplitude sensing with a trapped-ion mechanical oscillator - Supplementary Material

K. A. Gilmore,<sup>1,2,\*</sup> J. G. Bohnet,<sup>1</sup> B. C. Sawyer,<sup>3</sup> J. W. Britton,<sup>4</sup> and J. J. Bollinger<sup>1</sup>

<sup>1</sup>*National Institute of Standards and Technology, Boulder, Colorado 80305, USA*

<sup>2</sup>*JILA and Department of Physics, University of Colorado, Boulder, Colorado, 80309, USA*

<sup>3</sup>*Georgia Tech Research Institute, Atlanta, Georgia 30332, USA*

<sup>4</sup>*U.S. Army Research Laboratory, Adelphi, Maryland 20783, USA*

To model the lineshape of the signal, it is necessary to account for the accumulated phase due to the spin-dependent ODF potential without making the simplification that  $\omega = \mu$ . This results in a characteristic response function for each sequence. For the  $n = 8$  CPMG sequence the response function is given by:

$$\theta_{tot} = \theta_{max} \left[ \text{sinc} \left( \frac{T}{2} (\omega - \mu) \right) \right] \left[ \cos \left( \frac{T}{2} (\omega - \mu) \right) \right] [\cos(T(\omega - \mu))] [\cos(2T(\omega - \mu))] . \quad (1)$$

$$\theta = \frac{DWF \cdot (U/\hbar) \cdot \delta k Z_c}{2} \text{sinc} \left( \frac{T}{2} (\omega - \mu) \right) \sin \left( \frac{\omega}{2} (T + t_\pi) \right) \sin(\xi) \cos(2\xi) \cos(4\xi), \quad (2)$$

where  $\xi = \frac{1}{2} (T(\omega - \mu) + \omega(T + t_\pi))$ .

## Incoherent sensing limits

Following earlier discussions, the probability of measuring  $|\uparrow\rangle$  at the end of the Ramsey sequence is

$$\langle P_\uparrow \rangle = \frac{1}{2} [1 - e^{-\Gamma\tau} J_0(\theta_{max})] , \quad (3)$$

where  $\langle \rangle$  denotes an average over many experimental trials and therefore over the random phase between the 1D optical lattice and the classically driven COM motion, and

$$\theta_{max} = DWF \cdot (U/\hbar) \cdot \delta k Z_c \cdot \tau . \quad (4)$$

Defining  $F(\theta_{max}^2) \equiv (1 - J_0(\theta_{max}))/2$  and denoting  $\langle P_\uparrow \rangle_{bck} = [1 - e^{-\Gamma\tau}]/2$  as the probability of measuring  $|\uparrow\rangle$  at the end of the sequence in the absence of a classically driven motion,  $\theta_{max}^2$  can be determined from a measurement of the difference  $\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck}$  through

$$F(\theta_{max}^2) = e^{\Gamma\tau} (\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck}) . \quad (5)$$

The standard deviation  $\delta\theta_{max}^2$  in estimating  $\theta_{max}^2$  is determined from the standard deviation  $\delta(\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck})$  of the  $\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck}$  difference measurements through

$$\delta\theta_{max}^2 = \frac{e^{\Gamma\tau} \delta(\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck})}{\frac{dF(\theta_{max}^2)}{d\theta_{max}^2}} . \quad (6)$$

The signal-to-noise ratio of a measurement of  $\theta_{max}^2$  (and therefore  $Z_c^2$ ) is then  $\theta_{max}^2/\delta\theta_{max}^2$ . In general this signal-to-noise ratio depends on  $\theta_{max}^2$  and the experimental parameters  $U \cdot \tau$  and  $\Gamma \cdot \tau$ .

We use Eq. (6) to theoretically estimate  $\theta_{max}^2/\delta\theta_{max}^2$  and the amplitude sensing limits. We assume the only sources of noise are projection noise in the measurement of the spin state and fluctuations in  $P_\uparrow$  due to the random variation in the relative phase of the 1D optical lattice and the driven COM motion. In this case  $\delta(\langle P_\uparrow \rangle - \langle P_\uparrow \rangle_{bck}) = \sqrt{\delta\langle P_\uparrow \rangle^2 + \delta\langle P_\uparrow \rangle_{bck}^2}$  where the relevant variances are

$$\delta\langle P_\uparrow \rangle_{bck}^2 = \frac{1}{N} \langle P_\uparrow \rangle_{bck} (1 - \langle P_\uparrow \rangle_{bck}) = \frac{1}{4N} (1 - e^{-2\Gamma\tau}) \quad (7)$$

and

$$\delta\langle P_\uparrow \rangle^2 = \sigma_\phi^2 + \frac{1}{N} \langle P_\uparrow \rangle (1 - \langle P_\uparrow \rangle) . \quad (8)$$

Here  $N$  is the number of spins. Equation (7) and the second term in Eq. (8) are projection noise. The variance

$$\sigma_\phi^2 = \langle P_\uparrow^2 - \langle P_\uparrow \rangle^2 \rangle = \frac{e^{-2\Gamma\tau}}{8} (1 + J_0(2\theta_{max}) - 2J_0(\theta_{max})^2) \quad (9)$$

is due to the random variation in the relative phase of the 1D optical lattice and the driven COM motion. For our set-up,  $DWF = 0.86$  and  $\delta k = 2\pi/(900 \text{ nm})$  are fixed, and the decoherence  $\Gamma$  is a function of  $U$ ,  $\Gamma = \xi(U/\hbar)$  where  $\xi = 1.156 \times 10^{-3}$ . For a given  $Z_c$  we use Eqs. (4) and (6)-(9) to find the optimum  $\theta_{max}^2/\delta\theta_{max}^2$  as a function of  $(U\tau)/\hbar$ . This optimum value is the theoretical curve plotted in Figure (amplitude sensing limits) of the main text.

One can show that  $\theta_{max}^2/\delta\theta_{max}^2$  is optimized for relatively small values of  $\theta_{max}^2$  where  $F(\theta_{max}^2) \approx \theta_{max}^2/8$  is a good approximation. This leads to some simplifications for Eqs. (5) and (6),

$$\theta_{max}^2 \approx 8e^{\Gamma\tau} (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}) \quad (10)$$

and

$$\delta\theta_{max}^2 \approx 8e^{\Gamma\tau} \delta (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}) , \quad (11)$$

and to the following estimate for the signal-to-noise ratio of a single measurement,

$$\frac{\theta_{max}^2}{\delta\theta_{max}^2} \approx \frac{\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}}{\delta (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck})} . \quad (12)$$

Figure (amplitude sensing limits) of the main text uses Eq. (12), along with repeated measurements of  $\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}$ , to experimentally determine the signal-to-noise ratio as a function of the amplitude  $Z_c$  of the COM motion.

Finally we use Eqs. (4) and (6)-(9) to calculate the sensing limits for very small  $Z_c$ . For small  $Z_c$  the variance  $\sigma_{\phi}^2$  can be neglected compared to projection noise and  $\delta \langle P_{\uparrow} \rangle^2 \approx \delta \langle P_{\uparrow} \rangle_{bck}^2$ . In this case we obtain the following expression for the signal-to-noise ratio,

$$\frac{\theta_{max}^2}{\delta\theta_{max}^2} = \frac{\sqrt{N} DWF^2 \cdot (\delta k Z_c)^2 (U\tau/\hbar)^2}{4\sqrt{2} \sqrt{e^{2\xi U\tau/\hbar} - 1}} . \quad (13)$$

Equation (13) is maximized for  $\xi U\tau \approx 1.9603$ . With  $DWF = 0.86$ ,  $\delta k = 2\pi/(900 \text{ nm})$ ,  $\xi = 1.156 \times 10^{-3}$ , and  $N = 100$ ,

$$\left. \frac{\theta_{max}^2}{\delta\theta_{max}^2} \right|_{optimum} = \left[ \frac{Z_c}{0.196 \text{ nm}} \right]^2 . \quad (14)$$

For our set-up and available ODF power,  $\xi U\tau/\hbar \approx 1.9603$  is realized for  $\tau \approx 20 \text{ ms}$ . A measurement of the signal and a measurement of the background requires  $\sim 60 \text{ ms}$  for 16 independent measurements of  $\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}$  in 1 s. The limiting sensitivity is approximately  $(100 \text{ pm})^2$  in a 1 s measurement time, or  $(100 \text{ pm})^2/\sqrt{\text{Hz}}$ . We note that the limiting sensitivity is determined by the ratio  $\xi = \Gamma/(U/\hbar)$ . In particular, the optimum value for Eq. (13) scales as  $1/\xi^2$ .

## Coherent sensing limits

With appropriate care the 1D optical lattice can be stable for long periods of time with respect to the ion trapping electrodes [Hume, PRL], enabling phase coherent sensing of a COM motion  $Z_c \cos(\omega t)$ . In this case the same spin precession  $\theta_{max} = DWF \cdot (U/\hbar) \cdot \delta k Z_c \cdot \tau$  occurs for each experimental trial, which can be detected to first order in  $\theta_{max}$  (or  $Z_c$ ) in a Ramsey sequence with a  $\pi/2$  phase shift between the two  $\pi$ -pulses. Assuming  $\sin(\theta_{max}) \approx \theta_{max}$ , appropriate for small amplitudes  $Z_c$ , the equivalent coherent sensing expressions for Eqs. (10) and (11) are

$$\theta_{max} = 2e^{\Gamma\tau} (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}) \quad (15)$$

and

$$\delta\theta_{max} = 2e^{\Gamma\tau} \delta (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}) . \quad (16)$$

For a Ramsey experiment with a  $\pi/2$  phase shift,  $\langle P_{\uparrow} \rangle_{bck} = 1/2$ . If projection noise is the only source of noise, then for small  $Z_c$ ,  $\delta \langle P_{\uparrow} \rangle^2 \approx \delta \langle P_{\uparrow} \rangle_{bck}^2 = \frac{1}{N} \cdot \frac{1}{2} \cdot \frac{1}{2}$  and  $\delta (\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}) \approx \frac{1}{\sqrt{2N}}$ . The limiting signal-to-noise ratio  $\theta_{max}/\delta\theta_{max}$  of a  $(\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck})$  measurement is

$$\frac{\theta_{max}}{\delta\theta_{max}} = DWF \cdot (\delta k Z_c) \cdot \sqrt{\frac{N}{2}} \cdot \frac{(U\tau)}{\hbar} e^{-\xi U\tau/\hbar} . \quad (17)$$

Equation (17) is maximized for  $\xi U\tau/\hbar = 1$ . With  $DWF = 0.86$ ,  $\delta k = 2\pi/(900 \text{ nm})$ ,  $\xi = 1.156 \times 10^{-3}$ , and  $N = 100$ ,

$$\left. \frac{\theta_{max}}{\delta\theta_{max}} \right|_{optimum} = \frac{Z_c}{0.074 \text{ nm}}. \quad (18)$$

With 16 independent measurements of  $\langle P_{\uparrow} \rangle - \langle P_{\uparrow} \rangle_{bck}$  in 1 s, this corresponds to a limiting sensitivity of  $\sim (20 \text{ pm})/\sqrt{\text{Hz}}$ . In particular the optimum value for the signal-to-ratio of Eq. (17) scales as  $1/\xi$ . Further, by employing spin-squeezed states that have been demonstrated in this system [Bohnet, Science 2016],  $\theta_{max}/\delta\theta_{max}$  can be improved by another factor of 2.

Employing this technique to sense motion resonance with the COM mode can lead to the detection of very weak forces and electric fields. The detection of a 20 pm amplitude resulting from a 5 ms coherent drive on the 1.57 MHz COM mode (corresponds to a  $Q \sim 10^4$ ) is sensitive to a force/ion of  $10^{-3}$  yN corresponding to an electric field of 7 nV/m.

---

\* kevin.gilmore@colorado.edu