RF / REV A ENGINEERING PROTOTYPE

POWER / REV A ENGINEERING PROTOTYPE

SENSE / REV A ENGINEERING PROTOTYPE

BLE / REV A ENGINEERING PROTOTYPE

RF_IN
J1

DNP tune
C1

68n tune / 868MHz
L1

100p COG
C2

SMS7630-079LF
D1

SMS7630-079LF
D2

100p COG
C3

4.7u 10V
C4

BQ25504
U1

22u isat>=300mA
L2

4.7u 10V
C5

10n COG
C6

10M
R1

10M
R2

5.62M 0.1%
R3

4.22M 0.1%
R4

5.62M 0.1%
R5

4.42M 0.1%
R6

4.12M 0.1%
R7

4.12M 0.1%
R8

1.65M 0.1%
R9

220u 6.3V X5R
C10

220u 6.3V X5R
C11

220u 6.3V X5R
C12

220u 6.3V X5R
C13

220u 6.3V X5R
C14

220u 6.3V X5R
C15

220u 6.3V X5R
C16

220u 6.3V X5R
C17

1k
R10

10u 6.3V
C7

100n
C8

PRECHARGE 3.0V
J3

RECT
TP1

VSTOR
TP2

POWER_OK
TP3

VDD
TP4

GND
TP5

TPS22917DBV
U2

ADXL362BCCZ
U3

10R
R11

100n
C20

100n
C21

1M
R12

MDBT50Q-1MV2
U4

10u 6.3V
C22

100n
C23

SWD / VTREF
J2

RF matching values provisional. See README and design.json. BLE data link: AMP-powered architecture, no 802.11bp conformance claim.

Sheet: /	
File: amp_sensor.kicad_sch	
Title:	
Size: A2	Date:
KiCad E.D.A. kicad-cli 7.0.11+dfsg-1build4	**Rev:** Id: 1/1