

feature	prerequisites	test case	procedure	data	expected result	actual result	status	comments
Track Shipment API	Server is running	Verify successful tracking with valid Tracking ID and Password	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter valid Tracking ID and Password	{ "password": "1", "trackingId": "1" }	All shipment stages should be returned successfully	All shipment stages are returned successfully	pass	
	Server is running	Verify tracking fails with invalid Tracking ID	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter invalid Tracking ID and valid Password	{ "password": "1", "trackingId": "9999" }	Status code 401 (Unauthorized) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; The shipment was not returned.	pass	
	Server is running	Verify tracking fails with invalid Password	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter valid Tracking ID and invalid Password	{ "password": "9999", "trackingId": "1" }	Status code 401 (Unauthorized) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; The shipment was not returned.	pass	
	Server is running	Verify tracking fails when Tracking ID is empty	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Keep Tracking ID empty and enter valid Password	{ "password": "1", "trackingId": "" }	Status code 401 (Unauthorized) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; The shipment was not returned.	pass	
	Server is running	Verify tracking fails when password is empty	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter valid Tracking ID and keep Password empty	{ "password": "", "trackingId": "1" }	Status code 401 (Unauthorized) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; shipments must not be returned.	pass	
	Server is running	Verify tracking fails when Tracking ID field is missing	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter the password	{ "password": "1", "trackingId": "" }	Status code 400 (Bad Request) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; shipments must not be returned.	fail	This is Bug
	Server is running	Verify tracking fails when password field is missing	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/track" 4.Enter the Tracking ID	{ "trackingId": "1" }	Status code 400 (Bad Request) must be returned; shipments must not be returned.	Status code 401 (Unauthorized) was returned; shipments must not be returned.	fail	This is Bug
Update	Server is running	Verify stage can be updated to Done	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "1" }	Stage status should be updated to done successfully and the status code should be 200 (OK)	Stage status updated to done successfully and the status code is 200 (OK)	pass	
	Server is running	Verify stage can be updated to Pending	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "pending", "trackingId": "1" }	Stage status should be updated to pending successfully and the status code should be 200 (OK)	Stage status updated to pending successfully and the status code is 200 (OK)	pass	
	Server is running	Verify stage can be updated to Rejected with valid reason	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "test", "stageIndex": 1, "status": "rejected", "trackingId": "1" }	Stage status should be updated to rejected successfully and the status code should be 200 (OK)	Stage status updated to rejected successfully and the status code is 200 (OK)	pass	
	Server is running	Verify update fails with invalid Tracking ID	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "9999" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	The stage status was not updated successfully, and the status code is 401 (Unauthorized).	fail	This is Bug
	Server is running	Verify update fails when Tracking ID is empty	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	The stage status was not updated successfully, and the status code is 401 (Unauthorized).	fail	This is Bug
	Server is running	Verify update fails when Tracking ID is missing	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	The stage status was not updated successfully, and the status code is 401 (Unauthorized).	fail	This is Bug
	Server is running	Verify update fails with invalid Stage Index	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 300, "status": "done", "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	The stage status was not updated successfully, and the status code is 500 (Internal Server Error).	fail	This is Bug
	Server is running	Verify update fails when Stage Index is missing	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "status": "done", "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	The stage status was not updated successfully, and the status code is 500 (Internal Server Error).	fail	This is Bug
	Server is running	Verify update fails with invalid Status	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "test", "stageIndex": 1, "status": "inprogress", "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	Stage status updated to rejected successfully and the status code is 200 (OK)	fail	This is Bug

	Server is running	Verify update fails when Status is missing	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "test", "stageIndex": 1, "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	Stage status updated to rejected successfully and the status code is 200 (OK)	fail	This is Bug
	Server is running	Verify rejected stage requires rejection reason	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "rejected", "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	Stage status updated to rejected successfully and the status code is 200 (OK)	fail	This is Bug
	Server is running	Verify Stage 2 cannot be updated before Stage 1 is completed	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "1" }	The stage status must not be successfully updated, and the status code must be 400 (Bad Request).	Stage status updated to rejected successfully and the status code is 200 (OK)	fail	This is Bug
	Server is running	Verify Stage 2 can be updated after Stage 1 is completed	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "1" }	Stage status should be updated to rejected successfully and the status code must be 200 (OK)	Stage status updated to rejected successfully and the status code is 200 (OK)	pass	
	Server is running	Verify rejected stage can be changed to Pending	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "pending", "trackingId": "1" }	Stage status should be updated to rejected successfully and the status code must be 200 (OK)	Stage status updated to rejected successfully and the status code is 200 (OK)	pass	
	Server is running	Verify rejected stage can be changed to Done	1.Open Postman 2.Set the method to POST 3.Put the endpoint "http://localhost:3000/update"	{ "cause": "", "stageIndex": 1, "status": "done", "trackingId": "1" }	Stage status should be updated to rejected successfully and the status code must be 200 (OK)	Stage status updated to rejected successfully and the status code is 200 (OK)	pass	