

## MCQ

1 What will be the output of the following code snippet?

```
def func(a, b): return b if a == 0 else  
func(b % a, a) print(func(30, 75))
```

- a) 10
- b) 20
- c) 15
- d) 0

**Ans : (c) 15**

2 **.numbers = (4, 7, 19, 2, 89, 45, 72, 22) sorted\_numbers =**  
**sorted(numbers) even = lambda a: a % 2 == 0 even\_numbers =**  
**filter(even, sorted\_numbers) print(type(even\_numbers))**

- a) Int
- b) Filter
- c) List
- d) Tuple

**Ans: (b) Filter**

3) As what datatype are the \*args stored, when passed into

- a) Tuple
- b) List
- c) Dictionary
- d) none

**Ans : (a) tuple**

4) `set1 = {14, 3, 55} set2 = {82, 49, 62} set3={99,22,17} print(len(set1 + set2 + set3))`

- a) 105
- b) 270
- c) 0
- d) Error

Ans : (d) error

5) What keyword is used in Python to raise exceptions?

- a) raise
- b) try
- c) goto
- d) except

Ans: (a) raise

6) Which of the following modules need to be imported to handle date time computations in Python?

- a) timdate
- b) date
- c) datetime
- d) time

Ans: (c) datetime

7) What will be the output of the following code snippet?

`print(4**3 + (7 + 5)**(1 + 1))`

- a) 248
- b) 169
- c) 208
- d) 233

Ans: (c) 208

8) Which of the following functions converts date to corresponding time in Python?

- a) strptime
- b) strftime
- c) both a) and b)
- d) None

Ans : (c) both

9) The python tuple is \_\_\_\_\_ in nature.

- a) mutable
- b) immutable
- c) unchangeable
- d) none

Ans: (b) immutable

10)

The \_\_\_\_ is a built-in function that returns a range object that consists series of integer numbers, which we can iterate using a for loop.

- A. range()
- B. set()
- C. dictionary{ }
- D. None of the mentioned above

Ans: (a) range

### Question 11

Amongst which of the following is a function which does not have any name?

- A. Del function
- B. Show function
- C. Lambda function
- D. None of the mentioned above

Ans: (c) lambda function

Question 12

**The module Pickle is used to \_\_\_\_.**

- A. Serializing Python object structure
- B. De-serializing Python object structure
- C. Both A and B
- D. None of the mentioned above

Ans : (c) both

Question 13

**Amongst which of the following is / are the method of convert Python objects for writing data in a binary file?**

- A. set() method
- B. dump() method
- C. load() method
- D. None of the mentioned above

Ans: (b) dump method

14

**Amongst which of the following is / are the method used to unpickling data from a binary file?**

- A. load()
- B. set() method
- C. dump() method
- D. None of the mentioned above

Ans : (a) load

**15. A text file contains only textual information consisting of \_\_\_\_.**

- A. Alphabets
- B. Numbers
- C. Special symbols
- D. All of the mentioned above

Ans; (d) All of the mentioned above

16 . Which Python code could replace the ellipsis (...) below to get the following output? (Select all that apply.)

```
captains = {  
    "Enterprise": "Picard",  
    "Voyager": "Janeway",  
    "Defiant": "Sisko",  
}
```

Enterprise Picard,

Voyager Janeway

Defiant Sisko

- a) for ship, captain in captains.items():  
    print(ship, captain)
- b) for ship in captains:  
    print(ship, captains[ship])
- c) both a and b

Ans : (a)

17.

Which of the following lines of code will create an empty dictionary named captains ?

- a) captains = {}
- b) type(captains)
- c) captains.dict()
- d) captains = { }

Ans: (a)

**18)** Now you have your empty dictionary named `captains`. It's time to add some data!

Specifically, you want to add the key-value pairs `"Enterprise": "Picard"`, `"Voyager": "Janeway"`, and `"Defiant": "Sisko"`.

Which of the following code snippets will successfully add these key-value pairs to the existing `captains` dictionary?

a) `captains{"Enterprise" = "Picard"} captains{"Voyager" = "Janeway"}`  
`captains{"Defiant" = "Sisko"}`

b) `captains["Enterprise"] = "Picard" captains["Voyager"] = "Janeway"`  
`captains["Defiant"] = "Sisko"`

c) `captains = {`  
`"Enterprise": "Picard",`  
`"Voyager": "Janeway",`  
`"Defiant": "Sisko",`  
`}`

d) None of the above

Ans: (c)

**19 )** You're really building out the Federation Starfleet now! Here's what you have:

```
captains = {  
    "Enterprise": "Picard",  
    "Voyager": "Janeway",  
    "Defiant": "Sisko",  
    "Discovery": "unknown",
```

}Now, say you want to display the ship and captain names contained in the dictionary, but you also want to provide some additional context. How could you do it?

a) for item in captains.items():

```
    print(f"The [ship] is captained by [captain].")
```

b) for ship, captain in captains.items():

```
    print(f"The {ship} is captained by {captain}.")
```

c) for captain, ship in captains.items():

```
    print(f"The {ship} is captained by {captain}.")
```

d) All are correct

Ans : (d)

20 )

You've created a dictionary, added data, checked for the existence of keys, and iterated over it with a for loop. Now you're ready to delete a key from this dictionary:

```
captains = {  
    "Enterprise": "Picard",  
    "Voyager": "Janeway",  
    "Defiant": "Sisko",  
    "Discovery": "unknown",  
}
```

What statement will remove the entry for the key "Discovery"?

- a) del captains
- b) captains.remove()
- c) del captains["Discovery"]
- d) captains["Discovery"].pop()

Ans : (c)