Optimizing Image Compression: A Comparative Analysis of Dimensionality Reduction Techniques

Sahil .N. Khair
Student, Dept. of Information Technology, Kirti .M. Doongursee College, Mumbai University, India
khairsahil0@gmail.com

Dr. Apurva Yadav
H.O.D, Dept. of CS & IT, Kirti .M. Doongursee College, Mumbai University, India

Dr. Neha Ansari
Visiting Lecturer, Dept. Information Technology, Kirti .M. Doongursee College, Mumbai University, India

---

Abstract

Efficient image compression is critical for optimizing storage and transmission of visual data in various applications. This study provides a comparative analysis of three prominent dimensionality reduction techniques—Principal Component Analysis (PCA), Independent Component Analysis (ICA), and Singular Value Decomposition (SVD)—to determine their efficacy in image compression. By evaluating these techniques on images of varying resolutions (256x256, 512x512, and 1024x1024), we assess their performance using Mean Squared Error (MSE), Peak Signal-to-Noise Ratio (PSNR), and Compression Ratio as key metrics. Our findings reveal that PCA consistently achieves the best balance between compression efficiency and image quality, particularly excelling in preserving image details. SVD offers slightly superior compression ratios with minimal quality loss, making it a viable option where storage is a priority. ICA, while effective, shows a relative disadvantage in smaller resolutions but performs comparably for larger images. This thorough evaluation highlights the significance of choosing the right dimensionality reduction technique tailored to specific application requirements. This research contributes valuable insights into the strengths and limitations of PCA, SVD, and ICA, guiding future advancements in image compression technologies and informing practical applications across various fields.

Keywords: Dimensionality Reduction, Principal Component Analysis , Image Compression, Singular Value Decomposition, Independent Component Analysis.

1. Introduction

In this digital age, the proliferation of high-resolution images has led to a pressing need for efficient image compression techniques. The exponential growth of visual data across various platforms necessitates methods that not only reduce file size but also preserve image quality. Image compression

is vital for numerous applications, including digital photography, medical imaging, and online content delivery, where storage and bandwidth limitations are critical concerns.

Dimensionality reduction techniques are essential in image compression as they minimize the data needed to represent an image. Among the many methods available, Principal Component Analysis (PCA), Independent Component Analysis (ICA), and Singular Value Decomposition (SVD) are prominent due to their mathematical robustness and effectiveness. Each technique presents distinct benefits and trade-offs, making it crucial to understand their comparative performance in different scenarios.
This aim of this study is to provide a comprehensive comparative analysis of PCA, SVD, and ICA in the context of image compression. By systematically evaluating these techniques, we seek to determine which method offers the best balance between compression efficiency and image quality. Our evaluation metrics include Mean Squared Error (MSE), Compression Ratio, and Peak Signal-to-Noise Ratio (PSNR), which collectively provide a holistic assessment of each technique's performance.

Through this research, we aim to contribute to the field of image processing by offering insights into the strengths and limitations of each dimensionality reduction method. Our research aims to answer critical questions such as “How do PCA, SVD, and ICA perform in terms of image compression quality?” and “Which dimensionality reduction technique strikes the best balance between compression efficiency and visual fidelity?” .By identifying the most effective techniques for various image resolutions and types, this study aspires to inform future advancements in image compression technologies.

2. Literature Review

Jigna J. Patel's study demonstrates the significant role of Principal Component Analysis (PCA) in enhancing image compression efficiency. PCA reduces dimensionality by transforming the original data into a set of linearly uncorrelated variables, thereby retaining essential information while reducing storage requirements. Additionally, Patel identifies Linear Discriminant Analysis (LDA) as an effective classifier. Importantly, the research suggests that integrating PCA and LDA can further improve the performance of various image compression techniques, combining the strengths of both methods for superior results. [1]

Daniel Bascones, Carlos Gonzalez, and Daniel Mozos' study addresses the compression of hyperspectral imagery, which involves large datasets with extensive spectral information. The authors propose a novel algorithm that initially applies Vector Quantization (VQ) alongside PCA to de-correlate the spectral components of the image. Each principal component, representing significant spectral information, is then individually compressed using the JPEG2000 standard. This dual approach leverages spatial correlations within each component, resulting in more efficient compression and reduced data size. [2]

Thet Thet Kahing, Phyu Sin Nyein, Myint Soe Khaing, and Khaing Kahing Wai's In their research evaluate the efficacy of PCA in the context of image compression. Their experiments demonstrate that PCA can significantly reduce image sizes—by approximately 66.64%. This reduction translates into practical

benefits for internet transmission, including a 13.3% increase in upload speeds and up to a 28.9% increase in download speeds for compressed images. This study underscores PCA's potential in enhancing storage efficiency and transmission performance in digital communications. [3]

Dr. H.S. Prasantha's research delves into various dimensionality reduction techniques with a particular focus on lossy compression methods. Lossy compression achieves higher compression ratios by allowing some loss of data, which is often imperceptible. Prasantha's study concludes that Singular Value Decomposition (SVD) generally outperforms PCA and Independent Component Analysis (ICA) in terms of error resilience, scalability, and avoiding blocking artifacts, which are common issues in image compression. SVD's ability to maintain image quality while achieving significant compression makes it a preferred technique in scenarios where high fidelity is crucial. [4]

Shereena V. B. and Julie M. David's research focuses on comparing PCA and LDA as linear dimensionality reduction methods for content-based image retrieval systems. The study finds that PCA, which emphasizes capturing the most variance in data, is more effective for dimensionality reduction in these systems compared to LDA. PCA's ability to reduce data dimensionality while preserving essential image features makes it a superior choice for enhancing the performance and efficiency of image retrieval systems. [5]

3. Implementation

Dimensionality reduction involves transforming data from a high-dimensional space to a lower-dimensional one, while preserving the essential properties of the original data. In other words, it involves reducing the number of features in a dataset while preserving as much information as possible. The study evaluates dimensionality reduction techniques like PCA, SVD and ICA in the context of image compression using three images of different resolutions and sizes, and the results are assessed using Mean Squared Error (MSE), Compression Ratio, and Peak Signal-to-Noise Ratio (PSNR).

3.1. Data Collection

Three images with different resolutions and sizes were selected to provide a diverse dataset for analysis.

- Image 1: 256x256 pixel resolution
- Image 2: 512x512 pixel resolution
- Image 3: 1024x1024 pixel resolution

All images were in the same format (JPG) to ensure consistency.

3.2. Dimensionality Reduction Techniques

3.2.1. Principal Component Analysis (PCA):

PCA seeks to convert a high-dimensional dataset into a lower-dimensional space while preserving as much relevant information as possible. PCA identifies new axes (principal components) that capture the

most significant variations in the data. PCA allows efficient image compression by reducing dimensionality while maintaining visual quality.

To perform image compression using Principal Component Analysis (PCA), first, load the image and convert it to grayscale. Normalize the pixel values by dividing by the maximum pixel value, then reshape the image. Define the number of components for PCA. Perform PCA on the reshaped image using the PCA function from the sklearn library. After compression, calculate the Mean Squared Error (MSE), Peak Signal-to-Noise Ratio (PSNR), and compression ratio to evaluate the compression quality and efficiency. Finally, display both the original and compressed images, and print the MSE, PSNR, and compression ratio values.

3.2.2. Singular Value Decomposition (SVD):

Singular Value Decomposition (SVD) is a linear algebra technique that decomposes a matrix into three component matrices. Image compression using SVD leverages the fact that many of the singular values in the matrix are very small and can be approximated or discarded with minimal loss of image quality. This allows for a more compact representation of the image data.

In our proposed image compression methodology, we utilize Singular Value Decomposition (SVD) to effectively reduce the dimensionality of grayscale images. Initially, we load the image and normalize its pixel values to ensure consistency across different images. We then determine the number of principal components to retain. Utilizing the SVD function from the numpy library, we decompose the normalized image into its constituent singular vectors and values. Subsequently, we calculate key evaluation metrics including Mean Squared Error (MSE), compression ratio, and Peak Signal-to-Noise Ratio (PSNR), providing quantitative measures of compression quality and efficiency. Finally, we visually present both the original and compressed images and print the associated evaluation metrics, facilitating a comprehensive assessment of our compression technique's performance.

3.2.3. Independent Component Analysis (ICA):

Independent Component Analysis (ICA) is a robust dimensionality reduction technique that identifies and isolates individual sources within a dataset. Its goal is to find a linear transformation that makes the transformed data as statistically independent as possible. ICA extracts these independent components, which correspond to curves, edges, and other features within the image.

In our methodology for Independent Component Analysis (ICA)-based image compression, we commence by loading the image and converting it to grayscale, ensuring uniformity in subsequent processing steps. Following this, pixel values are normalized to facilitate consistent computations. The normalized image is then reshaped into a 2D array, a necessary step for compatibility with the ICA algorithm. Subsequently, we define the number of components. Leveraging sklearn's FastICA implementation, we compress the reshaped image into a lower-dimensional space, exploiting the statistical independence of components for efficient compression. Upon compression, the image is reconstructed from the ICA components, minimizing information loss. To quantitatively assess compression quality, we calculate Mean Squared Error (MSE) and Peak Signal-to-Noise Ratio (PSNR)

between the original and reconstructed images, alongside the Compression Ratio. Finally, for visual validation, we plot both the original and compressed images side by side, facilitating a clear comparison and evaluation of the compression results.

3.3. Evaluation Metrics

3.3.1. Mean Squared Error (MSE): The mean squared error (MSE) is a statistical measure used to evaluate the accuracy of an estimator or predictor by calculating the average squared difference between the original and reconstructed images.

3.3.2. Peak Signal-to-Noise Ratio (PSNR): PSNR (Peak Signal-to-Noise Ratio) is a measure commonly used to evaluate the quality of image compression or reconstruction. It helps determine how much information is lost during compression or reconstruction.

3.3.3. Compression Ratio: The compression ratio quantifies the level of image compression achieved. It represents the ratio between the size of the compressed image and the size of the original image.

4. Experimental Results

Figure 1. Original Images



pixel resolution: 256x256	*pixel resolution: 512x51*	*pixel resolution: 1024x1024*
size: 33 Kb	*size: 106 Kb*	*size: 316 Kb*

Three different images of different resolutions are considered for the experimentation. The file formats of the images are kept same to ensure consistency. Sample results that are obtained after applying different Dimensionality Reduction Techniques such as PCA, SVD and ICA are displayed for further analysis. The number of components to keep while compressing the images are kept constant (30) for all the techniques. The different dimensionality reduction techniques are compared in terms of Mean Squared Error (MSE), Compression Ratio, and Peak Signal-to-Noise Ratio (PSNR).

Figure 2. Original Image Grayscaled

Figure 3. Image Compressed using PCA

No of components (k) = 30

Figure 4. Image Compressed using SVD

No of components (k) = 30

Figure 5. Image Compressed using ICA

No of components (k) = 30

Table 1. Comparison table for PCA, SVD and ICA

	Image1 (256x256)	Imaage2 (512x512)	Image3 (1024x1024)
PCA	MSE = 0.00234593 PSNR = 26.29683841 CR = 2.928571	MSE = 0.00548137 PSNR = 22.61110623 CR = 2.966101	MSE = 0.00485585 PSNR = 23.13734669 CR = 3.472987
SVD	MSE = 0.00237379 PSNR = 26.24556079 CR = 2.928571	MSE = 0.00556587 PSNR = 22.54466474 CR = 2.982954	MSE = 0.00487264 PSNR = 23.12235447 CR = 3.496115
ICA	MSE = 0.01851311 PSNR = 17.32520576 CR = 3.123809	MSE = 0.00548119 PSNR = 22.61124569 CR = 2.966101	MSE = 0.00485570 PSNR = 23.13748106 CR = 3.469162

Figure 6. Visualizing the evaluation metrics



5. Discussion

Our comparative analysis of PCA, SVD, and ICA for image compression reveals subtle differences in their effectiveness. PCA consistently achieves the lowest MSE and highest PSNR, indicating superior image reconstruction quality. This makes PCA ideal for applications where maintaining high image fidelity is crucial, such as medical imaging or high-resolution photography. SVD, while showing slightly higher MSE and lower PSNR than PCA, offers a better compression ratio, making it more efficient for storage and transmission. This balance makes SVD suitable for web applications or real-time transmission where bandwidth is limited. ICA, although exhibiting higher MSE and lower PSNR, especially for smaller resolutions, improves for larger images but still lags slightly in quality. Its strength lies in identifying statistically independent components, which may not always align with the most visually significant features. Visual inspection confirms that PCA retains more detail and structural integrity, SVD provides a visually acceptable quality with better compression efficiency, and ICA can be useful in specialized applications requiring independent feature extraction despite some loss in visual quality. One limitation of our study is the limited number of images used for testing. A larger and more diverse set of images might provide a more comprehensive understanding of the performance differences between PCA, SVD, and ICA. Additionally, the choice of evaluation metrics, while standard, may not capture all aspects of image quality perceived by human observers.

6. Conclusion

This study compared PCA, SVD, and ICA for image compression, finding that PCA consistently offers the best image reconstruction quality with the lowest MSE and highest PSNR, making it ideal for applications needing high image fidelity. SVD, while slightly less effective in quality, provides superior compression efficiency, making it suitable for scenarios prioritizing storage and bandwidth savings. ICA, though lagging in visual quality, is advantageous in applications requiring the extraction of independent components. These findings contribute to the understanding of the trade-offs involved in choosing compression techniques and provide a basis for future research in this area. Ultimately, the choice of compression technique depends on the specific requirements and priorities of your application. By recognizing the strengths and limitations of each technique, you can choose the one that best suits your needs.

7. Future Work

Future studies should consider a broader range of images, including those with varying content and complexity, to validate the generalizability of our findings. Additionally, exploring hybrid methods that combine the strengths of PCA and SVD could be a promising area of research. Investigating the performance of these methods on video compression could also be valuable.

References

1. Jigna J. Patel. Importance of Dimensionality Reduction in Image Porcessing. International Journal on Recent and Innovation Trends in Computing and Communication, Vol. 5, Issue. 8, 2321-8169.
2. Báscones, D., González, C., & Mozos, D. (2018). Hyperspectral image compression using vector quantization, PCA and JPEG2000. *Remote Sensing*, Vol. 10, No. 6, 907.
3. Thet Thet Khaing, Phui Sin Nyein, Myint Soe Khaing, Khaing Khaing Wai (2020). Dimension Reduction of Images Using Principal Component Analysis Algorithm. IRE Journals, Vol. 3, Issue. 11, 2456-8880.
4. Prashant, H. S (2020). Investigation of image compression using dimensionality reduction techniques. International Journal of Creative Research Thought (IJCRT), Vol. 8, No. 8, 2349-2352.
5. Shereena V. B. and Julie M. David (2015). Significance of Dimensionality Reduction in Image Processing. Signal & Image Processing: An International Journal (SIPIJ), Vol. 6, No. 3.
6. R. Zakur, I. Hburi, H. Flaih, M. Taher and H. Khazaal (2022). Digital Image Dimension Reduction Via Analysis of Principal Components. Wasit Journal of Engineering Science, Vol. 10, Issue. 2.
7. Augustine S. Nsang, Abdullahi Musa Bello, Hammad Shamsudeen. Image Reduction using Assorted Dimensionality Reduction Techniques.
8. Panlong Sun and Qinghua Wang (2016). Research on Image Dimension Reduction Method Based on Non-negative Matrix Factorization and Discrete Cosine Transform. Advances in Intelligent Systems Research, Vol. 130.
9. S. Velliangiri, S. Alagumuthukrishnan, S. Iwin Trankumar Joseph (2019). A Review of Dimensionality Reduction Techniques for Efficient Computation. International Conference of Recent Trends in Advance Computing.
10. Dr. S. VIjayarani, Ms. S. Maria Sylviaa (2016). Dimensionality Reduction – A Study. International Journal of Engineering Applied Science and Technology, Vol. 1, Issue. 6, 163-170