

**BALCOMM LIMITED**

Commissioning, Ductwork Cleaning  
& Water Treatment

**Grilling Balance Test Record**

<b>Project:</b> 1234	<b>Ref:</b> test
<b>System:</b> Test1	<b>Sheet:</b> 1 of 3

Design Information					Measured				
Grille No.	Grille or Hood Size (mm)	Area m <sup>2</sup>	Design Volume m <sup>3</sup> /s	Design Velocity m/s	Final Velocity m/s	Measured Volume m <sup>3</sup> /s	Correction Factor	Actual Volume m <sup>3</sup> /s	Design %
dasd	dasdas	34	45.000	1.32	67.00	2278.000	0.00	0.000	0.000

The measuring hood correction factor is derived by dividing the duct	Duct Total m <sup>3</sup> /s:	0.000
Pitot traverse volume by the total of the grille indicated volume	Hood/Grille Total:	2278.000
	Correction Factor:	0.00

<b>Comments:</b> this is test
----------------------------------

<b>Engineer:</b> Elgin Thomas	<b>Date:</b> 23 Nov, 2017
-------------------------------	---------------------------

**BALCOMM LIMITED**Commissioning, Ductwork Cleaning  
& Water Treatment**Grilling Balance Test Record**

<b>Project:</b> 1234	<b>Ref:</b> test
<b>System:</b> Test1	<b>Sheet:</b> 2 of 3

Design Information					Measured				
Grille No.	Grille or Hood Size (mm)	Area m <sup>2</sup>	Design Volume m <sup>3</sup> /s	Design Velocity m/s	Final Velocity m/s	Measured Volume m <sup>3</sup> /s	Correction Factor	Actual Volume m <sup>3</sup> /s	Design %
testr	sd	sdsd	0.000	0.00	0.00	0.000	0.00	0.000	0.000

The measuring hood correction factor is derived by dividing the duct	Duct Total m <sup>3</sup> /s:	0.000
Pitot traverse volume by the total of the grille indicated volume	Hood/Grille Total:	0.000
	Correction Factor:	0.00

<b>Comments:</b>
------------------

<b>Engineer:</b> Elgin Thomas	<b>Date:</b> 23 Nov, 2017
-------------------------------	---------------------------

**BALCOMM LIMITED**Commissioning, Ductwork Cleaning  
& Water Treatment**Grilling Balance Test Record**

<b>Project:</b> 1234	<b>Ref:</b> RAJJJ
<b>System:</b> Test1	<b>Sheet:</b> 3 of 3

Design Information					Measured				
Grille No.	Grille or Hood Size (mm)	Area m <sup>2</sup>	Design Volume m <sup>3</sup> /s	Design Velocity m/s	Final Velocity m/s	Measured Volume m <sup>3</sup> /s	Correction Factor	Actual Volume m <sup>3</sup> /s	Design %
raj	raj	raj	3.000	0.00	3.00	0.000	0.00	0.000	0.000

The measuring hood correction factor is derived by dividing the duct	Duct Total m <sup>3</sup> /s:	3.000
Pitot traverse volume by the total of the grille indicated volume	Hood/Grille Total:	0.000
	Correction Factor:	0.00

<b>Comments:</b> raj
-------------------------

<b>Engineer:</b> Elgin Thomas	<b>Date:</b> 23 Nov, 2017
-------------------------------	---------------------------