

# Longest Substring with K Distinct Characters (medium)

We'll cover the following ^

- Problem Statement
- Try it yourself
- Solution
- Code
  - Time Complexity
  - Space Complexity

## Problem Statement #

Given a string, find the length of the **longest substring** in it **with no more than K distinct characters**.

### Example 1:

Input: String="araaci", K=2

Output: 4

Explanation: The longest substring with no more than '2' distinct characters is "araa".

## Example 2:



Input: String="araaci", K=1

Output: 2

Explanation: The longest substring with no more than '1' distinct characters is "aa".

## Example 3:

Input: String="cbbabi", K=3

Output: 5

Explanation: The longest substrings with no more than '3' distinct characters are "cbbab" & "bbabi".

## Try it yourself #

Try solving this question here:

Java	Python3	JS	C++	
<pre>3 class LongestSubstringKDistinct { 4     public static int findLength(String str, int k) { 5         // TODO: Write your code here 6         int windowstart=0; 7         int n=str.length(); 8         char key=' '; 9         int max=0; 10        HashMap&lt;Character,Integer&gt; h=new HashMap&lt;&gt;(); 11        for(int windowend=0;windowend&lt;n;windowend++) 12            { 13                key=str.charAt(windowend); 14                if(h.containsKey(key)) 15                    {</pre>				

```
16         h.put(key,h.get(key)+1);
17     }
18     else
19         h.put(key,1);
20
21     if(h.size()>k)
22     {
23         if(h.containsKey(str.charAt(windowstart)))
24         {
25             h.put(str.charAt(windowstart),h.get(str
26         }
27         if(h.get(str.charAt(windowstart))==0)
28             h.remove(str.charAt(windowstart));
29         windowstart++;
30     }
31     max=Math.max(max>windowend-windowstart+1);
32 }
33 return max;
```



Show Results

Show Console



3 of 3 Tests Passed

Result	Input	Expected Output	Actual Output	Reason
✓	findLength(araaci, 2)	4	4	Succeeded
✓	findLength(araaci, 1)	2	2	Succeeded
✓	findLength(cbbebi, 3)	5	5	Succeeded

2.870s



## Solution #



This problem follows the **Sliding Window** pattern, and we can use a similar dynamic sliding window strategy as discussed in Smallest Subarray with a given sum


(<https://www.educative.io/collection/page/5668639101419520/5671464854355968/5177043027230720/>).

We can use a **HashMap** to remember the frequency of each character we have processed. Here is how we will solve this problem:


1. First, we will insert characters from the beginning of the string until we have 'K' distinct characters in the **HashMap**.
2. These characters will constitute our sliding window. We are asked to find the longest such window having no more than 'K' distinct characters. We will remember the length of this window as the longest window so far.
3. After this, we will keep adding one character in the sliding window (i.e., slide the window ahead) in a stepwise fashion.
4. In each step, we will try to shrink the window from the beginning if the count of distinct characters in the **HashMap** is larger than 'K.' We will shrink the window until we have no more than 'K' distinct characters in the **HashMap**. This is needed as we intend to find the longest window.
5. While shrinking, we'll decrement the character's frequency going out of the window and remove it from the **HashMap** if its frequency becomes zero.
6. At the end of each step, we'll check if the current window length is the longest so far, and if so, remember its length.

Here is the visual representation of this algorithm for the Example-1:






Max Length = 4




Number of distinct characters &gt; 2, let's shrink the sliding window




Number of distinct characters are still &gt; 2, let's shrink the sliding window

Max Length = 4





Max Length = 4



Number of distinct character &gt; 2, let's shrink the sliding window

Max Length = 4






## Code #

Here is how our algorithm will look:

Java	Python3	C++	JS
<pre>3 class LongestSubstringKDistinct { 4     public static int findLength(String str, int k) { 5         if (str == null    str.length() == 0    str.length() 6             throw new IllegalArgumentException(); 7 8         int windowStart = 0, maxLength = 0; 9         Map&lt;Character, Integer&gt; charFrequencyMap = new HashM 10        // in the following loop we'll try to extend the rang 11        for (int windowEnd = 0; windowEnd &lt; str.length(); wir 12            char rightChar = str.charAt(windowEnd); 13            charFrequencyMap.put(rightChar, charFrequencyMap.ge 14            // shrink the sliding window, until we are left wi 15            while (charFrequencyMap.size() &gt; k) { 16                char leftChar = str.charAt(windowStart); 17                charFrequencyMap.put(leftChar, charFrequencyMap. 18                if (charFrequencyMap.get(leftChar) == 0) { 19                    charFrequencyMap.remove(leftChar); 20                } 21                windowStart++; // shrink the window 22            } 23            maxLength = Math.max(maxLength, windowEnd - window 24        } 25 26        return maxLength; 27    } 28 29    public static void main(String[] args) { 30        System.out.println("Length of the longest substring: 31        System.out.println("Length of the longest substring:</pre>			

```
32     System.out.println("Length of the longest substring:");
33 }
```



Output

1.502s

Length of the longest substring: 4  
Length of the longest substring: 2  
Length of the longest substring: 5

### Time Complexity #

The above algorithm's time complexity will be  $O(N)$ , where 'N' is the number of characters in the input string. The outer `for` loop runs for all characters, and the inner `while` loop processes each character only once; therefore, the time complexity of the algorithm will be  $O(N + N)$ , which is asymptotically equivalent to  $O(N)$ .

### Space Complexity #

The algorithm's space complexity is  $O(K)$ , as we will be storing a maximum of 'K+1' characters in the HashMap.

[← Back](#)[Next →](#)[Smallest Subarray with a given sum \(e...](#)[Fruits into Baskets \(medium\)](#)





3% completed, meet the criteria and claim your course certificate!

**Claim Certificate**



Report an  
Issue



Ask a Question

([https://discuss.educative.io/tag/longest-substring-with-k-distinct-characters-medium\\_\\_pattern-sliding-window\\_\\_grokking-the-coding-interview-patterns-for-coding-questions](https://discuss.educative.io/tag/longest-substring-with-k-distinct-characters-medium__pattern-sliding-window__grokking-the-coding-interview-patterns-for-coding-questions))