ZOMATO DATASET ANALYSIS

Alfido Tech Internship — Task 1 | Author: Shubham Khakale | Third Year Engineering — Information Technology (TE IT)

Project Overview

This project explores restaurant records from a Zomato dataset using Python. The analysis focuses on ratings, restaurant types, approximate cost for two people, online ordering, table booking, and location-wise distribution.

Tools & Workflow

Tools: Python, Pandas, Matplotlib, and Jupyter Notebook. Workflow: clean the dataset, inspect key columns, calculate summary statistics, and create four visualizations.

Key Findings

Metric	Finding
Average restaurant rating	3.7 / 5
Average approximate cost for two	■555.43
Most common restaurant type	Quick Bites — 19,132 records
Location with most records	BTM — 5,124 records
Online ordering available	30,444 records (about 58.9%)
Table booking available	6,449 records (about 12.5%)

Visualizations Created

1. Restaurant ratings distribution 2. Top 10 restaurant types 3. Approximate cost for two 4. Online ordering availability

Conclusion

In this dataset, Quick Bites is the most frequently listed restaurant type. Online ordering appears in more records than table booking, and BTM has the highest record count among the listed locations. These results summarize the supplied dataset and should not be interpreted as current live restaurant counts.

Dataset note: counts are based on the 51,717 records represented by the supplied analysis output. The GitHub repository contains a smaller sample CSV; the original cleaned dataset remains local.