

Voicecon Mobile — Delete Account & Notifications API Guide

Add-on to the Mobile Chat API Guide · v1.0 · 8 Oct 2026

1. Basics

Item	Value
REST base URL (production)	<code>https://api.voicecon.ai/api/v1</code>
Format	JSON request and response. Send <code>Content-Type: application/json</code> .
Auth	Every call here needs <code>Authorization: Bearer <access_token></code> . No <code>X-Organization-Id</code> is needed, because these belong to the user, not a workspace.
Timestamps	ISO 8601 in UTC with an offset, e.g. <code>2026-11-07T13:28:50+00:00</code> . Parse and convert to local time to display.
Errors	<code>{"detail": "..."} </code> with a message you can show to the user.

Screen	Endpoint
Settings: delete account	<code>POST /users/me/deactivation/code</code> (accounts with no password only) <code>POST /users/me/deactivation/verify</code> <code>POST /users/me/deactivate</code>
Notifications (bell)	<code>GET /notifications</code> , <code>GET /notifications/unread-count</code> <code>POST /notifications/{id}/read</code> , <code>POST /notifications/read-all</code> <code>DELETE /notifications/{id}</code>
Invitation buttons	<code>POST /invitations/{token}/accept</code> , <code>POST /invitations/{token}/reject</code>

2. Delete account

"Delete account" deactivates the account first. It is **permanently deleted after a recovery period** (currently 30 days). Until then, Voicecon support can bring it back. When the account is deactivated:

- It is signed out on every device, and it can't sign in.
- Workspaces the user **owns** are switched off and their subscriptions are cancelled.
- A confirmation email is sent with the deletion date.

A signed-in session alone is not enough. The user must prove it's them again, with their password, or with an emailed code if the account has no password (Google/Apple sign-in).

Flow

- 1 Check `has_password` from `GET /users/me`. If it is `true`, show a password field. If it is `false` (a Google/Apple account that never set a password), call `/deactivation/code` and show a code field.
- 2 Call `/deactivation/verify` with the password or code. This **changes nothing yet**. It returns the deletion date and a token that is valid for 10 minutes.
- 3 Show a final confirmation screen, e.g. "Your account will be permanently deleted on 7 Nov 2026. Contact support@voicecon.ai to undo this before then."
- 4 When the user confirms, call `/devices/unregister` with this phone's FCM token (chat guide, section 10). Then call `/deactivate` with the token from step 2.
- 5 Clear the stored tokens, close the WebSocket and show the sign-in screen.

POST `/users/me/deactivation/code` — accounts with no password only

No body. Emails a 6-digit code (valid for 10 minutes).

```
200 { "message": "We sent a code to user@example.com.", "expires_in_minutes": 10,
      "debug_code": null }
```

Status	Meaning
400	<code>Enter your password to continue.</code> : the account has a password, so use the password field instead
429	Resend limit (60 s between codes, 5 per hour). Has a <code>Retry-After</code> header in seconds.

POST `/users/me/deactivation/verify` — confirm it's the user

Request: send **one** of the two

```
{ "password": "MyPassword#1" } // has_password: true
{ "code": "123456" }           // has_password: false
```

Response **200**

```
{
  "deactivation_token": "eyJ...", // valid for 10 minutes
  "retention_days": 30,
  "deletion_date": "2026-11-07T13:28:50+00:00",
  "support_email": "support@voicecon.ai"
}
```

Status	Message / meaning
400	Your password is incorrect.
400	Enter the code we emailed you. / That code is not correct. 3 attempts left. / That code has expired. Request a new one.
429	Too many incorrect attempts. Please try again shortly. (wrong passwords). Has a <code>Retry-After</code> header.
409	Platform admin accounts can't be deactivated from the app.

POST `/users/me/deactivate` — **deactivate**

Request

```
{ "deactivation_token": "eyJ..." }
```

Response **200**

```
{
  "deactivated_at": "2026-10-08T13:28:50+00:00",
  "deletion_date": "2026-11-07T13:28:50+00:00",
  "retention_days": 30,
  "support_email": "support@voicecon.ai"
}
```

Status	Message / meaning
400	That confirmation has expired. Please verify it's you again. : more than 10 minutes passed, so go back to the verify step

After a 200, the access token no longer works. Any further call returns **401** with `"code": "account_inactive"`. Unregister the push device **before** calling `/deactivate`, because you can't afterwards.

Signing in to a deactivated account

POST `/auth/login` with the correct password returns **403**:

```
{ "detail": "This account has been deactivated. To reactivate it, contact us at support@voicecon.ai." }
```

Show the message as it is. Reactivation is done by Voicecon support. There is no reactivate endpoint in the app.

3. In-app notifications (bell)

This is the notification list inside the app, the same one the web app shows under the bell icon. It is different from push notifications (covered in section 10 of the chat guide). Notifications belong to the

user and cover all their workspaces.

The notification object

```
{
  "id": "6f1c2e4a-...",
  "type": "team_invitation",
  "title": "Invitation to join Pearl Dental",
  "body": "Sara Khan invited you to join Pearl Dental as a member.",
  "data": { ... },           // depends on type, see below
  "is_read": false,
  "is_actioned": false,      // true once an invitation was accepted/declined
  "created_at": "2026-10-08T09:12:44+00:00"
}
```

type	When	data
team_invitation	Someone invited this user to a workspace	invitation_token, invitation_id, organization_name, role, inviter_name
team_member_joined	Someone accepted an invitation to a workspace this user owns or invited them to	organization_id, organization_name, member_email, role

More types may be added later. For an unknown `type`, show `title` and `body` with no buttons.

GET /notifications — list

Query param	Meaning
limit	1–100, default 30
unread_only	true to get unread only. Default false.

Returns a plain array (no paging wrapper), with unread first and then newest first.

```
200 [ { notification }, { notification }, ... ]
```

GET /notifications/unread-count — badge

```
200 { "count": 3 }
```

Refresh the badge when the app opens or returns to the foreground, and after any read or delete call. There is no WebSocket event for these notifications.

POST `/notifications/{id}/read` — mark one read

No body. Returns the updated notification. **404** `Notification not found` if it's not this user's or it was deleted.

POST `/notifications/read-all` — mark all read

No body. **204 No Content**.

DELETE `/notifications/{id}` — remove one

204 No Content, or **404** if not found. This only removes the notification. An invitation it announced stays pending and can still be answered from the email link.

Invitation buttons (Accept / Decline)

For a `team_invitation` with `is_actioned: false`, show Accept and Decline. Use `data.invitation_token`:

```
POST /invitations/{invitation_token}/accept // needs the Bearer token
200 { "status": "accepted", "message": "You've joined Pearl Dental.",
      "organization_name": "Pearl Dental",
      "organization_id": "b2d9...", "role": "member" }

POST /invitations/{invitation_token}/reject
200 { "status": "rejected", "message": "You've declined the invitation to Pearl Dental.",
      "organization_name": "Pearl Dental", "organization_id": null, "role": null }
```

After either call, the server marks the notification as read and `is_actioned: true`, so reload the list. After accepting, `organization_id` is the new workspace, so refresh `GET /workspaces` and offer to switch to it.

Status	Message
400	This invitation has expired or is no longer valid
403	This invitation was sent to x@y.com. Sign in as x@y.com to accept it.