

# Smart Grid Management System Based on IoT

## Group: 3

Khaled Hasan - 172008  
Md. Jafar Ikbāl - 172009  
Md. Nayeem - 172010

## Supervised by:

Ashish Kumar Karmakar  
Assistant Professor (EEE, DUET)



**Department of Electrical & Electronic Engineering.  
Dhaka University of Engineering & Technology, Gazipur.**

# Presentation Outline

- Introduction
- Purpose And Motivation
- Objectives
- Methodology
- Required Equipment
- Circuit Diagram
- Project Implementation
- Experimental Results
- Societal And Environmental Impact
- Future Work
- Conclusion

# Introduction

- IoT based smart grid system is implemented here.
- ESP-8266 micro-controller is used to control this system.
- Google Firebase platform is used to store data in the cloud.
- An Android app monitors the condition of the grid.


# **Purpose and Motivation**

- Making smart grids more reliable, developed, and efficient to meet consumers' accurate demand without load-shedding.
- Maintaining the balance between production and demand.
- Reducing cost of electricity generation.

# Objectives

- To design and implement an IoT-based smart grid management system.
- To ensure the economic dispatch system and lowering generation costs.
- To create a model to help the load dispatch centre make decisions on power plant control and load shedding.
- To store all the data in the cloud for better computation and prediction of load schedule.

# Methodology



**Fig. 1: Flow Chart of the Project**

# Required Equipment



Fig. 2: ESP-8266



Fig. 3: I2C module




Fig. 4: 4 Channel Relay Module



Fig. 5: Buzzer




Fig. 6: Current Sensor



Fig. 7: LCD Display





Fig. 8: Pocket Router

# Circuit Diagram



**Fig. 9: Circuit diagram of the Project**



# Project Implementation

## Power Plant Capacity and Cost Per Unit:


Power plants	Hydroelectric power plant	Solar power plant	Thermal power plant
Max. capacity	3 Amp	3 Amp	2 Amp
Cost per unit	1.65 Tk.	2.35 Tk.	7.50 Tk.

## Load Consumption rate in this project:

Consumer area (listed by priority)	Max. Load consumption	Base load consumption	Ampere rating
Army	400W	200W	2A
Industry	400W	100 W	2A
VIP	100W	50W	1A
Residential	100W	50W	1A

Assumed values that implemented in this project's coding section

# Project Implementation




**Fig. 10: Generation side of the project**

**Fig. 11: Consumer side of the project**


# Experimental Results

Test	Availability of energy source	Consumers load demand	Result
Test 01	Solar – <b>available</b> Hydro – <b>available</b> Thermal - <b>available</b>	Residential- 200W 1 Amp	Solar – <b>on</b> Hydro – <b>off</b> Thermal - <b>off</b>
Test 02	Solar – <b>available</b> Hydro – <b>available</b> Thermal - <b>available</b>	Residential- 200 W VIP area- 200W Total 2 Amp	Solar – <b>on</b> Hydro – <b>off</b> Thermal - <b>off</b>
Test 03	Solar – <b>available</b> Hydro – <b>available</b> Thermal - <b>available</b>	Residential- 200 W VIP area- 200W Industrial – 400W Total 4 Amp	Solar – <b>on</b> Hydro – <b>on</b> Thermal - <b>off</b>
Test 04	Solar – <b>unavailable</b> Hydro – <b>available</b> Thermal - <b>available</b>	Residential- 200 W VIP area- 200W Industrial – 400W Army area – 400W Total 6 Amp	Solar – <b>off</b> Hydro – <b>on</b> Thermal – <b>on</b> ( <b>Residential area under load shedding</b> )

# Experimental Results



**Fig. 12: Supplying Electricity from Solar Power Plant to Residential and VIP Areas**




**Fig. 13: Supplying Electricity from Solar Power Plant to Residential and VIP Areas**



# Experimental Results



**Fig. 14: Supplying Electricity from Solar and Hydro Power Plant**



**Fig. 15: Supplying Electricity from Hydro and Thermal Power Plant**

## **Societal and Environmental Impact**

- This project helps to maintain the low costs of electricity.
- Energy efficiency is increased because resources are used properly, reducing unnecessary fuel usage.
- Utilities stand to benefit from a higher rate of return on capital investment and lower costs.
- It can reduce electricity costs, meter reading costs, T&M operations and maintenance costs etc.

# **Future Work**

- I. This project can be more useful to design GPS system which automatically updates the information via SMS into mobile.
- II. The complete smart grid network information can be updated/monitored by web site or web portal using laptop/mobile/tablet/PC.
- III. Web portal communicates with DCUs in real time for data collection and data processing.



# SUSTAINABLE DEVELOPMENT GOALS





# Conclusions

- I. While incredibly expensive and demanding, these practices can have an equally incredible effect on electricity production and electricity use, consequently improving our effect on the Earth's delicate ecosystem, securing our electric supply system and lowering electricity costs.
- II. With or without the perspective of global climate change, there are many benefits to implementing such a radical change in the electricity supply system.

**THANK YOU**