

negative time equals to the time of the cookie we want to destroy

8. How do you initiate a PHP session?

~~session_start()~~ ~~\$_SESSION~~['session name'] = ['session value']

9. Assume you are developing a multiple choice quiz application, which presents one question at a time, and you are using session to store a list of questions numbers which have been answered correctly and a list of questions numbers which have been answered incorrectly. Write a PHP snippets that initiates the session and the two lists. [4 marks]

~~\$_SESSION['correct']~~

~~\$_SESSION['incorrect']~~

~~\$_SESSION['questions'] = array('correctly', 'incorrectly')~~

if (isset(\$_SESSION['questions']))

~~\$_SESSION['correct'] = ...~~

~~\$_SESSION['incorrect'] = ...~~

Question Three[15 marks]

Write a PHP script called uni.php that stores in an associative array the following information about the Palestinian universities.

Key	Name	url	County
BZU	Birzeit	http://www.birzeit.edu	Ramallah
AQU	Al-Quds	http://www.alquds.edu	Al-Quds
PPU	Palestine Polytechnic	http://www.ppu.edu	Hebron
Najah	An-Najah	http://www.najah.edu	Nablus

When the script executed, generates an HTML page that displays the universities details in a table as follow, university name should be linked to the university's home page:

University	County
Birzeit	Ramallah
Al-Quds	Al-Quds
Palestine Polytechnic	Hebron
An-Najah	Nablus

<?php

```
$palestinian_uni = array ( BZU => array( [name] => "Birzeit",
                                             [url] => "www.birzeit.edu",
                                             [county] => "Ramallah"),
```

```
  AQU => array( [name] => "Al-Quds",
                [url] => "www.alquds.edu",
                [county] => "Alquds"),
```

```
  PPU => array( [name] => "Palestine Polytechnic",
                [url] => "www.ppu.edu",
                [county] => "Hebron"),
```

```
  Najah => array( [name] => "An-najah",
                  [url] => "www.najah.edu",
                  [county] => "Nablus")
```

?>

<HTML>

<HEAD> <TITLE> Palestinian Universities </TITLE></HEAD>

<BODY>

<TABLE>

<TR> <TH> Universities </TH>

<TH> County </TH>

</TR>

Question Two (15 marks)

Create an HTML page for your college, which consist of the following details a title, heading, image, description paragraph, and an unordered list of the departments (at least two departments).

```
<!DOCTYPE HTML>
<HTML>
  <HEAD> <TITLE> Birzeit University </TITLE> </HEAD>
  <BODY>
    <H1> Welcome to Birzeit University Page </H1>
    <H2> Information </H2>
    <P> Birzeit university stand in Palestine
        in Ramallah City, it has a huge number
        of students 11 thousand (according to 2015)
    </P>
    <H2> pictures </H2>
    
    <BR> <BR>
    
    <H2> departments: </H2>
    <UL>
      <LI> IT department </LI>
      <LI> civil eng Department </LI>
      <LI> physics Department </LI>
    </UL>
  </Body>
</HTML>
```

- ✓ Answer the questions clearly in the space provided. Use the back of the pages for your rough work
- ✓ Students' questions are allowed only in the first 10 minutes after distribution the exam papers.
- ✓ Leaving the exam not before half the exam time being passed.

Question One [20 marks]

1. What are the differences between GET and POST methods?

GET :- send string query to server ~~to~~ with header information web server passes it to CGI and store it in a file.

Post : send with bodies application layer packet to server and server ~~store~~ pass it to CGI and it stores it as input data stream

2. Once a Web server returns a cookie to a browser, the cookie will be included in all future requests from the browser to the same server. (True/False)

Student id	Name	GPA
....		
....		

GPA greater than:	1.5
Filter	

The page consists of a table of students, and a form at the bottom. If the GPA has not been sent, the output page displays all the students stored in the database. The purpose of the form at the bottom is to provide filtering based on the GPA value. Using the figure above, as a result of clicking on the "Filter" button, only those students whose GPA is greater than 1.5 will be displayed in the table. (the same script will be used to produce the table and the form)

```
<?php
@mysql_connect('localhost','test','test') OR die('Error Connection');
@mysql_select_db('school','test') OR die('Error Connection');

??
<table>
<tr>
<td> student id</td>
<td> Name</td>
<td> GPA</td>
</tr>
</table>

<?php
$query = "SELECT * FROM Students";
mysql_query($query) or die(mysql_error());
```

Question Four [25 marks]

Assume there is a "school" database at "localhost" host with "test"/"test" username and password. School database contains a "student" table with the following schema student(studentid int, name char(20), gpa number(2,1)). The gpa is a value between 0.0 and 4.0. Write a self-calling PHP script generates the following output page.

Student id	Name	GPA

GPA greater than:	1.5
Filter	

The page consists of a table of students, and a form at the bottom. If the GPA has not been sent, the output page displays all the students stored in the database. The purpose of the form at the bottom is to provide filtering based on the GPA value. Using the figure above, as a result of clicking on the "Filter" button, only those students whose GPA is greater than 1.5 will be displayed in the table. (the same script will be used to produce the table and the form)

```
<?php
@mysql_connect('localhost','test','test') OR die('error connection');
@mysql_select_db('school','test') OR die('error connection');
```

Question Two [15 marks]

Create an HTML page for your college, which consist of the following details a title, heading, image, description paragraph, and an unordered list of the departments (at least two departments).

```
<!DOCTYPE HTML>
```

```
<HTML>
```

```
<HEAD> <TITLE> Birzeit University </TITLE> </HEAD>
```

```
<BODY>
```

```
<H1> Welcome to Birzeit University Page </H1>
```

```
<H2> Information </H2>
```

```
<P> Birzeit university stand in Palestine
```


Form action = "file.php" method = GET >

GPA greater than:

<input type="text" value=""/>

<input type="submit" value="Filter" />

<?php

if (isset(\$_GET) && !empty(\$_GET)) {

\$query = "SELECT * From student
Where GPA > = .\$_GET";

while (\$query-run = mysql_fetch_db(\$query))

{ <TR> <TD> \$query-run[student id] </TD>
<TD> \$query-run[Name] </TD>
<TD> \$query-run[GPA] </TD>

<TR>

}

} else

will display the all using the
while loop.

\$query = SELECT * From student

Question Three[15 marks]

Write a PHP script called uni.php that stores in an associative array the following information about the Palestinian universities.

| Key | Name | url | County |
|-------|-----------------------|------------------------|----------|
| BZU | Birzeit | http://www.birzeit.edu | Ramallah |
| AQU | Al-Quds | http://www.alquds.edu | Al-Quds |
| PPU | Palestine Polytechnic | http://www.ppu.edu | Hebron |
| Najah | An-Najah | http://www.najah.edu | Nablus |

When the script executed, generates an HTML page that displays the universities details in a table as follow, university name should be linked to the university's home page:

| University | County |
|---------------------------------------|----------|
| Birzeit | Ramallah |
| Al-Quds | Al-Quds |
| Palestine Polytechnic | Hebron |
| An-Najah | Nablus |

<?php

\$palestinian_uni = array (BZU => array ([name] => "Birzeit",
[url] => "http://www.birzeit.edu",
[county] => "Ramallah",

AQU => array ([name] => "Al-Quds",

```

<TR><TD>
  <A href = <?php $palestinian-uni[BZU][URL] ?>
  <A href = <?php $palestinian-uni[BZU][URL] ?>
  <A href = <?php $palestinian-uni[BZU][URL] ?>
  Birzeit </A> </TD>
  <TD> <?php $palestinian-uni[BZU][URL] ?>
</TR>

<TR><TD>
  <A href = <?php $palestinian-uni[AQU][URL] ?>
  alquds </A> </TD>
  <TD> <?php $palestinian-uni[AQU][URL] ?>
</TR>

<TR><TD>
  <A href = <?php $palestinian-uni[PPU][URL] ?>
  palestine polytechnic </A> </TD>
  <TD> <?php $palestinian-uni[PPU][URL] ?>
</TR>

<TR><TD>
  <A href = <?php $palestinian-uni[ngan][URL] ?>
  An-najah </A> </TD>
  <TD> <?php $palestinian-uni[ngan][URL] ?>
  </TD> </TR>
</TABLE>
</Body>
</HTML>

```

5/2/15

POST: send with browser application layer packet to server and server ~~store~~ pass it to CGI and it stores it as input data stream

2. Once a Web server returns a cookie to a browser, the cookie will be included in all future requests from the browser to the same server. (True/False)

3. How do you get information from a form that is submitted using the "get" method?

`if (isset ( $_GET ['information'] ) && !empty ( $_GET ['information'] )`

4. What is the correct way to connect to a MySQL database?

Put connection lines in a file and include it in the files that we want to connect them to database.

`@mysql_connect (hostname, username, password) OR die (connection error)`
`@mysql_select_db (databaseName, password) OR die (connection error)`

1

5. How can you submit a group of selections from a web form using a single field name?

~~array~~ `<input type="submit" name="submit">`
~~`$_GET ['submit']`~~

6. Which PHP function converts HTML into a format that can be displayed but will not be interpreted as HTML by a browser?

`htmlspecialchars ( )`

7. How can you destroy a cookie? there is no function to destroy it!

~~But by setting time~~ But to destroy it we can make a cookie with negative time equals to the time of the cookie we want to destroy

8. How do you initiate a PHP session?

`session_start ( )` `$_SESSION ['session name'] = ['session value']`

9. Assume you are developing a multiple choice quiz application, which