


Decision Tree for *PlayTennis*



47

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

When to Consider Decision Trees

- Instances describable by attribute–value pairs
- Target function is discrete valued
- Disjunctive hypothesis may be required
- Possibly noisy training data

Examples:

- Equipment or medical diagnosis
- Credit risk analysis
- Modeling calendar scheduling preferences

50

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Decision Trees

Decision tree representation:

- Each internal node tests an attribute
- Each branch corresponds to attribute value
- Each leaf node assigns a classification

How would we represent:

- \wedge, \vee, XOR
- $(A \wedge B) \vee (C \wedge \neg D \wedge E)$
- M of N

49


lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Top-Down Induction of Decision Trees

Main loop:

1. $A \leftarrow$ the “best” decision attribute for next *node*
2. Assign A as decision attribute for *node*
3. For each value of A , create new descendant of *node*
4. Sort training examples to leaf nodes
5. If training examples perfectly classified, Then STOP, Else iterate over new leaf nodes


Which attribute is best?



51

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Entropy



- S is a sample of training examples
- p_{\oplus} is the proportion of positive examples in S
- p_{\ominus} is the proportion of negative examples in S
- Entropy measures the impurity of S

$$Entropy(S) \equiv -p_{\oplus} \log_2 p_{\oplus} - p_{\ominus} \log_2 p_{\ominus}$$


52

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Information Gain

$Gain(S, A) =$ expected reduction in entropy due to sorting on A

$$Gain(S, A) \equiv Entropy(S) - \sum_{v \in Values(A)} \frac{|S_v|}{|S|} Entropy(S_v)$$



54

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Entropy

$Entropy(S) =$ expected number of bits needed to encode class (\oplus or \ominus) of randomly drawn member of S (under the optimal, shortest-length code)

Why?

Information theory: optimal length code assigns $-\log_2 p$ bits to message having probability p .

So, expected number of bits to encode \oplus or \ominus of random member of S :

$$p_{\oplus}(-\log_2 p_{\oplus}) + p_{\ominus}(-\log_2 p_{\ominus})$$

$$Entropy(S) \equiv -p_{\oplus} \log_2 p_{\oplus} - p_{\ominus} \log_2 p_{\ominus}$$

53

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Training Examples


Day	Outlook	Temperature	Humidity	Wind	PlayTennis
D1	Sunny	Hot	High	Weak	No
D2	Sunny	Hot	High	Strong	No
D3	Overcast	Hot	High	Weak	Yes
D4	Rain	Mild	High	Weak	Yes
D5	Rain	Cool	Normal	Weak	Yes
D6	Rain	Cool	Normal	Strong	No
D7	Overcast	Cool	Normal	Strong	Yes
D8	Sunny	Mild	High	Weak	No
D9	Sunny	Cool	Normal	Weak	Yes
D10	Rain	Mild	Normal	Weak	Yes
D11	Sunny	Mild	Normal	Strong	Yes
D12	Overcast	Mild	High	Strong	Yes
D13	Overcast	Hot	Normal	Weak	Yes
D14	Rain	Mild	High	Strong	No

55

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Selecting the Next Attribute


Which attribute is the best classifier?



56


lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Hypothesis Space Search by ID3



58

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997



Which attribute should be tested here?

$S_{\text{sunny}} = \{D1,D2,D8,D9,D11\}$

$\text{Gain}(S_{\text{sunny}}, \text{Humidity}) = .970 - (3/5) \cdot 0.0 - (2/5) \cdot 0.0 = .970$

$\text{Gain}(S_{\text{sunny}}, \text{Temperature}) = .970 - (2/5) \cdot 0.0 - (2/5) \cdot 1.0 - (1/5) \cdot 0.0 = .570$

$\text{Gain}(S_{\text{sunny}}, \text{Wind}) = .970 - (2/5) \cdot 1.0 - (3/5) \cdot .918 = .019$

57

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Hypothesis Space Search by ID3

- Hypothesis space is complete!
 - Target function surely in there...
- Outputs a single hypothesis (which one?)
 - Can't play 20 questions...
- No back tracking
 - Local minima...
- Statistically-based search choices
 - Robust to noisy data...
- Inductive bias: approx "prefer shortest tree"

59

lecture slides for textbook *Machine Learning*, ©Tom M. Mitchell, McGraw Hill, 1997

Inductive Bias in ID3

Note H is the power set of instances X

→ Unbiased?

Not really...


- Preference for short trees, and for those with high information gain attributes near the root
- Bias is a *preference* for some hypotheses, rather than a *restriction* of hypothesis space H
- Occam's razor: prefer the shortest hypothesis that fits the data

Overfitting in Decision Trees

Consider adding noisy training example #15:

Sunny, Hot, Normal, Strong, PlayTennis = No

What effect on earlier tree?



Occam's Razor

Why prefer short hypotheses?

Argument in favor:

- Fewer short hyps. than long hyps.

→ a short hyp that fits data unlikely to be coincidence

→ a long hyp that fits data might be coincidence

Argument opposed:

- There are many ways to define small sets of hyps
- e.g., all trees with a prime number of nodes that use attributes beginning with "Z"
- What's so special about small sets based on *size* of hypothesis??

Overfitting

Consider error of hypothesis h over

- training data: $error_{train}(h)$
- entire distribution \mathcal{D} of data: $error_{\mathcal{D}}(h)$


Hypothesis $h \in H$ **overfits** training data if there is an alternative hypothesis $h' \in H$ such that

$$error_{train}(h) < error_{train}(h')$$

and

$$error_{\mathcal{D}}(h) > error_{\mathcal{D}}(h')$$

Overfitting in Decision Tree Learning



Reduced-Error Pruning

Split data into *training* and *validation* set

Do until further pruning is harmful:

1. Evaluate impact on *validation* set of pruning each possible node (plus those below it)
2. Greedily remove the one that most improves *validation* set accuracy

- produces smallest version of most accurate subtree
- What if data is limited?

Avoiding Overfitting


How can we avoid overfitting?

- stop growing when data split not statistically significant
- grow full tree, then post-prune

How to select “best” tree:

- Measure performance over training data
- Measure performance over separate validation data set
- MDL: minimize $size(tree) + size(misclassifications(tree))$

Effect of Reduced-Error Pruning



Rule Post-Pruning

1. Convert tree to equivalent set of rules
2. Prune each rule independently of others
3. Sort final rules into desired sequence for use


Perhaps most frequently used method (e.g., C4.5)

IF $(Outlook = Sunny) \wedge (Humidity = High)$
THEN $PlayTennis = No$

IF $(Outlook = Sunny) \wedge (Humidity = Normal)$
THEN $PlayTennis = Yes$

...

Converting A Tree to Rules



Continuous Valued Attributes

Create a discrete attribute to test continuous

- $Temperature = 82.5$
- $(Temperature > 72.3) = t, f$

Temperature:	40	48	60	72	80	90
PlayTennis:	No	No	Yes	Yes	Yes	No

Attributes with Many Values

Problem:

- If attribute has many values, *Gain* will select it
- Imagine using *Date = Jun_3_1996* as attribute

One approach: use *GainRatio* instead

$$\text{GainRatio}(S, A) \equiv \frac{\text{Gain}(S, A)}{\text{SplitInformation}(S, A)}$$

$$\text{SplitInformation}(S, A) \equiv - \sum_{i=1}^c \frac{|S_i|}{|S|} \log_2 \frac{|S_i|}{|S|}$$

where S_i is subset of S for which A has value v_i

Unknown Attribute Values

What if some examples missing values of A ?

Use training example anyway, sort through tree

- If node n tests A , assign most common value of A among other examples sorted to node n
- assign most common value of A among other examples with same target value
- assign probability p_i to each possible value v_i of A
 - assign fraction p_i of example to each descendant in tree

Classify new examples in same fashion

Attributes with Costs

Consider

- medical diagnosis, *BloodTest* has cost \$150
- robotics, *Width_from_1ft* has cost 23 sec.

How to learn a consistent tree with low expected cost?

One approach: replace gain by

- Tan and Schlimmer (1990)

$$\frac{\text{Gain}^2(S, A)}{\text{Cost}(A)}.$$

- Nunez (1988)

$$\frac{2^{\text{Gain}(S, A)} - 1}{(\text{Cost}(A) + 1)^w}$$

where $w \in [0, 1]$ determines importance of cost