

Computational Learning Theory

What general laws constrain inductive learning?

We seek theory to relate:

- Probability of successful learning
- Number of training examples
- Complexity of hypothesis space
- Accuracy to which target concept is approximated
- Manner in which training examples presented

Prototypical Concept Learning Task

- **Given:**

- Instances X : Possible days, each described by the attributes *Sky*, *AirTemp*, *Humidity*, *Wind*, *Water*, *Forecast*
- Target function c : $EnjoySport : X \rightarrow \{0, 1\}$
- Hypotheses H : Conjunctions of literals. E.g.
 $\langle ?, Cold, High, ?, ?, ? \rangle$.
- Training examples D : Positive and negative examples of the target function

$$\langle x_1, c(x_1) \rangle, \dots \langle x_m, c(x_m) \rangle$$

- **Determine:**

- A hypothesis h in H such that $h(x) = c(x)$ for all x in D ?
- A hypothesis h in H such that $h(x) = c(x)$ for all x in X ?

Sample Complexity

How many training examples are sufficient to learn the target concept?

1. If learner proposes instances, as queries to teacher
 - Learner proposes instance x , teacher provides $c(x)$
2. If teacher (who knows c) provides training examples
 - teacher provides sequence of examples of form $\langle x, c(x) \rangle$
3. If some random process (e.g., nature) proposes instances
 - instance x generated randomly, teacher provides $c(x)$

Sample Complexity: 1

Learner proposes instance x , teacher provides $c(x)$
(assume c is in learner's hypothesis space H)

Optimal query strategy: play 20 questions

- pick instance x such that half of hypotheses in V_S classify x positive, half classify x negative
- When this is possible, need $\lceil \log_2 |H| \rceil$ queries to learn c
- when not possible, need even more

Sample Complexity: 2

Teacher (who knows c) provides training examples
(assume c is in learner's hypothesis space H)

Optimal teaching strategy: depends on H used by learner

Consider the case $H =$ conjunctions of up to n boolean literals and their negations

e.g., $(AirTemp = Warm) \wedge (Wind = Strong)$,
where $AirTemp, Wind, \dots$ each have 2 possible values.

- if n possible boolean attributes in H , $n + 1$ examples suffice
- why?

Sample Complexity: 3

Given:

- set of instances X
- set of hypotheses H
- set of possible target concepts C
- training instances generated by a fixed, unknown probability distribution \mathcal{D} over X

Learner observes a sequence D of training examples of form $\langle x, c(x) \rangle$, for some target concept $c \in C$


- instances x are drawn from distribution \mathcal{D}
- teacher provides target value $c(x)$ for each

Learner must output a hypothesis h estimating c

- h is evaluated by its performance on subsequent instances drawn according to \mathcal{D}

Note: probabilistic instances, noise-free classifications

True Error of a Hypothesis



Definition: The **true error** (denoted $error_{\mathcal{D}}(h)$) of hypothesis h with respect to target concept c and distribution \mathcal{D} is the probability that h will misclassify an instance drawn at random according to \mathcal{D} .

$$error_{\mathcal{D}}(h) \equiv \Pr_{x \in \mathcal{D}}[c(x) \neq h(x)]$$

Two Notions of Error

Training error of hypothesis h with respect to target concept c

- How often $h(x) \neq c(x)$ over training instances


True error of hypothesis h with respect to c

- How often $h(x) \neq c(x)$ over future random instances

Our concern:

- Can we bound the true error of h given the training error of h ?
- First consider when training error of h is zero (i.e., $h \in VS_{H,D}$)

Exhausting the Version Space



(r = training error, $error$ = true error)

Definition: The version space $VS_{H,D}$ is said to be ϵ -**exhausted** with respect to c and \mathcal{D} , if every hypothesis h in $VS_{H,D}$ has error less than ϵ with respect to c and \mathcal{D} .

$$(\forall h \in VS_{H,D}) \text{ error}_{\mathcal{D}}(h) < \epsilon$$

How many examples will ϵ -exhaust the VS?

Theorem: [Haussler, 1988].

If the hypothesis space H is finite, and D is a sequence of $m \geq 1$ independent random examples of some target concept c , then for any $0 \leq \epsilon \leq 1$, the probability that the version space with respect to H and D is not ϵ -exhausted (with respect to c) is less than

$$|H|e^{-\epsilon m}$$

Interesting! This bounds the probability that any consistent learner will output a hypothesis h with $error(h) \geq \epsilon$

If we want to this probability to be below δ

$$|H|e^{-\epsilon m} \leq \delta$$

then

$$m \geq \frac{1}{\epsilon}(\ln |H| + \ln(1/\delta))$$

Learning Conjunctions of Boolean Literals

How many examples are sufficient to assure with probability at least $(1 - \delta)$ that

every h in $VS_{H,D}$ satisfies $error_D(h) \leq \epsilon$

Use our theorem:

$$m \geq \frac{1}{\epsilon}(\ln |H| + \ln(1/\delta))$$

Suppose H contains conjunctions of constraints on up to n boolean attributes (i.e., n boolean literals). Then $|H| = 3^n$, and

$$m \geq \frac{1}{\epsilon}(\ln 3^n + \ln(1/\delta))$$

or

$$m \geq \frac{1}{\epsilon}(n \ln 3 + \ln(1/\delta))$$

How About *EnjoySport*?

$$m \geq \frac{1}{\epsilon}(\ln |H| + \ln(1/\delta))$$

If H is as given in *EnjoySport* then $|H| = 973$, and

$$m \geq \frac{1}{\epsilon}(\ln 973 + \ln(1/\delta))$$

... if want to assure that with probability 95%, VS contains only hypotheses with $error_{\mathcal{D}}(h) \leq .1$, then it is sufficient to have m examples, where

$$m \geq \frac{1}{.1}(\ln 973 + \ln(1/.05))$$

$$m \geq 10(\ln 973 + \ln 20)$$

$$m \geq 10(6.88 + 3.00)$$

$$m \geq 98.8$$

PAC Learning

Consider a class C of possible target concepts defined over a set of instances X of length n , and a learner L using hypothesis space H .

Definition: C is **PAC-learnable** by L using H if for all $c \in C$, distributions \mathcal{D} over X , ϵ such that $0 < \epsilon < 1/2$, and δ such that $0 < \delta < 1/2$,

learner L will with probability at least $(1 - \delta)$ output a hypothesis $h \in H$ such that $error_{\mathcal{D}}(h) \leq \epsilon$, in time that is polynomial in $1/\epsilon$, $1/\delta$, n and $size(c)$.

Agnostic Learning

So far, assumed $c \in H$

Agnostic learning setting: don't assume $c \in H$

- What do we want then?
 - The hypothesis h that makes fewest errors on training data
- What is sample complexity in this case?

$$m \geq \frac{1}{2\epsilon^2}(\ln |H| + \ln(1/\delta))$$

derived from Hoeffding bounds:

$$Pr[error_{\mathcal{D}}(h) > error_D(h) + \epsilon] \leq e^{-2m\epsilon^2}$$


Shattering a Set of Instances

Definition: a **dichotomy** of a set S is a partition of S into two disjoint subsets.

Definition: a set of instances S is **shattered** by hypothesis space H if and only if for every dichotomy of S there exists some hypothesis in H consistent with this dichotomy.

Three Instances Shattered


Instance space X




The Vapnik-Chervonenkis Dimension

Definition: The **Vapnik-Chervonenkis dimension**, $VC(H)$, of hypothesis space H defined over instance space X is the size of the largest finite subset of X shattered by H . If arbitrarily large finite sets of X can be shattered by H , then $VC(H) \equiv \infty$.

VC Dim. of Linear Decision Surfaces



(a)



(b)

Sample Complexity from VC Dimension

How many randomly drawn examples suffice to ϵ -exhaust $VS_{H,D}$ with probability at least $(1 - \delta)$?

$$m \geq \frac{1}{\epsilon} (4 \log_2(2/\delta) + 8VC(H) \log_2(13/\epsilon))$$

Mistake Bounds

So far: how many examples needed to learn?

What about: how many mistakes before convergence?

Let's consider similar setting to PAC learning:

- Instances drawn at random from X according to distribution \mathcal{D}
- Learner must classify each instance before receiving correct classification from teacher
- Can we bound the number of mistakes learner makes before converging?

Mistake Bounds: Find-S

Consider Find-S when H = conjunction of boolean literals

FIND-S:

- Initialize h to the most specific hypothesis
 $l_1 \wedge \neg l_1 \wedge l_2 \wedge \neg l_2 \dots l_n \wedge \neg l_n$
- For each positive training instance x
 - Remove from h any literal that is not satisfied by x
- Output hypothesis h .

How many mistakes before converging to correct h ?

Mistake Bounds: Halving Algorithm

Consider the Halving Algorithm:

- Learn concept using version space
CANDIDATE-ELIMINATION algorithm
- Classify new instances by majority vote of
version space members

How many mistakes before converging to correct h ?

- ... in worst case?
- ... in best case?

Optimal Mistake Bounds

Let $M_A(C)$ be the max number of mistakes made by algorithm A to learn concepts in C . (maximum over all possible $c \in C$, and all possible training sequences)

$$M_A(C) \equiv \max_{c \in C} M_A(c)$$

Definition: Let C be an arbitrary non-empty concept class. The **optimal mistake bound** for C , denoted $Opt(C)$, is the minimum over all possible learning algorithms A of $M_A(C)$.

$$Opt(C) \equiv \min_{A \in \text{learning algorithms}} M_A(C)$$

$$VC(C) \leq Opt(C) \leq M_{Halving}(C) \leq \log_2(|C|).$$