

Lecture 3: Binary Arithmetic, Logic and Addressing

Table of contents

1	Objectives:	2
2	Addition and Subtraction	3
2.1	INC and DEC Instructions	3
2.1.1	Example:	3
2.2	ADD and SUB Instructions	4
2.3	NEG Instruction	5
2.4	Example: Basic Arithmetic Operations	5
2.5	Implementing Arithmetic Expressions	6
2.6	Flags Affected by Arithmetic Instructions	9
2.6.1	Carry Flag	9
2.6.2	Overflow Flag	10
2.6.3	How the ALU calculates the Overflow flag	11
2.7	Which Instructions Affect Flags	12
3	Multiplication and Division	12
3.1	Terminology	12
3.2	MUL Instruction	13
3.2.1	Flags Affected	13
3.2.2	Example	14
3.2.3	Example	14

3.3	IMUL Instruction	15
3.3.1	Single-Operand Form	15
3.3.2	Two-Operand Form	15
3.3.3	Three-Operand Form	16
3.3.4	Flags Affected	16
3.3.5	Examples	17
3.4	DIV Instruction	18
3.4.1	Flags Affected	19
3.5	IDIV Instruction	19
3.5.1	CBW Instruction	19
3.5.2	CWD Instruction	20
3.5.3	CDQ Instruction	20
4	Logic Instructions	22
4.0.1	Flags Affected	23
4.1	Practical Implementations	23
4.1.1	Clearing/Masking Bits	23
4.1.2	Setting Bits	24
4.1.3	Toggling Bits	24
4.1.4	Testing a Bit	25
5	Indirect Addressing Modes	25
5.1	Displacement (Direct Memory) Addressing Mode	26
5.2	Base Addressing Mode	26
5.3	Base + Displacement Addressing Mode	27
5.4	Index Addressing Mode	28
5.5	Base + Index Addressing Mode	28
5.6	Base + Index + Displacement Addressing Mode	29
5.7	Summary	29

1 Objectives:

- In this lecture, we focus on **binary** arithmetic and logic instructions that operate on 8-, 16-, and 32-bit numeric data encoded as signed or unsigned binary integers. The instructions include

- increment and decrement
 - addition and subtraction
 - Multiplication and division
 - Bitwise Boolean AND, OR, XOR and NOT
- Introduction to *indirect addressing modes*.

2 Addition and Subtraction

2.1 INC and DEC Instructions

Syntax

```
INC    <operand>
DEC    <operand>
```

- INC (increment) and DEC (decrement) instructions add 1 and subtract 1 from an operand, respectively.
- The operand must be either a memory location or register. The format is

```
inc    reg/mem
dec    reg/mem
```

2.1.1 Example:

```
section .data
var1    dd    10

section .text
```

```

mov    eax, 5      ; EAX <-- 5
inc    eax         ; EAX = 6
inc    eax         ; EAX = 7
dec    eax         ; EAX = 8
inc    var1        ; ERROR: var1 is label
inc    [var1]       ; ERROR: size is unknown
inc    DWORD [var1] ; var1 = 11

```

2.2 ADD and SUB Instructions

Syntax

```

ADD    <destination>, <source>
SUB    <destination>, <source>

```

- The ADD instruction adds a source operand to a destination operand. The sum is stored in the destination operand, and the source operand's value is unchanged.
- The SUB instruction subtracts a source operand from a destination operand. The result is stored in the destination operand. The source operand's value is unchanged



Rules

1. Both operands must be the same size
2. Both operands cannot be memory operands
3. The instruction pointer register (EIP, RIP) cannot be a destination operand

The following operand types are permitted for these instructions (both for ADD and SUB):

```

add    reg, reg
add    reg, mem
add    reg, imm
add    mem, reg
add    mem, imm

```

2.3 NEG Instruction

Syntax

```
NEG    <operand>
```

- The NEG (negate) instruction reverses the sign of an operand by converting the number to its two's complement. The following operands are permitted:

```
neg    reg/mem
```

- Intel implements NEG instruction by subtracting the operand from zero (i.e., $\text{<operand>} = 0 - \text{<operand>}$)

2.4 Example: Basic Arithmetic Operations

```

section .data
var1    dd    1000h        ; 4096
var2    dd    2000h        ; 8192

section .text

mov     eax, [var1]        ; EAX <-- 1000h
inc     eax                ; EAX = 1001h
dec     DWORD [var2]       ; VAR2 = 1FFFh
add     eax, [var2]         ; EAX = 1001h + 1FFFh = 3000h

```

```

sub    [var2], eax    ; [VAR2] = 1FFFh - 3000h = 0FFFF EFFFh (-4096)
neg    DWORD [var1]   ; [VAR1] = FFFF F000h (-4096)

```

2.5 Implementing Arithmetic Expressions

In the following examples, we learn how to translate high-level expressions into assembly instructions:

Example 2.1.

```
b = a;
```

Solution:

```

mov    eax, [a]        ; EAX <-- a
mov    [b], eax        ; b <-- EAX

```

Example 2.2.

```
b = a + 1;
```

Solution:

```

mov    eax, [a]        ; EAX <-- a
inc    eax             ; EAX ++
mov    [b], eax        ; b <-- EAX

```

Alternative solution:

```

mov    eax, [a]
add    eax, 1
mov    [b], eax

```

Incorrect solutions (avoid these):

The following solution is not acceptable because it changes the value of variable a:

```
add    [a], 1           ; ERROR: don't change the variable a
mov     eax, [a]
mov     [b], eax
```

The following solution has syntax error: memory to memory operands

```
mov     [b], [a]        ; ERROR: memory to memory operands
add     [b], 1
```

Example 2.3.

```
c = b - a;
```

Solution:

```
mov     eax, [a]         ; EAX <-- a
mov     ebx, [b]         ; EBX <-- b
sub     ebx, eax         ; EBX = EBX - EAX
mov     [c], ebx         ; c <-- EBX
```

Another solution:

```
mov     eax, [b]         ; EAX <-- b
sub     eax, [a]         ; EAX = EAX - a
mov     [c], eax         ; c <-- EAX
```

Example 2.4.

```
y = 5 - y;
```

Solution:

```
mov    eax, 5           ; EAX <-- 5
sub    eax, [y]          ; EAX = EAX - y
mov    [y], eax          ; y <-- EAX
```

Another solution:

```
neg    [y]               ; y = -y
add    [y], 5             ; y = y + 5
```

Example 2.5.

```
c = 2 * (a + b) + 10;
```

Solution:

```
    ; evaluate (a + b)
mov    eax, [a]
add    eax, [b]

    ; 2 * (a + b)
add    eax, eax

    ; 2 * (a + b) + 10
add    eax, 10

    ; c = <expr>
mov    [c], eax
```

2.6 Flags Affected by Arithmetic Instructions

- When a CPU executes arithmetic instructions, it consequently updates the status flags. (see lecture 1 for flag details)
- Status flags provide information about whether the output is
 - Positive or negative
 - zero or not zero
 - too large or too small to fit into the destination operand
 - the parity of the least significant byte
- The status flags can be used to activate conditional branching instructions (will be discussed in next lecture).

Status Flags	Is set when
CF	unsigned integer overflow
OF	signed integer overflow
ZF	the output is zero
SF	the output is negative
PF	The least significant byte of the output have even number of 1 bits
AF	there is a 1 bit carried out of position 3 in the least significant byte of the output

2.6.1 Carry Flag

Carry flag is set when:

- There is a carry out of the most significant bit (MSB) when adding two numbers:

$$\begin{array}{r}
 01000001 \\
 + 11000010 \\
 \hline
 CF = 1 \quad 00000011
 \end{array}$$

- There is a borrow into the MSB when subtracting two numbers

$$\begin{array}{r}
 00000001 \\
 - 00000010 \\
 \hline
 CF = 1 \quad 11111111
 \end{array}$$



Remember

- In unsigned arithmetic, watch the carry flag to detect errors
- In signed arithmetic, the carry flag tells you nothing interesting

2.6.2 Overflow Flag

Overflow flag is set when:

- the sum of two numbers with the sign bits off yields a result number with sign bit on.

$$\begin{array}{r}
 00100001 \\
 + 01100010 \\
 \hline
 OF = 1 \quad 10000011
 \end{array}$$

- the sum of two numbers with the sign bits on yields a result number with sign bit off.

$$\begin{array}{r}
 10100001 \\
 + 10100010 \\
 \hline
 OF = 1 \quad 01000011
 \end{array}$$

2.6.3 How the ALU calculates the Overflow flag

This material is optional reading.

- The value that carries out of the MSB is exclusive ORed with the carry into the MSB of the result.
- The value that borrows out of the MSB is exclusive ORed with the borrow into the MSB of the result.
- The resulting value of XOR is placed in the Overflow flag.
- Example

$$\begin{array}{r} 10000000 \\ + 11111111 \\ \hline OF = 1 \quad 01111111 \end{array}$$

The carry into the MSB is 0 and the carry out of the MSB is 1, $OF = 0 \text{ XOR } 1 = 1$

$$\begin{array}{r} 00000001 \\ - 00000010 \\ \hline OF = 0 \quad 11111111 \end{array}$$

The borrow into the MSB is 1 and the borrow out of the MSB is 1, $OF = 1 \text{ XOR } 1 = 0$



Remember

- In signed arithmetic, watch the overflow flag to detect errors
- In unsigned arithmetic, the overflow flag tells you nothing interesting

2.7 Which Instructions Affect Flags

- In general, each time the processor executes an instruction, the flags are altered to reflect the result. However, some instructions (1) don't affect any of the flags, (2) affect only some of them, or (3) may leave them undefined.
- Here is a summary of previous instructions:

Instructions	Flags
Transfer instructions (such as MOV, XCHG)	None
ADD and SUB	All flags
INC and DEC	All flags except CF
NEG	All flags (remember NEG = subtracting operand from zero)

3 Multiplication and Division

3.1 Terminology

- When multiplying two numbers, the first number is **multiplicand**, the second number is **multiplier** and the result is **product**.
- If the size of multiplicand is n-bit and the size of multiplier is m-bit, then the size of the product is at most (n+m)-bit.
- When dividing two numbers, the first number is **dividend**, the second number is **divisor**, and the result is **quotient**. So, the dividend is the number that is divided by the divisor. The number left behind after the division is called the **remainder**.

3.2 MUL Instruction

Syntax

MUL <multiplier>

- This is the *unsigned* version of multiplication
- The multiplier can be either mem or reg.
- There are three formats depending on the size of multiplier (in 32-bit mode):

Multiplier	Multiplicand	Product
reg/mem8	AL	AX
reg/mem16	AX	DX:AX
reg/mem32	EAX	EDX:EAX
imm	NOT ALLOWED	

3.2.1 Flags Affected

The OF and CF flags are set to 0 if the upper half of the result is 0; otherwise, they are set to 1. The SF, ZF, AF, and PF flags are undefined.

3.2.2 Example

Before	Instruction Executed	After				
AX: <table><tr><td>00</td><td>05</td></tr></table>	00	05	mul bx	DX: <table><tr><td>00</td><td>00</td></tr></table>	00	00
00	05					
00	00					
BX: <table><tr><td>00</td><td>02</td></tr></table>	00	02	AX: <table><tr><td>00</td><td>0A</td></tr></table>	00	0A	
00	02					
00	0A					
DX: <table><tr><td>??</td><td>??</td></tr></table>	??	??	OF,CF: <table><tr><td>0</td></tr></table>	0		
??	??					
0						

Before	Instruction Executed	After								
EAX: <table><tr><td>00</td><td>00</td><td>00</td><td>0A</td></tr></table>	00	00	00	0A	mul eax	EDX: <table><tr><td>00</td><td>00</td><td>00</td><td>00</td></tr></table>	00	00	00	00
00	00	00	0A							
00	00	00	00							
EDX: <table><tr><td>??</td><td>??</td><td>??</td><td>??</td></tr></table>	??	??	??	??	EAX: <table><tr><td>00</td><td>00</td><td>00</td><td>64</td></tr></table>	00	00	00	64	
??	??	??	??							
00	00	00	64							
	OF,CF: <table><tr><td>0</td></tr></table>	0								
0										

Before	Instruction Executed	After				
AX: <table><tr><td>22</td><td>05</td></tr></table>	22	05	mul BYTE [len]	AX: <table><tr><td>04</td><td>FB</td></tr></table>	04	FB
22	05					
04	FB					
len: <table><tr><td>FF</td></tr></table>	FF	OF,CF: <table><tr><td>1</td></tr></table>	1			
FF						
1						

3.2.3 Example

```

mov     al, 12      ; multiplicand
mov     bl, 5       ; multiplier
mul     bl          ; AX = 12 x 5 = 60 = 003Ch
; since the multiplier is reg8, the product in AX
; CF and OF are set to 0

mov     ax, 1000    ; multiplicand
mov     cx, 2000    ; multiplier
mul     cx          ; DX:AX = 1000 x 2000 = 2,000,000
; DX = 001Eh, AX = 8480h
; CF=1 and OF=1
; since the multiplier is reg16, the product is stored in
; two registers DX:AX

```

3.3 IMUL Instruction

Syntax

```
IMUL    <source>
IMUL    <destination>, <source>
IMUL    <destination>, <source1>, <source2>
```

- This is the *signed* version of multiplication.
- IMUL instruction can take either one operand, two operands, or three operands.

3.3.1 Single-Operand Form

- This form is identical to that used by the MUL instruction.

3.3.2 Two-Operand Form

- The destination operand is multiplied by the source operand. The product is truncated and stored in the destination operand.
- The destination operand must be register (either reg16 or reg32 only)
- The valid formats are

```
IMUL    reg16, reg/mem16
IMUL    reg16, imm8
IMUL    reg16, imm16
```

```
IMUL    reg32, reg/mem32
IMUL    reg32, imm8
IMUL    reg32, imm32
```

3.3.3 Three-Operand Form

- The first source operand is multiplied by the second source operand. The product is truncated and stored in the destination operand
- The destination operand must be register (either `reg16` or `reg32`). The first source operand must be a register or memory with same size as the destination operand. The second source operand must be immediate operand
- The valid formats are:

<code>IMUL</code>	<code>reg16, reg/mem16, imm8</code>
<code>IMUL</code>	<code>reg16, reg/mem16, imm16</code>
<code>IMUL</code>	<code>reg32, reg/mem32, imm8</code>
<code>IMUL</code>	<code>reg32, reg/mem32, imm32</code>

3.3.4 Flags Affected

- For the one operand form of the instruction, the CF and OF flags are set when significant bits are carried into the upper half of the result and cleared when the result fits exactly in the lower half of the result.
- For the two- and three-operand forms of the instruction, the CF and OF flags are set when the result must be truncated to fit in the destination operand size and cleared when the result fits exactly in the destination operand size.
- The SF, ZF, AF, and PF flags are undefined.



Remember

With the two- and three- operand forms, the result is truncated to the length of the destination before it is stored in the destination register. Because of this truncation, the CF or OF flag should be tested to ensure that no significant bits are lost.

3.3.5 Examples

Example 3.1.

```
section .data
varW    dw    4
varDW   dd    4

section .text
mov     ax, -16      ; AX <-- -16
mov     bx, 2        ; BX <-- 2

imul    bx, ax       ; BX = -32
imul    bx, 2        ; BX = -64
imul    bx, [varW]   ; BX = -256

mov     eax, -16
mov     ebx, 2

imul    ebx, eax     ; EBX = -32
imul    ebx, 2       ; EBX = -64
imul    ebx, [varDW] ; EBX = -256
```

Example 3.2. Translate $y = x * 7$ to Assembly, assuming that x and y are declared as signed integer.

Solution 1:

```
mov     eax, [x]
imul    eax, 7        ; eax = eax * 7
mov     [y], eax
```

Solution 2:

```

mov    eax, [x]
mov    ebx, 7
imul   ebx           ; eax = eax * ebx
mov    [y], eax

```

Solution 3:

```

imul   eax, [x], 7
mov    [y], eax

```

3.4 DIV Instruction

Syntax

```
DIV    <divisor>
```

- This is the unsigned version of division
- There are three formats depending on the size of divisor (in 32-bit mode):

Divisor	Dividend	Quotient	Remainder
reg/mem8	AX	AL	AH
reg/mem16	DX:AX	AX	DX
reg/mem32	EDX:EAX	EAX	EDX
immediate	NOT ALLOWED		

Remember

If you did not set the upper half of the dividend, don't forget to clear it using one of the following instructions:

```
xor    ax, ax
mov    ah, 0
sub    edx, edx
```

3.4.1 Flags Affected

The CF, OF, SF, ZF, AF, and PF flags are undefined.

3.5 IDIV Instruction

- This is the signed version of division
- It has the same syntax as DIV
- If $q = a/b$ where q is the quotient, a is the dividend, and b is divisor, then $a = q * b + r$
- The sign of the remainder is **always** the same as the sign of the dividend
- If the divisor is 0, an interrupt called #DE is generated to terminate the program.

Remember

The dividend must be sign-extended before the division takes place. As such, x86 architecture provides CBW, CWD, and CDQ to sign extend the dividend.

3.5.1 CBW Instruction

- **Convert Byte to Word**. This instruction requires no operand.
- Impact: If MSB of AL is 1, then AH = 0xFF, otherwise AH = 0.

3.5.2 CWD Instruction

- Convert **W**ord to **D**oubleword. This instruction requires no operand.
- Impact: If MSB of AX is 1, then DX = 0xFFFF, otherwise DX = 0.

3.5.3 CDQ Instruction

- Convert **D**oubleword to **Q**uadword. This instruction requires no operand.
- Impact: If MSB of EAX is 1, then EDX = 0xFFFF-FFFF, otherwise EDX = 0.

Example 3.3.

```
mov    al, 125      ; dividend: AL <-- 125
cbw                    ; AH = 0
mov    bl, 2        ; BL <-- 2
div    bl           ; AL = 125/2 = 62 = 3Dh, AH = 01h

mov    al, -125     ; AL <-- -125 = 83h
cbw                    ; AX = FF83h
mov    bl, 2
idiv   bl           ; AL = -125/2 = -62 = 0C2h, AH = -1 = 0FFh

mov    dx, 0        ; clear dividend, high
mov    ax, 8003h     ; dividend, low
mov    cx, 100h      ; divisor
div    cx           ; AX = 0080h, DX = 0003h
```

In the remaining examples, we are going to translate from high-level language to assembly language. All variables are 32-bit signed integers

Example 3.4.

```
f = 9/5*c + 32;
```

```
mov    eax, [c]      ; EAX = c
imul   eax, 9        ; EAX = 9 * c
mov    ebx, 5        ; EBX = 5 (divisor)
cdq    ; Sign-extend EAX to EDX
idiv   ebx          ; EAX = EAX / EBX
mov    [f], eax      ; f = EAX
```

Example 3.5.

```
v4 = (v1 * 5) / (v2 - 3);
```

```
mov    eax, [v1]     ; EAX <-- v1
imul   eax, 5        ; EAX = EAX * 5
mov    ebx, [v2]     ; EBX <-- v2
sub    ebx, 3        ; EBX = v2 - 3
cdq    ; Sign-extend EAX to EDX
idiv   ebx          ; EAX = EAX / EBX
mov    [v4], eax     ; v4 <-- EAX
```

Example 3.6.

```
v4 = -v1 * 5 / (-v2 % v3)
```

```
mov    eax, [v1]     ; EAX <-- v1
neg    eax           ; EAX = -v1
imul   ecx, eax, 5    ; ECX = -v1 * 5

mov    eax, [v2]     ; EAX <-- v2
neg    eax           ; EAX = -v2
mov    ebx, [v3]     ; EBX <-- v3
cdq    ; sign-extend EAX to EDX
idiv   ebx          ; EAX = EAX / EBX, Rem = EDX
```

```

mov    eax, ecx    ; Set EAX = ECX (enumerator)
mov    ebx, edx    ; Set EBX = EDX (denominator)
cdq
idiv   ebx         ; EAX = EAX / EBX

mov    [v4], eax   ; v4 = EAX

```

4 Logic Instructions

- The Intel instruction set contains the AND, OR, XOR, NOT, and many more instructions that directly implement Boolean operations on binary bits.

Syntax

```

AND    <destination>, <source>
OR     <destination>, <source>
XOR    <destination>, <source>
NOT    <destination>

```

- The following table describes the operation of each instruction

Instruction	Description
AND	Bitwise logical AND operation between a source operand and a destination operand
OR	Bitwise logical OR operation between a source operand and a destination operand
XOR	Bitwise logical exclusive-OR operation between a source operand and a destination operand
NOT	Bitwise NOT operation on a destination operand



Rules

1. Both operands must be the same size
2. Both operands cannot be memory operands
3. The instruction pointer register (EIP, RIP) cannot be a destination operand

The following operand types are permitted for these instructions:

```
and    reg, reg
and    reg, mem
and    reg, imm
and    mem, reg
and    mem, imm
not    reg
not    mem
```

4.0.1 Flags Affected

- The OF and CF are cleared.
- The SF, ZF, and PF are set according to the result.
- The state of AF is undefined.

4.1 Practical Implementations

4.1.1 Clearing/Masking Bits

- The AND instruction allows us to clear one or more bits in an operand without affecting other bits. This technique is called **bit masking**.
- To clear a bit (or more), use AND with a **mask** that has a 0 in the position that is to be cleared. All other positions in the mask contain 1.

- For example, suppose we have the bit string 1110 0110 and we want to clear bit 2 (change it to 0). We can use mask 1111 1011₂ as follows:

```
mov    AL, 1110_0110b    ; bit string
and    AL, 1111_1011b    ; AL=1110 0010
```

4.1.2 Setting Bits

- The OR instruction allows us to set one or more bits in an operand without affecting any other bits.
- To set a bit (or more), use OR with a mask that has 1 in the position which is to be set. All other positions in the mask contain 0.
- The following code:

```
or     AL, 0000_0100b    ; set bit 2
```

will set bit at position 2 to 1 and leave other bits unchanged.

4.1.3 Toggling Bits

- We can toggle or switch the value of individual bits from 1 to 0 or vice versa.
- To toggle a bit, use XOR with a mask that has 1 in the position which is to be toggled. All other positions in the mask contain 0.
- Consider the following example

$$\begin{array}{r}
 \text{Original Value} = 1\ 0\ 0\ 1\ 0\ 1\ 1\ 0 \\
 \text{XOR'ed Value} = 0\ 0\ 0\ 0\ 1\ 1\ 1\ 1 \\
 \hline
 \text{Toggled Value} = 1\ 0\ 0\ 1\ 1\ 0\ 0\ 1
 \end{array}$$

4.1.4 Testing a Bit

- To test a bit, use AND with a mask that has 1 in the position which is to be tested. All other positions in the mask contain 0.
- Example, suppose we have the bit string 1110 0110 and we want to test bit 5 (check its value). We can use mask 0010 0000₂ and the AND:

```
mov    AL, 1110_0110b    ; our bit string
and    AL, 0010_0000b    ; The result = 0010 0000
```

- Since bit 5 was set, the result is a nonzero value. However, suppose we want to test bit 4. We use mask 0001 0000 and the AND operation:

```
mov    AL, 1110_0110b    ; our bit string
and    AL, 0001_0000b    ; The result = 0000 0000
```

- Since bit 4 was not set, the result is a zero value.
- So after the AND, we need to test the result; if the result is nonzero, the bit is set; otherwise, it is not.

5 Indirect Addressing Modes

- Memory locations (where the objects are stored) can be specified:
 - **Directly** as static value (also known as displacement)
 - **Indirectly** through an address computation made up of one or more of the following components:
 1. Displacement
 2. Base
 3. Index
 4. Scale-Factor

- The offset address which results from adding these components is called an **effective address**.

In the following section, we consider the following data definition

```

section .data
v1      db      50, 62
arrX    dw      1, 2, 3, 4, 5
matr    dd      10, 11, 12, 13
         dd      20, 21, 22, 23

```

5.1 Displacement (Direct Memory) Addressing Mode

- A displacement is 8-, 16-, or 32-bit constant value or expression
- Displacement alone represents a direct offset to the operand.
- The syntax is:

```
[ <disp32> ]
```

where disp32 is 32-bit displacement value

- Example

```

mov    al, [v1]          ; AL = 50
add    al, [v1 + 1]      ; AL = 50 + 62 = 112

```

5.2 Base Addressing Mode

- Base alone represents an indirect offset to the operand.
- In this mode, the offset address is contained in a *general purpose register*. We say that the register acts as a **pointer** to the memory location.
- The syntax for 32-bit architecture is:

[<reg32>]

- Example:

```
mov     esi, arrX      ; ESI points to the 1st element in arrX
mov     ax, 0           ; set sum to zero
add     ax, [esi]       ; add arrX[0] to sum, AX = 1
add     esi, 2          ; move pointer to next element
add     ax, [esi]       ; add arrX[1] to sum, AX = 1+2 = 3
add     esi, 2          ; move pointer to next element
add     ax, [esi]       ; add arrX[2] to sum, AX = 3+3 = 6
```

Practical use: This mode is commonly used for traversing arrays and linked data structures.

5.3 Base + Displacement Addressing Mode

- A base register and a displacement can be used together to access a field of a record. The base register holds the address of the beginning of the record, while the displacement holds a static offset to the field
- This mode is especially useful when we need to access parameters in a procedure activation record. We will elaborate this mode when we discuss procedures.
- The syntax is

[<reg32> + <disp>]

[<reg32> - <disp>]

- Example:

```
mov     esi, v1         ; esi points to v1
mov     al, [esi + 0]   ; AL = 50
mov     bl, [esi + 1]   ; BL = 62
```

5.4 Index Addressing Mode

- In this mode, there are two forms:

`[index + displacement]`

`[index*scale + displacement]`

- The index is a general purpose register except ESP
- For 32-bit mode, the syntax:

`[ <reg32> + <disp32> ]`

`[ <reg32>*<scale> + <disp32> ]`

where <scale> can be either 1, 2, 4, or 8

- In index mode, the displacement locates the beginning of an array, the index register holds the subscript of the desired array element, and scale represents the data type.
- For example, `arrX[3]` can be translated to assembly as `[ecx*2 + arrX]` where the register ECX holds the value 3.
- Example

```
mov    ax, 0                ; set sum to zero
mov    esi, 0               ; set array index to 0
add    ax, [esi*2 + arrX]    ; add arrX[0] to sum, AX = 1
inc    esi                  ; increment the index by 1
add    ax, [esi*2 + arrX]    ; add arrX[1] to sum, AX = 1+2 = 3
inc    esi                  ; increment the index by 1
add    ax, [esi*2 + arrX]    ; add arrX[2] to sum, AX = 3+3 = 6
```

5.5 Base + Index Addressing Mode

- In this mode, the base register holds the address of a dynamic array, while the index register holds offset address or subscript index.

- In 2D arrays, the base register holds the address of the beginning of a row. The index register holds the column's subscription
- The syntax is:

[<base> + <index>]

[<base> + <index>*<scale>]

where <base> and <index> are reg32.

5.6 Base + Index + Displacement Addressing Mode

- This mode is a combination of previous modes
- This mode is suitable for traversing array of records.

5.7 Summary

The following diagram, adopted from Intel manual summarizes the memory addressing modes:




Figure 1: Offset (or Effective Address) Computation