

```

//-----
// bigengl()
// compares two structures of type Distance, returns the larger
Distance bigengl( Distance dd1, Distance dd2 )
{
    if(dd1.feet > dd2.feet)        //if feet are different, return
        return dd1;                //the one with the largest feet
    if(dd1.feet < dd2.feet)
        return dd2;
    if(dd1.inches > dd2.inches)    //if inches are different,
        return dd1;                //return one with largest
    else                            //inches, or dd2 if equal
        return dd2;
}
//-----
// engldisp()
// display structure of type Distance in feet and inches
void engldisp( Distance dd )
{
    cout << dd.feet << "\'-" << dd.inches << "\"";
}

```

Chapter 6

Answers to Questions

1. A class declaration describes how objects of a class will look when they are created.
2. class, object
3. c
- 4.

```

class leverage
{
    private:
        int crowbar;
    public:
        void pry();
};

```

5. false; both data and functions can be private or public
6. leverage lever1;
7. d
8. lever1.pry();
9. inline (also private)

10.

```
int getcrow()
{ return crowbar; }
```

11. created (defined)

12. the class of which it is a member

13.

```
leverage()
{ crowbar = 0; }
```

14. true

15. a

16. `int getcrow();`

17.

```
int leverage::getcrow()
{ return crowbar; }
```

18. member functions and data are, by default, public in structures but private in classes

19. three, one

20. calling one of its member functions

21. b, c, d

22. false; trial and error may be necessary

23. d

24. true

25. `void aFunc(const float jerry) const;`

Solutions to Exercises

1.

```
// ex6_1.cpp
// uses a class to model an integer data type
#include <iostream>
using namespace std;
////////////////////////////////////
class Int                               //(not the same as int)
{
private:
    int i;
public:
    Int()                               //create an Int
    { i = 0; }
```