

```

Int alpha = 20;
Int beta = 7;
Int delta, gamma;

gamma = alpha + beta;           //27
cout << "\ngamma="; gamma.putInt();
gamma = alpha - beta;          //13
cout << "\ngamma="; gamma.putInt();
gamma = alpha * beta;          //140
cout << "\ngamma="; gamma.putInt();
gamma = alpha / beta;          //2
cout << "\ngamma="; gamma.putInt();

delta = 2147483647;
gamma = delta + alpha;          //overflow error
delta = -2147483647;
gamma = delta - alpha;          //overflow error

cout << endl;
return 0;
}

```

Chapter 9

Answers to Questions

1. a, c
2. derived
3. b, c, d
4. `class Bosworth : public Alphonso`
5. false
6. protected
7. yes (assuming `basefunc` is not private)
8. `BosworthObj.alfunc();`
9. true
10. the one in the derived class
11. `Bosworth() : Alphonso() { }`
12. c, d
13. true
14. `Derv(int arg) : Base(arg)`

15. a
16. true
17. c
18. class Tire : public Wheel, public Rubber
19. Base::func();
20. false
21. generalization
22. d
23. false
24. stronger, aggregation

Solutions to Exercises

1.

```
// ex9_1.cpp
// publication class and derived classes
#include <iostream>
#include <string>
using namespace std;
/////////////////////////////////////////////////////////////////
class publication                                // base class
{
private:
    string title;
    float price;
public:
    void getdata()
    {
        cout << "\nEnter title: "; cin >> title;
        cout << "Enter price: "; cin >> price;
    }
    void putdata() const
    {
        cout << "\nTitle: " << title;
        cout << "\nPrice: " << price;
    }
};
/////////////////////////////////////////////////////////////////
class book : private publication                // derived class
{
private:
    int pages;
```