




FineFlow–Espresso: A Calibratable 1D Model of Fines Migration

**A continuum model linking fines transport
and hydraulic resistance**

Technical University of Munich
Chair of Process Systems Engineering

Ali Khalifa & Heiko Briesen




Presenter transcript

Today I will introduce FineFlow-Espresso as a one-dimensional continuum model of fines migration. The aim is to connect changes in the coffee puck with pressure, flow and fines leaving the puck. The current results demonstrate the numerical model. They are not a calibrated prediction of the experiments. Pore-network modeling is a possible next step for determining closures from the pore geometry.



Flow and fines inside the coffee bed



Flow and mobile fines

- Q : flow rate; A : puck area; $q = Q/A$: superficial velocity;
- c : mobile-fines concentration; $q c$: advective fines flux.

Pore structure and retained fines

- ε : porosity; K : permeability;
- m_a : remaining initially attached fines;
 m_d : recaptured deposits;
- m_a, m_d : mass per bulk volume; c : mass per water volume.

Distinct retained populations assume different kinetics or hydraulic effects.

Presenter transcript

The key distinction is the history of the retained fines. The variable m_a is the remaining releasable inventory that was initially attached to the coffee matrix. It is an evolving state, not just an initial condition. The variable m_d represents fines captured after entering the mobile phase. The current model assigns different release laws to these populations and associates additional blockage with m_d . This is a modeling hypothesis. If experiments do not support the distinction, we should combine them into one retained inventory.



Scope of the 1D continuum model

Present approach

- Forward flow with cross-section-averaged fields varying in z and t .
- CT stage snapshots can constrain axial structural changes.
- Pressure and flow histories constrain the evolving total resistance.

Limits and next measurements


- **Reverse flow and radial channeling are outside the scope of this work.**
- CT shows radial heterogeneity. Measurements must test whether axial averaging captures the overall hydraulic response.
- Time-resolved cup-fines data are a proposed measurement; availability is unconfirmed.
- Pore networks and 2D/3D continuum models are future extensions.

Presenter transcript

The present model considers forward flow and axial variations of cross-section-averaged fields. Reverse flow and radial channeling are explicitly outside the scope of this work. This does not mean radial structure is absent: Mahima's CT observations include radial heterogeneity and blocking clusters. We must compare with measurements to determine whether axial averaging adequately captures the overall hydraulic response. CT images at selected stages are snapshots, not continuous histories. Time-resolved cup-fines measurements remain a proposed input with unconfirmed availability. Pore-network and multidimensional continuum models are possible future extensions.



Continuum balance over an infinitesimal slice



Water-filled pore space

$$dM_m = \varepsilon c A dz$$

Mobile fines cross the slice boundaries by advection and dispersion.

Stationary coffee skeleton

$$dM_a = m_a A dz, \quad dM_d = m_d A dz$$


Release and capture exchange fines locally between water and skeleton.

The highlighted slice defines the continuum balance. It is not a numerical cell.

Presenter transcript

Consider an infinitesimally thin slice through the puck with cross-sectional area A and thickness dz . Within this volume, the water-filled pores contain mobile fines, while the stationary skeleton carries retained fines. Advection and dispersion act across the two axial boundaries. Release, capture and remobilization exchange fines locally between the two phases. Taking the slice thickness to zero gives the continuum equations. Finite-volume cells are a later numerical choice. Extraction chemistry is outside this model; its hydraulic relevance remains an assumption to assess.

Fines exchange locally and leave through the outlet



$$M_0 = M_a + M_m + M_d + M_{\text{sieve}} + M_{\text{cup}}.$$

$$M_a = A \int m_a \, dz, \, M_m = A \int \varepsilon c \, dz, \, M_d = A \int m_d \, dz.$$

Accounting domain: puck + basket + collected cup fines.



Presenter transcript

The global balance refers to a specific accounting domain: the entire puck, the fines retained by the basket, and the collected fines in the cup. Capital M denotes actual mass. In particular, mobile mass is the integral of epsilon times c over the puck; epsilon times c alone is a mass density. Local transfers cancel when the inventories are added. With clean inlet water and no creation or uncounted loss of fines, the total equals the initial fines mass.



Continuum equations and optional surface loading

$$\frac{\partial(\varepsilon c)}{\partial t} + \frac{\partial(qc)}{\partial z} = \frac{\partial}{\partial z} \left(\varepsilon D \frac{\partial c}{\partial z} \right) + R_{\text{rel}} - R_{\text{dep}} + R_{\text{wash}},$$

$$\frac{\partial m_a}{\partial t} = -R_{\text{rel}}, \quad \frac{\partial m_d}{\partial t} = R_{\text{dep}} - R_{\text{wash}}.$$

Equivalent surface description

$$m_a = \sigma c_a, \quad m_d = \sigma c_d, \quad [\sigma] = \text{m}^2/\text{m}_{\text{bulk}}^3, \quad [c_a] = [c_d] = \text{kg}/\text{m}^2.$$

Use $\partial_t(\sigma c_a)$ if the specific surface area changes.

Only mobile fines travel axially. All R terms have units $\text{kg}/(\text{m}_{\text{bulk}}^3 \text{ s})$.

Presenter transcript

These are the balance equations before choosing a grid or numerical method. The mobile phase gains fines from initial release and deposit remobilization, and loses fines by capture. Heiko's surface-loading formulation is equivalent: define sigma as accessible surface area per bulk volume and c_a as mass per unit surface. Then m_a equals sigma times c_a. If sigma changes, its derivative must remain inside the time derivative. The existing solver stores bulk mass densities; introducing measured surface area would clarify parameter interpretation without requiring a new conservation law.



Release and capture are constitutive hypotheses

Release of initially attached fines

$$R_{\text{rel}} = k_{\text{rel}} m_a (|q|/q_{\text{ref}})^{a_r}, \quad [k_{\text{rel}}] = \text{s}^{-1}.$$

Capture of mobile fines

$$R_{\text{dep}} = k_{\text{dep}} \chi(z) |q| c \left[1 - \frac{m_d}{m_{\text{cap}}} \right]_+, \quad [k_{\text{dep}}] = \text{m}^{-1}.$$

- Release depends on the remaining available inventory and flow.
- Capture depends on mobile flux and available deposit capacity.
- $\chi = 1$ is the unbiased baseline. Axial weighting needs evidence.
- Compare these laws using multiple flow rates and spatial deposit data.

Presenter transcript

These equations are closures, not consequences of mass conservation. The release law assumes that stronger flow increases the release rate and that the remaining available inventory limits release. The capture coefficient has units of inverse length because it multiplies a mass flux to give a volumetric rate. The capacity factor reduces capture as deposits accumulate. The optional axial weighting should not impose a basket-side blocking region without supporting evidence. We can replace these laws without changing the conservation framework.

Deposit remobilization and local pore accessibility

$$R_{\text{det}}^* = k_{\text{det}} m_d \left[\frac{G}{G_{\text{crit}}} - 1 \right]_+^b, \quad G = \left| \frac{\partial p}{\partial z} \right|.$$
$$R_{\text{wash}} = P_{\text{esc}} R_{\text{det}}^*, \quad P_{\text{esc}} = \frac{1}{1 + \exp[s(d_f/d_h - \lambda_c)]}.$$

- P_{esc} is an effective fraction entering the mobile phase locally.
- Unsuccessful mobilization remains in m_d in this coarse description.
- A mobile particle can be captured again before reaching the outlet.
- The logistic law is unvalidated. Compare with $P_{\text{esc}} = 1$.

Local remobilization does not imply arrival in the cup.



Presenter transcript


The word escape was ambiguous. Here it means local access to the flowing pore space after a deposit is disturbed. It does not mean escape from the entire puck. The model multiplies a potential detachment rate by an effective accessibility factor. The unsuccessful fraction remains in the deposit inventory; we do not resolve a separate detached-but-trapped state. Once mobile, fines can be captured again downstream. A mean hydraulic diameter is only a proxy for constrictions. The logistic law needs evidence and could be removed if it adds unidentifiable parameters.



The PSD is reduced to quantities used by the 1D closures

Measured bimodal PSD

- Fit a five-parameter mixture model.
- Choose a mobility cutoff d_{cut} .
- Estimate the fine fraction and its releasable share.
- Calculate representative fine and coarse diameters.



$f_{\text{fine}} + \text{releasable share} \rightarrow m_{a,0}, \quad d_f \rightarrow d_f/d_h, \quad d_{\text{eff}} \rightarrow d_{h,0} \text{ and structural baseline.}$

Source: Bora and Briesen, Journal of Food Process Engineering 49 (2026), e70645.

Presenter transcript

The particle-size distribution provides an estimate of the fine fraction and representative diameters. A diameter cutoff alone does not prove that every particle below it is releasable. An availability fraction or independent release measurement is needed to initialize m_a . The two curves are schematic. Specific surface area should preferably be measured or estimated consistently from the distribution and particle shape. A pore-network calculation could later help connect particle size to accessibility, but it is not a current data source.



Two alternative closures for the same permeability

Both closures supply K to Darcy’s law. They describe how deposits change resistance.

$$\varepsilon = \max(\varepsilon_0 - m_d/\rho_d, \varepsilon_{\min})$$

Kozeny–Carman: structural baseline

$$\frac{K}{K_0} = \left(\frac{\varepsilon}{\varepsilon_0}\right)^3 \left(\frac{1 - \varepsilon_0}{1 - \varepsilon}\right)^2$$

Relates permeability to porosity under fixed effective particle scale and Kozeny factor.

This simplified relation may miss changes in pore connectivity and localized plugging.

Exponential: empirical comparison

$$\frac{K}{K_0} = \exp\left(-\beta \frac{m_d}{m_{\text{cap}}}\right)$$

Assumes a direct sensitivity to deposit loading. β controls the imposed blockage strength.

Its form and coefficient were not derived from coffee measurements in this study.

The runs test closure sensitivity at identical K_0 . They do not validate either law.

Presenter transcript

These are alternative closures for the same permeability, and either can be used with Darcy flow. Kozeny-Carman is our structural baseline: the implemented ratio assumes fixed effective particle scale and Kozeny factor while porosity changes. The exponential relation instead assigns permeability directly from deposited mass. It was introduced as an empirical modeling assumption, not derived from our coffee measurements. Our comparison keeps initial permeability identical, so it tests the evolving relative permeability rather than independently predicting the initial permeability. Neither closure has been validated against the experiments. The displayed exponential results are retained as a sensitivity comparison.



Why the illustrative model used an exponential law

Motivation: represent strong blockage with a simple adjustable law

The hypothesis was that fines obstruct narrow flow paths, allowing a large resistance increase with a modest change in total porosity.

The exponential form stays positive and decreases smoothly. These useful mathematical properties do not establish physical validity.

m_d/m_{cap}	K/K_0 at $\beta = 5.5$
0	1
0.5	0.064
1	0.0041

An illustrative assumption

Neither the exponential law nor $\beta = 5.5$ was fitted to the coffee data or taken from a cited coffee study. Values shown are before any numerical lower bound.

Strong blockage is substantially imposed by this closure; it is not independent evidence of the mechanism.

Presenter transcript

The motivation for the exponential law was to allow strong resistance growth when fines obstruct narrow flow paths, even if the total void volume changes relatively little. That is a physical hypothesis, but the exponential equation itself does not resolve those paths. It was chosen for a simple, smooth, positive response with an adjustable coefficient. The coefficient 5.5 was illustrative and not fitted to our data or taken from a cited coffee study. At half the deposit capacity, the formula already reduces permeability to about 6.4 percent of its initial value. At full capacity it gives about 0.41 percent before numerical bounds. Thus the strong blockage in the original result is substantially imposed by the chosen closure. We should treat Kozeny-Carman as the structural baseline and the exponential law as an empirical sensitivity case until measurements can justify it.



Darcy flow and the permeability closure have different roles

Flow law: pressure gradient for a given superficial velocity

$$-\frac{\partial p}{\partial z} = \frac{\mu q}{K(z, t)}.$$

Structural closure: permeability of the evolving puck

$$K(z, t) = K_0(z) f_{\text{KC}}(\varepsilon(z, t)).$$

Total hydraulic resistance

$$\Delta p_{\text{puck}} = q \int_0^L \frac{\mu}{K(z, t)} \, dz.$$

Darcy and Kozeny–Carman are complementary. Forchheimer adds an optional inertial term to Darcy.

Presenter transcript

Darcy and Kozeny-Carman do different jobs. Darcy relates pressure gradient to flow through a material with permeability K . Kozeny-Carman estimates that permeability from structure. They are therefore used together. Forchheimer is an optional extension of the flow law when inertial pressure loss becomes relevant. A pore-network model can also supply permeability for Darcy flow; using PNM does not itself require Forchheimer. The integral gives the total puck resistance for the one-dimensional approximation.

Darcy gives practically the same results

We ran the same case twice, changing only the flow law.

Result at 60 s	Darcy–Forchheimer	Darcy
Pressure [bar]	8.9906	8.9906
Flow rate [mL/s]	0.04535	0.04535
Cup fines [g]	0.03993	0.03993

Values rounded for display.

Across the entire simulation, the largest pressure difference was only **0.0203 Pa**.

We therefore use Darcy for this tested case.

Controlled 60 s simulations with identical exponential permeability, kinetics and PI settings.



Presenter transcript

We ran the same case twice, changing only the flow law. One run includes the Forchheimer inertial term and the other uses Darcy alone. The permeability closure, initial state, kinetics and PI controller settings are identical. At sixty seconds, pressure, flow rate and collected cup fines are the same to the precision displayed in the table. They are not mathematically identical: the values have been rounded. Across the entire simulation, the largest pressure difference is only 0.0203 pascals. We therefore choose Darcy for this tested case because including inertia makes no meaningful difference to these predictions.

Operating conditions and basket resistance



$$\Delta p_{\text{total}} = \Delta p_{\text{puck}} + Q R_s, \quad \dot{M}_{\text{cup}} = (1 - \eta_s) A q c(L, t).$$

- R_s describes basket pressure loss. η_s describes fines retention.
- Prescribed pressure or flow is sufficient for controlled boundary conditions.
- PI mode reproduces a machine response only after characterizing that machine.

$$e = p_{\text{set}} - p, \quad Q_{\text{cmd}} = \text{clip} \left(Q_{\text{ff}} + K_P e + K_I \int e dt, 0, Q_{\text{max}} \right).$$

PI has no derivative term. Identify K_P , K_I , pump lag and flow cap independently.

Presenter transcript

Basket retention and basket hydraulic resistance are different effects. The resistance determines its pressure drop, while eta determines how much of the exiting fines mass stays in the basket. A constant-pressure experiment does not need a controller model. For a measured machine transient, either impose the measured boundary history or characterize the controller. This implementation uses PI, not PID, plus a pump lag and flow cap. Its gains are illustrative unless independently determined. Basket loading does not yet change basket resistance.



Boundary conditions for clean feed and an open outlet

$$J = qc - \varepsilon D \partial_z c$$

Inlet: no fines supplied

$$J(0, t) = qc_{\text{in}} = 0$$

The feed is clean water. We prescribe the total incoming fines flux.

This does not require imposing both $c = 0$ and $\partial_z c = 0$ on the interior solution.

In the code, boundary dispersive fluxes are omitted; inlet total flux is zero and outlet flux is qc . Reconsider this closure if downstream mixing or back-dispersion matters.

Outlet: convective removal

$$\partial_z c(L, t) = 0, \quad J(L, t) = qc(L, t)$$

We neglect dispersive exchange with the downstream basket/cup region.


This open-outlet approximation allows fines to leave by advection, without a modeled downstream concentration field.

Presenter transcript

The clean-water inlet supplies no fines, so we specify zero total incoming fines flux. This is a flux boundary condition; it does not mean imposing both zero concentration and zero concentration gradient on the interior solution. At the outlet, we neglect dispersive exchange with the downstream region and let advection carry fines out. The code omits the dispersive contribution at boundary faces. These choices close the truncated puck domain without modeling a downstream concentration field. They are assumptions, not a requirement of finite volumes. If downstream mixing or back-dispersion affects the result, the boundary model must be revisited. Initial fines fields remain necessary, and basket resistance sets the outlet pressure relative to the cup.



The finite-volume method enforces flux balance cell by cell



$$\frac{(\varepsilon C)_i^{n+1} - (\varepsilon C)_i^n}{\Delta t} = - \frac{F_{i+1/2} - F_{i-1/2}}{\Delta z} + R_{\text{rel},i} - R_{\text{dep},i} + R_{\text{wash},i}.$$

$$F_{i+1/2} = \underbrace{q c_i}_{\text{advection}} - \underbrace{\varepsilon_{i+1/2} D \frac{c_{i+1} - c_i}{\Delta z}}_{\text{dispersion}}, \quad q \geq 0.$$

First-order upwind advection and centred dispersion. No high-order flux limiter.

Shared face fluxes cancel between adjacent cells, preserving the global mass balance.

Presenter transcript

Finite volumes balance the fines inventory in each cell through shared face fluxes. The flux that leaves one cell enters its neighbor, so interior exchanges cancel in the global sum. The code uses first-order upwind advection and centered dispersion. It does not need a high-order advection flux limiter, but numerical diffusion can smear steep concentration fronts. We therefore assess spatial refinement. Positivity-preserving local reaction transfers are a separate issue from transport flux limiting. The next slide explains how the timestep is selected.

The smallest timescale limits the numerical step

$$\Delta t = \min(\Delta t_{\max}, \Delta t_{\text{transport}}, \Delta t_{\text{pump}}, t_{\text{end}} - t)$$

$$\Delta t_{\text{transport}} = \frac{0.42}{|q|/(\varepsilon_{\min}\Delta z) + 2D/\Delta z^2}$$

Limit	Purpose
$\Delta t_{\max}$	User-selected upper bound for temporal resolution.
$\Delta t_{\text{transport}}$	Combined explicit advection–dispersion restriction. Here $\varepsilon_{\min} = \min_i \varepsilon_i(t)$.
$\Delta t_{\text{pump}} = \tau_p/4$	Used only in PI mode to resolve pump response; this is not the PI integral time.
$t_{\text{end}} - t$	Stops exactly at the requested final time.

For $D = 0$: $\text{Co} = |q|\Delta t/(\varepsilon_{\min}\Delta z) \leq 0.42$. Timestep refinement still checks accuracy of kinetics and coupling. The transport bound is the implemented estimate, not a general heterogeneous-field proof.



Presenter transcript

The solver takes the smallest of four limits. The user maximum controls the largest permitted step. The transport estimate combines advection at the largest pore velocity with explicit dispersion and uses a safety factor of 0.42. In PI mode, another bound takes one quarter of the pump response time. This resolves the actuator response and is not a bound based on the PI integral time. The remaining simulation time prevents overshooting the endpoint. Exponential local transfers preserve nonnegative inventories, but this does not guarantee temporal accuracy of their coupling. Timestep refinement remains necessary, and strong porosity variation warrants checking the transport estimate against the actual face coefficients.



Why finite volumes for fines transport?

The main requirement is consistent mass accounting

- Each cell stores a fines inventory and exchanges mass through its faces.
- One shared face flux leaves one cell and enters the next.
- Summing the cells cancels internal fluxes; boundary fluxes give collected fines.
- Local release, capture and remobilization transfer mass between inventories.

Alternative	Assessment for this model
Finite differences	Equally viable in conservative flux form; on a uniform grid, they can give the same update.

FVM is a transparent first implementation. Its first-order upwind diffusion requires grid refinement.

Presenter transcript

We chose finite volumes because shared face fluxes make local and global fines mass accounting explicit. Mass leaving one cell enters its neighbor, and the outlet flux determines collected fines. Conservative finite differences can be equally appropriate and can yield the same update on a uniform grid. FVM is therefore a transparent implementation choice rather than the only valid method. First-order upwind transport adds numerical diffusion, so grid refinement is still necessary.



Pressure follows the current state algebraically

Quasi-steady hydraulic approximation

$$q(t) = Q(t)/A, \quad p(z, t) = QR_s + q \int_z^L \frac{\mu}{K(\zeta, t)} d\zeta.$$

- Flow mode supplies $Q(t)$ directly.
- Pressure mode gives

$$Q = \frac{\Delta p_{\text{total}}}{R_s + (1/A) \int_0^L \mu/K dz}.$$

- PI mode evolves the pump state and uses the same resistance relation.


No additional fluid momentum state is integrated. Fines and machine states can still evolve in time.

Presenter transcript

This is not an artificial numerical separation. The model assumes that hydraulic adjustment is fast enough to neglect a fluid momentum transient. At each time, the current permeability determines the pressure-flow relation. In pressure mode, total resistance gives flow directly. In flow mode, the same resistance gives pressure. PI mode additionally evolves the machine state. Uniform superficial velocity also neglects fluid-volume displacement from porosity changes. This assumption needs assessment if those volume changes become appreciable; exact transient fluid continuity would include storage.



Coupled physics and its numerical update



Presenter transcript

The feedback is physical: deposits change resistance, resistance changes flow and pressure gradients, and these alter fines transport and transfer. The equations define this coupling regardless of how we solve them. The code evaluates dependencies in a sequence during each timestep. That numerical ordering introduces discretization error and should be checked by timestep refinement.

Physical coupling: deposit changes ϵ , K and d_h ; these change pressure and flow; the new hydraulics then alter release, deposition and washout.

Quasi-steady flow is a physical assumption. Update ordering is a numerical choice.

Calibration begins with independently measured structure



Input	Measurement or proposed inference
Geometry and fluid	Puck height and area, temperature-dependent viscosity and density.
PSD and available fines	Fine fraction, representative sizes and an independently constrained releasable share.
Initial structure	CT porosity and heterogeneity. Accessible specific surface σ with resolution uncertainty.
Hydraulics	Low-flow pressure–flow slope for K_0 , empty-basket loss for R_s .
Future pore net-works	Connectivity-sensitive permeability and capture/accessibility closures.

CT-derived hydraulic diameter is a structural proxy, not a direct measurement of every pore throat.

Presenter transcript

We should determine as much as possible independently before fitting the kinetics. Geometry and fluid properties are straightforward inputs. PSD informs fine mass and representative sizes, but the releasable fraction needs separate attention. CT gives porosity and spatial variation, while surface area is sensitive to image resolution and segmentation. Low-flow pressure-flow data constrain permeability. Pore-network calculations could later provide connectivity-sensitive closures. We should not present those future results as available measurements.



Experiments to distinguish competing kinetic models

- Fines collected in time intervals at several flows constrain release and capture.
- Interrupted CT locates retained material and redistribution.
- Pressure pulses test deposit remobilization and threshold behavior.
- Outlet size distributions test size selectivity.
- Basket-retained mass separates puck transport from cup collection.


Model comparisons One versus two retained populations; accessibility factor versus $P_{\text{esc}} = 1$; uniform capture versus axial weighting.

These are proposed experiments and comparisons. Validate on withheld pucks or grind settings.

Presenter transcript

The experiments should distinguish mechanisms rather than merely provide more fitting points. Time-resolved fines at several flow rates help separate release from capture. Interrupted CT provides spatial evidence that cup mass alone cannot supply. Pressure pulses probe remobilization. We should explicitly compare a simpler one-inventory model with the two-inventory model, and test whether the accessibility factor is needed. These are proposed measurements. Their availability has not been established, and the final evaluation should use withheld cases.

The illustrative case develops strong viscous blockage



At 60 s

- total pressure: 8.99 bar;
- flow: 0.045 mL/s;
- minimum K/K_0 : 0.0126.

Interpretation

The PI controller approaches 9 bar while the increasing puck resistance strongly reduces flow.


New Darcy run: exponential permeability, PI control. Illustrative parameters, no experimental calibration.

Presenter transcript

These are the new Darcy results with the exponential permeability law and PI controller. A separate Kozeny-Carman run follows in the comparison slides. At 60 seconds the pressure is about 8.99 bar, while flow falls to about 0.045 milliliters per second. The lowest local permeability is about 1.26 percent of its reference value. This shows how the implemented feedback can generate blockage, but the magnitude is strongly closure-dependent and is not an experimentally validated prediction.



The model distinguishes puck washout from fines in the cup



Cumulative masses

- puck outlet: 0.0614 g;
- basket retained: 0.0215 g;
- cup: 0.0399 g.

With $\eta_s = 0.35$, the basket retains 35% of the fines that leave the puck.


Presenter transcript

The fines leaving the puck are divided between the basket and the cup. In the new Darcy example, roughly 0.0614 grams leaves the puck, 0.0215 grams stays at the basket and 0.0399 grams reaches the cup. The split follows directly from the configured constant retention fraction of 35 percent. Cup mass therefore cannot be interpreted as all the fines mobilized inside the puck, or even all the fines leaving it. Some released material remains or is recaptured upstream.

New Darcy run with exponential permeability; constant basket retention.



The axial fields locate the effective blocking region



These fields can be compared with interrupted CT reconstructions, but a 1D layer cannot represent lateral channel geometry.


New Darcy run with exponential permeability. Closure comparison follows.

Presenter transcript

These fields show axial deposition and relative permeability in the new Darcy example. They identify an effective region of high resistance within the assumed one-dimensional model. A strong axial weighting in a capture closure could influence this pattern, so we must check it against CT rather than treat it as an independently predicted location. Radial clusters and bypass paths remain unresolved. An especially useful next comparison is between internal redistribution with little outlet mass and sustained transport out of the puck.



Permeability closure strongly changes the flow response



At 60 s

Exponential:
 $Q = 0.0454 \text{ mL/s}$

Kozeny–Carman:
 $Q = 0.892 \text{ mL/s}$

Both Darcy runs approach
the 9 bar PI target.

The closure changes resistance and flow, even with nearly the same final pressure.


Same initial K_0 , kinetics and machine parameters. Gray and blue curves overlap: inertia is negligible.

Presenter transcript

The blue Darcy-exponential curve overlaps the gray Forchheimer reference. The orange curve changes only the permeability closure to Kozeny-Carman. At sixty seconds the flow is about 0.892 milliliters per second, compared with 0.0454 for exponential permeability. Both PI-controlled cases end near nine bar, so pressure alone hides a substantial difference in resistance and flow. This illustrates why simultaneous pressure and flow measurements are needed. All rates and controller settings were kept unchanged.



Kozeny–Carman predicts weaker permeability loss



Minimum K/K_0

Exponential:
0.0126

Kozeny–Carman:
0.723

The same deposit-to-porosity
law feeds both closures.

The exponential law imposes stronger blockage. The comparison does not establish which closure is correct.


Final profiles at 60 s. Coupled deposit fields also differ because flow feeds back on kinetics.

Presenter transcript

The exponential law produces a minimum relative permeability of about 0.0126. The implemented Kozeny-Carman relation gives about 0.723. The latter therefore predicts much weaker permeability loss for this material-state closure. These are coupled runs: different flow also produces different deposit profiles. The result identifies strong sensitivity to the structural closure, but does not establish which law is physically right. We must compare with measured hydraulic and structural changes rather than tune one closure to match the other.



The permeability closure also changes cup fines



Cup fines at 60 s

Exponential:
0.0399 g

Kozeny–Carman:
0.3466 g

Same basket retention:
 $\eta_s = 0.35$.

This is closure sensitivity, not validation. Neither prediction is an experimental target.

All kinetic and machine parameters held fixed. No fitting to reproduce the exponential-law result.

Presenter transcript

Cumulative cup fines increase from about 0.0399 grams for exponential permeability to about 0.3466 grams for Kozeny-Carman. The basket retention fraction remains 35 percent in both. Higher sustained flow changes release and transport, which changes the collected mass even though the kinetic coefficients are identical. This is a sensitivity result using illustrative inputs. Neither simulated curve is a substitute for experimental calibration and withheld-case validation.



Numerical verification and physical validation

Verification

- Conservation and nonnegative inventories.
- Analytical hydraulic limiting cases.
- Grid and timestep convergence.
- Controller limits and boundary accounting.

Validation

- Pressure and flow measurements.
- CT structural changes.
- Collected fines and size distributions.
- Predictions for withheld cases.

Current unit tests: 15/15 passed. All three comparison runs conserve fines mass to relative error below 1.4×10^{-15} . Physical validation remains outstanding.

Presenter transcript

The current fifteen unit tests pass. All three comparison runs also pass the mass-conservation and nonnegative-mobile-inventory checks, with relative mass errors below 1.4 times ten to the minus fifteen. The comparison script verifies that only the intended switches differ and that all output times align. These checks support numerical consistency. They do not validate the permeability or fines transfer closures against experiments.



Next comparison: redistribution versus washout

Retained redistribution Fines release and move, but deposition elsewhere in the puck dominates. CT changes while cumulative outlet mass stays small.

Net washout Mobile fines reach the puck outlet. Basket retention and cup collection quantify the outgoing mass.

Proposed study

- Compare pressure or flow levels with the same initial puck structure.
- Record M_a , M_m , M_d and M_{out} with axial deposit profiles.
- Darcy is sufficient here. Compare both permeability predictions with data.
- Use PNM or 2D/3D only where pore connectivity or radial bypass demands it.

Presenter transcript

Heiko suggests a particularly useful target: conditions where fines move internally but remain trapped, compared with conditions where they leave the puck. Low cup mass alone cannot distinguish no release from release followed by recapture. We need both the inventory history and spatial deposit changes. The closure study is complete. We should next compare operating levels and test the competing closure predictions against measurements. More detailed pore networks or multidimensional models should answer a demonstrated limitation rather than be assumed prerequisites.

References and model documentation



- M. Bora and H. Briesen, “Characterization of Bimodal Particle Size Distribution of Ground Coffee Powder,” *Journal of Food Process Engineering*, 49, e70645, 2026. doi:10.1111/jfpe.70645
- S. Ergun, “Fluid Flow through Packed Columns,” *Chemical Engineering Progress*, 48, 89–94, 1952.
- FineFlow–Espresso technical report, Python solver, named-case configuration and automated verification suite accompanying this presentation.

Presenter transcript

The technical report and solver define the underlying model. The new comparison script saves all three parameter snapshots, time histories, spatial fields and differences. Darcy is now the default flow law and the fine-puck configuration uses it. Forchheimer and Kozeny-Carman remain available. The main illustrative results use Darcy with exponential permeability, followed by the separate Kozeny-Carman sensitivity results. Physical validation remains open.