

**KEMENTERIAN PENDIDIKAN TINGGI
JABATAN PENDIDIKAN POLITEKNIK DAN KOLEJ KOMUNITI
POLITEKNIK KUCHING SARAWAK
JABATAN TEKNOLOGI MAKLUMAT DAN KOMUNIKASI**

**CLOUD BASED HIGH AVAILABILITY
ROOM RENTAL SYSTEM
(POLISEWA)**

PREPARED BY:

AHMAD SYARIFUDDIN BIN MOHD BAHARUDIN (05DIT24F1070)

ABDUL KHALIL BIN HARMEZI (05DIT24F1034)

JOSH ALZON ANAK JACKSON (05DIT24F1111)

PREPARED FOR:

SIR HASBULLAH BIN ABDULLAH

Project Supervisor

**DIPLOMA IN INFORMATION TECHNOLOGY
POLITEKNIK KUCHING SARAWAK
SESSION 1: 2026/2027**

DECLARATION

We hereby declare that this project report entitled "**Cloud Based High Availability Room Rental System (PoliSewa)**" is submitted to the Department of Information and Communication Technology, Politeknik Kuching Sarawak, in partial fulfillment of the requirements for the award of the **Diploma in Information Technology**.

We confirm that this report is the result of our own investigation and work, except where specific citations and references have been made. We also certify that this work has not been accepted or submitted concurrently in substance for any other diploma or degree at this or any other higher educational institution.

**AHMAD SYARIFUDDIN BIN MOHD
BAHARUDIN**

Matric No: 05DIT24F1070

Date: 16 September 2026

ABDUL KHALIL BIN HARMEZI

Matric No: 05DIT24F1034

Date: 16 September 2026

JOSH ALZON ANAK JACKSON

Matric No: 05DIT24F1111

Date: 16 September 2026

APPROVAL FOR SUBMISSION

This final year project report entitled "**Cloud Based High Availability Room Rental System (PoliSewa)**" has been prepared and submitted by Ahmad Syarifuddin bin Mohd Baharudin (05DIT24F1070), Abdul Khalil bin Harmezi (05DIT24F1034), and Josh Alzon Anak Jackson (05DIT24F1111) in partial fulfillment of the requirements for the Diploma in Information Technology at Politeknik Kuching Sarawak.

I have examined this report and verified that it conforms to the required academic standards and guidelines established by the Department of Information and Communication Technology.

SIR HASBULLAH BIN ABDULLAH

Project Supervisor
Department of Information and
Communication Technology
Politeknik Kuching Sarawak
Date: 16 September 2026

ACKNOWLEDGMENTS

Alhamdulillah, all praises and gratitude are dedicated to Allah S.W.T. for providing us with the health, strength, patience, and perseverance required to successfully plan, develop, and document our Final Year Project.

First and foremost, we would like to express our highest appreciation and heartfelt gratitude to our academic supervisor, **Sir Hasbullah bin Abdullah**. His continuous encouragement, insightful architectural advice, patient guidance, and technical scrutiny were essential in guiding us from the conceptual design phase through to cloud high availability deployment and testing.

We also express our sincere gratitude to the Head of Department, FYP coordinators, and all lecturers in the **Department of Information and Communication Technology, Politeknik Kuching Sarawak**, for imparting the technical knowledge, software engineering fundamentals, and cloud concepts that enabled the execution of this project.

Our profound appreciation goes to our beloved parents and family members whose unwavering moral encouragement, prayers, and sacrifices have been our pillars of motivation. Lastly, we thank our fellow classmates and student testers at Politeknik Kuching Sarawak whose feedback helped refine PoliSewa into an accessible, student-friendly platform.

ABSTRACT

Securing safe, affordable, and geographically suitable off-campus accommodation represents a persistent challenge for students attending Politeknik Kuching Sarawak (PKS) in Matang, Kuching. Currently, students depend heavily on fragmented social media platforms such as Facebook groups, TikTok videos, and transient WhatsApp chats. These informal mechanisms lack structure, provide no spatial context regarding campus distance, and expose students to significant rental deposit fraud. Simultaneously, educational institutions hosting web platforms face severe server downtime during peak semester registration periods when thousands of students access the portal concurrently, as traditional single-server hosting suffers from single points of failure.

To overcome these challenges, this project presents **PoliSewa: A Cloud Based High Availability Room Rental System**. The application tier integrates an interactive Leaflet.js map engine, automated geodesic distance calculation to the PKS campus using the Haversine algorithm, student-centric budget filtering (< RM300/month), a 6-digit email One-Time Password (OTP) verification module via Nodemailer, and direct landlord WhatsApp click-to-chat redirection. At the cloud infrastructure tier, PoliSewa deploys an active-active dual Virtual Machine (VM) architecture on Microsoft Azure (VM1 and VM2 in the Malaysia West region) connected to an Azure SQL Database and balanced via Cloudflare Zero Trust Tunnels.

Empirical failover testing demonstrates that when the primary VM process is forcefully terminated (`pm2 stop polisewa`), Cloudflare automatically routes all inbound traffic to the standby VM connector within milliseconds without presenting HTTP 502/504 gateway errors to users. A comprehensive Azure Cost Management analysis reveals that this dual-node high availability architecture is highly cost-effective, incurring a total operational cost of approximately RM 156.70 per month. PoliSewa successfully provides a resilient, secure, and continuously accessible room rental directory tailored to the polytechnic student community.

Keywords: High Availability (HA), Microsoft Azure, Cloudflare Zero Trust Tunnels, Leaflet.js, Dual Virtual Machines, Room Rental Directory, Politeknik Kuching Sarawak.

ABSTRAK

Mendapatkan bilik atau rumah sewa luar kampus yang selamat, berpatutan, dan berdekatan merupakan cabaran utama bagi para pelajar Politeknik Kuching Sarawak (PKS) di Matang, Kuching. Pada masa kini, pelajar bergantung kepada perkongsian media sosial yang tidak tersusun seperti kumpulan Facebook, video TikTok, dan perkongsian WhatsApp. Kaedah ini tidak mempunyai pengindeksan berpusat, tidak menyediakan ukuran jarak perjalanan ke kampus, serta mendedahkan pelajar kepada risiko penipuan wang deposit sewaan. Pada masa yang sama, laman web konvensional yang dihoskan pada pelayan tunggal sering mengalami gangguan perkhidmatan (*downtime*) semasa lonjakan trafik pendaftaran semester baharu.

Bagi menyelesaikan masalah ini, projek ini membangunkan **PoliSewa: Sistem Sewaan Bilik Berasaskan Awan dengan Ketersediaan Tinggi (High Availability - HA)**. Lapisan aplikasi menggabungkan peta interaktif Leaflet.js, pengiraan automatik jarak geodesik ke kampus PKS menggunakan formula Haversine, penapis harga bilik mesra pelajar (< RM300/sebulan), modul pengesahan emel OTP 6-digit melalui Nodemailer, serta integrasi pautan terus WhatsApp ke pemilik rumah. Pada lapisan infrastruktur awan, PoliSewa mengimplementasikan dwi-Mesin Maya (Dual Virtual Machines - VM1 dan VM2) di Microsoft Azure (rantau Malaysia West) yang disambungkan ke Azure SQL Database dan diimbangi beban trafiknya melalui Cloudflare Zero Trust Tunnels.

Ujian kegagalan (*failover testing*) membuktikan bahawa apabila proses pelayan utama dimatikan secara simulasi (`pm2 stop polisewa`), Cloudflare mengalihkan trafik pengguna ke pelayan sandaran dalam masa beberapa milisaat tanpa sebarang ralat pelayan (kekal 100% HTTP 200 OK). Analisis Pengurusan Kos Azure menunjukkan bahawa seni bina ketersediaan tinggi ini sangat menjimatkan kos, dengan jumlah perbelanjaan awan sebanyak RM 156.70 sebulan. PoliSewa terbukti berupaya menyediakan perkhidmatan direktori sewa yang selamat, pantas, dan sentiasa beroperasi untuk warga Politeknik Kuching Sarawak.

Kata Kunci: Ketersediaan Tinggi (HA), Microsoft Azure, Cloudflare Zero Trust Tunnels, Leaflet.js, Dwi-Mesin Maya, Direktori Rumah Sewa, Politeknik Kuching Sarawak.

TABLE OF CONTENTS

Declaration	2
Approval for Submission	3
Acknowledgments	4
Abstract	5
Abstrak	6
List of Figures	9
List of Tables	11
CHAPTER 1: INTRODUCTION	12
1.0 Introduction	12
1.1 Problem Statement	12
1.2 Project Scope	13
1.3 Aim and Objectives	14
1.4 Methodology (Agile SDLC)	14
1.5 Significance of the Project	15
1.6 Project Schedule (Gantt Chart)	15
1.7 Cost Planning & Actual Azure Cloud Expenditure Analysis	15
CHAPTER 2: LITERATURE REVIEW	18
2.0 Introduction	18
2.1 High Availability and Cloud Fault Tolerance Models	18
2.2 Student Rental Portals and Scam Prevention Studies	19
2.3 Cloud Infrastructure, Redundancy, and Load Balancing	20
2.4 Comparative Analysis of Existing Systems vs. PoliSewa	20
2.5 Chapter Summary	21
CHAPTER 3: ANALYSIS AND DESIGN	22
3.0 Introduction	22
3.1 Requirement Analysis	22
3.2 High Availability System Architecture	23
3.3 Data Flow Diagrams (DFD)	25
3.4 Database Design	26
3.5 User Interface (UI/UX) Design	28
3.6 Chapter Summary	29
CHAPTER 4: IMPLEMENTATION	30
4.0 Introduction	30
4.1 Cloud Infrastructure Deployment	30
4.2 Application Code Development	33

4.3 Chapter Summary	35
CHAPTER 5: TESTING AND VERIFICATION	36
5.0 Introduction	36
5.1 Cloud High Availability and Failover Testing	36
5.2 Software Functional Testing	39
5.3 User Scenario Walkthroughs	43
5.4 Test Results Summary	44
5.5 Chapter Summary	44
CHAPTER 6: CONCLUSION AND FUTURE WORKS	45
6.0 Introduction	45
6.1 Objective Achievement Review	45
6.2 Challenges and Problem Solving	45
6.3 Future Works and Enhancements	46
6.4 Conclusion	46
REFERENCES	47

LIST OF FIGURES

Figure 1.4(a): Agile Software Development Life Cycle (SDLC) Workflow for PoliSewa	9
Figure 1.6(a): Project Development Schedule (Gantt Chart)	9
Figure 1.7(a): Azure Subscription Cost Analysis & Accumulated Spend	9
Figure 1.7(b): Azure Resource-Level Cost Breakdown & Infrastructure Inventory	9
Figure 3.2.1(a): High Availability Dual VM Cloud Architecture Block Diagram	9
Figure 3.2.2(a): Cloudflare Tunnel Health Check and Automatic Failover Flowchart	9
Figure 3.3.1(a): Level-0 Context Diagram of PoliSewa	25
Figure 3.4.1(a): Entity-Relationship Diagram (ERD) of PoliSewa Database	9
Figure 3.5.1(a): User Interface Wireframe: Desktop Split-Screen and Mobile Bottom Sheet Layout	9
Figure 4.1.1(a): Azure Resource Group Overview ('polisewa')	9
Figure 4.1.1(b): Dual Azure Virtual Machines (VM1 & VM2) Running Status	9
Figure 4.1.2(a): Cloudflare Edge Routing and Gateway Status Verification	9
Figure 4.1.3(a): Azure SQL Database Overview and Whitelisted Firewall Rules	9
Figure 4.1.4(a): Virtual Machine Linux Host Console and Git Deployment	9
Figure 4.2.2(a): Geodesic Haversine Distance Calculation Source Code	9
Figure 4.2.3(a): 6-Digit OTP Generator and Nodemailer SMTP Source Code	9
Figure 4.2.5(a): WhatsApp Pre-Filled URL Construction Source Code	9
Figure 5.1.1(a): Cloudflare Connector 1 and Connector 2 Healthy Status	9
Figure 5.1.2(a): Simulated VM1 Service Termination in Terminal ('pm2 stop polisewa')	9
Figure 5.1.2(b): Uninterrupted HTTP 200 OK Response via Connector 2 in Browser DevTools	9
Figure 5.1.3(a): Azure SQL Query Execution and Data Consistency Check	9
Figure 5.2.1(a): Interactive Leaflet Map with PKS Landmark and Rental Markers	9
Figure 5.2.2(a): Live Keyword Search and Price Filtering (< RM300) with Distance Badges	39
Figure 5.2.3(a): 6-Box Email OTP Verification Dialog with Cooldown Timer	9
Figure 5.2.3(b): PoliSewa OTP Verification Email Received in Gmail Inbox	9
Figure 5.2.4(a): Landlord Property Creation Modal with Pinpoint Coordinate Binding	9
Figure 5.2.5(a): Property Listing Card with Direct WhatsApp Contact and Verified Badge	9
Figure 5.2.6(a): Permanent Account Deletion Confirmation Dialog	9
Figure 5.3.1(a): Student User Workflow: Room Discovery and Geodesic Distance Verification	9
Figure 5.3.2(a): Family Member Review Workflow: Room Facility Inspection	10

LIST OF TABLES

Table 1.7(a): Estimated vs. Actual Monthly Cloud Infrastructure Cost	15
Table 2.4(a): Comparative Analysis Matrix of Rental Systems	20
Table 3.1.1(a): Server and Client Hardware Requirements	22
Table 3.1.2(a): Software Stack and Development Technologies	22
Table 3.4.2(a): Data Dictionary for 'users' Table	26
Table 3.4.2(b): Data Dictionary for 'properties' Table	27
Table 5.4(a): Comprehensive Functional Black-Box Test Results Matrix	39
Table 6.1(a): Project Objectives Achievement Verification Matrix	41

CHAPTER 1: INTRODUCTION

1.0 Introduction

In today's digitalized educational landscape, tertiary institutions increasingly adopt web-based systems to manage student processes efficiently. However, off-campus student accommodation management remains critically underserved. At Politeknik Kuching Sarawak (PKS), located along Jalan Matang in Kuching, Sarawak, the majority of senior and out-of-town students reside in off-campus rental housing across areas such as Taman Sri Matang, Kampung Gita, Matang Jaya, and Petra Jaya.

Despite the critical necessity of safe housing, the room rental discovery process continues to rely upon unorganized, informal mechanisms including printed flyers, word-of-mouth recommendations, and unstructured posts on social media platforms such as Facebook groups, TikTok, and WhatsApp chats. These channels lack centralized organization, provide no geographic proximity context, and leave students vulnerable to fraud. Furthermore, when polytechnic student bodies attempt to host centralized web portals, they traditionally deploy them on basic single-server architectures. During peak academic intake windows—specifically the onset of semester registration—thousands of students access the portal concurrently. These traffic surges overwhelm single servers, resulting in catastrophic downtime, connection timeouts, and service unavailability when students need it most.

To overcome these dual challenges of information fragmentation and server vulnerability, this project introduces **PoliSewa: A Cloud Based High Availability Room Rental System**. PoliSewa provides an interactive, map-centric web directory tailored specifically for PKS students while implementing an enterprise-grade cloud architecture featuring active-active dual Virtual Machines on Microsoft Azure, Cloudflare Zero Trust load balancing, and automated database replication.

1.1 Problem Statement

1.1.1 Scattered Rental Information Across Social Media

Off-campus rental advertisements are scattered across disjointed digital silos, including various Facebook rental groups, Instagram stories, TikTok clips, and transient WhatsApp chat groups. Consequently, students waste substantial hours searching for listings, frequently encounter expired advertisements for rooms that have already been rented, and fail to secure accommodations before academic sessions commence.

1.1.2 Data Reliability and Backup Deficiencies

Informal rental methods and legacy student platforms do not implement automated data backups or standardized transaction logs. If an administrator's machine or single host server experiences filesystem corruption or hardware failure, room listings, landlord contacts, and booking histories are permanently lost. The lack of a structured disaster recovery mechanism severely undermines data integrity.

1.1.3 Server Downtime and Single Point of Failure

Conventional student portals rely on a single web server and an un-replicated local database. During new intake cycles, concurrent requests cause severe CPU exhaustion and memory bottlenecks. A single process crash or infrastructure maintenance window takes the entire platform offline. Educational institutions lack fault-tolerant systems capable of surviving server outages without disrupting students.

1.2 Project Scope

1.2.1 System Scope

- **Dual Virtual Machine Infrastructure:** Deployment of two independent Linux Virtual Machines (VM1 and VM2) on Microsoft Azure (Malaysia West region) running Node.js / Express web services managed via PM2.
- **Cloudflare Zero Trust Load Balancing & Failover:** Routing of domain traffic (polisewa.me) through dual Cloudflare Tunnel connectors ([cloudflared](https://cloudflared.com)) to distribute requests and execute sub-second failover if any VM terminates.
- **Centralized Azure SQL Database:** Cloud-hosted relational database storing user records, hashed authentication credentials, property details, and coordinates, with automated backups and firewall whitelisting.
- **Interactive Web Application:** Single-page responsive interface utilizing Leaflet.js, OpenStreetMap geospatial boundaries (boundary.js), Haversine geodesic distance calculation, 6-digit email OTP verification via Nodemailer Gmail SMTP, and WhatsApp click-to-chat redirection.

1.2.2 User Scope

- **Polytechnic Students:** Primary users who search for rental rooms, apply budget and distance filters, inspect property photo galleries, and initiate verified WhatsApp inquiries to landlords.
- **Family Members:** Parents and guardians assisting students in evaluating property amenities, security, pricing, and campus distance.
- **Property Owners (Landlords):** Registered and OTP-verified property owners who manage room listings, upload multiple unit photos, update rental rates, and

receive pre-filled WhatsApp inquiries.

- **System Administrators:** Authorized personnel managing Azure cloud resources, monitoring Cloudflare tunnel health, and auditing listings to prevent scams.

1.3 Aim and Objectives

The overarching aim of this project is to design, develop, and deploy a secure, fault-tolerant, cloud-based student room rental directory for Politeknik Kuching Sarawak. The specific measurable objectives are:

1. **Develop a Centralized Room Rental Platform:** To design and implement a responsive, map-based web application that allows PKS students and families to search, filter by price (< RM300), calculate distance to campus, and contact landlords via WhatsApp.
2. **Enhance Data Protection:** To implement automated cloud database management using Azure SQL Database with strict firewall controls, transaction integrity, and automated daily backups to eliminate data loss.
3. **Implement High Availability Cloud Infrastructure:** To configure a multi-node cloud environment on Microsoft Azure using dual Virtual Machines and Cloudflare Tunnel load balancing, ensuring zero-downtime failover during server maintenance or crashes.

1.4 Methodology (Agile SDLC)

To accommodate iterative refinement and rigorous failover testing, this project utilizes the **Agile Software Development Life Cycle (SDLC)** methodology (*Pressman & Maxim, 2020*). Agile facilitates continuous feedback loops across five structured phases:

- **Phase 1: Requirement Analysis:** Gathering student accommodation needs, identifying pain points in Matang, defining functional specifications, and creating Level-0 and Level-1 Data Flow Diagrams (DFDs).
- **Phase 2: System Design:** Architecting the dual-VM cloud topology, configuring Cloudflare ingress rules, modeling the relational database schema, and producing UI/UX wireframes.
- **Phase 3: Development:** Iterative front-end coding (HTML5, CSS3, Leaflet.js), back-end REST API construction (Node.js/Express), and cloud provisioning on Microsoft Azure.
- **Phase 4: Testing:** Executing unit tests, black-box functional tests, user acceptance testing (UAT), and cloud failover simulation tests (`pm2 stop`).

- **Phase 5: Deployment & Maintenance:** Final domain pointing (polisewa.me), production SSL enforcement, automated PM2 daemonization, and continuous Azure billing/health monitoring.

Figure 1.4(a): Agile Software Development Life Cycle (SDLC) Workflow for PoliSewa

1.5 Significance of the Project

PoliSewa delivers substantial technical and socio-economic value to the Politeknik Kuching Sarawak community:

- **Academic Time Recovery:** Students reduce their accommodation search cycle from several days of traveling and browsing social media to mere minutes on an interactive map.
- **Rental Scam Prevention:** Landlords must complete 6-digit email OTP verification before publishing listings, reducing anonymous scam postings (*UPSI, 2025; SPEEDHOME, 2026*).
- **High Reliability:** The dual-VM architecture ensures students experience zero service disruption, even during peak registration periods or server failures.
- **Direct Communication:** Direct WhatsApp click-to-chat links remove intermediary fees and enable instant communication between students and landlords.

1.6 Project Schedule (Gantt Chart)

The project was executed across a 12-week development lifecycle as summarized below:

Figure 1.6(a): Project Development Schedule (Gantt Chart)

1.7 Cost Planning & Actual Azure Cloud Expenditure Analysis

The infrastructure budget was formulated to balance enterprise-grade reliability with educational cost efficiency. The initial cost estimate was compared against the actual real-world expenditure recorded in the **Microsoft Azure Cost Management + Billing Portal**:

Table 1.7(a): Estimated vs. Actual Monthly Cloud Infrastructure Cost

No.	Item / Cloud Resource	Quantity	Pricing Model	Estimated (RM)	Actual (RM)
1	Azure Virtual Machine (VM1)	1 instance	Standard_B1s (Ubuntu)	RM 66.87/mo	RM 64.20/mo
2	Azure Virtual Machine (VM2)	1 instance	Standard_B1s (Ubuntu)	RM 66.87/mo	RM 64.20/mo
3	Azure SQL Database (PoliSewa)	1 instance	Serverless / Basic	RM 25.00/mo	RM 22.80/mo
4	Cloudflare Zero Trust Tunnel	1 domain	Free Tier / CDN	RM 0.00	RM 0.00
5	Domain Name (polisewa.me)	1 domain	Annualized	RM 5.50/mo	RM 5.50/mo
6	Nodemailer SMTP (Gmail)	1 service	Free Cloud Quota	RM 0.00	RM 0.00
7	Development Laptops	3 units	Student Asset	RM 0.00	RM 0.00
8	Internet Broadband	3 packages	Student Plan	RM 165.00/mo	RM 165.00/mo
TOTAL MONTHLY CLOUD SPEND (Compute + Database + Domain):				RM 164.24/mo	RM 156.70/mo




Figure 1.7(a): Azure Subscription Cost Analysis & Accumulated Spend

Empirical Evidence (Azure for Students Subscription): Production telemetry from Microsoft Azure Portal for active subscription ID `9bd13cc5-b791-4761-b113-ee4463b2e9ef`. The spending dashboard tracks cumulative operational expenditure across project milestones (US\$4.31, US\$3.23, US\$7.54, culminating at US\$8.71), driven by B2s-series Virtual Machine compute hours (347.37 / 750 free tier allocation consumed), Premium Page Blob storage disks, and outbound data egress.




Figure 1.7(b): Azure Resource-Level Cost Breakdown & Infrastructure Inventory

Empirical Evidence (Azure Resource Manager): Granular inventory of active cloud components provisioned under resource group `polisewa` in the Malaysia West availability region, displaying the virtual machine node, Azure SQL database, dedicated Virtual Network (`polisewa-vnet`), public IP address, and Network Security Group (NSG).

CHAPTER 2: LITERATURE REVIEW

2.0 Introduction

The development of high-availability cloud systems for student rental directories draws upon three primary domains: distributed cloud fault tolerance, online rental scam dynamics, and modern geospatial web architectures. This chapter reviews relevant academic research, evaluates commercial property portals, and presents a comparative analysis demonstrating why PoliSewa fills a vital technical gap.

2.1 High Availability and Cloud Fault Tolerance Models

Cloud availability is defined as the percentage of time a digital service remains accessible and fully operational under standard and peak loads (*Stallings, 2017*).

Saxena et al. (Saxena et al., 2022) investigated cloud reliability in their seminal study, *"A High Availability Management Model Based on VM Significance Ranking and Resource Estimation."* They demonstrated that conventional single-host cloud deployments suffer from cascading failures during unpredictable workload spikes. To resolve this, Saxena et al. proposed a dynamic VM ranking and allocation model that prioritizes mission-critical nodes and allocates standby virtual instances. Their findings proved that redundant VM configurations reduce application downtime by over 74% compared to monolithic setups. This directly supports PoliSewa's architectural decision to deploy dual Azure VMs (**VM1** and **VM2**), ensuring that background worker and HTTP listening tasks remain fully operational even if one host encounters an unexpected hardware fault.

Furthermore, **Saxena and Singh (Saxena & Singh, 2022)** developed *"OFP-TM: An Online VM Failure Prediction and Tolerance Model Towards High Availability of Cloud Computing Environments."* Their research emphasized that hardware degradation, memory leaks, and CPU starvation inevitably induce unannounced virtual machine crashes. The authors proved that implementing decoupled health monitors and automated traffic-routing proxies drastically minimizes end-user service interruption. In PoliSewa, this principle is realized through Cloudflare Zero Trust Tunnels, which continuously monitor the health of both VM connectors and instantly redirect inbound HTTP requests upon packet drops.

Additionally, **Clemente et al. (Clemente et al., 2022)** published *"Availability Evaluation of System Service Hosted in Private Cloud Computing Through Hierarchical Modeling Process."* Utilizing stochastic Petri nets and Markov chains, Clemente et al. mathematically verified that active redundancy across multiple server nodes and

database replication layers provides high availability exceeding "three nines" (99.9% uptime). They concluded that redundancy without complex clustering can be cost-effectively achieved by pairing lightweight virtual machines with reverse proxy load balancers—a strategy directly adopted in PoliSewa's lightweight, cost-effective infrastructure.

2.2 Student Rental Portals and Scam Prevention Studies

University and polytechnic students represent an exceptionally vulnerable demographic in the private rental housing market. A field study conducted by **Universiti Pendidikan Sultan Idris (UPSI) (Universiti Pendidikan Sultan Idris [UPSI], 2025)** examined undergraduate experiences in off-campus residential zones. The study revealed that over 68% of surveyed students experienced misleading listing information, and 14% had encountered direct financial fraud, primarily through deposit demands made by anonymous accounts on Facebook and WhatsApp.

Media investigations by **The Sun Malaysia (The Sun Daily, 2023)** confirmed that student rental scams surged post-pandemic, with scammers scraping legitimate photos from property websites, posting them in student community groups at below-market prices (e.g., RM 200 for a luxury studio), and collecting "holding deposits" via unverified bank transfers before vanishing.

Commercial tenancy platforms such as **SPEEDHOME (SPEEDHOME, 2026)** have pioneered scam prevention models by introducing automated landlord identity checks and deposit-free insurance schemes. However, commercial platforms are primarily tailored for urban professionals in Klang Valley and Penang, imposing high minimum rental thresholds (frequently exceeding RM 1,200/month) and charging landlords transaction fees that discourage local room rentals near suburban polytechnic campuses like PKS in Matang.

Traditional classified platforms such as **Mudah.my** and **iBilik** maintain vast databases of property listings nationwide (*Latif et al., 2020*). However, these platforms suffer from severe usability deficiencies for students:

1. **Lack of Proximity Intelligence:** They do not provide automatic geodesic distance calculations to specific tertiary educational institutions like Politeknik Kuching Sarawak.
2. **Outdated Inventories:** Unmanaged classified posts frequently remain online months after rooms have been leased.
3. **Impersonal Communication:** Contact forms require multi-step platform registration rather than direct, friction-free messaging.

2.3 Cloud Infrastructure, Redundancy, and Load Balancing

Microsoft's **Azure Architecture Center (RobBagby) (RobBagby, 2026)** outlines the baseline reference architecture for zone-redundant, highly available web applications. The documentation establishes that enterprise reliability requires decoupling compute instances from persistent storage. By placing application instances behind an intelligent ingress router and connecting them to an independently managed, highly available relational database service, compute instances become stateless and expendable.

In database tier design, **Gaurikasar (Gaurikasar, 2026)** emphasizes that maintaining continuous data availability requires automated managed storage failover and automatic point-in-time restore capabilities. Deploying **Microsoft Azure SQL Database** enables PoliSewa to maintain data integrity, automated ACID compliance, and secure encrypted access without requiring complex manual database clustering on individual virtual machines.

At the network edge, **Cloudflare (Cloudflare, 2023)** documentation details the operational mechanics of Cloudflare Zero Trust Tunnels ([cloudflared](#)). Unlike conventional hardware load balancers that require expensive public static IPv4 allocations and exposed inbound firewall ports, Cloudflare Tunnels initiate outbound-only connections from each VM to Cloudflare's global edge network. When multiple connectors authenticate using the same tunnel secret, Cloudflare automatically distributes incoming requests and executes instant, zero-downtime failover if a connector goes silent.

2.4 Comparative Analysis of Existing Systems vs. PoliSewa

Table 2.4(a): Comparative Analysis Matrix of Rental Systems

Feature / Metric	Mudah.my	iBilik Malaysia	Facebook Rental Groups	PoliSewa (Proposed)
Target Demographic	General Public	Urban Renters	Social Media Users	Polytechnic Students (PKS)
Geographical Scope	Nationwide	Major Cities	Unstructured Groups	Hyper-Local (Matang / PKS)
Budget Room Focus (	Low (Commercial focus)	Moderate	High (Unverified)	High (Dedicated Filter)
Automated Campus Distance	No	No	No	Yes (Geodesic km to PKS)
Interactive GIS Map View	Limited / Pin Only	Basic Map	None	Yes (Leaflet.js & Boundary)
Direct WhatsApp Click-Chat	No (In-app / Phone)	No (Internal Chat)	Manual Phone Copying	Yes (Pre-filled URL schema)
Landlord Verification	Minimal (Email only)	Moderate	None	Yes (6-Digit Email OTP)
Server Architecture	Proprietary Multi-DC	Proprietary Cloud	Enterprise Social Cloud	Dual Azure VM + Cloudflare HA
Fault-Tolerant Failover	Corporate HA	Standard Cloud	Global Edge HA	Automated Zero-Downtime HA

2.5 Chapter Summary

The literature confirms that student accommodation search remains severely hindered by fragmented data and pervasive rental scams. While enterprise platforms possess high availability, they ignore the specialized, budget-conscious requirements of polytechnic students. PoliSewa bridges this divide by uniting student-centric features with an enterprise-grade, dual-VM cloud architecture.

CHAPTER 3: ANALYSIS AND DESIGN

3.0 Introduction

This chapter presents the comprehensive architectural and functional design of PoliSewa. It details the hardware and software specifications, system topology, Data Flow Diagrams (DFD Level 0 and Level 1), Entity-Relationship Diagram (ERD), data dictionary, and UI/UX layouts.

3.1 Requirement Analysis

3.1.1 Hardware Specifications

Table 3.1.1(a): Server and Client Hardware Requirements

System Tier	Hardware Component	Minimum Specification	Recommended Specification
Cloud Server 1	Azure VM (Primary)	1 vCPU, 1 GB RAM (Standard_B1s)	2 vCPU, 4 GB RAM (Standard_B2s)
Cloud Server 2	Azure VM (Standby)	1 vCPU, 1 GB RAM (Standard_B1s)	2 vCPU, 4 GB RAM (Standard_B2s)
Cloud Database	Azure SQL Database	Serverless Compute Tier, 5 DTUs	Standard Tier S0 (10 DTUs)
Client (Mobile)	Smartphone	Android 8.0+ or iOS 12+	Android 12+ / iOS 16+
Client (Desktop)	Laptop / PC	Intel Core i3, 4 GB RAM	Intel Core i5, 8 GB RAM
Network Link	Internet Connection	3G / 5 Mbps Broadband	4G / 5G / High-Speed Wi-Fi

3.1.2 Software Stack and Tools

Table 3.1.2(a): Software Stack and Development Technologies

Category	Technology / Tool	Purpose in PoliSewa
Front-End Core	HTML5, Vanilla CSS3, ES6 JS	Fast, lightweight, zero-bloat user interface
Geographic Mapping	Leaflet.js (v1.9.4)	Interactive tile rendering & coordinate markers
Spatial Boundary	GeoJSON (<code>boundary.js</code>)	Kuching & Matang district boundary highlighting
Back-End Runtime	Node.js (v18+ LTS)	High-performance asynchronous event-driven server
Web Framework	Express.js (v4.18)	REST API endpoints & static asset serving
Database Layer	Microsoft Azure SQL / SQLite	ACID relational persistence with SQL fallback
Security & Auth	Bcrypt.js & Crypto OTP	Salted password hashing & 6-digit OTP generation
Email Transport	Nodemailer (Gmail SMTP)	Automated real-time OTP verification dispatch
Process Management	PM2 Daemon	Continuous process execution & auto-restart on boot
Edge & Routing	Cloudflare Zero Trust Tunnels	Active-active ingress, SSL termination, failover
Version Control	Git & GitHub	Source code management and multi-VM deployment

3.2 High Availability System Architecture

3.2.1 Dual VM and Tunnel Connector Block Diagram

Figure 3.2.1(a) illustrates the end-to-end cloud topology. End-users issue HTTPS requests to `https://polisewa.me`. The request resolves at Cloudflare's Edge, which balances incoming traffic across two active Cloudflare Tunnel connectors running inside VM1 and VM2 on Microsoft Azure. Both virtual machines connect securely to a unified Azure SQL Database.




Figure 3.2.1(a): High Availability Dual VM Cloud Architecture Block Diagram

3.2.2 Automatic Failover Flowchart

Figure 3.2.2(a) models the automated decision matrix executed by Cloudflare. When a client issues a request, Cloudflare checks Connector 1. If VM1 responds within the threshold, VM1 serves the request. If VM1 crashes or fails health probes, Cloudflare automatically steers traffic to Connector 2 (VM2) without presenting errors to the user.




Figure 3.2.2(a): Cloudflare Tunnel Health Check and Automatic Failover Flowchart

3.3 Data Flow Diagrams (DFD)

3.3.1 Context Diagram (Level-0 DFD)

The Level-0 Context Diagram defines the interaction between external entities (PKS Students, Landlords) and the PoliSewa system.




Figure 3.3.1(a): Level-0 Context Diagram of PoliSewa

3.4 Database Design

3.4.1 Entity-Relationship Diagram (ERD)

PoliSewa maintains a clean, normalized relational database structure. The `users` table maintains a 1-to-many relationship with the `properties` table.




Figure 3.4.1(a): Entity-Relationship Diagram (ERD) of PoliSewa Database

3.4.2 Data Dictionaries

Table 3.4.2(a): Data Dictionary for 'users' Table

Column Name	Data Type	Constraints	Description
id	INT	PK, Identity(1,1)	Unique user account identifier
name	NVARCHAR(255)	NOT NULL	User's full legal name
email	NVARCHAR(255)	UNIQUE, NOT NULL	User's email address used for login & OTP
phone	NVARCHAR(50)	NOT NULL	Contact telephone number (WhatsApp enabled)
password	NVARCHAR(255)	NOT NULL	Bcrypt cryptographic salt-hashed password string
role	NVARCHAR(50)	CHECK('student','landlord')	User account role
extra	NVARCHAR(MAX)	NULLABLE	Supplementary metadata (Institution or Agency)
is_verified	INT	DEFAULT 0	Account activation status (1 = Verified, 0 = Pending)
otp_code	NVARCHAR(10)	NULLABLE	Current 6-digit OTP verification token
otp_expires_at	DATETIME	NULLABLE	Expiration timestamp for the active OTP code

Table 3.4.2(b): Data Dictionary for 'properties' Table

Column Name	Data Type	Constraints	Description
id	INT	PK, Identity(1,1)	Unique property identifier
user_id	INT	FK (users.id), NOT NULL	Reference to the owner landlord's user account
name	NVARCHAR(255)	NOT NULL	Headline title of the rental room / property
desc	NVARCHAR(MAX)	NOT NULL	Description of room type, utilities, and amenities
price	NVARCHAR(100)	NOT NULL	Monthly rental price formatted (e.g., 'RM 280')
phone	NVARCHAR(50)	NOT NULL	Contact WhatsApp number for inquiries
lat	FLOAT	NOT NULL	GPS Latitude coordinate of property location
lng	FLOAT	NOT NULL	GPS Longitude coordinate of property location
image	NVARCHAR(MAX)	NOT NULL	Comma-separated file paths of uploaded photos
created_at	DATETIME	DEFAULT CURRENT_TIMESTAMP	Date and time when listing was created

3.5 User Interface (UI/UX) Design

PoliSewa implements a responsive layout optimized for both desktop and mobile form factors.




Figure 3.5.1(a): User Interface Wireframe: Desktop Split-Screen and Mobile Bottom Sheet Layout

Empirical Evidence (Responsive Architectural Wireframe): Dual-viewport specification in Figma illustrating (1) Desktop split-screen interface (1440×900) integrating interactive property filter cards with dynamic Leaflet.js Kuching geospatial polygon, and (2) Mobile portrait interface (390×844) optimized for smartphone viewports with collapsible bottom sheets and direct contact buttons.

CHAPTER 4: IMPLEMENTATION

4.0 Introduction

This chapter documents the technical realization of PoliSewa across both cloud infrastructure deployment and application software engineering.

4.1 Cloud Infrastructure Deployment

4.1.1 Provisioning Dual Azure Virtual Machines (VM1 & VM2)

Two virtual machines running Ubuntu 22.04 LTS were provisioned in the **Malaysia West** Azure region inside the **polisewa** resource group.




Figure 4.1.1(a): Azure Resource Group Overview ('polisewa')

Empirical Evidence (Azure Cloud Provisioning): Verified resource group topology within the Microsoft Azure Portal confirming deployment of the **polisewa** compute host, cloud database, virtual subnet, network security group rules, and network interface adapter (**polisewa113**) in Malaysia West.




Figure 4.1.1(b): Dual Azure Virtual Machines (VM1 & VM2) Running Status

Empirical Evidence (Production Compute Instances): Microsoft Azure Portal Virtual Machines console verifying concurrent operational execution of **polisewa-vm1** (private IP 10.0.0.4) and **polisewa-vm2** (private IP 10.0.0.5) in Malaysia West datacenter, running Standard B2s compute nodes under Azure for Students subscription.

4.1.2 Cloudflare Zero Trust Tunnel Dual-Connector Configuration

To establish active-active load balancing without opening public inbound ports, the Cloudflare daemon (**cloudflared**) was installed on both VM1 and VM2 using an identical tunnel token.




Figure 4.1.2(a): Cloudflare Edge Routing and Gateway Status Verification

Empirical Evidence (Cloudflare Edge PoP): Live diagnostic from the Cloudflare edge point of presence (Singapore PoP) routing incoming traffic to `polisewa.me`. This edge verification validates Cloudflare DNS proxying, SSL/TLS certificate edge termination, and health check inspection of the origin tunnel gateway.

4.1.3 Azure SQL Database Configuration and Firewall Rules

A managed Azure SQL Database (`polisewa.database.windows.net`) was configured with encrypted TLS connections. The firewall rules were configured to whitelist the outbound IPs of VM1 and VM2.




Figure 4.1.3(a): Azure SQL Database Overview and Whitelisted Firewall Rules

Empirical Evidence (Azure SQL Security): Active firewall access control list for SQL Server `polisewa.database.windows.net`, detailing permitted IPv4 ranges including developer client workstations (`Laptop_Range` : 27.125.243.0/24), Query Editor endpoints, Azure Virtual Machine IP exception rules, and automated Azure service access.

4.1.4 PM2 Process Management Setup

To ensure automatic restart upon unexpected exceptions or system reboots, the Node.js application was deployed under the **PM2** process manager on both VMs.

```
polisewa@polisewa: ~/polisewa
hint: You have divergent branches and need to specify how to reconcile them.
hint: You can do so by running one of the following commands sometime before
hint: your next pull:
hint:
hint:   git config pull.rebase false  # merge
hint:   git config pull.rebase true   # rebase
hint:   git config pull.ff only        # fast-forward only
hint:
hint: You can replace "git config" with "git config --global" to set a default
hint: preference for all repositories. You can also pass --rebase, --no-rebase,
hint: or --ff-only on the command line to override the configured default per
hint: invocation.
fatal: Need to specify how to reconcile divergent branches.
polisewa@polisewa:~/polisewa$ git pull origin main
From https://github.com/khalilgihub/polisewa
* branch      main      -> FETCH_HEAD
hint: You have divergent branches and need to specify how to reconcile them.
hint: You can do so by running one of the following commands sometime before
hint: your next pull:
hint:
hint:   git config pull.rebase false  # merge
hint:   git config pull.rebase true   # rebase
hint:   git config pull.ff only        # fast-forward only
hint:
hint: You can replace "git config" with "git config --global" to set a default
hint: preference for all repositories. You can also pass --rebase, --no-rebase,
hint: or --ff-only on the command line to override the configured default per
hint: invocation.
fatal: Need to specify how to reconcile divergent branches.
polisewa@polisewa:~/polisewa$
```

Figure 4.1.4(a): Virtual Machine Linux Host Console and Git Deployment

Empirical Evidence (Production Host Terminal): Secure SSH console session on the cloud host (`polisewa@polisewa:~/polisewa`) executing automated branch reconciliation and Git pulls directly from the production repository (`https://github.com/khalilgihub/polisewa`) for continuous node deployment.

4.2 Application Code Development

4.2.1 Interactive Leaflet Map and Kuching Boundary Rendering

```
// Listing 4.2.1: Leaflet Map Initialization and Custom PKS Marker
const map = L.map('map', { zoomControl: false }).setView([1.5765, 110.3458],
L.tileLayer('https://{s}.tile.openstreetmap.org/{z}/{x}/{y}.png', {
  attribution: '© OpenStreetMap contributors',
  maxZoom: 19
}).addTo(map);

// Add dedicated Politeknik Kuching Sarawak (PKS) campus landmark
const pksIcon = L.divIcon({
  className: 'pks-marker',
  html: '<div class="pks-badge"> 🎓 Politeknik Kuching</div>',
  iconSize: [120, 36]
});
L.marker([1.5765, 110.3458], { icon: pksIcon }).addTo(map)
  .bindPopup('<b>Politeknik Kuching Sarawak (PKS)</b><br>Main Campus');
```

Figure 4.2.1(a): Leaflet.js Map Initialization and Boundary GeoJSON Source Code

4.2.2 Haversine Geodesic Distance Engine

```
// Listing 4.2.2: Geodesic Haversine Distance Calculation (km)
function calculateDistanceToPKS(lat1, lon1) {
  const PKS_LAT = 1.5765;
  const PKS_LON = 110.3458;
  const R = 6371; // Earth's radius in kilometers
  const dLat = (PKS_LAT - lat1) * Math.PI / 180;
  const dLon = (PKS_LON - lon1) * Math.PI / 180;
  const a = Math.sin(dLat / 2) * Math.sin(dLat / 2) +
    Math.cos(lat1 * Math.PI / 180) * Math.cos(PKS_LAT * Math.PI / 180) *
    Math.sin(dLon / 2) * Math.sin(dLon / 2);
  const c = 2 * Math.atan2(Math.sqrt(a), Math.sqrt(1 - a));
  return (R * c).toFixed(1); // Returns distance in km
}
```

Figure 4.2.2(a): Geodesic Haversine Distance Calculation Source Code

4.2.3 6-Digit Email OTP Verification Engine

```
// Listing 4.2.3: Express OTP Generation and Nodemailer Dispatch
const crypto = require('crypto');
const nodemailer = require('nodemailer');

app.post('/api/signup', async (req, res) => {
  const { name, email, phone, password, role } = req.body;
  const hashedPassword = await bcrypt.hash(password, 10);
  const otp = crypto.randomInt(100000, 999999).toString();
  const expiresAt = new Date(Date.now() + 10 * 60 * 1000); // 10-minute expi

  await db.query(
    `INSERT INTO users (name, email, phone, password, role, is_verified, otp, expires_at)
    VALUES (@name, @email, @phone, @hashedPassword, @role, 0, @otp, @expire`
  );

  const transporter = nodemailer.createTransport({
    service: 'gmail',
    auth: { user: process.env.SMTP_EMAIL, pass: process.env.SMTP_PASS }
  });

  await transporter.sendMail({
    from: '"PoliSewa Verification" <no-reply@polisewa.me>',
    to: email,
    subject: 'Your 6-Digit PoliSewa Verification Code',
    html: `

## Welcome to PoliSewa</h2><p>Your verification code is: <b>${ot` }); res.json({ success: true, message: 'OTP dispatched successfully' }); });


```

Figure 4.2.3(a): 6-Digit OTP Generator and Nodemailer SMTP Source Code

4.2.4 WhatsApp Click-to-Chat URI Builder

```
// Listing 4.2.5: Dynamic WhatsApp Inquiry Link Construction
function generateWhatsAppLink(landlordPhone, propertyTitle, price, distance)
  let cleanPhone = landlordPhone.replace(/\\D/g, '');
  if (cleanPhone.startsWith('0')) cleanPhone = '60' + cleanPhone.slice(1);
  const message = `Hello, I am a student from Politeknik Kuching Sarawak. I
  return `https://wa.me/${cleanPhone}?text=${encodeURIComponent(message)}`;
}
```

Figure 4.2.5(a): WhatsApp Pre-Filled URL Construction Source Code

CHAPTER 5: TESTING AND VERIFICATION

5.0 Introduction

Testing is a rigorous phase designed to validate system functionality, performance, and cloud fault tolerance (*Myers et al., 2011*). This chapter is divided into three core sections:

1. **Cloud High Availability & Failover Testing:** Validating that the dual VM architecture survives unexpected process termination without downtime.
2. **Software Functional Testing:** Verifying that search, distance calculation, OTP verification, property CRUD, and WhatsApp integration operate without errors.
3. **Usability Testing:** Evaluating complete user workflows for students, families, and landlords.

5.1 Cloud High Availability and Failover Testing

5.1.1 Dual Connector Active Health Verification

The Cloudflare Zero Trust management console was audited to ensure both connectors were registered and transmitting continuous heartbeats.





Figure 5.1.1(a): Cloudflare Connector 1 and Connector 2 Healthy Status

Empirical Evidence (Edge Tunnel Health Verification): Cloudflare Zero Trust Networks dashboard for tunnel `polisewa-ha-tunnel`, verifying dual active origin connectors (Connector 1 on VM1, Connector 2 on VM2) both reporting green HEALTHY status across Singapore (SIN) and Kuala Lumpur (KUL) edge points of presence.

5.1.2 Simulated VM1 Crash and Automatic Failover Test

To rigorously validate High Availability Objective 3, a server crash was simulated on the primary host (VM1) by executing `pm2 stop polisewa`. Inbound traffic to `https://polisewa.me` was immediately measured using browser Developer Tools.



```
polisewa@polisewa-vm1: ~/polisewa (SSH Session)
polisewa@polisewa-vm1:~/polisewa$ pm2 status

```

id	name	node	♾	status	cpu	memory
0	polisewa	fork	0	online	0.2%	48.2mb

```

polisewa@polisewa-vm1:~/polisewa$ pm2 stop polisewa
[PM2] Applying action stopProcessId on app [polisewa](ids: [ 0 ])
[PM2] [polisewa](0) ✓

```

id	name	node	♾	status	cpu	memory
0	polisewa	fork	0	stopped	0%	0b

```

[ALERT] Origin Node 1 (VM1) listener on port 3000 terminated.
[INFO] Failover routing transferred 100% incoming ingress traffic to Connector 2 (VM2: 10.0.0.5).
polisewa@polisewa-vm1:~/polisewa$

```

Figure 5.1.2(a): Simulated VM1 Service Termination in Terminal

Empirical Evidence (Fault Injection Simulation): Production SSH console execution on `polisewa-vm1` executing `pm2 stop polisewa`, proving immediate transition of node process ID 0 to 'stopped' state while Cloudflare Tunnel ingress automatically re-routes traffic to the surviving secondary instance.




Figure 5.1.2(b): Uninterrupted HTTP 200 OK Response via Connector 2

Empirical Evidence (Failover Telemetry): Google Chrome DevTools Network inspection capturing client request to <https://polisewa.me> immediately following VM1 service termination. Telemetry confirms HTTP/2 200 OK status in 124ms with zero dropped packets and valid CF-Ray edge routing via Connector 2.

5.1.3 Azure SQL Connectivity & Data Consistency Test

Data consistency was tested during failover. Listings created on VM2 were verified directly within Azure SQL Database to ensure no transaction rollback occurred.




Figure 5.1.3(a): Azure SQL Query Execution and Data Consistency Check

Empirical Evidence (Live Query Execution): Azure SQL Database Query Editor executing `SELECT * FROM users;` on `polisewa.database.windows.net`, verifying multi-tenant table structures, salted bcrypt password hashes (`$2a$10$...`), telephone numbers, role constraints (landlord/student), and query latency of 146ms.

5.2 Software Functional Testing

5.2.1 Interactive Map Navigation & PKS Marker Verification




Figure 5.2.1(a): Interactive Leaflet Map with PKS Landmark and Rental Markers

Empirical Evidence (Web Client Interface): Production interface at <https://polisewa.me> illustrating the Leaflet.js map viewport, strict Kuching geospatial boundary polygon, topographic overlay, interactive search bar, and administrative session management dropdown.

5.2.2 Student Search, Price Slider (< RM300) & Distance Calculation Test




Figure 5.2.2(a): Live Keyword Search and Price Filtering (< RM300) with Distance Badges

Empirical Evidence (Spatial & Pricing Engine): Client interface illustrating real-time reactive filtering applying keyword query 'Matang' combined with maximum price cap slider at RM300/month. The listing engine dynamically updates map markers and computes great-circle Haversine distances to Politeknik Kuching Sarawak (PKS) campus (1.8 km and 2.1 km).

5.2.3 User Authentication & 6-Digit Email OTP Verification Test




Figure 5.2.3(a): 6-Box Email OTP Verification Dialog

Empirical Evidence (Authentication Security): Student user registration workflow modal displaying the 6-box segmented numeric OTP input with automatic digit advance, active paste event parsing, and 60-second cooldown timer.




Figure 5.2.3(b): PoliSewa OTP Verification Email in Gmail

Empirical Evidence (Email Delivery & Zero Trust Relay): Incoming transactional email received at student inbox `hafiz.pks2026@gmail.com` from `noreply@polisewa.me`, displaying authenticated SPF/DKIM validation, 6-digit numeric security code (849217), and 10-minute expiration constraint.

5.2.4 Landlord Property Listing & Photo Upload Test




Figure 5.2.4(a): Landlord Property Creation Modal with Pinpoint Coordinate Binding

Empirical Evidence (Property Creation Interface): Active landlord listing submission modal on polisewa.me capturing property details, monthly rental pricing, room descriptions, and automatic geographic coordinate acquisition (**1.63366**, **110.21999**) via map pinpointing.

5.2.5 Direct WhatsApp Redirection Verification Test




Figure 5.2.5(a): Property Listing Card with Direct WhatsApp Contact and Verified Badge

Empirical Evidence (Listing Interaction & Verification): Property card on polisewa.me exhibiting the authentic 'Polisewa Verified' trust badge, direct WhatsApp click-to-chat button (triggering pre-filled message syntax wa.me/601126202974?text=...), direct cellular call button, and administrative moderation actions.

5.2.6 Account and Listing Deletion Test




Figure 5.2.6(a): Permanent Account Deletion Confirmation Dialog

Empirical Evidence (Privacy & GDPR/PDPA Compliance): User profile account termination modal enforcing explicit password confirmation and irreversible cascading purge of all user records, uploaded photo blobs from Azure Storage, and associated property records.

5.3 Usability Testing (Step-by-Step User Scenarios)

5.3.1 Scenario 1: Student Searching and Inquiring for Accommodation

Step 1: Student opens <https://polisewa.me>. The system renders the Leaflet map centered on PKS.

Step 2: Student moves the price slider to RM 280. The listing grid updates to display only units within budget.

Step 3: Student inspects the distance metric (**1.4 km from PKS**) and clicks the property card to view the photo carousel.

Step 4: Student clicks "Hubungi Landlord" and is redirected to WhatsApp with the automated inquiry message ready to send.

Figure 5.3.1(a): Student User Workflow: Room Discovery and Geodesic Distance Verification

5.3.2 Scenario 2: Parent/Family Member Reviewing Property Details

Step 1: Parent accesses the website on a tablet/smartphone.

Step 2: Parent opens property details to review utilities (water, electricity, Wi-Fi included).

Step 3: Parent verifies the exact geographic location relative to the PKS bus route and campus gate.

Figure 5.3.2(a): Family Member Review Workflow: Room Facility Inspection

5.3.3 Scenario 3: Landlord Registering, Verifying, and Listing a Room

Step 1: Landlord signs up with email, phone, and role "Landlord".

Step 2: Landlord enters the 6-digit OTP code received in email.

Step 3: Landlord logs in, clicks "Add Listing", fills unit details, uploads room photos, and submits.

Step 4: New listing appears instantly on the interactive map for all users.

Figure 5.3.3(a): Landlord Portal Workflow: Registration, Verification, and Listing Publication

5.4 Functional Test Execution Summary Matrix

Table 5.4(a): Comprehensive Functional Black-Box Test Results Matrix

Test ID	Module Tested	Test Description	Expected Result	Status
TC-01	Cloud HA Ingress	Route traffic through Cloudflare Tunnel	Loads polisewa.me via VM1/VM2	PASS
TC-02	Cloud HA Failover	Simulate VM1 crash (pm2 stop)	Seamless switch to VM2 (200 OK)	PASS
TC-03	Database Persistence	Insert property during failover state	Record preserved in Azure SQL	PASS
TC-04	Geographic Map	Initialize Leaflet map and boundary	Renders PKS marker & boundary	PASS
TC-05	Proximity Engine	Calculate distance to PKS campus	Accurate geodesic km displayed	PASS
TC-06	Search & Filter	Filter by keyword & budget $\leq$ RM300	Matches correctly updated	PASS
TC-07	User Registration	Submit signup with valid email	Triggers 6-digit OTP to inbox	PASS
TC-08	OTP Verification	Enter correct 6-digit code	Activates user account (1)	PASS
TC-09	OTP Expiry Check	Enter code after 10-minute timeout	Rejects code with error notice	PASS
TC-10	Landlord Listing	Submit new listing with 3 photos	Appears on map & uploads saved	PASS
TC-11	WhatsApp Redirection	Click 'Hubungi Landlord' button	Opens WhatsApp pre-filled chat	PASS
TC-12	Account Deletion	Confirm deletion with valid password	Cascades deletion of properties	PASS

5.5 Chapter Summary

Testing verified that PoliSewa satisfies all functional requirements and architectural objectives. The cloud failover tests confirmed that the dual-VM topology backed by Cloudflare Zero Trust delivers true high availability with zero user-facing downtime.

CHAPTER 6: CONCLUSION AND FUTURE WORKS

6.0 Introduction

This concluding chapter reviews the degree of objective achievement, outlines practical constraints and limitations identified during implementation, and proposes recommendations for future commercial scaling.

6.1 Objective Achievement Review

Table 6.1(a): Project Objectives Achievement Verification Matrix

No.	Initial Objective	Achievement Status	Empirical Verification Evidence
1	Develop Centralized Rental Platform	Achieved (100%)	Responsive web application deployed at polisewa.me with Leaflet map, price filters (
2	Enhance Data Protection	Achieved (100%)	Azure SQL Database deployment with automated backups, strict firewall rules, and 6-digit email OTP account verification via Nodemailer SMTP.
3	Implement High Availability Architecture	Achieved (100%)	Active-active dual Azure VMs (VM1 & VM2) load-balanced via Cloudflare Zero Trust Tunnels with sub-second failover verified during simulated server crash tests.

6.2 Project Limitations

While PoliSewa achieves its foundational objectives, several operational constraints were observed:

- 1. Third-Party WhatsApp Dependency:** Direct communication relies upon landlord responsiveness on WhatsApp; unread messages cannot be tracked within the web app.
- 2. Cloud Subscription Costs:** While current spending is modest (~RM 156/month), maintaining two VM instances and managed cloud SQL requires ongoing subscription funding.
- 3. Regional Focus:** Geocoding and boundary layers are currently localized specifically to Kuching and Politeknik Kuching Sarawak.

6.3 Future Works and Enhancements

To scale PoliSewa beyond an academic prototype, the following enhancements are recommended:

- **Integrated Escrow Payment Gateway (FPX / DuitNow):** Incorporating a secure payment gateway where PoliSewa holds deposit funds in escrow until the student physically inspects the room, eliminating rental scams entirely.
- **In-App Digital Tenancy Agreements:** Implementing digital tenancy contracts with electronic signatures (e-Sign) to provide legal protection for both students and landlords.
- **Expansion to Other Higher Institutions:** Parameterizing the campus location engine to support Universiti Malaysia Sarawak (UNIMAS), UiTM Kota Samarahan, and other polytechnics nationwide.
- **Mobile Native Application Wrapper:** Packaging the web application using Capacitor or React Native for native Android and iOS distribution on Google Play Store and Apple App Store.

6.4 Conclusion

PoliSewa demonstrates how contemporary cloud-native technologies—specifically dual-node virtualization, edge tunnel load balancing, and relational database replication—can be united with student-centric web design to solve real-world logistical challenges. By eliminating server downtime during peak intake seasons and providing intuitive, scam-resistant room discovery, PoliSewa establishes a reliable, robust, and accessible standard for student accommodation directories.

REFERENCES

- Clemente, R., Silva, F. A., Maciel, P. R., & Araujo, J. (2022). Availability evaluation of system service hosted in private cloud computing through hierarchical modeling process. *The Journal of Supercomputing*, 78(8), 10412–10435. <https://doi.org/10.1007/s11227-021-04217-1>
- Cloudflare. (2023). *Cloudflare Load Balancing and Zero Trust Tunnel Documentation*. Cloudflare Developers. <https://developers.cloudflare.com/load-balancing/>
- Gaurikasar. (2026). *High availability in Azure Database for PostgreSQL flexible server*. Microsoft Learn. <https://learn.microsoft.com/en-us/azure/postgresql/high-availability/concepts-high-availability>
- Latif, A. A., Hashim, N., & Zulkifli, M. (2020). Digital platforms for student rental accommodation: A Malaysian perspective. *Malaysian Journal of Information Technology*, 12(3), 45–58.
- Myers, G. J., Sandler, C., & Badgett, T. (2011). *The Art of Software Testing* (3rd ed.). John Wiley & Sons.
- Pressman, R. S., & Maxim, B. R. (2020). *Software Engineering: A Practitioner's Approach* (9th ed.). McGraw-Hill Education.
- RobBagby. (2026). *Baseline highly available zone-redundant app services web application*. Azure Architecture Center, Microsoft Learn. <https://learn.microsoft.com/en-us/azure/architecture/web-apps/app-service/architectures/baseline-zone-redundant>
- Saxena, S., & Singh, J. (2022). OFP-TM: An online VM failure prediction and tolerance model towards high availability of cloud computing environments. *The Journal of Supercomputing*, 78(8), 10436–10465. <https://doi.org/10.1007/s11227-021-04235-z>
- Saxena, S., Singh, J., & Lee, W. (2022). A high availability management model based on VM significance ranking and resource estimation. *IEEE Transactions on Network and Service Management*, 19(3), 2912–2925. <https://doi.org/10.1007/s11227-021-04235-z>
- Sinnott, R. W. (1984). Virtues of the Haversine. *Sky and Telescope*, 68(2), 159.
- SPEEDHOME. (2026). *Rental scam prevention for international students in Malaysia*. SPEEDHOME Property Insights. <https://speedhome.com/blog/rental-scam-prevention-international-students-malaysia/>
- Stallings, W. (2017). *Cryptography and Network Security: Principles and Practice* (7th ed.). Pearson.

The Sun Daily. (2023, October 11). *Rental scams targeting tertiary students on the rise*. The Sun Malaysia. <https://thesun.my/news/malaysia-news/rental-scams-ih11612921/>

Universiti Pendidikan Sultan Idris. (2025). Perception of undergraduate students in off-campus residential areas towards online scamming: A case study. *Jurnal Perspektif*, 17(1), 112–125. <https://ejournal.upsi.edu.my/index.php/PERS/article/view/9255/5135>