

[[airport-migrations]] # Workstation Configuration Steps

## Pre-Domain Joining Setup

### 1. Configure Network Settings:

- **Note:** Ensure you have the correct IP configurations provided by your IT administrator before proceeding.
- Navigate to **Network & Internet settings**.
- Go to **Properties** for your network connection.
- Select **Internet Protocol Version 4 (TCP/IPv4)**.
- Click on **Properties** and manually configure the following:
  - **IP Address**
  - **Subnet Mask**
  - **Default Gateway:** After entering the default gateway, click on **Advanced**.
  - **DNS Settings:** Add the four IP addresses for DNS.
- **Warning:** Incorrect IP configuration can cause network connectivity issues. Double-check all entries before proceeding.

## Joining the Domain

### 1. Join the Workstation to the Domain:

- **Domain Name:** apcflex.aero.
- After joining the domain, the device will automatically restart.
- **Important:** Make sure you have your domain user credentials ready for the next login.
- Log in using your domain user credentials.
- **Note:** If the domain join fails, ensure that the network settings are correct and that the workstation has network access to the domain controller.

## Post-Domain Joining Setup

### 1. Enable Windows Features:

- Navigate to **Apps & features**.
- Click on **Turn Windows features on or off**.
- Look for **MSMQ Server** and check all the options under it.
- Apply changes and restart the workstation if prompted.
- **Warning:** Missing features can cause certain applications to fail. Ensure that all required features are enabled.

## Copying Files from Another Workstation

### 1. Copy Necessary Files:

- **Important:** Ensure that the files being copied are up to date and relevant to the new workstation's role.

- Copy the **Camille** folder to the **C:** drive.
- Copy any necessary **menus** and **airline apps** from the other workstation to the appropriate locations on the new workstation.
- **Note:** Verify that all copied applications are functioning correctly after the transfer.

## Configuring Certificates

### 1. Import ZScaler Certificate:

- Open **Run** (Win + R), type **mmc**, and press Enter to open the Microsoft Management Console.
- In the console, go to **File > Add/Remove Snap-in**.
- Select **Certificates** and choose **Computer account**, then click **Next** and **Finish**.
- In the left pane, expand **Certificates > Trusted Root Certification Authorities**.
- Right-click on **Trusted Root Certification Authorities** and select **All Tasks > Import**.
- Click **Next**, browse to **C:\Camille\** and select **ZScaler.crt**.
- Complete the import by clicking **Next > Finish**.
- **Warning:** An incorrect certificate installation can result in security warnings or connectivity issues. Ensure you select the correct certificate file.

## Proxy Configuration

### 1. Configure Proxy Settings:

- Go to **Settings > Network & Internet > Proxy**.
- Under **Manual proxy setup**, add the following address: **185.46.212.90**.
- **Note:** Ensure that the proxy address is correct and authorized by your network administrator.
- Open the **Camille** folder and open the **newtextdoc.txt**.
- Copy the second line from **newtextdoc.txt** and paste it into Microsoft Edge's address bar.

### 2. Run Locator:

- Navigate to the **Camille** folder and run the **Locator** file.
- Go to the **ajflck** folder within the **Camille** folder.
- Copy the **nodename.lck** file to the **Camille** folder.
- Update the **ring** and then open the Command Prompt.
- Navigate to the **Camille** folder and run the **.lck** file.
- **Warning:** Each workstation has a unique ring number. Ensure the correct ring number is used to avoid configuration errors.

## Final Configuration Steps

### 1. Install APC Prerequisites:

- In the **Camille** folder, click on **APC\_Perequasete** and follow the prompts until the installation is complete.
- Restart the computer when prompted.
- **Note:** If the installation fails, check that all previous steps have been completed correctly.

### 2. Create Necessary Folders:

- Navigate to **C:\SITA**.
- Create a new folder named **Cash** under **C:\SITA\temp**.
- Create another folder named **LCKFile** under **C:\SITA**.
- **Note:** Ensure that folder names are spelled correctly to avoid file path errors later on.

### 3. Run Services and Installations:

- In the **Camille** folder, go to **flexadapterservice** and run the **SITAFlexAdapterService** file.
- Run **APC\_CUTE.msi** from the **Camille** folder.
- Run **PROD-edgeConfig.reg** to apply the necessary registry settings.
- **Warning:** Always back up the registry before making changes. Incorrect registry settings can cause system instability.

### 4. Configure LCK Utility:

- The **LCK Utility Tool GUI** will open.
- Run **LCKUtilityTools.exe**.
- In the LCK Utility Tool, select the **nodename.lck** file you copied earlier.
- Set the **LCK Storage Path** to **C:\SITA\LCKFile** and click **Update**.
- Restart the computer.
- **Note:** Double-check the storage path to ensure that all files are correctly saved and accessible.