Product Development Specification

William Harrington, Jake Heath, Saroj Bardewa,
Shan Quinney, Michael Mathis

ECE411

October 22, 2015

Customer requirements

The Portland State Aerospace Society (PSAS) needs a device that can be used for command, control, communications between a **CubeSat** and a **ground station**. A **CubeSat** is a miniature satellite that can be used for scientific research in space. It has a volume of one liter (10cm cube), and has a mass of no more than 1.33kg. A **ground station** is a radio station located on earth that is designed for communication with spacecraft. Development of such a device is not trivial as it will need to eventually be "space ready" and will require multiple phases of development.

The first phase of development will involve finding and de-risking a microcontroller that is capable of handling command, control, and communications. Therefore, the device at this point will be a communications module "breakout board" that will allow easy access to the features of the microcontroller like UART, I2C, SPI, etc.

Must

- Be able to fit within the CubeSat form factor
  (no bigger than 10cm x 10cm x 10cm)

- Have access to UART

- Have access to I2C

- Have access to SPI

- Have access to GPIO pins

- Be capable of RF communication with another device

Should

- Be able to send/receive commands via RF communication

- Be battery powered

- If battery powered, utilize USB for recharging

May

- Be capable of long distance communication

- Be capable of operation in space *(e.g. really low temperatures)*